CHAPMAN, WOOD and GRISWOLD LTD.

Oct 1/73

09112

DD-20

DRILL HOLE GEOLOGIC LOG

COMPANY: LINDSAY - CD

PROPERTY: QUIET LAKE

LOGGED BY: M.P. PHILL

DATE: OCTOBER 1

PAGE 1 OF 7

HOLE NUMBER: Ddh 1.

C.W.& G. FORM BY S.T. FOR P.H.

ESTIMATES & ASSAYS, ELEMENTS or MINERALS: Cu. | Ni

Depth mark	Estimates/Assays (Cu, Ni)	Bottom of interval described	Recovery %	Foliation angle	Other
70		6,0	7,10	75	D ½
75		7,0	19.0	75	A
80	01 / .03	8,0	10,0	75	A
85		9,0	8,5	75	A

Structure and/or alteration column depths: 53.0, 67.8, 68.8, 95.0

Structure notes:

LAM - CONTORTED WEAKLY

67.8 - 68.8 - SPOTTED QITE

RARE CALQITE TO ½"

Host rock / comments:

53 - 57.5 - LIGHT COLOR CAL QITE > BLACK SHALE

57.5 - 60.0 ; BLACK SHALE > CAL QITE

INTERLAMINATED ALT BLACK SHALE + LIGHT GREY CAL QITE

PY - ¼ - ½% ALONG BEDDING - COBS ; MINOR LI + CB NARROW FRACTURES

67.8 - 68.8 - QITE NCB. PY 10-15%

DARK - OCC BI ALONG BEDDING - PY TO 10% IN PLACES

SHALE = ARGILLITE

PY < PR = EYES + ROLLS IN LAM - INC FRC = 5-10%

PR MAINLY LENSES ± 3-5%

80.5 - 89.5 - LIGHT GREY INTERLAM. - MORE SILICIOUS - NON CAL UF...

QITE - BLACK AGILLITE PARTING

87 - 6.3' QZ VEIN CNTN FRAG OF ARG

PR - 2-4%

89 - SX INCREASE 7-10%

89.5 - 100 - DARK INTERLAM

CHAPMAN, WOOD AND GRISWOLD LTD.

DRILL HOLE GEOLOGIC LOG

DD-20

HOLE NUMBER: Ddh 1

COMPANY: ____ PROPERTY: ____ LOGGED BY: ____ DATE: ____

PAGE 2 OF ____

C.W.&G. FORM BY S.T. FOR PH

DIP ____ AZIM ____

TYPE OF HOLE: DDH ☐ RDH ☐ PDH ☐

Column headings: CORE; STRUCTURE AND/OR ALTERATION; CONTACTS AND PRINCIPAL ZONES (IF ROTARY OR PERCUSSION HOLE) COMMENTS On Coarse, Heavies & Water float; ESTIMATES / ASSAYS ELEMENTS or MINERALS; BOTTOM OF INTERVAL DESCRIBED (7–10); RECOVERY % (11–12); STRUCTURE: FRC. DENSITY PER FT (< 30°, 30°-60°, 60°-90°, INTENSITY) (13–16); FOLIATION (ANGLE, INTENSITY) (17–19); ANGLE FRC TO FOLIATIO (20–21); HOST ROCK: COLOR, TYPE MODIFIER, ACCESSORY MINERALS, % HB, % BI, TEXTURE, GRAIN SIZE, ROCK TYPE (USE 4-LETTER CODE) (22–36); ALTERATION ASSEMBLAGE: QUARTZ QZ, K-SPAR KF, BIOTITE BI, SERICITE MU, CLAYS CY, CHLORITE CL, EPIDOTE EP, CARBONATES CB (MODE OF OCCURRENCE / AMOUNT), OTHER MG (Use 2-letter code at interval re or as he in space; MODE, AMT.), PRINCIPAL FACIES, INTENSITY (37–56); MINERALIZATION: PYRITE, BORNITE, CHALCOPYRITE, MALACHITE, AZURITE, COPPER LIMONITE, MAGNETITE, HEMATITE, % LEACH (MODE, AMT.) (57–78)

Estimate rows in each interval: COARSE (C), HEAVIES (H), WATER FLOAT (W), OTHER REMARKS & COMMENTS; VISUAL

Structure / alteration depths	Bottom of interval	Recovery %	Structure	Foliation angle	Comments	MG (col. 53)
108.3	110	91.3		75	DARK COLOR INTERLAM LENSE 1" FAULTED PR 108.8 - 0.3 FT QZ VEIN	X
112.7, 113.3, 114.3, 115.0	120	91.1	TR GARNETS	75	111-115 - HIGHLY CONTORTED. 112.7 - 113.3 - QZ V. WITH FRC OF INTERLAM 115-120 - DARK - PR = 5-7% 114.3 - 115.0 110.0 - 115.0 LIGHTER COLOR PR = TO 2% MG = L QITE	H
	130	91.6		75	121.0 - 124.5 - IN PARTS HIGHLY CONTORTED PR 5-7%. DARK - CALQITE LAM COMMON	H
	140	91.7		75	DARK - LAM NOT DISTINCT CALQITE IN LENSES - SLUMPING FEATURE PR - PY - 5-7% - GEN WITH BETTER LAM.	H. A
	150	80.0		75	PR - 5-7%	H
	160	9[illegible]		70 / 50	150 2" - GARNET SKARN PR 1-3% AT 152 CONTORTED MG = L-F IN PIECES = [illegible]	F. L

CHAPMAN, WOOD AND GRISWOLD LTD.

DRILL HOLE GEOLOGIC LOG

COMPANY: | PROPERTY: | LOGGED BY: | DATE:

HOLE NUMBER: DD-20 Ddh 1

PAGE 3 OF

C.W. & G. FORM BY S.T. FOR PH

DIP | AZIM. | TYPE OF HOLE: DDH / RDH / PDH

Column headings: STRUCTURE AND/OR ALTERATION | CORE | ESTIMATES ASSAYS ELEMENTS or MINERALS (VISUAL; Coarse, Heavies, Water Float, Other Remarks & Comments) | CONTACTS AND PRINCIPAL ZONES (IF ROTARY OR PERCUSSION HOLE) COMMENTS On Coarse, Heavies & Water float | BOTTOM OF INTERVAL DESCRIBED | RECOVERY % | STRUCTURE: FRC. DENSITY PER FT (< 30°, 30°-60°, 60°-90°, INTENSITY); FOLIATION (ANGLE, INTENSITY); ANGLE FRC TO FOLIATION | HOST ROCK: COLOR, TYPE MODIFIER, ACCESSORY MINERALS, % HB, % BI, TEXTURE, GRAIN SIZE, ROCK TYPE (USE 4-LETTER CODE) | ALTERATION ASSEMBLAGE: QUARTZ QZ, K-SPAR KF, BIOTITE BI, SERICITE MU, CLAYS CY, CHLORITE CL, EPIDOTE EP, CARBONATES CB, OTHER MG (Use 2-letter code at interval or as needed in space), PRINCIPAL FACIES, INTENSITY | MINERALIZATION: PYRITE, BORNITE, CHALCOPYRITE, MALACHITE, AZURITE, COPPER LIMONITE, MAGNETITE, HEMATITE, % LEACH (MODE / AMT.)

Columns 1–78

Bottom of interval described	Recovery %	Foliation angle	Other (MG)	Comments
170	100	25 (70 above)	N / L	160 - START V.FINLY LAM TRW FROM MORE MASSIVE; PY = 1 - 3% NOTE - NO PB or MINOR; FLAT DIPS IN CONTORT RX
180	75	30 (70 above)	N	PY 1-2%
190	76	76	N	PY 1-2%
200	30	76	N	190 TO 194.0 = 3FT REC; 194 TO 200 = 0 =; PY 1-2%
210	85	70	F / L	PY 2-3%
220	61	76		216 - 220 - DIRTY DARK GREEN ALT AEG QITE - MASSIVE WEAKLY LAM; 212.5 - CORE LOSS MAJOR; 210 - 216 - MG L; 216 - 220 MG = M-H - 5% to 3%; PY : PB - 1-3% 5% 1%

-216

336

CHAPMAN, WOOD AND GRISWOLD LTD.

DRILL HOLE GEOLOGIC LOG

DD-20

HOLE NUMBER: Ddh P

COMPANY:

PROPERTY:

LOGGED BY:

DATE:

PAGE 4 OF

C.W. & G. FORM BY B.T. FOR PM

DIP / AZIM. — TYPE OF HOLE: DDH / RDH / PDH

Bottom of interval described	Recovery %	Foliation angle	Other (MC)	Comments
				TALCOSE CL QITE → 221.0 - 229. - STRONGLY TALCOSE ON PARTING - PALE GREEN COLOR; PY<1% ±½ -; 223 - DARK DIRTY GREEN WEAKLY LAMINATED CHLORITIC QUARTZITE; RARE LIGHT GREY CB QITE LAM & BANDS
230	9.14	60	N	PY<1%
240	9.1	60	N	PY<1%; 247 - 250 = 0 REC
250	7.0	70	N	252.0 - 256.5 = 0' REC; PY = N - L TRACE
260	6.0	70	N	260.5 - 263.0 = 0 REC; 266.9 - 268.5 = 0 REC; 250 - INTERLAM. CL QITE - GREY QZ RICH CHLORITE POOR & DIRTY GREEN CL-RICH; FRC - SIDERITE - F-M
270	6.8	70	N	270.0 - 282.0 - 2.0 FT REC.; INTERLAM. DARK CL(H) QITE & LIGHT COLOR NON CAL QITE. - OPEN SIDERITE FRC & CLOSED SIDERITE FILLED FRC - OCC PY. MINOR QZ FILLED
280		60 (70)		

Left margin (structure/alteration column): 247.0, 250.0, 252.0, 256.5, 260.5, 263.0, 266.9, 268.5, 271.0

DD-20

Chapman, Wood & Griswold Ltd.

1 1/4" core

DRILL HOLE GEOLOGIC LOG

COMPANY: | PROPERTY: | LOGGED BY: | DATE: | HOLE NUMBER: DDh 1 | PAGE 5 OF

DIP | AZIM | TYPE OF HOLE: DDH / RDH / PDH

Column groups: CONTACTS AND PRINCIPAL ZONES (IF ROTARY OR PERCUSSION HOLE) COMMENTS | ESTIMATES (ASSAYS, ELEMENTS or MINERALS) On Coarse, Heavies & Water float | BOTTOM OF INTERVAL DESCRIBED | RECOVERY % | STRUCTURE (FRC. DENSITY PER FT: < 30°, 30°-60°, 60°-90°, INTENSITY; FOLIATION: ANGLE, INTENSITY, ANGLE FRC TO FOLIATION) | HOST ROCK (COLOR, TYPE MODIFIER, ACCESSORY MINERALS, % HB, % BI, TEXTURE, GRAIN SIZE, ROCK TYPE – USE 4-LETTER CODE) | ALTERATION ASSEMBLAGE (QUARTZ QZ, K-SPAR KF, BIOTITE BI, SERICITE MU, CLAYS CY, CHLORITE CL, EPIDOTE EP, CARBONATES CB, OTHER; MODE/AMOUNT; PRINCIPAL FACIES, INTENSITY) | MINERALIZATION (PYRITE, BORNITE, CHALCOPYRITE, MALACHITE, AZURITE, COPPER, LIMONITE, MAGNETITE, HEMATITE, % LEACH; MODE/AMT.)

Core depth (structure and/or alteration column)	Bottom of interval described	Notes
281.0, 282.5		282.0 – 293.0 = 1.0 FT REC
	290	
292.5, 293.5, 294.5, 295.5		293.0 – 295.0 = 1.0 FT REC; 295.0 – 299.0 = 1.5 FT REC
298.5	300	
300.0, 304.8, 306.5, 308.0, 309.0		299.0 – 306.0 = 2.2 FT REC; 306.0 – 308.0 = 0.5 FT =; 308.0 – 313.0 = 1.5 FT =
	310	
312.5, 313.0		313.0 – 320.0 = 0.5 FT REC
319.5	320	
324.5, 327.0, 329.5		320.0 – 325.0 = 1.5 FT REC; CNT – UB?? CHANGE 320 – DARK GREEN MASSIVE – ALT INTRUSIVE ? – CB – H – QUARTZ VEINED SERPENTIZED UB – TR PY – MODERATELY SOFT CALCITE VEINED
	330	
330.0, 332.0, 334.0, 336		325.0 – 331.0 = 1.5 =; 331.0 – 336.0 = 3.0 REC
END OF HOLE		

Row labels: COARSE, HEAVIES, WATER FLOAT, OTHER REMARKS & COMMENTS (C, H, W); VISUAL

CHAPMAN, WOOD AND GRISWOLD LTD.

DRILL HOLE GEOLOGIC LOG

COMPANY: PROPERTY: LOGGED BY: DATE:

HOLE NUMBER DD-20

PAGE 1 OF 17

CW & G FORM BY B.T. FOR PH

DIP AZIM

CORE

TYPE OF HOLE: DDH RDH PDH

CONTACTS AND PRINCIPAL ZONES

(IF ROTARY OR PERCUSSION HOLE) COMMENTS On Coarse, Heavies & Water float

ESTIMATES (ASSAYS ELEMENTS or MINERALS)

BOTTOM OF INTERVAL DESCRIBED

STRUCTURE

RECOVERY %

FRC. DENSITY PER FT: < 30° | 30-60° | 60-90°

FOLIATION: INTENSITY | ANGLE | INTENSITY | ANGLE FFC TO FOLIATION

HOST ROCK

COLOR | TYPE MODIFIER | ACCESSORY MINERALS | % HB | % BI | TEXTURE | GRAIN SIZE | ROCK TYPE — USE 4-LETTER CODE

ALTERATION ASSEMBLAGE

QUARTZ QZ | K-SPAR KF | BIOTITE BI | SERICITE MU | CLAYS CY | CHLORITE CL | EPIDOTE EP | CARBONATES CB | OTHER

MODE OF OCCURRENCE | MODE | AMOUNT

Use 2-letter code or as here in space

PRINCIPAL FACIES | INTENSITY

MINERALIZATION

PYRITE | BORNITE | CHALCOPYRITE | MALACHITE | AZURITE | COPPER LIMONITE | MAGNETITE | HEMATITE | % LEACH

MODE | AMT.

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78

STRUCTURE AND/OR ALTERATION

COARSE

HEAVIES

WATER FLOAT

OTHER REMARKS & COMMENTS

VISUAL

S

C

H

W

3.50

3.60

3.70

3.80

3.90

4.00

ST

HE

LI

GO

LI

SP

SU

CHAPMAN, WOOD AND GRISWOLD LTD.

DRILL HOLE GEOLOGIC LOG

DD-20

HOLE NUMBER DDH 7

COMPANY: PROPERTY: LOGGED BY: DATE: PAGE 7 OF 7

DIP AZIM. CORE

TYPE OF HOLE: DDH RDH PDH

STRUCTURE AND/OR ALTERATION

ESTIMATES ASSAYS ELEMENTS or MINERALS

VISUAL

COARSE HEAVIES WATER FLOAT OTHER REMARKS & COMMENTS

CONTACTS AND PRINCIPAL ZONES (IF ROTARY OR PERCUSSION HOLE) COMMENTS On Coarse, Heavies & Water float

BOTTOM OF INTERVAL DESCRIBED

RECOVERY %

STRUCTURE: FRC. DENSITY PER FT (< 30°, 30-60°, 60-90°, INTENSITY); FOLIATION (ANGLE, INTENSITY, ANGLE FRC TO FOLIATION)

HOST ROCK: COLOR, TYPE MODIFIER, ACCESSORY MINERALS, %, %, TEXTURE, GRAIN SIZE, ROCK TYPE (USE 4-LETTER CODE)

ALTERATION ASSEMBLAGE: QUARTZ QZ (MODE OF OCCURRENCE, AMOUNT); K-SPAR KF; BIOTITE BI; SERICITE MU; CLAYS CY; CHLORITE CL; EPIDOTE EP; CARBONATES CB; OTHER (Use 2-letter code at left of interval for ores to be in space); PRINCIPAL FACIES; INTENSITY

MINERALIZATION: PYRITE, BORNITE, CHALCOPYRITE, MALACHITE, AZURITE, COPPER LIMONITE, MAGNETITE, HEMATITE

BOTTOM OF INTERVAL DESCRIBED
4,1,0
4,2,0
4,3,0
4,4,0
4,5,0
4,6,0

SURFACE

OVERBURDEN

MINERALIZED

DIORITE

SYENITE

MINERALIZED

DIORITE

SYENITE

MINERALIZED

DIORITE

SYENITE

MINERALIZED

DIORITE

SYENITE

MINERALIZED

DIORITE

SYENITE

MINERALIZED

DD-20

CHAPMAN, WOOD AND GRISWOLD LTD.

DRILL HOLE GEOLOGIC LOG

COMPANY: PROPERTY: LOGGED BY: DATE: HOLE NUMBER DDH 2 PAGE 1 OF

DIP AZIM TYPE OF HOLE: DDH RDH PDH

Columns: CORE; STRUCTURE AND/OR ALTERATION; ESTIMATES (ASSAYS ELEMENTS or MINERALS); CONTACTS AND PRINCIPAL ZONES (IF ROTARY OR PERCUSSION HOLE) COMMENTS On Coarse, Heavies & Water float; BOTTOM OF INTERVAL DESCRIBED; RECOVERY %; STRUCTURE: FRC. DENSITY PER FT (< 30°, 30°-60°, 60°-90°, INTENSITY), FOLIATION (ANGLE, INTENSITY), ANGLE FRC TO FOLIATION; HOST ROCK: COLOR, TYPE MODIFIER, ACCESSORY MINERALS, % HB, % BI, TEXTURE, GRAIN SIZE, ROCK TYPE USE 4-LETTER CODE; ALTERATION ASSEMBLAGE: QUARTZ QZ, K-SPAR KF, BIOTITE BI, SERICITE MU, CLAYS CY, CHLORITE CL, EPIDOTE EP, CARBONATES CB, OTHER MC (Use 2-letter code at interval or as in space), PRINCIPAL FACIES, INTENSITY; MINERALIZATION: PYRITE, BORNITE, CHALCOPYRITE, MALACHITE, AZURITE, COPPER, LIMONITE, MAGNETITE, HEMATITE, % LEACH (MODE / AMT.)

COARSE / HEAVIES / WATER FLOAT / OTHER REMARKS & COMMENTS — VISUAL

Depth (margin)	Structure notes	Bottom of interval	Recovery %	Foliation angle	Description
54.0		6.0	6.0	60	0 - 54.0 - OVERBURDEN 54.0 - 61.0 = BLACK PHYLLITE-SLATE WITH WEAK-STRONG WHITE STRONGLY CALCAREOUS QUARTZITE LAMINATIONS CALCITE ALSO ON FRC BROWN LIMONITE ON LEACHED FRACTURES PYRITE VEINLET ALONG BEDDING - ½-1% BEDDING @ 60° CONTORTED
61°	60°	7.0	5.0	10-60°; 30° M	61.0 - 76.0 DARK GREEN MASSIVE WEAKLY GNEISSIC - TALC-CHLORITE - HS - CALC PHYLLITE WITH PARTINGS & LAMINATIONS OF WHITE HIGHLY CALC QUARTZITE (2 TO 4 IN "BLOWS") PYRITE ½-1%
76.0	30°?	8.0	1.0		76.0 - 97.0 TALC SCHIST DARK GREEN WHEN FRESH WHITE WEATHERED, WEAK FOLIATION (BEDDING) - BECOMING MASSIVE TOWARDS BOTTOM CONTACT - WEAK QUARTZ LAMINATIONS IN UPPER SECTION, CONTORTED BEDDING TRACES PYRITE; CARBONATE ON FRC
83.0 - 86.0	CORE LOSS	9.0	7.0	60	
97.0		10.0	1.0	60	97.0 - GRADATIONAL 97.0 - 103.5 - BLEACHED ALTERED DARK GREEN MASSIVE ULTRABASIC - SOME FOLIATION IN ROCK

S E M C E P S

DD-20

CHAPMAN WOOD GRISWOLD LTD.

DRILL HOLE GEOLOGIC LOG

COMPANY: PROPERTY: LOGGED BY: DATE: HOLE NUMBER DDH 2 PAGE 2 OF

DIP AZIM. TYPE OF HOLE: DDH RDH PDH

CONTACTS AND PRINCIPAL ZONES (IF ROTARY OR PERCUSSION HOLE) COMMENTS On Coarse, Heavies & Water Float

ESTIMATES (ASSAYS) ELEMENTS or MINERALS

BOTTOM OF INTERVAL DESCRIBED

STRUCTURE: RECOVERY %; FRC. DENSITY PER FT (< 30°, 30°-60°, 60°-90°); INTENSITY; FOLIATION ANGLE; INTENSITY; ANGLE EFC TO FOLIATIO

HOST ROCK: COLOR; TYPE MODIFIER; ACCESSORY MINERALS; % HB; % BI; TEXTURE; GRAIN SIZE; ROCK TYPE (USE 4-LETTER CODE)

ALTERATION ASSEMBLAGE: QUARTZ QZ; K-SPAR KF; BIOTITE BI; SERICITE MU; CLAYS CY; CHLORITE CL; EPIDOTE EP; CARBONATES CB; OTHER MC (Use 2-letter code at left of each mode in space); MODE OF OCCURRENCE; AMOUNT; MODE; AMOUNT; PRINCIPAL FACIES; INTENSITY

MINERALIZATION: PYRITE; BORNITE; CHALCO-PYRITE; MALAC-HITE; AZURITE; COPPER LIMONITE; MAGNE-TITE; HEMATITE; % LEACH; MODE; AMT.

STRUCTURE AND/OR ALTERATION

ESTIMATES (ASSAYS) ELEMENTS or MINERALS: COARSE; HEAVIES; WATER FLOAT; OTHER REMARKS & COMMENTS

103.5 LOST

VISUAL

105.5 - DARK GREEN FINE GRAINED PYROXENE - FELDSPAR INTRUSIVE PERIDOTITE

MODERATE LEACHED OPEN CRACKS & FRACTURES WITH THIN JAROSITE FILM QUARTZ - FELDSPAR FILLED FRACTURES OCCASIONALLY PRESENT TRACES OF PYRITE - CHALCOPYRITE

START AT 119 FT FOLIATION WEAK

110 | 60 | N

119.0 - 3% = PY DISS

VISUAL

120 | 10 | 60 | N

123.0 126.0 - THIN SECTION

125.0

VISUAL

130 | 10 | 60 | N

132.5 132.0 - 150 STRONGLY FRACTURED & PITTED

133 1.5 133.0 FINE GRAINED EDED & INTRUSIVE IN DARK FINE GRAINED MATRIX

VISUAL

135.0 2.0

138.0

139.0 1.0

140.0

140 | N

142.0 2.5

144.5

146.0 1.0

147.0

VISUAL

150 | N

VISUAL

DD-20

Chapman, Wood and Griswold Ltd.

DRILL HOLE GEOLOGIC LOG

HOLE NUMBER: Ddh 2

COMPANY: ______ PROPERTY: ______ LOGGED BY: ______ DATE: ______

PAGE 3 OF ______

C.W.& G. FORM BY S.T. FOR PH

DIP ______ AZIM ______

TYPE OF HOLE: DDH ☐ RDH ☐ PDH ☐

STRUCTURE AND/OR ALTERATION	CONTACTS AND PRINCIPAL ZONES (IF ROTARY OR PERCUSSION HOLE) COMMENTS On Coarse, Heavies & Water float	BOTTOM OF INTERVAL DESCRIBED	RECOVERY %	STRUCTURE	HOST ROCK	ALTERATION ASSEMBLAGE	MINERALIZATION
		170			162.0 – THIN SECTION FRC – OPEN = WHITE XLS – QZ? & CLOSED – FL(?) FILLED W = 45-60 ∠ OCC 0-10°		
		180			175.0 – 180.0 = TRACES OF PYRITE		
180.0 END OF HOLE							

Column headings: STRUCTURE — FRC. DENSITY PER FT (< 30°, 30°-60°, 60°-80°, INTENSITY), FOLIATION (ANGLE, INTENSITY, ANGLE FRC TO FOLIATION); HOST ROCK — COLOR, TYPE MODIFIER, ACCESSORY MINERALS, % HB, % BI, TEXTURE, GRAIN SIZE, ROCK TYPE (USE 4-LETTER CODE); ALTERATION ASSEMBLAGE — QUARTZ QZ (MODE OF OCCURRENCE, AMOUNT), K-SPAR KF, BIOTITE BI, SERICITE MU, CLAYS CY, CHLORITE CL, EPIDOTE EP, CARBONATES CB, OTHER (Use 2-letter code at interval or as here in space), PRINCIPAL FACIES, INTENSITY; MINERALIZATION — PYRITE, BORNITE, CHALCOPYRITE, MALACHITE, AZURITE, COPPER LIMONITE, MAGNETITE, HEMATITE, % LEACH (MODE, AMT.).

ESTIMATES & ASSAYS ELEMENTS or MINERALS — VISUAL; COARSE, HEAVIES, WATER FLOAT, OTHER REMARKS & COMMENTS (C, H, W)