


Airborne Geophysical Survey Report



Precision
GeoSurveys Inc.

095362

| Claim Name and Number | Grant Number | Claim Name and Number | Grant Number |
|-----------------------|-----------------|-----------------------|-----------------|
| VIP 1-56 | YD61501-YD61556 | VIP521-522 | YD62101-YD62102 |
| VIP 61-70 | YD61561-YD61570 | VIP523-528 | YD63653-YD63698 |
| VIP 75-86 | YD61575-YD61586 | VIP531-564 | YD63661-YD63694 |
| VIP 89-100 | YD61589-YD61600 | VIP573-578 | YD64003-YD64008 |
| VIP 103-120 | YD61483-YD61500 | VIP646 | YD63926 |
| VIP 121-126 | YD61477-YD61482 | VIP648 | YD63928 |
| VIP 127-138 | YD12527-YD12538 | VIP698-720 | YD63978-YD64000 |
| VIP 172-181 | YD12572-YD12581 | VIP721-725 | YD63801-YD63805 |
| VIP 204-214 | YD62134-YD62144 | VIP726-731 | YD63816-YD63821 |
| VIP225-241 | YD62155-YD62171 | VIP737-750 | YD63827-YD63840 |
| VIP242-277 | YD62312-YD62347 | VIP757-764 | YD63887-YD63894 |
| VIP282-293 | YD62352-YD62363 | VIP793-794 | YD62873-YD62874 |
| VIP306-307 | YD62376-YD62377 | VIP795-796 | YD62215-YD62216 |
| VIP308-319 | YD61648-YD61659 | VIP797-818 | YD63717-YD63738 |
| VIP400 | YD62100 | VIP830 | YD63900 |
| VIP401-413 | YD62201-YD62213 | VIP832-833 | YC86542-YC86543 |
| VIP417-420 | YD62217-YD62220 | VIP867 | YD63787 |
| VIP473-478 | YD62273-YD62278 | VIP869 | YD63789 |
| VIP507-519 | YD12587-YD12599 | XT7-12 | YD51007-YD51012 |



VIP Property – Whitehorse Mining District

N.T.S. 115J13 – UTM Coordinates 552000N-563000N / 6972000N-6986000N

Work performed between December 11-18, 2010

Airborne Geophysical Survey Report

Prepared for: Goldspike Exploration Inc. (2258501 Ontario Inc.)

December 2010, Jenny Poon, B.Sc., GIT

Table of Contents

| | | |
|-----|--|-------------|
| 1.0 | Introduction..... | 1 |
| 2.0 | Geophysical Data..... | 2 |
| 2.1 | Magnetic Data..... | 2 |
| 2.2 | Radiometric Data..... | 3 |
| 3.0 | Survey Operations..... | 3 |
| 4.0 | Equipment..... | 4 |
| 4.1 | AGIS..... | 4 |
| 4.2 | Spectrometer..... | 5 |
| 4.3 | Magnetometer..... | 5 |
| 4.4 | Base Station..... | 6 |
| 4.5 | Laser Altimeter..... | 7 |
| 5.0 | Data Processing..... | 7 |
| 5.1 | Magnetic Processing..... | 7 |
| 5.2 | Radiometric Processing..... | 8 |
| 5.3 | Final Data Format..... | 8 |
| | Appendix A: Maps..... | 9 |
| | Appendix B: Statement of Qualifications..... | Back Pocket |
| | Appendix C: List of Claims..... | Back Pocket |
| | Appendix D: Claim Location Map | Back Pocket |

Appendix E: Data CD.....Back Pocket

- VIP_Database.gdb
- VIP_Dataset.XYZ
- _dz.grd
- k_lag_corr.grd
- TC_lag_corr.grd
- TH_lag_corr.grd
- TotalMagIntensity.grd
- Ur_lag_corr.grd
- CalculatedVerticalGradient.jpg
- Potassium_Lag_Corrected.jpg
- Thorium_Lag_Corrected.jpg
- TotalCount_Lag_Corrected.jpg
- TotalMagIntensity.jpg
- TotalMagIntensity_Flightlines.jpg
- Uranium_Lag_Corrected.jpg
- Airborne Geophysical Survey Report

Introduction:

This report outlines the survey operations and data processing actions taken during the airborne geophysical survey flown at the VIP Block. The airborne geophysical survey was flown by Precision GeoSurveys Inc. for 2258501 Ontario Inc. The geophysical survey, carried out from December 11, 2010 to December 18, 2010, saw the acquisition of gamma ray spectrometer data and magnetic data.




Figure 1: VIP Block area location relative to Dawson, YT.

The VIP Block is located south of Dawson, YT and north of Thistle Creek (Figure 1). It is located approximately 125 km south-west of Dawson, YT (Figure 2). The survey area itself is approximately 7.5 km by 12 km. A total of 1055 line kilometers of radiometric and magnetic data were flown for this survey; this total includes tie lines and survey lines. The survey lines were flown at 100 meter spacings at a $020^{\circ}/200^{\circ}$ heading; the tie lines were flown at 1 km spacings at a heading of $110^{\circ}/290^{\circ}$.




Figure 2: Survey and tie lines outlined in yellow and the boundary in red.

1.0 Geophysical Data:

Geophysical data are collected in a variety of ways and are used to aid in the exploration and determination of geology, mineral deposits, oil and gas deposits, contaminated land sites and UXO detection.

For the purposes of this survey, airborne gamma ray spectrometer and magnetic data were collected to serve in the exploration of the VIP Block which contains rocks that are prospective for gold mineralization.

2.1 Magnetic Data:

Magnetic surveying is probably the most common airborne survey type to be conducted for both mineral and hydrocarbon exploration. The type of survey specifications, instrumentation, and interpretation procedures, depend on the objectives of the survey. Typically magnetic surveys are performed for:

1. Geological Mapping to aid in mapping lithology, structure and alteration in both hard rock environments and for mapping basement lithology, structure and alteration in sedimentary basins or for regional tectonic studies.
2. Depth to Basement mapping for exploration in sedimentary basins or mineralization associated with the basement surface.

2.2 Radiometric Data:

Radiometric surveys detect and map natural radioactive emanations, called gamma rays, from rocks and soils. All detectable gamma radiation from earth materials come from the natural decay products of three primary elements: uranium, thorium, and potassium. The purpose of radiometric surveys is to determine either the absolute or relative amounts of U, Th, and K in surface rocks and soils.

3.0 Survey Operations:

Precision GeoSurveys flew the VIP Block using a Bell 206 BIII Jet Ranger (Figure 3). The survey lines were flown at a nominal line spacing of one hundred (100) meters and the tie lines were flown at 1 km spacing for both the spectrometer and magnetometer as they were acquired simultaneously. The average survey elevation was 37 meters vertically above ground as to avoid dead white spots on the snow covered mountains. The experience of the pilot helped to ensure that the data quality objectives were met and that the safety of the flight crew was never compromised given the potential risks involved in airborne surveying.




Figure 3: Bell 206 Jet Ranger equipped with mag stinger for magnetic data acquisition.

The base of operations for this survey was in Dawson, YT. The Precision crew consisted of a total of three members:

John Withem– Pilot
Shawn Walker – Operator
Jenny Poon –On-site Geophysicist

The survey was started on December 11, 2010 and completed on December 18, 2010. The survey was complete with delays due to low cloud ceilings and from magnetic solar storms and the survey was flown with variable snow covered conditions.

4.0 Equipment:

For this survey a magnetometer, spectrometer, base station, laser altimeter, and a data acquisition system were required to carry out the survey and collect quality, high resolution data.

4.1 AGIS:

The Airborne Geophysical Information System, AGIS, (Figure 4), is the main computer used in data recording, data synchronizing, displaying real-time QC data for the geophysical operator, and generation of navigation information for the pilot display system.



Figure 4: AGIS installed in the Bell 206.

The AGIS was manufactured by Pico Envirotec; therefore the system uses standardized Pico software and external sources are connected to the system via RS-232 serial communication cables. The AGIS data format is easily converted into Geosoft or ASCII file formats by a supplied conversion program called PEIView. Additional Pico software allows for post survey quality control procedures.

4.2 Spectrometer:

The IRIS, or Integrated Radiometric Information System is a fully integrated, gamma radiation detection system containing two downward facing NaI detecting crystals for a total volume of 8.4 litres (Figure 5). Real time data acquisition, navigation and

communication tasks are integrated into a single unit that is installed in the rear of the aircraft as indicated below. Information such as total count, counts of various elements (K, U, Th, etc.), temperature, barometric pressure, atmospheric humidity and survey altitude can all be monitored on the AGIS screen for immediate QC. All the radiometric data are recorded at 1 Hz.




Figure 5: IRIS strapped into the cargo box of the helicopter.

4.3 Magnetometer:

The magnetometer used by Precision GeoSurveys is a Scintrex cesium vapor CS-3 magnetometer. The system was housed in a front mounted “stinger” (Figure 6). The CS-3 is a high sensitivity/low noise magnetometer with automatic hemisphere switching and a wide voltage range, the static noise rating for the unit is ± 0.01 nT. On the AGIS screen the operator can view the raw magnetic response, the magnetic fourth difference and the survey altitude for immediate QC of the magnetic data. The magnetic data are recorded at 10 Hz. A magnetic compensator is also used to remove noise created by the movement of the helicopter as it pitches, rolls and yaws within the Earth’s geomagnetic field.



Figure 6: View of the mag stinger.

4.4 Base Station:

For monitoring and recording of the Earth's diurnal magnetic field variation, Precision GeoSurveys uses a Scintrex proton precession Envi Pro magnetometer as its base station (Figure 7). This is mounted as close to the survey block as possible to give high, accurate magnetic field data. The Envi Pro base station, uses the well proven precession technology to sample at a rate of 0.5 Hz. A GPS is integrated with the system to record real GPS time that is used to correlate with the GPS time collected by the airborne CS-3 magnetometer.



Figure 7: Scintrex Envi Pro proton precession magnetometer.

4.5 Laser Altimeter:

The pilot is provided with terrain guidance and clearance with an Acuity AccuRange AR3000 laser altimeter (Figure 8). This is attached at the aft end of the magnetometer boom. The AR3000 sensor is a time-of-flight sensor that measures distance by a rapidly-modulated and collimated laser beam that creates a dot on the target surface. The maximum range of the laser altimeter is 300 m off of natural surfaces with 90% reflectance and 3 km off special reflectors. Within the sensor unit, reflected signal light is collected by the lens and focused onto a photodiode. Through serial communications and analog outputs, the distance data are transmitted and collected by the AGIS at 10 Hz.



Figure 8: Acuity AccuRange AR3000 laser altimeter.

5.0 Data Processing:

After all the data are collected after a survey flight several procedures are undertaken to ensure that the data meet a high standard of quality. All data were processed using Pico Envirotec software and Geosoft Oasis Montaj geophysical processing software.

5.1 Magnetic Processing:

During aeromagnetic surveying noise is introduced to the magnetic data by the aircraft itself, movement in the aircraft (roll, pitch and yaw) and the permanent magnetization of the aircraft parts (engine and other ferric objects) are large contributing factors to this noise. To remove this noise a process called magnetic compensation is implemented. The magnetic compensation process starts with a test flight at the beginning of the survey where the aircraft flies in the four orthogonal headings required for the survey ($000^{\circ}/152^{\circ}$ and $080^{\circ}/217^{\circ}$ in the case of this survey) at an elevation where there is no ground effect in the magnetic data. In each heading roll, pitch and yaw maneuvers are performed by the pilot, these maneuvers provide the data that is required to calculate the necessary parameters for compensating the magnetic data. A computer program called PEIComp is used to create a model for each survey to remove the noise induced by aircraft movement; this model is applied to each survey flight so the data can be further processed.

A magnetic base station is set up before every flight to ensure that diurnal activity is recorded during the survey flights. Precision GeoSurveys uses a Geometrics 858 base station and sampled at 0.1Hz. Base station readings were reviewed at regular intervals to insure that no data were collected during periods with high diurnal activity (greater than 5 nT per minute). The base station was installed at a magnetically noise-free area, away from metallic items such as steel objects, vehicles, or power lines. The magnetic variations recorded from the stationary base station are removed from the magnetic data recorded in flight to ensure that the anomalies seen are real and not due to solar activity.

Some filtering of the magnetic data is also required. A Non Linear filter was used for spike removal. The 1D Non-Linear Filter is ideal for removing very short wavelength, but high amplitude features from data. It is often thought of as a noise spike-rejection filter, but it can also be effective for removing short wavelength geological features, such as signals from surficial features. The 1D Non-Linear Filter is used to locate and remove data that are recognized as noise. The algorithm is 'non-linear' because it looks at each data point and decides if that datum is noise or a valid signal. If the point is noise, it is simply removed and replaced by an estimate based on surrounding data points. Parts of the data that are not considered noise are not modified. The combination of a Non-Linear filter for noise removal and a low pass trend enhancement filter resulted in level data as indicated in the results section of this report. The low pass filters simply smoothes out the magnetic profile to remove isolated noise.

A lag correction of 1.7 seconds was applied to the total magnetic field data to compensate for the lag in the recording system as the magnetometer sensor flies 6.45 m ahead of the GPS antenna.

5.2 Radiometric Processing:

Radiometric data were collected simultaneously with the magnetic data and with variable thick deposit of snow, lag correction of 1.4 secs was corrected for the radiometric data only.


5.3 Final Data Format

Abbreviations used in the GDB files are as follows:


X – Easting in WGS84, UTM zone 7N
Y – Northing in WGS84, UTM zone 7N
galt – gps altimeter readings
lalt – laser altimeter readings
dtm – digital terrain model
GPStime– GPS time
basemag – diurnal data
mag – total magnetic field
TC_lag_corr – lag corrected total count
K_lag_corr – lag corrected potassium
U_lag_corr – lag corrected uranium
Th_lag_corr – lag corrected thorium

The file format will be provided in two (2) formats, the first will be a .GDB file for use in Geosoft Oasis Montaj, the second format will be a .XYZ file, this is text file. A complete file provided in each format will contain both radiometric and magnetic data.


Appendix A
Maps




Map 1: VIP Block total magnetic intensity.




Map 2: VIP Block total count lag corrected.



Map 3: VIP Block potassium lag corrected.



Map 4: VIP Block uranium lag corrected.



Map 5: VIP Block thorium lag corrected.

STATEMENT OF QUALIFICATIONS

I, Jenny C.M. Poon, hereby certify that:

1. I am employed as a geophysicist with Precision GeoSurveys Inc. with office address #520-355 Burrard Street, Vancouver, British Columbia V6C 2G8.
2. I am a graduate of the University of Calgary with a B.Sc. in geophysics (2009).
3. I have been employed as a geophysicist on a full-time basis since 2010.
4. I am a registered as a Geophysicist in Training with the Association of Professional Engineers, Geologists, and Geophysicists of Alberta.
5. I am the author of this report, and I supervised the collection and processing of airborne geophysical data on the VIP property.
6. This report is intended to satisfy assessment requirements only.


June 9, 2011










Jenny Poon, B.Sc., GIT

APPENDIX 'C' – LIST OF CLAIMS

| <u>CLAIM NAME & NO.</u> | <u>GRANT NO.</u> | <u>REGISTERED OWNER</u> |
|-----------------------------|------------------|----------------------------|
| VIP 1-56 | YD61501-YD61556 | Goldspike Exploration Inc. |
| VIP 61-70 | YD61561-YD61570 | Goldspike Exploration Inc. |
| VIP 75-86 | YD61575-YD61586 | Goldspike Exploration Inc. |
| VIP 89-100 | YD61589-YD61600 | Goldspike Exploration Inc. |
| VIP 103-120 | YD61483-YD61500 | Goldspike Exploration Inc. |
| VIP 121-126 | YD61477-YD61482 | Goldspike Exploration Inc. |
| VIP 127-138 | YD12527-YD12538 | Goldspike Exploration Inc. |
| VIP 172-181 | YD12572-YD12581 | Goldspike Exploration Inc. |
| VIP 204-214 | YD62134-YD62144 | Goldspike Exploration Inc. |
| VIP225-241 | YD62155-YD62171 | Goldspike Exploration Inc. |
| VIP242-277 | YD62312-YD62347 | Goldspike Exploration Inc. |
| VIP282-293 | YD62352-YD62363 | Goldspike Exploration Inc. |
| VIP306-307 | YD62376-YD62377 | Goldspike Exploration Inc. |
| VIP308-319 | YD61648-YD61659 | Goldspike Exploration Inc. |
| VIP400 | YD62100 | Goldspike Exploration Inc. |
| VIP401-413 | YD62201-YD62213 | Goldspike Exploration Inc. |
| VIP417-420 | YD62217-YD62220 | Goldspike Exploration Inc. |
| VIP473-478 | YD62273-YD62278 | Goldspike Exploration Inc. |
| VIP507-519 | YD12587-YD12599 | Goldspike Exploration Inc. |
| VIP521-522 | YD62101-YD62102 | Goldspike Exploration Inc. |
| VIP523-528 | YD63653-YD63658 | Goldspike Exploration Inc. |
| VIP531-564 | YD63661-YD63694 | Goldspike Exploration Inc. |
| VIP573-578 | YD64003-YD64008 | Goldspike Exploration Inc. |
| VIP646 | YD63926 | Goldspike Exploration Inc. |
| VIP648 | YD63928 | Goldspike Exploration Inc. |
| VIP698-720 | YD63978-YD64000 | Goldspike Exploration Inc. |
| VIP721-725 | YD63801-YD63805 | Goldspike Exploration Inc. |
| VIP726-731 | YD63816-YD63821 | Goldspike Exploration Inc. |
| VIP737-750 | YD63827-YD63840 | Goldspike Exploration Inc. |
| VIP757-764 | YD63887-YD63894 | Goldspike Exploration Inc. |
| VIP793-794 | YD62873-YD62874 | Goldspike Exploration Inc. |
| VIP795-796 | YD62215-YD62216 | Goldspike Exploration Inc. |
| VIP797-818 | YD63717-YD63738 | Goldspike Exploration Inc. |
| VIP830 | YD63900 | Goldspike Exploration Inc. |
| VIP832-833 | YC86542-YC86543 | Goldspike Exploration Inc. |
| VIP867 | YD63787 | Goldspike Exploration Inc. |
| VIP869 | YD63789 | Goldspike Exploration Inc. |
| XT7-12 | YD51007-YD51012 | Goldspike Exploration Inc. |



- Legend**
-  Active - Quartz Mineral Claims
 -  Location line direction
 -  Contour line intervals - 100 feet
 -  Contour line intervals - 500 feet
 -  Watercourses
 -  Waterbody



GOLDSPIKE EXPLORATION INC.
 WHITEHORSE DISTRICT - NTS 115J13
CLAIM LOCATION PLAN
VIP PROPERTY

Drawn: R. Sedore

Date: June 12, 2011