

M. Mining Recorder of MAYO

Supervising Mining Recorder at Whitehorse, Y.T.

ACTION ARE:

NEW APPL'N for PLACER LEASE to PROSPECT: Name:

RENEWAL APPL'N PLACER LEASE to PROSPECT: Name:

AFFIDAVIT of EXPENDITURE on PLACER LEASE. Name:

ASSIGNMENT of PLACER LEASE No.

From:

To:

GROUPING APPL'N UNDER SEC. 52(2) PLACER MINING ACT.

Owner:

DIAMOND DRILL LOGS:

Claims: SNOWDRIFT 1-29
KPD 1-4, 18-29
BUCONJO 17-24

QUARTZ ASSESSMENT REPORT:

Claims:

Type of report: DD

Cls. work performed on:

SNOWDRIFT 5, 22-24, 26-2946 HOLES5270 FEETClaim sheet no. 105-M-13

Claim sheet no.

Submitted by:

UNITED KENO HILL MINES LIMITED

\$ Req. for ren. application

Signature Guill M. Graham

LY ACTION.

Date Ret.

CC: GEOLOGY

091049

Signature

091049

UNITED KENO HILL MINES LTD.

#6-B

OVERBURDEN DRILL HOLE LOG

Location Snow Drift Latitude 69228.43 Departure 161874.58 Hole No. 10330 ✓
 Date Drilled Oct/81 Elevation 2948.52 Bearing 235° Page No. 1 Of 4
 Casing Depth 30' Overburden Depth 35-40' Length of Hole 200' Dip 50°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)			Sample No.	Geochemical Results				Au Assay Results			
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams				Pb. (ppm)	Ag. (ppm)	Zn (ppm)	W ₃	Ag. (oz/ton)	Pb. (%)	Zn (%)	
0	10	86099	25	25		25	25	T	4.5	GQ 70% Qtz 20% GS 6% Grnst T. Fe ₂ O ₄ MnO ₃ Lim 1% ZnS T.	86099	118	3.1	337						
10	15	86100	25	25		25	25	T	5.3	GQ 60% Qtz 25% MnO ₄ Grnst 1% SS 2% Lim 2% ZnS 1% GS 5%	86100	26	.7	146						
15	20	86101	25	25		25	25	T	2.0	GQ 75% Qtz 10% GS 10% ZnS 1% MnO ₃ 3% Lim 1%	86101	37	.6	144						
20	25	86102	25			50	25	T	1.9	GQ 70% Qtz 15% GS 5% Grnst 3% Lim 2% MnO ₃ 5% ZnS T	86102	7	1.0	127						
25	30	86103	25	25		25	25	T	1.1	GQ 80% Qtz 10% GS 4% Lim 2% SS 1% ZnS 1% MnO ₃ 2%	86103	25	.1	138						
30	35	86104	25	10	15	25	25	T	6.9	GQ 75% Grnst 15% Qtz 5% SS 1% MnO ₃ 1% Py 1% Lim 2%	86104	83	1.4	158						
35	40	86105	25		25	25	25	T	6.7	GQ 65% Qtz 22% Lim 4% GS 5% MnO ₃ 2% ZnS 2% Grnst, Fe ₂ O ₄ , SS, Fe ₂ O ₃ , Py T	86105	6	.1	131						
40	45	86106	25		25	25	25	T	6.1	GQ 40% Qtz 30% Lim 8% SS 4% Grnst 5% ZnS 2% Py 4% GS 7%	86106	159	(3.2)	188						
45	50	86107	25		25	25	25	T	7.3	GQ 50% SS 10% Lim 10% Qtz 10% Py 4% Grnst 6%	86107	5	.1	150						
50	55	86108	25		25	25	25	T	9.0	Qtz 30% GQ 30% SS 10% GS 7% Lim 5% Py 10% Grnst 8% ZnS T.	86108	30	.1	166						
55	60	86109	25		25	25	25	T	7.2	GQ 60% Py 15% SS 10% GS 2% Qtz 8% ZnS 2% Lim 3%	86109	2	.1	128						

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Drift Latitude _____ Departure _____ Hole No. 10330
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 of 4
 Casing Depth 30' Overburden Depth 35'-40' Length of Hole 200' Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results			
From	To		G.Q.	G.S.	S.S.	Gmst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	W ₀₃	Au (oz/ton)	Pb. (%)	Zn (%)
60	65	86110	25		25	25	25	T	5.1	GQ + Gmst 65% Mn 0.5% SS 10% Py 30% Lim 2% Qtz 4% ZnS 1%	86110	1	1	1212				
65	70	86111	25		25	25	25	T	5.0	GQ 70% SS 25% ZnS 2% Qtz 2% Lim 1% Py T	86111	(109)	(3)	179				
70	75	86112	25		25	25	25	T	7.5	GQ + Gmst 65% SS 30% Py 2% Lim T Qtz 3%	86112	12	1	161				
75	80	86113	25		25	50		T	9.0	GQ 40% Qtz 10% Fe ₂ S ₈ % Py 10% FeS 2% ZnS T Lim T	86113	10	1	151		.013		
80	85	86114	25		50	25		T	7.5	GQ 55% Py 20% SS 10% Qtz 15% Fe ₂ S T	86114	14	1	169				
85	90	86115	25		25	25	25	T	5.3	GQ 70% SS 5% ZnS 2% Qtz 5% Py 8%	86115	27	1	206				
90	95	86116	25		25	50		T	6.0	GQ 80% SS 12% Py 3% Mn 0.2% ZnS 1% Fe ₂ S 1% Lim 1%	86116	1	1	141				
95	100	86117	50		25		25	T	4.4	GQ 65% SS 30% Py 3% Lim 1% ZnS 1% Fe ₂ S T	86117	1	1	129				
100	105	86118	50		50			T	7.8	Qtz 40% SS 40% Py 4% Fe ₂ S 1% GQ 15%	86118	1	1	115				
105	110	86119	25		25	50		T	6.4	SS 50% GQ 43% Py 5% Fe ₂ S 1% Lim 1% ZnS T	86119	1	1	111				
110	115	86120	25		25	50		T	6.6	SS 60% GQ 40% Lim + Py T	86120	1	1	90				

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Drift Latitude _____ Departure _____ Hole No. 10330
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 3 of 4
 Casing Depth 30' Overburden Depth 35-42' Length of Hole 200' Dip 58°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Au Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86121	50				50	T	5.6	GA 55% SS 40% Grnst 1% Py 2% MnO 1% GS 1%	86121	1	1	90			
120	125	86122	50				50	T	5.5	Gr 2 50% GA 30% SS 20% Py 7% GS 3% Lim T	86122	8	1	52			
125	130	86123	25		25	25	25	T	9.0	Gr 2 45% GA 35% SS 5% GS 6% Lim 1% Py 8%	86123	8	1	58			
130	135	86124	25		25	50		T	7.3	GA + Gr 90% SS 4% Lim 1% Py 3% GS 2%	86124	11	1	37			
135	140	86125	25		25	50		T	7.9	GA 85% SS 8% Py 7% Calc + Fe 30% Lim T	86125	1	1	85			
140	145	86126	25		25	50		T	6.7	Gr 2 30% GA 30% SS 15% Py 20% Fe 35% S 5%	86126	5	1	211	012		
145	150	86127	50		25	25		T	8.2	GA 50% Py 4% SS 10% Gr 2 25% GS 5% Fe - S 1% ZnS T Lim T	86127	71	1	492			
150	155	86128	50		25	25		T	5.2	GA 45% Fe - S 10% Gr 2 40% Py 3% GS 2%	86128	1	1	125			
155	160	86129	75		25			T	6.3	Gr 2 70% Fe - S 15% SS 10% Py 20% Lim 10% MnO 2% GS T	86129	2	2.0	153			
160	165	86130	25		25	25	25	T	6.6	Gr 2 75% SS 15% Calc 1% Fe - S 30% Py 3% MnO 1% Lim 2%	86130	1	1.4	95			
165	170	86131	25		25	25	25	T	7.4	GA 50% Gr 2 30% GS 5% SS 5% Fe - S 4% Py 2% Lim 1% Grnst 3%	86131	1	1.5	149			

UNITED KENO HILL MINES LTD.

Location Snow DRIFT Latitude _____ Departure _____ Hole No. 10330
Date Drilled _____ Elevation _____ Bearing _____ Page No. 4 Of 4
Casing Depth 30' Overburden Depth 35-40' Length of Hole 200' Dip 58°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

#76

Location Snow Drift Latitude 68 932.67 Departure 162 297.45 Hole No. 10331
 Date Drilled Oct/81, 13th Elevation 2944.19 Bearing 320° Page No. 1 Of 4
 Casing Depth 30' Overburden Depth 33' 40' Length of Hole 170' Dip 55°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86138	50		25		25	T	0.5	QT240 GRNST20 SS10 PY10 MN.5 CaCO3 5 Lim 5 Fe2O3 5	86138	6	1.5	118			
10	15	86139	50		25		25	T	8.5	QT230 MN.10 PY10 GRNST10 SS.10 Lim10 MNO2.5 GS.10 GAB	86139	28	(2.5)	128			
15	20	86140	50			50		T	10	QT230 GQ20 GS.10 Lim10 GRNST10 PY10 ZNS.1	86140	42	(2.2)	162			
20	25	86141	50			50		T	7	QT230 PY10 GS.10 MN.5 GRNST10 ZNS.5 MNO2.5 SS.5 GQ10 Lim10	86141	19	2.0	20			
25	30	86142	25			50	25	T	1	QT230 PY5 GS.10 MN.5 GRNST10 ZNS.1 MNO2.5 SS5 GQ10 Lim10	86142	24	2.8	1			
30	35	86143	25	25		25	25	T	10	QT230 MN.5 GS10 GQ15 SS.10 PY.5 MNO2.5 FE3O4.5 GRNST15	86143	21	2.0	1			
35	40	86144	25	25		25	25	T	10	GQ20 GRNST20 QT2.20 MN.10 SS5 PY5 FE3O4.5 CaCO3.5	86144	1	2.1	1			
40	45	86145		15	10	50	25	T	7	MN.10 QT230 GS.10 PY5 SS.15 GRNST15 GQ15	86145	31	2.4	1			
45	50	86146	25		25	50		T	8	SS.30 QT230 PY5 GRNST10 CaCO3.5 GQ15 MN.5 KP55	86146	1	1.2	1			
50	55	86147	50			50		T	9	QT230 GQ30 Lim5 GRNST10 CaCO3.10 MN.5 GS.5 PY5	86147	1	.9	1			
55	60	86148	50			50		T	10	MN.5 QT230 GQ30 PY5 Lim10 CaCO3.5 FE3O4.5 GS.5 SS.5	86148	1	1.4	1			

UNITED KENO HILL MINES LTD. OVERBURDEN DRILL HOLE LOG

Location Snow DRIFT Latitude _____ Departure _____ Hole No. 10331
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 of 3
 Casing Depth 30' Overburden Depth 35-40' Length of Hole 170' Dip 55°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86148	25	25		25	25	T	9.	QT230 SS.30 LIM10 GRNST10 PY5 MN5 GQ10	86149	1	1.3	1			
65	70	86150	25	25		25	25	T	8.	QT230 SS.30 LIM10 GRNST10 PY5 MN5 GQ10	86150	1	1.3	112			
70	75	86151	50			25	25	T	10.	MN025 QT230 LIM10 GRNST10 PY5 MN5 MN5 SS.10 FEAS.10 ZNS.10	86151	1	3.4	112		.037	
75	80	86152	25	25		25	25	T	5.	ZNS.5 PY10 LIM15 QT230 GRNST10 GQ10 CS.10 SS.10	86152	5	1.4	107			
80	85	86153	25	25		25	25	T	8.5	LIM15 QT230 PY10 ZNS.5 GRNST10 SS.20 MN5 CAL035	86153	(22)	(3.4)	298			
85	90	86154	25	25	25	25		T	8.	LIM10 SS.15 QT230 ZNS.5 PY5 MN5 GQ25 CS.10 MN25 CAL035 FE3045	86154	1	1.6	107			
90	95	86155	25	25	25	25		T	10.	QT2.30 SS.15 PY10 LIM20 GRNST15 FEAS5 GQ5 ZNST	86155	1	1.3	113			
95	100	86156	25	25	25	25		T	4.	QT230 PY5 GRNST15 SS.20 LIM10 GQ5 FE1-XS5 FE2035 ZNST	86156	1	1.2	120			
100	105	86157	25	25	25	25		T	6.	QT230 SS.20 GQ10 LIM5 FE1-XS.5 PY10 CS.5 MN5 GRNST10	86157	1	1.3	76			
105	110	86158	25	25		25	25	T	7.	QT240 SS.20 MN5 GQ10 PY10 GRNST10 FEAS5	86158	1	2.0	169			
110	115	86159	25	25	25	25		T	8.	QT230 GRNST10 PY10 FE30410 GQ10 FEAS10 ZNS.5 MN5 FEAS5	86159	1	1.6	110		.019	

UNITED KENO HILL MINES LTD. OVERBURDEN DRILL HOLE LOG

Location Snow DRIFT Latitude _____ Departure _____ Hole No. 10331
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 3 of 3
 Casing Depth 30 Overburden Depth 36-40 Length of Hole 170 Dip 55°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim.	grams			Pb. (ppm)	Ag. (ppm)	EN (PAM)	WGS (PAM)	Pb. (oz/ton)	Pb. (%)	Zn (%)
115	120	86160	25	25	25	25		T	6.	QTZ 30 SS.15 GRNST10 Mn.10 FE3045 ZNS5 CaCO3 10 PY10 GQ10 (CaWO4 15) FEAS5.5	86160	1	1.2	107	164	.020		
120	125	86161	25	25	25	25		T	8.	QTZ 50 SS.15 GRNST10 PY10 CaCO3 10	86161	1	1.1	99				
125	130	86162	25	25	25	25		T	7.	QTZ 40 SS.15 MNS ZNS.T PY10 CaCO3 10 GQ10 LIM10	86162	1	1.1	107				
130	135	86163	25	25	25	25		T	9.5	LIM10 SS.25 PY10 QTZ 30 CaCO3 10 GQ10 MNS25 GS.5	86163	1	2.5	92				
135	140	86164	25	25	25	25		T	7.5	QTZ 30 FE1-XS10 FEAS10 CaCO3 10 PY10 SS.15 GRNST10 GQ10 (CaWO4 10)	86164	(24)	(1.9)	127	<40	.007		
140	145	86165	25	25	25	25		T	10.	QTZ 30 FE1-XS10 FEAS10 GRNST15 PY10 CaCO3 10 ZNS5 MNS5 GS.5	86165	1	1.2	163	<40	.015		
145	150	86166	25	25		25	25	T	8.5	QTZ 30 FE1-XS15 GQ10 FEAS10 (CaWO4 10) GRNST15 SS.15 MNS5 CaCO3 10	86166	1	1.2	94	<40	.011		
150	155	86167	50				50	T	8.	QTZ 30 GQ30 GRNST10 SS.15 CaCO3 10 LIM5 (CaWO4 10)	86167	1	1.9	87	88			
155	160	86168	50			50		T	9.	QTZ 30 GQ30 FE1-XS15 LIM5 CaCO3 10 PY10 (CaWO4 10)	86168	1	1.1	100	<40			
160	165	86169	50			50		T	4.	QTZ 30 GQ30 PY10 FE1-XS15 FEAS10 CaCO3 5 (CaWO4 10)	86169	1	1.2	115	<40	.011		
165	170	86170	50			50		T	7.	QTZ 30 GQ30 ZNS5 CaCO3 10 PY10 FE1-XS10 FEAS10 (CaWO4 10)	86170	1	.9	153	<40	.010		

OVERBURDEN DRILL HOLE LOG

Location Snow drift Latitude 68640.30 Departure 162688.09 Hole No. 10332 ✓
 Date Drilled Oct 18/81 Elevation 2936.65 Bearing 320° Page No. 1 Of 4
 Casing Depth 60 Overburden Depth 65 Length of Hole 180 Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86171	25	25		25	25	T	10	GA 80% GT 15% SS 2% Fe ₂ O ₃ T GP GS 3% CaCO ₃ T	86171	1	1.2	124			
10	15	86172	25	25			50	T	7	GA 85% GT 26% ZnS 2% GP GS 5% SS 2% CaCO ₃ T.	86172	1	1.5	310			
15	20	86173				100		T	5	GA 96% GP GS 2% GT 1% Fe ₂ O ₃ T PyT ZnS 1% SS T CaCO ₃ T	86173	1	1.1	134			
20	25	86174	25	25		25	25	T	10	GA 70% GT 25% Grnst 1% GS 3% Lim 1% ZnS 1% CaCO ₃ T.	86174	1	2.1	121			
25	30	86175	25	25		25	25	T	8	GA 65% GT 30% Grnst 5% GS 4% SS 3% Py 2% MnO ₂ 1% CaCO ₃ T.	86175	1	1.1	107			
30	35	86176	25	25		95	25	T	9	GA 70% GT 20% Grnst 2% Lim 1% GS 4% PyT CaCO ₃ T Fe ₂ O ₃ T SS 2% ZnS 1%	86176	1	1.6	126			
35	40	86177	25	25		25	25	T	8	GA 70% GT 15% SS 2% Fe ₂ O ₃ 1% Py 1% MnO ₂ 3% Lim 2% CaCO ₃ 1% Grnst 5% Fe ₂ O ₃ T.	86177	1	1.0	98			
40	45	86178	25	25		25	25	T	4	GA 50% GT 25% SS 5% Grnst 8% MnO ₂ 3% Lim 4% CaCO ₃ 1% GS 4%	86178	1	.9	80			
45	50	86179	25	25		25	25	T	7	GA 45% Grnst 10% GT 30% MnO ₂ 8% SS 5% CaCO ₃ 2% Fe ₃ O ₄ T.	86179	1	.8	96			
50	55	86180	25	25		25	25	T	10	GA 55% GT 25% SS 8% GS 2% MnO ₂ 7% LimT Fe ₂ O ₃ T Grnst 3% CaCO ₃ T.	86180	1	.9	98			
55	60	86181	25	25		25	25	T	9	GA 53% GT 35% Grnst 5% GS 2% MnO ₂ 3% CaCO ₃ 2%	86181 (3)	(3.0)	96				

UNITED KENO HILL MINES LTD. # 109.

OVERBURDEN DRILL HOLE LOG

Location _____ Latitude _____ Departure _____ Hole No. 10332
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 Of 4.
 Casing Depth _____ Overburden Depth _____ Length of Hole _____ Dip _____

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	WO ₃ (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86182	25	25		25	25	T	10	GA 60% SS 8% Grnst 4% G.S. 1% Qtz. 20% Py 1% Scheelite T.	86182	1	1.2	77	<40			
65	70	86183	25		20	30	25	T	7	GA 55% Grnst 30% SS 10% Fe ₃ O ₄ 2% G.S. 3% Py 1% Scheelite T.	86183	17	1	58	<40			
70	75	86184	25		20	30	25	T	10	Grnst 45% SS 10% GA 40% Grnst 3% Fe ₃ O ₄ 1% CaCO ₃ 1% Py T.	86184	34	1.2	59				
75	80	86185	25		25	50		T	6	Grnst 50% SS 40% GA 40% Py 1% Fe ₃ O ₄ 1% CaCO ₃ 2%	86185	19	1	47				
80	85	86186	25		50	25		T	8.5	Grnst 75% SS 15% GA 8% CaCO ₃ 1% MnO 1%	86186	48	1	52				
85	90	86187	50		50			T	5	Grnst 80% SS 10% CaCO ₃ 2% Py 1% MnO 1% GA 6%	86187	19	1	40				
90	95	86188	50		50			T	8	Grnst 35% GA 45% SS 10% CaCO ₃ 3% G.S. 2% Grnst 5% Py T.	86188	15	1	67				
95	100	86189	25	25		25	25	T	9	GA 65% Grnst 25% SS 5% Grnst 2% Fe ₃ O ₄ 1% CaCO ₃ 1% Py 1%	86189	22	1	59				
100	105	86190	25		25	25	25	T	8	GA 55% Grnst 20% SS 15% G.S. 4% Py 1% Fe ₃ O ₄ 2% CaCO ₃ 3% Fe ₂ -xS T.	86190	15	1	49				
105	110	86191	25	25		25	25	T	8	GA 50% Grnst 20% SS 25% Py 1% Fe ₃ O ₄ 2% CaCO ₃ 2% Fe ₂ -xS T.	86191	21	1	57				
110	115	86192	25	25		25	25	T	10	GA 75% Grnst 15% SS 20% Fe ₃ O ₄ 1% Fe ₂ -xS 1% Py 3%	86192	28	1	65				

UNITED KENO HILL MINES LTD. # 189

OVERBURDEN DRILL HOLE LOG

Location _____ Latitude _____ Departure _____ Hole No. 10332
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 3 Of 4.
 Casing Depth _____ Overburden Depth _____ Length of Hole _____ Dip _____

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86193	20		20	40	30	T	8.	Gr 50% SS 50% Qtz 25% py 3% CaCO ₃ 1% Fe ₃ O ₄ 1% Grnst T	86193	16	.1	69			
120	125	86194	20		20	40	20	T	8.	Gr 65% SS 15% GQ 15% py 3% GS 2% Fe ₃ O ₄ 1% CaCO ₃ T	86194	31	.1	52			
125	130	86195	25	25	10	25	15	T	6	GQ 50% SS 25% Gr 25% GS 5% py 3% MnO ₂ 2% ZnS T. CaCO ₃ T.	86195	13	.1	85			
130	135	86196	25	25	10	25	15	T	7.	Gr 40% GQ 20% SS 20% SS 15% py 4% Fe ₃ O ₄ 1% CaCO ₃ T.	86196	17	.1	57			
135	140	86197	25	25	15	25	10	T	9.	Gr 60% SS 15% GS 5% GQ 20% Fe ₃ O ₄ T. Lim T.	86197	16	.1	32			
140	145	86198	25	25	15	25	10	T	8.	Gr 35% SS 10% GQ 20% Lim 1% GS 2% MnO ₂ 1% py 1%	86198	14	.1	70			
145	150	86199	25	25	15	25	10	T	10	Gr 65% SS 20% GQ 13% py 2% Lim T.	86199	10	.1	35			
150	155	86200	25	25	15	25	10	T	7.	GQ 55% Gr 30% SS 11% py 2% MnO ₂ 1% Fe ₃ O ₄ 1% Lim T.	86200	9	.1	31			
155	160	86201	25	25		25	25	T	7.3	GQ 60% Gr 10% SS 10% py 5% Fe ₃ O ₄ 2% Lim 2% GS 10% MnO ₂ 1%	86201	16	.1	61			
160	165	86202	25	10	15		50	T	8	Gr 60% GS 10% GQ 15% py 10% SS 5%	86202	8	.1	37			
165	170	86203	25	25		25	25	T	5.	GQ 65% Gr 20% py 5% GS 5% SS 5%	86203	10	.1	62			

109

10332

Page No. 4 Of 4 .[illegible]

091049

UNITED KENO HILL MINES LTD.

#16

OVERBURDEN DRILL HOLE LOG

Location Snow DRIET Latitude 68 308.49 Departure 163 308.49 Hole No. 10333 ✓
 Date Drilled Oct/81, 14th Elevation 2948.87 Bearing 320° Page No. 1 Of 4
 Casing Depth 14' Overburden Depth 15'-30' Length of Hole 180' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)				Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams					Pb. (ppm)	Ag. (ppm)	Zn (ppm)	WO ₃ (ppm)	Assay (oz/ton)	Pb. (%)	Zn (%)
0	10	86206	25	25		25	25	T	8	QT220 PY10 C.Q.10 FE304.5 MN.5 CS.10 GRNST15 LIM10 C.S.5 SS.5 FE203.5	86206	23	1	73						
10	15	86207	25	25		25	25	T	8.5	QT220 PY10 C.Q.10 FE304.5 MN.5 CS.10 GRNST15 LIM10 C.S.5 SS.5 FE203.5	86207	21	1	91						
15	20	86208	25	50		25		T	6	QT230 PY5 C.Q.15 FE304.5 MN.5 SS.5 FE203.5 GRNST10 C.S.10 ZNS.5	86208	11	1	44						
20	25	86209	25	25		25	25	T	5	QT230 GRNST10 PY10 SS.5 C.Q.10 C.S.10 FE304.5 MN.5 FE203.5 C.S.10	86209	24	1	55						
25	30	86210	25	25		25	25	T	10	QT220 C.Q.15 C.S.10 PY10 C.S.10 MN.5 FE304.5 FE203.5 ZNS.5 LIM10 SS.5 C.S.5	86210	55	1	82						
30	35	86211	25	25		25	25	T	4.5	QT230 PY10 C.S.10 C.S.10 FE304.5 ZNS.5 GRNST10 LIM10 SS.5 MN.5 MN.5	86211	19	1	88						
35	40	86212	25	25		25	25	T	8	C.Q.15 QT230 SS.5 MN.5 LIM10 GRNST10 FE304.5 C.S.10 PY10 FE203.5	86212	23	1	100						
40	45	86213	25	25		25	25	T	6.5	GRNST30 QT230 PY10 LIM10 SS.5 C.S.10	86213	28	1	93						
45	50	86214	25	25		25	25	T	10	QT230 LIM10 FE304.10 GRNST10 SS.5 ZNS.5 C.S.10 C.S.10 C.S.10 C.S.5	86214	21	1	62						
50	55	86215	25			50	25	T	8	QT230 GRNST10 LIM10 PY10 SS.5 C.S.10 FE304.5 C.S.10 C.S.10 MN.5	86215	23	1	61						
55	60	86216	25			50	25	T	7	GRNST20 QT230 LIM10 PY10 SS.5 MN.5 FE304.10 C.S.10 C.Q.5	86216	14	1	77	<40					

C.A.W. 3.1

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Driest Latitude _____ Departure _____ Hole No. 10333
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 Of 4
 Casing Depth 14' Overburden Depth 15-30' Length of Hole 180' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	W03 (ppm)	Assay (oz/ton)	Pb. (%)	Zn (%)
60	65	86217	25			50	25	T	45	QTZ 30 SS.10 GRNST 10 G.S.10 G.Q.10 LIM 5 CaWO4.2.P FE304.5 MN.5 PY10 CAL23.5	86217	11	.1	72	<40			
65	70	86218	50			50		T	8	GRNST 10 QTZ 30 PY10 FE304.10 CAL23.5 LIM 10 CaWO4 3.P FE304.5 G.Q.10 G.S.10	86218	19	.1	75	<40			
70	75	86219	25			50	25	T	7	MN.5 GRNST 15 SS.5 QTZ 30 PY10 LIM 10 CaWO4.2.P G.S.10 G.Q.10	86219	16	.1	84	<40			
75	80	86220	25	25		25	25	T	10.5	QTZ 20 G.Q.20 ZNS 3 PY10 GRNST 20 SS.10 G.S.10 LIM 5	86220	15	.1	156				
80	85	86221	25	25		25	25	T	7	ZNS 5 FE45.10 PY10 GRNST 20 LIM 10 G.Q.20 MN.5 SS.10 FE203.5 FE1-XS.5	86221	15	.1	129				
85	90	86222	25	25		25	25	T	8	MN.5 G.S.10 PY10 QTZ 60 FE45.10 CAL23.5	86222	7	.1	60				
90	95	86223	25	25		25	25	T	8	QTZ 40 G.Q.20 PY10 FE45.10 G.Q.5 CAL23.5 GRNST 10	86223	10	.1	52				
95	100	86224	25	25		25	25	T	10	SS.20 QTZ 30 G.Q.10 PY10 GRNST 15 CAL23.10 FE203.5	86224	12	.1	41				
100	105	86225	25	25		25	25	T	8	FE304.5 SS.15 QTZ 20 CAL23.5 GRNST 10 MN.5 G.Q.10 FE45.10 LIM 10 G.S.5 PY10	86225	16	.1	60				
105	110	86226	25	50		25		T	10	QTZ 30 SS.10 G.Q.10 FE45.10 FE1-XS.10 LIM 10 FE203.5 GRNST 3 CAL23.5 G.S.5	86226	15	.1	55				
110	115	86227	50	25	25			T	7	QTZ 30 FE1-XS.10 PY10 G.Q.15 FE45.10 GRNST 10 SS.10 CAL23.5	86227	13	.1	42	.012			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow DRIET Latitude _____ Departure _____ Hole No. 10333
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 3 Of 4
 Casing Depth 14' Overburden Depth 15'-30' Length of Hole 180' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams	Pb. (ppm)		Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)	
115	120	86228	25	25		25	25	T	5	QTZ 30 GRNST 10 SS 10 AU 5 LIM 10 PY 20 FE, XS 10 GQ 5	86228	9	1	53	.025		
120	125	86229	25	25		25	25	T	8	QTZ 30 GQ 15 GRNST 15 SS 10 PY 15 FE, XS 10 CaCO3 5	86229	11	1	67	.010		
125	130	86230	25	25		25	25	T	8	GQ 15 QTZ 30 SS 10 GRNST 15 PY 15 FE, XS 10 CaCO3 5	86230	15	1	43			
130	135	86231	25	50		25		T	10	FE, XS 10 PY 10 SS 10 CaCO3 10 QTZ 30 GRNST 10 GQ 15 LIM 5	86231	12	12	50			
135	140	86232	50	25	25			T	8	QTZ 30 PY 10 SS 10 FE, XS 10 GQ 15 MNS CaCO3 10 GSS LIM 5	86232	9	12	35			
140	145	86233	25	50	25			T	10	QTZ 30 SS 20 GQ 20 FE, XS 10 CaCO3 10 PY 10	86233	10	18	66			
145	150	86234	25	50	25			T	7	SS 20 QTZ 30 GQ 20 FE, XS 10 CaCO3 10 PY 10	86234	(9)	(1.3)	46			
150	155	86235	50	25		25		T	7	QTZ 30 PY 10 SS 10 FE, XS 10 AU 5 GQ 10 CaCO3 10 GRNST 10 GSS FE ASS 10 FE 20 5	86235	2	9	49			
155	160	86236	25	25		25	25	T	5	QTZ 40 GQ 20 PY 20 CaCO3 10 SS 10	86236	9	5	62			
160	165	86237	50			25	25	T	10	QTZ 30 CaCO3 10 PY 10 GQ 10 SS 10 GRNST 10 FE, XS 10 LIM 5 FE ASS 5	86237	10	11	64			
165	170	86238	50			25	25	T	5	QTZ 30 FE, XS 10 PY 15 CaCO3 10 GQ 15 SS 15 FE ASS 5	86238	15	11	68			

OVERBURDEN DRILL HOLE LOG

Location Snow DRIFT Latitude _____ Departure _____ Hole No. 10333
Date Drilled _____ Elevation _____ Bearing _____ Page No. 4 Of 4
Casing Depth 14' Overburden Depth 15-30' Length of Hole 180' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

091049

UNITED KENO HILL MINES LTD.

73

OVERBURDEN DRILL HOLE LOG

Location Snow Creek Latitude 68 094.93 Departure 163422.73 Hole No. 10334 ✓
 Date Drilled Oct 18/81 14th Elevation 2953.97 Bearing 320° Page No. 1 Of 1
 Casing Depth 40 Overburden Depth ? Length of Hole 55' Dip 59°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	WO ₃ (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86241	25	25		25	25	T	6	QTZ 30 G.S. 15 PYR 10 GRNST 15 G.Q. 10 LIM 5 SS. 5 ZNS 5 CALCO 3.5 FE 304.5	86241	42	.6	95				
10	15	86242	25	25		25	25	T	6	QTZ 30 G.S. 15 PYR 10 GRNST 20 G.Q. 10 LIM 5 SS. 5 FE 304.5 CALCO 3.5 Cd 5.5	86242	30	.6	90				
15	20	86243	25	25		25	25	T	9	GRNST 20 G.P.S. 5 G.S. 10 QTZ 20 G.Q. 15 PYR 10 LIM 5 FE 304.5 MN 5	86243	25	.3	58				
20	25	86244	25	25		25	25	T	5	QTZ 30 G.Q. 10 SS. 5 G.S. 10 PYR 10 G.S. 15 FE 304.5 LIM 5 MN 5 GRNST 5	86244	25	.5	72				
25	30	86245	25	25		25	25	T	7	GRNST 15 G.S. 10 PYR 10 QTZ 30 G.Q. 15 FE 304.5 FE 304.10 MN 5	86245	21	14	51				
30	35	86246	25	25		25	25	T	6.5	GRNST 15 PYR 10 FE 304.5 QTZ 30 G.Q. 15 MN 5 SS. 5 CALCO 3.5 FE 203.5 MN 2.5	86246	42	2.1	75				
35	40	86247	25	25		25	25	T	7	QTZ 30 GRNST 10 MN 10 G.Q. 30 G.S. 10 SS. 5 PYR 5	86247	34	.9	82				
40	45	86248	25	25		25	25	T	10	PBS 10 ZNS 10 G.P.S. 5 GRNST 15 QTZ 30 PYR 10 G.Q. 10 G.S. 5 MN 5	86248	38	1.0	87				
45	50	86249	25	25		25	25	T	8.5	GRNST 15 PYR 10 G.S. 10 QTZ 20 MN 5 SS. 5 LIM 5 CALCO 3.5 G.P.S. 5 FE 304.5 MN 2.5 Cd 5.5 FE 203.5	86249	28	.6	115				
50	55	86250	25	25		25	25	T	7	QTZ 30 PYR 10 GRNST 15 MN 5 G.S. 5 CALCO 3.5 G.Q. 5 FE 304.5 MN 2.5 SS. 10 ZNS 5	86250	47	.9	103				

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snowdrift Latitude 67 715.20 Departure 163 960.46 Hole No. 10335 ✓
 Date Drilled Oct/81, 14th Elevation 2925.82 Bearing 320° Page No. 1 Of 4
 Casing Depth 10 Overburden Depth 20 Length of Hole 180' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	W O ₃ (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86251	25	25		25	25	T	8	GQ 60% Grt 15% GS 8% Grnst 5% MnO ₂ 5% SS 5% Fe ₃ O ₄ T Fe ₂ O ₃ T Py T Lim 2% CaCO ₃ T	86251	27	8	78				
10	15	86252	25	25		25	25	T	7.5	GQ 80% Grt 10% GS 5% Lim 3% Fe ₂ O ₃ T SS 1% CaCO ₃ T MnO ₂ 1%	86252	25	14	82				
15	20	86253	25	25		25	25	T	8	GQ 60% Grnst 10% Grt 15% GS 5% MnO ₂ 5% Py T Lim T	86253	27	14	70				
20	25	86254	25	25		25	25	T	7	Grt 75% Grnst 5% GQ 15% Fe ₃ O ₄ T SS 2% GS 2% CaCO ₃ 1%	86254	29	16	78				
25	30	86255	25			25	50	T	6	Grt 80% SS 4% Py 1% GQ 5% MnO ₂ 1% Grnst 4% CaCO ₃ 2% Lim 3% CaCO ₃ (Scheelite T.)	86255	18	12	47	<40			
30	35	86256	25			25	50	T	4	Grt 90% SS 2% CaCO ₃ 3% Py 2% Lim 1% GQ 2%	86256	17	1	39				
35	40	86257	50				50	T	5	Grt 85% Py 4% GS 1% GQ 5% SS 5% Fe ₃ O ₄ T	86257	49	2	43				
40	45	86258	50		25		25	T	9	Grt 90% SS 2% GQ 2% MnO ₂ T Py 1% GS 2% Lim 1% CaCO ₃ 2%	86258	37	16	39				
45	50	86259	50				50	T	8	Grt 55% Py 5% GQ 20% Grnst 10% Fe-S 1% SS 2% MnO ₂ 6% Lim 1% CaCO ₃ T	86259	(48)	(19)	64				
50	55	86260	50				50	T	7.5	Grt 85% GQ 10% Py 3% MnO ₂ 2% CaCO ₃ T Fe-As-S	86260	25	2	38				
55	60	86261	50				50	T	8	Grt 65% Py 6% CaCO ₃ 1% Fe-As-S 4% GQ 24%	86261	21	1	46				

UNITED KENO HILL MINES LTD. OVERBURDEN DRILL HOLE LOG

Location _____ Latitude _____ Departure _____ Hole No. 10335
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 Of 4
 Casing Depth _____ Overburden Depth _____ Length of Hole _____ Dip _____

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	WO ₃ (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86262	50			25	25	T	9	GA 45% GTZ 40% PY 5% FeAsS 5% Fe SS 3% Calc 3%	86262	22	12	69				
65	70	86263	50				50	T	7	GA 55% GTZ 25% PY 10% FeAsS 5% Fe SS 5% Calc 5%	86263	19	14	63				
70	75	86264	50				50	T	10	NO SAMPLE		NO SAMPLE						
75	80	86265	50				50	T	12.5	GA 50% GTZ 30% PY 15% FeAsS 5% MnO ₂ 2% Calc 3%	86265	18	1.9	89				
80	85	86266	50				50	T	8	GA 55% GTZ 30% PY 10% FeAsS 3% Calc 2%	86266	19	1.5	70				
85	90	86267	50				50	T	7	GA 40% GTZ 35% PY 15% FeAsS 5% SS 2% Calc 3%	86267	(41)	(1.4)	79				
90	95	86268	50				50	T	9	GA 60% GTZ 20% PY 10% SS 2% SS 3% FeAsS T Calc 5% Lim T. (Sphalerite) CaWO ₄	86268	29	1.5	70	<40			
95	100	86269	50				50	T	8	GA 50% GTZ 15% PY 20% SS 5% MnO ₂ 2% Lim 1% Calc 2% SS 3% CaWO ₄ (Sphalerite approx 30-40 pieces)	86269	28	1.3	65				
100	105	86270	50				50	T	9	GA 45% GTZ 40% PY 5% SS 2% MnO ₂ 1% GS 2% Calc 1% Lim 1% CaWO ₄ (Sphalerite 5-10 pieces)	86270	18	1	48				
105	110	86271	50				50	T	10	GA 60% GTZ 20% PY 8% SS 4% GS 2% Lim 1% Calc T	86271	23	1	66				
110	115	86272	50				50	T	5	GA 55% GTZ 25% PY 15% GS 4% SS 2% Lim 1% FeAsS 3%	86272	15	1.3	87				

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location _____ Latitude _____ Departure _____ Hole No. 10335
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 3 Of 4
 Casing Depth _____ Overburden Depth _____ Length of Hole _____ Dip _____

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86273	50				50	T	5	GA 45% Qtz 24% Py 13% FeAsS + lim + GS + SS CaCO ₃ +	86273	23	1	77			
120	125	86274	25	25		25	25	T	9	GA + Qtz 28% SS 10% Py 6% Lim 1% MnO ₂ 1% GS 2%	86274	20	11	77			
125	130	86275	50				50	T	8	Qtz 33% GA 33% SS 5% CaCO ₃ 5% Py 3% GS 2%	86275	21	14	48			
130	135	86276	50				50	T	3	GA 30% Qtz 45% Py 15% FeAsS 3% CaCO ₃ 3% lim 1% SS 5%	86276	29	6	40			
135	140	86277	50				50	T	7	GA 35% Qtz 55% Py 4% FeAsS 3% CaCO ₃ 2%	86277	22	13	56			
140	145	86278	25	25		25	25	T	7	GA + Qtz 90% GS 3% Py 7% lim 1% SS 1%	86278	17	5	59			
145	150	86279	25	25		25	25	T	8	GA + Qtz 90% FeAsS 3% Py 3% lim 1% SS 4% CaCO ₃ 1%	86279	15	11	60			Au (oz/ton)
150	155	86280	25	25		25	25	T	7	GA 65% Qtz 20% CaCO ₃ 2% Py 9% FeAsS 4%	86280	15	12	71			.012
155	160	86281	50				50	T	9	GA 45% Qtz 35% SS 1% Py 9% lim 1% CaCO ₃ 4% FeAsS 5%	86281	21	5	45			.011
160	165	86282	25	25		25	25	T	8	GA + Qtz 90% Grnst 5% Py 4% SS 4% CaCO ₃ + lim 1%	86282	14	11	85			
165	170	86283	50				50	T	4	GA 75% Qtz 5% Py 3% CaCO ₃ 7% SS 8% FeAsS 2%	86283	15	11	91			

UNITED KENO HILL MINES LTD. OVERBURDEN DRILL HOLE LOG

Location _____ Latitude _____ Departure _____ Hole No. 10-225
Date Drilled _____ Elevation _____ Bearing _____ Page No. 4 Of 4
Casing Depth _____ Overburden Depth _____ Length of Hole _____ Dip _____

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

#96

Location Snowdrift Latitude 67404.41 Departure 164400.24 Hole No. 10336 ✓
 Date Drilled Oct/81 Elevation 2913.23 Bearing 320° Page No. 1 of 3
 Casing Depth 15 Overburden Depth 20' Length of Hole 165' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	WO ₃ (ppm)	Pb. (oz/ton)	Pb. (%)	Zn (%)
0	10	86286	25	25		25	25	T	7	QTZ 20 GRNST 15 FE213.5 GS.10 FE304.5 FE83.5 CPS.5 MN.5 MA2.5 SS.10 CA.15 RT220 PY10 FEASS.10	86286	23	.1	92				
10	15	86287	25	25		25	25	T	7	GRNST 10 MN.10 GS.10 SS.10 CA.10 CPS.5	86287	20	.4	91		.002		
15	20	86288	40		10	40	10	T	3	QTZ 35 PY10 CAL0310 MN.5 FEASS.10 CPS.5 GRNST 10 LIM.5 FE304.5 SAHEE (60%) FE203.5	86288	150	4.1	62		.010		
20	25	86289	30		10	60		T	2.5	LIM.10 GRNST 15 PY10 FEASS.10 QTZ 20 CA.10 SS.10 CAL03.5 SCHEE LIKE 15-20 PIECES FEI-XS.10 GRNST 15	86289	28	.3	58	440	.013		
25	30	86290	45		10	45		T	2	FEASS.10 QTZ 20 PY10 CAL0310 SS.15 CA.10	86290	22	.1	48				
30	35	86291	45		10	45		T	4	QTZ 50 GRNST 10 SS.15 FEI-XS.10 FEASS.10 CAL03.5	86291	14	.9	54				
35	40	86292	40		10	40	10	T	5	QTZ 40 GRNST 15 PY10 FEI-XS.10 SS.10 CAL0310 FEASS.10	86292	8	.3	48				
40	45	86293	25		25	25	25	T	7	FEASS.30 QTZ 30 CAL0310 SS.10 FEI-XS.5 GRNST 15	86293	14	.6	64		.010		
45	50	86294	25		25	25	25	T	10	GRNST 30 QTZ 30 FEASS.10 SS.10 PY10 FEI-XS.10	86294	11	.3	58				
50	55	86295	25		25	25	25	T	7	GRNST 30 QTZ 30 FEASS.10 SS.10 PY10 FEI-XS.10	86295	6	.1	35				
55	60	86296	10		10	70	10	T	2	CAL0310 GRNST 30 QTZ 30 SS.10 FEASS.10 PY10 FEI-XS.10	86296	7	.1	37				

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location _____ Latitude _____ Departure _____ Hole No. 10326
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 of 3
 Casing Depth _____ Overburden Depth _____ Length of Hole _____ Dip _____

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results	
From	To		G.Q.	G.S.	S.S.	Gmst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	4003 (ppm)	Pb. (oz/ton)	Zn (%)
60	65	86297	25		25	25	25	T	3.5	FEASS.10 RT2.30 LIM10 Gmst.20 SS.10 PY10 CaCO3 10 (CaWO4 35)	86297	8	.4	45	<40	.013	
65	70	86298	25		25	50		T	4	SS.15 FEASS.10 SS.10 RT2.50 Gmst.15 PY.5 (CaWO4 T)	86298	1	.3	36	<40	.015	
70	75	86299	25		25	50		T	4	GPS.15 Gmst.30 PY10 RT2.30 FEASS.10 SS10 CaCO3 5 (CaWO4 25)	86299	11	.5	70		.006	
75	80	86300	25		25	50		T	3.5	FEASS.40 RT2.30 Gmst.10 SS.10 PY.5 FEI-XS.5 (CaWO4.25)	86300	12	.6	57		.010	
80	85	86301			50	50		T	1.5	FEASS.30 RT2.30 Gmst.10 SS.10 PY.5 FEI-XS.5 (CaWO4-T)	86301	10	.2	77	<40	.008	
85	90	86302	25		25	50		T	3	FEASS.40 RT2.30 Gmst.10 SS.10 PY.5 FEI-XS.5 (CaWO4 10)	86302	(160)	(1.0)	62	<40	.006	
90	95	86303	25		25	50		T	5.5	GS.10 Gmst.15 RT2.30 SS.10 FEASS.20 CaCO3 15 (CaWO4 2)	86303	(63)	(1.6)	68	<40	.007	
95	100	86304	15		40	40	5	T	1.5	RT2.30 Gmst.30 FEASS.25 SS.15	86304	25	.7	72	<40	.006	
100	105	86305	25		25	50		T	4	RT2.30 FEASS.30 Gmst.20 SS.10 CaCO3 10 (CaWO4.T)	86305	7	.2	67	<40	.007	
105	110	86306	45		10	45		T	4	SS.30 RT2.30 Gmst.20 FEASS.10 CaCO3 5 FE-XS.5 (CaWO4 T)	86306	16	.6	132	<40	.005	
110	115	86307	50		10	40		T	1.5	Gmst.30 RT2.30 CaCO3 10 FEASS.15 SS10 FE-XS.5 (CaWO4 T)	86307	12	.3	68	<40	.009	

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location _____ Latitude _____ Departure _____ Hole No. 10396
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 3 of 3
 Casing Depth _____ Overburden Depth _____ Length of Hole _____ Dip _____

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	MoS ₃	Ag (oz/ton)	Pb. (%)	Zn (%)
115	120	86308	30		30	30	10	T	1a	Grnst 20 SS. 30 Qtz. 30 FeAsS. 10 CaCO ₃ 5 (CaWO ₄ -T)	86308	18	.7	51	<40	.006		
120	125	86309	25		50	25		T	3s	Qtz 30 Py 10 SS. 30 CaCO ₃ 10 FeAsS. 10 Grnst 10 (CaWO ₄ -T)	86309	1	11	38	<40	.008		
125	130	86310	25		25	25	25	T	3	Qtz 30 SS. 30 CaCO ₃ 10 FeAsS. 10 Grnst 10 Fe-xS 10	86310	10	11	47				
130	135	86311	25		25	50		T	2	Qtz 50 G.S. 5 SS. 25 CaCO ₃ 10 FeAsS. 10	86311	1	11	47				
135	140	86312	25		25	25	25	T	4s	Qtz 40 Grnst 20 SS. 20 CaCO ₃ 10 FeAsS. 5 Py 5	86312	6	11	69				
140	145	86313	25		25	50		T	5s	Qtz 40 Grnst 20 SS. 20 CaCO ₃ 10 FeAsS. 5 Py 5	86313	1	11	50				
145	150	86314	25		25	25	25	T	3	Qtz 40 Grnst 20 FeAsS. 20 Py 10 SS. 10	86314	2	11	44				
150	155	86315			50	50		T	6	Qtz 60 FeAsS. 25 SS. 10 Py. 5 (CaWO ₄ -T)	86315	18	11	45	<40	.014		
155	160	86316			50	50		T	5	Qtz 40 FeAsS. 40 Qtz. 10 SS. 10 (CaWO ₄ -T)	86316	6	.3	67	<40	.012		
160	165	86317	25		25	25	25	T	2s	FeAsS. 10 SS. 10 Grnst. 10 Lim. 10 Qtz 30 MnS Py 5 Fe-xS. 5 G.S. 5 CaCO ₃ 5 (CaWO ₄ -2)	86317	36	.8	75	<40	.012		

OVERBURDEN DRILL HOLE LOG

Location Snowdrift Latitude 67069.69 Departure 164867.34 Hole No. 10337 ✓
 Date Drilled Oct 18, 15th Elevation 2892.67 Bearing 320° Page No. 1 Of 3
 Casing Depth 10' Overburden Depth 10 Length of Hole 170' Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim.	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86318	25			50	25	T	3	QTZ 20 GRNST 20 GS 15 GR 15 20% 5 Lim 5 PY 5 S.S. 5 MN 5 FE 3045	86318	20	12	59			
10	15	86319	45		5	45	5	T	3.5	GRNST 20 ZNS 10 PY 10 QTZ 20 GR 15 Lim 10 FE 3045 MN 5	86319	16	11	37			
15	20	86320	10		5	75	10	T	2.5	FE 5.5 GRNST 15 Lim 10 ZNS 5 QTZ 30 PY 10 GS 10 GR 10 FE 3045	86320	1	11	38			
20	25	86321	45		10	45		T		QTZ 30 GRNST 15 FE 5.10 GS 10 GR 15 PY 10 MN 5 MA 2.5	86321	1	11	36			
25	30	86322	25		25	25	25	T	2	QTZ 20 PY 20 FE 5.10 MN 5 Lim 10 GS 10 GR 10 CaCO3 5 S.S. FE 3045	86322	1	11	55			
30	35	86323	25		25	25	25	T	2.5	FE 1-ES 15 QTZ 20 PY 10 FE 5.5 GS 10 GRNST 15 MN 5 FE 30410 S.S. 10	86323	1	11	67			
35	40	86324	25		25	25	25	T	2.5	FE 1-ES 10 QTZ 20 PY 10 S.S. 10 GRNST 20 FE 5.5 CaCO3 5 GR 20	86324	1	11	64			
40	45	86325	25		25	25	25	T	5	FE 1-XS 10 GRNST 15 FE 5.10 QTZ 20 PY 15 S.S. 15 CaCO3 5 Lim. 5	86325	1	11	58			
45	50	86326	10		30	30	30	T	6	QTZ 40 GR 10 FE 5.10 FE 1-XS 10 GS 5 GRNST 20	86326	3	1	52			
50	55	86327	30		10	30	30	T	5	QTZ 40 PY 10 S.S. 10 FE 1-S 10 FE 5.10 GRNST 10 GS 5	86327	12	11	62			
55	60	86328	25		25	25	25	T	5	QTZ 30 S.S. 30 PY 10 FE 1-XS 15 FE 5.10 GRNST 5	86328	1	1	37			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location _____ Latitude _____ Departure _____ Hole No. 10337
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 of 3
 Casing Depth _____ Overburden Depth _____ Length of Hole _____ Dip _____

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim.	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	As ₂ (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86329	25		25	25	25	T	6	QTZ 40 SS. 20 PY 5 FE ₁ -XS.10 FESS.5 GRNST 20	86329	1	1	37				
65	70	86330	25		25	25	25	T	5	QTZ 40 SS. 20 PY 5 FE ₁ -XS.15 FESS.10 GRNST 15	86330	1	1	67				
70	75	86331	25		25	25	25	T	8	PY 40 QTZ 40 FESS.5 FE ₁ -XS.10 GRNST 5	86331	1	(2.3)	44				
75	80	86332	25		25	25	25	T	8	PY 20 QTZ 40 FESS.10 FE ₁ -XS.10 SS.5 GRNST 15	86332	6	1	68				
80	85	86333	25		25	25	25	T	4	QTZ 40 SS. 20 PY 15 FE ₁ -XS.10 GRNST 10 FESS.5	86333	14	.4	81				
85	90	86334	25		25	25	25	T	4	CaCO ₃ 8 QTZ 40 SS. 5 PY 15 GRNST 10 FESS.10 FE ₁ -XS.15	86334	1	1	78				
90	95	86335	30	10	10	40	30	T	5	SS.10 QTZ 40 PY 20 FE ₁ -XS.10 FESS.10 GRNST 10	86335	16	1	58				
95	100	86336	20	5	5	20	50	T	6	CaCO ₃ 10 PY 15 QTZ 30 SS.10 GRNST 15 20% FESS.10 FE ₁ -XS.10 Scheelite	86336	4	2.1	61	604	.009		
100	105	86337	25		20	50	5	T	4	QTZ 30 PY 20 CaCO ₃ 3 SS.10 GRNST 15 20% FESS.10 FE ₁ -XS.5 Scheelite	86337	16	1	59	126	0.011		
105	110	86338	25			25	50	T	3	QTZ 30 GRNST 30 CaCO ₃ 10 FESS.5 PY 10 FE ₁ -XS.10 Scheelite to Canoy	86338	16	2	56	440	.016		
110	115	86339	30		10	30	30	T	3	QTZ 30 GRNST 15 PY 15 SS.10 FESS.10 FE ₁ -XS.10 G.S. 5 Scheelite to Canoy	86339	7	1	57	440	.011		

UNITED KENO HILL MINES LTD. OVERBURDEN DRILL HOLE LOG

Location _____ Latitude _____ Departure _____ Hole No. 10337
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 3 of 3
 Casing Depth _____ Overburden Depth _____ Length of Hole _____ Dip _____

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Co ₂ (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86340	30		10	50	10	T	5.5	QTZ 30 Lim 15 Py 10 Grnst 15 Fe 55.15 G.S. 5 Fe - x5.10 S.S. 5 CaWO ₄ Scheelite	86340	8	.1	60	<40	.013		
120	125	86341	T		35		55	10	2.5	QTZ 20 Fe 55.20 Lim 10 Fe - x5.10 Py 10 Grnst 10 S.S. 10 Ca 10 CaWO ₄ Scheelite	86341	19	.1	77	<40	.014		
125	130	86342	30		50		15	5	4	QTZ 30 Py 10 Grnst 10 Lim 10 Fe - x5.15 S.S. 10 Fe 55.10 Lim 5	86342	4	.1	53				
130	135	86343	25		65		10		7	QTZ 30 Fe 55.20 Lim 5 Grnst 10 S.S. 10 Py 10 Fe - x5.10 Ca 5	86343	1	.1	58				
135	140	86344	60	T	15		25		5	QTZ 30 G.Q. 15 Py 10 Grnst 10 S.S. 15 Fe 55.10 Fe - x5.5	86344	1	.1	63				
140	145	86345	40	30	10		20		3	QTZ 30 G.Q. 15 Py 10 Grnst 15 S.S. 15 Lim 5 Mn. 5 Fe 30.45	86345	1	.1	57				
145	150	86346	55	10	5		30	T	4	QTZ 30 Grnst 15 S.S. 15 Py 10 Fe 55.10 Fe - x5.10 Lim 5 Mn. 5 Scheelite & CaWO ₄	86346	1	.1	61	<40	.011		
150	155	86347	40	30	T		30		2.5	S.S. 15 QTZ 20 G.Q. 15 Py 10 Fe 55.10 Lim 10 Fe - x5.10 Grnst 10 Scheelite & CaWO ₄	86347	1	.1	66	<40	.010		
155	160	86348	40	10	25		15	10	10	QTZ 30 Grnst 15 Py 10 Fe 55.10 Fe - x5.10 Lim 10 G.Q. 15 S.S. 5 CaWO ₄ Scheelite	86348	6	.3	73	<40	.011		
160	165	86349	55	5	30		10		8.5	QTZ 30 Lim 10 S.S. 10 Grnst 15 Py 10 Fe 55.10 Fe - x5.5 G.Q. 15 Scheelite & CaWO ₄	86349	13	.1	100	<40	.012		
165	170	86350	80	5	10		5	T	3.5	QTZ 30 Grnst 20 Lim 10 Py 20 Lim 10 Fe 55.10 G.S. 5 Scheelite Fe - x5.5	86350	5	.2	84	<40	.006		

09.10.49

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow DRIET Latitude 66 768.64 Departure 115 291.12 Hole No. 10338
 Date Drilled Oct/81, 15th Elevation 2864.24 Bearing 320° Page No. 1 Of 3
 Casing Depth 10' Overburden Depth 10-15' Length of Hole 155' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86351	35		40	T	10	15	4.8	MIN. 15 QTZ 30 GS 10 LIM 20 GRNST 15 PY 10 SS 5	86351	6	1	101			
10	15	86352	35		55			10	7.3	ZNS 15 QTZ 20 SS 10 GRNST 15 GQ 10 LIM 15 PY 10 MIN 5	86352	1	1	87			
15	20	86353	50		35			15	5.3	QTZ 30 PY 10 MIN 5 LIM 15 GRNST 10 FE 30 45 ZNS 10 SS 5 GQ 10	86353	1	1	74			
20	25	86354	55		25		10	10	8.9	QTZ 40 LIM 10 MIN 5 GRNST 10 PY 10 ZNS 5 FE 20 35 SS 5 GQ 10	86354	3	1	71			
25	30	86355	60		15		10	15	7.3	QTZ 30 PY 10 MIN 5 FE 20 35 SS 5 GQ 10 GRNST 10 FE 35 5 GQ 30	86355	1	1	55			
30	35	86356	85	15	T				8.6	QTZ 30 GQ 30 PY 10 FE 1-XS 5 FE 35 5 SS 10 ZNS 5 GS 5	86356	1	1	41			
35	40	86357	40	60					5.4	QTZ 30 GQ 30 PY 5 ZNS 5 SS 5 FE 1-XS 10 FE 35 5 LIM 5 GS 5	86357	1	1	59			
40	45	86358	30	70					2.4	FE 1-XS 10 GQ 30 QTZ 5 LIM 10 PY 10 GRNST 10	86358	1	1	66			
45	50	86359	60	40					4.2	QTZ 40 GQ 30 MIN 5 GRNST 5 PY 5 SS 5 FE 1-XS 5 GRNST 5	86359	1	1	51			
50	55	86360	75	25					5.4	QTZ 45 GQ 30 LIM 5 PY 10 FE 1-XS 10	86360	1	1	50			
55	60	86361	50	50				T	5.2	QTZ 60 GQ 25 PY 10 GQ 35	86361	1	1	40			

UNITED KENO HILL MINES LTD. #1 OVERBURDEN DRILL HOLE LOG

Location Snow Drift Latitude _____ Departure _____ Hole No. 10338
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 Of 3
 Casing Depth 10 Overburden Depth 10-15 Length of Hole 155 Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86362	15	85				T	5.6	QTZ 40 PY 10 GR 30 CALC 310 FEI-XS 5 SS 5	86362	1	.1	46			
65	70	86363	5	95				T	5.7	QTZ 40 PY 10 GR 30 GRNST 10 FEI-XS 5 SS 5	86363	1	.1	49			
70	75	86364		100				T	4.9	QTZ 40 GR 30 LIM 10 PY 5 FEI-XS 5 FEA 55.5 GS 5	86364	1	.1	53			
75	80	86365	25		25	40	10	T	1.9	QTZ 40 PY 20 FEA 55.5 GR 10 FEI-XS 5	86365	1	.1	66			
80	85	86366	20		20	50	10	T	5.0	QTZ 40 GR 40 PY 10 FEA 55.5 FEI-XS 5	86366	2	.5	36			
85	90	86367	30		10	30	30	T	3.2	QTZ 40 GR 30 PY 10 FEA 55.5 FEI-XS 5 GRNST 10	86367	3	.7	53			
90	95	86368	30		5	35	30	T	1.4	CALC 310 QTZ 40 GR 10 SS 10 FEI-XS 10 PY 10 LIM 5 LIM 5	86368	4	.2	69			
95	100	86369	40		10	40	10	T	6.4	SS 20 GR 30 QTZ 40 CALC 35 PY 5	86369	4	.1	70			
100	105	86370	40		10	40	10	T	6.9	GR 30 SS 15 QTZ 30 PY 10 GRNST 5 CALC 35 FEI-XS 5	86370	18	5	61			
105	110	86371	25		25	25	25	T	3.1	QTZ 40 GR 30 PY 10 CALC 35 FEI-XS 5 FEA 55.5	86371	11	.2	41			
110	115	86372	25		25	25	25	T	2.9	QTZ 60 GR 20 PY 10 FEA 55.5 FEI-XS 5	86372	1	.8	81			

#G/

Hole No. 14338

Page No. 3 Of 3Dip 60°

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)	Sample No.	Geochemical Results			Assay Results			
From	To		G.Q.	G.S.	S.S.	Gmst.	Qtz.	Lim			grams	Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86373	25		25	25	25	T	3.5	RTZ 50 C.Q. 25 PY 10 FEI-XS.5 FEA 55.5 SS.5	86373	1	.9	82			
120	125	86374	25	5	10	50	10	T	2.7	RTZ 50 C.Q. 15 SS.5 PY 10 FEI-XS.5 FEA 55.5 CAC 3.5 SS.5	86374	1	1.5	76			
125	130	86375	30	10	10	30	20	T	7.9	FEI-XS.10 PY 15 RTZ 40 SS.40 C.Q. 10 FEA 55.5 CAC 3.5	86375	(11)	(1.8)	58			
130	135	86376	25		25	50		T	2.6	SS.15 PY 15 RTZ 30 C.Q. 15 LIM 5 FEA 55.10 CAC 3.5 FEI-XS.5	86376	1	1.0	80			
135	140	86377	20		20	50	10	T	2.4	SS 20 RTZ 40 PY 20 C.Q. 10 FEI-XS.5 CAC 3.5	86377	8	1.7	79			
140	145	86378	30		10	30	30	T	3.6	RTZ 30 C.Q. 15 SS.10 CAC 3.5 PY 10 FEI-XS.5 FEA 55.5	86378	1	1.1	80			
145	150	86379	30		10	30	30	T	4.6	RTZ 30 C.Q. 15 SS.10 CAC 3.5 PY 10 FEI-XS.5 FEA 55.5	86379	(21)	(1.6)	78			
150	155	86380	30		10	30	30	T	4.0	LIM 5 RTZ 30 C.Q. 15 SS.15 CAC 3.5 PY 15 FEA 55.5 FEI-XS.5	86380	(12)	(1.5)	80			

UNITED KENO HILL MINES LTD. #1 OVERBURDEN DRILL HOLE LOG

Location Snow Drift Latitude 66 480 Departure 165 740 Hole No. 12339 ✓
 Date Drilled Oct/81, 15th Elevation 2816 Bearing 320° Page No. 1 Of 1
 Casing Depth 42' Overburden Depth ? Length of Hole 50' Dip 55°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)	Sample No.	Geochemical Results			Assay Results			
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim			grams	Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86381				50	50	T	1.6	QTZ 40 MN 5 PY 10 CAL 03.5 MN 02.5 LIM 10 FE 304.5 FE 1-X55 GRNSTIC G.S.	86381	23	1.9	87			
10	15	86382			100			T	1.0	ZNS 5 MN 5 QTZ 30 PY 10 GRNSTIC LIM 10 CAL 10 MN 02.5 FE 304.5	86382	1	1.2	73			
15	20	86383				100		T	1.4	CAL 03.5 PY 10 MN 5 QTZ 20 MN 02.5 SS. 5 GPS. 5 GRNSTIC G.S. FE 304.5 FE 203.5	86383	1	1.5	90			
20	25	86384				95	5	T	1.5	ZNS 5 QTZ 30 PY 10 GRNSTIC MN 5 MN 02.5 FE 304.5 SS. 5 LIM 5 G.S. 5 MN 5	86384	1	1.2	87			
25	30	86385	25			50	25	T	4.3	ZNS 5 QTZ 30 PY 5 MN 02.5 CAL 10 G.S. 10 FE 304.5 MN 5 CAL 03.5 GPS. 5 GRNSTIC	86385	1	1.0	71			
30	35	86386	30			40	30	T	6.6	MN 5 QTZ 20 PY 10 GRNSTIC CAL 10 G.S. 10 FE 304.35 GPS. 5 ZNS 5 FE 203.5 CAL 03.5 SS. 5	86386	(85)	(3.1)	102			
35	40	86387	25			50	25	T	1.9	QTZ 30 PY 5 ZNS 5 FE 304.5 SS. 5 GRNSTIC 20 G.S. MN 5 MN 02.5 GPS. 5 LIM 5 G.S. 5	86387	1	1.5	82			
40	45	86388	45			T	45	10	T	4.7	QTZ 30 ZNS 10 GRNSTIC 10 PY 10 CAL 03.5 CAL 10 G.S. 5 SS. 5 FE 304.5 FE 203.5 MN 5	86388	1	1.2	74		
45	50	86389	35	5		50	10	T	2.7	QTZ 20 ZNS 10 PY 10 GRNSTIC SS. 5 GPS. 5 MN 5 MN 02.5 G.S. 5 CAL 5 LIM 5 FE 304.5 FE 203.5 CAL 03.5	86389	(23)	(2.1)	105			

091049

UNITED KENO HILL MINES LTD. # 302

OVERBURDEN DRILL HOLE LOG

Location Snow D.R.F.T Latitude 66 284.57 Departure 165 976.94 Hole No. 10340 ✓
 Date Drilled Oct/81, 16th Elevation 2815.99 Bearing 320° Page No. 1 Of 2
 Casing Depth 38' Overburden Depth 40' Length of Hole 100' Dip 55°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86390	45			45	10	T	5	QTZ 20 GRNST 10 CS 10 PY 10 ZNS 5 MN 5 CA 10 MNO 10 SS 5 GS 5 FE 304 5 FE 203 5	86390	1	1.2	82			
10	15	86391	45		T	45	10	T	5.5	QTZ 20 GRNST 10 Pbs CS 5 FE 304 5 CA 10 MN 5 MNO 5 FE 304 5 LIM 5 SS 5 ZNS 5 CA 10	86391	1	1.2	100			
15	20	86392	25	25		25	25	T	10	QTZ 20 GRNST 10 PY 10 ZNS 10 GS 5 SS 5 MN 5 FE 304 5 LIM 10 CS 10 CA 10	86392	(93)	(1.7)	90			
20	25	86393	50	T		50	T	T	6	QTZ 20 GRNST 15 ZNS 5 PY 10 GS 5 MN 5 FE 304 5 MNO 5 LIM 10 FE 203 5 CA 10	86393	1	1.3	82			
25	30	86394	15	10		70	5	T	5	QTZ 30 PY 10 SS 10 CA 10 GRNST 10 CA 10 MN 5 MNO 5 FE 304 5 LIM 10	86394	1	1.4	103			
30	35	86395	40	10	T	40	10	T	2	FE 1 XS 5 FE ASS 5 Pbs QTZ 30 GRNST 10 SS 5 LIM 5 CA 10 GS 10 FE 304 5 MN 5 ZNS 5	86395	1	1.0	95			
35	40	86396	35	10	10	35	10	T	3.5	ZNS 5 QTZ 25 GRNST 10 SS 10 PY 10 CA 10 GS 10 CA 10 MN 5 FE 304 5 FE 203 5	86396	1	.5	86			
40	45	86397	20	5	25	25	25	T	4	QTZ 30 SS 30 GRNST 10 PY 10 CA 10 MN 5 FE 304 5 GS 5	86397	1	.9	81			
45	50	86398	10	10	20	30	30	T	10	QTZ 25 PY 10 FE ASS 20 FE 1 XS 10 GRNST 10 CS 5 CA 10 LIM 5 MNO 5	86398	1	.5	51			
50	55	86399	25	50		5	20	T	4.5	CA 30 QTZ 30 PY 15 FE 1 XS 10 FE ASS 10 LIM 5	86399	1	1.2	83			
55	60	86400	90	5			5	T	4.5	QTZ 40 CA 15 LIM 5 SS 20 ZNS 5 PY 15	86400	1	1.3	45			

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG #38 (No Cawoy)

Location Snow DRIFF Latitude 66002.89 Departure 166 381.40 Hole No. 10341 ✓
 Date Drilled Oct/81 16th Elevation 2797.81 Bearing 320° Page No. 1 Of 3
 Casing Depth 10' Overburden Depth 10' 15' Length of Hole 160' Dip 63°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86438	40			50	10	T	7.	QT220 SS3 GRNSTIC LIM10 PY10 GS10 GR10 FE304.5 MN5 FE203.5 MN5 LIM5 ZNS.5 QT230 GRNSTIC	86438	1	.3	79			
10	15	86439	45			50	5	T	7.5	PY10 SS5 GR10 GS10 FE304.5 FE203.5 CAS LIM5	86439	1	.4	97			
15	20	86440	35			35	30	T	5.	QT220 LIM20 GS10 MN5 GRNSTIC ZNS.5 SS5 GR10 FE304.5 FE203.5 CAS	86440	(168)	(1.1)	172			
20	25	86441	25	25		25	25	T	4.5	QT230 LIM20 GS10 SS10 FE203.5 PY10 ZNS10 CAS	86441	35	.1	150			
25	30	86442	25	25		25	25	T	1.	GRNSTIC PY10 QT230 ZNS.5 LIM10 FE304.5 FE1X5.5 CAS FE203.5 GRNSTIC SS5	86442	28	.1	88			
30	35	86443	25	40		25	10	T	2.5	ZNS10 LIM10 CAS QT230 PY10 SS5 FE1-X5.5 MN5 CAS FE203.5 CP5.5 GS.5	86443	20	.1	81			
35	40	86444	20	50		20	10	T	2.	GS120 QT230 ZNS3 CAS3.5 MN.5 SS.5 FE304.5 PY2.5	86444	27	.1	81			
40	45	86445	25	25		25	25	T	3.	GRNSTIC QT230 SS10 GS10 PY10 GR10 CAS3.5 ZNS5 FE203.5	86445	38	.1	63			
45	50	86446	20	50		10	20	T	4.	CQ30 QT230 PY20 SS15 CAS3.5	86446	35	.1	81			
50	55	86447	10	50		15	25	T	5.	QT230 PY25 SS20 CAS3.5 LIM10 CAS	86447	32	.1	86			
55	60	86448	15	50		15	20	T	9.5	PY40 QT220 GS120 LIM10 GR5 SS10	86448	51	.1	93			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

38

Location Snow DRIET Latitude _____ Departure _____ Hole No. 10341
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 Of 3
 Casing Depth 12' Overburden Depth 10-15' Length of Hole 160' Dip 63°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86449	50	10			40	T	7.	GS. 25 PY 30 QT 230 Lim 10 CaCO3 5	86449	31	12	90			
65	70	86450	40	10			50	T	4.	QT 240 GQ 30 PY 25 GS 5 Lim 5	86450	28	1	79			
70	75	86451	45	10			45	T	5.	QT 230 PY 40 GQ 20 Lim 5 GS 5	86451	30	11	64			
75	80	86452	45	45		5	5	T	6.5	QT 240 PY 30 GQ 20 Lim 5 GS 5	86452	19	4	53			
80	85	86453	45	5		5	45	T	5.	GS. 20 QT 230 PY 20 Lim 5 Grnst 10 SS. 10	86453	17	1	91			
85	90	86454	50	50				T	8.	GS. 15 QT 230 PY 30 SS 10 Lim 5 Grnst 5 ZnS 5	86454	9	1	55			
90	95	86455	50	50				T	8.	QT 230 GS. 30 PY 20 Lim 5 CaCO3 10 SS 5	86455	28	1	89			
95	100	86456	10	90				T	10.	GS. 30 QT 230 PY 30 Lim 5 CaCO3 5	86456	19	1	107			
100	105	86457	25	25		25	25	T	3.	PY 30 GQ 30 QT 230 MnS 5 Lim 5	86457	47	1	68			
105	110	86458	40	40			20	T	6.	PY 30 GQ 30 QT 230 MnS 5 GS 5	86458	20	1	95			
110	115	86459	15	50		5	10	T	4.	GQ 30 Grnst 15 QT 230 PY 15 Lim 5 GQ 5	86459	33	1	94			

38

Snow DRIFT

10.

[illegible]

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

#133

Location SNEED DRY ET Latitude 65966.45 Departure 115837.39 Hole No. 10342 ✓
 Date Drilled Oct/81, 16th Elevation 2809.22 Bearing 320° Page No. 1 of 3
 Casing Depth 22' Overburden Depth 25' 30' Length of Hole 150' Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage.		Sample No.	Coarse Material (%) (+14 mesh)					Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams		Pb. (ppm)	Ag. (ppm)	Cu (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86409	40			50	10	T	2.5	GA 80% GS 5% QTZ 10% Py 1% Lim 2% SS 2%	1	.8	75			
10	15	86410	25	5		50	20	T	4	GA 70% QTZ 10% MnO 5% Grnst 10% Py 3% Lim 2% FeAsS T.	1	.7	64			
15	20	86411	15	5		70	10	T	9	GA 55% Grnst 80% QTZ 20% Py 1% ZnS 1% MnO 2% Lim 1%	1	.8	74			
20	25	86412	20	T		75	5	T	4	GA 60% Grnst 20% SS 1% Fe ₂ O ₃ 1% Py 1% FeAsS 1% Lim 1% QTZ 15%	1	.6	66			
25	30	86413	20	5		70	5	T	7	GA 55% QTZ 38% GS 5% Fe ₂ O ₃ 2% Grnst 3% ZnS 1% Lim 3% MnO 1%	1	(1.5)	83			
30	35	86414	20			60	20	T	7	GA 40% QTZ 30% Grnst 10% SS 3% GS 7% Fe ₂ O ₃ 3% Lim 2% Fe ₂ O ₃ 1% ZnS 2% MnO 2%	1	.6	75			
35	40	86415	40			50	10	T	3	GA 35% Grnst 20% QTZ 20% SS 10% Lim 2% ZnS 5% SS 3%	1	.5	77			
40	45	86416	20			75	5	T	4	GA 50% Grnst 20% QTZ 15% ZnS 3% Lim 5% Fe ₂ O ₃ 3% Fe ₂ O ₃ 1% MnO 2% Py 1%	1	.2	81			
45	50	86417	25	5		50	20	T	2	GA 30% QTZ 35% SS 10% Fe ₂ O ₃ 1% Grnst 6% Lim 2% MnO 6% ZnS 5% Grnst 5% Py 1% FeAsS T.	1	.3	67			
50	55	86418	10	5		75	10	T	3.5	GA 40% Grnst 5% QTZ 40% SS 5% ZnS 3% Py 2% FeAsS T. Lim 5% Fe ₂ O ₃ 5%	1	.3	92			
55	60	86419	10	10		10	70	T	7	QTZ 60% GP 65% GS 20% SS 5% ZnS 1% Lim 2% Fe ₂ O ₃ 1% FeAsS 1%	1	.2	54			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SAND DRIFF Latitude _____ Departure _____ Hole No. 10342
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 of 3
 Casing Depth 22 Overburden Depth 25-30 Length of Hole 150 Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)							Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams				Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86420	25	25		25	25	T	4.5	GA 50% GP 63% AT 20% Py 5% Lim 5% Fe ₂ O ₃ 2%		86420	1	1	70			
65	70	86421	25	25		25	25	T	2.5	GP 65% GA 20% Lim 10% Py 10% AT 15% FeAsS 5% ZnS 4% Fe ₃ O ₄ 1%		86421	1	1	78			
70	75	86422	20	40		20	20	T	2.6	AT 35% Py 30% Lim 10% FeAsS 7% GS 3% GS 5% GA 10%		86422	1	1	74			
75	80	86423	20	50		20	10	T	6.9	AT 20% GP 65% Py 10% Lim 5% GA 35%		86423	1	14	74			
80	85	86424	40	15		5	40	T	6.6	AT 40% Py 25% Lim T GP 65% GA 25%		86424	1	1	92			
85	90	86425	45	5		5	45	T	8.1	AT 40% Py 35% GA 25% Lim T.		86425	1	(4.9)	50			
90	95	86426	30	10			60	T	9.4	AT 50% Py 40% FeAsS 5% GA 3%		86426	(350)	(34.4)	64			
95	100	86427	40	20			40	T	4.3	AT 30% GA 30% GP 65% Py 25% FeAsS T.		86427	1	(2.9)	52			
100	105	86428	35	30			35	T	5.8	GA 85% AT 15% Py 45% Fe ₂ S ₅ GS 10%		86428	1	1.3	57			
105	110	86429	40	20			40	T	8.3	AT 35% GP 65% Py 20% Fe ₂ S ₅ Lim T.		86429	1	.7	59			
110	115	86430	30	30			40	T	3.8	AT 30% Py 40% GA 15% Lim T. Fe ₂ S ₅ GS 13%		86430	1	.5	61			

UNITED KENO HILL MINES LTD.
OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude _____ Departure _____ Hole No. 10342
Date Drilled _____ Elevation _____ Bearing _____ Page No. 3 Of 3
Casing Depth 22' Overburden Depth 25-30' Length of Hole 150' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Drift Latitude 66609.00 Departure 166384.66 Hole No. 10343 ✓
 Date Drilled Oct/81, 16th Elevation 2790.03 Bearing 320° Page No. 1 Of 2
 Casing Depth 10-20' Overburden Depth 20-25' Length of Hole 100' Dip 64°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86469	40			50	10	T	3.5	GA 70% Py 2% SS 2% Qtz 15% MnO 4% Lim 2% Grnst 5% ZnST. GST	86469	4	1	11			
10	15	86470		NO Sample						nothing to write home NO SAMPLE about	86470			NO Sample			
15	20	86471	30	5		60	5	T	5.5	GA 55% Qtz 25% GS 5% MnO 5% SS 5% Lim 2% Py 1% Grnst 7%	86471	4	1	118			
20	25	86472				75	25	T	5	Qtz 70% FeL 5% SS 4% GA + Grnst 15% Lim 1% ZnS 1% Py 2% GS 2%	86472	1	1	53			
25	30	86473	15	T	T	10	15	T	3	Qtz 75% FeL 3% SS 2% GA 15% Py 3% ZnST	86473	1	1	51			
30	35	86474	10	5		75	10	T	5	Qtz 70% FeL 5% SS 5% Py 3% GS 3% Lim 3% FeAs 3% GA 10%	86474	1	1	46			
35	40	86475	10	10	5	70	5	T	4.5	GA 65% Qtz 30% GS 3% Lim 1% SS 5% Py 4% FeAs 1% ZnS 1%	86475	1	1	74			
40	45	86476	25	25		25	25	T	5.5	GA 45% Qtz 40% Lim 4% GS 3% SS 3% Py 5%	86476	1	1	71			
45	50	86477	5	5	T	20	70	T	7	Qtz 85% Py 8% GS 2% MnO 4% Lim 1%	86477	1	1	49			
50	55	86478	25	25		25	25	T	5	Qtz 75% GS 5% SS 3% Py 2% MnO 3% ZnS 1% GA 10% Lim 1%	86478	1	1	40			
55	60	86479	40	10		10	40	T	6	Qtz 85% GA 10% Py 1% GS 3% Lim 1%	86479	1	1	29			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG #17

Location SNOW Drift Latitude _____ Departure _____ Hole No. 16343
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 Of 2
 Casing Depth 10 - 20 Overburden Depth 20 - 25 Length of Hole 100 Dip 64°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Gmst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86480	25	25		25	25	T	6	QTZ 45% GQ 15% PY 3% Fe-xS 2% FeAsS 2% GS 3%	86480		1				
65	70	86481	20	40		20	20	T	8	GQ 40% QTZ 35% GS 8% PY 10% FeAsS 5% Fe 2% Lim T.	86481		1				
70	75	86482	25	30				T	5	GQ 50% QTZ 40% MnO 5% PY 3% Fe-xS 2% SST Lim T. GS T	86482		(.6)				
75	80	86483	20	50		25	5	T	8	PY 40% QTZ 20% GQ 40%	86483		1				
80	85	86484	15	60		10	15	T	10	PY 70% QTZ 5% GQ 20% GS 3%	86484		1				
85	90	86485	NO Sample							MISS	86485	No sample			missing		
90	95	86486	15	70		10	5	T	7	PY 60% QTZ 20% GQ 20%	86486	3	1	92			
95	100	86487	NO Sample							INVISIBLE SCHEELITE 100%	86487	-	-	-	MISSING		

OVERBURDEN DRILL HOLE LOG

Location Snow Drift Latitude 67144.44 Departure 166828.16 Hole No. 10344 ✓
 Date Drilled Oct/81, 19th Elevation 2759.14 Bearing 320° Page No. 1 Of 2
 Casing Depth 40 Overburden Depth 55 Length of Hole 115 Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams	Pb. (ppm)		Ag. (ppm)	Zn (ppm)	CO ₃ (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)	
0	10	86488	20	5		70	5	T	2.5	GA 65% G.S. 8% Qtz 15% Fe 3.2% Py 4% Lim 2% SS 2%	86488	1	1	62				
10	15	86489	20			75	5	T	6.5	GA 75% G.S. 15% Py 2% Fe 6.1% MnO ₂ 6% ZnS 1% SS 3% Lim 2%	86489	(17)	(11)	89				
15	20	86490	40			50	10	T	4	GA 55% Qtz 20% MnO ₂ 6% Lim 4% Py 2% ZnS 3% Fe ₂ O ₃ 1% Grnst 9%	86490	7	2	78				
20	25	86491	45			45	10	T	5	GA 45% MnO ₂ + MnO ₃ 10% Grnst 10% ZnS 5% Qtz 25% Py 2% Lim 3% FeAsS	86491	1	1	44				
25	30	86492	45			45	10	T	5	GA 60% Qtz 20% SS 3% Fe ₂ O ₄ T Fe ₂ O ₃ + ZnS 4% SS 5% Py 3% Lim 3% Grnst 3%	86492	1	1	74				
30	35	86493	45			45	10	T	7	GA 40% Qtz 30% FeAsS 2% SS 8% Grnst 10% MnO ₂ 5% ZnS 1% Lim 4%	86493	1	1	63				
35	40	86494	45			50	5	T	4	GA 35% Qtz 35% Grnst 15% Py 3% FeAsS 2% Lim 5% MnO ₂ 5%	86494	1	1	47				
40	45	86495	30			50	20	T	5	GA 55% Grnst 10% Qtz 20% Py 3% MnO ₂ 7% ZnS 3% Lim 2% Scheelite T	86495	1	1	61	<40	.003		
45	50	86496	25			70	5	T	8	GA 55% Qtz 20% Grnst 15% Fe ₂ O ₄ 1% MnO ₂ 2% ZnS 2% Lim 5%	86496	1	1	62				
50	55	86497	45			45	10	T	3	GA 55% Grnst 20% Qtz 15% Py 2% Fe ₂ O ₄ 1% FeAsS 2% Lim 5%	86497	1	1	60				
55	60	86498	45			T	50	5	T	4	GA 50% Qtz 25% FeCO ₃ 3% Py 4% FeAsS 3% MnO ₂ 5% Lim 2% Grnst 8%	86498	1	1	50			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Drift Latitude _____ Departure _____ Hole No. 10344
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 of 2
 Casing Depth 40' Overburden Depth 55' Length of Hole 115' Dip 60'

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)			Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams				Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86499	20		5	75		T	2	Qtz 35% FeAsS 1% SS 5% Lim 4% G 3 2% GQ 20%	Py 15% MnO 5%	86499	1	1	71			
65	70	86500	10		T	90		T	3.5	Qtz 55% FeAsS 2% SS 8% G 10% Lim 2%	MnO 3%	86500	1	1	69			
70	75	86501	10	5	25	50	10	T	3	Qtz 35% SS 35% Lim 3% GQ 17%	Py 10%	86501	2	1	74			
75	80	86502	25	5	25	40	5	T	1	Qtz 45% SS 30% Py 10% Fe 30% T Fe 5% GQ 15%		86502	1	1	62			
80	85	86503	25		50	25		T	6	Py 90% Qtz 5% Fe 5%		86503	1	1	74			
85	90	86504	50		25	20	5	T	5	Qtz 20% SS 15% Py 15% GQ 50% Lim T		86504	1	1.3	77			
90	95	86505	75	5	25			T	4	Qtz 40% SS 5% Py 10% Fe 10% GQ 35%		86505	1	1	61			
95	100	86506	35		25	35	5	T	6	GQ 45% Qtz 15% SS 30% Py 6% Fe 2% FeAsS 2%		86506	1	1	63	W ₃ (ppm)	As (oz/ton)	
100	105	86507	40		20	40		T	7	GQ 40% Qtz 35% SS 5% Py 10% Lim T FeAsS T.		86507	1	1	54			
105	110	86508	45		5	50		T	8	GQ 55% Qtz 15% Py 5% MnO 5% ZnS 2% Lim 3% Grnst 10% SS 5% Scheelite T		86508	1	1	62	<40	.017	
110	115	86509	45		T	45	10	T	4	GQ 55% Qtz 20% Py 8% MnO 5% Fe 2% Grnst 8% Scheelite T.		86509	1	1	63	<40	.002	

091049

UNITED KENO HILL MINES LTD.

#103

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude 70618.37 N Departure 165442.44 W Hole No. 10352
 Date Drilled may 15. 82 Elevation 2718.23' Bearing 345° Page No. 1 Of 2
 Casing Depth 50' Overburden Depth ? Length of Hole 65 Dip 50°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)	Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	90115	55			15	30		1.6 GQ 15% G.S. 80% Ba(SO ₄) 2% Py, Lim, FeS, Fe ₂ O ₃ T. MnO 3%	90115	25	.2	102			
10	15	90116	45		T	20	35		.9 GQ 65% GQ 20% Ba(SO ₄) 10% SS 5% Py, FeAsS T.	90116	33	.5	101			
15	20	90117	55			25	20		2.3 GQ 70% GQ 15% Ba(SO ₄) 5% MnO 3% Lim 1% Py 1% SS 5% ZnST.	90117	18	.4	83			
20	25	90118	60			15	25		3.7 GQ 55% GQ 15% MnO 10% Py 40% Fe ₂ O ₃ 1% SS 5% Ba(SO ₄) 5%	90118	18	.1	64			
25	30	90119	60			20	20		2.3 GQ 85% GQ 5% GS 3% SS 2% Py T. MnO 5%	90119	25	.2	92			
30	35	90120	65			10	25		1.5 GQ 80% GQ 7% Ba(SO ₄) 3% MnO 4% Py T. Lim 1% SS, GS, T.	90120	26	.7	102			
35	40	90121	80				20		3.2 GQ 75% GQ 15% SS 5% MnO 2% Ba(SO ₄) 3% Py, Lim T.	90121	24	.1	88			
40	45	90122	60			5	35		2.3 GQ 70% GQ 20% SS 5% SS 2% Py 1% MnO 2% Lim T.	90122	30	.2	97			
45	50	90123	85		5		10		2.6 GQ 95% GQ 3% Py 1% SS 1% Lim T.	90123	34	.1	94			
50	55	90124	80		5		15		3.4 GQ 85% GQ 5% Py 3% SS 2% MnO 5%	90124	21	.1	87			
55	60	90125	90	5	T		5		2.6 GQ 90% GQ 5% MnO 3% Py 2% SS, Lim T.	90125	22	.1	87			

UNITED KENO HILL MINES LTD. OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude _____ Departure _____ Hole No. 10352
Date Drilled MAY 15 1962 Elevation _____ Bearing _____ Page No. 2 Of 2
Casing Depth SD Overburden Depth ? Length of Hole 65' Dip 50°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

#091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow DIRT Latitude 70.313.55 N Departure 165,347.41 W Hole No. 12356
 Date Drilled May 15/82 Elevation 2734.85' Bearing 345° Page No. 1 Of 2
 Casing Depth 50' Overburden Depth ? Length of Hole 85' Dip 66°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	90099	75			15	10		3.6	GG 65% Qtz 20% Bkay 5% Grnst 5% SS 3% Lim T. GS 8%	90099	15	.4	73			
10	15	90100	60			20	20		4.3	GG 40% Grnst 20% Qtz 25% Bkay 5% GS 4% Lim 10% MnO 5% ZnST	90100	22	.5	69			
15	20	90101	65		5	15	15		5.6	GG 65% Qtz 15% Grnst 10% Bkay 5% GS 3% SS 1% Fe ₃ O ₄ 1% Fe ₂ O ₃ , Py, ZnS T.	90101	19	.5	71			
20	25	90102	55		T	20	25		3.8	GG 55% Qtz 15% GS 5% Grnst 20% MnO 2% Bkay 3% Fe ₃ O ₄ , Py T.	90102	22	.7	90			
25	30	90103	65			15	20		4.3	GG 70% Qtz 20% Py 1% SS 3% GS 3% Fe ₃ O ₄ 1% MnO 2%	90103	32	1.3	92			
30	35	90104	75		5	10	10	T	4.1	Grnst 30% GG 50% Qtz 15% GS 3% SS 2% Py T.	90104	28	.7	96			
35	40	90105	70			5	25	T	4.5	GG 75% Qtz 15% Bkay 3% Py 1% SS 1% GS 5% MnO T. ZnST	90105	32	1.0	84			
40	45	90106	65		5	10	20	T	1.8	GG 85% Qtz 10% Py 1% SS 2% GS, Lim, Fe ₂ O ₃ T.	90106	29	.6	85			
45	50	90107	70		T	15	15		3.5	GG 80% Qtz 10% SS 3% Py 2% Lim T. MnO 5%	90107	19	.4	77			
50	55	90108	65		5	20	10		1.2	GG 75% Qtz 10% Py 3% MnO 7% SS 1% GS 4% Fe ₃ O ₄ T.	90108	20	.3	80			
55	60	90109	60		10	15	15		3.2	GG 65% Qtz 15% Py 10% MnO 5% GS 5% Lim T. FeASS T.	90109	21	.6	68			

UNITED KENO HILL MINES LTD.

Location SNOW DRIFT

Latitude

Departure

Hole No. 10336

Date Drilled may 15 / 82

Elevation

Bearing

Page No. 2 Of 2

Casing Depth 150

Overburden Depth _____

Length of Hole 23

Dip 66°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

137
091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude 70270.08 N Departure 165,333.78 W Hole No. 10357
 Date Drilled MAY 15 - 82 Elevation 2743.71 Bearing 345° Page No. 1 Of 4
 Casing Depth 54' Overburden Depth 60' Length of Hole 180 Dip 64°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)	Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	90064	60			15	25		3.5 GQ 75% Grnst 10% Qtz 10% Pb 3% Fe ₃ O ₄ T SS 2%	90064	12	.4	83			
10	15	90065	80			10	10		4.3 GQ 55% Grnst 20% Qtz 15% Py T. Pb 4% SS 6% Fe ₃ O ₄	90065	9	.3	81			
15	20	90066	60	5		15	20		4.1 GQ 50% Grnst 35% Qtz 15% Py T. MnO 5% Fe ₃ O ₄ T Lim T. Pb 5%	90066	10	.4	73			
20	25	90067	50	5		20	25		2.2 GQ 45% Grnst 20% Qtz 20% Pb 5% MnO 3% SS 3% Fe ₃ O ₄ 2% Lim T.	90067	7	.3	69			
25	30	90068	45	T		35	20		4.6 GQ 65% MnO 5% Qtz 15% GQ 55% Grnst 70% Fe ₃ O ₄ 3% ZnS T.	90068	11	.5	80			
30	35	90069	55	T	T	30	15		2.4 GQ 70% Grnst 10% Qtz 10% GQ 55% SS 5% ZnS T. Lim T.	90069	8	.4	77			
35	40	90070	65			20	15		3.4 GQ 65% Qtz 20% Grnst 15% Pb 3% SS 3%	90070	13	.4	75			
40	45	90071	50			40	10		3.4 GQ 55% Qtz 20% Pb 5% Grnst 15% MnO 2% Lim 2% Fe ₃ O ₄ T. Fe ₂ O ₃ T	90071	12	.4	97			
45	50	90072	65			20	15		2.3 GQ 70% Qtz 10% SS 5% Grnst 10% Lim 2% MnO 3%	90072	6	.2	81			
50	55	90073	50		10	15	25		3.0 GQ 90% Qtz 5% SS 5%	90073	4	.1	54			
55	60	90074	55		15	5	25		1.0 GQ 80% Qtz 8% SS 7% Grnst 5%	90074	1	.1	47			

#13

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude _____ Departure _____ Hole No. 10357
 Date Drilled may 15/82 Elevation _____ Bearing _____ Page No. 2 Of 4
 Casing Depth 54' Overburden Depth 62' Length of Hole 180 Dip 64°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	90075	60		15	T	25		3.1	GQ 80% Qtz 10% SS 10% Py T	90075	3	.2	54			
65	70	90076	65		10	5	20		2.9	GQ 65% Qtz 20% BaSO ₄ 5% Py 1% MnO ₂ 1% SS 8% Lim T.	90076	7	.4	50			
70	75	90077	65		10	10	15		3.0	GQ 70% Qtz 10% SS 15% Py 2% Lim 2% Fe ₂ O ₃ T.	90077	14	.5	60			
75	80	90078	60	5	15	T	20		1.6	GQ 65% Qtz 15% SS 15% Grnst 5% Py T. GST.	90078	10	.3	62			
80	85	90079	50	5	20		25		2.7	GQ 55% Qtz 8% BaSO ₄ 10% SS 20% Grnst 15% Py T.	90079	9	.3	78			
85	90	90080	40		30		30	T	1.3	GQ 50% Qtz 20% SS 20% BaSO ₄ 3% MnO ₂ 2% Grnst 5% Py T.	90080	15	.5	87			
90	95	90081	40	5	35		20	T	2.3	GQ 45% SS 20% Qtz 25% Py 3% GS 2% ZnST Lim 5%	90081	24	.3	91			
95	100	90082	25	10	40		25	T	2.1	GQ 45% Qtz 25% BaSO ₄ 10% SS 20% Py 2% Lim 3%	90082	14	.2	72			
100	105	90083	30	15	30		25	T	3.8	GQ 50% Qtz 25% SS 15% GS 5% Py 5% Lim T.	90083	10	.1	60			
105	110	90084	40	5	20		35	T	1.7	Qtz 40% SS 10% GS 25% Py 4% Lim 1% BaSO ₄ 20%	90084	16	.9	47			
110	115	90085	20	5	35		40	T	3.5	Qtz 35% Py 10% FeAsS 10% SS 5% BaSO ₄ 10% GQ 30%	90085	36	2.5	41			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW CREEK Latitude _____ Departure _____ Hole No. 10357
 Date Drilled MAY 15 82 Elevation _____ Bearing _____ Page No. 3 Of 4
 Casing Depth 54' Overburden Depth 60' Length of Hole 180 Dip 64°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	90086	15	10	45		30		2.1	GQ 35% Qtz 25% SS 15% Py 15% FeAsS 10% Lim T. Fe ₂ S T. 10% Scheelite	90086	11	.7	48			
120	125	90087	15	30	35		20		2.3	Fe ₂ S 30% Qtz 30% SS 5% Py 10% FeAsS 10% Lim 2% 20% Scheelite GQ 13%	90087	10	.5	62			
125	130	90088		90			10		1.0	Qtz 30% SS 30% Py 8% Fe ₂ S 5% GQ 20% FeAsS 7%	90088	9	.3	63			
130	135	90089		100			T		2.8	SS 35% Qtz 25% GQ 35% Py 2% FeAsS T. Fe ₂ S 3% T. Scheelite	90089	12	.3	66			
135	140	90090		95			5		3.7	Qtz 30% SS 15% GQ 45% Py 5% FeAsS T. Fe ₂ S 5% T. Scheelite	90090	7	.2	55			
140	145	90091	10	85			5		3.6	Qtz 40% GQ 35% SS 10% Py 5% FeAsS 5% Fe ₂ S 5%	90091	20	.2	60			
145	150	90092	5	80			15		1.1	SS 25% Qtz 30% GQ 30% FeAsS 8% Py 7%	90092	11	.1	56			
150	155	90093		95			5		2.7	SS 40% Qtz 25% GQ 35% Py ₂ FeAsS T.	90093	3	.1	41			
155	160	90094	10	80			10		3.2	Qtz 30% SS 20% GQ 45% Py 2% FeAsS 2% Fe ₂ S 1% Lim T.	90094	4	.1	51			
160	165	90095		100					3.3	SS 25% GQ 60% Qtz 15% Py T.	90095	10	.1	56			
165	170	90096		100					4.3	GQ 70% SS 20% Qtz 10% Py T.	90096	6	.1	63			

UNITED KENO HILL MINES LTD. OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude _____ Departure _____ Hole No. 10357
Date Drilled may 15 / 82 Elevation _____ Bearing _____ Page No. 4 Of 4
Casing Depth 54' Overburden Depth 60' Length of Hole 180' Dip 64°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude 70° 4.41' N Departure 165,308.24 Hole No. 1035A
 Date Drilled MAY 15 - 82 Elevation 2758.10 Bearing 345° Page No. 1 Of 4
 Casing Depth 44 Overburden Depth 45-50 Length of Hole 180 Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	90029	45			25	30		3.0	GQ 55% Qtz 20% Grnst 15% MnO 5% Lim 4% ZnS 1% SST.	90029	28	1.1	102			
10	15	90030	35			40	25		3.6	GQ 60% Grnst 25% Qtz 10% SS 2% MnO 2% Lim 1% ZnS T.	90030	15	.6	82			
15	20	90031	60			30	10		5.2	GQ 55% Qtz 15% Grnst 15% Lim 2% MnO 3% ZnS 2% GS 3% Grnst 15%	90031	13	.5	106			
20	25	90032	55			20	25		3.4	GQ 70% Grnst 10% Qtz 10% BaSO ₄ 5% GS 4% SS 1% Py, Lim, ZnS T.	90032	12	.5	99			
25	30	90033	60			10	30		3.5	GQ 70% Qtz 15% Grnst 10% GS 2% Fe ₂ O ₄ 1% ZnS 1% MnO 1% Py. Lim T.	90033	19	.7	89			
30	35	90034	65			5	30		5.6	GQ 75% Qtz 15% GS 5% Grnst 5% Py, SS, Lim, ZnS T.	90034	13	.9	69			
35	40	90035	90				10		4.2	GQ 90% Qtz 10% GS, MnO, ZnS, Py, Lim T.	90035	5	.5	47			
40	45	90036	80		5		15		3.7	GQ 85% Qtz 10% GS 3% Lim 1% Py 1%	90036	6	.5	46			
45	50	90037	85		5		10		6.0	GQ 95% Qtz 5%	90037	14	.4	52			
50	55	90038	70		10		20		4.2	GQ 90% Qtz 5% GS 2% Lim 1% Py 1% BaSO ₄ 1% ZnS T.	90038	9	.5	64			
55	60	90039	90		5		5		3.1	GQ 65% Grnst 15% Qtz 15% GS 4% Py 1%	90039	10	.5	66			

#16

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIET Latitude _____ Departure _____ Hole No. 10358
 Date Drilled MAY 15/82 Elevation _____ Bearing _____ Page No. 3 Of 4
 Casing Depth 44' Overburden Depth 45-50' Length of Hole 180 Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	90051	45	T	45		10		1.0	Qtz 30% G.Q. 60% SS 5% Py 5% Lim T	90051	17	.9	46			
120	125	90052	40	T	50		10		3.3	GQ 50% Qtz 35% SS 2% Py 6% FeAsS 4% Fe ₂ S ₃ 5% 45% Scheelite	90052	16	1.0	45			
125	130	90053	35		60		5		2.4	GQ 60% Qtz 15% SS 15% Fe ₂ S ₃ 1% Py 3% FeAsS 2% Lim 4% 5% Scheelite	90053	22	.6	69			
130	135	90054	15		10	55	10		3.2	GQ 55% SS 20% Qtz 15% FeAsS 5% Py 5% Fe ₂ S ₃ T. Approx 50 pieces Scheelite	90054	16	.6	75			
135	140	90055	45	T	40		15		1.2	GQ 45% Qtz 20% SS 10% Py 6% FeAsS 8% Fe ₂ S ₃ 1% Lim T. Scheelite T.	90055	34	1.0	68			
140	145	90056	45	T	45		10		5.1	GQ 75% SS 10% Qtz 15% Py, FeAsS T. Lim T	90056	27	1.0	59			
145	150	90057	35		50		15		3.4	GQ 60% Qtz 25% SS 10% Py 3% FeAsS 2%	90057	22	.7	86			
150	155	90058	45		35		20		4.1	GQ 65% Qtz 10% SS 25% FeAsS, Py T.	90058	19	.6	67			
155	160	90059	50		25		25		4.2	Qtz 35% SS 25% G.Q. 35% Py T. Fe ₂ S ₃ 5%	90059	13	.5	77			
160	165	90060	35		30		35		3.6	GQ 55% Qtz 25% SS 10% Py 6% FeAsS 4% Fe ₂ S ₃ T.	90060	12	.5	89			
165	170	90061	50	10	15		25		3.2	GQ 40% GS 5% Qtz 20% SS 25% Py 10% FeAsS 5%	90061	8	.5	107			

.. 16

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

06-049

UNITED KENO HILL MINES LTD.

#17

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude 70085 73 N Departure 165, 276 75 W Hole No. 10359
 Date Drilled _____ Elevation 2772.69' Bearing 345° Page No. 1 Of 4
 Casing Depth 10' Overburden Depth 10'-15' Length of Hole 180' Dip 56°
 G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)	Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim.			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86994	80		T	10	10		4.3 GG 70% Qtz 10% Grnst 15% SS T. Fe ₃ O ₄ T. GS T.	86994	33	.7	90			
10	15	86995	40		10	35	15		4.4 GG 65% Grnst 10% Qtz 15% (BaSO ₄) 8% MnO ₂ 1% SS 1% Py, ZnS T.	86995	32	.9	88			
15	20	86996	55			30	15		4.5 GG 55% Qtz 15% Grnst 20% (BaSO ₄) 5% Py T. MnO ₂ 2% SS 2% GS 1% Lim T.	86996	14	.2	78			
20	25	86997	60			20	20		3.4 Grnst 35% GG 65% Qtz 8% Lim 1% Py 1% GS 1%	86997	19	.4	88			
25	30	86998	75			10	15		4.2 Grnst 40% GG 50% Qtz 6% Py 1% Lim 1% GS 2%	86998	15	.3	69			
30	35	86999	95		T	T	5		7.1 GG 65% Grnst 25% Qtz 7% (BaSO ₄) 3% Py, Lim, GS, SS T.	86999	18	.4	64			
35	40	87000	60		5	25	10		5.4 GG 70% Qtz 15% Grnst 10% Py, FeAsS, Lim T. GS 3% Fe ₂ O ₃ , Fe ₃ O ₄ T. SS 2%	87000	18	.3	83			
40	45	87001	70		5	20	5		3.7 GG 50% Qtz 15% Grnst 30% (BaSO ₄) 3% Py 1% GS 1%	87001	14	.2	71			
45	50	87002	75		5	10	10		4.8 GG 60% Qtz 20% Grnst 15% Py 1% MnO ₂ 4% Lim T.	87002	14	.1	75			
50	55	87003	80		10	5	5		6.6 GG 80% Qtz 10% Grnst 5% MnO ₂ 2% Py 1% SS 2%	87003	13	.1	79			
55	60	87004	85		5		10		3.1 GG 85% Qtz 5% Py 3% Fe ₂ O ₄ 1% SS 4% (BaSO ₄) 2% FeAsS.	87004	20	.2	77			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

17

Location SNOW DRIFT Latitude _____ Departure _____ Hole No. 10359
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 2 of 4
 Casing Depth 10' Overburden Depth 10-15' Length of Hole 180' Dip 56°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Gmst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	90005	100					T	6.3	GQ 90% GTZ 8% Py 2% SS, S.S., FeAsS.T.	90005	15	.1	69			
65	70	90006	85		5		10		4.4	GQ 80% GTZ 15% SS 5% Py, FeAsS, ZnS, Lim T. Scheelite T	90006	10	.1	62			
70	75	90007	50		20		30		2.7	GQ 70% GTZ 15% SS 15% Lim T.	90007	43	.5	86			
75	80	90008	55		25		20		1.5	GQ 70% GTZ 20% SS 10% Py, ZnS, Lim T. Scheelite T	90008	17	.1	72			
80	85	90009	40		25		35		3.6	GQ 60% Gmst 10% GTZ 15% SS 20% Py 20% SS 60% Ba(SO ₄) 5% Scheelite T	90009	9	.1	73			
85	90	90010	25	15	30		30		3.8	GQ 55% Gmst 15% GTZ 15% FeAsS.T. SS 10% Ba(SO ₄) 5% Scheelite T	90010	13	.1	75			
90	95	90011	35	10	25		30		5.6	GQ 60% GTZ 25% SS 15% ZnS, Py, T. Scheelite T	90011	9	.1	78			
95	100	90012	30	10	40		20		3.4	GQ 65% GTZ 15% SS 20% Py, ZnS, MnO ₂ , T. Scheelite T	90012	9	.1	82			
100	105	90013	15	5	50		30		5.8	SS 35% GTZ 20% G.Q. 40% ZnS, Py, T. MnO 3% Lim 2% Scheelite T.	90013	16	.1	71			
105	110	90014	10		35		35		2.3	GTZ 55% SS 20% GQ 25% MnO, Py, ZnS, T. Lim T.	90014	11	.3	46			
110	115	90015	T		80		20		1.8	SS 40% GTZ 25% GQ 30% Lim 3% MnO 2%	90015	7	.1	57			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

7

Location SNOW DRIFT Latitude _____ Departure _____ Hole No. 10359
 Date Drilled _____ Elevation _____ Bearing _____ Page No. 3 Of 4
 Casing Depth 10' Overburden Depth 10-15' Length of Hole 180' Dip 56°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	90016	10		70		20	T	3.8	SS 30% Gr 230% G.Q. 35% Lim 30% Py 2%	90016	23	.1	49			
120	125	90017			100				4.7	SS 45% Gr 15% G.Q. 30% Fe x 32% Ba(SO ₄) 6% Py 2%	90017	9	.1	37			
125	130	90018			100				5.7	SS 50% Gr 10% G.Q. 40% Py, Lim T.	90018	6	.2	33			
130	135	90019			100				5.0	SS 65% G.Q. 25% Gr 10%	90019	14	.1	101			
135	140	90020	10		90		T		2.2	G.Q. 55% SS 35% Gr 8% Py 1% Lim 1%	90020	9	.1	32			
140	145	90021	15	15	70				3.1	SS 50% Gr 15% G.Q. 35% Py T.	90021	3	.2	27			
145	150	90022	15	20	65				5.9	SS 55% G.Q. 40% Gr 5% Py T.	90022	11	.3	77			
150	155	90023	50	T	50				6.1	G.Q. 40% SS 35% Gr 25% Py, Lim T.	90023	8	.3	65			
155	160	90024	35	5	60				2.4	G.Q. 45% SS 40% Gr 10% G.S. 5%	90024	11	.4	137			
160	165	90025	25	5	70				3.1	G.Q. 45% Gr 35% SS 10% Py 7% FeAsS T. Lim 2% Fe x 5 1%	90025	5	.2	106			
165	170	90026	15	10	75				4.4	Gr 25% G.Q. 45% SS 10% Py 8% FeAsS 3% Lim 4% Fe x 5.3% Ba(SO ₄) 2%	90026	17	.4	116			

✱ 7

[illegible]

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

#1B

Location Snow DRIET Latitude 70009.92 N Departure 165,258.07 W Hole No. 10360
 Date Drilled May 17/82 Elevation 2774.05 Bearing 345 Page No. 1 Of 4
 Casing Depth 27' Overburden Depth 40-45' Length of Hole 160 Dip 60°
 G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86959	65			25	10		2.5	GQ 55% Qtz 20% Grnst 20% BaSO ₄ 5% Py 55, 63 Fe ₂ O ₄ T.	86959	15	.8	106			
10	15	86960	45			40	15		2.3	GQ 50% Qtz 20% Grnst 25% SS 5% GS T.	86960	16	.7	98			
15	20	86961	50			20	30		4.9	GQ 55% Qtz 25% Grnst 10% SS 5% BaSO ₄ 5% ZnS Lim	86961	16	.6	107			
20	25	86962	65			10	25		5.0	GQ 45% Qtz 20% Grnst 10% GS 5% SS 10% BaSO ₄ 7% Lim 1% ZnS 2%	86962	29	.9	111			
25	30	86963	55			30	15		5.2	GQ 45% Grnst 25% Qtz 15% SS 7% ZnS 2% Lim 1% BaSO ₄ 5% MnO T.	86963	18	.8	95			
30	35	86964	30			50	20		4.4	GQ 60% Grnst 20% Qtz 10% SS T. GS 4% BaSO ₄ 6%	86964	10	.6	75			
35	40	86965	15			60	25		5.6	GQ 65% BaSO ₄ 10% Qtz 15% Grnst 10% Py T.	86965	8	.4	67			
40	45	86966	50			30	20		4.4	GQ 50% Qtz 15% Grnst 15% SS 7% Py 3% ZnS T. BaSO ₄ 5% SS 5%	86966	10	1.0	63			
45	50	86967	95				5		5.4	GQ 75% Grnst 10% Qtz 10% GS 5% TR Scheelite.	86967	23	.4	65			
50	55	86968	80		T	10	10		3.7	GQ 90% Qtz 8% GS 2% Lim T.	86968	14	.5	77			
55	60	86969	95		T		5		4.3	GQ 70% Qtz 10% SS 15% GS T. Lim T. BaSO ₄ 5%	86969	1	.2	68			
										5.10 Scheelite							

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude _____ Departure 320° 15' Hole No. 10360
 Date Drilled May 17/82 Elevation _____ Bearing _____ Page No. 2 Of 4
 Casing Depth 27' Overburden Depth 40-45' Length of Hole 180' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim.	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86970	100	T	T		T		3.4	GQ 70% GT 215% SS 10% GS 5% Lim T. Py T.	86970	2	.1	81			
65	70	86971	80	15	5				3.8	GQ 65% GT 25% B (60%) 5% SS 10% GS 4% Lim 1%	86971	4	.1	73			
70	75	86972	55	35	10		T		4.3	GQ 65% GT 20% SS 15% GS T. Lim T.	86972	5	.3	58			
75	80	86973	20	20	25		35		5.3	GT 55% SS 20% GQ 25% Py T.	86973	3	.1	28			
80	85	86974	35	10	15		40		6.2	GQ 55% GT 30% B (60%) 15% SS 10% Py T.	86974	3	.1	44			
85	90	86975	40	15	20		25		4.4	GT 35% GQ 35% SS 20% Py 3% FeAsS 2% Lim 5%	86975	1	.1	40			
90	95	86976	40	15	20		25		2.5	GT 40% SS 10% GQ 40% Py 6% FeAsS 4%	86976	3	.1	26			
95	100	86977	40	40	T		20		3.6	GS 35% GQ 20% GT 20% SS 15% FeAsS 3% Py 5% Lim 2%	86977	2	.1	47			
100	105	86978	25	35	10	20	10		3.3	GT 25% Py 15% FeAsS 5% SS 15% GQ 35% Lim 5%	86978	1	.2	42			
105	110	86979	55	10	25	10	T		5.4	GS 15% SS 10% GQ 40% Py 15% FeAsS 5% GT 15%	86979	1	.2	91			
110	115	86980	30	25	45				6.8	SS 50% GQ 25% FeAsS 8% Py 10% Fe 3.2% GT 5%	86980	19	.8	75			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Driest Latitude _____ Departure _____ Hole No. 10360
 Date Drilled May 17, 82 Elevation _____ Bearing _____ Page No. 3 Of 4
 Casing Depth 27' Overburden Depth 40.45' Length of Hole 180 Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86981	10	45	45				4.7	Qtz 20% SS 20% Py 10% Pbs 5% GQ 40% Lim 5% FeAsS 7%	86981	12	.3	59			
120	125	86982		50	50				4.3	GQ 50% Qtz 15% Py 9% SS 20% Pbs 5% FeAsS 12% L.M.T.	86982	6	.3	50			
125	130	86983	10	25	60			5	3.8	GQ 40% Qtz 25% SS 10% Py 10% FeAsS 5% Lim 5% 40% 20% Scheelite	86983	24	1.2	46			
130	135	86984	25	15	50			10	3.6	GQ 55% Qtz 15% SS 15% Py 7% FeAsS 3% GS 3% 30-40 pieces Scheelite	86984	7	.3	60			
135	140	86985	25	30	40			5	4.4	GQ 60% SS 10% Py 8% Qtz 10% GS 10% FeAsS 2% 5-10 pieces Scheelite	86985	1	.2	61			
140	145	86986	15	65	10			10	3.8	GQ 25% GS 35% Qtz 15% Py 7% FeAsS 3% Lim 5% SS 10%	86986	1	.1	72			
145	150	86987		70	30			T	4.1	Qtz 40% GQ 35% Py 5% GS 5% SS 10% Lim 5% FeAsS 7%	86987	1	.2	66			
150	155	86988	10	50	25			15	3.3	GQ 45% Qtz 10% Py 12% Pbs 5% SS 20% FeAsS 3% GS 5%	86988	2	.2	68			
155	160	86989	30	40	25			5	2.9	GQ 60% Qtz 25% SS 5% Py 7% Lim 2% ZnS 1% Fe 51%	86989	1	.1	51			
160	165	86990	30	10	30			30	5.5	GQ 45% Qtz 25% Py 10% SS 20% Lim 7%	86990	3	.1	69			
165	170	86991			95			5	5.0	GQ 25% Qtz 30% SS 20% Pbs 5% GS 7% Py 10% FeAsS 6% Fe 51% Lim 3%	86991	1	.1	79			

UNITED KENO HILL MINES LTD.

Location SNOW DRIFT

Latitude

Departure

Hole No. 10360

Date Drilled may 17 / 82

Elevation

Bearing

Page No. 4 Of 4

Casing Depth 27'

Overburden Depth

Length of Hole

Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

091049

UNITED KENO HILL MINES LTD.

75

OVERBURDEN DRILL HOLE LOG

Location Snow DRIET Latitude 69°15.05' N Departure 165, 230.18 W Hole No. 10361
 Date Drilled mar 17 / 1962 Elevation 2782.81 Bearing 345° Page No. 1 Of 3
 Casing Depth 27' Overburden Depth 30-35 Length of Hole 150 Dip 63°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)			Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams				Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86930	70		T	15	15	T	5.1	GQ 55% Grnst 15% Qtz 20% BaSO ₄ 8% ZnS 1% Fe ₂ O ₃ T SS 1%	86930	9	.4	87				
10	15	86931	70		T	20	10		5.2	GQ 55% Grnst 25% BaSO ₄ 5% Qtz 10% Py, ZnS, Fe ₂ O ₃ , Fe ₃ O ₄ T. GS 5%	86931	10	.6	74				
15	20	86932	60			25	15		4.0	GQ 50% Qtz 20% Grnst 20% BaSO ₄ 4% ZnS 1% GS 5% Py, Lim, Fe ₃ O ₄ T.	86932	14	.7	108				
20	25	86933	30		T	60	10		5.1	Grnst 70% Qtz 20% GS 6% ZnS 1% Lim 1% BaSO ₄ 2%	86933	21	.6	123				
25	30	86934	35		10	40	15		3.6	GQ 55% Qtz 20% GS 5% Grnst 10% BaSO ₄ 5% Py T. ZnS 2% SS 3% Lim T.	86934	16	.6	95				
30	35	86935	35		T	45	20	T	5.6	GQ 55% Qtz 15% Py T. SS 5% Grnst 25% ZnS T.	86935	13	.6	95				
35	40	86936	20		70	T	10		2.3	GQ 55% Qtz 25% BaSO ₄ 10% SS 10% FeAsT. GS 5%	86936	10	.4	83				
40	45	86937	30	15	50		5		2.4	SS 30% Grnst 30% Qtz 20% GQ 15% FeAs 5% Lim 2% GS 2%	86937	10	.4	90				
45	50	86938	15	15	65		5		3.7	SS 45% Grnst 20% Lim 5% Qtz 10% GQ 20%	86938	8	.4	75				
50	55	86939	30	10	40		20		7.2	Qtz 35% SS 25% Grnst 20% GQ 18% Lim 2%	86939	6	.5	68				
55	60	86940	30	35	25		10		5.0	SS 50% Qtz 15% Grnst 5% GQ 20% Lim T.	86940	6	.3	105				

OVERBURDEN DRILL HOLE LOG

Location Snow DRIET Latitude _____ Departure _____ Hole No. 10361
 Date Drilled May 17 / 82 Elevation _____ Bearing _____ Page No. 2 Of 3
 Casing Depth 27' Overburden Depth 30-35' Length of Hole 120 Dip 63°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86941	20	20	35	15	10	T	2.1	SS 45% Qtz 15% Lim 5% Grnst 10% GQ 25% Py T.	86941	26	4	130			
65	70	86942	20	45	15	5	10	5	4.0	SS 65% Qtz 10% GS 10% GQ 15% Lim T.	86942	6	4	86			
70	75	86943	30	25	25		20	T	4.9	SS 35% Qtz 25% Lim 5% GS 5% GQ 30% Py T.	86943	8	4	96			
75	80	86944	25	40	20		15	T	3.6	GQ 40% SS 25% GS 5% Qtz 15% Grnst 10% Lim 5% Py T.	86944	17	3	104			
80	85	86945	25	40	10		25		3.1	GQ 40% SS 30% Qtz 20% Pbs 10% GS T, Lim T, Py T.	86945	8	3	94			
85	90	86946	25	25	10		40	T	2.7	GQ 40% Qtz 25% SS 30% Py 10% Lim 4%	86946	4	3	81			
90	95	86947	30	25	15		30	T	2.2	GQ 50% Qtz 15% SS 20% GS 10% Py T. FeAsS T. Pbs 5%	86947	1	3	96			
95	100	86948	20	20	20		40	T	3.4	Qtz 45% FeAsS 20% Py 20% Lim 5% GQ 10%	86948	5	3	90			
100	105	86949	10	30	5		55	T	2.9	Qtz 45% SS 15% Py 15% FeAsS 5% GQ 20% Lim T.	86949	1	3	80			
105	110	86950	30	45	10		15		3.6	Qtz 50% SS 10% Py 8% FeAsS 10% Lim 1% GQ 30%	86950	3	3	43			
110	115	86951	50	25	15		10		3.1	GQ 60% SS 20% Qtz 15% Lim 3% Py 2%	86951	4	3	80			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

* 75

Location Snow Drift Latitude _____ Departure _____ Hole No. 10361
 Date Drilled May 17 / 1962 Elevation _____ Bearing _____ Page No. 3 Of 3
 Casing Depth 27' Overburden Depth 30.35' Length of Hole 150 Dip 63°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86952	65	15	5		15		4.1	GQ 50% Qtz 25% SS 20% Lim 5%	86952	4	.2	90			
120	125	86953	50	25	T		25		3.4	GQ 65% Qtz 10% SS 15% Lim 6% Py 4%	86953	4	.2	99			
125	130	86954	10	90					4.9	Fe ₂ S 60% SS 15% Py 5% GQ 10% Qtz 10% Lim T.	86954	7	.3	112			
130	135	86955	15	70	10		5		4.6	Fe ₂ S 25% Qtz 20% Py 5% FeAsS 2% SS 8% GP 4%	86955	1	.2	95			
135	140	86956	40	45	T		15	T	2.1	Qtz 30% Py 10% Fe ₂ S 20% FeAsS 10% SS 20% GQ 20%	86956	6	.4	93			
140	145	86957	40	40	10		10		8.6	Py 35% FeAsS 25% GQ 10% Fe ₂ S 10% Qtz 20% SS T.	86957	58	5.8	68			
145	150	86958	50	10	15		25		5.4	Qtz 50% FeAsS 15% Py 15% GQ 15% SS 5% Fe ₂ S T. 15% Scheelite	86958	14	.9	47			

#104

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude 69°43.15' N Departure 165,210.75 W Hole No. 10362
 Date Drilled may 17/82 Elevation 2794.65 Bearing 345 Page No. 1 Of 3
 Casing Depth 20' Overburden Depth 30' Length of Hole 170' Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86897	50			20	30		4.3	60% Grnst. 20% Qtz 10% BaSO ₄ 7% FeS ₂ 2% ZnS 1% GS.T.	86897	17	.3	127			
10	15	86898	40			30	30	T	4.8	70% Grnst 15% BaSO ₄ 8% Qtz 7% MnO ₅ 5% ZnS T.	86898	25	.3	130			
15	20	86899	65			15	20		4.7	40% Qtz 20% Grnst 25% MnO ₅ 5% GS 4% SS 1% Fe ₂ O ₃ , Fe ₃ O ₄ , ZnS T. BaSO ₄ 5%	86899	16	.2	89			
20	25	86900	20			15	65		6.7	50% Qtz 25% Grnst 15% FeS ₂ T. GS 5% BaSO ₄ 5% Fe ₃ O ₄ T.	86900	13	.2	43			
25	30	86901	40			30	30		7.1	45% Qtz 20% Grnst 20% GS 5% ZnS 2% BaSO ₄ 8% FeS ₂ T.	86901	17	.1	82			
30	35	86902	40		35	10	15	T	3.6	65% SS 20% GS 5% Qtz 10% ZnS T.	86902	6	.1	82			
35	40	86903	45		50		5	T	3.9	30% SS 30% Qtz 10% GS 10% 4m T.	86903	11	.1	78			
40	45	86904	40	5	50		5		3.2	15% Qtz 50% GS 20% SS 20% FeS ₂ 2% BaSO ₄ 8% Lim 5%	86904	10	.1	88			
45	50	86905	15	5	80				2.3	30% SS 10% Qtz 15% GS 45% BaSO ₄ 10% MnO ₅ T Py T. ZnS T.	86905	6	.1	93			
50	55	86906	10	45	45				3.0	60% GS 10% BaSO ₄ 10% Qtz 10% SS 20% Py T. Lim T.	86906	10	.1	81			
55	60	86907	5	35	60				2.5	50% GS 25% SS 25% Qtz 15% BaSO ₄ 5% Py 2% Lim 3%	86907	6	.1	68			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow DRIFT Latitude _____ Departure _____ Hole No. 10362
 Date Drilled May 17.82 Elevation _____ Bearing _____ Page No. 2 Of 3
 Casing Depth 20' Overburden Depth 30' Length of Hole 170 Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Cu (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86908	20	30	40		10		4.1	GQ 35% GT 25% SS 35% GS 5% Lim T.	86908	7	1	60			
65	70	86909	25	15	40		20		2.0	SS 40% GT 10% GQ 45% GS 5% Lim T.	86909	31	12	125			
70	75	86910	20	20	45		15	+	4.3	GQ 70% GT 15% SS 15% Py T. Lim T.	86910	15	1	112			
75	80	86911	45	5	25		20	5	2.4	GQ 70% SS 10% GT 15% Py 2% Lim 2% FeAsS 1%	86911	13	1	101			
80	85	86912	40	30	20		10		4.1	GQ 55% SS 25% GT 15% Py 3% Lim 2%	86912	1	1	91			
85	90	86913	20	70	10		T		2.2	GQ 40% SS 30% GT 20% Ba(SO ₄) 5% Py 3% Lim 2%	86913	10	1	92			
90	95	86914	15	60	15		10		4.3	GQ 58% SS 25% GT 15% GS 5% Py T. Um T.	86914	7	1	86			
95	100	86915	30	35	30		5	T	4.6	SS 35% GS 10% GQ 40% GT 15% Py T.	86915	11	1	84			
100	105	86916	T	50	50		T		4.5	GQ 45% GT 10% GS 15% SS 30%	86916	12	1	89			
105	110	86917	20	40	25		15		4.3	GQ 55% GT 20% SS 15% Py 5% GS 5%	86917	3	1	87			
110	115	86918	10	65	15		10		3.8	GS 30% GQ 35% GT 10% Py 5% FeAsS T. SS 10% Ba(SO ₄) 10%	86918	2	5	81			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Duff Latitude _____ Departure _____ Hole No. 10362
 Date Drilled May 17/82 Elevation _____ Bearing _____ Page No. 3 of 3
 Casing Depth 20' Overburden Depth 30' Length of Hole 170' Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)			Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim.	grams				Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86919	25	40	15		20		3.4	Qtz 30% Grnst 5% GS 15% Py 8% Fe As S 2% SS 5% GQ 35%		86919	17	.6	95			
120	125	86920	5	90	T		5		3.5	GQ 55% Qtz 15% GS 20% Py 4% Fe As S 1% SS 5%		86920	7	.3	75			
125	130	86921		100					2.3	GQ 40% GS 30% Qtz 20% Py 5% Fe As S 4% Fe ₂ S 1% SS T.		86921	8	.5	94			
130	135	86922		100					4.2	GS 40% GQ 40% Qtz 15% Py 5% Fe As S T. Fe ₂ S T.		86922	9	.5	103			
135	140	86923		95	5		T		3.1	Qtz 35% Py 25% Fe As S 15% GS 10% SS 3% GQ 10% Fe ₂ S 2%		86923	10	.9	94			
140	145	86924	10	80	5		5		4.7	Py 35% Fe As S 25% Qtz 18% GS T. GQ 10% Fe ₂ S 2%		86924	8	.6	103			
145	150	86925	25	40	20		15		3.1	GQ 30% Qtz 15% GS 30% Py 15% Fe As S 7% Fe ₂ S 3%		86925	32	.5	97			
150	155	86926	20	50	20		10		2.8	Qtz 25% GQ 30% GS 5% Py 20% Fe As S 15% Fe ₂ S 5%		86926	25	.6	101			
155	160	86927	25	60	T		15		4.3	Qtz 30% Grnst 5% GQ 25% Fe ₂ S 5% SS 10% GS 10% Fe As S 8% Py 7%		86927	13	.5	99			
160	165	86928	15	50	20		15		2.6	GQ 55% Qtz 20% GS 15% Py 5% Fe As S 3% Fe ₂ S 2% SS T.		86928	6	.5	79			
165	170	86929	50	30	5		15		1.2	GQ 55% Qtz 25% GS 10% Py 6% Fe As S 4% Fe ₂ S T.		86929	9	.4	95			

#115

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude 69, 756.15 N Departure 165, 183.45 W Hole No. 10363
 Date Drilled May 17, 1962 Elevation 2806.98 Bearing 345° Page No. 1 Of 4
 Casing Depth 44' Overburden Depth 50' Length of Hole 200 Dip 64°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86858	65		T	20	15		3.6	GQ 50% Qtz 15% Grnst 35% GS 20% MnO 8% Grnst 15%	86858	14	.5	86			
10	15	86859	60			30	10		5.3	GQ 65% Grnst 20% Qtz 10% SS 20% GS 3% ZnS 7%	86859	18	.2	74			
15	20	86860	60			25	15		4.4	GQ 55% Grnst 15% Qtz 15% Pb(Sq) 10% MnO 5% Fe ₂ O ₃ , GS, SS, ZnS 7%	86860	17	.4	66			
20	25	86861	65			10	25		5.3	GQ 55% Qtz 10% Grnst 20% GS 50% MnO 5% Pb(Sq) 5%	86861	14	.3	75			
25	30	86862	55			20	25		3.0	Grnst 45% GQ 40% Qtz 10% Pb(Sq) 7% FeS 7% GS 7%	86862	10	.4	74			
30	35	86863	60		T	15	25		4.3	GQ 50% Grnst 25% Qtz 30% FeS 3% Pb(Sq) 2% GS 7% Fe ₃ O ₄ 7%	86863	19	.3	84			
35	40	86864	45	5		30	20		3.8	GQ 50% Grnst 30% Qtz 15% FeS 3% Fe ₃ O ₄ 2% ZnS 7%	86864	6	.3	62			
40	45	86865	30	5		30	30		6.1	GQ 50% Qtz 20% Grnst 20% MnO 5% GS 3% Fe ₃ O ₄ 2%	86865	17	.4	75			
45	50	86866	45	5		20	25	T	3.7	GQ 60% Qtz 20% Grnst 5% FeS 5% GS 5% MnO 5%	86866	12	.4	58			
50	55	86867	45	5		5	20	T	3.1	FeS 35% Qtz 30% GQ 25% FeS 5% Fe ₂ S 2% SS 3%	86867	11	.4	64			
55	60	86868	50	5			15	T	7.5	100+ pieces Scheelite FeS 80% Qtz 15% Fe ₂ S 5%	86868	1	.9	60			
										100+ pieces Scheelite							

Page No.

Dip

Geochemical Results

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude _____ Departure _____ Hole No. 10363
 Date Drilled May 17 / 82 Elevation _____ Bearing _____ Page No. 2 of 4
 Casing Depth 44' Overburden Depth 50' Length of Hole 200 Dip 64°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86869	35	10	35		15	5	1.3	Qtz 40% SS 5% GQ 30% FeS 3% FeAs 2% FeS ₂ 20%	86869	10	1.7	78			
										Approx. 80-100 pieces Sphalerite							
65	70	86870	10	T	80		10	T	3.7	FeS 40% Qtz 15% GQ 35% SS 3% FeAs 5% Lim T FeS 5%	86870	7	.3	119			
70	75	86871	10	30	45		15	T	3.2	Qtz 30% SS 25% GQ 30% FeS 10% FeAs 4% FeS ₂ 1%	86871	16	.2	87			
75	80	86872	15	40	45		T		1.5	GQ 55% Qtz 25% SS 15% FeS 3% FeAs 2%	86872	11	.3	92			
80	85	86873	T	45	55				2.6	GQ 60% Qtz 10% SS 15% GS 5% FeS 8% FeAs 2%	86873	11	.1	97			
85	90	86874	10	20	70				2.4	GQ 55% SS 20% Qtz 10% GS 5% FeS 6% FeAs 4% MnO ₂ , ZnS T.	86874	1	.1	85			
90	95	86875	25	15	50		10		3.3	GQ 50% Qtz 15% FeS 10% SS 15% FeAs 5% GS 5%	86875	5	.1	85			
95	100	86876	25	20	40		15		1.5	GQ 45% Qtz 20% GS 20% SS 10% FeAs T. FeS 5%	86876	7	.1	103			
100	105	86877	10	60	30		T		3.2	GS 35% GQ 35% SS 15% Qtz 15% FeS T.	86877	5	.1	97			
105	110	86878	15	60	20		5		1.3	GS 25% GQ 35% SS 20% Qtz 20% FeAs T. FeS T.	86878	6	.1	100			
110	115	86879	10	70	10		10		3.1	GS 40% Qtz 25% SS 10% GQ 20% FeS 5% FeAs T.	86879	1	.1	85			

UNITED KENO HILL MINES LTD. OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude _____ Departure _____ Hole No. 10363
 Date Drilled MAY 17 82 Elevation _____ Bearing _____ Page No. 3 of 4
 Casing Depth 44' Overburden Depth 50' Length of Hole 200 Dip 64°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim.	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86880	20	55	10		15		4.2	SS 30% Qtz 35% SS 10% GQ 25% FeS ₂ T.	86880	3	.2	95			
120	125	86881	15	40	35		10		3.3	Qtz 35% SS 20% GS 10% FeS ₂ 10% FeAsS 5% GQ 20%	86881	1	.1	77			
125	130	86882	35	30	20		15		1.2	GQ 45% Qtz 25% FeS ₂ 10% Fe 3.5% FeAsS 5% SS 10%	86882	1	.1	83			
130	135	86883	40	25	15		20		1.8	GQ 35% Qtz 20% SS 15% GS 15% FeS ₂ 10% FeAsS 3% Fe-x 2.2%	86883	11	.2	144			
135	140	86884	20	35	30		15		2.3	SS 30% GQ 45% Qtz 25% FeS ₂ T.	86884	20	.1	97			
140	145	86885	25	25	40		10		3.2	SS 35% Qtz 30% GQ 35% FeS ₂ T.	86885	16	.1	89			
145	150	86886	20	15	60		5		1.7	GQ 35% Qtz 25% FeS ₂ 15% SS 20% FeAsS 5%	86886	17	.1	76			
150	155	86887	20	5	60		15		2.8	SS 40% Qtz 35% GQ 25% FeS ₂ T.	86887	17	.1	77			
155	160	86888	10	20	70		T		4.7	SS 50% GS 25% Qtz 25% FeS ₂ T.	86888	12	.1	103			
160	165	86889	10	25	50		15		4.1	SS 35% Qtz 30% GS 5% FeAsS 5% FeS ₂ 4% Lim 1% GQ 20%	86889	9	.1	94			
165	170	86890	25	30	35		10		3.5	SS 30% Qtz 40% GQ 30% FeS ₂ T.	86890	14	.1	67			

UNITED KENO HILL MINES LTD. OVERBURDEN DRILL HOLE LOG

Location Snow Drift Latitude _____ Departure _____ Hole No. 10363
Date Drilled May 17 82 Elevation _____ Bearing _____ Page No. 4 of 4
Casing Depth 44' Overburden Depth 50' Length of Hole 200 Dip 64°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

09104

UNITED KENO HILL MINES LTD.

78

OVERBURDEN DRILL HOLE LOG

Location SNEW DRIFT Latitude 69259.13 N Departure 165,866.90 W Hole No. 10364
 Date Drilled May 17, 82 Elevation 2760.80 Bearing 345° Page No. 1 Of 4
 Casing Depth 23' Overburden Depth 30' Length of Hole 180 Dip 57°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)			Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams				Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	P6823	40		T	15	45	T	5.2	GQ 45% Qtz 25% Grnst 15% SS 5% ZnS 1% BaSO ₄ 1% Lim T.	P6823	19	.2	77				
10	15	P6824	45		T	15	40	T	3.9	GQ 60% Qtz 15% Grnst 20% BaSO ₄ 5% GS, SS, ZnS T.	P6824	24	.9	79				
15	20	P6825	40		5	20	35		6.8	GQ 55% Grnst 25% Qtz 15% MnO ₂ 5% Lim, Fe ₂ O ₃ , BaSO ₄ T.	P6825	30	.2	94				
20	25	P6826	50	5	10	15	20		7.2	GQ 50% Grnst 20% BaSO ₄ 5% MnO ₂ 5% Qtz 15% GS 5% Fe ₂ O ₃ , Lim, ZnS T.	P6826	17	.1	65				
25	30	P6827	50	5	5	20	20	T	3.5	GQ 60% Qtz 15% Grnst 15% BaSO ₄ 5% Fe ₂ O ₃ 1% FeAs ₂ 2% ZnS 1% Lim 1%	P6827	22	.1	91				
30	35	P6828	65	5	5	15	10		4.2	GQ 60% Qtz 10% BaSO ₄ 5% Grnst 20% Fe ₂ O ₃ 3% FeAs ₂ 2% ZnS T, GS, Lim T.	P6828	19	.3	83				
35	40	P6829	50		5	30	15		3.3	GQ 30% Qtz 10% SS 5% Grnst 25% MnO ₂ 5% GS 2% Lim 2% Fe ₂ O ₃ 1% FeAs ₂ T.	P6829	12	.1	74				
40	45	P6830	35	T	15	20	30		4.8	GQ 60% Qtz 10% BaSO ₄ 10% Fe ₂ O ₃ 5% Grnst 15% FeAs ₂ T. SS T.	P6830	11	.1	80				
45	50	P6831	40	10	T	15	35		4.4	GQ 65% Grnst 20% MnO ₂ 5% Qtz 5% Fe ₂ O ₃ 4% FeAs ₂ 1% Lim.	P6831	21	.1	76				
50	55	P6832	65	5		10	20		3.9	GQ 65% Qtz 15% Fe ₂ O ₃ 5% Grnst 10% GS 2% SS 2% Fe ₂ O ₃ T. ZnS T. Lim 1%	P6832	18	.1	79				
55	60	P6833	75	10		5	10		4.5	GQ 65% Grnst 20% BaSO ₄ 5% Qtz 5% Fe ₂ O ₃ 2% SS 3%	P6833	21	.2	80				

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude _____ Departure _____ Hole No. 10364
 Date Drilled May 17 / 1982 Elevation _____ Bearing _____ Page No. 2 of 4
 Casing Depth 23' Overburden Depth 30' Length of Hole 180 Dip 57°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)			Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams				Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86834	75	10			15		4.8	GQ 90% FeS ₂ T	QTZ 10% FeAsS T. SS T.	86834	13	.2	85			
65	70	86835	70	5			10	15	4.2	GQ 25% FeS ₂ 4%	QTZ 15% SS 6%	86835	11	.1	66			
70	75	86836	60	5	15	T	20		3.7	QTZ 40% FeAsS 40%	SS 15% FeS ₂ 6% GQ 15% BSS 15%	86836	5	.1	27			
Approx 40-50 pieces Scheelite																		
75	80	86837	45	10	25		20		4.5	QTZ 30% FeAsS 10% Fe, x S T.	SS 15% GQ 15% FeS ₂ 10%	86837	8	.1	27			
80	85	86838	15	T	55		30		3.2	QTZ 55% FeAsS T.	SS 10% GQ 20% FeS ₂ 15%	86838	7	.2	28			
85	90	86839	5		75		20		1.7	QTZ 55% SS 5%	FeS ₂ 20% Fe, x S 5% FeAsS 15%	86839	8	.3	31			
90	95	86840	T		80		20		3.4	QTZ 65% SS 5%	FeS ₂ 7% Fe, x S 3% FeAsS 10% GQ 10%	86840	9	.3	26			
95	100	86841	20		50		30		2.2	QTZ 65% SS 8%	GQ 10% FeAsS 5% Fe, x S 2% FeS ₂ 10%	86841	7	.2	20			
100	105	86842	25		40		35		3.8	QTZ 70% FeS ₂ 2%	SS 20% FeAsS 2% GQ 5% Fe, x S 1%	86842	7	.2	33			
105	110	86843	20	T	50		30		4.9	QTZ 45% FeAsS 5%	FeS ₂ 35% Fe, x S 5% SS 10%	86843	6	.5	30			
110	115	86844	20	20	40		20		2.6	QTZ 55% FeS ₂ 25%	Fe, x S 10% FeAsS T. SS 10%	86844	9	.3	24			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude _____ Departure _____ Hole No. 10364
 Date Drilled may 17 / 1982 Elevation _____ Bearing _____ Page No. 3 Of 4
 Casing Depth 23' Overburden Depth 32' Length of Hole 180' Dip 57°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Gmst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Cu (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86845	20	45	25		10		2.7	Qtz 30% SS 30% FeS ₂ 10% Fe _x S 5% FeAs 3.5%	86845	7	.5	41			
120	125	86846	40	40	20		T		1.2	Qtz 50% SS 35% FeS ₂ 10% FeAs ST. Fe _x S 5%	86846	1	.4	35			
125	130	86847	20	80	T				5.1	Qtz 30% SS 25% GQ 15% Fe _x S 15% FeS ₂ 10% FeAs 5%	86847	5	.4	44			
130	135	86848	45	45			10		2.2	SS 30% Qtz 25% GQ 20% Fe _x S 4% FeS ₂ 15% FeAs 8%	86848	5	.4	35			
135	140	86849	45	40			15		5.1	GQ 65% Qtz 20% SS 5% FeS ₂ 6% FeAs 3% Fe _x S 1%	86849	9	.4	93			
140	145	86850	25	40	10		25		4.0	Qtz 35% SS 20% FeS ₂ 20% Fe _x S 10% FeAs 8% GQ 7%	86850	14	.7	50			
145	150	86851	30	35	T		35		5.0	Qtz 50% SS 10% GQ 15% Fe _x S 5% FeS ₂ 20%	86851	19	.6	49			
150	155	86852	40	10	20		30		3.8	FeS ₂ 65% Qtz 30% S.T. GQ 5% Fe _x S T.	86852	84	.3	119			
155	160	86853	45	T	35		20		5.6	FeS ₂ 75% Qtz 25%	86853	24	2.6	75			
160	165	86854	40	T	60		T		4.3	FeS ₂ 45% SS 25% Qtz 20% GQ 10% FeAs 8%	86854	16	1.0	54			
165	170	86855	40	15	40		5		1.9	FeS ₂ 55% Qtz 20% SS 5% Fe _x S 15% FeAs 5%	86855	23	.6	65			

G. Galina, Best Results

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

#1

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude 69179.92 N Departure 165,844.13 W Hole No. 10365
 Date Drilled may 12, 82 Elevation 2765.45 Bearing 345 Page No. 1 of 4
 Casing Depth 16' Overburden Depth 20-25' Length of Hole 180 Dip 58°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; FeS. Sphene; Zn. Sphene																	
Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams	Pb. (ppm)		Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)	
0	10	86788	65	T	T	20	15	T	4.2	GQ 55% Qtz 20% Grnst. 20% G.S.T. SST MnO 5% FeS ₂ T.	86788	30	.4	174			
10	15	86789	60	T		20	20	T	6.8	GQ 55% Grnst. 30% SS 2% Qtz 8% MnO 5% ZnS.T.	86789	17	.4	114			
15	20	86790	45	5	5	20	25	T	4.1	GQ 55% Grnst. 20% Qtz 15% G.S. 4% Fe ₃ O ₄ 1% Lim. T. SST. ZnS.T. MnO 5%	86790	16	.3	69			
20	25	86791	50	T	5	20	25	T	2.8	GQ 60% Qtz 20% Grnst. 15% G.S. 2% FeS ₂ 3% Fe ₃ O ₄ T. SST. Fe ₃ O ₄ T.	86791	22	.5	71			
25	30	86792	55	10	T	20	15	T	4.4	GQ 70% Qtz 15% Grnst. 10% G.S. 3% FeS ₂ 2% ZnS.T. Fe ₃ O ₄ T.	86792	18	.4	88			
30	35	86793	45	15		20	20	T	5.2	GQ 75% Qtz 10% FeS ₂ 5% Grnst. 10% G.S.T.	86793	19	.7	73			
35	40	86794	45	20		15	20	T	3.9	GQ 65% Qtz 5% FeS ₂ 5% Grnst. 25% MnO T.	86794	7	.1	62			
40	45	86795	30	25		15	30	T	2.8	GQ 60% Qtz 20% Grnst. 15% G.S. 2% FeS ₂ 2% Fe ₃ O ₄ 1%	86795	24	.3	84			
45	50	86796	25	25		20	30	T	4.6	GQ 65% Qtz 15% Zn(SO ₄) 2% G.S. 2% FeS ₂ 2% Fe ₃ O ₄ 2% SST. Grnst. 10%	86796	15	.1	94			
50	55	86797	30	25		20	25	T	3.7	GQ 85% Qtz 15% G.S.T. FeS ₂ T. Fe ₃ O ₄ T.	86797	23	.2	108			
55	60	86798	25	35		10	30	T	4.7	GQ 70% Qtz 20% Zn(SO ₄) 3% G.S. 4% FeS ₂ 3% Fe ₃ O ₄ T.	86798	12	.1	57			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SANDWICH CREEK Latitude _____ Departure _____ Hole No. 10365
 Date Drilled May 12 82 Elevation _____ Bearing _____ Page No. 2 of 4
 Casing Depth 16' Overburden Depth 20-25' Length of Hole 180' Dip 58°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)			Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams				Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86799	40	20	15		25		3.0	Qtz 50% SS 10% BaSO ₄ 5% GQ 20% FeAsS 8% FeS ₂ 7% Fe, x S 4% Lim 1%		86799	12	.4	47			
65	70	86800	35	10	15		40	T	2.8	Qtz 40% GQ 30% FeS ₂ 5% FeCO ₃ 8% FeAsS 7% Fe, x ST. SS 5% BaSO ₄ 5%		86800	12	.1	32			
70	75	86801	35	10	15		40	T	2.7	Qtz 40% GQ 20% SS 15% FeCO ₃ 5% FeAsS 5% FeS ₂ 4% BaSO ₄ 10% Fe, x S 1%		86801	10	.1	20			
75	80	86802	15	30	20		35		4.8	Qtz 25% BaSO ₄ 10% SS 15% GQ 25% FeS ₂ 10% FeAsS 5%		86802	7	.1	22			
80	85	86803	20	25	25		30	T	3.3	Qtz 55% BaSO ₄ 10% GQ 15% SS 4% FeAsS 8% FeS ₂ 7% Fe, x S 1%		86803	6	.2	6			
85	90	86804	20	10	50		20		3.8	Qtz 55% SS 15% GQ 15% BaSO ₄ 5% FeAsS 5% FeS ₂ 4% Fe, x S 1%		86804	2	.3	37			
90	95	86805	10	5	50		35		3.1	Qtz 60% FeS ₂ 20% FeAsS 15% SS 3% Fe, x S 2%		86805	3	.2	32			
95	100	86806	10		70		20		2.7	Qtz 50% SS 20% GQ 15% FeS ₂ 10% FeAsS 5%		86806	6	.1	24			
100	105	86807	T		90		10		3.4	Qtz 45% SS 25% GQ 20% FeS ₂ 6% FeAsS 4% Fe, x S T.		86807	5	.1	37			
105	110	86808			100		T		4.6	SS 35% Qtz 25% GQ 25% FeS ₂ 7% FeAsS 3% Fe, x S 5%		86808	11	.1	40			
110	115	86809			100				4.1	Qtz 55% SS 20% GQ 5% Fe, x S 5% FeS ₂ 10% FeAsS 5%		86809	10	.2	17			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIET Latitude _____ Departure _____ Hole No. 10365
 Date Drilled may 12 82 Elevation _____ Bearing _____ Page No. 3 Of 4
 Casing Depth 16 Overburden Depth 20-25 Length of Hole 180 Dip 50°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim.	grams			Pb. (ppm)	Ag. (ppm)	Cu (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86810	10		80		10		2.8	QTZ 45% SS 20% GQ 15% FeS ₂ 10% FeAsS 4% Fe ₂ S 1%	86810	8	.1	29			
120	125	86811	10		65		25		2.6	QTZ 70% FeAsS 10% FeS ₂ 10% SS 7% Fe ₂ S 3%	86811	15	.1	10			
125	130	86812	30		40		30		3.4	GQ 15% QTZ 60% SS 15% FeS ₂ 5% FeAsS 5% Fe ₂ S T.	86812	7	.1	12			
130	135	86813	30	5	40		25		3.3	GQ 20% QTZ 50% SS 10% GST. FeAsS 5% FeS ₂ 5% Ba(SO ₄) 10%	86813	5	.1	15			
135	140	86814	35		30		35		3.9	QTZ 70% Ba(SO ₄) 5% GQ 15% SS 2% FeAsS 3% FeS ₂ 5%	86814	4	.1	10			
140	145	86815	35		50		15		3.3	QTZ 65% FeS ₂ 20% SS 10% FeAsS 5% Fe ₂ S T.	86815	3	.1	15			
145	150	86816	25		65		10		4.2	QTZ 50% Ba(SO ₄) 10% SS 10% FeS ₂ 15% FeAsS 5% GQ 10% Fe ₂ S T.	86816	5	.1	20			
150	155	86817	20		60		20		3.6	QTZ 70% FeS ₂ 20% SS 5% FeAsS 3% Fe ₂ S 2%	86817	1	.1	16			
155	160	86818	30	T	45		25		2.9	QTZ 75% SS 15% FeS ₂ 5% FeAsS 5% Fe ₂ S T.	86818	9	.1	38			
160	165	86819	35	T	50		15		3.4	QTZ 70% SS 20% FeS ₂ 3% FeAsS 4% Fe ₂ S 3%	86819	4	.1	40			
165	170	86820	40		60		T		2.3	QTZ 60% SS 5% FeS ₂ 30% Fe ₂ S 3% FeAsS 2%	86820	8	.1	50			

UNITED KENO HILL MINES LTD.
OVERBURDEN DRILL HOLE LOG

Location SNOWDRIFT Latitude _____ Departure _____ Hole No. 10365
Date Drilled may 12, 82 Elevation _____ Bearing _____ Page No. 4 Of 4
Casing Depth 16' Overburden Depth 20-25' Length of Hole 180 Dip 50°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

#103 091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude 69103.79 N Departure 165,819.52 W Hole No. 10366
 Date Drilled may 12 / 82 Elevation 2768.14 Bearing 345° Page No. 1 Of 4
 Casing Depth 23' Overburden Depth 2530' Length of Hole 180' Dip 56°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86753	60		T	20	20		3.5	GQ 50% Qtz 20% Grnst 15% Ba(SO ₄) 6% SS 4% MnO ₂ 5% GS T. Fe ₃ O ₄ T.	86753	14	.4	92			
10	15	86754	55	5	T	15	25		5.8	GQ 45% Grnst 25% Qtz 15% Ba(SO ₄) 10% SS 5% Fe ₃ O ₄ T. MnO ₂ T. Lim T.	86754	9	.4	55			
15	20	86755	55	T	5	10	30		3.2	GQ 50% Qtz 10% Grnst 30% Fe ₃ O ₄ 1% Fe ₃ O ₄ 1% SS 3% Lim T. Ba(SO ₄) 5%	86755						
20	25	86756	65	T	5	10	20	T	4.3	GQ 40% Qtz 25% GS 10% Grnst 15% Fe ₃ O ₄ 5% SS T. Lim 3% Fe ₃ O ₄ 2%	86756	1	.1	48			
25	30	86757	55	10	T	15	20	T	3.5	GQ 40% Grnst 15% Qtz 20% GS 5% Ba(SO ₄) 8% MnO ₂ 3% Fe ₃ O ₄ 2% SS 5% Fe ₃ O ₄ 2%	86757	1	.1	74			
30	35	86758	45	10		20	25		7.3	GQ 45% Qtz 10% Grnst 30% Fe ₃ O ₄ 5% Ba(SO ₄) 10% GS T. 3% T.	86758	1	.1	60			
35	40	86759	45	15		15	25		3.8	GQ 50% Grnst 35% Qtz 10% Ba(SO ₄) 5% Fe ₃ O ₄ T. GS T.	86759	1	.2	88			
40	45	86760	35	10	5	15	35		3.6	GQ 65% Qtz 20% Fe ₃ O ₄ 5% Fe ₃ O ₄ T. Ba(SO ₄) 5% Grnst 5% Fe ₃ O ₄ T.	86760	9	.1	82			
45	50	86761	60	15		5	20		2.0	GQ 65% Qtz 25% Ba(SO ₄) 5% Fe ₃ O ₄ 2% Fe ₃ O ₄ 2% GS 1% SS T.	86761	4	.1	87			
50	55	86762	60	15	5	T	20		4.6	GQ 55% Grnst 25% GS 5% Qtz 15% SS T. Fe ₃ O ₄ T. Fe ₃ O ₄ T.	86762	4	.2	84			
55	60	86763	25	20	25		30		4.5	Qtz 45% Ba(SO ₄) 20% Fe ₃ O ₄ 10% SS 10% Fe ₃ O ₄ 4% Fe ₃ O ₄ 1% GS 1% GQ 9%	86763	14	.4	45			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude _____ Departure _____ Hole No. 10366
 Date Drilled May 12, 82 Elevation _____ Bearing _____ Page No. 2 Of 4
 Casing Depth 23' Overburden Depth 25-30' Length of Hole 180' Dip 56°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86764	15	25	30		30		2.7	Qtz 30% GQ 55% SS 5% FeS ₂ 3% FeAsS 1% Fe ₂ O ₃ 1% MnO ₂ 5%	86764	5	12	89			
65	70	86765	10	60	20		10		4.2	Qtz 30% SS 35% GQ 30% FeAsS 3% FeS ₂ 2% G.S.T.	86765	2	4	77			
70	75	86766	10	40	35		15		3.9	Qtz 40% SS 15% GQ 35% FeAsS 5% FeS ₂ 2% Fe ₂ S ₃ 2% MnO ₂ T.	86766	6	5	62			
75	80	86767	5	45	40		10		4.0	Qtz 45% SS 15% Fe ₂ S ₃ 10% FeAsS 8% FeS ₂ 7% GQ 15%	86767	9	5	58			
80	85	86768	20	45	10		25		2.4	Qtz 60% SS 10% Fe ₂ S ₃ 10% GQ 10% FeAsS 5% FeS ₂ 5%	86768	3	12	46			
85	90	86769	40	45	T		15		3.6	Qtz 50% Fe ₂ S ₃ 15% FeS ₂ 10% SS 15% FeAsS 10%	86769	11	5	46			
90	95	86770	35	40	5		20		5.2	Qtz 40% GQ 30% FeS ₂ 10% Fe ₂ S ₃ 4% FeAsS 6% SS 10%	86770	12	4	32			
95	100	86771	50	35			15		3.3	Qtz 45% GQ 15% FeS ₂ 15% FeAsS 10% Fe ₂ S ₃ 5% SS 10%	86771	5	14	35			
100	105	86772	20	65			15		5.1	GQ 55% SS 20% Qtz 15% FeAsS 5% FeS ₂ 2 Fe ₂ S ₃ 2%	86772	6	4	40			
105	110	86773	35	40	T		25		4.4	Qtz 75% SS 5% GQ 10% FeAsS 5% FeS ₂ 5% Fe ₂ S ₃ T.	86773	2	11	109			
110	115	86774	45	35			20		6.1	Qtz 75% SS 10% GQ 10% FeAsS 5% FeS ₂ T.	86774	7	12	33			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow DRAFT Latitude _____ Departure _____ Hole No. 10366
 Date Drilled May 12, 82 Elevation _____ Bearing _____ Page No. 3 Of 4
 Casing Depth 23' Overburden Depth 25-30' Length of Hole 180 Dip 56°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)	Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Gmst.	Qtz.	Lim	grams		Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86775	45	45			10		5.3 GQ 45% SS 15% QTZ 25% FeAsS 5% FeS 5% Fe ₂ S 5%	86775	1	.3	26			
120	125	86776	50	50					4.6 SS 40% GQ 45% QTZ 15% Zn ST FeAsS T. Fe ₂ S T.	86776	5	.1	24			
125	130	86777	55	20			25		4.9 GQ 50% SS 20% QTZ 20% FeAsS 5% FeS 5% Fe ₂ S T.	86777	4	.1	28			
130	135	86778	40	30			30		4.7 QTZ 50% SS 15% GQ 25% FeAsS 7% FeS 3%	86778	5	.2	27			
135	140	86779	40	35			25		3.5 GQ 50% QTZ 35% SS 10% FeAsS 3% FeS 2%	86779	4	.1	16			
140	145	86780	45	35			20	T	3.2 GQ 35% QTZ 40% SS 15% FeAsS 6% FeS 4% Fe ₂ S T.	86780	1	.3	24			
145	150	86781	50	40			10	T	6.0 GQ 50% QTZ 25% SS 10% GS 5% FeAsS 3% FeS 2%	86781	6	.1	40			
150	155	86782	50	30			20	T	4.3 GQ 45% SS 20% QTZ 25% FeS 4% FeAsS 4% Fe ₂ S 2% GS T.	86782	1	.1	37			
155	160	86783	40	35	T		25		3.4 GQ 50% SS 15% QTZ 20% FeS 10% FeAsS 5% GS T.	86783	8	.2	58			
160	165	86784	45	30	5		20	T	3.2 QTZ 55% SS 20% GQ 20% FeS 4% FeAsS 1% Fe ₂ S T.	86784	8	.1	49			
165	170	86785	35	45	T		20	T	4.0 QTZ 30% GQ 30% SS 25% FeS 9% FeAsS 3% Fe ₂ S 3%	86785	10	.1	61			

UNITED KENO HILL MINES LTD.

Location Snow Dallet Latitude _____ Departure _____ Hole No. 10366
Date Drilled May 12 62 Elevation _____ Bearing _____ Page No. 4 of 4
Casing Depth 23' Overburden Depth 25-30' Length of Hole 180 Dip 56°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

#96

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow V. AFT Latitude 67° 11.45' N Departure 165,795.03 W Hole No. 10367
 Date Drilled May 12 82 Elevation 2769.23 Bearing 345° Page No. 1 Of 4
 Casing Depth 27 Overburden Depth 45' Length of Hole 180 Dip 57°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim.	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86718	70			T	10	20	3.1	GQ 55% Qtz 20% Grnst 15% BaSO ₄ 5% MnO 5% Fe ₃ O ₄ T.	86718	14	2.2	109			
10	15	86719	55			T	15	30	4.3	GQ 58% Qtz 15% Grnst 20% MnO 10% GS T. 3.50% 5% Fe ₃ O ₄ T.	86719	30	1.2	85			
15	20	86720	50				25	25	5.8	GQ 45% Qtz 20% Grnst 20% GS 5% FeS ₂ 1% Fe ₃ O ₄ 1% MnO 8% Lim T.	86720	10	1.1	83			
20	25	86721	65	T			10	25	3.8	GQ 45% Qtz 20% Grnst 25% FeS ₂ 2% GS 3% MnO 5% Fe ₃ O ₄ T.	86721	2	.9	80			
25	30	86722	60	T			5	15	4.2	GQ 50% Qtz 25% FeS ₂ 10% Fe ₃ O ₄ T. Fe ₃ O ₄ 2% SS 3% Grnst 10%	86722	5	1.0	103			
30	35	86723	55			10	5	30	4.0	GQ 60% Qtz 15% Grnst 10% FeS ₂ 5% MnO 5% SS + GS T.	86723	7	1.0	81			
35	40	86724	85	10				5	5.5	GQ 55% Grnst 15% Qtz 15% FeS ₂ 5% MnO 10% ZnS T. Fe ₃ O ₄ T.	86724	9	1.1	103			
40	45	86725	60	20			5	15	2.1	GQ 60% Grnst 15% Qtz 10% MnO 5% ZnS 1% BaSO ₄ 4% Fe ₃ O ₄ T. FeS ₂ 1% GS 4%	86725	11	1.0	102			
45	50	86726	60	25				15	4.9	GQ 60% Grnst 10% Qtz 20% GS 7% Fe ₃ O ₄ 1% FeS ₂ 2% SS T.	86726	1	.3	77			
50	55	86727	50	15			10	25	3.7	GQ 65% Qtz 20% BaSO ₄ 5% GS 5% SS 3% Fe ₃ O ₄ 2% ZnS T. FeS ₂ T.	86727	1	.5	83			
55	60	86728	45	5		15	T	35	5.7	GQ 50% Qtz 35% MnO 5% ZnS 2% GS 3%	86728	6	.4	74			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow DRIET Latitude _____ Departure _____ Hole No. 10367
 Date Drilled May 12 / 82 Elevation _____ Bearing _____ Page No. 2 of 4
 Casing Depth 27' Overburden Depth 45' Length of Hole 180' Dip 57°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86729	20	5	30		45		4.0	GQ 40% Qtz 40% Grnst 5% FeS ₂ 2% ZnS 1% MnO 5% SS 2% GS 5%	86729	11	.3	67			
65	70	86730	5	T	50		45		3.1	Qtz 60% GQ 30% SS 15% FeS ₂ 5% FeAsS Fe ₂ S ₃	86730	7	.1	47			
70	75	86731	15	5	40		40		5.3	Qtz 50% SS 15% Baboy 15% GQ 15% FeS ₂ 5%	86731	9	.1	44			
75	80	86732	15		55		30		5.8	Qtz 65% SS 15% FeS ₂ 10% MnO 4% Fe ₂ S ₃ 5% GS T GQ 5%	86732	6	.1	33			
80	85	86733	20		25		55		5.7	Qtz 70% FeS ₂ 10% SS 10% GQ 10% FeAsS T.	86733	7	.1	32			
85	90	86734	15		15		70		3.5	Qtz 60% FeS ₂ 15% SS 10% GS 3% FeAsS 2% GQ 10%	86734	4	.3	25			
90	95	86735	40		10		50		5.0	Qtz 30% GQ 25% SS 20% FeS ₂ 15% GS 5% FeAsS 5%	86735	7	.3	57			
95	100	86736	25	45	20		10		5.9	GQ 35% SS 25% Qtz 20% FeS ₂ 15% Fe ₂ S ₃ 5% FeAsS 5%	86736	2	.2	67			
100	105	86737	20	55	15		10		3.2	Qtz 50% GQ 20% SS 20% FeAsS 5% FeS ₂ 5% Fe ₂ S ₃ T.	86737	4	.2	62			
105	110	86738	55	45	T		T		3.9	Qtz 25% GQ 35% SS 20% GS 5% FeAsS 8% FeS ₂ 6% Fe ₂ S ₃ 1%	86738	26	1.0	94			
110	115	86739	55	40	T		5		4.4	Qtz 35% GQ 40% FeS ₂ 5% SS 15% FeAsS 5% GS T.	86739	5	.1	41			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOWBRIEF Latitude _____ Departure _____ Hole No. 10367
 Date Drilled May 12 / 82 Elevation _____ Bearing _____ Page No. 3 of 4
 Casing Depth 27' Overburden Depth 45' Length of Hole 180 Dip 57°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86740	20	80			T		2.1	Qtz 45% SS 20% GQ 30% G.S. 3% FeAsS 1% FeS ₂ 1%	86740	1	.1	39			
120	125	86741	25	65			10		3.4	Qtz 40% GQ 35% G.S. 10% SS 5% FeS ₂ 5% Fe ₂ S ₂ 2% FeAsS 3%	86741	1	1.0	50			
125	130	86742	25	60			15		3.3	GQ 40% Qtz 25% GS 10% SS 10% FeS ₂ 7% Fe ₂ S ₂ 3% FeAsS 5%	86742	2	.1	57			
130	135	86743	10	90			T		2.8	GQ 35% Qtz 20% GS 25% FeS ₂ 8% Fe ₂ S ₂ 2% SS 10%	86743	5	.1	97			
135	140	86744	35	45			20		5.4	Qtz 40% GQ 25% GS 20% SS 5% FeS ₂ 10% FeAsS 1%	86744	16	.1	68			
140	145	86745	T	100					2.6	GQ 30% Fe ₂ S ₂ 30% Qtz 20% GS 20%	86745	7	.1	79			
145	150	86746		100					2.9	GQ 25% Qtz 10% Fe ₂ S ₂ 35% GS 20% SS 10%	86746	1	.3	69			
150	155	86747	T	100					3.0	Fe ₂ S ₂ 30% SS 20% GQ 20% Qtz 15% GS 15% FeS ₂ T.	86747	2	.1	67			
155	160	86748	T	100			T		3.4	Qtz 25% GQ 30% Fe ₂ S ₂ 20% SS 15% GS 10% ZnS T.	86748	3	.1	81			
160	165	86749	10	90			T		4.6	Fe ₂ S ₂ 60% GQ 10% Qtz 5% SS 25%	86749	1	.1	85			
165	170	86750	15	85			T		4.3	Fe ₂ S ₂ 35% Qtz 35% FeS ₂ 5% SS 25%	86750	1	.2	84			

UNITED KENO HILL MINES LTD.

Location SNOW DALE Latitude _____ Departure _____ Hole No. 10367
Date Drilled May 12 82 Elevation _____ Bearing _____ Page No. 4 of 4
Casing Depth 27' Overburden Depth 45' Length of Hole 180' Dip 57°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snowdrift Latitude _____ Departure _____ Hole No. 10365
 Date Drilled May 12 82 Elevation _____ Bearing _____ Page No. 2 Of 4
 Casing Depth 27 Overburden Depth 35-40 Length of Hole 180 Dip 56°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Gmst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86694	10	10	30		10	T	2.1	SS 50% GQ 25% Qtz 20% BaSO ₄ 3% FeS ₂ 2%	86694	6	.5	76			
65	70	86695	10	5	70		15		5.2	Qtz 60% SS 25% GQ 15% FeAsS T FeS ₂ T Fe ₃ O ₄ T	86695	3	.2	38			
70	75	86696	15	10	55		20		5.4	Qtz 55% BaSO ₄ 20% SS 15% FeS ₂ 5% GQ 5% FeAsS T Lim T. Fe ₃ O ₄ T.	86696	6	.1	32			
75	80	86697	30	40	15		15		5.8	GQ 45% Qtz 25% SS 20% FeAsS 5% FeS ₂ 2% BaSO ₄ 3% Lim T.	86697	5	.1	44			
80	85	86698	15	40	10		5		5.3	Qtz 35% GQ 15% SS 15% FeAsS 10% FeS ₂ 5% BaSO ₄ 20%	86698	21	.4	37			
85	90	86699	15	45	30		10		5.2	Qtz 55% BaSO ₄ 5% GQ 15% FeS ₂ 5% FeAsS 10% SS 10% Lim T.	86699	4	.1	38			
90	95	86700	5	55	40		T		8.2	Qtz 50% BaSO ₄ 10% GQ 20% FeAsS 5% FeS ₂ 5% Lim T Fe ₃ -x S T. SS 10% Fe ₃ O ₄ T.	86700	13	.7	33			
95	100	86701	20	45	30		5		4.3	GQ 40% SS 25% Qtz 25% FeAsS 4% BaSO ₄ 5% Fe ₃ -x 1%	86701	16	.1	44			
100	105	86702	20	40	30		10	T	4.4	SS 20% GQ 35% Qtz 25% FeAsS 10% FeS ₂ 5% Fe ₃ -x 2% BaSO ₄ 2% Lim 1%	86702	5	.7	12			
105	110	86703	40	35	10		15		5.8	Qtz 45% BaSO ₄ 10% SS 20% FeAsS 15% FeS ₂ 10% GQ Fe ₃ -x S T. Lim T.	86703	12	.1	55			
110	115	86704	40	35	20		10		5.9	GQ 20% Qtz 30% BaSO ₄ 15% SS 5% FeAsS 7% FeS ₂ 3%	86704	2	.1	37			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DAFT Latitude _____ Departure _____ Hole No. 10368
 Date Drilled may 12 82 Elevation _____ Bearing _____ Page No. 3 Of 4
 Casing Depth 27' Overburden Depth 35-40' Length of Hole 180 Dip 56°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86705	15	45	40		T		5.2	Qtz 30% BaSO ₄ 5% GQ 30% FeAs 5% FeS ₂ 5% SS 25% Fe _{1-x} S T.	86705	4	.2	34			
120	125	86706	30	30	25		15		6.0	Qtz 75% GQ 15% SS 5% FeAs 3% FeS ₂ 2%	86706	9	.2	29			
125	130	86707	25	30	25		20		5.1	Qtz 80% GQ 5% SS 5% FeAs 4% FeS ₂ 3% BaSO ₄ 2% Fe _{1-x} S 1%	86707	1	.1	24			
130	135	86708	30	40	15		15		4.2	GQ 45% Qtz 25% SS 20% BaSO ₄ 5% FeS ₂ 3% FeAs 2% Fe _{1-x} S T.	86708	5	.5	45			
135	140	86709	30	30	25		15		5.3	GQ 45% Qtz 35% SS 10% FeS ₂ 6% Fe _{1-x} S 2% FeAs 2% GS T.	86709	3	.3	37			
140	145	86710	35	45	10		10		5.4	GQ 45% Qtz 20% SS 10% GS 10% Fe _{1-x} S 2% FeS ₂ 8% FeAs 5%	86710	1	.1	113			
145	150	86711	20	70	T		10		3.4	GQ 60% Qtz 10% GS 20% BaSO ₄ 20% FeS ₂ 3% SS 5% Fe _{1-x} S T. FeAs ST Lim T	86711	4	.2	117			
150	155	86712	T	100					6.9	Qtz 25% GQ 40% SS 20% GS 10% BaSO ₄ 5% Fe _{1-x} S T.	86712	1	.3	83			
155	160	86713	10	85			5		4.9	Qtz 45% BaSO ₄ 10% FeS ₂ 20% Fe _{1-x} S 2% SS 20% GS 3%	86713	5	1.1	110			
160	165	86714	20	75			5		6.8	GQ 55% Qtz 20% SS 15% FeAs ST. FeS ₂ 9% Fe _{1-x} S 1%	86714	8	.9	94			
165	170	86715	T	100					5.2	GQ 30% Qtz 20% SS 20% GS 10% BaSO ₄ 5% FeS ₂ 15% Fe _{1-x} S T. FeAs 5 T.	86715	3	1.0	112			

OVERBURDEN DRILL HOLE LOG

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

091049

315

UNITED KENO HILL MINES, LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Dr. Fr Latitude 68° 70' 52" N Departure 165,757.51 W Hole No. 10369
 Date Drilled May 12 82 Elevation 2773 55 Bearing 345 Page No. 1 Of 4
 Casing Depth 25' Overburden Depth 35' 40" Length of Hole 180' Dip 56°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Cu. (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86648	80			T	20		1.3	GQ 55% Qtz 25% SS 5% Grnst. 15% BaSO ₄ T.	86648	48	1.3	80			
10	15	86649									86649						
			NO SAMPLE									NO SAMPLE					
15	20	86650	70			10	20	T	7.3	GQ 40% Grnst 15% Qtz 20% BaSO ₄ 5% SS 5% CaCO ₃ T. GS 5%	86650	10	1.2	87			
20	25	86651	55		5	10	30	T	6.6	GQ 30% Grnst 20% Qtz 25% BaSO ₄ 10% FeS ₂ 3% GS 5% Fe ₃ O ₄ 2% MnO 5%	86651	17	1.7	85			
25	30	86652	50		5	25	20	T	3.7	GQ 35% Grnst 20% BaSO ₄ 10% Qtz 20% MnO 10% ZnS T. Fe ₃ O ₄ 2% FeS ₂ 1% GS 2%	86652	3	1.0	77			
30	35	86653	55		T	20	25	T	6.4	GQ 35% Grnst 20% Qtz 25% SS 3% FeS ₂ 5% MnO 5% GS 7% Fe ₃ O ₄ T.	86653	6	1.2	69			
35	40	86654	60		10	15	15		5.7	GQ 35% Qtz 30% Grnst 15% SS 5% MnO 10% FeS ₂ 5% Fe ₃ O ₄ T. ZnS T.	86654	13	1.0	77			
40	45	86655	55	10	20	T	15	T	7.7	SS 75% Qtz 10% GQ 10% Lim T. BaSO ₄ 5% ZnS T.	86655	6	.4	129			
45	50	86656	25	45	20		10		3.4	SS 80% Qtz 10% FeAsS T. GQ 10% FeS ₂ T.	86656	6	.6	110			
50	55	86657	15	50	25	5	5		4.3	SS 65% Qtz 15% GQ 20% FeS ₂ T.	86657	3	1.4	88			
55	60	86658	25	35	35	T	5		6.2	Qtz 35% SS 30% GQ 30% FeS ₂ T. GS 3% BaSO ₄ 2% Lim T.	86658	7	4	94			

#315

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Spruce Dale Latitude _____ Departure _____ Hole No. 10369
 Date Drilled May 12, 1982 Elevation _____ Bearing _____ Page No. 2 Of 4
 Casing Depth 25' Overburden Depth 35' - 40' Length of Hole 180' Dip 58°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)	Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	866659	25	45	20		10		5.5 SS 50% GQ 30% Qtz 15% FeAsS 3.5% FeS ₂ T. GS T. Fe _x -S T.	866659	3	.6	110			
65	70	866660	15	60	25		T		7.3 SS 70% GQ 20% Qtz 10% FeS ₂ T. Fe _x -S T.	866660	110	.5	292			
70	75	866661	35	40	25		T		6.5 SS 60% Qtz 20% GQ 15% FeS ₂ 1% Fe _x -S T. GS 2% Ba(SO ₄) 2%	866661	5	.5	91			
75	80	866662	40	15	45		T		5.1 Qtz 75% GQ 5% SS 15% FeS ₂ 2% Ba(SO ₄) 3% ZnS T.	866662	65	.1	124			
80	85	866663	30	25	40		5		3.2 Qtz 60% SS 30% FeS ₂ 5% FeAsS 3% Lim 2%	866663	4	.4	110			
85	90	866664	10	40	40		10		4.2 Qtz 60% SS 25% FeAsS 10% FeS ₂ 5% Lim T.	866664	1	.3	61			
90	95	866665	20	60	5		15		4.8 Qtz 65% FeAsS 20% SS 10% FeS ₂ 5% Fe _x -S T.	866665	6	.2	41			
95	100	866666	25	50	5		20		6.3 SS 25% GQ 25% FeS ₂ 15% Fe _x -S 3% Qtz 25% FeAsS 7%	866666	1	.2	61			
100	105	866667	30	45	10		15		3.8 SS 20% Qtz 55% FeS ₂ 5% Fe _x -S 15% FeAsS 5%	866667	1	.1	38			
105	110	866668	30	35	30		5		3.7 Qtz 25% SS 20% GS 5% Fe _x -S 8% FeAsS 10% FeS ₂ 1% GQ 20% Ba(SO ₄) 2%	866668	1	.1	78			
110	115	866669	20	35	40		5		4.2 Qtz 60% SS 20% Fe _x -S 5% GS 5% FeAsS 5% FeS ₂ 5%	866669	2	.1	46			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Dart Latitude _____ Departure _____ Hole No. 10369
 Date Drilled May 12, 80 Elevation _____ Bearing _____ Page No. 3 Of 4
 Casing Depth 25' Overburden Depth 35-40' Length of Hole 180 Dip 56°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86670	40	35	25			T	4.2	Qtz 30% GQ 40% FeAsS 3% ZnS 2% Fe ₂ S ₃ 5% FeS ₂ 2% SS 25%	86670	2	.3	70			
120	125	86671	45	40	5		10		5.3	Qtz 50% GQ 25% FeAsS 5% SS 15% FeS ₂ 3% Fe ₂ S ₃ 2%	86671	1	.1	44			
125	130	86672	20	80					2.5	Qtz 58% SS 25% GS 5% FeAsS 10% FeS ₂ 5% Fe ₂ S ₃ 3% Lim 2%	86672	1	.1	57			
130	135	86673	5	95					5.8	Qtz 20% GQ 40% SS 20% Fe ₂ S ₃ 2% GS 8% FeAsS 5% FeS ₂ 5%	86673	1	.1	56			
135	140	86674	10	85			5		2.9	Qtz 45% GQ 15% SS 15% GS 10% FeAsS 9% FeS ₂ 6% Fe ₂ S ₃ 2%	86674	2	.1	64			
140	145	86675	15	80			5		6.3	GQ 30% Qtz 25% SS 30% FeAsS 5% FeS ₂ 5% GS 5% Fe ₂ S ₃ 5%	86675	8	.3	41			
145	150	86676	55	25			20		7.4	Qtz 75% GQ 10% SS 10% FeAsS 3% FeS ₂ 2% GST Fe ₂ S ₃ 5%	86676	15	.3	77			
150	155	86677	40	35			25		5.0	Qtz 75% SS 15% GQ 5% Fe ₂ S ₃ 5% FeAsS 5% FeS ₂ 5%	86677	3	.2	48			
155	160	86678	40	60			T		4.6	Qtz 70% SS 20% GS T Fe ₂ S ₃ 5% FeAsS 5%	86678	1	.3	86			
160	165	86679	30	10	50		10		4.6	Qtz 75% FeAsS 5% SS 5% Fe ₂ S ₃ 10% FeS ₂ 5%	86679	1	.1	86			
165	170	86680	10	10	55		25		6.1	Qtz 90% SS 5% Lim T FeAsS 3% FeS ₂ 2% Fe ₂ S ₃ 5%	86680	7	.8	78			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Duff Latitude _____ Departure _____ Hole No. 10567
Date Drilled May 12 82 Elevation _____ Bearing _____ Page No. 4 Of 4
Casing Depth 25' Overburden Depth 35-40' Length of Hole 180' Dip 56°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

#17

Location Snow Drift Latitude 68827.23 N Departure 165,741.98 W Hole No. 10370
 Date Drilled May 12 1982 Elevation 2775.11 Bearing 345° Page No. 1 Of 4
 Casing Depth 25' Overburden Depth 25-30' Length of Hole 180' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim.	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86613	70		5	10	15		8.1	GQ 60% Qtz 10% Grnst 20% FeAsS 20% MnO 5%	86613	26	.5	75			
10	15	86614	50		10	20	20		8.6	GQ 55% Grnst 25% Qtz 10% FeAsS 20% GP 20% BaSO ₄ 3% MnO 5% Fe ₂ O ₃ T Fe ₃ O ₄ T.	86614	39	.4	71			
15	20	86615	70		T	T	30		5.9	GQ 40% Grnst 20% G.S. 20% Qtz 25% Fe ₂ O ₄ 20% Fe ₂ O ₃ 10% SS 50% BaSO ₄ 50%	86615	20	.4	64			
20	25	86616	45		15	5	35		7.2	GQ 30% Qtz 35% Grnst 15% Fe ₂ O ₄ 20% GS 50% BaSO ₄ 8% ZnS T. SS 50%	86616	20	.2	78			
25	30	86617	35		40	5	20		3.3	GQ 50% SS 15% Qtz 25% BaSO ₄ 50% Fe ₃ O ₄ 10% FeAsS 10% Fe ₃ O ₄ 10% Fe ₂ O ₃ T. GS 20%	86617	19	.1	99			
30	35	86618	10	T	80		10		4.0	SS 60% GQ 30% Qtz 10% FeS T. Lim T.	86618	17	.8	104			
35	40	86619	25	T	55		20		3.7	SS 40% Qtz 25% GQ 15% BaSO ₄ 50% Fe ₂ O ₃ 50% GS 50% FeAsS T. Lim 20% MnO 30%	86619	21	.4	85			
40	45	86620	20		65		15		1.0	SS 55% Qtz 20% GQ 10% MnO 5% FeS ₂ 10% Fe ₃ O ₄ T.	86620	18	.3	87			
45	50	86621	T		100		T		4.2	SS 65% Qtz 15% FeS ₂ 15% FeAsS 20% BaSO ₄ 3%	86621	12	.2	97			
50	55	86622	5		95		T		3.8	Qtz 50% FeS ₂ 15% FeAsS 50% SS 50% Fe ₂ S 20% Lim 30%	86622	14	.3	106			
55	60	86623	15		80		5		4.4	SS 45% Qtz 25% FeS ₂ 10% BaSO ₄ 10% FeAsS 10%	86623	12	.1	115			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Duff Latitude _____ Departure _____ Hole No. 10370
 Date Drilled May 12, 82 Elevation _____ Bearing _____ Page No. 2 of 4
 Casing Depth 25' Overburden Depth 25.30' Length of Hole 180' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86624	10		85		5		3.5	SS 55% Qtz 20% FeS ₂ 15% FeAsS 8% Ba(S ₂) 5% Lim 2%	86624	12	.1	70			
65	70	86625	25	T	70		5		9.7	SS 95% Qtz 5% FeS ₂ T.	86625	14	.1	113			
70	75	86626	20	20	40		20		1.3	SS 90% Qtz 8% FeS ₂ 2% Lim T.	86626	10	.1	84			
75	80	86627	40	5	45		10		40	SS 75% Qtz 15% FeS ₂ 10% FeAsS T. Lim T.	86627	12	.1	111			
80	85	86628	50	5	40		5	T	7.6	SS 50% FeS ₂ 25% Qtz 20% FeAsS 4% Fe ₂ O ₃ 1%	86628	8	.1	115			
85	90	86629	50		50				3.4	SS 60% Qtz 10% FeS ₂ 20% FeAsS 5% Lim 5%	86629	7	.1	104			
90	95	86630	60		35		5		6.1	SS 45% Qtz 10% FeS ₂ 8% Lim 2% GQ 35%	86630	14	.1	116			
95	100	86631	40		55		5		6.2	SS 35% GQ 40% Qtz 15% FeS ₂ 5% Lim 2% Ba(S ₂) 2% Fe ₂ S T. FeAsS 1%	86631	9	.1	93			
100	105	86632	30	40	20		10		1.6	SS 75% GQ 15% Qtz 4% Lim 2% FeS ₂ 2% FeAsS 2% Fe ₂ S T.	86632	7	.1	116			
105	110	86633	40	60			T		3.3	Qtz 40% SS 20% GQ 20% FeAsS 3 7% FeS ₂ 8% Fe ₂ S 1% Ba(S ₂) 1%	86633	10	.1	79			
110	115	86634	30	40	25		5		6.6	Qtz 60% FeAsS 10% SS 15% FeS ₂ 10% Ba(S ₂) 5%	86634	15	.1	47			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

17

Location SNOW DRAFT Latitude _____ Departure _____ Hole No. 10370
 Date Drilled May 12 / 82 Elevation _____ Bearing _____ Page No. 3 Of 4
 Casing Depth 25' Overburden Depth 25-30' Length of Hole 180' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
115	120	86635	10	85	5		7		6.8	FeAsS 60% Qtz 15% SS 15% Fe ₂ S ₃ 3% FeS ₂ 7%	86635	19	.1	95			
120	125	86636	15	80			5		5.5	Qtz 60% FeS ₂ 10% SS 20% FeAsS 10%	86636	13	.1	100			
125	130	86637	35	60	10		5		3.2	Qtz 35% Fe ₂ S ₃ 30% SS 10% FeS ₂ 20% FeAsS 5%	86637	11	.3	48			
130	135	86638	10	40	40		10		4.6	Qtz 60% SS 30% Fe ₂ S ₃ 10% FeS ₂ 5% FeAsS 5% Fe ₂ S ₃ 3%	86638	10	.1	75			
135	140	86639	40	30	30		T		3.8	Qtz 60% SS 25% FeS ₂ 5% FeAsS 5% FeS ₂ 5%	86639	12	.1	86			
140	145	86640	35	35	15		15		6.2	Qtz 90% FeAsS T FeS ₂ T SS 10%	86640	3	1.0	62			
145	150	86641	15	60	5		10		5.0	Qtz 60% SS 30% GQ 10% FeS ₂ T	86641	5	1.2	128			
150	155	86642	30	75			5		4.5	SS 65% Qtz 10% GQ 15% FeAsS 6% FeS ₂ 4%	86642	4	1.0	99			
155	160	86643	5	95					8.7	SS 50% GQ 20% Qtz 15% FeS ₂ 10% FeAsS 5%	86643	1	1.3	88			
160	165	86644	15	85					5.3	GQ 50% Qtz 23% SS 20% FeS ₂ 5% FeAsS 2%	86644	8	1.5	105			
165	170	86645	T	15					8.5	Qtz 30% SS 15% FeS ₂ 5% GQ 45% FeAsS 5% Lim T	86645	5	1.0	102			

UNITED KENO HILL MINES LTD. OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude _____ Departure _____ Hole No. 103-0
Date Drilled May 12 / 82 Elevation _____ Bearing _____ Page No. 4 Of 4
Casing Depth 25' Overburden Depth 25-30' Length of Hole 180' Dip 60°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

#38

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude 68°16.64 N Departure 165,681.62 W Hole No. 10372
 Date Drilled may 12 82 Elevation 2773.87 Bearing 345° Page No. 1 Of 1
 Casing Depth 47' Overburden Depth ? Length of Hole 60' Dip 57°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86602	60		10	5	20	5	8.5	Qtz 25% GQ 55% Grnst 10% Py 5% Calc T. MnO ₂ 2% BaSO ₄ 3%	86602	31	.7	69			
10	15	86603	65		10	5	20	T	7.3	GQ 50% Qtz 20% Grnst 10% FeAsS 8% BaSO ₄ 2% Py 5% Calc T. MnO ₂ 5%	86603	19	.7	80			
15	20	86604	55		10	10	25		7.7	GQ 45% Qtz 30% Grnst 5% BaSO ₄ 5% FeAsS 8% SS 5% Py 12%	86604	27	.6	84			
20	25	86605	55		5	5	35	T	5.5	GQ 40% Qtz 35% FeAsS 5% MnO ₂ 5% Py 3% Grnst 5% BaSO ₄ 5% Lim 2% SS T.	86605	20	.2	64			
25	30	86606	60		10		30		6.1	Qtz 25% GQ 50% FeAsS 10% SS 7% Lim 2% Fe ₃ O ₄ 1% MnO ₂ 5% Py T.	86606	22	.2	108			
30	35	86607	50	T	5	10	35	T	7.9	GQ 50% Qtz 20% Grnst 15% FeAsS 3% Py 1% MnO ₂ 5% Fe ₃ O ₄ 1% SS 5% Calc T.	86607	21	.2	132			
35	40	86608	55	5	10	5	25		3.6	GQ 50% Grnst 15% Qtz 15% SS 5% MnO ₂ 10% Fe ₃ O ₄ T. Calc T. Py 2% FeAsS 1% GS 2%	86608	24	1.3	86			
40	45	86609	75	T	T	10	15		9.6	GQ 60% Qtz 25% SS 4% Fe ₃ O ₄ T. FeAsS 2% Py 2% GS 2% MnO ₂ 5%	86609	21	.4	98			
45	50	86610	60		5		35		8.3	GQ 60% Qtz 15% Grnst 10% SS 5% GS 5% MnO ₂ 4% Py T. FeAsS T. Fe ₃ O ₄ 1%	86610	20	.2	82			
50	55	86611	65	5		5	25	T	7.9	GQ 50% Qtz 20% GS 3% Grnst 10% Lim 2% MnO ₂ 9% SS 2% FeAsS 2% Fe ₃ O ₄ T.	86611	37	1.0	85			
55	60	86612	75	10			15		8.9	GQ 45% Qtz 25% Grnst 10% BaSO ₄ 5% SS 5% Lim 2% MnO ₂ 8% Calc T.	86612	23	.4	68			

091049

UNITED KENO HILL MINES LTD.

137

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude 68563.22 N Departure 165,665.42 W Hole No. 10373
 Date Drilled MAY 3, 1982 Elevation 2795.81 Bearing 345° Page No. 1 Of 4
 Casing Depth 40' Overburden Depth 40-45' Length of Hole 180 Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)			Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams				Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86567	85	T	5	5	5	T	6.1	GQ 46% Qtz 33% Grnst 15% Fe ₂ O ₃ T. SS 5% Py T.		86567	26	4	10			
10	15	86568	75		5	10	10		5.5	GQ 45% Qtz 20% Grnst 20% MnO ₂ 5% Py T. BaSO ₄ 5% Fe ₂ O ₃ T. SS 5%		86568	26	.5	72			
15	20	86569	80		5	5	10		6.9	GQ 50% Qtz 10% GS 5% Grnst 10% MnO ₂ 5% BaSO ₄ 2% Fe ₂ O ₃ 1% FeS ₂ 1% Fe ₃ O ₄ 1%		86569	24	.2	66			
20	25	86570	75			5	15	5	4.5	GQ 40% Qtz 20% Grnst 15% MnO ₂ 10% BaSO ₄ 5% GS 5% SS 5% Fe ₂ O ₃ T.		86570	24	.2	67			
25	30	86571	70		5	5	20	T	6.4	GQ 55% Qtz 10% SS 10% MnO ₂ 10% BaSO ₄ 10% Lim 3% Fe ₃ O ₄ 1% FeS ₂ 1% ZnS T.		86571	27	.4	76			
30	35	86572	60	5	5	15	15		6.7	GQ 65% Qtz 20% MnO ₂ 5% Lim 2% FeS ₂ 2% Fe ₃ O ₄ 1% SS 5%		86572	26	.1	59			
35	40	86573	75	T	5	10	10		3.8	GQ 45% Qtz 20% SS 10% MnO ₂ 5% Lim 3% Fe ₃ O ₄ 1% FeAsS T. FeS ₂ 1% Fe ₂ O ₃ 1% BaSO ₄ 4%		86573	43	.2	78			
40	45	86574	55	10	20	T	10	5	6.5	GQ 40% Qtz 20% SS 15% Lim 5% MnO ₂ 5% BaSO ₄ 10% FeS ₂ 3% Fe ₂ O ₃ 1% Fe ₃ O ₄ 1%		86574	23	.3	84			
45	50	86575	35		50		10	5	5.4	SS 50% GQ 20% Lim 3% Qtz 15% BaSO ₄ 10% FeS ₂ 2%		86575	17	.2	86			
50	55	86576	10		80		10	T	8.2	SS 70% Qtz 15% BaSO ₄ 5% GQ 10% Lim T. FeAsS T.		86576	13	.3	76			
55	60	86577			100				5.9	SS 70% GQ 15% BaSO ₄ 3% Lim 2% Qtz 8% FeAsS 2% FeS ₂ T.		86577	17	.6	90			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Duff Latitude _____ Departure _____ Hole No. 10373
 Date Drilled May 12 82 Elevation _____ Bearing _____ Page No. 2 of 4
 Casing Depth 40' Overburden Depth 40-45' Length of Hole 180 Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86578	5		95				7.6	SS 80% GQ 10% Lim T. QTz 10%	86578	15	.4	78			
65	70	86579	35		60		5	T	6.7	SS 80% QTz 15% FeAsS 5% Lim T.	86579	16	.7	50			
70	75	86580	30		60		10	T	4.2	QTz 55% BaSO ₄ 5% FeAsS 10% FeS ₂ 10% Lim T. SS 20%	86580	14	.4	38			
75	80	86581	40		40		20	T	4.4	QTz 60% SS 25% FeS ₂ 7% FeAsS 7% Lim 1%	86581	14	.4	46			
80	85	86582	25	5	35		35	T	3.7	QTz 40% SS 25% FeAsS 10% BaSO ₄ 10% FeS ₂ 5% GQ 10%	86582	18	.4	42			
85	90	86583	25	5	35		35	T	8.0	QTz 40% FeAsS 15% SS 15% FeS ₂ 5% GQ 15% BaSO ₄ 10% Lim T.	86583	23	.5	41			
90	95	86584	15	5	60		20		7.4	SS 45% QTz 20% GQ 20% FeS ₂ 2% FeAsS 5% Lim 1% BaSO ₄ 7%	86584	24	.5	53			
95	100	86585	45		45		10		7.1	QTz 30% SS 30% GQ 20% FeAsS 5% FeS ₂ T BaSO ₄ 15% Lim T.	86585	14	.5	38			
100	105	86586	25		60		15		4.2	SS 40% QTz 25% BaSO ₄ 5% GQ 25% FeAsS 3% FeS ₂ 1% MnO ₂ 1%	86586	12	.4	60			
105	110	86587	25		50		25		5.9	SS 55% GQ 20% BaSO ₄ 4% FeS ₂ 3% QTz 15% FeAsS 3% Lim T.	86587	15	.1	84			
110	115	86588	40		40		20		9.0	QTz 70% SS 30% FeS ₂ T BaSO ₄ T.	86588	20	.8	58			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow DRAFT Latitude _____ Departure _____ Hole No. 10373
 Date Drilled May 12 1982 Elevation _____ Bearing _____ Page No. 3 of 4
 Casing Depth 40' Overburden Depth 40-45' Length of Hole 180' Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)				Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Gmst.	Qtz.	Lim	grams					Pb. (ppm)	Ag. (ppm)	Zn (ppm)		Ag. (oz/ton)	Pb. (%)
115	120	86589	6.5		25		10		6.1	Qtz 45% SS 30% BaSoy 5% py T. Lim T.	86589	18	.9	57					
120	125	86590	6.0		30		10		8.4	Qtz 30% GQ 30% SS 25% FeS ₂ 8% MnO ₂ 5% Lim 2%	86590	22	.4	97					
125	130	86591	6.0		25		15		5.0	Qtz 30% GQ 15% SS 35% MnO ₂ 5% FeAsS 5% FeS ₂ 8% Lim 2%	86591	19	.5	78					
130	135	86592	6.5		20		15		6.1	Qtz 40% SS 30% GQ 15% FeS ₂ 5% FeS ₂ 2% FeAsS 2% BaSoy 5% MnO 1% ZnST.	86592	22	.7	70					
135	140	86593	6.0		35		5		3.8	SS 55% Qtz 15% GQ 15% FeS ₂ 8% FeAsS 3% MnO ₂ 2% Lim 2%	86593	21	.8	87					
140	145	86594	3.0		40		30		2.8	Qtz 25% SS 15% GQ 20% FeS ₂ 15% FeAsS 5% BaSoy 10%	86594	18	.5	4					
145	150	86595	3.5		35		30		6.3	Qtz 30% SS 25% GQ 20% FeS ₂ 10% FeAsS 5% MnO 3% BaSoy 7%	86595	16	.1	65					
150	155	86596	3.5		30		35		4.1	Qtz 35% BaSoy 10% FeS ₂ 30% FeAsS 10% SS 10% GQ 15% Lim T.	86596	16	.1	75					
155	160	86597	5.5	15	20		10		6.5	SS 60% FeAsS 15% Qtz 10% Fe ₂ ST. FeS ₂ 15% Lim T.	86597	13	.1	101					
160	165	86598	6.0	30	10		T		7.7	SS 55% GQ 25% Qtz 10% FeS ₂ 8% FeAsS 2%	86598	11	.1	97					
165	170	86599	6.5	15	15		5		4.6	SS 50% GQ 35% Qtz 10% FeS ₂ 3% FeAsS 2%	86599	11	.2	84					

UNITED KENO HILL MINES LTD. OVERBURDEN DRILL HOLE LOG

Location Snow Drift Latitude _____ Departure _____ Hole No. 10373
Date Drilled May 12, 82 Elevation _____ Bearing _____ Page No. 4 Of 4
Casing Depth 40' Overburden Depth 40-45' Length of Hole 180' Dip 62°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

[illegible]

#46 091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SW 1/4 JAIET Latitude 68°47'0.30" N Departure 165,644.94 W Hole No. 10374
 Date Drilled May 3, 1982 Elevation 2777.14 Bearing 345° Page No. 1 Of 2
 Casing Depth 10' Overburden Depth 10-15' Length of Hole 110' Dip 57°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results			Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86546	75	T	T	5	15	5	8.0	GA 50% Qtz 20% Grnst. 5% GS 10% FeAsS 5% Py T. Lim 2% ZnS 1% SS 2%	86546	7	.1	45			
10	15	86547	60	T		30	5	5	4.8	GA 65% Qtz 15% Grnst 9% GS 5% Lim 2% FeAsS 2% MnO 2% ZnS T Fe ₃ O ₄ T.	86547	12	.1	50			
15	20	86548	65		T	20	10	5	6.5	GA 60% Grnst 10% Qtz 15% GS 5% SS 2% FeAsS T Lim 3% MnO 5% Fe ₃ O ₄ T.	86548	10	.1	67			
20	25	86549	90			5	5	T	5.7	GA 65% Qtz 20% GS 10% SS 5% Lim T. FeAsS T.	86549	6	.1	27			
25	30	86550	80	10	5		5		7.4	Qtz 50% GA 30% FeAsS 5% GS 10% SS 2% FeS ₂ 1% Lim 2%	86550	1	.3	38			
30	35	86551	85	10			5	T	5.3	Qtz 70% GA 35% FeAsS 2% GS 20% Py T. Lim 1% Fe ₂ -xS T.	86551	2	.1	23			
35	40	86552	85	5			10	T	6.4	GA 40% Qtz 35% GS 20% FeAsS 2% FeS ₂ 2% Fe ₂ -xS 1%	86552	1	.3	28			
40	45	86553	80	10			10	T	3.7	GA 40% Qtz 33% GS 15% FeAsS 10% Fe ₂ -xS 2%	86553	1	.2	31			
45	50	86554	65	20			15	T	5.9	GA 70% Qtz 10 GS 15% FeAsS T FeS ₂ 1% Fe ₂ -xS 2% BaSO ₄ 2%	86554	1	.1	54			
50	55	86555	45	35			20	T	7.6	GA 65% Qtz 20% GS 8% FeAsS 5% ZnS T. FeAsS 2% MnO T.	86555	14	1.7	73			
55	60	86556	30	50			20		4.9	GA 45% Qtz 25% GS 20% Py 2% FeAsS 5% Lim T FeS ₂ 3%	86556	4	1.3	67			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow Drift Latitude _____ Departure _____ Hole No. 10374
 Date Drilled May 3, 82 Elevation _____ Bearing _____ Page No. 2 Of 2
 Casing Depth 10 Overburden Depth 10-15 Length of Hole 110 Dip 57°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Gmst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Gmst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Al (wt%)	Ag. (oz/ton)	Pb. (%)	Zn (%)
60	65	86557	15	75			10	T	7.3	GG 50% Qtz 20% FeAs 7% SS 20% FeS 20% Fe-x S 1% MnO ₂ T.	86557	5	2.1	75				
65	70	86558	15	80			5		5.6	GG 35% Qtz 15% FeS 20% FeAs 20% SS 15% MnO ₂ T. Fe-x S T.	86558	21	.4	72	.006			
70	75	86559	25	55			20		4.8	GG 50% Qtz 15% FeAs 10% SS 20% Fe-x S T. FeS 5% Lim T.	86559	5	.4	66				
75	80	86560	45	40			15	T	5.5	GG 60% Qtz 10% SS 10% FeAs 8% FeS 7% Lim T. Fe-x S T. MnO ₂ 1% GS 3%	86560	1	.1	56				
80	85	86561	35	30			30	S	4.7	GG 60% Qtz 10% SS 10% FeS 10% FeAs 5% Lim T. Fe-x S 3% MnO ₂ 2%	86561	1	.4	49				
85	90	86562	40	25		10	20	S	7.2	GG 40% Qtz 20% SS 15% FeS 15% FeAs 5% Lim 2% MnO 3% Fe-x S T.	86562	11	1.0	63	.010			
90	95	86563	45	50			5	T	9.6	GG 50% Qtz 20% SS 10% FeS 5% Gmst 3% Lim 3% MnO ₂ 2% FeAs 5%	86563	13	.5	67				
95	100	86564	50	40			10	T	6.9	SS 20% Qtz 20% GG 50% Gmst 5% FeS 3% FeAs 2% Lim T.	86564	1	.2	73				
100	105	86565	60	35			5	T	4.6	GG 40% Gmst 20% SS 25% Qtz 10% FeS 5% FeAs 5% MnO ₂ T.	86565	2	.3	63				
105	110	86566	65	20		5	10	T	4.3	Qtz 30% FeS 20% GG 20% FeAs 5% SS 15% Gmst 10%	86566	21	1.8	67	.006			

76

091049

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location SNOW DRIFT Latitude 68°54' 33" N Departure 165,609.13 W Hole No. 10375
 Date Drilled May 3, 82 Elevation 2789.17 Bearing 345 Page No. 1 Of 3
 Casing Depth 10' Overburden Depth 10-15' Length of Hole 140' Dip 65°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Au (oz/l)	Ag. (oz/ton)	Pb. (%)	Zn (%)
0	10	86519	75		5	5	15		8.1	GQ 80% Qtz 10% ZnS 2% Grnst 5% GS 2% BaSO ₄ 1% Lim T. SST. FeAsS T. Fe ₂ O ₃ T.	86519	128	3.2	68				
10	15	86520	55		15	T	25	5	9.9	Qtz 85% FeAsS 3% SS 2% GQ 5% Grnst 1% Lim 1% CaCO ₃ 1% BaSO ₄ 1% ZnS 1%	86520	45	1.2	56				
15	20	86521	70		10		20	T	8.1	Qtz 70% GQ 20% Py 2% FeAsS 4% GS 3% CaCO ₃ 1% PbS T.	86521	49	.3	30				
20	25	86522	85		5		10	T	8.9	GQ 70% Qtz 25% GS 2% FeAsS 2% ZnS 1% Py 2% SS, FeCO ₃ , Lim, + BaSO ₄ T.	86522	41	.6	22				
25	30	86523	65	5	5		20	5	7.5	Qtz 60% GQ 30% Py 2% FeAsS 5% Fe, x S T. Lim 2% SS 2%	86523	46	.4	33				
30	35	86524	55	T	10		35	T	8.6	Qtz 45% GQ 45% Py 2% FeS ₂ 3% FeAsS 4% Fe, x S 1% SS. T.	86524	38	.7	94				
35	40	86525	65		5		30		6.7	GQ 65% Qtz 15% Fe, x S 8% Grnst 5% SS 2% FeAsS 2% GS 2% Py 1%	86525	43	.4	61				
40	45	86526	50	5	5		40		6.9	GQ 50% Qtz 25% Fe, x S 10% Py 5% FeS ₂ 5% BaSO ₄ 3% FeAsS 2% SS. T.	86526	24	.2	49				
45	50	86527	60	T	5		35		7.7	Qtz 60% Fe, x S 15% GQ 15% FeAsS 3% Py 5% GS 2%	86527	30	.3	36				
50	55	86528	65	10	5		20		9.8	Qtz 60% FeAsS 20% GQ 10% GS 5% Py 3% Fe, x S 2%	86528	75	.6	91	.016			
55	60	86529	65	25	T		10		9.9	FeAsS 25% Qtz 45% GQ 10% Fe, x S 10% Py 5% GS 5%	86529	39	.1	81	.008			

UNITED KENO HILL MINES LTD.

OVERBURDEN DRILL HOLE LOG

Location Snow D.A.F.T Latitude _____ Departure _____ Hole No. 10375
 Date Drilled May 3 / 12 Elevation _____ Bearing _____ Page No. 2 Of 3
 Casing Depth 10' Overburden Depth 10-15' Length of Hole 140' Dip 65°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)		Sample No.	Geochemical Results				Assay Results			
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim	grams			Pb. (ppm)	Ag. (ppm)	Zn (ppm)	A ₊ o/t	Ag. (oz/ton)	Pb. (%)	Zn (%)	
60	65	86530	30	60			10		3.7	GQ 65% GTZ 15% FeAsS 8% Py 2% SS 3% GS 5% Fe ₂ S 2% Lim T	86530	42	.3	171					
65	70	86531	30	70					6.6	GQ 60% GTZ 20% FeAsS 10% Py 5% Fe ₂ S T GS 5%	86531	26	.1	55					
70	75	86532	25	60			15		5.3	GQ 40% GTZ 30% FeAsS 10% BaSO ₄ 2% GS 8% FeS ₂ 8% Fe ₂ S 2%	86532	21	.1	31					
75	80	86533	40	40			20		4.1	GTZ 35% FeAsS 20% FeS ₂ 15% GQ 20% Fe ₂ S 3% GS 7%	86533	18	.1	32	.010				
80	85	86534	40	60					4.5	GTZ 40% FeAsS 23% FeS ₂ 15% GQ 10% GS 4% 20S T Fe ₂ S 1%	86534	28	.1	54	.005				
85	90	86535	50	50			T		7.2	GTZ 65% FeAsS 10% FeS ₂ 10% GQ 11% BaSO ₄ 4%	86535	30	.3	43					
90	95	86536	60	40			T		4.8	GTZ 45% GQ 25% FeAsS 15% FeS ₂ 10% BaSO ₄ 1% GS 3% Fe ₂ S 1%	86536	52	.1	73					
95	100	86537	30	70					4.3	GQ 50% GS 20% GTZ 20% FeAsS 5% FeS ₂ 4% Fe ₂ S 1% BaSO ₄ T	86537	25	.1	57					
100	105	86538	35	65					7.4	GQ 45% GTZ 25% GS 20% SS 2% FeAsS 4% FeS ₂ 4%	86538	32	.1	64					
105	110	86539	50	50					4.9	GQ 30% GTZ 30% GS 25% FeAsS 8% FeS ₂ 7% Lim T	86539	24	.1	42					
110	115	86540	35	65					8.7	GQ 35% GS 30% GTZ 20% FeAsS 10% FeS ₂ 5%	86540	26	.1	37					

UNITED KENO HILL MINES LTD.

Location Santa Delfa

Date Drilled may 3. 82

Casing Depth 10

Latitude

Elevation

Overburden Depth 10.5'

Departure

Bearing

Length of Hole 240

Hole No.

Page No.

Dip 65°

G.Q. Grey Quartzite; G.S. Graphite Schist; S.S. Sericite Schist; Grnst. Greenstone; Qtz. Quartz; Lim. Limonite; Py. Pyrite; Pbs. Galena; ZnS Sphalerite

Footage		Sample No.	Coarse Material (%) (+14 mesh)						Panning Concentrate Mineral Content (%)	Sample No.	Geochemical Results				Assay Results		
From	To		G.Q.	G.S.	S.S.	Grnst.	Qtz.	Lim			grams	Pb. (ppm)	Ag. (ppm)	Zn (ppm)	Ac. oz/t	Ag. (oz/ton)	Pb. (%)
115	120	86541	20	80					4.4	GS 30% GQ 30% QTZ 25% FeAsS 10% FeS ₂ 5% Fe ₂ S ₃ T	86541	23	1	45			
120	125	86542	15	85					3.7	GS 40% QTZ 20% GQ 30% FeAsS 7% FeS ₂ 3% Fe ₂ S ₃ T	86542	15	1	70			
125	130	86543	T	100					4.2	GS 30% GQ 30% QTZ 25% FeAsS 10% FeS ₂ 5% Fe ₂ S ₃ T	86543	24	1	73			
130	135	86544	15	85			T		6.3	GQ 30% GS 25% QTZ 20% FeAsS 20% FeS ₂ 5%	86544	25	1	72			
135	140	86545	15	75			10		6.1	QTZ 30% GS 25% GQ 25% FeAsS 10% FeS ₂ 5% Fe ₂ S ₃ 3% Grnst 2%	86545	45	2.2	54			