MAP NO.:
115 O 14

ASSESSMENT REPORT X

PROSPECTUS

CONFIDENTIAL X

OPEN FILE

DOCUMENT NO: 092969

MINING DISTRICT: Dawson

TYPE OF WORK: Trenching, Geochemical
Rotary Drilling
Geological Mapping

REPORT FILED UNDER: Arbor Resources Inc.

DATE PERFORMED: June 6 - December 13, 1990

DATE FILED: July 5, 1991

LOCATION: **LAT.:** 63°53'N

LONG.: 139°15'W

AREA: Lone Star Property

VALUE $: 538,024.90

CLAIM NAME & NO.: DE, DN, ND, RJ, RON, VI, plus Crown Grants

*** DUE TO SIZE OF CLAIM BLOCK CHECK OWNERSHIP RECORDS FOR MOST ACCURATE RECORD OF CLAIM INFORMATION.**

WORK DONE BY: Scott Tomlinson

WORK DONE FOR: Arbor Resources Inc.

DATE TO GOOD STANDING:	

REMARKS: # 115 O - Lone Star Property
The company conducted an extensive exploration program in order to explore for high grade quartz veins and to further delineate a gold anomaly previously discovered near the Lone Star Mine. A total of 308 soil samples, 40 trenches, and 45 reverse circulation rotary drill holes were undertaken. A intensive geophysical program was also run but the results were never approved for assessment credit because of problems encountered by the consultant. The rotary drilling delineated a possible low grade bulk tonnage gold deposit but more work is required to test extent of deposit.

YUKON ASSESSMENT REPORT

OFFICE OF THE REGIONAL MINERAL RECORDER
JUL 12 1991
WHITEHORSE
YUKON TERRITORY

092969

PROPERTY: LONE STAR

NTS MAP SHEET: 115O/14

LATITUDE: 63°53' N LONGITUDE: 139°15' W

CLAIMS AND GRANT NUMBERS WORKED:

LOT 86,104,408,409,410,534	
DE 11,12,13	YA552260,261,262
DN F	YA47088
DN 2,15,16,17,18,20,26	YA32784,950,951,952,953,955,961
DN 32,33	YA47604,605
ND 2,4,6,8,9,10,11	YA49725,727,729,731,732,733,734
RJ 1	YA64126
RON 1,3,5,9,11,17,19	YA10300,302,304,308,310,316,318
VI 1,43	YA55285, YA65550

OWNERS OF PROPERTY: Arbor Resources Inc.

ADDRESS: #1000 - 675 West Hastings Street
Vancouver, B.C.
V6B 1N6

TELEPHONE: (604) 685-2222

OPERATORS: Arbor Resources Inc.

TYPE OF WORK: Geological mapping, geochemical sampling, trenching, rotary drilling.

DATES WORK WAS DONE: JUNE 6 - DECEMBER 13, 1990.

AUTHOR OF REPORT: Scott Tomlinson, B.Sc.

RECEIVED
JUN 21 1991
MINING RECORDER'S OFFICE
DAWSON, Y.T.

LIST OF PERSONNEL:
Scott Tomlinson, Hastings Management Corp.
Christian Marriott, Hastings Management Corp.
Larry Johnson, Hastings Management Corp.
Allan Whalley, Hastings Management Corp.
Jerry Bryde, Hastings Management Corp.
Jim M°Faull, Aurex Exploration
Art Troup, Archean Engineering Ltd.
Ralph Gonzalez, Adder Exploration and Development Ltd.

GEOLOGICAL AND GEOCHEMICAL REPORT ON THE LONE STAR PROPERTY

DAWSON MINING DISTRICT, YUKON

SUMMARY

The Lone Star property is owned 100 % by Arbor Resources Inc. and is located in the Klondike Mining District of northwestern Yukon Territory, approximately 14 km south-southeast of Dawson City. The claims are situated along the valleys of Bonanza and Eldorado Creeks. These claims are adjacent to and overlie some of the most productive placer depositss in the Klondike.

The claims are underlain by the Klondike Series, a unit of quartzofeldspathic mica schists. Graphitic schists, possibly related to thrust faulting, also occur on the property. Both of these lithologies are cross-cut by Tertiary dykes.

Mineral exploration in the Klondike has occurred since the late 1800's, but has concentrated on placer deposits. Lode gold exploration has consisted mostly of individual efforts to find high grade vein structures, although a few larger programs involving trenching and drilling have also been carried out. The most successful venture was the Lone Star Mine, which produced 7,650 tonnes grading 0.148 oz/ton between 1912 and 1914. In 1980, Dawson Eldorado Gold Explorations Ltd. started a comprehensive exploration program in the vicinity of the abandoned Lone Star mine. Geophysical and geochemical surveys, trenching, and drilling resulted in several significant anomalies.

In 1983, several companies of the Hughes Lang Group began to acquire and explore ground in the Klondike for hard rock gold potential. Work included multiple geological, geochemical, and ground geophysical surveys, two airborne geophysical surveys, trenching, and diamond and rotary drilling.

The 1990 program was designed to prospect for high grade quartz veins and to further delineate a gold anomally previously discovered near the Lone Star mine. To these ends the following work was performed: 35.9 1km of Induced Polarization, 308 soil samples, 40 trenches, and 45 reverse circulation rotary drill holes totalling 2,796 m.

Work to date indicates two major types of gold deposits. Mesothermal auriferous quartz veins are known to occur in several areas on the property, but they are discontinuous and of limited economic potential. The other deposit type is more enigmatic, but has a much larger economic potential. One (or more) gold bearing horizon occurs within the Klondike Series, and possibly connects anomallies found at the Lone Star mine and near Gay Gulch. This horizon is probably genetically related to either a thrust fault or represents a primary gold layer.

Further work should concentrate on developing the Lone Star area as a possible low grade - bulk tonnage deposit. Specifically, the continuation of the pattern rotary drill program started in 1990 is recommended, although at a wider spacing to determine if a large tonnage potential exists. A similar drill program in the Gay Gulch area is a second priority.

TABLE OF CONTENTS

	Page
SUMMARY	ii
TABLE OF CONTENTS	iv
FIGURES, TABLES AND APPENDICES	v
1. INTRODUCTION	1
1.1 LOCATION AND ACCESS	1
1.2 PHYSIOGRAPHY AND CLIMATE	3
1.3 CLAIM INFORMATION	4
1.4 HISTORY AND PREVIOUS PRODUCTION	5
1.5 PREVIOUS WORK	6
1.6 WORK COMPLETED IN 1990	8
2. GEOLOGY	9
2.1 REGIONAL GEOLOGY	9
2.2 PROPERTY GEOLOGY	11
2.3 ECONOMIC GEOLOGY	13
3. GEOPHYSICS	15
4. SOIL SAMPLING	17
5. TRENCHING	19
6. ROTARY DRILLING	24
7. CONCLUSIONS	34
8. REFERENCES	36
9. STATEMENT OF PROFESSIONAL QUALIFICATIONS	38
10. COST STATEMENT	39

FIGURES

Figure 1: LOCATION MAP 2

Figure 2: COMPILATION MAP .....POCKET

Figure 3: REGIONAL GEOLOGY OF THE KLONDIKE MAP 10

Figure 4: VIOLET V1 TRENCH MAP 21

Figure 5: VIOLET V2 TRENCH MAP 22

Figure 6: 27 PUP TRENCH MAP .....POCKET

Figure 7: 90R8-24 DETAILED PLAN 29

Figure 8: 90R8,9,10,17,18,19 PROFILE DRILL RESULTS 30

Figure 9: 90R11-16 PROFILE DRILL RESULTS 31

TABLES

Table I : CLAIM STATUS 4

Table II : TRENCHING DATA 19

Table III : TRENCH ASSAYS > 0.1 oz/ton Au 23

Table IV : ROTARY DRILLING DATA 24

Table V : ROTARY DRILL ASSAYS > 0.01 oz/ton Au 26

Table VI : ROTARY DRILL ASSAYING TECHNIQUE COMPARISONS .. 32

APPENDICES

APPENDIX I : SOIL SAMPLES CERTIFICATES OF ANALYSIS

APPENDIX II : TRENCHES AND SAMPLES LISTING

APPENDIX III: TRENCH SAMPLES CERTIFICATES OF ANALYSIS

APPENDIX IV : ROTARY DRILL LOGS

APPENDIX V : ROTARY DRILL SAMPLE CERTIFICATES OF ANALYSIS

GEOLOGICAL AND GEOCHEMICAL REPORT ON THE LONE STAR PROPERTY

DAWSON MINING DISTRICT, YUKON

1. INTRODUCTION

This report covers the field program completed between June 6 and December 13, 1990 under the supervision of Project Geologist Scott Tomlinson of Hastings Management Corp.

1.1 LOCATION AND ACCESS

Dawson City is the principal population and supply center of northwestern Yukon. It can be reached via the two-lane, all-weather, Klondike Highway from Whitehorse on the Alaska Highway, a distance of 535 km. Dawson City is presently served by scheduled flights from Whitehorse where connections to Vancouver or Edmonton are available.

The mineral claims are located 14 km south-southeast of Dawson City in the Klondike Mining District as shown in Figure 1. The claims overlie the valleys of Bonanza and Eldorado Creeks and are plotted on Figure 2.

Relief is on the order of 650 m (2100 ft) with elevations ranging from 500 m (1600 ft) to 1173 m (3851 ft). Terrestrial coordinates for the center of the claim block are: 63° 53' North Latitude, 139° 15' West Longitude.

Access to the property is provided by the Bonanza Creek Road which connects with the Klondike Highway approximately 3 km east of Dawson City. The Bonanza Creek Road branches at the former site of the town of Grand Forks with roads going along both Bonanza and Eldorado Creeks. Several recently completed unimproved roads provide good access for 4x4 trucks within much of the claim group.

ARBOR RESOURCES INC.


LONE STAR PROPERTY

DAWSON MINING DISTRICT, Y.T.

LOCATION MAP

BY: S.T./p.s.
DATE: MAY, 1991

FIGURE: 1



1.2 PHYSIOGRAPHY AND CLIMATE

The Klondike region forms a part of the Yukon Plateau or upland surface which, locally, occupies an area between the Pacific and Alaskan Mountain Ranges to the west and northwest, the Ogilvie Mountains to the northeast and east, and the Dawson Range to the southwest and south.

The region is a thoroughly dissected upland which was elevated at one period into a high plateau. This plateau was subsequently deeply eroded by a multitude of small streams tributary to the main water courses. A secondary uplift resulted in further deepening of the valleys from 150 m to 200 m. Portions of the old valley-bottoms, still covered with thick accumulations of gravel forming terraces of varying width, border the newer valleys (McConnell, 1905; also, G.S.C. Mem.84, 1957). Today, the valleys are flat and wide in their lower reaches, but gradually narrow toward their head waters into steep-sided gulches ending in broad, amphitheater-shaped bowls.

The Klondike proper occupies an area of approximately 30 by 60 km. The drainage is dominated by the northerly flowing Yukon River and its westerly flowing tributaries, the Klondike River on the north and the Indian River on the south. Elevations within the Klondike range from 320 m (1050 ft) at Dawson City to 1295 m (4048 ft) at the top of King Solomon Dome, a span of approximately 915 m (3000 ft). The principal gold-producing streams of the Klondike originate near, and radiate in a general way from, King Solomon Dome, flowing eventually into the Klondike River on the north and the Indian River on the south and thence into the Yukon River.

The Klondike region was not glaciated and, as a result, the deeply weathered, pre-glacial, gently rolling upland surface has been preserved. A thick covering of decomposed schist, usually intermingled with slide rock, mantles the side hills nearly everywhere. On the ridges the covering is less; the schists occasionally project above surface or crop out along the sides of the steeper hills.

The region has a northern continental climate, characterized by low precipitation and a wide temperature range. The winters are intensely cold and long, while the summers, although short, are pleasant with cool nights and warm days. Because of the land form there is a tendency for local micro-climates to develop at the bottom of steep valleys which involves higher summer maxima and lower winter minima than are recorded in Dawson City. Precipitation is only about 30 cm (12 inches) per year with more rain in summer than snow in winter. Most of the mountain ridges are free of snow by mid-July, but frost may occur at any time during the summer. As a rule, precipitation is so low that shortages of water for placer mining are sometimes experienced.

Vegetation is mixed boreal forest and tundra. Immature and stunted stands of aspen, balsam, poplar, and birch are present in the valley bottoms and are beginning to reclaim the older mining areas. Softwood timber consisting mainly of white and black spruce are limited to slopes and ridge tops.

1.3 CLAIM INFORMATION

The property is located in the Dawson Mining District of northwestern Yukon Territory and is comprised of 285 located quartz claims and 14 Crown Granted claims covering an area of approximately 63 km^2, as shown on Figure 2. The claims are 100% owned by Arbor Resources Inc. Disposition of the claims is as follows in Table I:

TABLE I
CLAIM STATUS

CLAIMS	GRANT NUMBERS	ANNIVERSARY
AC 1-10	YA64270-YA64279	DECEMBER 31
AC 11	YA64281	DECEMBER 31
AC 12-35	YA65627-YA65650	DECEMBER 31
ARGYLE	LOT 223	CROWN GRANT
CATO	LOT 535	CROWN GRANT
CIM 1-4	YA64519-YA64522	DECEMBER 31
DE 1-14	YA55250-YA55263	DECEMBER 31
DN 1-2	YA32783-YA32784	DECEMBER 31
DN 3-9	YA47890-YA47896	DECEMBER 31
DN 10	YA47082	DECEMBER 31
DN 11-26	YA32946-YA32961	DECEMBER 31
DN 27-31	YA47083-YA47087	DECEMBER 31
DN 32-33	YA47604-YA47605	DECEMBER 31
DN F	YA47088	DECEMBER 31
DN 1F-2F	YA47090-YA47091	DECEMBER 31
ESTER EDNA	LOT 106	CROWN GRANT
LONE STAR	LOT 410	CROWN GRANT

CLAIMS	GRANT NUMBERS	ANNIVERSARY
ND 1-22	YA49724-YA49745	DECEMBER 31
ND F	YA47089	DECEMBER 31
NEW BONANZA	LOT 408	CROWN GRANT
NEW BONANZA NO.2	LOT 424	CROWN GRANT
NIOBE FRACTION	LOT 409	CROWN GRANT
PORPHYRY LODE	LOT 104	CROWN GRANT
REX 1-51	YA84183-YA84233	DECEMBER 31
RJ 1-32	YA64126-YA64247	DECEMBER 31
RJ 39-60	YA65595-YA65616	DECEMBER 31
RJ 62-63	YA65618-YA65619	DECEMBER 31
RJ 65-70	YA65621-YA65626	DECEMBER 31
RON 1-40	YA10300-YA10339	DECEMBER 31
SWASTIKA	LOT 533	CROWN GRANT
THISTLE	LOT 536	CROWN GRANT
UDAS	LOT 534	CROWN GRANT
VI 1-15	YA55285-YA55299	DECEMBER 31
VI 16	YA65523	DECEMBER 31
VI 18	YA65525	DECEMBER 31
VI 43-44	YA65550-YA65551	DECEMBER 31
VICTORIA	LOT 86	CROWN GRANT
YANKEE GIRL	LOT 105	CROWN GRANT
ZULU CHIEF	LOT 411	CROWN GRANT

1.4 HISTORY AND PREVIOUS PRODUCTION

The Klondike region is well known for the 11 million ounces of placer gold recovered since 1896, over half of which has come from Bonanza and Eldorado Creeks.

The mining of the placer deposits has been accomplished by a succession of methods. Originally, hand miners would shaft down through frozen gravels to "pay zones" near bedrock in the winter and sluice the gravel in the summer; using these techniques over five milllion ounces of gold was recovered. Subsequently, from 1903 to 1966, dredges reworked the streams and recovered an additional five million ounces. Since the dredging ended, bulldozers have been used to push gravel through sluice boxes and have recovered approximately one million ounces of gold.

The earliest known staking for lode deposits was in 1899 on an auriferous quartz vein known as the Corthay Vein (Maclean, 1914). This vein was later mined by the Lone Star Company. At about the same time as the initial staking, numerous other auriferous sulphide-bearing quartz veins were discovered in the region. It appears, however, that little real work was completed on any of the lode prospects until 1910. In 1909, the Lone Star Company Ltd. was formed to explore the Lone Star property, which was the most

promising lode prospect at the time.

Historical accounts show that the Lone Star Company mined 7,650 tonnes grading 0.148 oz/ton Au from the mine site between 1912 and 1914 (Roche, 1916). A 4-stamp mill on Victoria Gulch processed the ore and amalgamation recovered the gold. It appears that sulphides were discarded and only free gold was recovered. The ore was mined without selection from a 105 m long open cut which was up to 10 m wide and 8 m deep. Downward extension of the mineralization was tested by a 7 m deep shaft and a cross-cut 18 m below the open cut. By 1914 there had been 230 m of drifting under the cut, 70 m of which was on the Corthay Vein. In 1914, grades dropped substantially after a fault was encountered and subsequent caving and rising labour costs caused the mine to close.

1.5 PREVIOUS WORK

The area surrounding the Lone Star has been intermittently prospected since the turn of the century. Numerous small pits and trenches on surface showings of quartz float or veins are scattered along the Lone Star ridge and attest to the considerable primitive exploration that took place during the early days of the Klondike.

At the end of World War I, the Lone Star Company was reformed as Consolidated Lone Star Ltd. and resumed work from 1925 to 1929; however, the work was without much success. By 1931, a new adit (190 m long) and raise (30 m) had been driven under the cut to connect the older, caved workings.

Yukon Consolidated Gold Corp. Ltd. optioned the property in 1946-47 and drove a 60 m cross-cut from the 1930-31 underground working for the purpose of exploring the northern end of the open cut. Six churn drill holes totalling 205 m and eight surface trenches were completed, all within 300 m of the north end of the cut. The company attempted to trace the northern extension of the mineralization; however, the results proved inconclusive and the option was terminated. The Lone Star Mine site workings have not been explored substantially since.

In 1960, the property was acquired by Klondike Lode Gold Mines Ltd. This group conducted the first systematic exploration of the area outside of the limits of the old workings. Contour-controlled bulldozer trenching was carried out on various parts of the claim group, and overburden samples from the trenches were panned and sluiced to determine gold content. Results were encouraging and six diamond drill holes totalling 238 m were drilled on the Eldorado Creek side of the claims in 1962. The project was abandoned in 1962 due to lack of funds.

In 1979-80, Klon Explorations Company Ltd. carried out VLF-EM and magnetometer surveys across Eldorado Creek at French Gulch. This was followed by minor diamond drilling in an attempt to locate what were believed to be auriferous structures beneath the creek. A coincident program involving reverse circulation drilling in the creek to locate buried placer gold was also conducted. This project was also hampered by lack of funds and was terminated in 1980.

Dawson Eldorado Gold Explorations Ltd. acquired the present land position between 1980 and 1985 and were the first to attempt to understand the complex geological, geochemical, and mineralogical relationships involved with the property. In 1980, a resistivity survey was conducted over the Lone Star workings with only limited success (permafrost being the main problem). During 1981, much of the central portion of the claim group was soil sampled at 120 m stations using conventional sampling techniques, and several bulldozer trenches were sampled. In 1984, the soil sampling grids were extended and additional bulldozer trenches were excavated. In 1985, six rotary drill holes, totalling 168 m, were drilled in the vicinity of anomalous zones as outlined in the 1960 and 1981-84 programs.

Exploration continued by Mark Management Ltd. for Arbor Resources and an extensive program was completed during 1986 and early 1987. This program included 86 line-kilometres (1km) of magnetometer, 3 1km of VLF-EM16, and 31.3 1km of Induced Polarization (I.P.) surveys. Reconnaissance work included 250 soil and 42 rock chip samples. Targets outlined by this ground work were later drilled, and a total of 2,617 m of diamond and 2,807 m of rotary drilling were completed. Diamond drill holes intersected disseminated sulfide horizons which contained gold values up to 0.357 oz/T. These were commonly bound by wider zones of lower grade gold content.

A low level helicopter supported airborne geophysical survey was carried out by Aerodat Limited of Mississauga, Ontario, during December 1986 and January 1987. Ground follow-up included 10 1km of VLF-EM and 18 1km of I.P. surveying. An extensive grid was established over the ridge between Upper Bonanza and Eldorado Creeks, with 1588 soil samples and 29 rock samples being collected. Targets outlined by these surveys were eventually trenched and drilled, with 23 bulldozer trenches, 1,690 m of diamond drilling and 4,063 m of rotary drilling being completed. Many gold bearing intersections were obtained and two main zones of interest outlined: near Gay Gulch, and near the old Lone Star mine workings. One trench near the former zone, 87TR08, returned an assay of 7.086 oz/t. Geological interpretation indicates that these two zones are related, although the connection between them is uncertain.

In 1988, 18 1km of VLF-EM and 9 1km of Induced Polarization geophysical surveying was done. In addition, 1,437 "B" horizon soil samples on four grids and 61 rock chip samples were taken. This was followed by 39 bulldozer trenches and a further 1,352 rock chip samples.

In 1989, 19 soil, 32 heavy mineral concentrate, and 90 rock chip samples were taken. Based on this sampling, 21 trenches (with a further 88 rock chip samples) were excavated.

1.6 WORK COMPLETED IN 1990

Field work completed by Hastings Management Corp. for Arbor Resources Inc. was carried out from June to December, 1990. This work included:

(1) 35.9 1km of Induced Polarization and Resistivity surveying carried out over seven grids.
(2) 308 soil samples carried out over four grids.
(3) 40 bulldozer or excavator trenches with 629 rock chip samples
(4) 45 reverse circulation rotary drill holes totalling 2,796 m, with 1,835 samples analyzed.

2. GEOLOGY

2.1 REGIONAL GEOLOGY


Bedrock exposures amount to less than one percent of the area and are generally confined to gulches, recent landslide areas, and road cuts. The Klondike district was first mapped by Bostock (1942), followed by Green and Roddick (1961), Metcalfe (1981), and Debicki (1984 and 1985), and most recently by Mortensen (1990). Bedrock in the Klondike area is generally grouped into five major units which are, from oldest to youngest, the Nasina Series, the Klondike Series, the Moosehide Assemblage, early Tertiary volcanics/ volcanoclastics and Tertiary intrusives. An overview of the geology is shown in Figure 3.

Rocks of the Nasina Series consist of graphitic schists, graphitic quartzites and siliceous marbles with minor chlorite schists and muscovite schists. These rocks have been metamorphosed to grades ranging from upper greenschist to middle amphibolite facies, and appear to have been derived from marine offshore sedimentation similar to that found along continental shelves. Field studies indicate that the Nasina Series pre-dates the Klondike Series; thus, an age of formation in the late Carboniferous to mid-Permian is likely.

Most litologies exposed in the Klondike district belong to the Klondike Series. These are quartzofeldspathic schists containing varying amounts of chlorite, muscovite and sericite. They have undergone upper greenschist to middle amphibolite grade metamorphism and at least four separate deformational events. This series appears to represent water lain arkosic sediments and rhyolitic to andesitic tuffs derived from a succession of stratovolcaniclastic venting. The minimum estimated age of formation of the Klondike Series lies within the middle Permian. Metcalfe claims that the Klondike formation has a conformable basal contact with the structurally underlaying rocks of the Nasina Series, although field studies indicate a low angle thrust contact.

To the west the Klondike Schists are in contact with a blocky weathering, granitic textured, biotite-quartz-feldspar orthogneiss. Thin section studies of these rocks indicate that they were originally medium to coarse grained plutonic rocks of granodiorite to quartz diorite composition, and may represent the magmatic source for those tuffs now comprising the Klondike Series. Zircon dating of these rocks indicates an age of emplacement between Late Devonian and early Carboniferous (Mortensen).

The age of metamorphism of the Klondike and Nasina Series formations has been placed in the Late Triassic (Metcalfe).



LEGEND

- 1 QUARTZ FELDSPAR PORPHYRY
- 2 CLASTIC SEDIMENTS AND VOLCANICS

MOOSEHIDE ASSEMBLAGE

- 3 MASSIVE GREENSTONE AND DIABASE
- 4 SERPENTINITE AND ALTERED ULTRAMAFIC ROCKS

KLONDIKE SERIES

- 5 MUSCOVITIC QUARTZITE
- 6 MUSCOVITE AND QUARTZ MUSCOVITE SCHIST
- 7 CHLORITIC SCHIST
- 8 MUSCOVITIC AND CHLORITIC QUARTZITE AND FELDSPATIC QUARTZITE

NASINA SERIES

- 9 CARBONACEOUS PHYLLITE AND SCHIST
- 10 METAGRANODIORITE

S S FAULT (NATURE UNCERTAIN)

NOTE: MODIFIED FROM MORTENSEN, 1985

ARBOR RESOURCES INC.

LONE STAR PROPERTY
DAWSON MINING DISTRICT, Y.T.

REGIONAL GEOLOGY OF THE KLONDIKE

BY: S.T./p.s.
DATE: MAY, 1991

FIGURE: 3

Structurally overlying the rocks of the Klondike and Nasina Series are occurrences of greenstone and altered ultramafics belonging to the Moosehide Assemblage. Included in the ultramafic unit are a variety of rock types including massive, partially serpentinized peridotite (harzburgite), massive to sheared serpentinite, silica-carbonate altered serpentinite, and talc-carbonate schist. Massive greenstone and strongly altered, fine to medium grained diabase are exposed in several steep bluffs in the vicinity of Dawson. These rocks are unfoliated and form part of a slab of greenstone and serpentinite that underlies the southwestern slope of the Midnight Dome east of Dawson. Occurrences of greenstone and ultramafic rocks are commonly found along the sheared contact between the Klondike and Nasina Series rocks. They are thought to represent exotic slices of uncertain origin (ophiolite?), structurally emplaced during thrust faulting.

Gently folded andesitic volcanics and clastic sediments belonging to the Carmacks suite are present in the Last Chance Creek area. These rocks were considered to be early Tertiary in age; however, recent work on similar rocks in the Indian River area suggests that these rocks are middle Cretaceous in age (Mortensen, 1986).

Intrusive rocks are present as numerous dykes and sills ranging in nature from diabase to rhyolite. These have been dated as Tertiary to early Quaternary in age. Larger Tertiary intrusive bodies are rare in the Klondike except for a rhyolite porphyry stock that outcrops along Hunker Creek. Isotopic dating (Debicki) indicates that the porphyry is approximately 50 to 60 million years old.

The regional structure is dominated by the Tintina Thrust Fault, which is only 15 kms away. Much of the faulting, deformation, and lithology trends to the northwest, parallel the Tintina.

2.2 PROPERTY GEOLOGY

The geology of the property was chiefly determined from the examination of trenches, road cuts and diamond-drill core, and the interpretation of geophysical information, as there are few outcrops. The property is underlain almost entirely by facies of the Klondike Schist. Lithological and structural continuity has been disrupted by folding and faulting. Age relationships of the various lithologies are largely unknown since tops cannot be determined and contacts are either gradational, interlayered, or faulted.

There are four main lithologies on the property: quartzofeldspathic mica schists, micaceous quartzites, carbonaceous schists, and intrusives.

The dominant rock type are well-foliated, rust-yellow weathering, light grayish-green, undifferentiated chloritic schists, muscovite schists, and quartz-sericite schists. The primary bedding of these schists is believed to correspond with schistosity, which has a general attitude of 140°/30SW to the west of the Lone Star ridge, and 140°/30NE to the east of the ridge. This foliation parllels the regional stratigraphic trends.

Underlying this unit is a sequence of quartzites, with varying amounts of muscovite and commonly up to 15% small blue quartz eyes. These eyes may represent crystals, tuff fragments, or porphyroblasts.

The carbonaceous schists are enigmatic as to their genesis. They were originally thought to be stratigraphic, as there are gradational contacts between the graphite and the mica schists. However, the graphite does not appear to be conformable with the surrounding schists, and may represent a thrust plane. If the graphite does represent a thrust fault, the carbon may have been deposited by hydrothermal solutions moving along the thrust plane. Alternatively, the carbon may represent slices of the underlying Nasina Series caught up in the thrust.

Intruding the three lithologies mentioned above are a series of north to north-west trending quartz-feldspar porphyry and diabase dykes. The porphyry is anomalous in arsenic, and is rhyolitic in areas. The diabase contains magnetite, showing up as a magnetic low in geophysical surveys, and may be basaltic. These dykes are penecontemperanous, as they cross-cut, and appear to have been implaced either along or adjacent to major faults.

The local geology is complicated by a series of northwest trending antiforms and synforms. Interpretation of these features indicates that the schists are folded into a broad northwest trending anticline, with the hinge roughly following the ridge between Upper Bonanza and Eldorado Creeks. French Gulch and Bonanza and Eldorado Creeks are probably recent high angle faults. There is also the possiblility of a low angle (i.e. thrust) fault which parallels Eldorado Creek.

The target horizon for gold within the Klondike schists is outlined as a unit of quartz-muscovite schist which contains some combination of pyrite, arsenopyrite, possibly mariposite, or grey coloured carbonate blebs (diamond drill core observations). The gold bearing units intersected near the old Lone Star mine may by genetically related to those intersected near Gay Gulch.

2.3 ECONOMIC GEOLOGY

With few exceptions, exploration of the area has always focused on the placer deposits. Since production began in 1896, the Klondike district southeast of Dawson City has produced over 11 million ounces of placer gold.

The little previous hard rock exploration has concentrated on exploring quartz deposits. Quartz occurs in two forms: foliaform and discordant. The foliaform quartz forms pods and lenses ranging in thickness from 1 cm to over 1 m within the schists, and are probably the result of metamorphic segregation of the protolithologies. The discordant or vein quartz varies from less than 1 cm to over 2 m in thickness, has a general attitude of 140°/40NE, and is mesothermal in origin (as determined by fluid inclusion work). Very similar veins near the property have been age dated at 138 m.y.a. (Mortensen, 1990). Carbonate is a common constituent, galena may be present, and a pyrite selvage often forms. Pyrite may also form stringers and veinlets by itself. Although there has been exploration on both types of quartz, only the discordant veins carry gold; the gold is almost always associated with galena and/or pyrite. The pyrite stringers and veinlets also may have gold.

The earliest reported study on the lode deposits was by Cairnes (1911) in which he briefly described the development work on some of the more promising quartz veins in the district. One property (Boulder Lode), near the head waters of Victoria Gulch, a tributary of Bonanza Creek, was considered the source of the gold in the gulch, and along part of Bonanza Creek. The principal vein, with its associated surrounding mineralized zone, varied in thickness from 1 to 3 m and was traceable along strike for 120 m with a possible extension of another 200 m. Cairnes failed to indicate the grade of this deposit, but he suggested that the gold content was in excess of 0.25 oz/T. Reserves in this vein indicated approximately 1,500 tons per meter containing about 400 ounces per meter. McConnell (1905) reported that ten 150 m wide placer claims along Victoria Gulch and Bonanza Creek produced over 200,000 ounces: the implication is that all the gold recovered in the placers could not have come solely from this vein.

Diamond drilling in 1986 of geochemical and geophysical targets near the Boulder Lode intercepted several sulphide rich horizons within quartz-muscovite and chloritic muscovite schists. Fire assays of samples from these zones detected gold values up to 0.357 oz/T. None of these gold bearing horizons were related to any quartz veining as studied by Cairnes. Rotary drilling during January and early February 1987 intersected several gold bearing zones between Oro Grande and Gay Gulches. Fire assays of samples from these zones detected gold values up to 0.230 oz/T at depths ranging from 6 m to 145 m.

Recent trenching and drilling has further confirmed and expanded the gold bearing horizons as outlined in previous drilling near the old Lone Star workings, and between Oro Grande and Gay Gulches.

3. GEOPHYSICS

In 1990, a total of 35.9 line-kilometres (1km) of Induced Polarization (I.P.) and resistivity surveying was done over seven grids. A synopsis of each of these grids follows.

The Boulder Lode grid is located near the old Boulder Lode workings, and consists of 2.82 1km peformed to 10 levels of penetration. This survey was designed to tested for deep anomalies that previous I.P. work did not reach. Although a few anomalies were detected at depth, more importantly a correlation between chargability highs, resistivity lows, and economic drill intersections was observed; this may help in outining future drill targets.

The 7 Pup grid is located on 7 Pup near current placer mining, and consists of 2.85 1km to 10 levels. This was a reconnaissance survey to search for anomallies possibly related to the placer gold. No significant anomallies were detected.

The McKay/O'Neil grid is located along Upper Bonanza Creek between McKay and O'Neil Gulches, and consists of 4.44 1km performed to 10 levels. This survey searched for the source of massive sulphide mineralization observed on the dredge tailings in the vicinity. No anomalies indicating a massive sulphide deposit were detected, suggesting that the mineralization must be very localized.

The Eldorado grid is located along Eldorado Creek between Skookum and Gay Gulch, and consists of 6.78 1km performed to 6 levels along one line. This survey checked for structures that may cross Eldorado Creek. Although no significant structures were found, this line did tie in the following three grids.

The Irish grid is located long Eldorado Creek north of Irish Gulch, and consiststst of 2.07 1km performed to 8 levels. This survey tested for a suspected fault running along Eldorado Creek. The fault was clearly delineated, and may be a future drill target.

The French grid is located at the mouth of French Gulch, and consists of 7.29 1km performed to 8 levels. This survey searched for any anomallies which might explain why the mouth of French Gulch was exceptionally rich in placer gold. Several faults were discovered, but drilling is needed to determine their significance.

Finally, the Oro Grande/Gay grid is located along Eldorado Creek between Oro Grande and Gay Gulches, and consists of 9.65 1km performed to 8 or 10 levels. Again, as in the French grid, this survey searched for anomallies which might explain the very rich placer gold from this area. A number of anomallies exist in this area, including the continuation of the fault delineated at Irish Gulch, but unfortunately drilling done late in the year was not orientated properly to intersect this fault, and further drilling is necessary.

A complete description and interpretation of the geophysical program is contained in a separate report by Geotronics Surveys Ltd., written by David Marks.

4. SOIL SAMPLING

In 1990, a total of 308 soil samples were taken from four different areas, as shown in Figure 2. All samples were taken on ten metre intervals except for the FGBENCH and EL samples, which were taken on 30 m spacings.

Along Victoria Gulch 112 samples were taken along one line starting at 13 Pup and proceeding upstream for 1.12 km. These samples are VG 000N 000W-730W and 750W-1120W; no sample was taken at 740W due to permafrost.

Another line of 143 samples was taken along Gay Gulch, starting at the ridge between Gay and Victoria Gulches. These are GG 000N 000W-1420W.

Near French Gulch, 24 samples were taken on the northern bench. Samples FGRD 180-330 are 16 samples collected along the road going up French Gulch, with the numbers refering to distance from the road/creek intersection. Samples FGBENCH 240S-450S are 8 samples taken along the French Gulch 360E I.P. line, with the numbers refering to the I.P. grid.

The last area sampled was along Eldorado Creek, where 29 samples were taken along the Left Limit (LL) and Right Limit (RL) between Golden and Gay Gulches. The number of the sample is relative to the Eldorado I.P. line. The samples are: EL/LL 6570, 6630-6720, 6780-6900; and EL/RL 6360-6900. The gaps in the sampling on the EL/LL line are due to tailings preventing a sample from being taken.

The VG, GG, and FG samples were sent to Chemex Labs Ltd in North Vancouver. There they were oven dried and sieved to -80 mesh; the coarse fraction was then discarded and the fine fraction pulverised for analysis. Gold was analyzed using the Fire Assay -Atomic Absorption (FA-AA) method, and 32 additional elements were analyzed using the Inductively Coupled Plasma - Atomic Emission Spectrometry (ICP-AES) technique. The EL samples were sent to Northern Analytical Labs Ltd. in Whitehorse, Y.T. for gold assay and Acme Analytical Labs Ltd. in Vancouver for 29 additional elements analysis, using similar techniques to Chemex. The analysis results are listed in Appendix I.

The VG line had several gold anomallies, with sample VG 000N 200W returning a value of 3880 ppb Au. This and the other highly anomalous samples are on strike with the soil geochemical anomally that overlies the Boulder Lode, indicating that the mineralized zone extends at least to Victoria Gulch.

The GG line had only one gold anomally, 725 ppb Au at station GG 000N 140W. Based on previous experience of following up such anomallies, there is probably a small auriferous vein nearby, although none was observed.

The FG samples resulted in two anomalous samples, with 2400 ppb Au being returned from station FGRD 290. When panning was done near the sample location, however, placer gold flakes were recovered, suggesting that the anomalies are due to placer rather than lode gold.

The EL samples had several anomalous values, but as in the FG samples, these may be due to placer contamination.

5. TRENCHING

A total of 40 trenches were excavated on the property for hard rock purposes, as shown in Figure 2. They were made using a Caterpillar D8 bulldozer, with the exception of trenches OG and OGJV which used a Caterpillar 245 excavator.

Most of the trenches were excavated in search of quartz veins, but several were put in to uncover dykes, expose old workings, or explore altered zones. Most of the trenches are located between 27 Pup and Upper Eldorado Creek.

Listed below in Table II are the trenches, their claim location, and their target.


TABLE II
TRENCHING DATA

TRENCH NUMBER	CLAIM	TARGET
90JUN UBON1	DN 33	dyke extension
90JUN 7PUP1	LOT 86	dyke extension
90JUN LSTAR1	LOT 534	dyke extension
90JUN LSTAR2	LOT 408	quartz vein extension
90OG	RON 9	quartz vein
90OGJV	RON 9	quartz vein
90OGTR01	DN 20	quartz vein
90GGTR01	DN 15	quartz vein
90GGTR02	DN 15	quartz vein
90GGTR03	DN 17	quartz vein
90GGTR04	DN 17	quartz vein
90GGTR05	DN 17	quartz vein
90GGTR06	RON 5	quartz vein
90GGTR09	RON 1	quartz vein
90GGTR10	ND 4	surficial lineament
90GGTR11	ND 2	surficial lineament
90GGTR12	DN 17	I.P. anomaly
90GGTR13	RON 5	quartz vein
90GGTR14	DN 18	quartz vein
90GGTR15	DN 18	quartz vein
90GGTR16	DN 18	quartz vein
90GGTR17	RON 3	quartz vein
90GGTR18	RON 3	quartz vein
90GGTR19	RON 3	quartz vein
90GGTR20	RON 3	quartz vein
90GGTR21	RON 3	quartz vein

TRENCH NO.	CLAIM	TARGET
90GGTR22	ND 2	old workings extension
90V1	VI 1	old workings extension
90V2	VI 43	surficial lineament
9027PUPTR01	RON 11	quartz vein extension
9027PUPTR02	RON 11	quartz vein extension
9027PUPTR03	RJ 1	quartz vein extension
9027PUPTR04	RJ 1	quartz vein extension
9027PUPTR01A	RON 11	quartz vein extension
9027PUPSQTR	RJ 1	quartz vein extension
90GAY GULCH CUT	DN 15	quartz vein
90GAY GULCH FGVN	DN 15	quartz vein
90GAY GULCH HEAD	ND 9,10	I.P. anomaly
90DOWSE TRENCH	DN 26	old workings extension
90FGVN EXTN	DN 16	quartz vein extension

The sampling method varied from one trench to another: most trenches systematically chip (grab) sampled; where high grade gold was suspected the trenches were selectively sampled at quartz veins or shear zones; and occassionally no samples were taken if after excavation a trench appeared to have no merit. Detailed drawings of the Violet and 27 Pup trenches are shown in Figures 4 and 5 respectively.

The samples were sent to Chemex Labs Ltd. in North Vancouver, where they were crushed to -200 mesh. Gold was then assayed using the FA-AA method, and 32 additional elements were analyzed using the ICP-AES technique. Some of the samples were sent to Northern Analytical Labs Ltd. in Whitehorse, Y.T. for gold assay and Acme Analytical Labs Ltd. in Vancouver for 29 additional elements analysis, using similar techniques to Chemex. Seventeen samples which assayed high for gold were re-assayed using the metallics assaying procedure, which involves using a 100 mesh screen and fire assaying both the coarse and the fine fractions. A listing of the trenches and sample numbers is given in Appendix II, and the analysis results are given in Appendix III, with significant assays listed below in Table III.



LEGEND

OG	LIGHT GREY TO PINKISH GREY FELDSPAR–QUARTZ–MUSCOVITE ORTHOGNEISS
OGm	DARK GREEN WELL FOLIATED MUSCOVITE–QUARTZ–FELDSPAR–ORTHOGNEISS
OGp	PINKISH GREY TO LIGHT PINK FELDSPAR–QUARTZ–MUSCOVITE ORTHOGNEISS
OGs	GREY SERICITE RICH SHEARED OG
OGf	WELL FOLIATED OG
OGa	OG ALTERED TO LIGHT GREEN IN COLOR WITH CLAY RICH ZONES PERVASIVE THROUGHOUT
Q	MILKY WHITE TO DARK ORANGE CRYSTALLINE QUARTZ VEINS. FERRUGINOUS FRACTURES COMMON THROUGHOUT
B	CHALKY WHITE BARITE VEIN
Qf	MILKY WHITE TO DARK ORANGE QUARTZ FELDSPAR VEINS
	INFERRED/KNOWN GEOLOGICAL BOUNDARY
+	DIABASE DYKE (MAGNETIC)
64° ?	ORIENTATION KNOWN/INFERRED/VERTICAL
X	SAMPLE SITE LOCATION/INTERVAL
	SHEAR

SCALE 1:500

0 5 10 15 20 25

METRES

NOTE: MAP BY C. MARRIOTT, 1990

ARBOR RESOURCES INC.

LONE STAR PROPERTY


DAWSON MINING DISTRICT, Y.T.

VIOLET SHOWING TRENCH V1


BY: S.T./p.s.

DATE: MAY, 1991

FIGURE: 4








SAMPLING INTERVAL

LEGEND

Q	MILKY WHITE TO DARK ORANGE CRYSTALLINE QUARTZ VEINS. FERRUGINOUS FRACTURES COMMON THROUGHOUT
OGfs	WELL FOLIATED GREY SERICITIC ORTHOGNEISS
OGf	WELL FOLIATED OG
OGp	PINKISH GREY TO LIGHT PINK
Qf	MILKY WHITE TO DARK ORANGE QUARTZ FELDSPAR VEINS
– – –	GEOLOGICAL CONTACT



NOTE: MAP BY C. MARRIOTT, 1990

ARBOR RESOURCES INC.

LONE STAR PROPERTY
DAWSON MINING DISTRICT, Y.T.

VIOLET SHOWING TRENCH V2

BY: S.T./p.s.
DATE: MAY, 1991

FIGURE: 5

TABLE III
TRENCH ASSAYS > 0.1 oz/ton Au

SAMPLE	TRENCH	DESCRIPTION*	ASSAY
24481	90GGTR17	7-9 m grab	0.189
24494	90GGTR18	3 m quartz vein	1.248
37893	9027PUPTR04	21 m west sheared quartz vein	0.110
37900	9027PUPTR04	19-21 m west qutz sereicite schist	0.101
37923	9027PUPTR1A	limonitic quartz vein	0.117
38964	90GGTR02	10 m 40 cm quartz vein	1.358
38968	90GGTR02	41 m quartz boulder	0.102
38971	90GGTR02	45 m quartz boulder	0.858
38973	90GGTR02	50.5 m quartz boulder	0.385
38975	90GGTR12	56 m quartz boulder	0.165
39168	90OGJV	15 m quartz vein	0.179
39202	90GGTR13	23 m quartz vein	0.238
39211	90GGTR14	27 m quartz vein	0.145
39336	90GGTR06	59-61 m grab	2.224
108147	90GGTR03	quartz vein select	0.109
108151	90GGTR02	quartz vein	0.656
108152	90GGTR02	quartz vein	0.437
108153	90GGTR02	quartz vein	0.516
108156	90GGTR01	21 m grab	0.326
108164	90GGTR06	12 cm quartz vein	0.226
108190	90GGTR06	69-71 m grab	8.290
108195	90GGTR06	79-81 m grab	0.178

*N.B.: where a meterage is given, this is the location of the sample.

Most of the high assays can be attributed to quartz veins, which (based on previous experience in the camp) have no economic potential due to their limited extent.

6. ROTARY DRILLING

A total of 2,796 m was drilled in 45 reverse circulation rotary drill holes between October 27 and November 19, 1990, as shown in Figure 2. A Schramm T450H air rotary rig mounted on a TF 360 Nodwell carrier was used to drill 11.4 cm diameter holes. Drilling was carried out by Midnight Sun Drilling Co. Ltd. of Whitehorse, Y.T.

The drilling can be grouped into seven areas, each with a different target. Holes 90R1-7 are located in or near Gay Gulch, and targeted a quartz vein exposed in trenching that carried free gold. Holes 90R8-24 are located near the old Lone Star showing, with holes 90R8-90R19 trying to outline a gold bearing hoizon indicated in previous drilling, and holes 90R20-24 searching for the extension of the Boulder Lode vein. Holes 90R25-28 are located near 7 Pup, with 90R25 trying to confirm an old report of gold recovered in a churn drill hole, and 90R26-28 targeting I.P. anomallies. Holes 90R29-31 and 90R48-50 are located along Eldorado Creek between Gay Gulch and 27 Pup, and were also based on I.P. anomallies. Holes 90R32-35 are located along 27 Pup, and searched for a high grade quartz/pyrite vein exposed in trenching. Holes 90R36-38 and 90R45-47 are located near French Gulch, and targeted I.P. anomallies. Finally, hole 90R39 was located on Upper Bonanza Creek near O'Neil Gulch, and was based on an I.P. anomally. Listed below in Table IV is a description of the rotary drill holes (lengths are given in feet).

TABLE IV
ROTARY DRILLING DATA

HOLE NO.	AZIMUTH	DIP	LENGTH	DATE	LOCATION
90R1	250	60	100	10/27	30 m @ 080 from FG vein
90R2	-	90	100	10/27-28	GG I.P.L. 13+32.5E
90R3	240	60	100	10/28	GG I.P.L. 12+90E
90R4	250	45	80	10/28	15 m @ 080 from FG vein
90R5	070	45	125	10/28-29	15 m @ 260 from FG vein
90R6	210	60	150	10/29	30 m @ 090 from 90GGTR2
90R7	-	90	200	10/29	30 m @ 090 from 90GGTR2
90R8	-	90	150	10/29	old I.P.L. 0+00 2+75S
90R9	-	90	150	10/29-30	old I.P.L. 0+50W 2+75S
90R10	-	90	150	10/30	old I.P.L. 1+00W 2+75S
90R11	-	90	150	10/30	old I.P.L. 0+00 2+25S
90R12	-	90	150	10/30	old I.P.L. 0+50W 2+25S
90R13	-	90	150	10/30	old I.P.L. 1+00W 2+25S
90R14	-	90	150	10/31	old I.P.L. 1+50W 2+25S
90R15	-	90	150	10/31	old I.P.L. 2+00W 2+25S
90R16	-	90	150	10/31	old I.P.L. 2+50W 2+25S
90R17	-	90	150	10/31	old I.P.L. 2+50W 2+75S
90R18	-	90	395	10/31-11/1	old I.P.L. 1+95W 2+65S
90R19	-	90	150	10/31	old I.P.L. 1+50W 2+75S

HOLE NO.	AZIMUTH	DIP	LENGTH	DATE	LOCATION
90R20	030	65	200	11/1-2	old I.P.L. 0+00 2+35S
90R21	210	65	150	11/2	old I.P.L. 0+25E 2+05S
90R22	210	65	150	11/2	old I.P.L. 0+05W 1+90S
90R23	030	65	150	11/1	old I.P.L. 0+30W 2+35S
90R24	040	45	200	11/2	old I.P.L. 1+70E 2+80S
90R25	-	90	157	11/2	near 90JUN 7PUP1 trench
90R26	-	90	300	11/2-3	7P I.P.L. 3+80E 1+10N
90R27	-	90	200	11/4	7P I.P.L. 3+80E 1+60S
90R28	360	60	200	11/3-4	7P I.P.L. 4+80E 0+60N
90R29	260	45	500	11/4-5	GG I.P.L. 3+00E
90R30	260	45	500	11/6	GG I.P.L. 2+20N 2+00E
90R31	200	45	300	11/7	EL I.P.L. 45+00S
90R32	-	90	100	11/8	near 9027PUPTR1
90R33	-	90	100	11/8	near 9027PUPTR1
90R34	-	90	100	11/8	near 9027PUPTR1
90R35	-	90	100	11/7	near 9027PUPTR1
90R36	180	50	400	11/8-9	FG I.P.L. 6+60S 8+60E
90R37	030	75	300	11/9	FG I.P.L. 3+60E 5+50S
90R38	040	50	250	11/9-10	FG I.P.L. 3+40E 3+60S
90R39	160	60	300	11/10-11	ON I.P.L. 1+00E 0+20S
90R45	345	60	350	11/16	EL I.P.L. 29+40S
90R46	080	50	500	11/17-18	FG I.P.L. 6+61S 7+60E
90R47	220	50	250	11/18	FG I.P.L. 3+80E 3+15S
90R48	-	90	100	11/18	OG I.P.L. 49+70S 0+00W
90R49	-	90	100	11/19	OG I.P.L. 49+70S 0+30W
90R50	-	90	115	11/19	OG I.P.L. 49+70S 0+60W

Upon recovery, the samples passed through a cyclone desander, and thence through a three tier Jones Splitter. All samples were taken on five foot intervals. Half of the sample was bagged and stored on site, while 12.5 % of the sample was separately bagged and labled for analysis. A small sample was also taken for logging the drill cuttings; these logs appear in Appendix IV.

The samples were sent to Northern Analytical Labs Ltd. in Whitehorse, Y.T. There gold was assayed using the FA-AA method, except for samples from 90R8-24, which were done by metallics fire assay. This involved screening to -100 mesh and then fire assaying both the +100 mesh and the -100 mesh fractions. Any sample which assayed greater than 0.01 oz/t using the regular assay method was subsequently assayed by the metallic assay method. A portion of all of the samples was then sent to Acme Analytical Labs Ltd. in Vancouver for 29 additional elements using the ICP-AES technique. The analysis results are listed in Appendix V, with significant assays listed below in Table V.


TABLE V
ROTARY DRILL ASSAYS > 0.01 oz/ton Au

HOLE NO.	FOOTAGE	ASSAY	HOLE NO.	FOOTAGE	ASSAY
90R2	20-25	0.012	90R2	30-35	0.024
90R2	35-40	0.015			
90R7	35-40	0.011	90R7	70-75	0.062
90R7	155-160	0.027			
90R8	40-45	0.044	90R8	55-60	0.016
90R8	70-75	0.032	90R8	75-80	0.045
90R8	80-85	0.283	90R8	85-90	0.013
90R8	90-95	0.035	90R8	105-110	0.014
90R8	115-120	0.090	90R8	130-135	0.041
90R8	135-140	0.250	90R8	145-150	0.336
90R9	20-25	0.032	90R9	35-40	0.022
90R9	65-70	0.020	90R9	80-85	0.014
90R9	95-100	0.837	90R9	100-105	0.011
90R9	110-115	0.019	90R9	115-120	0.039
90R9	120-125	0.018	90R9	125-130	0.031
90R9	130-135	0.094			
90R10	15-20	0.020	90R10	50-55	0.093
90R10	80-85	0.022			
90R11	0-5	0.025	90R11	5-10	0.010
90R11	10-15	0.038	90R11	15-20	0.290
90R11	30-35	0.068	90R11	35-40	0.018
90R11	40-45	0.021	90R11	45-50	0.035
90R11	115-120	0.030	90R11	130-135	0.011
90R11	135-140	0.046			
90R12	25-30	0.029	90R12	30-35	0.013
90R12	35-40	0.017	90R12	105-110	0.035
90R12	115-120	0.023	90R12	130-135	0.062
90R13	105-110	0.163	90R13	125-130	0.075
90R14	0-5	0.027	90R14	10-15	0.090
90R14	15-20	0.145	90R14	20-25	0.060
90R14	25-30	0.062	90R14	30-35	0.055
90R14	60-65	0.023	90R14	65-70	0.017
90R14	70-75	0.020	90R14	75-80	0.050
90R14	80-85	0.175	90R14	85-90	0.020
90R14	105-110	0.017	90R14	110-115	0.012

HOLE NO.	FOOTAGE	ASSAY	HOLE NO.	FOOTAGE	ASSAY
90R15	10-15	0.010	90R15	35-40	0.042
90R15	40-45	0.129	90R15	45-50	0.019
90R15	55-60	0.019	90R15	60-65	0.012
90R15	75-80	0.011	90R15	80-85	0.719
90R15	100-105	0.011			
90R16	5-10	0.021	90R16	25-30	0.032
90R16	30-35	0.167	90R16	40-45	0.042
90R16	80-85	0.014	90R16	110-115	0.011
90R16	120-125	0.012	90R16	130-135	0.020
90R16	135-140	0.024	90R16	140-145	0.016
90R17	15-20	0.012	90R17	45-50	0.022
90R17	50-55	0.062	90R17	105-110	0.256
90R17	125-130	0.044	90R17	140-145	0.029
90R18	35-40	0.061	90R18	40-45	0.015
90R18	55-60	0.062	90R18	60-65	0.011
90R18	65-70	0.046	90R18	70-75	0.011
90R18	85-90	0.011	90R18	90-95	0.014
90R18	95-100	0.019	90R18	100-105	0.158
90R18	105-110	0.139	90R18	110-115	0.019
90R18	115-120	0.501	90R18	120-125	0.217
90R18	130-135	0.025	90R18	140-145	0.019
90R18	145-150	0.095	90R18	150-155	0.080
90R18	160-165	0.028	90R18	165-170	0.018
90R18	180-185	0.062	90R18	190-195	0.010
90R18	195-200	0.039	90R18	200-205	0.015
90R18	205-210	0.012	90R18	215-220	0.068
90R18	275-280	0.027			
90R19	70-75	0.018	90R19	75-80	0.020
90R19	80-85	0.022	90R19	90-95	0.044
90R19	110-115	0.016			
90R20	5-10	0.013	90R20	20-25	0.026
90R20	25-30	0.053	90R20	30-35	0.011
90R20	40-45	0.026	90R20	45-50	0.013
90R20	130-135	0.010			
90R21	50-55	0.032	90R21	95-100	0.019
90R21	100-105	0.017	90R21	120-125	0.010
90R22	45-50	0.045	90R22	100-105	0.016
90R22	120-125	0.018	90R22	130-135	0.026
90R22	135-140	0.025			

HOLE NO.	FOOTAGE	ASSAY	HOLE NO.	FOOTAGE	ASSAY
90R23	0-5	0.015	90R23	25-30	0.258
90R23	30-35	0.284	90R23	35-40	0.079
90R23	55-60	0.024	90R23	60-65	0.020
90R23	65-70	0.022	90R23	70-75	0.029
90R23	90-95	0.087	90R23	95-100	0.043
90R23	100-105	0.036	90R23	110-115	0.017
90R23	135-140	0.026	90R23	140-145	0.050
90R24	20-25	0.013	90R24	30-35	0.123
90R24	35-40	0.068	90R24	90-95	0.013
90R24	105-110	0.017			
90R28	20-25	0.0149			
90R30	150-155	0.0239	90R30	205-210	0.0146
90R30	260-265	0.0350	90R30	355-360	0.0103
90R30	360-365	0.0210	90R30	365-370	0.0183
90R30	445-450	0.0160	90R30	450-455	0.0364
90R32	50-55	0.1236	90R32	55-60	0.0143
90R34	5-10	0.0158	90R34	75-80	0.0181
90R35	0-5	0.0202	90R35	10-15	0.0903
90R35	15-20	0.0138			
90R38	85-90	0.0381			
90R47	200-205	0.0128	90R47	205-210	0.0391
90R47	210-215	0.0170	90R47	220-225	0.0180
90R47	225-230	0.0392	90R47	230-235	0.0239

All of the economic assays returned were from the Lone Star area. Two deposit types were drilled: high grade veins and mineralized horizons. The high grade veins not only include the well documented Boulder Lode vein, which was intersected in 90R20-23, but may also be responsible for the high assays from the pattern drill holes 90R8-19. These latter holes, and possibly 90R24, appear to be intersecting a low grade mineralized sheet, and most of the economic assays returned from this drilling program have come from this sheet. A detailed plan view of the Lone Star drill holes is shown in Figure 6. The assay results of the two fences at Lone Star are shown as profiles in Figures 7 (90R8,9,10,17,18,19) and 8 (90R11-16).



SCALE 1:1,000

0 10 20 30 40 50

METRES

ARBOR RESOURCES INC.

LONE STAR PROPERTY


DAWSON MINING DISTRICT, Y.T.

1990 ROTARY DRILLHOLE LOCATION MAP

BY: S.T./p.s.

DATE: JUNE, 1991

FIGURE: 7



Note: Any Au values less than 0.005 Oz/Ton were filtered
Au: 1mm=0.0025 Oz/Ton

SCALE 1:1,000
0 10 20 30 40 50
METRES


ARBOR RESOURCES INC.

LONE STAR PROPERTY
DAWSON MINING DISTRICT, Y.T.

PROFILE DRILL RESULTS 90R8-10 & 90R17-19

BY: S.T./p.s.
DATE: MAY, 1991

FIGURE: 8



Note: Any Au values less than 0.005 Oz/Ton were filtered
Au: 1mm=0.0025 Oz/Ton

SCALE 1:1,000
0 10 20 30 40 50
METRES

ARBOR RESOURCES INC.

LONE STAR PROPERTY
DAWSON MINING DISTRICT, Y.T.

PROFILE DRILL RESULTS 90R11-16

BY: S.T./p.s.
DATE: MAY, 1991

FIGURE: 9

Hole 90R30 was drilled on Eldorado Creek near a presumed steeply dipping fault (which may underlie and be responsible for Eldorado Creek). The assays returned, although erratic and uneconomic, indicate gold mineralization is associated with this fault.

Hole 90R47 was drilled near French Gulch to intersect the graphite horizons, which are inferred thrust faults. Again, the anomalous assays suggest a mineralizing event occurred along the fault.

In addition to the routine assaying performed on all of the samples, several intervals had leach and gravity concentration assays performed to test for the nugget affect caused by coarse gold particles. The leach assays were performed by Barringer Laboratories of Mississauga, Ont., and the gravity concentration assays were done by Bacon Donaldson & Associates Ltd. of Richmond, B.C.

The cyanide leach assay technique was performed on eleven samples: 90R18 100-105 to 120-125, and 90R23 10-15 to 35-40. From the drill cuttings, a 900 to 3400 gm sample was pulverised to -150 mesh. After weighing, the sample was tumbled in a hot cyanide solution for several hours. The cyanide solution was then analysed for gold content, and a portion of the residue was fire assayed. The gravity concentration test was performed on four samples: 90R23 20-25 to 35-40. From the drill cuttings, 8.4 to 13.8 kgs was crushed to -10 mesh. After weighing, the sample was deslimed at 325 mesh, with the coarse fraction jigged and panned. The entire jig concentrate was assayed, and a sample cut was assayed from both the -325 mesh slime and the jig tails fractions. The assay results are listed in Appendix V, and a comparison between the metallics fire assay, the leach assay, and the gravity concentration assay techniques is listed below in Table VI.

TABLE VI
ROTARY DRILL ASSAYING TECHNIQUE COMPARISONS

SAMPLE NO.	METALLICS	LEACH	GRAVITY
90R18 100-105	0.158	0.144	-
90R18 105-110	0.139	0.259	-
90R18 110-115	0.019	0.031	-
90R18 115-120	0.501	0.220	-
90R18 120-125	0.217	0.331	-
90R23 10-15	0.008	0.031	-
90R23 15-20	0.008	0.016	-
90R23 20-25	0.002	0.016	0.028
90R23 25-30	0.258	0.289	0.166
90R23 30-35	0.284	0.300	0.199
90R23 35-40	0.079	0.061	0.386

From these assay comparisons, it appears that there is a nugget affect. The best example of this is sample 90R23 35-40, where the gravity concentrate assayed approximately 500% higher than the leach or metallics assays. How important the nugget affect is can only be determined by performing similar comparisons on a statistically significant number of samples; 100 comparisons would probably be enough to draw accurate conclusions.

7. CONCLUSIONS

The mineral claims owned by Arbor Resources Inc. are situated along two of the most productive placer creeks in the world, Bonanza and Eldorado Creeks. The source of this gold is almost certainly covered by these claims.

The Induced Polarization/Resistivity survey resulted in two significant anomalies. A suspected high angle fault running parallel to Eldorado Creek was delineated with enough precision to allow future drill targets to be selected. And at the Lone Star showing, a correlation between chargeable zones and drill intersections was observed, which may help in the selection of future drill targets.

The soil sampling indicates that the gold anomally which covers the Lone Star showing probably extends at least as far as Victoria Gulch. This adds approximately 0.5 km to the known strike length of 2 km.

The trenching discovered several high grade quartz veins, mostly in the vicinity of Gay Gulch. However, although these veins are probably important sources for placer gold, they are not economically significant for lode gold potential due to their erratic nature.

The rotary drilling at French Gulch, although intersecting uneconomic grades, suggests mineralization may be associated with the inferred thrust fault. Similarly, drilling along Eldorado Creek indicates potential for mineralization along the steeply dipping faults. The most successful and only economic drill intersections, however, were in the vicinity of the Lone Star showing. Both high grade quartz veins and a mineralized sheet were intersected.

Based on results from this years work, and on re-examining previous work, the primary target is a mineralized horizon at the Lone Star showing. Whether this horizon connects with anomallies occurring near Gay Gulch or whether the horizon sub-parallels an inferred thrust fault are unknown, but the target is well defined at the Lone Star.

Work in 1991 should concentrate on extending the mineralized horizon delineated at the Lone Star. Specifically, a series of fences of rotary drill holes should be pattern drilled to the east between the area of the 1990 holes and Victoria Gulch. These widely spaced holes would indicate whether there is the potential for a large tonnage deposit. If the results are encouraging, infill drilling would be the next stage.

Respectfully submitted;



Scott Tomlinson

8. REFERENCES

Bostock, H.S.,1957; Yukon Territory-Selected Field Reports of the Geological Survey of Canada, 1893 to 1937: Geol. Surv. of Canada, Memoir 284.

Boyle, R.W.,1979; The Geochemistry of Gold and its Deposits: Geol. Surv. of Canada, Bulletin 280, p. 350-357.

Cairnes, D.D.,1912; Quartz Mining in the Klondike District: Geol. Surv. of Canada, Sum. Rept. for 1911, pp. 4,17-40: Also Geol. Surv. of Canada, Memoir 284, P. 343-351.

DeCarle, R.J.,1984; Airborne Electromagnetic Survey, Mark Management Limited, Dawson Area, Yukon Territory: File No. 26023, Commissioned Report.

Desborough, George A.,1970; Silver Depletion Indicated by Microanalysis of Gold from Placer Occurrences, Western United States: Econ. Geol., v.65, no.3, p.304-311.

Dufresne, M.B.,1986; Origin of Gold in the White Channel Sediments of the Klondike Region, Yukon Territory. Master of Science Thesis, University of Alberta, 166 pp.

Gleeson, C.F.,1970; Heavy Mineral Studies in the Klondike Area, Yukon Territory: Geol. Surv. of Canada, Bull. 173, 63 pp.

Grunenberg, P. and Troup, A.,1985; Geological, Geochemical and Geophysical Report on the Dawson Property: Unpub. Rept., 42pp.

Grunenberg, P. and Troup, A.,1986; Geological, Geochemical and Geophysical Report for Work Performed by Mark Management Ltd.: Unpub. Rept., 42 pp.

Grunenberg, P.,1987; Geological, Geochemical, and Diamond Drill Report for Work Performed by Mark Management Ltd. on the Dawson Property: Unpub. Rept., 51 pp.

Grunenberg, P.,1987; Geological, Geochemical, and Diamond and Rotary Drilling Report on the Lone Star Property: Unpub. Rept., 49 pp.

Grunenberg, P.,1988; Geological, Geochemical, Geophysical, and Diamond and Rotary Drilling Report on the Lone Star Property; Unpub. Rept., 49 pp.

Grunenberg, P.,1989; Geological, Geochemical, Geophysical and Trenching Report for Work Performed by Mark Management Ltd.: Unpub. Rept., 63 pp.

MacLean, T.A.,1914; Lode Mining in Yukon; An Investigation of Quartz Deposits in the Klondike Division: Can. Dept. of Mines, Mines Br. Pub. 222, Ottawa.

McConnell, R.G.,1905; Report on the Klondike Gold Fields: Geol. Surv. of Canada, Annu. Rep., pt. B, v.14,p. 1-71.

Metcalfe, P.,1981; Petrogenesis of the Klondike Formation, Yukon Territory, a Thesis Presented to the University of Manitoba in Partial Fulfillment for the Requirements for the Degree of Master of Science in Department of Earth Sciences, University of Manitoba.

Milner, M.W.,1977; Geomorphology of the Klondike Placer Gold Fields, Yukon Territory. Indian and Northern Affairs Canada (Whitehorse), Final Report, 157 p.

Mortensen, J.K.,1986; Bedrock Geology and U-Pb Geochronology of the Klondike District, West-Central Yukon Territory, Geological Survey of Canada.

Mortensen, J.K., 1990; Geology and U-Pb Geochronolgy of the Klondike District, West-Central Yukon Territory; Canadian Journal of Earth Sciences, Vol. 27, p. 903-914.

Roche, W.J.,1916; The Yukon Territory; Its History and Resources: an Issue by the Ministry of the Interior, Ottawa.

Tomlinson, S., 1990; Geological, Geochemical, and Trenching Report on the Dawson Property; Unpub. Rept., 35 pp.

Tuck, R.,1968; Origin of the Bedrock Values of Placer Deposits: Econ. Geol., v. 63, no. 2, p. 191-193.

VanAngeren, P.D.,1986; Compilation Report on the Lone Star Property, Dawson Mining District, Y.T.: Unpub. Rpt. for Dawson Eldorado Mines Ltd.

Walcott, P.E. and Associates Ltd.,1987; A Report on Magnetic and Electromagnetic Surveys, RON 17-22. (Unpublished Report for Arbor Resources Inc.)

Walcott, P.E. and Associates Ltd.,1987; A Report on Magnetic and Induced Polarization Surveys, RON, SYNDICATE, RJ, DN, ND, DE claims and LOTS. (Unpublished Report for Arbor Resources Inc. and Kangeld Resources Ltd.)

9. STATEMENT OF PROFESSIONAL QUALIFICATIONS

SCOTT TOMLINSON, B.Sc.

ACADEMIC

1983
UNIVERSITY OF BRITISH COLUMBIA
B.Sc. IN GEOLOGY

PROFESSIONAL

AUGUST 1990 - FEBRUARRY 1991
HASTINGS MANAGEMENT
PROJECT GEOLOGIST
Responsible for regional and detailed exploration programs, including rotary drilling, in Dawson, Yukon.

JUNE 1990 - AUGUST 1990
GEWARGIS GEOLOGICAL CONSULTING LTD.
GEOLOGIST
Assisted in a mapping and diamond drilling program near Stewart, B.C.

JUNE 1986 - JUNE 1990
HUGHES LANG EXPLORATIONS LTD.
PROJECT GEOLOGIST
Responsible for regional and detailed exploration programs in Dawson, Yukon, and central and western British Columbia. Also, was involved in monitoring placer mining operations.

JUNE 1985 - MAY 1986
GEWARGIS GEOLOGICAL CONSULTING LTD.
PROJECT GEOLOGIST
Responsible for detailed exploration programs in central and south-western British Columbia and southern California.

JUNE 1984 - NOVEMBER 1984, JUNE 1983 - NOVEMBER 1983
MARK MANAGEMENT
GEOLOGIST
Worked on regional and detailed exploration programs near Atlin, British Columbia.

10. COST STATEMENT

LIST OF YUKON RESIDENT EMPLOYEES

JERRY BRYDE
P.O. BOX 469
DAWSON, Y.T.
Y0B 1G0

Arbor Resources Inc.
LONE STAR PROPERTY
COST STATEMENT
1 June - 13 December 1990

GENERAL COST

FOOD & ACCOMMODATION 699 mdays @ $67.37		$ 47,790.88
SUPPLIES		5,795.27
FUEL		430.30
SHIPMENTS		1,881.47
MAINTENANCE		755.60
RENTALS:		
Arbor Field Equipment 699 days @ $10	$6,990.00	
Norcan 4wd Crewcab 14 days	836.72	
Norcan 4wd Bronco 2.5 mos @ $1,450	3,625.00	
Arbor 4wd Blazer 129 days @ $55	7,095.00	
Faith 4wd Suburban 129 days @ $60	7,740.00	
Faith 4wd PU 129 days @ $55	7,095.00	
Arbor 4wd Bronco 27 days @ $55	1,485.00	34,866.72
FIXED WING (CAI, Air North, Alkan Air)		9,731.29
CONSULTANT FEES:		
Adder Exploration & Development Ltd.		1,936.03
Archean Engineering Ltd.		20,475.00
REPORT PREPARATION		11,714.94
TOTAL GENERAL COST		$135,377.50

GEOLOGY & FIELD SUPERVISION
6 June - 15 October 1990

SALARIES & WAGES:		
S.Tomlinson 29 days @ $160.42	$4,652.18	
C.Mariott 10 days @ $186.67	1,866.70	
A.Whalley 13 days @ $140	1,820.00	
L.Johnson 7 days @ $177.33	1,241.31	
J.McFaull 8 days @ $140	1,120.00	$ 10,700.19
BENEFITS @ 20%		2,140.04
GENERAL COST APPORTIONED (67/699 X $135,377.50)		12,976.10
TOTAL GEOLOGY & FIELD SUPERVISION COST		$ 25,816.33

GEOCHEMICAL SURVEY COST
5 September - 7 October 1990

SALARIES & WAGES:		
S.Tomlinson 5 days @ $160.42	$ 802.10	
C.Mariott 4 days @ $186.67	746.68	
A.Whalley 4 days @ $140	560.00	
L.Johnson 3 days @ $177.33	531.99	$ 2,640.77
BENEFITS @ 20%		528.15
LINE-CUTTING (Marc Habel 6.57 lkm @ $400)		2,628.00
ASSAYS & ANALYSES:		

Chemex Labs 279 Soils for AU & 32-El ICP @ $18.77		5,236.00
Northern 29 Soils for AU & 30-El ICP @ $11.75		340.75
GENERAL COST APPORTIONED (16/699 X $135,377.50)		3,098.77
TOTAL GEOCHEMICAL SURVEY COST		$ 14,472.44

TRENCHING COST
14 June - 18 October 1990

SALARIES & WAGES:		
S.Tomlinson 20 days @ $160.42	$3,208.40	
A.Whalley 55 days @ $140	7,700.00	
C.Mariott 15 days @ $186.67	2,800.05	
L.Johnson 3 days @ $177.33	531.99	
J.Bryde 1 day	100.00	
J.McFaull 13 days @ $140	1,820.00	$ 16,160.44
BENEFITS @ 20%		$ 3,232.09
CONTRACT BULLDOZER TRENCHING:		
Hawk Mining D8, 478.5 Hrs @ $160.88		$ 76,980.00
ASSAYS & ANALYSES:		
Chemex Labs 679 Rocks for AU & 32-El ICP @ $19.75		13,410.25
17 Pulp for Au Metallics @ $22.00		374.00
Northern 29 Rocks for AU & 30-El ICP @ $15.25		381.25
GENERAL COST APPORTIONED (107/699 X $135,377.50)		20,723.02
TOTAL TRENCHING COST		$131,261.05

SURVEYING COST
9 September - 12 December 1990

SALARIES & WAGES:	
S.Tomlinson 6 days @ $160.42	$ 962.52
BENEFITS @ 20%	192.50
GENERAL COST APPORTIONED (6/699 X $135,377.50)	1,162.04
TOTAL GEOLOGY & FIELD SUPERVISION COST	$ 2,317.06

ROTARY DRILLING COST
13 October - 7 December 1990

SALARIES & WAGES:		
S.Tomlinson 46 days @ $160.42	$7,379.32	
C.Mariott 9 days @ $186.67	1,680.03	
J.McFaull 43 days @ $140	6,020.00	
J.Bryde 29 days @ $100	2,900.00	
R.Gonzalez 19 days @ $275	5,225.00	$ 23,204.35
BENEFITS @ 20%		$ 3,595.87
MIDNIGHT SUN 8,957 ft @ $21.06		$188,656.10
ASSAYS & ANALYSES:		
Northern 1,190 core for Au @ $12		14,280.00
1,779 pulp for 30-El ICP @ $3.25		5,781.75
574 core for Au metallics @ $26.25		15,067.50
41 pulp for Au metallics @ $24		984.00
Accurassay 11 core for Au leach @ $43.68		480.43

Barringer 4 core for Au gravity @ $357.94	1,431.75
ROADS AND DRILL PADS:	
Henry Gulch Placers 25Oct-20Nov 90 Hrs @ $200	18,000.00
GENERAL COST APPORTIONED (146/699 X $135,377.50)	28,276.27
TOTAL ROTARY DRILLING COST	$299,758.02

COST SUMMARY

GEOLOGICAL	$ 25,816.33
GEOCHEMICAL	14,472.44
TRENCHING	131,261.05
SURVEYING	2,317.06
ROTARY DRILLING	299,758.02
GEOPHYSICAL (see Geotronics report)	~~150,622.00~~
	~~$624,246.90~~

See following pages for revised cost statment.

Your file Votre référence

Our file Notre référence

November 9, 1992

TO WHOM THIS MAY CONCERN

Re: Assessment Report Number 092969 - Arbor Resources Lone Star Property.

This report was originally submitted as one report containing two sections;

a) a report covering the geology, rotary drilling and physical work performed on the Lone Star Property.

and

b) a geophysics report containing the results of the various geophysical surveys carried out on the property.

The geophysical portion of the exploration program was carried out under contract by Geotronics Surveys Ltd.. Geotronics originally filed a preliminary report because they were in the process of upgrading their computer programs. A final report was never forth coming from Geotronics due to computer and financial problems. Due to the fact that Arbor had no control over the actions of their contractor it was finally decided by the Dawson Mining Recorder in consultation with the Geology Section to allow Arbor to file revised statement of costs to renew those claims affected by the geophysical report. The amount of physical credit allowed was based on the amount of physical work expended during the 1990 field season.

Since there was never any problem with the report filed for the geology and rotary drilling program the amount of assessment credit for these items were allowed to stand.

Sincerely,

Robert Deklerk

Staff Geologist
Whitehorse, Yukon

STATEMENT OF COSTS

FILING DATE: 09 Oct 90

CLAIMS WORKED: ND 2, 4

CLAIMS RENEWED: Cal, Rado

WORK REQUIRED: $8400

TYPE OF WORK: Trenching

COST STATEMENT: 6000 cu.m. x $1.60 = $9600

REFERENCES: 1990 Lone Star Assessment Report

I verify that these costs were incurred during the period referred to in the report above-noted.

Dated at Dawson City, Yukon, this 16th day of July 1992.

SCOTT TOMLINSON

This report has been examined by the Geological Evaluation Unit under Section 53 (4) Yukon Quartz Mining Act and is allowed as representation work in the amount of $ 3 4 6 5.

Robert Deblock
Regional Manager, Exploration and Geological Services for Commissioner of Yukon Territory.

Assessment report re Report # 092965

STATEMENT OF COSTS

FILING DATE: 31 Oct 90

CLAIMS WORKED: DN 33;"98 35"

CLAIMS RENEWED: Reef, DN, DE

WORK REQUIRED: $2800

TYPE OF WORK: Trenching, Linecutting

COST STATEMENT:

1500 cu.m. * $1.60 =		$2400
1 l.km. * $400 =		$400
TOTAL		$2800

REFERENCES: 1990 Lone Star Assessment Report

*NOTE: This claim was inadvertently included in application for renewal as one of the claims worked. It is not mentioned in report as no work was performed on it.

I verify that these costs were incurred during the period referred to in the report.

Scott Tomlinson

This report has been examined by the Geological Evaluation Unit under Section 53 (4) Yukon Quartz Mining Act and is allowed as representation work in the amount of $2,800.

Regional Manager, Exploration and Geological Services for Commissioner of Yukon Territory.

STATEMENT OF COSTS

FILING DATE: 17 Oct 90

CLAIMS WORKED: DN 15, 17; Ron 3; VI 1

CLAIMS RENEWED: Rado

WORK REQUIRED: $11600

TYPE OF WORK: Trenching

COST STATEMENT: 18750 cu.m. * $1.60 = $30000

REFERENCES: 1990 Lone Star Assessment Report

I verify that these costs were incurred during the period referred to in the report above-noted.

Dated at Dawson City, Yukon, this 16th day of July 1992.

SCOTT TOMLINSON

This report has been examined by the Geological Evaluation Unit under Section 53 (4) Yukon Quartz Mining Act and is allowed as representation work in the amount of $ [illegible].

[illegible]
Regional Manager, Exploration and Geological Services for Commissioner of Yukon Territory.

Amendment to report #[illegible]

STATEMENT OF COSTS

FILING DATE: 16 Nov 90

CLAIMS WORKED: ND 10; DN 15

CLAIMS RENEWED: Cab, Win

WORK REQUIRED: $3450

TYPE OF WORK: Trenching

COST STATEMENT: 4250 cu.m. * $1.60 = $6800

REFERENCES: 1990 Lone Star Assessent Report

I verify that these costs were incurred during the period referred to in the report above-noted.

Dated at Dawson City, Yukon, this 16th day of July 1992.

SCOTT TOMLINSON

This report has been examined by the Geological Evaluation Unit under Section 53 (4) Yukon Quartz Mining Act and is allowed as representation work in the amount of $ 3450.

Regional Manager, Exploration and Geological Services for Commissioner of Yukon Territory.

Amendment & Agent 07207

STATEMENT OF COSTS

FILING DATE: 26 Nov 90

CLAIMS WORKED: DN 2

CLAIMS RENEWED: Cab, Win, Top

WORK REQUIRED: $9150

TYPE OF WORK: Drilling

COST STATEMENT: 500 ft. * $33.50 = $16,750

REFERENCES: 1990 Lone Star Assessment Report

I verify that these costs were incurred during the period referred to in the report above-noted.

Dated at Dawson City, Yukon, this 16th day of July 1992.

SCOTT TOMLINSON

This report has been examined by the Geological Evaluation Unit under Section 53 (4) Yukon Quartz Mining Act and is allowed as representation work in the amount of $ 9150.

Regional Manager, Exploration and Geological Services for Commissioner of Yukon Territory.

Amendment to report 092 968

STATEMENT OF COSTS

FILING DATE: 30 Nov 90

CLAIMS WORKED: DN 33

CLAIMS RENEWED: De, Top

WORK REQUIRED: $5700

TYPE OF WORK: Drilling

COST STATEMENT: 300 ft. * $33.50 = $10050

REFERENCES: 1990 Lone Star Assessment Report

I verify that these costs were incurred during the period referred to in the report above-noted.

Dated at Dawson City, Yukon, this 16th day of July 1992.

SCOTT TOMLINSON

This report has been examined by the Geological Evaluation Unit under Section 53 (4) Yukon Quartz Mining Act and is allowed as representation work in the amount of $_____.

Regional Manager, Exploration and Geological Services for Commissioner of Yukon Territory,

STATEMENT OF COSTS

FILING DATE: 14 Jan 91

CLAIMS WORKED: VI 1, 43

CLAIMS RENEWED: KH, Rado, Nugget

WORK REQUIRED: $12000

TYPE OF WORK: Trenching

COST STATEMENT: 9500 cu.m. * $1.60 = $15200

REFERENCES: 1990 Lone Star Assessment Report

I verify that these costs were incurred during the period referred to in the report above-noted.

Dated at Dawson City, Yukon, this 16th day of July 1992.

SCOTT TOMLINSON

This report has been examined by the Geological Evaluation Unit under Section 53 (4) Yukon Quartz Mining Act and is allowed as representation work in the amount of $ 12 000.

Regional Manager, Exploration and Geological Services for Commissioner of Yukon Territory.

STATEMENT OF COSTS

FILING DATE: 01 Feb 91

CLAIMS WORKED: ND 6; *Joe 10*; Oyro

CLAIMS RENEWED: Tom, Oyro

WORK REQUIRED: $11300

TYPE OF WORK: Geochemical Survey, Trenching, Drilling

COST STATEMENT:

18 samples * $47 =	$846
1000 cu.m. * $1.60 =	$1600
305 ft. * $33.5 =	$10217.50
TOTAL	$12663.50

REFERENCES: 1990 Lone Star Assessment Report

*NOTE: This claim was inadvertently included in application for renewal as one of the claims worked. It is not mentioned in report as no work was performed on it.

I verify that these costs were incurred during the period referred to in the report.

Scott Tomlinson

This report has been examined by the Geological Evaluation Unit under Section 53 (4) Yukon Quartz Mining Act and is allowed as representation work in the amount of $ 11300.

Regional Manager, Exploration and Geological Services for Commissioner of Yukon Territory.

APPENDIX I

SOIL SAMPLES CERTIFICATES OF ANALYSES

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

A9024267

Comments: CC: A. TROUP

CERTIFICATE A9024267

ARBOR RESOURCES INC.

Project: AOR-DAWSON
P.O. # :

Samples submitted to our lab in Vancouver, BC.
This report was printed on 14-OCT-90.

SAMPLE PREPARATION

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION
203	234	Dry, sieve to -35 mesh
205	234	Geochem ring to approx 150 mesh
238	234	NITRIC-AQUA REGIA DIGESTION

* NOTE 1:

The 32 element ICP package is suitable for trace metals in soil and rock samples. Elements for which the nitric-aqua regia digestion is possibly incomplete are: Al, Ba, Be, Ca, Cr, Ga, K, La, Mg, Na, Sr, Ti, Tl, W.

ANALYTICAL PROCEDURES

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION	METHOD	DETECTION LIMIT	UPPER LIMIT
100	234	Au ppb: Fuse 10 g sample	FA-AAS	5	10000
922	234	Ag ppm: 32 element, soil & rock	ICP-AES	0.2	200
921	234	Al %: 32 element, soil & rock	ICP-AES	0.01	15.00
923	234	As ppm: 32 element, soil & rock	ICP-AES	5	10000
924	234	Ba ppm: 32 element, soil & rock	ICP-AES	10	10000
925	234	Be ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
926	234	Bi ppm: 32 element, soil & rock	ICP-AES	2	10000
927	234	Ca %: 32 element, soil & rock	ICP-AES	0.01	15.00
928	234	Cd ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
929	234	Co ppm: 32 element, soil & rock	ICP-AES	1	10000
930	234	Cr ppm: 32 element, soil & rock	ICP-AES	1	10000
931	234	Cu ppm: 32 element, soil & rock	ICP-AES	1	10000
932	234	Fe %: 32 element, soil & rock	ICP-AES	0.01	15.00
933	234	Ga ppm: 32 element, soil & rock	ICP-AES	10	10000
951	234	Hg ppm: 32 element, soil & rock	ICP-AES	1	10000
934	234	K %: 32 element, soil & rock	ICP-AES	0.01	10.00
935	234	La ppm: 32 element, soil & rock	ICP-AES	10	10000
936	234	Mg %: 32 element, soil & rock	ICP-AES	0.01	15.00
937	234	Mn ppm: 32 element, soil & rock	ICP-AES	5	10000
938	234	Mo ppm: 32 element, soil & rock	ICP-AES	1	10000
939	234	Na %: 32 element, soil & rock	ICP-AES	0.01	5.00
940	234	Ni ppm: 32 element, soil & rock	ICP-AES	1	10000
941	234	P ppm: 32 element, soil & rock	ICP-AES	10	10000
942	234	Pb ppm: 32 element, soil & rock	ICP-AES	2	10000
943	234	Sb ppm: 32 element, soil & rock	ICP-AES	5	10000
958	234	Sc ppm: 32 elements, soil & rock	ICP-AES	1	10000
944	234	Sr ppm: 32 element, soil & rock	ICP-AES	1	10000
945	234	Ti %: 32 element, soil & rock	ICP-AES	0.01	5.00
946	234	Tl ppm: 32 element, soil & rock	ICP-AES	10	10000
947	234	U ppm: 32 element, soil & rock	ICP-AES	10	10000
948	234	V ppm: 32 element, soil & rock	ICP-AES	1	10000
949	234	W ppm: 32 element, soil & rock	ICP-AES	10	10000
950	234	Zn ppm: 32 element, soil & rock	ICP-AES	2	10000

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Page Number : 4-A
Total Pages : 6
Invoice Date: 14-OCT-90
Invoice No. : I-9024267
P.O. Number :

CERTIFICATE OF ANALYSIS A9024267

SAMPLE DESCRIPTION	PREP CODE		Au ppb FA+AA	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
OPC 0+00N 1+90W	203	205	< 5	0.6	1.16	< 5	420	< 0.5	< 2	0.38	< 0.5	4	50	9	1.62	10	< 1	0.11	20	0.29	275
OPC 0+00N 2+10W	203	205	10	0.8	1.94	< 5	790	< 0.5	< 2	0.86	< 0.5	8	180	18	2.44	20	< 1	0.18	50	0.41	555
VG 0+00N 0+00W	203	205	35	1.4	1.40	30	430	< 0.5	< 2	0.22	1.0	9	101	21	2.30	10	< 1	0.16	30	0.60	495
VG 0+00N 0+10W	203	205	10	1.4	1.81	100	290	< 0.5	< 2	0.26	1.0	29	128	27	3.18	20	< 1	0.10	40	0.97	1255
VG 0+00N 0+20W	203	205	20	1.4	1.26	25	400	< 0.5	< 2	0.21	0.5	14	68	16	2.09	10	< 1	0.15	40	0.68	595
VG 0+00N 0+30W	203	205	30	1.2	0.99	30	400	< 0.5	2	0.17	0.5	7	79	11	1.43	10	< 1	0.19	70	0.32	175
VG 0+00N 0+40W	203	205	25	0.6	0.95	10	600	< 0.5	< 2	0.16	0.5	7	57	11	1.53	10	< 1	0.14	40	0.31	450
VG 0+00N 0+50W	203	205	25	0.6	1.01	15	1350	< 0.5	< 2	0.07	< 0.5	6	560	11	1.68	< 10	< 1	0.25	30	0.39	285
VG 0+00N 0+60W	203	205	25	0.6	0.60	10	630	< 0.5	< 2	0.05	< 0.5	3	63	6	0.78	10	< 1	0.19	40	0.13	140
VG 0+00N 0+70W	203	205	30	0.6	0.65	5	670	< 0.5	< 2	0.07	< 0.5	3	83	7	0.93	< 10	< 1	0.20	40	0.21	120
VG 0+00N 0+80W	203	205	30	0.8	0.77	5	550	< 0.5	2	0.07	0.5	4	120	9	1.20	10	< 1	0.19	40	0.25	135
VG 0+00N 0+90W	203	205	25	0.8	0.98	5	660	< 0.5	2	0.09	0.5	5	176	11	1.33	10	< 1	0.25	40	0.31	210
VG 0+00N 1+00W	203	205	40	0.8	0.94	10	1730	< 0.5	< 2	0.08	0.5	5	117	10	1.18	10	< 1	0.30	50	0.27	195
VG 0+00N 1+10W	203	205	50	0.8	0.91	10	1800	< 0.5	2	0.05	< 0.5	4	60	9	0.84	10	< 1	0.37	60	0.18	160
VG 0+00N 1+20W	203	205	185	0.8	1.11	5	1010	< 0.5	2	0.09	< 0.5	3	144	13	1.65	10	< 1	0.19	30	0.45	110
VG 0+00N 1+30W	203	205	230	1.2	0.94	10	2160	< 0.5	4	0.07	0.5	6	113	11	1.20	10	< 1	0.29	80	0.24	175
VG 0+00N 1+40W	203	205	135	1.0	1.07	5	1250	< 0.5	< 2	0.08	< 0.5	3	134	7	1.11	10	< 1	0.30	60	0.29	110
VG 0+00N 1+50W	203	205	15	0.8	0.80	5	2610	< 0.5	2	0.08	< 0.5	4	95	6	0.97	10	< 1	0.27	60	0.24	95
VG 0+00N 1+60W	203	205	25	1.0	0.83	5	3660	< 0.5	4	0.06	< 0.5	3	122	7	1.00	10	< 1	0.29	50	0.23	70
VG 0+00N 1+70W	203	205	95	0.8	1.33	5	470	< 0.5	2	0.10	< 0.5	3	295	11	1.55	10	< 1	0.32	40	0.53	105
VG 0+00N 1+80W	203	205	70	1.2	1.25	10	670	< 0.5	2	0.05	< 0.5	5	113	13	1.51	10	< 1	0.50	70	0.23	110
VG 0+00N 1+90W	203	205	25	1.0	1.08	10	450	< 0.5	2	0.08	< 0.5	4	125	6	1.60	10	< 1	0.43	70	0.39	110
VG 0+00N 2+00W	203	205	3880	0.6	1.06	10	590	< 0.5	2	0.14	< 0.5	7	96	15	2.30	10	< 1	0.20	30	0.58	145
VG 0+00N 2+10W	203	205	70	0.4	0.95	15	330	< 0.5	< 2	0.14	< 0.5	4	155	8	1.60	< 10	< 1	0.20	30	0.46	100
VG 0+00N 2+20W	203	205	30	0.8	0.95	10	500	< 0.5	2	0.16	< 0.5	5	114	11	1.60	10	< 1	0.24	40	0.44	130
VG 0+00N 2+30W	203	205	15	0.8	0.88	< 5	280	< 0.5	< 2	0.14	< 0.5	6	65	11	1.31	10	< 1	0.34	60	0.30	175
VG 0+00N 2+40W	203	205	45	0.8	1.24	15	510	< 0.5	4	0.31	1.5	13	132	25	1.87	10	< 1	0.26	30	0.60	340
VG 0+00N 2+50W	203	205	335	0.6	1.15	5	560	< 0.5	4	0.12	< 0.5	5	171	19	1.87	< 10	< 1	0.21	30	0.66	160
VG 0+00N 2+60W	203	205	320	0.6	1.25	5	420	< 0.5	2	0.29	0.5	7	154	23	2.14	10	< 1	0.21	30	0.64	325
VG 0+00N 2+70W	203	205	100	0.6	1.17	10	350	< 0.5	2	0.15	0.5	6	193	19	1.91	10	< 1	0.22	30	0.62	150
VG 0+00N 2+80W	203	205	215	1.4	1.24	10	350	< 0.5	2	0.28	< 0.5	6	170	17	1.91	10	< 1	0.20	30	0.62	195
VG 0+00N 2+90W	203	205	185	0.6	0.95	5	370	< 0.5	2	0.10	< 0.5	3	176	12	1.59	10	< 1	0.24	40	0.49	90
VG 0+00N 3+00W	203	205	45	0.6	1.36	< 5	420	< 0.5	2	0.22	1.0	10	112	25	1.81	10	< 1	0.22	30	0.55	280
VG 0+00N 3+10W	203	205	60	0.6	1.09	5	350	< 0.5	2	0.16	< 0.5	5	222	13	1.85	10	< 1	0.21	30	0.55	130
VG 0+00N 3+20W	203	205	75	0.4	1.15	5	300	< 0.5	4	0.15	< 0.5	5	181	14	1.83	< 10	< 1	0.17	20	0.62	115
VG 0+00N 3+30W	203	205	170	0.4	1.38	5	410	< 0.5	< 2	0.26	0.5	11	152	20	2.39	10	< 1	0.22	30	0.92	275
VG 0+00N 3+40W	203	205	30	0.8	1.21	10	550	< 0.5	< 2	0.27	0.5	11	95	18	2.33	10	< 1	0.23	30	0.67	395
VG 0+00N 3+50W	203	205	90	1.0	1.20	10	850	< 0.5	2	0.19	0.5	12	107	26	2.92	10	< 1	0.28	40	0.54	335
VG 0+00N 3+60W	203	205	185	1.0	1.28	10	370	0.5	2	0.11	1.0	32	148	24	2.67	10	< 1	0.25	30	0.74	1490
VG 0+00N 3+70W	203	205	55	0.4	1.23	5	320	< 0.5	2	0.10	0.5	7	195	15	2.45	< 10	< 1	0.23	30	0.50	180

CERTIFICATION: B. Caryl

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

[redacted]: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Page [redacted]er : 4-B
Total P[redacted] : 6
Invoice Date: 14-OCT-90
Invoice No. : I-9024267
P.O. Number :

CERTIFICATE OF ANALYSIS A9024267

SAMPLE DESCRIPTION	PREP CODE	Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
OPC 0+00N 1+90W	203 205	< 1	0.01	7	370	12	< 5	2	24	0.06	< 10	< 10	28	< 10	42
OPC 0+00N 2+10W	203 205	< 1	0.02	13	620	14	< 5	5	53	0.07	< 10	< 10	43	< 10	64
VG 0+00N 0+00W	203 205	1	0.01	14	540	60	< 5	3	24	0.04	< 10	< 10	30	< 10	174
VG 0+00N 0+10W	203 205	2	0.01	29	880	28	< 5	6	28	< 0.01	< 10	< 10	27	< 10	374
VG 0+00N 0+20W	203 205	< 1	< 0.01	15	720	24	< 5	3	18	0.01	< 10	< 10	18	< 10	172
VG 0+00N 0+30W	203 205	< 1	< 0.01	8	570	20	< 5	2	14	< 0.01	< 10	< 10	7	< 10	164
VG 0+00N 0+40W	203 205	< 1	0.01	10	380	30	< 5	2	17	0.03	< 10	< 10	21	< 10	96
VG 0+00N 0+50W	203 205	2	0.03	10	280	44	< 5	1	26	0.01	< 10	< 10	15	< 10	94
VG 0+00N 0+60W	203 205	< 1	< 0.01	3	230	30	< 5	1	12	0.01	< 10	< 10	7	< 10	66
VG 0+00N 0+70W	203 205	< 1	0.01	5	270	26	< 5	1	13	0.01	< 10	< 10	7	< 10	72
VG 0+00N 0+80W	203 205	1	0.01	6	300	40	< 5	1	14	0.01	< 10	< 10	12	< 10	82
VG 0+00N 0+90W	203 205	1	0.01	8	310	44	< 5	1	17	0.01	< 10	< 10	13	< 10	104
VG 0+00N 1+00W	203 205	1	0.01	6	260	48	< 5	2	26	0.01	< 10	< 10	9	< 10	128
VG 0+00N 1+10W	203 205	< 1	< 0.01	4	220	34	< 5	2	21	< 0.01	< 10	< 10	4	< 10	106
VG 0+00N 1+20W	203 205	1	0.01	10	390	60	< 5	1	18	0.02	< 10	< 10	18	< 10	106
VG 0+00N 1+30W	203 205	1	0.01	8	280	50	< 5	2	27	< 0.01	< 10	< 10	8	< 10	118
VG 0+00N 1+40W	203 205	< 1	0.01	6	260	42	< 5	2	20	0.01	< 10	< 10	11	< 10	88
VG 0+00N 1+50W	203 205	< 1	0.01	6	240	34	< 5	1	30	0.01	< 10	< 10	8	< 10	88
VG 0+00N 1+60W	203 205	< 1	0.01	5	240	32	< 5	1	29	0.01	< 10	< 10	8	< 10	78
VG 0+00N 1+70W	203 205	1	0.02	10	350	46	< 5	2	15	0.02	< 10	< 10	19	< 10	96
VG 0+00N 1+80W	203 205	2	0.01	12	270	44	< 5	3	11	< 0.01	< 10	< 10	4	< 10	166
VG 0+00N 1+90W	203 205	2	0.01	6	350	40	< 5	2	14	0.01	< 10	< 10	20	< 10	100
VG 0+00N 2+00W	203 205	< 1	0.01	11	500	44	< 5	2	23	0.02	< 10	< 10	19	< 10	150
VG 0+00N 2+10W	203 205	1	0.01	10	450	30	< 5	1	17	0.03	< 10	< 10	23	< 10	92
VG 0+00N 2+20W	203 205	< 1	0.02	10	510	38	< 5	1	20	0.02	< 10	< 10	17	< 10	114
VG 0+00N 2+30W	203 205	< 1	< 0.01	8	430	24	< 5	1	19	< 0.01	< 10	< 10	6	< 10	180
VG 0+00N 2+40W	203 205	< 1	0.02	22	460	50	< 5	2	33	0.04	< 10	< 10	23	< 10	308
VG 0+00N 2+50W	203 205	1	0.01	13	360	66	< 5	2	20	0.02	< 10	< 10	18	< 10	150
VG 0+00N 2+60W	203 205	< 1	0.02	16	480	52	< 5	3	28	0.04	< 10	< 10	29	< 10	126
VG 0+00N 2+70W	203 205	1	0.01	14	400	58	< 5	2	20	0.02	< 10	< 10	20	< 10	136
VG 0+00N 2+80W	203 205	1	0.02	14	460	48	< 5	2	27	0.04	< 10	< 10	26	< 10	110
VG 0+00N 2+90W	203 205	1	0.01	9	370	50	< 5	1	21	0.02	< 10	< 10	16	< 10	112
VG 0+00N 3+00W	203 205	< 1	0.02	21	390	60	< 5	3	32	0.04	< 10	< 10	27	< 10	396
VG 0+00N 3+10W	203 205	1	0.02	12	440	36	< 5	2	21	0.03	< 10	< 10	22	< 10	110
VG 0+00N 3+20W	203 205	1	0.01	13	440	40	< 5	2	17	0.03	< 10	< 10	22	< 10	108
VG 0+00N 3+30W	203 205	1	0.01	19	560	40	< 5	3	29	0.04	< 10	< 10	28	< 10	172
VG 0+00N 3+40W	203 205	1	0.01	17	610	32	< 5	4	28	0.03	< 10	< 10	26	< 10	180
VG 0+00N 3+50W	203 205	4	0.01	15	640	48	< 5	3	24	0.02	10	< 10	21	< 10	254
VG 0+00N 3+60W	203 205	6	0.01	18	460	72	< 5	3	17	0.01	< 10	< 10	18	< 10	232
VG 0+00N 3+70W	203 205	2	0.01	11	430	46	< 5	2	15	0.01	< 10	< 10	20	< 10	158

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Page Number : 5-A
Total Pages : 6
Invoice Date: 14-OCT-90
Invoice No. : I-9024267
P.O. Number :

CERTIFICATE OF ANALYSIS A9024267

SAMPLE DESCRIPTION	PREP CODE	Au ppb FA+AA	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
VG 0+00N 3+80W	203 205	25	0.6	1.31	10	320	< 0.5	< 2	0.13	0.5	8	161	27	3.29	10	< 1	0.22	30	0.46	205
VG 0+00N 3+90W	203 205	15	0.6	1.26	15	530	< 0.5	< 2	0.09	1.0	21	187	41	3.15	10	< 1	0.35	40	0.43	1295
VG 0+00N 4+00W	203 205	20	0.8	1.37	15	420	< 0.5	2	0.10	0.5	11	40	33	2.68	10	< 1	0.54	60	0.30	280
VG 0+00N 4+10W	203 205	10	2.6	0.62	80	460	< 0.5	< 2	0.01	< 0.5	1	175	17	2.83	< 10	< 1	0.49	20	0.14	55
VG 0+00N 4+20W	203 205	25	1.6	0.59	70	330	< 0.5	< 2	0.01	< 0.5	< 1	128	12	5.17	10	< 1	0.53	30	0.10	40
VG 0+00N 4+30W	203 205	25	2.6	0.77	100	640	< 0.5	< 2	0.02	1.0	1	149	23	4.55	10	< 1	0.93	20	0.19	75
VG 0+00N 4+40W	203 205	25	2.2	2.59	210	400	< 0.5	< 2	0.06	1.5	2	94	202	8.09	10	< 1	0.61	30	2.09	300
VG 0+00N 4+50W	203 205	105	1.2	1.52	25	370	< 0.5	< 2	0.07	0.5	5	146	73	4.92	< 10	< 1	0.42	10	0.85	195
VG 0+00N 4+60W	203 205	35	0.4	1.58	10	340	< 0.5	< 2	0.07	< 0.5	3	321	19	2.73	< 10	< 1	0.34	20	1.16	210
VG 0+00N 4+70W	203 205	95	0.2	1.07	5	370	< 0.5	2	0.07	< 0.5	3	587	9	1.47	< 10	< 1	0.25	30	0.52	95
VG 0+00N 4+80W	203 205	230	1.6	2.71	10	370	< 0.5	< 2	0.06	1.0	14	200	61	5.03	< 10	< 1	0.34	10	2.81	465
VG 0+00N 4+90W	203 205	135	< 0.2	1.09	5	240	< 0.5	< 2	0.15	< 0.5	3	436	7	1.58	< 10	< 1	0.12	20	0.31	80
VG 0+00N 5+00W	203 205	35	0.2	1.20	5	460	< 0.5	2	0.10	< 0.5	5	502	19	1.93	< 10	< 1	0.19	20	0.64	125
VG 0+00N 5+10W	203 205	15	0.2	1.23	< 5	270	< 0.5	< 2	0.12	< 0.5	3	248	7	1.99	< 10	< 1	0.15	20	0.57	150
VG 0+00N 5+20W	203 205	60	0.4	1.05	5	640	< 0.5	2	0.17	0.5	7	417	22	2.09	< 10	< 1	0.12	20	0.53	125
VG 0+00N 5+30W	203 205	25	0.2	1.18	< 5	500	< 0.5	< 2	0.60	6.0	10	123	22	2.24	10	< 1	0.15	20	0.67	455
VG 0+00N 5+40W	203 205	10	0.2	0.70	< 5	310	< 0.5	< 2	0.14	0.5	2	351	4	1.17	< 10	< 1	0.13	20	0.26	80
VG 0+00N 5+50W	203 205	40	3.0	0.69	< 5	300	< 0.5	< 2	0.08	< 0.5	2	427	3	1.12	< 10	< 1	0.12	20	0.25	65
VG 0+00N 5+60W	203 205	20	< 0.2	0.81	5	370	< 0.5	< 2	0.10	< 0.5	2	307	4	1.10	< 10	< 1	0.18	30	0.29	70
VG 0+00N 5+70W	203 205	30	0.2	0.95	< 5	380	< 0.5	< 2	0.13	< 0.5	2	396	5	1.30	< 10	< 1	0.18	30	0.31	80
VG 0+00N 5+80W	203 205	50	< 0.2	0.70	< 5	290	< 0.5	< 2	0.09	< 0.5	1	344	2	0.91	< 10	< 1	0.13	20	0.26	65
VG 0+00N 5+90W	203 205	155	1.0	0.58	10	1060	< 0.5	< 2	0.07	< 0.5	2	179	11	0.93	< 10	< 1	0.22	40	0.18	50
VG 0+00N 6+00W	203 205	20	0.8	1.16	< 5	280	< 0.5	2	0.15	< 0.5	3	355	9	1.56	10	< 1	0.12	20	0.41	100
VG 0+00N 6+10W	203 205	35	1.4	0.79	< 5	590	< 0.5	2	0.10	< 0.5	2	194	8	1.14	10	< 1	0.22	50	0.35	80
VG 0+00N 6+20W	203 205	15	1.2	0.75	5	560	< 0.5	< 2	0.06	< 0.5	2	192	7	1.07	10	< 1	0.28	40	0.30	60
VG 0+00N 6+30W	203 205	40	1.2	1.46	5	440	< 0.5	< 2	0.11	< 0.5	3	267	9	1.81	10	< 1	0.24	30	0.87	135
VG 0+00N 6+40W	203 205	25	1.4	0.99	< 5	520	< 0.5	4	0.08	< 0.5	3	226	6	1.23	10	< 1	0.28	40	0.51	85
VG 0+00N 6+50W	203 205	< 5	1.2	1.05	5	360	< 0.5	2	0.07	< 0.5	3	234	10	1.68	10	< 1	0.27	30	0.56	125
VG 0+00N 6+60W	203 205	15	1.4	1.50	< 5	600	< 0.5	2	0.13	0.5	6	232	17	2.29	10	< 1	0.23	30	1.00	215
VG 0+00N 6+70W	203 205	30	1.2	1.17	5	550	< 0.5	2	0.07	0.5	5	196	16	2.14	10	< 1	0.23	30	0.79	200
VG 0+00N 6+80W	203 205	55	1.4	1.91	< 5	640	< 0.5	4	0.17	0.5	6	243	20	2.46	10	< 1	0.23	30	1.18	255
VG 0+00N 6+90W	203 205	30	1.0	0.84	5	390	< 0.5	2	0.13	< 0.5	4	171	8	1.49	10	< 1	0.26	40	0.26	100
VG 0+00N 7+00W	203 205	60	0.8	1.18	10	390	< 0.5	2	0.08	0.5	5	265	12	1.75	10	< 1	0.37	30	0.48	220
VG 0+00N 7+10W	203 205	15	1.0	0.94	< 5	250	< 0.5	2	0.06	< 0.5	3	222	9	1.45	10	< 1	0.30	30	0.35	140
VG 0+00N 7+20W	203 205	55	1.6	2.26	20	320	< 0.5	< 2	0.07	1.0	5	169	47	3.76	10	< 1	0.37	20	1.59	255
VG 0+00N 7+30W	203 205	145	1.8	2.12	20	420	< 0.5	< 2	0.06	1.5	6	108	56	4.30	10	< 1	0.41	20	1.56	325
VG 0+00N 7+50W	203 205	105	1.8	2.58	10	390	< 0.5	< 2	0.13	2.5	13	177	70	4.50	10	< 1	0.38	20	2.06	435
VG 0+00N 7+60W	203 205	60	1.4	2.41	20	320	< 0.5	< 2	0.13	2.0	12	316	73	3.58	10	< 1	0.27	20	1.90	440
VG 0+00N 7+70W	203 205	110	1.6	2.39	15	280	< 0.5	< 2	0.13	2.5	18	197	87	3.83	10	< 1	0.30	20	1.91	510
VG 0+00N 7+80W	203 205	30	0.8	1.42	10	290	< 0.5	2	0.12	< 0.5	4	311	21	2.13	10	< 1	0.19	20	0.68	120

CERTIFICATION: B. Caglioni

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Invoice Date: 14-OCT-90
Invoice No. : I-9024267
P.O. Number :

CERTIFICATE OF ANALYSIS A9024267

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
VG 0+00N 3+80W	203	205	5	0.01	14	540	48	< 5	2	17	0.01	< 10	< 10	19	< 10	250
VG 0+00N 3+90W	203	205	12	0.01	17	610	64	< 5	2	25	0.01	< 10	< 10	11	< 10	288
VG 0+00N 4+00W	203	205	3	< 0.01	14	710	38	< 5	2	20	< 0.01	< 10	< 10	3	< 10	304
VG 0+00N 4+10W	203	205	8	0.05	5	520	452	5	1	144	< 0.01	< 10	< 10	7	< 10	104
VG 0+00N 4+20W	203	205	8	0.37	2	540	206	< 5	1	238	< 0.01	< 10	< 10	3	< 10	38
VG 0+00N 4+30W	203	205	6	0.05	5	750	514	5	2	283	< 0.01	< 10	< 10	7	< 10	68
VG 0+00N 4+40W	203	205	2	0.07	13	1670	650	5	7	558	< 0.01	< 10	< 10	55	< 10	312
VG 0+00N 4+50W	203	205	3	0.03	10	720	226	5	2	130	0.01	< 10	< 10	13	< 10	320
VG 0+00N 4+60W	203	205	3	0.03	11	440	76	5	2	39	0.01	< 10	< 10	30	< 10	154
VG 0+00N 4+70W	203	205	1	0.03	12	250	24	< 5	1	17	0.01	< 10	< 10	15	< 10	78
VG 0+00N 4+80W	203	205	7	0.02	29	480	120	< 5	4	69	0.01	< 10	< 10	25	< 10	416
VG 0+00N 4+90W	203	205	< 1	0.02	11	350	24	< 5	2	18	0.04	< 10	< 10	18	< 10	54
VG 0+00N 5+00W	203	205	2	0.02	18	280	32	< 5	2	17	0.02	< 10	< 10	23	< 10	108
VG 0+00N 5+10W	203	205	1	0.01	9	380	42	< 5	2	21	0.04	< 10	< 10	28	< 10	88
VG 0+00N 5+20W	203	205	4	0.02	19	380	46	< 5	2	24	0.03	< 10	< 10	20	< 10	104
VG 0+00N 5+30W	203	205	< 1	0.03	22	620	10	< 5	3	35	0.08	< 10	< 10	43	< 10	152
VG 0+00N 5+40W	203	205	1	0.02	10	320	10	< 5	1	15	0.03	< 10	< 10	16	< 10	44
VG 0+00N 5+50W	203	205	< 1	0.02	9	250	12	< 5	1	13	0.02	< 10	< 10	11	< 10	54
VG 0+00N 5+60W	203	205	1	0.02	8	250	22	< 5	1	14	0.03	< 10	< 10	15	< 10	52
VG 0+00N 5+70W	203	205	2	0.02	10	310	26	< 5	1	18	0.03	< 10	< 10	15	< 10	62
VG 0+00N 5+80W	203	205	< 1	0.02	8	200	12	< 5	1	13	0.02	< 10	< 10	10	< 10	38
VG 0+00N 5+90W	203	205	35	0.02	7	160	82	< 5	1	13	0.01	< 10	< 10	9	< 10	54
VG 0+00N 6+00W	203	205	< 1	0.01	11	410	24	< 5	2	20	0.03	< 10	< 10	16	< 10	76
VG 0+00N 6+10W	203	205	5	0.01	6	270	60	< 5	1	16	0.02	< 10	< 10	13	< 10	62
VG 0+00N 6+20W	203	205	2	0.01	5	200	40	< 5	1	12	0.01	< 10	< 10	12	< 10	56
VG 0+00N 6+30W	203	205	1	0.02	10	390	52	< 5	2	28	0.02	< 10	< 10	22	< 10	104
VG 0+00N 6+40W	203	205	5	0.01	6	260	52	< 5	1	17	0.01	< 10	< 10	14	< 10	72
VG 0+00N 6+50W	203	205	2	0.02	6	310	64	< 5	1	16	0.01	< 10	< 10	18	< 10	88
VG 0+00N 6+60W	203	205	1	0.02	12	480	68	< 5	2	27	0.02	< 10	< 10	22	< 10	146
VG 0+00N 6+70W	203	205	1	0.01	9	370	80	< 5	1	23	0.01	< 10	< 10	17	< 10	140
VG 0+00N 6+80W	203	205	1	0.01	15	550	72	< 5	3	35	0.03	< 10	< 10	28	< 10	154
VG 0+00N 6+90W	203	205	2	0.02	7	300	40	< 5	1	14	0.02	< 10	< 10	15	< 10	70
VG 0+00N 7+00W	203	205	1	0.02	8	290	54	< 5	1	19	0.01	< 10	< 10	16	< 10	92
VG 0+00N 7+10W	203	205	1	0.04	6	240	66	< 5	1	13	0.01	< 10	< 10	16	< 10	78
VG 0+00N 7+20W	203	205	2	0.02	19	640	154	< 5	3	84	0.01	< 10	< 10	31	< 10	260
VG 0+00N 7+30W	203	205	3	0.05	15	760	170	< 5	3	144	< 0.01	< 10	< 10	21	< 10	274
VG 0+00N 7+50W	203	205	2	0.03	34	670	174	< 5	5	111	0.01	< 10	< 10	38	< 10	346
VG 0+00N 7+60W	203	205	1	0.02	36	430	116	5	6	26	0.03	< 10	< 10	42	< 10	254
VG 0+00N 7+70W	203	205	1	0.01	48	320	108	< 5	6	15	0.02	< 10	< 10	34	< 10	434
VG 0+00N 7+80W	203	205	< 1	0.01	15	420	60	< 5	2	16	0.03	< 10	< 10	25	< 10	114

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Invoice Date: 14-OCT-90
Invoice No. : I-9024267
P.O. Number :

CERTIFICATE OF ANALYSIS A9024267

SAMPLE DESCRIPTION	PREP CODE	Au ppb FA+AA	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
VG 0+00N 7+90W	203 205	55	0.8	1.12	5	270	< 0.5	< 2	0.08	< 0.5	3	188	18	1.96	10	< 1	0.24	30	0.33	100
VG 0+00N 8+00W	203 205	25	0.4	1.00	< 5	250	< 0.5	4	0.09	< 0.5	2	420	11	1.89	< 10	< 1	0.18	20	0.37	80
VG 0+00N 8+10W	203 205	25	0.2	1.19	10	250	< 0.5	< 2	0.13	< 0.5	5	185	11	1.90	< 10	< 1	0.15	20	0.34	185
VG 0+00N 8+20W	203 205	15	< 0.2	1.07	5	240	< 0.5	< 2	0.12	< 0.5	3	251	12	1.77	< 10	< 1	0.12	20	0.29	75
VG 0+00N 8+30W	203 205	70	0.6	1.17	5	210	< 0.5	< 2	0.15	< 0.5	3	175	7	1.86	10	< 1	0.16	20	0.34	90
VG 0+00N 8+40W	203 205	15	0.4	1.58	5	360	< 0.5	< 2	0.20	< 0.5	4	283	9	1.80	10	< 1	0.21	20	0.33	100
VG 0+00N 8+50W	203 205	25	0.4	1.55	5	320	< 0.5	< 2	0.17	< 0.5	3	289	10	1.97	10	< 1	0.20	30	0.36	90
VG 0+00N 8+60W	203 205	25	0.2	1.02	5	210	< 0.5	< 2	0.14	< 0.5	2	316	4	1.32	< 10	< 1	0.14	30	0.27	80
VG 0+00N 8+70W	203 205	15	0.2	1.08	< 5	250	< 0.5	< 2	0.16	< 0.5	3	389	7	1.55	< 10	< 1	0.14	20	0.28	95
VG 0+00N 8+80W	203 205	15	0.8	0.72	60	180	1.0	< 2	0.13	< 0.5	2	184	7	1.00	10	1	0.10	10	0.17	55
VG 0+00N 8+90W	203 205	25	0.2	1.31	< 5	240	< 0.5	< 2	0.16	0.5	3	215	9	1.87	< 10	< 1	0.13	20	0.34	85
VG 0+00N 9+00W	203 205	15	0.2	1.22	< 5	270	< 0.5	< 2	0.18	0.5	3	513	8	1.97	< 10	< 1	0.14	20	0.33	110
VG 0+00N 9+10W	203 205	10	0.4	1.50	< 5	390	< 0.5	< 2	0.29	0.5	5	329	10	2.39	10	< 1	0.18	20	0.35	115
VG 0+00N 9+20W	203 205	10	30.0	1.51	< 5	340	< 0.5	< 2	0.21	0.5	4	223	11	2.11	< 10	< 1	0.16	20	0.41	105
VG 0+00N 9+30W	203 205	20	0.2	0.96	< 5	170	< 0.5	< 2	0.14	< 0.5	2	184	4	1.28	< 10	< 1	0.13	20	0.34	80
VG 0+00N 9+40W	203 205	25	< 0.2	1.20	< 5	240	< 0.5	< 2	0.16	0.5	3	207	7	1.75	< 10	< 1	0.14	20	0.38	95
VG 0+00N 9+50W	203 205	65	0.2	1.24	< 5	280	< 0.5	< 2	0.17	< 0.5	4	255	9	1.83	< 10	< 1	0.15	20	0.39	100
VG 0+00N 9+60W	203 205	20	0.2	1.45	< 5	270	< 0.5	< 2	0.16	0.5	3	173	6	1.84	< 10	< 1	0.16	20	0.39	95
VG 0+00N 9+70W	203 205	10	0.4	1.39	< 5	300	< 0.5	< 2	0.19	0.5	3	279	11	2.21	< 10	< 1	0.15	20	0.35	110
VG 0+00N 9+80W	203 205	10	0.2	1.19	< 5	240	< 0.5	< 2	0.18	< 0.5	3	224	8	1.67	< 10	< 1	0.14	20	0.33	95
VG 0+00N 9+90W	203 205	25	0.6	1.18	< 5	340	< 0.5	< 2	0.30	< 0.5	4	263	11	2.14	10	< 1	0.15	10	0.26	125
VG 0+00N 10+00W	203 205	15	0.6	1.43	< 5	260	< 0.5	4	0.21	< 0.5	4	343	7	1.61	10	< 1	0.19	20	0.42	120
VG 0+00N 10+10W	203 205	10	0.2	1.30	< 5	240	< 0.5	2	0.18	< 0.5	3	246	9	1.69	< 10	< 1	0.16	20	0.37	95
VG 0+00N 10+20W	203 205	15	0.4	1.19	< 5	210	< 0.5	2	0.15	< 0.5	2	297	5	1.35	10	< 1	0.18	20	0.31	80
VG 0+00N 10+30W	203 205	< 5	0.2	1.19	< 5	250	< 0.5	2	0.19	< 0.5	4	263	8	1.45	10	< 1	0.16	20	0.30	90
VG 0+00N 10+40W	203 205	15	0.2	1.11	< 5	240	< 0.5	< 2	0.19	< 0.5	3	289	7	1.52	< 10	< 1	0.15	20	0.28	85
VG 0+00N 10+50W	203 205	15	0.2	1.22	5	240	< 0.5	< 2	0.18	< 0.5	3	301	6	1.49	10	< 1	0.17	20	0.33	90
VG 0+00N 10+60W	203 205	30	0.4	1.48	< 5	280	< 0.5	< 2	0.20	< 0.5	3	213	6	1.45	10	< 1	0.21	30	0.39	105
VG 0+00N 10+70W	203 205	15	0.4	1.09	< 5	260	< 0.5	2	0.22	< 0.5	3	208	10	1.69	10	< 1	0.14	20	0.29	95
VG 0+00N 10+80W	203 205	15	0.4	1.06	5	250	< 0.5	2	0.18	< 0.5	3	299	6	1.50	10	< 1	0.16	20	0.25	95
VG 0+00N 10+90W	203 205	10	0.4	1.06	< 5	300	< 0.5	2	0.22	< 0.5	3	238	7	1.43	10	< 1	0.14	20	0.23	95
VG 0+00N 11+00W	203 205	20	0.8	1.19	5	250	< 0.5	2	0.18	< 0.5	3	170	5	1.34	10	< 1	0.17	20	0.29	85
VG 0+00N 11+10W	203 205	10	0.6	1.28	< 5	260	< 0.5	2	0.18	< 0.5	2	251	5	1.20	10	< 1	0.19	20	0.29	85
VG 0+00N 11+20W	203 205	20	0.8	1.35	< 5	250	0.5	2	0.16	< 0.5	2	198	2	1.14	10	< 1	0.26	30	0.35	90

CERTIFICATION: B. Caughlin

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

[redacted]: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Page [redacted]er : 6-B
Total P[redacted]s : 6
Invoice Date: 14-OCT-90
Invoice No. : I-9024267
P.O. Number :

CERTIFICATE OF ANALYSIS A9024267

SAMPLE DESCRIPTION	PREP CODE	Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
VG 0+00N 7+90W	203 205	1	0.01	8	380	68	< 5	1	15	0.02	< 10	< 10	19	< 10	82
VG 0+00N 8+00W	203 205	1	0.03	9	410	40	< 5	1	17	0.02	< 10	< 10	16	< 10	68
VG 0+00N 8+10W	203 205	1	0.01	10	430	42	< 5	2	14	0.04	< 10	< 10	26	< 10	66
VG 0+00N 8+20W	203 205	< 1	0.01	9	420	38	< 5	1	14	0.03	10	< 10	26	< 10	52
VG 0+00N 8+30W	203 205	1	0.01	8	440	38	< 5	2	15	0.05	10	< 10	33	< 10	56
VG 0+00N 8+40W	203 205	< 1	0.02	11	560	32	< 5	2	22	0.05	< 10	< 10	25	< 10	64
VG 0+00N 8+50W	203 205	1	0.02	11	440	44	< 5	2	20	0.06	< 10	< 10	32	< 10	58
VG 0+00N 8+60W	203 205	< 1	0.02	8	330	20	< 5	1	16	0.04	< 10	< 10	21	< 10	42
VG 0+00N 8+70W	203 205	< 1	0.02	10	420	18	< 5	1	17	0.04	< 10	< 10	22	< 10	48
VG 0+00N 8+80W	203 205	< 1	< 0.01	11	310	< 2	30	1	13	0.02	50	10	14	< 10	40
VG 0+00N 8+90W	203 205	< 1	0.01	10	410	22	< 5	2	17	0.04	< 10	< 10	24	< 10	58
VG 0+00N 9+00W	203 205	< 1	0.02	12	430	18	< 5	2	19	0.04	< 10	< 10	24	< 10	62
VG 0+00N 9+10W	203 205	< 1	0.02	13	640	24	< 5	2	31	0.04	< 10	< 10	23	< 10	104
VG 0+00N 9+20W	203 205	< 1	0.01	12	600	24	< 5	2	24	0.04	< 10	< 10	23	< 10	78
VG 0+00N 9+30W	203 205	< 1	0.01	7	340	12	< 5	1	14	0.04	< 10	< 10	19	< 10	48
VG 0+00N 9+40W	203 205	< 1	0.01	10	360	18	< 5	1	17	0.04	< 10	< 10	24	< 10	58
VG 0+00N 9+50W	203 205	< 1	0.02	10	370	16	< 5	2	18	0.04	< 10	< 10	27	< 10	64
VG 0+00N 9+60W	203 205	< 1	0.01	9	390	16	< 5	2	19	0.04	< 10	< 10	28	< 10	58
VG 0+00N 9+70W	203 205	< 1	0.02	11	610	20	< 5	2	21	0.04	< 10	< 10	22	< 10	64
VG 0+00N 9+80W	203 205	< 1	0.01	10	470	16	< 5	1	20	0.04	< 10	< 10	21	< 10	54
VG 0+00N 9+90W	203 205	< 1	0.02	12	720	18	< 5	2	31	0.04	< 10	< 10	20	< 10	98
VG 0+00N 10+00W	203 205	< 1	0.02	10	420	22	< 5	2	22	0.05	< 10	< 10	23	< 10	80
VG 0+00N 10+10W	203 205	< 1	0.01	11	430	20	< 5	2	20	0.04	< 10	< 10	22	< 10	56
VG 0+00N 10+20W	203 205	< 1	0.01	9	330	16	< 5	2	17	0.04	< 10	< 10	18	< 10	44
VG 0+00N 10+30W	203 205	< 1	0.01	10	490	16	< 5	1	22	0.04	< 10	< 10	17	< 10	56
VG 0+00N 10+40W	203 205	< 1	0.01	9	440	16	< 5	1	21	0.03	< 10	< 10	17	< 10	58
VG 0+00N 10+50W	203 205	< 1	0.01	11	410	14	< 5	2	21	0.04	< 10	< 10	17	< 10	54
VG 0+00N 10+60W	203 205	< 1	0.01	10	340	22	< 5	2	22	0.05	< 10	< 10	22	< 10	58
VG 0+00N 10+70W	203 205	< 1	0.01	9	520	16	< 5	1	24	0.03	< 10	< 10	19	< 10	52
VG 0+00N 10+80W	203 205	< 1	0.01	10	500	14	< 5	1	21	0.03	< 10	< 10	15	< 10	46
VG 0+00N 10+90W	203 205	< 1	0.01	10	520	14	< 5	1	26	0.03	< 10	< 10	15	< 10	60
VG 0+00N 11+00W	203 205	< 1	0.01	8	400	16	< 5	2	20	0.04	< 10	< 10	19	< 10	46
VG 0+00N 11+10W	203 205	< 1	0.01	9	330	16	< 5	2	20	0.05	< 10	< 10	19	< 10	46
VG 0+00N 11+20W	203 205	< 1	0.02	8	280	14	< 5	2	19	0.05	< 10	< 10	20	< 10	50

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

A9024266

Comments: CC: A..TROUP

CERTIFICATE A9024266

ARBOR RESOURCES INC.

Project: AOR-DAWSON
P.O. # :

Samples submitted to our lab in Vancouver, BC.
This report was printed on 14-OCT-90.

SAMPLE PREPARATION

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION
203	240	Dry, sieve to -35 mesh
205	240	Geochem ring to approx 150 mesh
238	240	NITRIC-AQUA REGIA DIGESTION

* NOTE 1:

The 32 element ICP package is suitable for trace metals in soil and rock samples. Elements for which the nitric-aqua regia digestion is possibly incomplete are: Al, Ba, Be, Ca, Cr, Ga, K, La, Mg, Na, Sr, Ti, Tl, W.

ANALYTICAL PROCEDURES

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION	METHOD	DETECTION LIMIT	UPPER LIMIT
100	240	Au ppb: Fuse 10 g sample	FA-AAS	5	10000
922	240	Ag ppm: 32 element, soil & rock	ICP-AES	0.2	200
921	240	Al %: 32 element, soil & rock	ICP-AES	0.01	15.00
923	240	As ppm: 32 element, soil & rock	ICP-AES	5	10000
924	240	Ba ppm: 32 element, soil & rock	ICP-AES	10	10000
925	240	Be ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
926	240	Bi ppm: 32 element, soil & rock	ICP-AES	2	10000
927	240	Ca %: 32 element, soil & rock	ICP-AES	0.01	15.00
928	240	Cd ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
929	240	Co ppm: 32 element, soil & rock	ICP-AES	1	10000
930	240	Cr ppm: 32 element, soil & rock	ICP-AES	1	10000
931	240	Cu ppm: 32 element, soil & rock	ICP-AES	1	10000
932	240	Fe %: 32 element, soil & rock	ICP-AES	0.01	15.00
933	240	Ga ppm: 32 element, soil & rock	ICP-AES	10	10000
951	240	Hg ppm: 32 element, soil & rock	ICP-AES	1	10000
934	240	K %: 32 element, soil & rock	ICP-AES	0.01	10.00
935	240	La ppm: 32 element, soil & rock	ICP-AES	10	10000
936	240	Mg %: 32 element, soil & rock	ICP-AES	0.01	15.00
937	240	Mn ppm: 32 element, soil & rock	ICP-AES	5	10000
938	240	Mo ppm: 32 element, soil & rock	ICP-AES	1	10000
939	240	Na %: 32 element, soil & rock	ICP-AES	0.01	5.00
940	240	Ni ppm: 32 element, soil & rock	ICP-AES	1	10000
941	240	P ppm: 32 element, soil & rock	ICP-AES	10	10000
942	240	Pb ppm: 32 element, soil & rock	ICP-AES	2	10000
943	240	Sb ppm: 32 element, soil & rock	ICP-AES	5	10000
958	240	Sc ppm: 32 elements, soil & rock	ICP-AES	1	10000
944	240	Sr ppm: 32 element, soil & rock	ICP-AES	1	10000
945	240	Ti %: 32 element, soil & rock	ICP-AES	0.01	5.00
946	240	Tl ppm: 32 element, soil & rock	ICP-AES	10	10000
947	240	U ppm: 32 element, soil & rock	ICP-AES	10	10000
948	240	V ppm: 32 element, soil & rock	ICP-AES	1	10000
949	240	W ppm: 32 element, soil & rock	ICP-AES	10	10000
950	240	Zn ppm: 32 element, soil & rock	ICP-AES	2	10000

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Page Number : 1-A
Total Pages : 6
Invoice Date: 14-OCT-90
Invoice No. : I-9024266
P.O. Number :

CERTIFICATE OF ANALYSIS A9024266

SAMPLE DESCRIPTION	PREP CODE	Au ppb FA+AA	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
GG 000N 0000W	203 205	< 5	0.2	1.57	5	210	< 0.5	< 2	0.09	< 0.5	2	76	10	2.01	< 10	< 1	0.16	20	0.28	100
GG 000N 0010W	203 205	10	< 0.2	2.24	< 5	240	< 0.5	< 2	0.09	< 0.5	4	51	10	2.88	< 10	< 1	0.12	20	0.43	165
GG 000N 0020W	203 205	25	0.2	1.73	5	300	< 0.5	< 2	0.06	< 0.5	2	60	9	2.02	< 10	< 1	0.23	30	0.41	185
GG 000N 0030W	203 205	< 5	< 0.2	1.66	5	250	< 0.5	< 2	0.08	< 0.5	2	53	10	2.05	< 10	< 1	0.19	20	0.48	150
GG 000N 0040W	203 205	35	< 0.2	1.88	< 5	200	< 0.5	< 2	0.13	< 0.5	3	63	12	2.45	< 10	< 1	0.11	20	0.43	155
GG 000N 0050W	203 205	< 5	< 0.2	1.67	< 5	200	< 0.5	< 2	0.12	< 0.5	3	60	6	2.04	< 10	< 1	0.12	20	0.43	130
GG 000N 0060W	203 205	< 5	< 0.2	1.84	< 5	220	< 0.5	2	0.12	< 0.5	2	67	10	2.21	< 10	< 1	0.09	10	0.30	120
GG 000N 0070W	203 205	15	< 0.2	2.16	5	200	< 0.5	< 2	0.13	< 0.5	4	57	14	3.19	< 10	< 1	0.10	20	0.51	210
GG 000N 0080W	203 205	< 5	< 0.2	1.65	10	150	< 0.5	< 2	0.09	< 0.5	4	58	10	3.09	< 10	< 1	0.12	10	0.73	190
GG 000N 0090W	203 205	25	< 0.2	1.92	5	190	< 0.5	< 2	0.10	< 0.5	6	43	16	2.59	< 10	< 1	0.11	20	0.55	210
GG 000N 0100W	203 205	< 5	0.2	1.53	< 5	210	< 0.5	< 2	0.07	< 0.5	3	38	12	2.23	< 10	< 1	0.17	30	0.56	150
GG 000N 0110W	203 205	< 5	0.2	1.66	< 5	380	< 0.5	< 2	0.08	< 0.5	4	61	23	2.33	< 10	< 1	0.23	30	0.80	230
GG 000N 0120W	203 205	15	< 0.2	1.69	< 5	310	< 0.5	< 2	0.08	< 0.5	4	66	15	2.33	< 10	< 1	0.15	20	0.70	170
GG 000N 0130W	203 205	< 5	< 0.2	1.86	5	230	< 0.5	< 2	0.12	< 0.5	5	69	15	3.33	< 10	< 1	0.12	10	0.52	250
GG 000N 0140W	203 205	725	< 0.2	1.85	< 5	260	< 0.5	< 2	0.12	< 0.5	5	56	16	2.65	< 10	< 1	0.16	20	0.48	205
GG 000N 0150W	203 205	< 5	< 0.2	1.95	< 5	220	< 0.5	< 2	0.14	< 0.5	4	56	9	3.09	< 10	< 1	0.10	20	0.40	230
GG 000N 0160W	203 205	< 5	0.4	1.34	< 5	310	< 0.5	< 2	0.10	< 0.5	3	73	9	1.97	< 10	< 1	0.23	20	0.25	210
GG 000N 0170W	203 205	20	0.2	3.05	< 5	380	< 0.5	< 2	0.14	< 0.5	9	56	21	3.39	< 10	< 1	0.17	20	0.54	405
GG 000N 0180W	203 205	30	0.2	1.32	5	280	< 0.5	< 2	0.10	< 0.5	2	54	13	1.35	< 10	< 1	0.16	40	0.24	105
GG 000N 0190W	203 205	5	0.2	1.39	5	210	< 0.5	2	0.08	< 0.5	3	46	14	1.84	< 10	< 1	0.18	30	0.34	145
GG 000N 0200W	203 205	< 5	< 0.2	1.48	< 5	230	< 0.5	2	0.07	< 0.5	4	44	34	2.02	< 10	< 1	0.09	20	0.40	190
GG 000N 0210W	203 205	< 5	< 0.2	1.11	< 5	320	< 0.5	2	0.09	< 0.5	1	56	12	1.26	< 10	< 1	0.08	20	0.14	75
GG 000N 0220W	203 205	5	< 0.2	1.67	< 5	200	< 0.5	< 2	0.08	< 0.5	3	42	9	2.28	< 10	< 1	0.08	10	0.29	105
GG 000N 0230W	203 205	< 5	< 0.2	1.42	5	190	< 0.5	< 2	0.06	< 0.5	3	47	8	2.04	< 10	< 1	0.10	10	0.28	130
GG 000N 0240W	203 205	< 5	< 0.2	1.83	5	170	< 0.5	< 2	0.08	< 0.5	4	50	8	2.65	< 10	< 1	0.09	10	0.34	185
GG 000N 0250W	203 205	5	0.2	1.33	5	190	< 0.5	2	0.07	< 0.5	3	48	7	1.72	< 10	< 1	0.11	20	0.24	160
GG 000N 0260W	203 205	10	0.2	1.63	< 5	230	< 0.5	< 2	0.09	< 0.5	5	48	11	1.99	< 10	< 1	0.14	30	0.33	170
GG 000N 0270W	203 205	5	0.2	1.61	5	260	< 0.5	< 2	0.08	< 0.5	3	70	11	1.80	< 10	< 1	0.14	30	0.27	125
GG 000N 0280W	203 205	30	0.4	1.21	< 5	210	< 0.5	2	0.05	< 0.5	2	47	7	1.23	< 10	< 1	0.18	30	0.23	95
GG 000N 0290W	203 205	15	0.2	1.03	< 5	200	< 0.5	< 2	0.06	< 0.5	1	73	5	1.09	< 10	< 1	0.20	30	0.18	70
GG 000N 0300W	203 205	< 5	0.4	0.82	5	170	< 0.5	< 2	0.04	< 0.5	1	45	3	0.76	< 10	< 1	0.17	20	0.14	60
GG 000N 0310W	203 205	< 5	< 0.2	1.34	5	200	< 0.5	2	0.07	< 0.5	3	47	6	1.69	< 10	< 1	0.13	20	0.25	140
GG 000N 0320W	203 205	5	< 0.2	1.80	< 5	270	< 0.5	< 2	0.10	< 0.5	4	58	14	2.12	< 10	< 1	0.13	20	0.34	170
GG 000N 0330W	203 205	< 5	0.2	1.71	< 5	260	< 0.5	< 2	0.10	< 0.5	4	50	11	2.09	< 10	< 1	0.14	30	0.36	195
GG 000N 0340W	203 205	5	0.2	1.75	10	260	< 0.5	< 2	0.11	< 0.5	5	56	10	2.37	< 10	< 1	0.15	30	0.35	250
GG 000N 0350W	203 205	10	0.4	1.82	10	390	< 0.5	< 2	0.11	< 0.5	5	64	14	2.27	< 10	< 1	0.17	40	0.34	270
GG 000N 0360W	203 205	10	< 0.2	1.63	10	360	0.5	< 2	0.12	< 0.5	5	59	14	2.28	< 10	< 1	0.15	30	0.32	255
GG 000N 0370W	203 205	5	0.4	1.13	< 5	220	< 0.5	2	0.04	< 0.5	2	54	7	1.31	< 10	< 1	0.17	20	0.26	95
GG 000N 0380W	203 205	10	0.6	1.56	< 5	470	< 0.5	< 2	0.09	< 0.5	3	53	15	1.77	< 10	< 1	0.17	30	0.31	140
GG 000N 0390W	203 205	25	0.4	1.50	< 5	300	< 0.5	< 2	0.09	< 0.5	4	68	10	1.94	< 10	< 1	0.14	20	0.37	165

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Page Number : 1-B
Total Pages : 6
Invoice Date: 14-OCT-90
Invoice No. : I-9024266
P.O. Number :

CERTIFICATE OF ANALYSIS A9024266

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
GG 000N 0000W	203	205	< 1	0.01	7	160	34	< 5	2	9	0.04	< 10	< 10	40	< 10	40
GG 000N 0010W	203	205	1	0.01	11	200	24	< 5	3	10	0.06	< 10	< 10	54	< 10	52
GG 000N 0020W	203	205	< 1	0.01	6	160	22	< 5	2	7	0.02	< 10	< 10	27	< 10	80
GG 000N 0030W	203	205	< 1	0.01	5	140	18	< 5	2	8	0.03	< 10	< 10	31	< 10	82
GG 000N 0040W	203	205	1	0.01	9	350	18	< 5	2	13	0.06	< 10	< 10	53	< 10	46
GG 000N 0050W	203	205	< 1	0.01	8	150	16	< 5	2	12	0.06	< 10	< 10	44	< 10	42
GG 000N 0060W	203	205	< 1	0.01	7	820	22	< 5	2	13	0.05	< 10	< 10	52	< 10	38
GG 000N 0070W	203	205	1	0.02	12	360	14	< 5	3	12	0.07	< 10	< 10	67	< 10	56
GG 000N 0080W	203	205	1	0.01	11	560	16	< 5	2	10	0.06	< 10	< 10	69	< 10	54
GG 000N 0090W	203	205	1	0.01	15	160	46	< 5	2	10	0.05	< 10	< 10	46	< 10	58
GG 000N 0100W	203	205	1	0.01	8	240	40	< 5	1	8	0.02	< 10	< 10	38	< 10	66
GG 000N 0110W	203	205	1	0.01	8	300	38	< 5	2	10	0.03	< 10	< 10	30	< 10	76
GG 000N 0120W	203	205	1	0.01	9	220	28	< 5	2	9	0.04	< 10	< 10	39	< 10	62
GG 000N 0130W	203	205	1	0.01	13	350	18	< 5	3	11	0.07	< 10	< 10	60	< 10	68
GG 000N 0140W	203	205	1	0.01	12	270	12	< 5	3	13	0.06	< 10	< 10	54	< 10	58
GG 000N 0150W	203	205	1	0.02	9	300	28	< 5	3	17	0.09	< 10	< 10	77	< 10	50
GG 000N 0160W	203	205	1	0.01	6	550	28	< 5	1	12	0.03	< 10	< 10	41	< 10	58
GG 000N 0170W	203	205	1	0.01	17	350	60	< 5	4	16	0.07	< 10	< 10	60	< 10	80
GG 000N 0180W	203	205	1	0.01	5	260	296	< 5	1	11	0.02	< 10	< 10	29	< 10	44
GG 000N 0190W	203	205	1	0.01	9	190	84	< 5	2	10	0.03	< 10	< 10	30	< 10	54
GG 000N 0200W	203	205	1	0.01	9	130	50	< 5	2	8	0.03	< 10	< 10	35	< 10	52
GG 000N 0210W	203	205	< 1	0.01	5	400	72	< 5	< 1	10	0.01	< 10	< 10	27	< 10	28
GG 000N 0220W	203	205	1	0.01	9	180	54	< 5	2	8	0.05	< 10	< 10	45	< 10	40
GG 000N 0230W	203	205	< 1	0.01	8	160	32	< 5	2	7	0.04	< 10	< 10	37	< 10	44
GG 000N 0240W	203	205	1	0.01	12	250	28	< 5	2	8	0.05	< 10	< 10	52	< 10	52
GG 000N 0250W	203	205	< 1	0.01	7	210	30	< 5	2	7	0.04	< 10	< 10	36	< 10	40
GG 000N 0260W	203	205	< 1	0.01	11	210	48	< 5	2	10	0.04	< 10	< 10	38	< 10	54
GG 000N 0270W	203	205	< 1	0.02	8	300	62	< 5	2	10	0.04	< 10	< 10	42	< 10	52
GG 000N 0280W	203	205	< 1	0.01	6	100	36	< 5	1	7	0.02	< 10	< 10	23	< 10	42
GG 000N 0290W	203	205	1	0.01	4	110	24	< 5	1	8	0.03	< 10	< 10	25	< 10	40
GG 000N 0300W	203	205	< 1	0.01	4	70	20	< 5	1	5	0.02	< 10	< 10	19	< 10	28
GG 000N 0310W	203	205	< 1	0.01	6	140	26	< 5	1	8	0.04	< 10	< 10	39	< 10	40
GG 000N 0320W	203	205	1	0.01	10	280	46	< 5	1	12	0.03	< 10	< 10	47	< 10	58
GG 000N 0330W	203	205	1	0.01	9	190	34	< 5	2	11	0.05	< 10	< 10	49	< 10	56
GG 000N 0340W	203	205	1	0.01	9	240	44	< 5	2	11	0.05	< 10	< 10	52	< 10	64
GG 000N 0350W	203	205	1	0.01	11	400	64	< 5	2	13	0.04	< 10	< 10	43	< 10	68
GG 000N 0360W	203	205	1	0.02	10	350	66	< 5	2	15	0.05	< 10	< 10	49	< 10	68
GG 000N 0370W	203	205	1	0.01	5	90	48	< 5	1	5	0.02	< 10	< 10	22	< 10	44
GG 000N 0380W	203	205	1	0.01	9	330	64	< 5	1	13	0.03	< 10	< 10	35	< 10	58
GG 000N 0390W	203	205	1	0.01	8	190	36	< 5	2	10	0.04	< 10	< 10	36	< 10	58

CERTIFICATION: B. Caplan

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Invoice Date: 14-OCT-90
Invoice No. : I-9024266
P.O. Number :

CERTIFICATE OF ANALYSIS A9024266

SAMPLE DESCRIPTION	PREP CODE	Au ppb FA+AA	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
GG 000N 0400W	203 205	60	< 0.2	1.54	5	330	< 0.5	< 2	0.10	< 0.5	3	55	10	2.05	< 10	< 1	0.13	20	0.39	155
GG 000N 0410W	203 205	< 5	0.4	2.01	5	550	< 0.5	< 2	0.15	< 0.5	6	52	15	2.34	< 10	< 1	0.15	30	0.43	215
GG 000N 0420W	203 205	< 5	0.2	1.70	< 5	320	< 0.5	< 2	0.14	< 0.5	6	56	14	2.28	< 10	< 1	0.12	20	0.44	240
GG 000N 0430W	203 205	5	< 0.2	2.07	< 5	380	< 0.5	< 2	0.16	< 0.5	6	68	17	2.64	< 10	< 1	0.14	30	0.52	230
GG 000N 0440W	203 205	< 5	< 0.2	2.12	< 5	410	< 0.5	< 2	0.19	< 0.5	6	60	17	2.71	< 10	< 1	0.15	30	0.52	225
GG 000N 0450W	203 205	< 5	0.2	1.94	5	500	< 0.5	< 2	0.19	< 0.5	7	107	16	2.54	< 10	< 1	0.17	30	0.47	325
GG 000N 0460W	203 205	50	< 0.2	0.98	5	280	< 0.5	< 2	0.12	< 0.5	4	46	15	1.47	< 10	< 1	0.13	30	0.28	215
GG 000N 0470W	203 205	5	0.4	1.73	< 5	530	< 0.5	2	0.26	< 0.5	4	116	15	2.23	< 10	< 1	0.19	30	0.43	175
GG 000N 0480W	203 205	< 5	< 0.2	1.33	< 5	320	< 0.5	< 2	0.15	< 0.5	4	50	14	1.92	< 10	< 1	0.11	20	0.37	195
GG 000N 0490W	203 205	15	< 0.2	1.59	5	360	< 0.5	< 2	0.14	< 0.5	6	54	15	2.24	< 10	< 1	0.09	20	0.41	240
GG 000N 0500W	203 205	25	0.4	1.44	< 5	460	< 0.5	< 2	0.16	< 0.5	5	55	21	2.18	< 10	< 1	0.10	20	0.32	150
GG 000N 0510W	203 205	10	0.4	1.30	< 5	350	< 0.5	< 2	0.14	< 0.5	3	57	13	1.75	< 10	< 1	0.12	30	0.33	130
GG 000N 0520W	203 205	10	0.2	0.98	< 5	420	< 0.5	< 2	0.15	< 0.5	4	53	11	1.53	< 10	< 1	0.10	30	0.27	230
GG 000N 0530W	203 205	< 5	< 0.2	0.94	5	250	< 0.5	< 2	0.09	< 0.5	3	53	10	1.51	< 10	< 1	0.09	20	0.24	155
GG 000N 0540W	203 205	< 5	< 0.2	1.00	< 5	230	< 0.5	< 2	0.09	< 0.5	2	57	8	1.44	< 10	< 1	0.12	20	0.25	125
GG 000N 0550W	203 205	< 5	< 0.2	1.12	5	260	< 0.5	< 2	0.13	< 0.5	4	52	9	1.68	< 10	< 1	0.09	30	0.33	180
GG 000N 0560W	203 205	10	< 0.2	0.99	< 5	250	< 0.5	< 2	0.14	< 0.5	3	55	8	1.42	< 10	< 1	0.11	30	0.27	175
GG 000N 0570W	203 205	5	0.4	1.59	5	550	< 0.5	< 2	0.26	< 0.5	4	79	14	1.93	< 10	< 1	0.17	40	0.38	175
GG 000N 0580W	203 205	< 5	< 0.2	1.62	< 5	390	< 0.5	< 2	0.18	< 0.5	3	51	11	1.89	< 10	< 1	0.14	30	0.39	130
GG 000N 0590W	203 205	5	0.8	1.70	< 5	630	< 0.5	< 2	0.58	0.5	4	61	15	1.94	< 10	< 1	0.13	50	0.36	190
GG 000N 0600W	203 205	15	0.8	1.68	5	570	< 0.5	< 2	0.52	< 0.5	5	53	14	1.86	< 10	< 1	0.17	60	0.36	275
GG 000N 0610W	203 205	10	1.0	1.87	5	680	< 0.5	< 2	0.62	0.5	6	58	19	1.96	< 10	< 1	0.18	60	0.39	300
GG 000N 0620W	203 205	15	0.6	1.46	10	400	< 0.5	< 2	0.36	< 0.5	4	52	10	1.56	< 10	< 1	0.23	60	0.39	325
GG 000N 0630W	203 205	10	1.0	1.75	10	1920	0.5	< 2	0.67	1.5	4	46	26	1.74	< 10	< 1	0.21	120	0.42	365
GG 000N 0640W	203 205	10	0.4	0.71	10	570	< 0.5	< 2	0.20	0.5	6	77	22	2.34	< 10	< 1	0.23	50	0.24	485
GG 000N 0650W	203 205	30	0.6	0.54	10	770	< 0.5	< 2	0.16	0.5	5	48	17	1.90	< 10	< 1	0.25	50	0.10	320
GG 000N 0660W	203 205	15	0.6	0.66	5	420	< 0.5	< 2	0.38	< 0.5	4	45	13	1.84	< 10	< 1	0.23	70	0.18	170
GG 000N 0670W	203 205	< 5	< 0.2	0.52	< 5	970	< 0.5	< 2	0.28	0.5	1	52	10	0.74	< 10	< 1	0.24	50	0.09	75
GG 000N 0680W	203 205	10	0.4	1.00	10	960	< 0.5	< 2	0.97	0.5	4	49	26	1.37	< 10	< 1	0.22	110	0.21	455
GG 000N 0690W	203 205	10	< 0.2	0.75	5	710	< 0.5	< 2	0.22	< 0.5	2	63	11	1.36	< 10	< 1	0.25	50	0.24	195
GG 000N 0700W	203 205	< 5	0.4	1.15	< 5	590	< 0.5	< 2	0.31	< 0.5	2	42	13	1.67	< 10	< 1	0.30	70	0.49	110
GG 000N 0710W	203 205	< 5	0.6	1.18	< 5	820	< 0.5	< 2	0.74	< 0.5	3	54	12	1.66	< 10	< 1	0.23	70	0.40	195
GG 000N 0720W	203 205	< 5	0.4	1.39	5	720	< 0.5	< 2	0.80	0.5	4	49	17	1.97	< 10	< 1	0.33	80	0.52	305
GG 000N 0730W	203 205	< 5	0.4	1.35	< 5	670	< 0.5	< 2	1.11	< 0.5	3	53	16	1.81	< 10	< 1	0.16	60	0.41	145
GG 000N 0740W	203 205	< 5	0.4	1.32	< 5	480	< 0.5	< 2	0.53	< 0.5	4	47	17	1.92	< 10	< 1	0.18	40	0.42	245
GG 000N 0750W	203 205	< 5	0.6	1.31	5	1020	< 0.5	2	1.26	0.5	5	34	19	1.88	< 10	< 1	0.30	80	0.54	950
GG 000N 0760W	203 205	< 5	0.4	1.08	5	650	< 0.5	< 2	0.43	< 0.5	3	57	12	1.76	< 10	< 1	0.27	70	0.50	225
GG 000N 0770W	203 205	15	0.4	1.20	5	910	< 0.5	< 2	0.73	1.0	8	48	19	2.21	< 10	< 1	0.29	80	0.50	1085
GG 000N 0780W	203 205	< 5	0.4	1.06	< 5	440	< 0.5	< 2	0.38	0.5	2	65	8	1.33	< 10	< 1	0.18	50	0.48	110
GG 000N 0790W	203 205	< 5	< 0.2	1.26	< 5	510	< 0.5	< 2	0.30	< 0.5	3	98	8	1.54	< 10	< 1	0.23	50	0.70	150

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Invoice Date: 14-OCT-90
Invoice No. : I-9024266
P.O. Number :

CERTIFICATE OF ANALYSIS A9024266

SAMPLE DESCRIPTION	PREP CODE	Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
GG 000N 0400W	203 205	1	0.01	8	170	42	< 5	2	11	0.04	< 10	< 10	38	< 10	56
GG 000N 0410W	203 205	1	0.01	10	300	48	< 5	2	18	0.05	< 10	< 10	51	< 10	64
GG 000N 0420W	203 205	< 1	0.01	12	170	32	< 5	3	14	0.06	< 10	< 10	44	< 10	62
GG 000N 0430W	203 205	< 1	0.01	14	240	34	< 5	3	18	0.07	< 10	< 10	52	< 10	72
GG 000N 0440W	203 205	1	0.01	13	250	36	< 5	3	19	0.07	< 10	< 10	55	< 10	72
GG 000N 0450W	203 205	1	0.02	13	330	30	< 5	3	20	0.06	< 10	< 10	51	< 10	70
GG 000N 0460W	203 205	1	0.01	7	180	68	< 5	2	11	0.03	< 10	< 10	24	< 10	56
GG 000N 0470W	203 205	1	0.02	13	250	32	< 5	3	23	0.06	< 10	< 10	45	< 10	64
GG 000N 0480W	203 205	< 1	0.01	10	160	44	< 5	3	13	0.05	< 10	< 10	36	< 10	54
GG 000N 0490W	203 205	1	0.01	12	190	32	< 5	3	12	0.05	< 10	< 10	42	< 10	58
GG 000N 0500W	203 205	1	0.01	12	400	50	< 5	3	16	0.04	< 10	< 10	40	< 10	60
GG 000N 0510W	203 205	1	0.01	9	250	42	< 5	2	13	0.03	< 10	< 10	33	< 10	60
GG 000N 0520W	203 205	< 1	0.01	8	270	42	< 5	2	15	0.03	< 10	< 10	27	< 10	56
GG 000N 0530W	203 205	< 1	0.01	7	190	38	< 5	1	9	0.03	< 10	< 10	27	< 10	46
GG 000N 0540W	203 205	< 1	0.01	6	160	30	< 5	1	8	0.03	< 10	< 10	27	< 10	44
GG 000N 0550W	203 205	< 1	0.01	8	190	34	< 5	2	11	0.04	< 10	< 10	30	< 10	50
GG 000N 0560W	203 205	< 1	0.01	7	190	34	< 5	2	11	0.04	< 10	< 10	26	< 10	46
GG 000N 0570W	203 205	1	0.01	10	400	54	< 5	3	23	0.04	< 10	< 10	37	< 10	68
GG 000N 0580W	203 205	< 1	0.01	10	210	42	< 5	3	16	0.05	< 10	< 10	39	< 10	60
GG 000N 0590W	203 205	1	0.01	11	390	56	< 5	3	44	0.03	< 10	< 10	35	< 10	62
GG 000N 0600W	203 205	1	0.01	10	420	68	< 5	3	38	0.02	< 10	< 10	29	< 10	122
GG 000N 0610W	203 205	1	0.01	14	520	90	< 5	3	49	0.02	< 10	< 10	34	< 10	140
GG 000N 0620W	203 205	< 1	0.01	8	270	66	< 5	3	27	0.02	< 10	< 10	21	< 10	146
GG 000N 0630W	203 205	1	0.01	16	530	92	< 5	4	58	0.01	< 10	< 10	20	< 10	166
GG 000N 0640W	203 205	1	0.02	8	570	190	< 5	1	42	< 0.01	< 10	< 10	5	< 10	168
GG 000N 0650W	203 205	1	0.01	6	330	80	< 5	2	28	< 0.01	< 10	< 10	4	< 10	114
GG 000N 0660W	203 205	1	0.01	5	410	64	< 5	2	48	< 0.01	< 10	< 10	7	< 10	78
GG 000N 0670W	203 205	< 1	0.01	3	240	44	< 5	1	25	< 0.01	< 10	< 10	4	< 10	48
GG 000N 0680W	203 205	1	0.01	8	400	98	< 5	2	78	0.01	< 10	< 10	11	< 10	84
GG 000N 0690W	203 205	1	0.01	5	290	50	< 5	1	29	< 0.01	< 10	< 10	5	< 10	78
GG 000N 0700W	203 205	1	0.02	6	320	54	< 5	2	48	< 0.01	< 10	< 10	7	< 10	74
GG 000N 0710W	203 205	1	0.02	7	460	50	< 5	2	75	0.01	< 10	< 10	12	< 10	72
GG 000N 0720W	203 205	1	0.02	9	480	56	< 5	3	77	0.01	< 10	< 10	13	< 10	88
GG 000N 0730W	203 205	< 1	0.02	11	480	38	< 5	3	83	0.03	< 10	< 10	26	< 10	62
GG 000N 0740W	203 205	< 1	0.01	12	250	34	< 5	3	44	0.04	< 10	< 10	31	< 10	54
GG 000N 0750W	203 205	< 1	0.01	10	560	52	< 5	2	106	< 0.01	< 10	< 10	12	< 10	98
GG 000N 0760W	203 205	1	0.01	7	350	52	< 5	2	52	< 0.01	< 10	< 10	9	< 10	78
GG 000N 0770W	203 205	1	0.02	11	490	58	< 5	2	78	< 0.01	< 10	< 10	12	< 10	110
GG 000N 0780W	203 205	< 1	0.01	7	320	32	< 5	2	41	0.01	< 10	< 10	11	< 10	66
GG 000N 0790W	203 205	< 1	0.01	8	270	38	< 5	2	38	0.01	< 10	< 10	12	< 10	84

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Page Number : 3-A
Total Pages : 6
Invoice Date: 14-OCT-90
Invoice No. : I-9024266
P.O. Number :

CERTIFICATE OF ANALYSIS A9024266

SAMPLE DESCRIPTION	PREP CODE	Au ppb FA+AA	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
GG 000N 0800W	203 205	< 5	0.6	1.38	5	700	< 0.5	< 2	0.65	0.5	8	68	20	1.82	< 10	< 1	0.22	60	0.59	1060
GG 000N 0810W	203 205	< 5	0.4	1.66	15	500	< 0.5	2	0.35	< 0.5	4	53	41	2.18	< 10	< 1	0.36	40	0.94	245
GG 000N 0820W	203 205	< 5	< 0.2	1.35	5	540	< 0.5	2	0.27	< 0.5	5	84	9	1.65	< 10	< 1	0.26	50	0.76	380
GG 000N 0830W	203 205	< 5	0.4	1.60	< 5	550	< 0.5	< 2	0.41	< 0.5	5	51	11	1.66	< 10	< 1	0.28	50	0.78	235
GG 000N 0840W	203 205	< 5	< 0.2	1.48	< 5	470	< 0.5	< 2	0.45	< 0.5	4	65	12	1.55	< 10	< 1	0.22	50	0.83	230
GG 000N 0850W	203 205	< 5	0.4	1.73	25	910	< 0.5	< 2	0.79	0.5	8	52	24	2.90	< 10	< 1	0.31	80	0.76	1160
GG 000N 0860W	203 205	< 5	0.4	1.42	5	540	< 0.5	< 2	0.36	< 0.5	4	56	15	1.58	< 10	< 1	0.25	50	0.76	255
GG 000N 0870W	203 205	< 5	0.8	1.59	15	710	< 0.5	< 2	0.70	0.5	9	53	32	2.05	< 10	< 1	0.27	60	0.75	1725
GG 000N 0880W	203 205	< 5	0.8	1.51	5	720	< 0.5	< 2	0.54	< 0.5	6	38	25	1.80	< 10	< 1	0.27	50	0.78	400
GG 000N 0890W	203 205	15	0.8	1.51	15	1100	< 0.5	< 2	0.73	0.5	9	53	38	1.82	< 10	< 1	0.36	40	0.50	1720
GG 000N 0900W	203 205	< 5	< 0.2	1.17	40	490	< 0.5	< 2	0.26	< 0.5	4	49	35	1.73	< 10	< 1	0.25	50	0.50	350
GG 000N 0910W	203 205	10	0.4	1.46	20	810	< 0.5	< 2	0.46	< 0.5	8	50	36	2.03	< 10	< 1	0.28	50	0.56	775
GG 000N 0920W	203 205	< 5	0.8	1.49	20	660	< 0.5	< 2	0.33	< 0.5	6	59	32	2.00	< 10	< 1	0.26	40	0.52	370
GG 000N 0930W	203 205	< 5	0.4	1.33	30	790	< 0.5	< 2	0.37	< 0.5	8	43	45	1.86	< 10	< 1	0.28	50	0.53	630
GG 000N 0940W	203 205	< 5	< 0.2	1.07	5	380	< 0.5	< 2	0.24	< 0.5	3	69	14	1.51	< 10	< 1	0.37	40	0.51	190
GG 000N 0950W	203 205	< 5	1.2	1.15	5	1080	< 0.5	< 2	0.78	1.0	3	45	34	1.43	< 10	< 1	0.29	40	0.32	250
GG 000N 0960W	203 205	15	0.8	1.15	5	560	< 0.5	< 2	0.43	0.5	4	75	27	1.71	< 10	< 1	0.32	30	0.40	195
GG 000N 0970W	203 205	30	1.2	1.39	10	860	< 0.5	< 2	0.82	0.5	6	62	36	1.94	< 10	< 1	0.30	40	0.44	1100
GG 000N 0980W	203 205	25	1.2	1.53	< 5	780	< 0.5	< 2	1.11	0.5	7	78	39	2.41	< 10	< 1	0.35	40	0.84	395
GG 000N 0990W	203 205	10	0.4	1.90	25	970	< 0.5	< 2	1.07	< 0.5	11	66	36	2.79	< 10	< 1	0.24	40	0.65	1685
GG 000N 1000W	203 205	< 5	0.6	1.46	10	840	< 0.5	< 2	0.77	0.5	6	73	34	2.17	< 10	< 1	0.22	40	0.56	805
GG 000N 1010W	203 205	5	0.4	1.50	< 5	730	< 0.5	< 2	0.57	< 0.5	4	66	26	1.72	< 10	< 1	0.20	40	0.55	185
GG 000N 1020W	203 205	< 5	< 0.2	0.95	10	410	< 0.5	2	0.26	< 0.5	6	73	12	1.56	< 10	< 1	0.16	20	0.35	395
GG 000N 1030W	203 205	< 5	< 0.2	1.21	5	510	< 0.5	< 2	0.32	< 0.5	5	64	15	1.79	< 10	< 1	0.20	30	0.42	365
GG 000N 1040W	203 205	< 5	< 0.2	1.45	5	590	< 0.5	< 2	0.38	< 0.5	6	70	16	2.10	< 10	< 1	0.29	50	0.74	460
GG 000N 1050W	203 205	< 5	< 0.2	1.16	5	330	< 0.5	< 2	0.19	< 0.5	4	68	11	1.63	< 10	< 1	0.29	40	0.52	230
GG 000N 1060W	203 205	< 5	< 0.2	1.26	15	370	< 0.5	< 2	0.25	< 0.5	7	67	12	2.13	< 10	< 1	0.28	30	0.69	575
GG 000N 1070W	203 205	< 5	< 0.2	1.01	10	280	< 0.5	< 2	0.22	< 0.5	5	62	10	1.74	< 10	< 1	0.26	40	0.55	260
GG 000N 1080W	203 205	< 5	< 0.2	1.15	10	320	< 0.5	< 2	0.29	< 0.5	5	61	12	1.80	< 10	< 1	0.25	40	0.54	260
GG 000N 1090W	203 205	< 5	< 0.2	1.35	5	470	< 0.5	< 2	0.27	< 0.5	5	57	8	1.86	< 10	< 1	0.32	40	0.48	480
GG 000N 1100W	203 205	< 5	< 0.2	1.48	15	280	< 0.5	2	0.21	< 0.5	4	53	11	2.27	< 10	< 1	0.32	40	0.71	195
GG 000N 1110W	203 205	< 5	< 0.2	1.54	25	410	< 0.5	< 2	0.25	< 0.5	5	66	13	2.22	< 10	< 1	0.35	40	0.68	590
GG 000N 1120W	203 205	< 5	< 0.2	1.54	20	380	< 0.5	< 2	0.28	0.5	6	62	12	2.32	< 10	< 1	0.46	50	0.85	465
GG 000N 1130W	203 205	< 5	< 0.2	1.25	10	310	< 0.5	< 2	0.24	< 0.5	5	58	10	1.96	< 10	< 1	0.37	40	0.69	300
GG 000N 1140W	203 205	< 5	< 0.2	1.25	5	330	< 0.5	< 2	0.24	< 0.5	5	65	11	1.94	< 10	< 1	0.32	40	0.62	250
GG 000N 1150W	203 205	< 5	< 0.2	1.22	5	290	< 0.5	< 2	0.17	< 0.5	4	49	10	1.81	< 10	< 1	0.24	30	0.58	225
GG 000N 1160W	203 205	< 5	< 0.2	1.33	20	440	< 0.5	< 2	0.13	< 0.5	5	48	11	1.86	< 10	< 1	0.43	50	0.45	395
GG 000N 1170W	203 205	< 5	< 0.2	1.44	5	420	< 0.5	< 2	0.19	< 0.5	4	46	10	2.04	< 10	< 1	0.33	40	0.63	200
GG 000N 1180W	203 205	< 5	< 0.2	1.16	< 5	410	< 0.5	< 2	0.23	< 0.5	2	54	7	1.52	< 10	< 1	0.40	20	0.23	265
GG 000N 1190W	203 205	45	< 0.2	1.48	110	520	< 0.5	< 2	0.51	< 0.5	7	39	24	2.86	< 10	< 1	0.47	50	0.90	410

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Page Number : 3-B
Total Pages : 6
Invoice Date: 14-OCT-90
Invoice No. : I-9024266
P.O. Number :

CERTIFICATE OF ANALYSIS A9024266

SAMPLE DESCRIPTION	PREP CODE	Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
GG 000N 0800W	203 205	1	0.01	13	450	52	< 5	3	59	0.02	< 10	< 10	20	< 10	86
GG 000N 0810W	203 205	< 1	0.01	8	290	36	< 5	3	39	0.04	< 10	< 10	20	< 10	98
GG 000N 0820W	203 205	< 1	0.01	7	240	50	< 5	2	36	0.01	< 10	< 10	13	< 10	82
GG 000N 0830W	203 205	< 1	0.01	8	360	44	< 5	3	43	0.01	< 10	< 10	16	< 10	90
GG 000N 0840W	203 205	< 1	0.01	8	300	38	< 5	3	38	0.02	< 10	< 10	15	< 10	84
GG 000N 0850W	203 205	2	0.01	11	550	56	< 5	4	72	0.01	< 10	< 10	25	< 10	100
GG 000N 0860W	203 205	< 1	0.01	7	280	44	< 5	3	37	0.03	< 10	< 10	17	< 10	76
GG 000N 0870W	203 205	1	0.01	13	560	50	< 5	3	60	0.02	< 10	< 10	20	< 10	108
GG 000N 0880W	203 205	< 1	0.01	10	400	40	< 5	3	49	0.02	< 10	< 10	19	< 10	84
GG 000N 0890W	203 205	1	0.01	17	460	42	< 5	3	56	0.02	< 10	< 10	22	< 10	104
GG 000N 0900W	203 205	2	0.01	10	370	60	< 5	2	23	0.02	< 10	< 10	17	< 10	90
GG 000N 0910W	203 205	1	0.01	16	400	42	< 5	3	34	0.03	< 10	< 10	26	< 10	78
GG 000N 0920W	203 205	1	0.01	13	390	36	< 5	3	29	0.03	< 10	< 10	26	< 10	76
GG 000N 0930W	203 205	2	0.01	15	480	42	< 5	3	34	0.02	< 10	< 10	19	< 10	82
GG 000N 0940W	203 205	< 1	0.01	7	340	18	< 5	2	20	0.04	< 10	< 10	14	< 10	64
GG 000N 0950W	203 205	< 1	0.01	14	700	30	< 5	2	64	0.02	< 10	< 10	15	< 10	70
GG 000N 0960W	203 205	< 1	0.01	12	580	38	< 5	2	32	0.02	< 10	< 10	19	< 10	68
GG 000N 0970W	203 205	1	0.01	16	790	48	< 5	3	62	0.02	< 10	< 10	21	< 10	98
GG 000N 0980W	203 205	< 1	0.01	19	900	46	< 5	4	69	0.04	< 10	< 10	25	< 10	82
GG 000N 0990W	203 205	1	0.01	20	700	32	< 5	5	71	0.05	< 10	< 10	43	< 10	76
GG 000N 1000W	203 205	< 1	0.01	16	670	26	< 5	4	58	0.03	< 10	< 10	30	< 10	86
GG 000N 1010W	203 205	< 1	0.01	14	330	26	< 5	4	39	0.04	< 10	< 10	31	< 10	60
GG 000N 1020W	203 205	< 1	0.01	8	250	24	< 5	2	18	0.03	< 10	< 10	24	< 10	48
GG 000N 1030W	203 205	< 1	0.01	10	430	20	< 5	2	20	0.03	< 10	< 10	25	< 10	64
GG 000N 1040W	203 205	< 1	0.01	11	600	24	< 5	3	28	0.03	< 10	< 10	21	< 10	82
GG 000N 1050W	203 205	< 1	0.01	6	390	24	< 5	2	16	0.04	< 10	< 10	19	< 10	60
GG 000N 1060W	203 205	< 1	0.01	7	500	36	< 5	2	19	0.03	< 10	< 10	18	< 10	74
GG 000N 1070W	203 205	< 1	0.01	6	440	20	< 5	2	16	0.03	< 10	< 10	16	< 10	64
GG 000N 1080W	203 205	< 1	0.01	8	460	22	< 5	3	19	0.04	< 10	< 10	22	< 10	62
GG 000N 1090W	203 205	< 1	0.01	7	310	10	< 5	3	20	0.03	< 10	< 10	23	< 10	58
GG 000N 1100W	203 205	< 1	0.01	9	380	22	< 5	3	16	0.04	< 10	< 10	26	< 10	72
GG 000N 1110W	203 205	< 1	0.01	9	430	24	< 5	3	18	0.03	< 10	< 10	25	< 10	82
GG 000N 1120W	203 205	< 1	0.01	9	490	30	< 5	5	19	0.03	< 10	< 10	20	< 10	84
GG 000N 1130W	203 205	< 1	0.01	6	400	24	< 5	3	18	0.04	< 10	< 10	17	< 10	66
GG 000N 1140W	203 205	< 1	0.01	7	430	16	< 5	3	17	0.05	< 10	< 10	22	< 10	62
GG 000N 1150W	203 205	< 1	0.01	6	340	24	< 5	2	13	0.04	< 10	< 10	22	< 10	54
GG 000N 1160W	203 205	< 1	0.01	7	540	20	< 5	3	10	0.01	< 10	< 10	18	< 10	60
GG 000N 1170W	203 205	< 1	0.01	8	360	18	< 5	3	13	0.03	< 10	< 10	24	< 10	66
GG 000N 1180W	203 205	< 1	0.01	5	380	14	< 5	2	16	0.03	< 10	< 10	24	< 10	54
GG 000N 1190W	203 205	1	0.01	11	870	32	< 5	9	26	0.13	< 10	< 10	21	< 10	90

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Invoice Date: 14-OCT-90
Invoice No. : I-9024266
P.O. Number :

CERTIFICATE OF ANALYSIS A9024266

SAMPLE DESCRIPTION	PREP CODE	Au ppb FA+AA	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
GG 000N 1200W	203 205	< 5	0.6	1.54	15	370	< 0.5	< 2	0.21	< 0.5	6	54	12	2.46	10	< 1	0.22	20	0.56	305
GG 000N 1210W	203 205	< 5	0.8	1.58	35	410	< 0.5	< 2	0.23	< 0.5	4	40	22	3.02	10	< 1	0.42	50	0.69	390
GG 000N 1220W	203 205	< 5	0.6	1.26	10	330	< 0.5	< 2	0.16	< 0.5	6	59	10	2.08	10	< 1	0.27	30	0.55	270
GG 000N 1230W	203 205	< 5	0.6	1.45	10	290	< 0.5	< 2	0.16	< 0.5	8	55	9	2.41	10	< 1	0.28	20	0.55	475
GG 000N 1240W	203 205	< 5	0.8	1.41	15	380	< 0.5	< 2	0.28	< 0.5	7	79	12	2.30	10	< 1	0.39	30	0.61	425
GG 000N 1250W	203 205	15	0.6	1.78	75	420	< 0.5	< 2	0.30	< 0.5	8	61	20	3.49	10	< 1	0.45	30	0.70	630
GG 000N 1260W	203 205	50	0.8	1.73	100	420	< 0.5	< 2	0.28	< 0.5	8	62	25	3.10	20	< 1	0.42	30	0.71	600
GG 000N 1270W	203 205	< 5	0.8	1.64	5	440	< 0.5	< 2	0.15	< 0.5	5	66	10	2.06	10	< 1	0.34	40	0.59	220
GG 000N 1280W	203 205	< 5	0.6	1.65	25	530	< 0.5	< 2	0.24	< 0.5	6	63	14	2.32	10	< 1	0.33	30	0.60	455
GG 000N 1290W	203 205	< 5	0.6	1.37	35	370	< 0.5	< 2	0.30	< 0.5	7	45	15	2.38	10	< 1	0.26	20	0.52	335
GG 000N 1300W	203 205	< 5	0.4	1.33	10	350	< 0.5	< 2	0.19	< 0.5	4	59	11	2.17	10	< 1	0.28	20	0.47	240
GG 000N 1310W	203 205	< 5	0.4	1.31	15	340	< 0.5	< 2	0.20	< 0.5	4	46	12	2.19	10	< 1	0.26	20	0.53	175
GG 000N 1320W	203 205	10	0.6	1.42	25	370	< 0.5	< 2	0.22	< 0.5	5	53	14	2.30	10	< 1	0.24	30	0.55	200
GG 000N 1330W	203 205	10	0.6	1.36	15	430	< 0.5	< 2	0.26	< 0.5	6	64	14	2.18	10	< 1	0.26	40	0.54	365
GG 000N 1340W	203 205	5	0.8	1.34	10	400	< 0.5	< 2	0.29	< 0.5	5	54	14	2.06	10	< 1	0.28	40	0.53	300
GG 000N 1350W	203 205	5	1.0	1.76	15	550	< 0.5	< 2	0.42	< 0.5	8	63	17	2.45	10	< 1	0.39	40	0.65	670
GG 000N 1360W	203 205	< 5	0.8	1.49	10	450	< 0.5	< 2	0.24	< 0.5	5	74	13	2.04	10	< 1	0.31	40	0.52	275
GG 000N 1370W	203 205	< 5	0.8	2.03	20	650	0.5	< 2	0.23	0.5	11	69	16	2.28	10	< 1	0.37	40	0.52	940
GG 000N 1380W	203 205	< 5	0.6	1.45	50	330	< 0.5	< 2	0.45	< 0.5	8	63	17	2.37	10	< 1	0.31	30	0.60	525
GG 000N 1390W	203 205	< 5	0.8	1.40	20	340	< 0.5	< 2	0.29	< 0.5	6	59	13	2.18	10	< 1	0.29	40	0.60	345
GG 000N 1400W	203 205	< 5	0.8	1.26	30	280	< 0.5	< 2	0.31	< 0.5	5	63	14	2.07	10	< 1	0.26	30	0.52	300
GG 000N 1410W	203 205	< 5	0.6	1.37	5	280	< 0.5	< 2	0.18	< 0.5	5	60	9	1.85	10	< 1	0.21	30	0.40	170
GG 000N 1420W	203 205	< 5	0.8	1.35	5	340	< 0.5	< 2	0.22	< 0.5	5	66	10	1.97	10	< 1	0.35	40	0.64	260
KSD 400S 0000E	203 205	75	1.0	2.74	320	180	< 0.5	< 2	0.22	< 0.5	14	46	69	4.49	10	< 1	0.10	10	1.44	530
KSD 400S 0015E	203 205	70	1.6	2.76	295	220	< 0.5	< 2	0.30	0.5	20	49	93	4.70	10	< 1	0.15	10	1.79	840
KSD 400S 0030E	203 205	75	0.8	1.59	100	160	< 0.5	< 2	0.18	0.5	5	64	39	2.33	< 10	< 1	0.11	10	0.38	190
KSD 400S 0045E	203 205	35	0.8	2.69	545	230	< 0.5	< 2	0.30	1.5	17	68	69	5.09	10	< 1	0.23	10	1.58	740
KSD 400S 0060E	203 205	330	4.4	2.50	1170	160	< 0.5	< 2	0.63	10.5	33	52	191	5.65	10	< 1	0.28	10	2.68	1200
KSD 400S 0090E	203 205	120	0.8	3.13	2480	120	< 0.5	< 2	0.97	< 0.5	45	47	114	6.85	10	< 1	0.35	10	3.83	1645
KSD 400S 0105E	203 205	115	1.4	1.78	85	200	< 0.5	2	0.29	1.5	11	74	42	2.96	< 10	< 1	0.11	10	0.88	440
KSD 400S 0120E	203 205	265	13.4	2.46	670	190	< 0.5	< 2	0.29	4.0	11	66	1065	4.23	10	< 1	0.16	10	1.55	505
KSD 400S 0135E	203 205	70	11.8	2.44	515	190	< 0.5	< 2	0.48	4.5	19	86	115	4.47	10	< 1	0.17	10	1.73	855
KSD 400S 0150E	203 205	25	3.0	2.56	325	220	< 0.5	< 2	0.25	1.0	12	73	61	4.22	10	< 1	0.15	20	1.30	485
KSD 400S 0165E	203 205	10	1.4	2.34	160	190	< 0.5	< 2	0.24	0.5	9	72	30	3.56	10	< 1	0.14	20	0.90	345
KSD 400S 0180E	203 205	40	9.0	2.58	400	190	< 0.5	< 2	0.29	2.5	13	66	106	4.45	10	< 1	0.18	10	1.70	530
KSD 400S 0195E	203 205	35	9.6	3.58	180	160	< 0.5	< 2	0.22	2.5	26	63	116	5.94	10	< 1	0.23	10	3.15	1100
KSD 400S 0210E	203 205	25	5.2	2.62	75	210	< 0.5	< 2	0.27	1.5	12	60	77	3.80	10	< 1	0.14	20	1.15	505
KSD 400S 0225E	203 205	15	2.2	3.18	145	140	< 0.5	< 2	0.22	1.0	23	63	75	5.27	10	< 1	0.13	10	2.60	1010
KSD 400S 0240E	203 205	20	0.8	2.99	130	170	< 0.5	< 2	0.16	1.0	16	60	59	5.10	10	< 1	0.14	10	1.77	625
KSD 400S 0255E	203 205	30	2.4	2.75	50	170	< 0.5	< 2	0.19	0.5	17	52	58	4.33	10	< 1	0.11	10	1.38	770

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAWSON
Comments: CC: A. TROUP

Invoice Date: 14-OCT-90
Invoice No. : I-9024266
P.O. Number :

CERTIFICATE OF ANALYSIS A9024266

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
GG 000N 1200W	203	205	1	0.01	10	360	24	< 5	3	15	0.06	< 10	< 10	40	< 10	60
GG 000N 1210W	203	205	1	0.01	9	780	46	< 5	6	12	0.01	< 10	< 10	21	< 10	138
GG 000N 1220W	203	205	1	0.01	8	360	14	< 5	2	12	0.05	< 10	< 10	26	< 10	56
GG 000N 1230W	203	205	< 1	0.01	8	500	20	< 5	3	11	0.05	< 10	< 10	36	< 10	58
GG 000N 1240W	203	205	< 1	0.01	9	520	20	< 5	4	17	0.09	< 10	< 10	26	< 10	64
GG 000N 1250W	203	205	1	0.01	12	1020	24	< 5	7	16	0.07	< 10	< 10	31	< 10	96
GG 000N 1260W	203	205	1	0.01	13	610	46	< 5	7	17	0.06	< 10	< 10	28	< 10	116
GG 000N 1270W	203	205	< 1	0.01	8	190	22	< 5	4	12	0.05	< 10	< 10	25	< 10	60
GG 000N 1280W	203	205	< 1	0.01	9	360	18	< 5	5	18	0.06	< 10	< 10	31	< 10	66
GG 000N 1290W	203	205	< 1	0.01	9	520	18	< 5	5	16	0.09	< 10	< 10	27	< 10	64
GG 000N 1300W	203	205	< 1	0.01	8	400	16	< 5	3	12	0.05	< 10	< 10	26	< 10	56
GG 000N 1310W	203	205	< 1	0.01	8	320	22	< 5	4	12	0.07	< 10	< 10	24	< 10	64
GG 000N 1320W	203	205	< 1	0.01	10	260	16	< 5	4	15	0.07	< 10	< 10	29	< 10	64
GG 000N 1330W	203	205	< 1	0.01	9	470	22	< 5	4	19	0.04	< 10	< 10	26	< 10	68
GG 000N 1340W	203	205	< 1	0.01	9	460	18	< 5	5	18	0.04	< 10	< 10	24	< 10	70
GG 000N 1350W	203	205	< 1	0.01	13	580	24	< 5	6	31	0.04	< 10	< 10	28	< 10	88
GG 000N 1360W	203	205	< 1	0.02	8	420	20	< 5	4	18	0.05	< 10	< 10	25	< 10	66
GG 000N 1370W	203	205	1	0.01	11	640	28	< 5	3	21	0.02	< 10	< 10	27	< 10	72
GG 000N 1380W	203	205	1	0.01	11	680	68	< 5	5	24	0.07	< 10	< 10	24	< 10	96
GG 000N 1390W	203	205	1	0.01	9	450	42	< 5	3	20	0.04	< 10	< 10	23	< 10	76
GG 000N 1400W	203	205	1	0.01	9	480	40	< 5	4	21	0.04	< 10	< 10	23	< 10	72
GG 000N 1410W	203	205	< 1	0.01	7	260	20	< 5	2	14	0.05	< 10	< 10	29	< 10	46
GG 000N 1420W	203	205	< 1	0.01	7	360	24	< 5	2	16	0.04	< 10	< 10	19	< 10	62
KSD 400S 0000E	203	205	1	0.01	19	410	130	5	9	12	0.05	< 10	< 10	74	< 10	144
KSD 400S 0015E	203	205	1	0.01	21	360	172	< 5	11	18	0.04	< 10	< 10	75	10	222
KSD 400S 0030E	203	205	1	0.03	8	860	130	< 5	2	17	0.03	< 10	< 10	47	< 10	78
KSD 400S 0045E	203	205	1	0.02	17	610	170	< 5	6	17	0.05	< 10	< 10	70	10	222
KSD 400S 0060E	203	205	7	0.01	26	490	428	< 5	8	33	0.03	< 10	< 10	49	30	768
KSD 400S 0090E	203	205	1	0.01	35	190	84	5	14	57	0.03	< 10	< 10	70	10	166
KSD 400S 0105E	203	205	1	0.02	13	480	68	< 5	5	15	0.04	< 10	< 10	50	< 10	96
KSD 400S 0120E	203	205	2	0.01	23	650	900	5	6	15	0.03	< 10	< 10	53	20	638
KSD 400S 0135E	203	205	2	0.01	21	880	604	5	6	16	0.02	< 10	< 10	55	< 10	424
KSD 400S 0150E	203	205	1	0.01	23	590	244	< 5	6	13	0.05	< 10	< 10	62	< 10	266
KSD 400S 0165E	203	205	1	0.02	17	380	114	< 5	5	16	0.07	< 10	< 10	65	< 10	140
KSD 400S 0180E	203	205	1	0.02	17	450	378	5	9	15	0.07	< 10	< 10	79	20	284
KSD 400S 0195E	203	205	1	0.01	24	400	614	10	13	10	0.06	< 10	< 10	93	10	568
KSD 400S 0210E	203	205	< 1	0.02	26	260	272	< 5	9	17	0.08	< 10	< 10	74	10	270
KSD 400S 0225E	203	205	1	0.01	27	440	176	< 5	12	10	0.05	< 10	< 10	109	< 10	288
KSD 400S 0240E	203	205	< 1	0.01	21	240	80	< 5	10	10	0.07	< 10	< 10	110	10	228
KSD 400S 0255E	203	205	< 1	0.01	25	320	166	< 5	8	11	0.05	< 10	< 10	79	< 10	170

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

A9024236

Comments: CC: ART TROUP

CERTIFICATE A9024236

ARBOR RESOURCES INC.

Project: AOR-DAW
P.O. # :

Samples submitted to our lab in Vancouver, BC.
This report was printed on 11-OCT-90.

SAMPLE PREPARATION

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION
203	24	Dry, sieve to -35 mesh
205	24	Geochem ring to approx 150 mesh
238	24	NITRIC-AQUA REGIA DIGESTION
* NOTE	1:	

The 32 element ICP package is suitable for trace metals in soil and rock samples. Elements for which the nitric-aqua regia digestion is possibly incomplete are: Al, Ba, Be, Ca, Cr, Ga, K, La, Mg, Na, Sr, Ti, Tl, W.

ANALYTICAL PROCEDURES

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION	METHOD	DETECTION LIMIT	UPPER LIMIT
100	24	Au ppb: Fuse 10 g sample	FA-AAS	5	10000
922	24	Ag ppm: 32 element, soil & rock	ICP-AES	0.2	200.
921	24	Al %: 32 element, soil & rock	ICP-AES	0.01	15.00
923	24	As ppm: 32 element, soil & rock	ICP-AES	5	10000
924	24	Ba ppm: 32 element, soil & rock	ICP-AES	10	10000
925	24	Be ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
926	24	Bi ppm: 32 element, soil & rock	ICP-AES	2	10000
927	24	Ca %: 32 element, soil & rock	ICP-AES	0.01	15.00
928	24	Cd ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
929	24	Co ppm: 32 element, soil & rock	ICP-AES	1	10000
930	24	Cr ppm: 32 element, soil & rock	ICP-AES	1	10000
931	24	Cu ppm: 32 element, soil & rock	ICP-AES	1	10000
932	24	Fe %: 32 element, soil & rock	ICP-AES	0.01	15.00
933	24	Ga ppm: 32 element, soil & rock	ICP-AES	10	10000
951	24	Hg ppm: 32 element, soil & rock	ICP-AES	1	10000
934	24	K %: 32 element, soil & rock	ICP-AES	0.01	10.00
935	24	La ppm: 32 element, soil & rock	ICP-AES	10	10000
936	24	Mg %: 32 element, soil & rock	ICP-AES	0.01	15.00
937	24	Mn ppm: 32 element, soil & rock	ICP-AES	5	10000
938	24	Mo ppm: 32 element, soil & rock	ICP-AES	1	10000
939	24	Na %: 32 element, soil & rock	ICP-AES	0.01	5.00
940	24	Ni ppm: 32 element, soil & rock	ICP-AES	1	10000
941	24	P ppm: 32 element, soil & rock	ICP-AES	10	10000
942	24	Pb ppm: 32 element, soil & rock	ICP-AES	2	10000
943	24	Sb ppm: 32 element, soil & rock	ICP-AES	5	10000
958	24	Sc ppm: 32 elements, soil & rock	ICP-AES	1	10000
944	24	Sr ppm: 32 element, soil & rock	ICP-AES	1	10000
945	24	Ti %: 32 element, soil & rock	ICP-AES	0.01	5.00
946	24	Tl ppm: 32 element, soil & rock	ICP-AES	10	10000
947	24	U ppm: 32 element, soil & rock	ICP-AES	10	10000
948	24	V ppm: 32 element, soil & rock	ICP-AES	1	10000
949	24	W ppm: 32 element, soil & rock	ICP-AES	10	10000
950	24	Zn ppm: 32 element, soil & rock	ICP-AES	2	10000

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Page Number : 1-A
Total Pages : 1
Invoice Date: 11-OCT-90
Invoice No. : I-9024236
P.O. Number :

CERTIFICATE OF ANALYSIS A9024236

SAMPLE DESCRIPTION	PREP CODE		Au ppb FA+AA	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
FG-BENCH-240S	203	205	10	< 0.2	2.22	< 5	330	< 0.5	< 2	0.25	< 0.5	11	125	18	2.91	< 10	< 1	0.26	20	1.59	300
FG-BENCH-270S	203	205	< 5	< 0.2	2.95	< 5	190	< 0.5	< 2	0.28	< 0.5	13	107	24	4.04	< 10	< 1	0.21	20	2.60	480
FG-BENCH-300S	203	205	< 5	< 0.2	1.55	< 5	400	< 0.5	< 2	0.22	< 0.5	9	121	15	1.83	< 10	< 1	0.27	30	0.91	195
FG-BENCH-330S	203	205	15	0.6	1.91	10	340	< 0.5	< 2	0.28	< 0.5	7	84	29	3.31	< 10	< 1	0.24	30	1.27	265
FG-BENCH-360S	203	205	10	0.8	2.28	10	380	< 0.5	< 2	0.17	< 0.5	2	79	16	4.28	< 10	< 1	0.36	10	2.15	340
FG-BENCH-390S	203	205	< 5	0.4	2.28	5	360	< 0.5	< 2	0.34	< 0.5	12	82	46	4.02	< 10	< 1	0.15	30	1.60	375
FG-BENCH-420S	203	205	< 5	< 0.2	1.91	10	230	< 0.5	< 2	0.38	< 0.5	9	58	39	3.63	< 10	< 1	0.15	30	1.19	305
FG-BENCH-450S	203	205	< 5	< 0.2	0.84	< 5	300	< 0.5	< 2	0.10	< 0.5	3	64	13	1.38	< 10	< 1	0.19	20	0.29	105
FG-RD-180	203	205	15	< 0.2	0.86	< 5	150	< 0.5	< 2	0.15	< 0.5	3	68	12	1.30	< 10	< 1	0.13	10	0.47	95
FG-RD-190	203	205	5	0.4	2.21	25	720	< 0.5	< 2	0.41	0.5	17	90	37	4.03	< 10	< 1	0.21	30	1.77	600
FG-RD-200	203	205	15	0.4	1.52	20	270	< 0.5	< 2	0.33	< 0.5	6	73	20	2.46	< 10	< 1	0.31	30	0.52	260
FG-RD-210	203	205	< 5	< 0.2	0.63	< 5	470	< 0.5	< 2	0.25	0.5	2	28	3	0.59	< 10	< 1	0.39	40	0.11	320
FG-RD-220	203	205	10	2.0	1.69	100	370	< 0.5	< 2	0.23	1.0	13	118	63	5.43	< 10	< 1	0.29	10	1.31	355
FG-RD-230	203	205	130	9.8	1.27	70	540	< 0.5	< 2	0.28	1.5	11	32	47	7.32	< 10	1	0.58	30	0.75	420
FG-RD-240	203	205	15	2.0	4.02	130	150	< 0.5	< 2	0.19	3.0	43	292	81	7.36	< 10	< 1	0.10	10	4.03	1385
FG-RD-250	203	205	15	0.6	3.47	30	230	< 0.5	< 2	0.11	< 0.5	7	74	50	5.36	< 10	< 1	0.22	20	3.01	390
FG-RD-260	203	205	15	1.8	3.81	75	150	< 0.5	< 2	0.20	2.5	46	195	78	7.40	< 10	< 1	0.15	10	3.77	1405
FG-RD-270	203	205	10	0.6	2.73	15	160	< 0.5	< 2	0.08	0.5	6	49	43	4.35	< 10	< 1	0.22	20	2.54	360
FG-RD-280	203	205	30	0.8	2.86	85	170	< 0.5	< 2	0.17	1.0	12	42	79	5.00	< 10	< 1	0.28	30	2.47	595
FG-RD-290	203	205	2400	2.0	2.15	525	140	< 0.5	< 2	0.54	1.5	25	46	78	7.77	< 10	< 1	0.33	20	2.15	960
FG-RD-300	203	205	5	< 0.2	2.16	25	250	< 0.5	< 2	0.24	< 0.5	15	64	40	3.65	< 10	< 1	0.17	20	1.60	365
FG-RD-310	203	205	10	< 0.2	1.82	55	320	< 0.5	< 2	0.23	0.5	12	79	51	3.30	< 10	< 1	0.17	20	1.26	345
FG-RD-320	203	205	< 5	< 0.2	1.66	25	290	< 0.5	< 2	0.27	< 0.5	13	68	40	3.14	< 10	1	0.13	20	0.81	400
FG-RD-330	203	205	< 5	< 0.2	0.91	15	230	< 0.5	< 2	0.12	< 0.5	4	127	14	1.57	< 10	< 1	0.17	10	0.54	140

CERTIFICATION: B. Caplan

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Invoice Date: 11-OCT-90
Invoice No. : I-9024236
P.O. Number :

CERTIFICATE OF ANALYSIS A9024236

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
FG-BENCH-240S	203	205	< 1	0.01	18	700	16	< 5	3	14	0.02	< 10	< 10	36	< 10	136
FG-BENCH-270S	203	205	< 1	0.01	20	920	8	< 5	3	11	0.02	< 10	< 10	51	< 10	152
FG-BENCH-300S	203	205	< 1	0.01	19	590	12	< 5	2	17	0.01	< 10	< 10	18	< 10	100
FG-BENCH-330S	203	205	2	0.02	16	930	32	< 5	4	35	0.02	< 10	< 10	35	< 10	116
FG-BENCH-360S	203	205	3	0.05	12	790	36	5	4	80	< 0.01	< 10	< 10	45	< 10	104
FG-BENCH-390S	203	205	2	0.01	24	940	20	< 5	5	16	0.02	< 10	< 10	58	< 10	142
FG-BENCH-420S	203	205	2	0.01	18	1050	18	< 5	4	15	0.01	< 10	< 10	47	< 10	134
FG-BENCH-450S	203	205	< 1	0.01	7	150	20	< 5	2	9	0.01	< 10	< 10	17	< 10	50
FG-RD-180	203	205	< 1	0.01	6	380	14	< 5	1	8	0.02	< 10	< 10	16	< 10	56
FG-RD-190	203	205	< 1	0.03	35	700	54	5	4	28	0.02	< 10	< 10	41	< 10	170
FG-RD-200	203	205	< 1	0.01	13	460	22	< 5	3	12	< 0.01	< 10	< 10	23	< 10	86
FG-RD-210	203	205	< 1	0.01	1	90	18	< 5	1	11	< 0.01	< 10	< 10	< 1	< 10	46
FG-RD-220	203	205	2	0.04	42	910	366	5	4	113	0.02	< 10	< 10	34	< 10	224
FG-RD-230	203	205	2	0.11	15	1500	2020	5	6	342	0.01	< 10	< 10	17	< 10	596
FG-RD-240	203	205	< 1	0.01	138	550	138	< 5	12	30	0.02	< 10	< 10	100	< 10	332
FG-RD-250	203	205	1	0.02	20	540	64	5	4	26	0.03	< 10	< 10	70	< 10	172
FG-RD-260	203	205	< 1	0.01	115	780	230	< 5	10	22	0.03	< 10	< 10	89	< 10	368
FG-RD-270	203	205	1	0.01	15	600	322	< 5	3	59	< 0.01	< 10	< 10	35	< 10	332
FG-RD-280	203	205	1	0.01	22	870	256	< 5	4	68	0.01	< 10	< 10	36	< 10	446
FG-RD-290	203	205	9	0.01	48	1340	38	5	7	27	0.08	< 10	< 10	47	< 10	280
FG-RD-300	203	205	2	0.01	35	710	18	< 5	4	17	0.02	< 10	< 10	45	< 10	114
FG-RD-310	203	205	7	0.01	61	470	20	< 5	3	27	0.05	< 10	< 10	39	< 10	144
FG-RD-320	203	205	3	0.02	40	420	12	< 5	5	30	0.07	< 10	< 10	54	< 10	82
FG-RD-330	203	205	1	0.01	14	320	12	< 5	2	11	0.01	< 10	< 10	17	< 10	52

CERTIFICATION: B. Caplette

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Invoice Date: 22-AUG-90
Invoice No. : I-9020957
P.O. Number : NONE

CERTIFICATE OF ANALYSIS A9020957

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
108201	208	294	< 1	< 0.01	8	90	12	< 5	< 1	3	< 0.01	< 10	< 10	1	< 10	8
108202	208	294	< 1	0.01	6	50	30	< 5	1	5	< 0.01	< 10	< 10	1	< 10	8
108203	208	294	< 1	0.02	1	220	24	< 5	1	11	< 0.01	< 10	< 10	< 1	< 10	22
108204	208	294	1	0.01	6	20	4	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	2
108205	208	294	< 1	0.01	185	1490	944	5	6	14	< 0.01	10	< 10	36	< 10	506
108206	208	294	2	< 0.01	727	70	32	< 5	16	20	0.01	10	< 10	28	< 10	112
108207	208	294	< 1	< 0.01	10	30	10	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	6
108208	208	294	4	0.01	16	180	14	5	1	9	0.02	< 10	< 10	8	< 10	18
108209	208	294	< 1	0.02	2	40	6	< 5	< 1	11	< 0.01	< 10	< 10	< 1	< 10	18
108210	208	294	< 1	0.16	28	1570	< 2	5	18	89	0.46	< 10	< 10	156	< 10	110
108211	208	294	< 1	< 0.01	2	10	4	< 5	< 1	1	< 0.01	< 10	< 10	2	< 10	4
108212	208	294	< 1	0.05	2	90	2	< 5	< 1	8	< 0.01	< 10	< 10	2	< 10	28
108251	208	294	< 1	0.02	2	40	6	< 5	< 1	38	< 0.01	< 10	< 10	1	< 10	6
108252	208	294	< 1	0.01	4	30	4	< 5	< 1	3	< 0.01	< 10	< 10	1	< 10	8
108253	208	294	< 1	0.04	< 1	270	26	< 5	1	10	< 0.01	< 10	< 10	4	< 10	58
108254	208	294	1	0.15	2	80	558	5	1	11	0.02	< 10	< 10	4	< 10	142
108255	208	294	< 1	0.08	< 1	110	26	< 5	1	25	< 0.01	< 10	< 10	1	< 10	12
108256	208	294	< 1	0.01	2	40	390	< 5	< 1	4	< 0.01	< 10	< 10	1	< 10	14
108257	208	294	< 1	0.05	10	1260	78	15	3	19	< 0.01	< 10	< 10	5	< 10	32
108260	208	294	1	< 0.01	1	< 200	4000	2760	< 1	55	< 0.01	< 10	< 10	3	< 10	1845
108263	208	294	< 1	0.01	3	< 10	384	15	< 1	189	< 0.01	< 10	< 10	1	< 10	200
108264	208	294	7	0.04	6	< 10	>10000	135	1	5	< 0.01	< 10	< 10	1	< 10	>10000
108265	208	294	9	0.05	6	20	>10000	245	1	7	< 0.01	< 10	< 10	1	10	>10000
108266	208	294	1	0.01	17	280	1105	5	4	66	< 0.01	< 10	< 10	30	< 10	490
108267	208	294	< 1	0.03	3	20	30	< 5	< 1	7	< 0.01	< 10	< 10	1	< 10	24
108268	208	294	2	0.08	5	280	86	< 5	2	6	< 0.01	< 10	< 10	13	< 10	162
108269	208	294	< 1	0.02	10	90	8	< 5	1	8	0.01	< 10	< 10	11	< 10	12
108272	208	294	< 1	0.04	7	300	292	< 5	2	15	< 0.01	< 10	< 10	8	< 10	126
108273	208	294	< 1	0.04	55	1520	8	5	16	79	0.07	< 10	< 10	149	10	120
108277	208	294	2	0.07	1	40	30	< 5	< 1	10	< 0.01	< 10	< 10	3	< 10	16
108278	208	294	< 1	< 0.01	4	30	30	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	22
108279	208	294	< 1	0.01	13	380	170	5	3	23	0.01	< 10	< 10	31	< 10	42
108280	208	294	1	0.02	32	540	42	< 5	3	12	< 0.01	< 10	< 10	7	< 10	232
108281	208	294	< 1	0.02	2	210	38	< 5	1	11	< 0.01	< 10	< 10	2	< 10	22
108282	208	294	< 1	0.08	30	750	96	< 5	10	144	0.10	< 10	< 10	60	< 10	216
108283	208	294	< 1	0.03	3	20	22	< 5	< 1	5	< 0.01	< 10	< 10	2	< 10	14
108284	208	294	1	0.14	30	1110	14	< 5	14	160	0.08	< 10	< 10	114	< 10	106
108285	208	294	< 1	0.01	4	100	10	< 5	< 1	47	< 0.01	< 10	< 10	1	< 10	12
108286	208	294	< 1	< 0.01	3	< 10	68	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	12
108287	208	294	1	< 0.01	6	260	6	< 5	< 1	2	< 0.01	< 10	< 10	2	< 10	6

CERTIFICATION: B. Caufield

Northern Analytical Laboratories ltd.

October 30,1990

Work Order # 08479

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 08479b

Sample: Soil

Assay Certificate for Samples Provided

Line: EL/LL

Sample	ppb Au
6570	183
6630	53
6660	475
6690	62
6720	63
6780	<10
6810	<10
6840	<10
6870	24
6900	<10

Au -- 15g Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

Northern Analytical Laboratories ltd.

October 30,1990

Work Order # 08479

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 08479c

Sample: Soil

Assay Certificate for Samples Provided

Line: EL/RL

Sample	ppb Au
6360	135
6390	26
6420	28
6450	11
6480	41
6510	19
6540	12
6570	12
6600	11
6630	19
6660	27
6690	57
6720	187
6750	10
6780	<10
6810	<10
6840	17
6870	11
6900	<10

Au -- 15g Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#08479 File # 90-5690 Page 1

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
EL/LL 6570	1	15	8	60	.2	14	9	345	1.93	21	5	ND	3	25	.4	3	2	16	.48	.092	14	13	.54	210	.02	2	.79	.01	.06	2
EL/LL 6630	1	20	88	78	.2	16	9	350	2.10	15	5	ND	3	32	.2	2	2	25	.63	.091	13	22	.63	217	.04	5	.98	.01	.07	2
EL/LL 6660	1	44	17	115	1.8	23	16	485	3.31	19	5	4	4	45	.9	5	2	34	.59	.072	19	29	1.00	268	.05	4	1.34	.02	.09	1
EL/LL 6690	1	29	26	117	.6	18	9	346	2.98	14	5	ND	7	38	.2	4	2	24	.35	.070	33	16	.53	530	.03	2	1.17	.01	.10	2
EL/LL 6720	1	19	14	99	.2	16	9	333	2.14	18	5	ND	4	30	.6	3	2	25	.48	.084	14	24	.71	202	.03	2	1.02	.01	.06	3
EL/LL 6780	1	42	16	100	.4	28	14	629	3.18	28	5	ND	4	46	.3	4	2	42	.61	.079	21	31	.92	396	.06	5	1.41	.02	.10	1
EL/LL 6810	1	40	18	105	.2	19	13	570	2.84	9	5	ND	4	29	.9	4	2	42	.54	.072	29	26	1.12	356	.06	2	1.73	.01	.11	1
EL/LL 6840	1	38	23	112	.4	21	13	558	2.67	9	5	ND	5	27	.5	3	3	36	.52	.075	31	29	1.03	254	.04	4	1.54	.01	.10	1
EL/LL 6870	1	46	28	156	.6	27	14	565	2.82	12	5	ND	7	30	1.3	4	2	37	.54	.093	53	29	1.14	244	.01	2	1.75	.01	.10	1
EL/LL 6900	1	39	42	133	.4	21	17	735	2.87	13	5	ND	5	33	.6	3	2	40	.50	.076	29	26	1.05	326	.04	6	1.61	.01	.08	1
EL/RL 6360	1	23	19	97	.7	26	17	384	5.12	15	5	ND	2	71	1.0	7	2	69	.76	.050	20	22	1.57	505	.07	4	2.75	.13	.07	1
EL/RL 6390	1	8	21	42	.1	10	5	136	2.06	101	5	ND	4	11	.2	2	2	14	.12	.018	15	6	.16	251	.01	2	.90	.01	.08	3
EL/RL 6420	1	22	22	129	.7	26	9	583	2.99	42	5	ND	3	50	1.0	3	2	25	.75	.049	28	18	.77	478	.02	2	1.77	.01	.06	2
EL/RL 6450	1	19	25	112	.5	18	7	895	2.82	32	5	ND	7	28	.9	6	2	16	.38	.076	28	13	.85	599	.02	3	1.46	.01	.07	1
EL/RL 6480	3	46	64	210	1.8	58	11	501	3.31	100	5	ND	6	27	.8	10	2	18	.19	.056	23	18	.41	621	.02	6	1.01	.01	.06	1
EL/RL 6510	1	13	22	93	.3	15	7	779	2.53	18	5	ND	7	33	.8	4	2	17	.35	.061	25	12	.76	743	.02	2	1.42	.01	.07	2
EL/RL 6540	1	16	14	76	.3	11	8	1149	2.46	12	5	ND	5	29	.2	3	2	24	.42	.066	25	16	.61	427	.04	3	1.44	.02	.08	1
EL/RL 6570	1	16	13	80	.4	11	6	409	2.26	11	5	ND	6	26	.6	2	2	17	.37	.066	25	11	.43	262	.02	2	1.18	.01	.09	1
EL/RL 6600	1	10	19	38	.2	8	4	442	1.21	19	5	ND	6	24	.2	2	2	12	.43	.098	24	7	.17	243	.02	2	.66	.01	.12	2
EL/RL 6630	1	12	12	44	.3	9	5	324	1.84	24	5	ND	6	19	.2	2	2	8	.31	.093	22	7	.12	145	.01	2	.46	.01	.10	1
EL/RL 6660	1	15	10	74	.2	8	4	223	2.23	16	5	ND	4	20	.4	2	2	16	.31	.068	21	11	.38	188	.02	3	.96	.01	.10	2
EL/RL 6690	1	14	11	59	.1	13	6	332	2.15	6	5	ND	4	27	.3	3	2	32	.35	.051	19	21	.45	295	.05	2	1.32	.01	.07	1
EL/RL 6720	1	23	14	81	.3	8	6	192	2.16	12	5	ND	5	24	1.0	2	2	16	.33	.080	26	10	.32	191	.02	4	.97	.01	.14	1
EL/RL 6750	1	14	7	79	.2	13	6	197	2.14	11	5	ND	5	25	.8	2	2	25	.34	.063	21	19	.45	239	.05	2	1.13	.01	.09	2
EL/RL 6780	1	16	13	85	.2	13	6	209	2.29	14	5	ND	3	26	.9	2	2	20	.29	.057	19	19	.51	226	.03	2	1.18	.01	.10	1
EL/RL 6810	1	27	9	77	.3	21	9	290	2.69	24	5	ND	3	27	.4	5	2	39	.34	.070	17	33	.67	246	.05	4	1.55	.01	.07	2
EL/RL 6840	1	45	7	101	.1	38	11	259	2.65	29	5	ND	4	34	.7	2	2	38	.49	.120	20	39	.67	173	.05	2	1.23	.01	.08	1
EL/RL 6870	1	28	11	86	.2	27	10	278	2.47	19	5	ND	3	36	.6	3	2	37	.46	.079	18	33	.59	235	.05	2	1.35	.01	.08	1
EL/RL 6900	1	20	14	71	.3	22	8	259	2.37	15	5	ND	4	33	.5	4	2	39	.41	.067	17	31	.58	296	.06	3	1.45	.02	.08	1
01822	8	16	57	72	1.1	3	1	45	.71	12	5	ND	11	5	.2	2	2	1	.05	.014	15	88	.22	72	.01	2	.43	.02	.08	1
01823	4	41	40	118	.3	11	5	177	2.30	13	12	ND	6	12	.4	2	2	10	.06	.010	11	53	.05	154	.01	6	.40	.01	.28	1
01824	16	80	17	1063	.5	583	48	3035	17.58	9	7	ND	1	11	3.3	2	2	43	.13	.066	2	110	.06	72	.01	23	.76	.01	.01	1
01825	5	5	14	83	.2	10	4	282	2.08	17	5	ND	5	14	.8	2	2	7	.17	.048	16	34	.44	379	.01	2	1.04	.01	.22	1
37972	2	44	54	155	1.4	195	21	1013	4.51	135	5	ND	1	199	1.9	4	2	57	4.68	.034	3	188	3.45	119	.01	4	.36	.02	.02	1
37980	11	82	69	274	1.5	479	23	123	5.74	102	20	ND	7	31	1.2	19	2	35	.14	.055	11	296	.09	202	.01	8	.41	.01	.07	1
37982	6	35	418	454	1.7	25	6	763	2.54	50	5	ND	1	229	2.7	20	3	10	3.26	.013	5	64	1.47	519	.01	2	.19	.01	.06	1
STANDARD C	17	58	38	130	6.9	70	30	1051	3.97	39	19	7	36	52	18.0	15	19	56	.45	.090	37	56	.89	181	.08	34	1.89	.06	.14	11

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: NOV 1 1990 **DATE REPORT MAILED:** Nov 7/90. **SIGNED BY** ..... D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
37983	10	30	58	70	.9	7	1	63	.65	20	5	ND	2	6	.4	3	2	3	.08	.002	5	137	.08	87	.01	2	.20	.02	.05	1
37984	10	10	48	60	.7	3	1	80	.36	13	5	ND	3	11	.3	2	2	1	.15	.002	11	122	.05	54	.01	2	.13	.01	.04	1
37985	11	27	60	59	.8	11	3	362	.64	6	5	ND	11	37	.4	2	2	3	1.04	.005	17	108	.16	24	.01	2	.30	.02	.03	1
37986	11	7	76	51	1.0	8	5	255	1.05	21	5	ND	1	51	.2	2	2	12	.60	.011	5	140	.33	419	.02	6	.56	.06	.04	1
37987	45	65	3732	1185	26.4	3	4	418	12.41	168	40	ND	7	30	6.5	44	10	1	.18	.026	26	28	.06	422	.01	3	.33	.01	.11	1
37988	30	29	36	98	.6	44	4	349	.94	14	5	ND	1	250	1.5	2	2	30	4.06	.025	5	118	.47	46	.01	4	.42	.01	.03	1
37989	8	32	16	51	.1	14	20	688	10.93	2	5	ND	25	18	.3	2	2	128	.28	.050	60	130	.51	161	.11	2	.93	.03	.15	1
37990	14	217	42	34	3.0	9	1	92	1.23	66	5	ND	1	38	.4	4	2	11	.60	.004	2	120	.17	15	.01	3	.25	.01	.01	1
37991	35	59	63	231	2.3	20	4	1447	1.80	36	9	ND	2	800	5.7	5	2	37	15.15	.032	13	42	.58	158	.01	2	.85	.01	.05	1
37992	17	37	16	66	1.5	24	14	18545	1.88	83	5	ND	1	94	1.2	5	2	77	.14	.012	4	127	.02	767	.01	2	.07	.01	.03	1
37993	7	37	372	435	6.5	6	6	389	4.08	20	5	9	5	35	1.8	10	2	8	.37	.025	20	63	.88	680	.01	2	1.48	.01	.18	1
37994	26	41	67	266	1.3	32	8	355	2.94	67	5	ND	4	227	3.5	2	2	24	3.25	.123	9	75	.75	39	.01	2	.63	.03	.09	1
39801	32	665	43	1439	1.8	1266	50	6780	38.61	28	5	ND	6	17	10.6	2	2	75	.12	.047	10	107	.20	286	.01	2	1.49	.01	.07	1
39802	15	13	57	68	.9	12	2	103	.85	29	5	ND	1	2	.2	2	3	2	.02	.004	2	179	.03	24	.01	4	.07	.01	.01	1
STANDARD C	18	57	38	133	7.1	73	31	1054	3.97	42	19	7	40	52	18.8	15	19	59	.46	.097	39	60	.90	183	.07	31	1.90	.06	.14	11

APPENDIX II

TRENCHES AND SAMPLES LISTING

SAMPLE NUMBERS	TRENCH	CERTIFICATE	TOTAL
108101H-108129H	90OGTR01	A9021703	129
108130H-108143H	90GGTR03	A9021703	14
108144H-108147H	90GGTR03	A9021730	4
108148H-108150H	90GGTR04	A9021730	3
108151H-108153H	90GGTR02	A9021730	3
108154H-108158H	90GGTR01	A9021730	5
108159H-108164H	90GGTR06	A9021730	6
108165H	90GGTR04	A9021730	1
108166H	90GGTR10	A9021730	1
108167H-108200H	90GGTR06	A9021730	34
108213H-108215H	90OGTR01	A9021730	3
108218H-108250H	90OGTR01	A9021730	32
1805H-1812H	9027PUPTR01A	08473	8
1858J-1866J	90GGTR18	A9020957	9
1867J-1875J	90GGTR21	A9023700	9
1877J-1881J	90GGTR21	A9023700	5
1882J-1886J	90GGTR19	A9023700	5
1888J-1894J	90GGTR19	A9023700	7
1895J-1900J	90GGTR20	A9023700	6
24477G-24492G	90GGTR17	A9023700	16
24493G-24500G	90GGTR18	A9023700	8
37851F-37870F	9027PUPTR01	A9024260	20
37871F-37879F	9027PUPTR02	A9024260	9
37880F-37881F	9027PUPTR03	A9024260	2
37882F-37884F	9027PUPTR01	A9024261	3
37885F-37892F	9027PUPTR03	A9024261	8
37893F-37918F	9027PUPTR04	A9024261	26
38951G-38955G	90GGTR06	A9021703	5
38956G	90GGTR06	A9023700	1
38957G-38962G	90GGTR06	A9021703	6
38963G-38974G	90GGTR02	A9021703	12
38975G-38976G	90GGTR12	A9021703	2
38977G-38978G	90GGTR05	A9021703	2
38979G-39000G	90OGTR01	A9021703	22
39051G-39068G	90OGTR01	A9021703	18
39070G-39079G	90OGTR01	A9021703	10
39081G-39100G	90GGTR11	A9022461	20
39144G-39165G	90GGTR11	A9022461	22
39166G-39167G	90GGTR10	A9022461	2
39168G	90OGJV	A9022461	1
39170G-39171G	90GGTR08	A9022461	2
39193G-39197G	90GGTR12	A9022461	5
39200G	90GGTR09	A9022461	1
39201G	90GGTR12	A9023250	1
39202G-39205G	90GGTR13	A9023250	4
39206G-39212G	90GGTR14	A9023250	7
39213G-39216G	90GGTR15	A9023250	4
39217G-39220G	90GGTR16	A9023250	4
39222G-39224G	90GGTR20	A9023700	3
39226G-39228G	90GGTR20	A9023700	3
39230G-39233G	90GGTR20	A9023700	4
39235G	90GGTR20	A9023700	1

SAMPLE NO.	TRENCH	CERTIFICATE	TOTAL
39237G-39242G	90GGTR20	A9023700	6
39244G-39248G	90GGTR12	A9023700	5
39250G	90GGTR12	A9023700	1
39301G-39306G	90GGTR12	A9023700	6
39307G-39326G	90GGTR22	A9023700	20
39334G	90GGTR06	A9023250	1
39336G-39337G	90GGTR06	A9023250	2
39339G-39340G	90GGTR11	A9023250	2
39350G	90GGTR06	A9023250	1
39557G-39591G	90V2	A9024260	35
39599G-39600G	9027PUPTR01	A9024260	2
39601G-39645G	90V1	A9023700	45
39648G-39650G	90V1	A9023700	3
39651G-39662G	90GGTR13	A9024237	12
39696G-39700G	9027PUPTR01A	08473	5
39811G-39822G	9027PUPSQTR	08473	12

APPENDIX III

TRENCH SAMPLES CERTIFICATES OF ANALYSES

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

A9020957

Comments:

CERTIFICATE A9020957

ARBOR RESOURCES INC.

Project: DAWSON
P.O. # : NONE

Samples submitted to our lab in Vancouver, BC.
This report was printed on 22-AUG-90.

SAMPLE PREPARATION

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION
208	145	Assay ring to approx 150 mesh
294	145	Crush and split (0-10 pounds)
238	145	NITRIC-AQUA REGIA DIGESTION
* NOTE	1:	

The 32 element ICP package is suitable for trace metals in soil and rock samples. Elements for which the nitric-aqua regia digestion is possibly incomplete are: Al, Ba, Be, Ca, Cr, Ga, K, La, Mg, Na, Sr, Ti, Tl, W.

ANALYTICAL PROCEDURES

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION	METHOD	DETECTION LIMIT	UPPER LIMIT
398	145	Au oz/T: 1/2 assay ton	FA-AAS	0.002	20.00
922	145	Ag ppm: 32 element, soil & rock	ICP-AES	0.2	200
921	145	Al %: 32 element, soil & rock	ICP-AES	0.01	15.00
923	145	As ppm: 32 element, soil & rock	ICP-AES	5	10000
924	145	Ba ppm: 32 element, soil & rock	ICP-AES	10	10000
925	145	Be ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
926	145	Bi ppm: 32 element, soil & rock	ICP-AES	2	10000
927	145	Ca %: 32 element, soil & rock	ICP-AES	0.01	15.00
928	145	Cd ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
929	145	Co ppm: 32 element, soil & rock	ICP-AES	1	10000
930	145	Cr ppm: 32 element, soil & rock	ICP-AES	1	10000
931	145	Cu ppm: 32 element, soil & rock	ICP-AES	1	10000
932	145	Fe %: 32 element, soil & rock	ICP-AES	0.01	15.00
933	145	Ga ppm: 32 element, soil & rock	ICP-AES	10	10000
951	145	Hg ppm: 32 element, soil & rock	ICP-AES	1	10000
934	145	K %: 32 element, soil & rock	ICP-AES	0.01	10.00
935	145	La ppm: 32 element, soil & rock	ICP-AES	10	10000
936	145	Mg %: 32 element, soil & rock	ICP-AES	0.01	15.00
937	145	Mn ppm: 32 element, soil & rock	ICP-AES	5	10000
938	145	Mo ppm: 32 element, soil & rock	ICP-AES	1	10000
939	145	Na %: 32 element, soil & rock	ICP-AES	0.01	5.00
940	145	Ni ppm: 32 element, soil & rock	ICP-AES	1	10000
941	145	P ppm: 32 element, soil & rock	ICP-AES	10	10000
942	145	Pb ppm: 32 element, soil & rock	ICP-AES	2	10000
943	145	Sb ppm: 32 element, soil & rock	ICP-AES	5	10000
958	145	Sc ppm: 32 elements, soil & rock	ICP-AES	1	10000
944	145	Sr ppm: 32 element, soil & rock	ICP-AES	1	10000
945	145	Ti %: 32 element, soil & rock	ICP-AES	0.01	5.00
946	145	Tl ppm: 32 element, soil & rock	ICP-AES	10	10000
947	145	U ppm: 32 element, soil & rock	ICP-AES	10	10000
948	145	V ppm: 32 element, soil & rock	ICP-AES	1	10000
949	145	W ppm: 32 element, soil & rock	ICP-AES	10	10000
950	145	Zn ppm: 32 element, soil & rock	ICP-AES	2	10000

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Page Number : 1-A
Total Pages : 4
Invoice Date: 22-AUG-90
Invoice No. : I-9020957
P.O. Number : NONE

CERTIFICATE OF ANALYSIS A9020957

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
108201	208	294	2.016	5.0	0.01	15	170	< 0.5	< 2	< 0.01	< 0.5	5	244	3	1.35	< 10	< 1	< 0.01	< 10	< 0.01	45
108202	208	294	< 0.002	0.6	0.31	5	360	< 0.5	< 2	< 0.01	< 0.5	4	280	3	0.49	< 10	< 1	0.26	10	0.01	145
108203	208	294	< 0.002	1.0	0.52	10	890	< 0.5	4	0.03	< 0.5	5	91	2	0.44	< 10	< 1	0.34	30	0.13	70
108204	208	294	< 0.002	< 0.2	0.03	5	20	< 0.5	2	< 0.01	< 0.5	2	241	< 1	0.29	< 10	< 1	< 0.01	< 10	0.01	20
108205	208	294	< 0.002	2.0	2.08	< 5	280	< 0.5	8	0.55	0.5	14	635	25	2.12	< 10	< 1	0.14	< 10	0.75	55
108206	208	294	< 0.002	0.4	1.37	15	40	< 0.5	< 2	0.13	< 0.5	34	2380	61	3.47	< 10	< 1	< 0.01	< 10	8.99	140
108207	208	294	< 0.002	0.2	0.02	20	10	< 0.5	< 2	< 0.01	< 0.5	4	173	3	0.24	< 10	< 1	< 0.01	< 10	0.08	50
108208	208	294	0.002	0.6	0.21	70	70	< 0.5	2	0.09	< 0.5	6	580	14	2.73	< 10	2	< 0.01	< 10	0.17	135
108209	208	294	0.012	0.4	0.07	5	580	< 0.5	< 2	< 0.01	< 0.5	3	159	5	0.42	< 10	< 1	0.03	< 10	0.01	35
108210	208	294	< 0.002	0.2	4.50	30	330	< 0.5	< 2	2.07	< 0.5	35	61	15	7.47	< 10	< 1	0.09	< 10	3.59	990
108211	208	294	< 0.002	0.2	0.08	< 5	10	< 0.5	< 2	0.01	< 0.5	4	221	5	0.38	< 10	< 1	< 0.01	< 10	0.03	65
108212	208	294	< 0.002	0.4	0.17	15	60	< 0.5	< 2	0.03	< 0.5	6	318	3	1.60	< 10	< 1	0.01	10	0.02	690
108251	208	294	< 0.002	0.4	0.11	< 5	1890	< 0.5	< 2	0.01	< 0.5	4	235	3	0.38	< 10	2	0.04	< 10	0.02	40
108252	208	294	< 0.002	0.2	0.18	25	130	< 0.5	< 2	0.03	< 0.5	3	402	3	0.50	< 10	1	0.07	< 10	0.02	150
108253	208	294	< 0.002	0.6	1.05	5	200	1.0	< 2	0.15	< 0.5	6	106	7	1.36	10	< 1	0.42	30	0.14	485
108254	208	294	< 0.002	4.8	0.46	< 5	160	< 0.5	< 2	0.09	< 0.5	5	425	173	1.27	< 10	1	0.14	10	0.09	185
108255	208	294	< 0.002	1.4	0.52	< 5	400	< 0.5	< 2	< 0.01	< 0.5	5	146	10	0.57	< 10	< 1	0.37	40	0.07	35
108256	208	294	< 0.002	2.8	0.08	< 5	90	< 0.5	2	0.02	< 0.5	4	389	15	0.45	< 10	< 1	< 0.01	< 10	0.02	70
108257	208	294	0.009	4.0	0.31	30	270	< 0.5	< 2	0.31	< 0.5	12	42	31	2.97	< 10	< 1	0.12	30	0.05	655
108260	208	294	0.307	>200	0.36	1435	350	< 0.5	< 20	2.64	20.0	7	289	>10000	1.57	< 10	712	0.02	< 10	0.58	475
108263	208	294	0.002	4.0	0.25	< 5	2350	< 0.5	< 2	2.43	1.0	1	210	49	0.47	< 10	< 1	< 0.01	< 10	0.47	1010
108264	208	294	0.033	64.4	1.31	165	60	< 0.5	< 2	0.03	93.0	< 1	260	665	7.78	< 10	15	0.05	10	1.67	330
108265	208	294	0.041	65.6	1.34	260	70	< 0.5	< 2	0.02	>100.0	< 1	214	1160	6.67	< 10	23	0.07	10	1.72	325
108266	208	294	< 0.002	2.4	2.80	< 5	90	< 0.5	< 2	1.48	2.0	8	529	16	4.87	10	< 1	0.06	10	4.47	3120
108267	208	294	< 0.002	0.4	0.33	5	390	< 0.5	< 2	0.01	< 0.5	< 1	140	5	0.43	< 10	< 1	0.23	< 10	0.06	25
108268	208	294	< 0.002	1.4	1.62	10	100	< 0.5	< 2	0.06	1.0	5	232	36	2.07	< 10	< 1	0.09	10	1.58	425
108269	208	294	< 0.002	< 0.2	0.41	< 5	110	< 0.5	< 2	0.05	< 0.5	3	571	5	1.00	< 10	< 1	< 0.01	< 10	0.17	125
108272	208	294	< 0.002	1.4	1.64	< 5	370	< 0.5	< 2	0.17	0.5	4	207	14	1.44	10	< 1	0.53	40	0.53	300
108273	208	294	< 0.002	0.2	4.95	25	1230	< 0.5	< 2	0.76	1.0	34	43	30	7.48	20	< 1	0.14	20	2.46	950
108277	208	294	< 0.002	0.4	0.35	< 5	160	< 0.5	< 2	0.02	< 0.5	< 1	107	12	1.13	< 10	< 1	0.23	< 10	0.01	105
108278	208	294	< 0.002	0.2	0.06	5	30	< 0.5	< 2	0.01	< 0.5	1	263	5	0.45	< 10	< 1	< 0.01	< 10	0.02	60
108279	208	294	0.002	0.8	0.84	< 5	200	< 0.5	2	0.38	0.5	7	396	15	2.09	< 10	< 1	0.14	20	0.58	280
108280	208	294	1.602	14.8	1.42	50	880	< 0.5	< 2	0.06	1.0	22	218	65	4.30	< 10	< 1	0.30	20	0.52	785
108281	208	294	< 0.002	< 0.2	0.25	230	170	< 0.5	< 2	0.05	0.5	< 1	207	4	0.88	< 10	< 1	0.24	10	0.01	100
108282	208	294	< 0.002	0.8	2.16	< 5	240	< 0.5	< 2	1.51	1.5	16	110	38	4.20	10	< 1	0.15	30	2.02	665
108283	208	294	< 0.002	0.2	0.36	5	140	< 0.5	4	0.04	< 0.5	1	451	5	0.65	< 10	< 1	0.08	10	0.17	105
108284	208	294	< 0.002	0.8	2.78	< 5	160	< 0.5	< 2	2.32	1.0	28	58	18	5.63	10	< 1	0.16	20	3.07	805
108285	208	294	< 0.002	0.2	0.23	5	2660	< 0.5	2	0.02	< 0.5	1	404	3	0.51	< 10	< 1	0.18	< 10	0.04	40
108286	208	294	0.004	1.8	0.01	< 5	90	< 0.5	< 2	0.01	< 0.5	< 1	377	17	0.40	< 10	< 1	< 0.01	< 10	0.08	75
108287	208	294	< 0.002	< 0.2	0.07	10	30	< 0.5	< 2	0.05	< 0.5	1	600	2	0.55	< 10	< 1	< 0.01	< 10	0.02	60

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Page Number : 2-A
Total Pages : 4
Invoice Date: 22-AUG-90
Invoice No. : I-9020957
P.O. Number : NONE

CERTIFICATE OF ANALYSIS A9020957

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
108288	208	294	< 0.002	< 0.2	0.07	< 5	160	< 0.5	< 2	0.01	< 0.5	1	271	6	0.36	< 10	< 1	< 0.01	< 10	0.01	435
108289	208	294	0.002	2.2	0.02	< 5	170	< 0.5	< 2	0.02	< 0.5	< 1	495	8	0.44	< 10	1	< 0.01	< 10	0.02	50
108290	208	294	0.008	9.0	0.01	< 5	4030	< 0.5	2	0.01	< 0.5	< 1	285	82	0.40	< 10	< 1	< 0.01	< 10	0.02	45
108291	208	294	< 0.002	< 0.2	0.14	< 5	60	< 0.5	< 2	0.74	0.5	1	384	6	0.55	< 10	< 1	0.01	10	0.48	945
108292	208	294	< 0.002	< 0.2	0.08	< 5	920	< 0.5	< 2	0.02	< 0.5	1	369	7	0.45	< 10	< 1	< 0.01	< 10	0.03	50
108294	208	294	< 0.002	1.2	4.33	95	980	< 0.5	< 2	1.93	1.5	30	61	25	9.16	< 10	< 1	0.06	50	3.31	1470
108295	208	294	< 0.002	< 0.2	0.06	< 5	50	< 0.5	< 2	< 0.01	< 0.5	< 1	267	5	0.44	< 10	< 1	0.02	10	< 0.01	40
108296	208	294	< 0.002	< 0.2	0.07	< 5	30	< 0.5	< 2	0.01	< 0.5	< 1	276	4	0.33	< 10	< 1	< 0.01	< 10	0.02	25
108297	208	294	< 0.002	< 0.2	0.07	< 5	30	< 0.5	< 2	0.01	< 0.5	< 1	281	4	0.36	< 10	< 1	< 0.01	< 10	0.02	65
108301	208	294	< 0.002	< 0.2	3.02	120	1520	0.5	< 2	1.33	< 0.5	18	91	21	4.16	< 10	< 1	0.60	30	0.60	540
108302	208	294	< 0.002	1.6	1.67	5	530	< 0.5	< 2	0.89	1.0	10	77	28	2.69	< 10	< 1	0.18	30	0.69	470
108303	208	294	< 0.002	< 0.2	0.05	< 5	30	< 0.5	< 2	0.03	< 0.5	< 1	269	2	0.25	< 10	< 1	< 0.01	< 10	< 0.01	30
108304	208	294	< 0.002	< 0.2	0.03	< 5	130	< 0.5	< 2	0.05	< 0.5	< 1	284	3	0.31	< 10	< 1	< 0.01	< 10	0.01	50
108305	208	294	< 0.002	< 0.2	0.15	15	5380	< 0.5	< 2	3.42	0.5	2	221	6	1.13	< 10	< 1	0.05	< 10	0.69	1140
108306	208	294	< 0.002	< 0.2	0.62	10	1950	< 0.5	< 2	0.32	< 0.5	1	139	5	0.60	< 10	< 1	0.50	40	0.17	85
108308	208	294	< 0.002	< 0.2	4.11	10	1680	< 0.5	< 2	3.72	< 0.5	30	37	21	7.96	< 10	< 1	0.19	10	2.55	1055
108309	208	294	< 0.002	0.6	1.10	20	920	< 0.5	< 2	0.08	< 0.5	3	140	7	2.16	< 10	< 1	0.21	50	0.31	560
108310	208	294	< 0.002	0.6	0.31	< 5	250	< 0.5	< 2	< 0.01	< 0.5	< 1	75	3	0.30	< 10	< 1	0.37	40	0.05	55
108311	208	294	0.002	1.0	0.22	20	580	< 0.5	< 2	0.03	< 0.5	< 1	157	4	1.46	< 10	1	0.03	10	0.13	140
108312	208	294	< 0.002	0.4	0.50	< 5	90	< 0.5	< 2	0.04	< 0.5	1	121	8	0.94	< 10	1	0.13	20	0.16	195
108313	208	294	< 0.002	< 0.2	0.04	< 5	20	< 0.5	< 2	< 0.01	< 0.5	1	294	2	0.29	< 10	1	< 0.01	< 10	< 0.01	85
108314	208	294	< 0.002	0.4	0.40	< 5	270	< 0.5	< 2	0.01	< 0.5	< 1	102	11	0.40	< 10	< 1	0.31	30	0.11	90
108315	208	294	< 0.002	4.6	0.16	5	50	< 0.5	< 2	< 0.01	< 0.5	< 1	123	17	0.73	< 10	< 1	0.03	30	0.01	30
108316	208	294	< 0.002	< 0.2	1.48	145	290	< 0.5	< 2	0.08	< 0.5	4	37	12	3.21	10	< 1	0.25	10	0.40	680
108317	208	294	< 0.002	< 0.2	0.08	30	20	< 0.5	< 2	< 0.01	< 0.5	2	184	3	0.63	< 10	< 1	< 0.01	< 10	0.02	115
108318	208	294	0.004	< 0.2	0.03	< 5	30	< 0.5	< 2	< 0.01	< 0.5	< 1	221	2	0.32	< 10	< 1	< 0.01	< 10	0.01	35
108319	208	294	4.215	27.0	1.07	235	1370	< 0.5	< 2	0.28	1.0	88	182	114	>15.00	10	< 1	0.46	30	0.28	410
108320	208	294	< 0.002	< 0.2	0.15	5	110	< 0.5	< 2	0.01	< 0.5	1	378	3	0.48	< 10	< 1	0.05	< 10	0.03	40
108321	208	294	0.002	0.6	1.24	35	800	< 0.5	< 2	0.15	0.5	5	165	11	2.21	< 10	< 1	0.60	40	0.31	140
108322	208	294	0.132	3.4	0.11	< 5	80	< 0.5	2	< 0.01	< 0.5	1	437	5	0.53	< 10	1	0.03	< 10	0.03	35
108323	208	294	0.007	0.4	1.06	160	290	0.5	< 2	0.04	< 0.5	2	94	12	1.69	< 10	< 1	0.57	20	0.06	135
108324	208	294	0.429	6.4	0.06	< 5	30	< 0.5	2	< 0.01	< 0.5	< 1	298	2	0.47	< 10	< 1	0.01	< 10	0.02	70
108325	208	294	< 0.002	< 0.2	0.94	20	340	< 0.5	< 2	0.07	< 0.5	3	196	7	1.56	< 10	< 1	0.42	30	0.36	95
108327	208	294	0.002	1.6	0.13	25	150	< 0.5	2	0.03	< 0.5	9	255	24	1.34	< 10	< 1	0.04	< 10	0.04	105
108333	208	294	< 0.002	16.0	4.25	1475	3430	< 0.5	< 2	0.94	5.0	24	39	76	8.31	< 10	< 1	0.18	30	2.55	1645
108336	208	294	< 0.002	0.2	2.80	< 5	280	< 0.5	< 2	2.89	< 0.5	44	133	27	5.01	< 10	< 1	0.11	20	1.91	1585
108338	208	294	< 0.002	2.4	1.35	70	2490	0.5	< 2	0.86	0.5	4	86	5	1.65	< 10	< 1	0.49	30	0.46	285
108360	208	294	0.002	>200	0.53	90	120	< 0.5	6	0.11	71.0	3	415	11	1.85	< 10	< 1	0.17	< 10	0.28	140
108366	208	294	0.002	0.4	2.40	45	160	< 0.5	< 2	2.52	< 0.5	29	82	70	5.81	< 10	< 1	0.45	< 10	2.17	1175
108368	208	294	< 0.002	1.0	0.66	5	110	< 0.5	2	0.08	< 0.5	1	133	23	1.41	< 10	< 1	0.25	10	0.06	95

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Invoice Date: 22-AUG-90
Invoice No. : I-9020957
P.O. Number : NONE

CERTIFICATE OF ANALYSIS A9020957

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
108288	208	294	< 1	0.01	6	20	22	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	20
108289	208	294	< 1	0.01	7	40	74	< 5	< 1	3	< 0.01	< 10	< 10	1	< 10	6
108290	208	294	< 1	0.01	5	10	852	20	< 1	92	< 0.01	< 10	< 10	< 1	< 10	12
108291	208	294	1	0.02	6	420	280	< 5	< 1	47	< 0.01	< 10	< 10	3	< 10	54
108292	208	294	< 1	0.01	11	30	14	< 5	< 1	7	< 0.01	< 10	< 10	3	< 10	8
108294	208	294	1	0.12	343	2870	8	< 5	18	154	0.10	< 10	< 10	188	< 10	150
108295	208	294	1	0.01	4	20	16	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	2
108296	208	294	< 1	0.02	4	20	< 2	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	4
108297	208	294	< 1	0.02	5	20	< 2	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	4
108301	208	294	1	0.04	34	1080	18	5	11	120	0.02	< 10	< 10	61	< 10	90
108302	208	294	1	0.06	27	870	712	5	4	52	0.09	< 10	< 10	61	< 10	404
108303	208	294	< 1	0.05	4	60	4	< 5	< 1	3	< 0.01	< 10	< 10	1	< 10	4
108304	208	294	< 1	0.01	3	30	20	< 5	< 1	10	< 0.01	< 10	< 10	1	< 10	8
108305	208	294	< 1	0.01	4	10	6	5	1	490	< 0.01	< 10	< 10	1	< 10	24
108306	208	294	< 1	0.02	2	110	24	< 5	1	56	< 0.01	< 10	< 10	2	< 10	26
108308	208	294	< 1	0.14	32	1780	14	5	20	311	0.01	< 10	< 10	148	10	120
108309	208	294	1	0.05	5	440	30	< 5	2	39	< 0.01	< 10	< 10	34	< 10	70
108310	208	294	< 1	0.02	1	40	20	< 5	< 1	3	< 0.01	< 10	< 10	< 1	< 10	20
108311	208	294	1	0.04	6	20	352	< 5	2	11	< 0.01	< 10	< 10	1	< 10	18
108312	208	294	1	0.02	5	140	22	< 5	< 1	6	< 0.01	< 10	< 10	5	< 10	40
108313	208	294	< 1	0.01	5	< 10	4	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	2
108314	208	294	< 1	0.05	2	70	6	< 5	1	3	< 0.01	< 10	< 10	1	< 10	22
108315	208	294	1	0.11	1	150	< 2	15	< 1	19	< 0.01	< 10	< 10	1	< 10	4
108316	208	294	2	0.06	5	590	64	< 5	2	25	< 0.01	< 10	< 10	48	< 10	62
108317	208	294	1	0.01	7	30	6	< 5	< 1	1	< 0.01	< 10	< 10	3	< 10	10
108318	208	294	< 1	0.01	3	< 10	10	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	2
108319	208	294	9	0.06	35	630	3060	< 5	3	269	0.04	< 10	< 10	36	1550	98
108320	208	294	1	0.01	7	30	8	< 5	< 1	2	< 0.01	< 10	< 10	2	< 10	8
108321	208	294	2	0.02	10	780	62	5	2	15	< 0.01	< 10	< 10	9	< 10	78
108322	208	294	1	0.01	6	< 10	188	< 5	< 1	2	< 0.01	< 10	< 10	2	< 10	8
108323	208	294	2	0.01	4	250	36	< 5	1	11	< 0.01	< 10	< 10	3	< 10	62
108324	208	294	1	0.01	4	< 10	98	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	16
108325	208	294	< 1	0.04	7	380	20	< 5	1	10	0.01	< 10	< 10	12	< 10	46
108327	208	294	4	0.01	11	110	102	< 5	< 1	7	< 0.01	< 10	< 10	3	< 10	12
108333	208	294	6	0.04	20	3140	274	15	12	91	0.22	< 10	< 10	162	10	278
108336	208	294	< 1	0.46	72	2090	4	< 5	13	273	0.25	< 10	< 10	104	< 10	116
108338	208	294	< 1	0.03	10	260	714	5	4	80	< 0.01	< 10	< 10	9	< 10	322
108360	208	294	3	0.02	8	150	>10000	165	1	27	0.03	< 10	< 10	17	< 10	4660
108366	208	294	< 1	0.02	16	530	104	5	9	105	0.12	< 10	< 10	91	< 10	58
108368	208	294	3	0.12	4	130	96	< 5	1	12	0.01	< 10	< 10	10	< 10	34

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Page Number : 3-A
Total Pages : 4
Invoice Date: 22-AUG-90
Invoice No. : I-9020957
P.O. Number : NONE

CERTIFICATE OF ANALYSIS A9020957

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
108375	208	294	< 0.002	0.6	2.90	< 5	650	< 0.5	< 2	0.48	0.5	9	148	24	5.47	10	< 1	0.23	30	2.03	690
108376	208	294	< 0.002	0.8	2.40	< 5	440	< 0.5	< 2	2.39	< 0.5	33	49	22	6.54	10	< 1	0.16	20	1.94	2470
108378	208	294	< 0.002	< 0.2	2.15	< 5	520	< 0.5	< 2	0.33	< 0.5	8	250	12	4.70	10	< 1	0.32	10	1.24	545
108379	208	294	< 0.002	< 0.2	0.96	35	110	< 0.5	< 2	0.35	< 0.5	3	150	4	1.43	< 10	< 1	0.08	10	0.28	225
108380	208	294	0.004	< 0.2	0.29	< 5	140	< 0.5	< 2	0.02	< 0.5	1	390	4	0.87	< 10	< 1	0.04	< 10	0.16	80
108381	208	294	< 0.002	0.4	0.66	50	2430	< 0.5	< 2	0.04	< 0.5	2	98	12	1.78	< 10	< 1	0.29	20	0.08	80
108385	208	294	< 0.002	< 0.2	0.17	< 5	210	< 0.5	2	0.01	< 0.5	1	163	6	0.42	< 10	< 1	0.14	10	0.01	180
108387	208	294	< 0.002	< 0.2	0.31	< 5	190	< 0.5	< 2	0.20	< 0.5	< 1	133	3	0.57	< 10	< 1	0.24	30	0.10	85
108390	208	294	< 0.002	< 0.2	0.63	< 5	710	< 0.5	2	0.18	< 0.5	4	169	49	1.64	< 10	< 1	0.47	30	0.42	355
108391	208	294	< 0.002	< 0.2	1.14	5	820	< 0.5	< 2	0.13	< 0.5	4	115	12	2.64	< 10	< 1	0.29	10	0.63	270
108392	208	294	< 0.002	< 0.2	0.76	< 5	70	< 0.5	2	0.16	< 0.5	2	248	3	1.53	< 10	< 1	0.04	< 10	0.51	190
108396	208	294	0.002	0.4	0.46	95	320	< 0.5	< 2	0.04	0.5	2	521	11	1.65	< 10	< 1	0.16	< 10	0.07	145
108399	208	294	< 0.002	1.2	0.90	690	150	0.5	< 2	0.13	1.5	2	95	6	1.40	10	< 1	0.39	60	0.12	150
1803 J	208	294	< 0.002	1.6	3.29	25	750	1.5	< 2	1.86	1.0	25	51	28	7.59	20	< 1	0.37	40	1.83	750
1804 J	208	294	< 0.002	1.4	0.80	20	740	0.5	2	0.16	< 0.5	9	76	16	2.10	< 10	< 1	0.31	30	0.31	135
1805 J	208	294	< 0.002	9.8	0.43	230	350	< 0.5	< 2	5.87	2.0	40	573	15	3.12	< 10	< 1	< 0.01	< 10	11.70	855
1806 J	208	294	< 0.002	>200	0.08	60	20	< 0.5	8	0.01	>100.0	< 1	126	615	1.30	< 10	< 1	< 0.01	< 10	0.04	20
1807 J	208	294	< 0.002	0.8	0.52	15	110	< 0.5	2	0.06	< 0.5	< 1	87	12	1.42	< 10	< 1	0.31	10	0.05	55
1808 J	208	294	0.013	>200	0.07	150	< 10	< 0.5	< 2	0.04	46.0	< 1	226	1710	1.81	< 10	< 1	< 0.01	< 10	0.05	40
1809 J	208	294	< 0.002	1.0	0.17	< 5	3660	< 0.5	2	0.01	< 0.5	< 1	151	6	0.30	< 10	< 1	0.15	< 10	0.01	10
1810 J	208	294	< 0.002	0.6	0.24	10	350	< 0.5	2	0.01	0.5	< 1	189	7	0.58	< 10	< 1	0.28	20	0.02	60
1811 J	208	294	0.026	5.8	0.20	< 5	140	< 0.5	2	0.01	0.5	< 1	309	24	0.80	< 10	< 1	0.07	< 10	0.05	50
1812 J	208	294	< 0.002	< 0.2	0.03	< 5	30	< 0.5	< 2	0.01	< 0.5	< 1	268	3	0.28	< 10	< 1	< 0.01	< 10	< 0.01	20
1813 J	208	294	< 0.002	< 0.2	0.02	5	60	< 0.5	< 2	0.01	< 0.5	< 1	220	3	0.30	< 10	< 1	< 0.01	< 10	< 0.01	40
1815 J	208	294	< 0.002	< 0.2	0.08	< 5	70	< 0.5	2	0.01	< 0.5	< 1	223	2	0.42	< 10	< 1	0.06	< 10	0.01	30
1816 J	208	294	< 0.002	< 0.2	0.11	5	40	< 0.5	2	0.02	< 0.5	3	200	6	0.82	< 10	< 1	< 0.01	< 10	0.02	95
1817 J	208	294	0.051	8.0	0.22	< 5	1220	< 0.5	2	0.01	< 0.5	< 1	262	16	0.80	< 10	< 1	0.13	< 10	0.05	45
1818 J	208	294	0.002	< 0.2	0.11	< 5	6460	< 0.5	2	0.01	< 0.5	< 1	323	7	0.80	< 10	< 1	< 0.01	< 10	0.01	35
1819 J	208	294	0.319	1.2	0.43	20	190	< 0.5	< 2	0.02	0.5	12	264	7	0.80	< 10	< 1	0.08	< 10	0.44	515
1820 J	208	294	0.002	2.0	4.00	< 5	170	< 0.5	< 2	2.52	18.5	35	44	23	8.80	20	< 1	0.14	30	3.37	950
1821 J	208	294	0.022	1.4	0.41	10	170	< 0.5	4	0.07	0.5	2	297	12	1.12	< 10	< 1	0.01	< 10	0.54	120
1822 J	208	294	0.145	0.4	0.16	< 5	100	< 0.5	2	0.03	< 0.5	< 1	224	2	0.58	< 10	< 1	0.08	< 10	0.06	130
1823 J	208	294	< 0.002	< 0.2	0.03	5	20	< 0.5	2	0.01	< 0.5	< 1	279	1	0.33	< 10	< 1	< 0.01	< 10	0.02	90
1824 J	208	294	< 0.002	0.4	0.54	5	160	< 0.5	< 2	0.14	< 0.5	2	260	12	0.95	< 10	1	0.11	10	0.21	95
1825 J	208	294	0.002	>200	0.09	700	< 10	< 0.5	80	0.03	>100.0	< 1	204	>10000	3.46	< 10	< 1	< 0.01	< 10	0.04	20
1826 J	208	294	< 0.002	27.8	2.91	20	120	< 0.5	< 2	2.88	2.0	26	80	356	6.51	10	< 1	0.36	< 10	2.11	1060
1827 J	208	294	< 0.002	22.0	0.44	110	350	< 0.5	< 2	0.08	2.5	1	337	318	2.70	< 10	< 1	0.30	< 10	0.21	130
1828 J	208	294	0.004	24.6	0.12	520	20	< 0.5	8	0.03	3.0	< 1	237	449	3.76	< 10	< 1	0.08	< 10	0.02	55
1829 J	208	294	< 0.002	2.0	0.50	85	250	< 0.5	< 2	0.04	0.5	3	253	69	1.11	< 10	< 1	0.29	10	0.06	180
1830 J	208	294	< 0.002	< 0.2	0.06	10	300	< 0.5	< 2	0.01	< 0.5	< 1	240	4	0.42	< 10	< 1	0.02	< 10	0.01	20

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Page Number : 3-B
Total Pages : 4
Invoice Date: 22-AUG-90
Invoice No. : I-9020957
P.O. Number : NONE

CERTIFICATE OF ANALYSIS A9020957

SAMPLE DESCRIPTION	PREP CODE	Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
108375	208 294	< 1	0.05	16	990	30	< 5	11	26	0.24	< 10	< 10	57	< 10	144
108376	208 294	< 1	0.28	29	2720	20	< 5	9	124	0.12	< 10	< 10	79	< 10	108
108378	208 294	< 1	0.07	16	930	22	< 5	11	22	0.04	< 10	< 10	59	< 10	62
108379	208 294	< 1	0.02	4	280	26	< 5	2	30	0.05	< 10	< 10	15	< 10	40
108380	208 294	< 1	0.01	7	50	24	< 5	< 1	1	< 0.01	< 10	< 10	7	< 10	26
108381	208 294	1	0.01	7	210	26	< 5	1	15	< 0.01	< 10	< 10	7	< 10	24
108385	208 294	1	0.01	4	20	42	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	8
108387	208 294	< 1	0.02	1	90	96	< 5	1	20	< 0.01	< 10	< 10	1	< 10	26
108390	208 294	< 1	0.04	8	310	64	< 5	3	27	0.11	< 10	< 10	6	< 10	32
108391	208 294	< 1	0.02	3	800	82	< 5	6	51	0.05	< 10	< 10	24	< 10	28
108392	208 294	< 1	0.02	8	630	120	< 5	1	6	0.02	< 10	< 10	12	< 10	44
108396	208 294	4	0.01	11	110	186	< 5	1	9	< 0.01	< 10	< 10	8	< 10	46
108399	208 294	2	0.02	7	230	282	10	1	15	< 0.01	< 10	< 10	4	< 10	62
1803 J	208 294	< 1	0.04	34	4980	492	5	19	91	0.07	< 10	< 10	97	10	150
1804 J	208 294	1	0.01	33	250	882	< 5	1	27	< 0.01	< 10	< 10	5	< 10	64
1805 J	208 294	< 1	0.01	762	< 10	5400	10	4	789	< 0.01	20	< 10	11	< 10	112
1806 J	208 294	6	0.01	2	20	>10000	980	< 1	183	< 0.01	< 10	< 10	1	30	6370
1807 J	208 294	2	0.01	4	100	402	< 5	< 1	9	< 0.01	< 10	< 10	2	< 10	34
1808 J	208 294	3	0.01	5	20	8200	30	< 1	5	< 0.01	< 10	< 10	3	10	2750
1809 J	208 294	< 1	0.03	2	60	108	< 5	< 1	121	< 0.01	< 10	< 10	< 1	< 10	32
1810 J	208 294	2	0.02	3	60	74	< 5	< 1	5	< 0.01	< 10	< 10	1	< 10	26
1811 J	208 294	< 1	0.03	4	80	260	< 5	< 1	4	< 0.01	< 10	< 10	2	< 10	56
1812 J	208 294	< 1	0.01	3	10	46	< 5	< 1	< 1	< 0.01	< 10	< 10	1	< 10	12
1813 J	208 294	< 1	0.01	3	10	60	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	12
1815 J	208 294	< 1	0.03	4	110	112	< 5	< 1	9	< 0.01	< 10	< 10	< 1	< 10	12
1816 J	208 294	1	0.01	11	120	40	< 5	< 1	1	< 0.01	< 10	< 10	9	< 10	20
1817 J	208 294	1	0.03	3	110	178	< 5	< 1	13	< 0.01	< 10	< 10	2	< 10	54
1818 J	208 294	< 1	0.01	5	90	30	< 5	< 1	22	< 0.01	< 10	< 10	1	< 10	22
1819 J	208 294	1	0.02	9	20	40	< 5	< 1	2	< 0.01	< 10	< 10	4	< 10	50
1820 J	208 294	< 1	0.12	22	2940	188	5	17	76	0.14	< 10	< 10	162	10	1690
1821 J	208 294	< 1	0.06	5	260	246	< 5	< 1	5	< 0.01	< 10	< 10	4	< 10	36
1822 J	208 294	< 1	0.01	4	50	54	< 5	< 1	3	< 0.01	< 10	< 10	2	< 10	28
1823 J	208 294	< 1	0.01	4	10	12	< 5	< 1	< 1	< 0.01	< 10	< 10	1	< 10	10
1824 J	208 294	< 1	0.03	8	460	50	< 5	2	6	0.02	< 10	< 10	9	< 10	32
1825 J	208 294	4	0.01	3	< 200	>10000	7190	< 1	21	< 0.01	< 10	< 10	< 1	30	5580
1826 J	208 294	4	0.05	16	470	1820	35	13	87	0.15	< 10	< 10	159	< 10	186
1827 J	208 294	27	0.02	6	70	6290	30	1	8	< 0.01	< 10	< 10	22	< 10	254
1828 J	208 294	335	0.01	4	10	>10000	15	< 1	5	< 0.01	< 10	< 10	3	< 10	310
1829 J	208 294	1	0.01	4	80	340	10	< 1	6	< 0.01	< 10	< 10	1	< 10	62
1830 J	208 294	1	0.01	4	30	84	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	10

CERTIFICATION: B. Caplette

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Invoice Date: 22-AUG-90
Invoice No. : I-9020957
P.O. Number : NONE

CERTIFICATE OF ANALYSIS A9020957

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
1831 J	208	294	< 0.002	0.6	0.03	< 5	20	< 0.5	4	0.01	< 0.5	< 1	279	6	0.34	< 10	< 1	< 0.01	< 10	0.01	50
1832 J	208	294	< 0.002	0.4	0.06	10	60	< 0.5	< 2	< 0.01	< 0.5	< 1	311	2	0.35	< 10	< 1	0.01	< 10	< 0.01	55
1833 J	208	294	< 0.002	1.0	0.50	15	330	< 0.5	4	0.01	< 0.5	1	190	2	0.56	10	< 1	0.43	30	0.03	65
1834 J	208	294	< 0.002	< 0.2	0.09	< 5	50	< 0.5	4	< 0.01	< 0.5	< 1	404	2	0.36	< 10	1	0.01	< 10	0.01	60
1835 J	208	294	< 0.002	1.0	0.79	180	4640	0.5	2	0.04	0.5	< 1	109	8	1.21	10	< 1	0.39	30	0.04	80
1836 J	208	294	0.004	0.8	0.21	5	1690	< 0.5	6	0.03	< 0.5	2	294	21	0.73	< 10	< 1	0.07	10	0.07	120
1837 J	208	294	< 0.002	0.8	7.18	< 5	50	< 0.5	< 2	0.17	0.5	43	731	216	6.28	20	< 1	< 0.01	< 10	8.44	1250
1838 J	208	294	< 0.002	< 0.2	0.12	< 5	20	< 0.5	2	< 0.01	< 0.5	< 1	292	6	0.49	< 10	< 1	< 0.01	< 10	0.13	65
1839 J	208	294	< 0.002	< 0.2	5.12	5	70	< 0.5	< 2	0.07	1.0	16	382	165	5.61	< 10	< 1	0.10	< 10	6.45	1020
1842 J	208	294	< 0.002	2.8	0.17	< 5	120	< 0.5	4	0.08	0.5	< 1	178	39	1.73	< 10	< 1	0.05	10	0.06	80
1843 J	208	294	0.151	55.0	0.03	< 5	310	< 0.5	2	0.05	6.0	< 1	298	455	0.43	< 10	2	< 0.01	< 10	0.05	35
1844 J	208	294	0.051	104.5	0.03	5	120	< 0.5	26	0.02	3.5	< 1	290	449	0.44	< 10	< 1	< 0.01	< 10	0.02	35
1845 J	208	294	0.002	2.8	0.13	< 5	480	< 0.5	2	0.08	0.5	< 1	289	14	0.38	< 10	< 1	< 0.01	10	0.09	65
1846 J	208	294	0.002	4.2	0.51	< 5	520	< 0.5	12	0.13	< 0.5	5	80	10	1.65	< 10	< 1	0.48	30	0.05	30
1847 J	208	294	< 0.002	22.0	0.03	5	6040	< 0.5	6	0.02	6.0	1	335	321	0.40	< 10	1	< 0.01	< 10	0.01	35
1848 J	208	294	0.002	5.4	0.02	< 5	4530	< 0.5	4	0.02	< 0.5	< 1	395	16	0.41	< 10	< 1	< 0.01	< 10	0.01	30
1849 J	208	294	< 0.002	0.8	0.28	5	450	< 0.5	< 2	0.32	0.5	1	229	25	1.45	< 10	< 1	0.21	10	0.08	75
1850 J	208	294	< 0.002	0.4	0.54	10	2420	< 0.5	6	0.03	< 0.5	1	137	7	0.87	< 10	< 1	0.32	10	0.20	75
1851 J	208	294	< 0.002	< 0.2	0.19	< 5	410	< 0.5	< 2	0.03	< 0.5	1	401	4	0.59	< 10	< 1	0.07	< 10	0.06	105
1852 J	208	294	< 0.002	< 0.2	3.63	< 5	1710	< 0.5	< 2	4.51	< 0.5	31	32	21	7.92	10	< 1	0.14	< 10	2.67	1035
1853 J	208	294	0.002	< 0.2	0.15	< 5	770	< 0.5	< 2	0.02	< 0.5	< 1	195	2	0.40	< 10	< 1	0.08	10	0.02	55
1854 J	208	294	< 0.002	< 0.2	3.75	10	2270	< 0.5	< 2	3.40	1.0	27	41	22	6.81	10	< 1	0.08	10	2.31	825
1855 J	208	294	0.006	< 0.2	0.62	5	3880	< 0.5	< 2	0.10	1.0	< 1	114	3	1.91	< 10	< 1	0.11	40	0.30	510
1856 J	208	294	< 0.002	< 0.2	0.06	< 5	100	< 0.5	< 2	0.04	< 0.5	< 1	398	2	0.44	< 10	1	< 0.01	< 10	0.02	85
1857 J	208	294	< 0.002	< 0.2	0.27	< 5	180	< 0.5	< 2	0.02	< 0.5	1	145	1	0.40	< 10	< 1	0.22	30	0.01	40

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Page Number : 4-B
Total Pages : 4
Invoice Date: 22-AUG-90
Invoice No. : I-9020957
P.O. Number : NONE

CERTIFICATE OF ANALYSIS A9020957

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
1831 J	208	294	< 1	0.01	5	30	48	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	10
1832 J	208	294	< 1	0.01	4	10	28	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	14
1833 J	208	294	< 1	0.05	3	40	30	< 5	1	2	< 0.01	< 10	< 10	1	< 10	18
1834 J	208	294	< 1	0.01	5	10	32	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	6
1835 J	208	294	1	0.01	3	210	34	< 5	1	45	< 0.01	< 10	< 10	2	< 10	36
1836 J	208	294	< 1	0.04	5	130	90	< 5	< 1	58	< 0.01	< 10	< 10	1	< 10	38
1837 J	208	294	< 1	0.01	155	60	390	5	24	3	0.13	< 10	< 10	184	< 10	504
1838 J	208	294	< 1	0.01	7	20	24	< 5	< 1	< 1	< 0.01	< 10	< 10	3	< 10	20
1839 J	208	294	1	0.02	79	70	266	10	18	2	0.07	< 10	< 10	150	< 10	518
1842 J	208	294	9	0.09	3	90	736	5	< 1	9	< 0.01	< 10	< 10	< 1	< 10	136
1843 J	208	294	1	0.01	4	< 10	2860	100	< 1	7	< 0.01	< 10	< 10	1	< 10	126
1844 J	208	294	1	0.01	4	< 10	>10000	85	< 1	2	< 0.01	< 10	< 10	< 1	< 10	82
1845 J	208	294	< 1	0.09	4	60	680	< 5	1	16	< 0.01	< 10	< 10	< 1	< 10	76
1846 J	208	294	3	0.01	4	290	182	< 5	< 1	13	< 0.01	< 10	< 10	< 1	< 10	60
1847 J	208	294	22	0.01	4	< 10	2790	55	< 1	98	< 0.01	< 10	< 10	< 1	< 10	302
1848 J	208	294	< 1	0.01	5	< 10	280	15	< 1	101	< 0.01	< 10	< 10	< 1	< 10	24
1849 J	208	294	2	0.03	8	300	230	< 5	< 1	30	< 0.01	< 10	< 10	2	< 10	108
1850 J	208	294	< 1	0.07	4	90	32	< 5	4	26	< 0.01	< 10	< 10	3	< 10	48
1851 J	208	294	< 1	0.01	5	120	12	< 5	< 1	4	< 0.01	< 10	< 10	3	< 10	12
1852 J	208	294	< 1	0.09	26	1760	6	< 5	22	181	0.01	< 10	< 10	158	20	126
1853 J	208	294	< 1	0.05	3	50	6	< 5	< 1	5	< 0.01	< 10	< 10	1	< 10	8
1854 J	208	294	< 1	0.22	29	1710	6	< 5	21	175	0.11	< 10	< 10	157	10	106
1855 J	208	294	< 1	0.10	4	40	82	< 5	14	26	< 0.01	< 10	< 10	5	< 10	60
1856 J	208	294	< 1	0.01	4	70	8	< 5	< 1	2	< 0.01	< 10	< 10	2	< 10	8
1857 J	208	294	< 1	0.09	2	30	14	< 5	< 1	3	< 0.01	< 10	< 10	1	< 10	8

CERTIFICATION: B. Caplan

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

A9021703

Comments:

CERTIFICATE A9021703

ARBOR RESOURCES INC.

Project: DAWSON
P.O. # :

Samples submitted to our lab in Vancouver, BC.
This report was printed on 5-SEP-90.

SAMPLE PREPARATION

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION
208	120	Assay ring to approx 150 mesh
294	120	Crush and split (0-10 pounds)

* NOTE 1:

The 32 element ICP package is suitable for trace metals in soil and rock samples. Elements for which the nitric-aqua regia digestion is possibly incomplete are: Al, Ba, Be, Ca, Cr, Ga, K, La, Mg, Na, Sr, Ti, Tl, W.

ANALYTICAL PROCEDURES

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION	METHOD	DETECTION LIMIT	UPPER LIMIT
398	120	Au oz/T: 1/2 assay ton	FA-AAS	0.002	20.00
922	120	Ag ppm: 32 element, soil & rock	ICP-AES	0.2	200
921	120	Al %: 32 element, soil & rock	ICP-AES	0.01	15.00
923	120	As ppm: 32 element, soil & rock	ICP-AES	5	10000
924	120	Ba ppm: 32 element, soil & rock	ICP-AES	10	10000
925	120	Be ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
926	120	Bi ppm: 32 element, soil & rock	ICP-AES	2	10000
927	120	Ca %: 32 element, soil & rock	ICP-AES	0.01	15.00
928	120	Cd ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
929	120	Co ppm: 32 element, soil & rock	ICP-AES	1	10000
930	120	Cr ppm: 32 element, soil & rock	ICP-AES	1	10000
931	120	Cu ppm: 32 element, soil & rock	ICP-AES	1	10000
932	120	Fe %: 32 element, soil & rock	ICP-AES	0.01	15.00
933	120	Ga ppm: 32 element, soil & rock	ICP-AES	10	10000
951	120	Hg ppm: 32 element, soil & rock	ICP-AES	1	10000
934	120	K %: 32 element, soil & rock	ICP-AES	0.01	10.00
935	120	La ppm: 32 element, soil & rock	ICP-AES	10	10000
936	120	Mg %: 32 element, soil & rock	ICP-AES	0.01	15.00
937	120	Mn ppm: 32 element, soil & rock	ICP-AES	5	10000
938	120	Mo ppm: 32 element, soil & rock	ICP-AES	1	10000
939	120	Na %: 32 element, soil & rock	ICP-AES	0.01	5.00
940	120	Ni ppm: 32 element, soil & rock	ICP-AES	1	10000
941	120	P ppm: 32 element, soil & rock	ICP-AES	10	10000
942	120	Pb ppm: 32 element, soil & rock	ICP-AES	2	10000
943	120	Sb ppm: 32 element, soil & rock	ICP-AES	5	10000
958	120	Sc ppm: 32 elements, soil & rock	ICP-AES	1	10000
944	120	Sr ppm: 32 element, soil & rock	ICP-AES	1	10000
945	120	Ti %: 32 element, soil & rock	ICP-AES	0.01	5.00
946	120	Tl ppm: 32 element, soil & rock	ICP-AES	10	10000
947	120	U ppm: 32 element, soil & rock	ICP-AES	10	10000
948	120	V ppm: 32 element, soil & rock	ICP-AES	1	10000
949	120	W ppm: 32 element, soil & rock	ICP-AES	10	10000
950	120	Zn ppm: 32 element, soil & rock	ICP-AES	2	10000

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Invoice Date: 5-SEP-90
Invoice No. : I-9021703
P.O. Number :

CERTIFICATE OF ANALYSIS A9021703

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
38951	208	294	< 0.002	< 0.2	0.44	25	690	< 0.5	< 2	0.06	< 0.5	< 1	65	2	0.49	< 10	< 1	0.29	30	0.04	100
38952	208	294	< 0.002	< 0.2	0.43	20	900	0.5	< 2	0.07	< 0.5	1	43	4	0.60	< 10	< 1	0.33	40	0.05	100
38953	208	294	< 0.002	< 0.2	0.56	5	710	0.5	< 2	0.06	< 0.5	< 1	37	2	0.55	< 10	< 1	0.33	40	0.06	120
38954	208	294	< 0.002	< 0.2	0.56	10	640	< 0.5	< 2	0.06	< 0.5	< 1	38	< 1	0.50	< 10	< 1	0.34	40	0.06	145
38955	208	294	< 0.002	< 0.2	0.66	10	580	< 0.5	< 2	0.07	0.5	1	34	< 1	0.55	< 10	< 1	0.36	40	0.06	125
38957	208	294	< 0.002	< 0.2	0.50	10	620	< 0.5	< 2	0.05	< 0.5	< 1	33	< 1	0.53	< 10	< 1	0.32	40	0.05	335
38958	208	294	< 0.002	< 0.2	0.40	10	380	< 0.5	< 2	0.11	< 0.5	< 1	41	< 1	0.32	< 10	< 1	0.32	20	0.02	190
38959	208	294	< 0.002	< 0.2	0.41	5	640	< 0.5	< 2	0.03	< 0.5	< 1	31	< 1	0.42	< 10	< 1	0.41	20	0.04	250
38960	208	294	< 0.002	< 0.2	0.37	10	400	< 0.5	< 2	0.05	< 0.5	< 1	38	< 1	0.44	< 10	< 1	0.26	40	0.03	220
38961	208	294	< 0.002	< 0.2	0.16	5	270	< 0.5	< 2	0.02	< 0.5	< 1	132	< 1	0.28	< 10	< 1	0.08	< 10	0.01	110
38962	208	294	< 0.002	< 0.2	0.47	< 5	610	< 0.5	< 2	0.03	< 0.5	< 1	47	1	0.46	< 10	< 1	0.30	30	0.04	150
38963	208	294	< 0.002	< 0.2	1.00	< 5	350	< 0.5	2	0.45	0.5	4	71	9	1.36	< 10	< 1	0.57	30	0.66	490
38964	208	294	1.358	15.0	0.14	10	70	< 0.5	6	0.01	< 0.5	< 1	196	3	0.59	< 10	< 1	0.07	< 10	0.04	45
38965	208	294	0.020	1.2	0.77	35	390	< 0.5	< 2	0.11	1.5	4	64	3	1.25	< 10	< 1	0.47	30	0.40	325
38966	208	294	0.600	8.2	0.11	5	50	< 0.5	4	0.02	< 0.5	1	214	1	0.42	< 10	< 1	0.04	< 10	0.07	65
38967	208	294	0.060	2.4	0.05	10	60	< 0.5	2	< 0.01	< 0.5	< 1	198	1	0.77	< 10	< 1	0.03	< 10	0.01	25
38968	208	294	0.102	< 0.2	0.15	5	50	< 0.5	< 2	0.01	< 0.5	1	197	1	0.44	< 10	< 1	0.05	< 10	0.12	160
38969	208	294	0.052	1.4	0.27	20	100	< 0.5	2	0.02	< 0.5	1	185	1	0.66	< 10	< 1	0.14	10	0.11	100
38970	208	294	0.036	4.8	0.06	< 5	40	< 0.5	< 2	< 0.01	< 0.5	< 1	248	< 1	0.37	< 10	< 1	0.01	< 10	0.03	110
38971	208	294	0.858	33.0	0.07	< 5	30	< 0.5	< 2	< 0.01	< 0.5	< 1	267	1	0.38	< 10	< 1	0.03	< 10	0.02	45
38972	208	294	0.008	1.2	0.08	< 5	50	< 0.5	2	0.03	< 0.5	< 1	193	3	0.38	< 10	< 1	0.02	< 10	0.04	85
38973	208	294	0.385	5.4	0.15	5	60	< 0.5	2	0.01	0.5	1	249	4	0.55	< 10	< 1	0.04	< 10	0.10	120
38974	208	294	0.042	< 0.2	0.11	5	40	< 0.5	2	0.02	0.5	1	242	2	0.45	< 10	< 1	0.02	< 10	0.07	205
38975	208	294	0.165	2.6	0.16	5	60	< 0.5	< 2	0.02	0.5	1	200	2	0.54	< 10	< 1	0.05	< 10	0.10	180
38976	208	294	0.068	3.6	0.10	10	30	< 0.5	< 2	0.02	0.5	< 1	215	2	0.60	< 10	< 1	0.03	< 10	0.08	115
38977	208	294	< 0.002	< 0.2	0.29	5	80	< 0.5	< 2	0.08	1.0	3	202	4	0.74	< 10	< 1	0.04	< 10	0.18	180
38978	208	294	< 0.002	< 0.2	0.36	< 5	210	< 0.5	< 2	0.03	< 0.5	1	68	4	0.41	< 10	< 1	0.25	30	0.14	90
38979	208	294	< 0.002	0.4	2.47	< 5	370	< 0.5	< 2	0.43	1.0	15	55	15	3.48	< 10	< 1	0.37	20	1.17	565
38980	208	294	< 0.002	< 0.2	1.03	15	310	4.0	< 2	0.28	< 0.5	7	66	14	1.98	< 10	< 1	0.28	20	0.47	435
38981	208	294	< 0.002	< 0.2	1.15	10	310	4.0	< 2	0.29	< 0.5	8	71	14	1.93	< 10	< 1	0.31	20	0.49	375
38982	208	294	< 0.002	< 0.2	1.12	15	310	3.5	< 2	0.31	< 0.5	7	74	8	1.84	< 10	< 1	0.36	20	0.48	280
38983	208	294	< 0.002	< 0.2	1.23	10	340	3.5	< 2	0.27	< 0.5	8	77	13	1.99	< 10	< 1	0.30	20	0.61	340
38984	208	294	< 0.002	< 0.2	1.39	5	410	4.0	< 2	0.30	< 0.5	8	80	12	2.21	< 10	< 1	0.43	30	0.68	435
38985	208	294	< 0.002	< 0.2	2.37	20	520	4.5	< 2	0.40	< 0.5	14	57	21	2.95	< 10	< 1	0.37	30	0.94	545
38986	208	294	< 0.002	< 0.2	4.23	45	860	6.5	< 2	0.64	< 0.5	26	42	20	5.29	< 10	< 1	0.24	20	2.02	805
38987	208	294	< 0.002	< 0.2	4.57	35	550	5.0	< 2	0.64	0.5	24	37	18	4.74	< 10	< 1	0.28	20	2.19	635
38988	208	294	< 0.002	< 0.2	4.79	35	740	5.5	< 2	0.71	< 0.5	26	40	20	5.30	< 10	< 1	0.36	20	2.39	760
38989	208	294	< 0.002	< 0.2	1.99	75	340	2.5	< 2	0.37	0.5	11	55	27	3.07	< 10	< 1	0.21	20	1.09	490
38990	208	294	< 0.002	< 0.2	2.01	135	320	< 0.5	< 2	0.36	0.5	9	63	22	3.15	< 10	< 1	0.23	20	1.15	425
38991	208	294	< 0.002	< 0.2	1.67	120	250	< 0.5	< 2	0.29	< 0.5	8	85	18	2.94	< 10	< 1	0.18	10	0.99	295

CERTIFICATION: B. Caryl

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Invoice Date: 5-SEP-90
Invoice No. : I-9021703
P.O. Number :

CERTIFICATE OF ANALYSIS A9021703

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
38951	208	294	< 1	0.02	< 1	100	32	< 5	2	10	< 0.01	10	< 10	< 1	< 10	32
38952	208	294	< 1	0.02	1	110	20	< 5	2	9	< 0.01	< 10	< 10	< 1	< 10	50
38953	208	294	< 1	0.02	< 1	100	20	< 5	2	9	< 0.01	< 10	< 10	< 1	< 10	38
38954	208	294	< 1	0.01	< 1	80	56	< 5	2	7	< 0.01	< 10	< 10	< 1	< 10	40
38955	208	294	< 1	0.01	< 1	80	20	< 5	2	7	< 0.01	< 10	< 10	< 1	< 10	62
38957	208	294	< 1	0.01	< 1	90	28	< 5	2	7	< 0.01	< 10	< 10	< 1	< 10	34
38958	208	294	< 1	0.02	< 1	70	16	< 5	1	11	< 0.01	< 10	< 10	< 1	< 10	22
38959	208	294	< 1	0.01	1	90	18	< 5	2	5	< 0.01	< 10	< 10	< 1	< 10	20
38960	208	294	< 1	0.03	< 1	90	22	< 5	2	9	< 0.01	10	< 10	< 1	< 10	32
38961	208	294	< 1	0.01	1	30	10	< 5	< 1	3	< 0.01	< 10	< 10	< 1	< 10	10
38962	208	294	< 1	0.01	< 1	60	16	< 5	2	6	< 0.01	< 10	< 10	< 1	< 10	22
38963	208	294	< 1	0.02	4	430	38	< 5	1	25	0.02	< 10	< 10	3	< 10	46
38964	208	294	< 1	0.01	3	30	862	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	82
38965	208	294	< 1	0.02	4	360	68	< 5	1	11	0.01	< 10	< 10	3	< 10	104
38966	208	294	< 1	< 0.01	3	50	272	< 5	< 1	4	< 0.01	< 10	< 10	< 1	< 10	48
38967	208	294	1	< 0.01	2	10	130	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	22
38968	208	294	< 1	< 0.01	3	20	112	< 5	< 1	1	< 0.01	10	< 10	1	< 10	40
38969	208	294	< 1	0.01	3	60	190	< 5	< 1	3	< 0.01	10	< 10	1	< 10	90
38970	208	294	< 1	< 0.01	2	< 10	50	< 5	< 1	< 1	< 0.01	< 10	< 10	< 1	< 10	26
38971	208	294	< 1	< 0.01	3	< 10	76	< 5	< 1	< 1	< 0.01	10	< 10	1	< 10	14
38972	208	294	< 1	< 0.01	2	< 10	154	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	24
38973	208	294	1	< 0.01	3	10	374	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	60
38974	208	294	< 1	< 0.01	3	30	178	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	48
38975	208	294	< 1	< 0.01	3	20	126	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	68
38976	208	294	< 1	< 0.01	2	40	352	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	54
38977	208	294	< 1	0.01	7	110	22	< 5	1	7	0.02	< 10	< 10	7	< 10	18
38978	208	294	< 1	0.01	2	80	28	< 5	< 1	5	< 0.01	< 10	< 10	< 1	< 10	26
38979	208	294	< 1	0.01	16	830	10	< 5	9	22	0.12	< 10	< 10	51	< 10	62
38980	208	294	< 1	0.02	10	670	16	< 5	7	13	0.05	< 10	< 10	24	< 10	56
38981	208	294	< 1	0.02	10	770	22	< 5	5	13	0.04	< 10	< 10	22	< 10	52
38982	208	294	< 1	0.02	8	710	10	< 5	6	14	0.07	< 10	< 10	21	< 10	48
38983	208	294	< 1	0.02	9	630	22	< 5	7	13	0.04	< 10	< 10	23	< 10	56
38984	208	294	< 1	0.02	11	730	10	< 5	8	14	0.04	< 10	< 10	26	< 10	62
38985	208	294	< 1	0.02	18	820	8	< 5	9	30	0.05	< 10	< 10	43	< 10	68
38986	208	294	1	0.03	36	1150	2	< 5	14	54	0.07	< 10	< 10	112	< 10	98
38987	208	294	< 1	0.02	23	1110	< 2	< 5	13	39	0.10	< 10	< 10	96	< 10	90
38988	208	294	1	0.03	27	1240	< 2	< 5	14	48	0.09	< 10	< 10	114	< 10	98
38989	208	294	1	0.02	13	860	8	5	4	22	0.01	< 10	< 10	41	< 10	112
38990	208	294	< 1	0.02	13	730	10	5	4	20	0.02	< 10	< 10	43	< 10	106
38991	208	294	1	0.01	10	580	14	< 5	3	16	< 0.01	< 10	< 10	30	< 10	86

CERTIFICATION: B. Caugh

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Invoice Date: 5-SEP-90
Invoice No. : I-9021703
P.O. Number :

CERTIFICATE OF ANALYSIS A9021703

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
38992	208	294	< 0.002	< 0.2	1.81	110	290	< 0.5	< 2	0.32	< 0.5	8	229	17	2.98	< 10	< 1	0.26	10	0.99	340
38993	208	294	< 0.002	0.4	1.86	115	200	< 0.5	< 2	0.34	< 0.5	8	112	24	3.05	< 10	< 1	0.14	10	1.04	315
38994	208	294	< 0.002	< 0.2	1.56	60	230	< 0.5	< 2	0.40	< 0.5	6	203	22	2.57	< 10	< 1	0.16	10	0.84	250
38995	208	294	< 0.002	0.4	1.81	105	200	< 0.5	< 2	0.30	< 0.5	7	148	30	3.49	< 10	< 1	0.14	10	1.05	260
38996	208	294	< 0.002	0.4	2.02	110	230	< 0.5	< 2	0.32	< 0.5	9	187	30	3.54	< 10	< 1	0.16	10	1.09	325
38997	208	294	< 0.002	< 0.2	2.16	60	230	< 0.5	< 2	0.36	< 0.5	7	201	13	3.17	< 10	< 1	0.16	10	1.34	375
38998	208	294	< 0.002	0.4	1.87	55	310	< 0.5	< 2	0.35	< 0.5	9	135	31	2.85	10	< 1	0.25	20	1.02	380
38999	208	294	< 0.002	< 0.2	0.93	25	210	< 0.5	< 2	0.21	0.5	5	147	10	1.69	< 10	1	0.18	10	0.50	250
39000	208	294	< 0.002	< 0.2	1.87	50	330	< 0.5	< 2	0.40	< 0.5	11	118	23	2.93	10	< 1	0.26	20	1.08	480
39051	208	294	< 0.002	< 0.2	0.95	40	170	< 0.5	< 2	0.20	< 0.5	6	178	15	1.70	< 10	< 1	0.15	10	0.56	230
39052	208	294	< 0.002	< 0.2	1.50	50	190	< 0.5	< 2	0.30	< 0.5	8	114	28	2.31	< 10	< 1	0.14	10	0.94	325
39053	208	294	< 0.002	< 0.2	2.01	105	220	< 0.5	< 2	0.40	< 0.5	12	88	38	3.05	< 10	< 1	0.13	10	1.27	465
39054	208	294	< 0.002	< 0.2	1.84	75	210	< 0.5	< 2	0.36	< 0.5	9	96	36	2.77	< 10	< 1	0.18	10	1.21	370
39055	208	294	< 0.002	< 0.2	1.85	125	260	< 0.5	< 2	0.35	< 0.5	9	63	23	3.09	< 10	< 1	0.15	20	1.06	330
39056	208	294	< 0.002	< 0.2	2.24	90	320	< 0.5	< 2	0.38	< 0.5	10	87	29	3.48	< 10	< 1	0.17	20	1.24	365
39057	208	294	< 0.002	< 0.2	3.53	60	750	< 0.5	< 2	0.49	0.5	28	45	32	5.63	< 10	< 1	0.24	30	1.90	910
39058	208	294	< 0.002	0.4	3.95	75	890	< 0.5	< 2	0.47	< 0.5	28	56	36	5.54	< 10	< 1	0.28	30	1.79	975
39059	208	294	< 0.002	< 0.2	0.95	15	300	< 0.5	< 2	0.09	< 0.5	5	110	7	1.19	< 10	< 1	0.34	40	0.32	215
39060	208	294	< 0.002	< 0.2	1.92	30	430	< 0.5	< 2	0.21	< 0.5	10	108	15	2.66	< 10	1	0.40	30	0.81	425
39061	208	294	< 0.002	< 0.2	1.82	15	390	< 0.5	< 2	0.26	< 0.5	11	77	20	2.87	< 10	< 1	0.31	30	0.87	375
39062	208	294	< 0.002	< 0.2	1.56	50	310	< 0.5	< 2	0.31	< 0.5	8	106	18	2.49	< 10	< 1	0.24	20	0.84	310
39063	208	294	< 0.002	< 0.2	1.19	50	210	< 0.5	< 2	0.24	< 0.5	6	84	17	2.07	< 10	< 1	0.15	20	0.70	245
39064	208	294	< 0.002	< 0.2	1.33	85	230	< 0.5	< 2	0.26	< 0.5	7	140	21	2.50	< 10	< 1	0.19	20	0.77	265
39065	208	294	< 0.002	< 0.2	1.30	50	280	< 0.5	< 2	0.25	0.5	7	104	19	2.28	< 10	< 1	0.20	20	0.82	235
39066	208	294	< 0.002	< 0.2	1.51	60	320	< 0.5	< 2	0.28	< 0.5	8	120	24	2.80	< 10	< 1	0.26	20	0.86	280
39067	208	294	< 0.002	< 0.2	1.06	55	260	< 0.5	< 2	0.20	< 0.5	7	184	18	2.22	< 10	< 1	0.21	10	0.63	245
39068	208	294	< 0.002	< 0.2	1.22	20	400	< 0.5	< 2	0.16	< 0.5	8	86	15	2.13	< 10	< 1	0.33	30	0.60	260
39070	208	294	< 0.002	< 0.2	0.80	15	280	< 0.5	< 2	0.19	< 0.5	6	168	17	1.74	< 10	< 1	0.30	20	0.46	225
39071	208	294	< 0.002	< 0.2	1.25	35	340	< 0.5	< 2	0.24	< 0.5	7	107	20	2.34	< 10	< 1	0.32	30	0.72	290
39072	208	294	< 0.002	< 0.2	1.25	35	300	0.5	< 2	0.25	< 0.5	8	91	20	2.31	< 10	< 1	0.17	20	0.84	285
39073	208	294	< 0.002	< 0.2	1.29	40	360	< 0.5	< 2	0.23	< 0.5	8	77	19	2.34	< 10	< 1	0.28	20	0.66	190
39074	208	294	< 0.002	< 0.2	0.94	10	370	< 0.5	< 2	0.15	< 0.5	4	79	8	1.38	< 10	< 1	0.24	20	0.44	185
39075	208	294	< 0.002	< 0.2	0.49	< 5	360	0.5	< 2	0.06	< 0.5	2	137	2	0.69	< 10	< 1	0.28	10	0.10	100
39076	208	294	< 0.002	< 0.2	0.67	5	440	< 0.5	< 2	0.07	< 0.5	2	208	2	0.88	< 10	< 1	0.27	20	0.19	95
39077	208	294	< 0.002	< 0.2	0.80	10	790	< 0.5	< 2	0.04	< 0.5	3	111	2	0.84	< 10	< 1	0.42	20	0.12	505
39078	208	294	< 0.002	< 0.2	0.46	5	580	< 0.5	< 2	0.02	< 0.5	3	105	1	0.56	< 10	< 1	0.30	20	0.06	545
39079	208	294	< 0.002	< 0.2	1.10	45	310	< 0.5	< 2	0.17	< 0.5	6	109	12	1.82	< 10	< 1	0.29	30	0.45	240
108101	208	294	< 0.002	< 0.2	0.85	5	340	0.5	< 2	0.23	< 0.5	7	125	13	1.70	< 10	< 1	0.45	30	0.58	440
108102	208	294	< 0.002	< 0.2	1.14	< 5	460	0.5	< 2	0.32	< 0.5	9	94	16	2.08	< 10	< 1	0.59	30	0.72	400
108103	208	294	< 0.002	< 0.2	0.99	< 5	340	0.5	< 2	0.29	0.5	7	104	13	1.94	< 10	< 1	0.59	30	0.72	325

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Invoice Date: 5-SEP-90
Invoice No. : I-9021703
P.O. Number :

CERTIFICATE OF ANALYSIS A9021703

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
38992	208	294	1	0.02	13	690	18	< 5	3	17	0.01	< 10	< 10	34	< 10	102
38993	208	294	1	0.01	14	740	14	5	2	16	< 0.01	< 10	< 10	37	< 10	134
38994	208	294	1	0.01	12	1170	20	< 5	2	18	< 0.01	< 10	< 10	29	< 10	96
38995	208	294	2	0.01	14	750	24	5	2	17	< 0.01	< 10	< 10	32	< 10	174
38996	208	294	1	0.01	16	720	22	5	2	19	< 0.01	< 10	< 10	38	< 10	162
38997	208	294	1	0.01	17	730	2	5	2	21	< 0.01	< 10	< 10	36	< 10	114
38998	208	294	< 1	0.02	15	780	8	< 5	3	22	0.01	< 10	< 10	37	< 10	104
38999	208	294	1	0.01	9	480	16	< 5	4	11	0.01	< 10	< 10	19	< 10	54
39000	208	294	1	0.02	13	850	20	5	5	22	0.02	< 10	< 10	37	< 10	86
39051	208	294	1	0.01	9	470	54	< 5	2	11	< 0.01	< 10	< 10	19	< 10	66
39052	208	294	1	0.01	13	620	12	< 5	2	19	< 0.01	< 10	< 10	31	< 10	106
39053	208	294	2	0.01	16	840	14	5	3	28	< 0.01	< 10	< 10	41	< 10	146
39054	208	294	1	0.01	15	810	16	< 5	2	25	< 0.01	< 10	< 10	37	< 10	130
39055	208	294	2	0.01	8	810	6	< 5	4	32	< 0.01	< 10	< 10	40	< 10	92
39056	208	294	2	0.01	16	880	12	< 5	6	31	0.03	< 10	< 10	58	< 10	112
39057	208	294	3	0.02	30	750	12	5	13	43	0.05	< 10	< 10	99	< 10	126
39058	208	294	1	0.03	44	680	14	5	16	54	0.12	< 10	< 10	101	< 10	186
39059	208	294	< 1	0.02	7	160	16	< 5	3	10	0.01	< 10	< 10	13	< 10	32
39060	208	294	1	0.02	13	440	62	< 5	8	19	0.06	< 10	< 10	35	< 10	74
39061	208	294	< 1	0.02	15	590	22	< 5	8	21	0.04	< 10	< 10	35	< 10	74
39062	208	294	< 1	0.01	12	700	2	< 5	4	20	0.02	< 10	< 10	35	< 10	70
39063	208	294	1	0.01	9	610	10	< 5	2	14	< 0.01	< 10	< 10	27	< 10	62
39064	208	294	1	0.01	10	710	8	< 5	3	16	< 0.01	< 10	< 10	33	< 10	84
39065	208	294	1	0.01	9	670	10	< 5	3	18	< 0.01	< 10	< 10	27	< 10	68
39066	208	294	1	0.02	10	740	4	< 5	3	22	< 0.01	< 10	< 10	29	< 10	84
39067	208	294	1	0.01	10	540	4	< 5	3	16	< 0.01	< 10	< 10	22	< 10	56
39068	208	294	1	0.02	11	480	16	< 5	6	18	0.03	< 10	< 10	24	< 10	120
39070	208	294	1	0.02	9	600	12	< 5	4	16	0.01	< 10	< 10	15	< 10	42
39071	208	294	1	0.02	11	640	22	< 5	5	17	0.02	< 10	< 10	23	< 10	64
39072	208	294	1	0.01	12	580	16	< 5	3	15	< 0.01	< 10	< 10	24	< 10	74
39073	208	294	1	0.01	12	570	18	< 5	3	14	< 0.01	< 10	< 10	25	< 10	102
39074	208	294	< 1	0.01	9	250	12	< 5	3	10	< 0.01	< 10	< 10	8	< 10	68
39075	208	294	< 1	0.03	3	150	16	< 5	1	5	< 0.01	< 10	< 10	3	< 10	22
39076	208	294	< 1	0.01	5	130	18	< 5	2	6	< 0.01	< 10	< 10	4	< 10	36
39077	208	294	1	0.02	3	90	18	< 5	2	5	< 0.01	< 10	< 10	3	< 10	28
39078	208	294	1	0.01	4	80	20	< 5	1	4	< 0.01	< 10	< 10	1	< 10	20
39079	208	294	1	0.02	9	390	10	< 5	3	12	0.02	< 10	< 10	20	< 10	54
108101	208	294	< 1	0.02	10	570	30	< 5	3	16	0.03	< 10	< 10	11	< 10	46
108102	208	294	< 1	0.02	10	710	18	< 5	5	20	0.05	< 10	< 10	18	< 10	54
108103	208	294	1	0.02	10	670	12	< 5	3	18	0.06	< 10	< 10	16	< 10	56

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Page Number : 3-A
Total Pages : 3
Invoice Date: 5-SEP-90
Invoice No. : I-9021703
P.O. Number :

CERTIFICATE OF ANALYSIS A9021703

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
108104	208	294	< 0.002	< 0.2	1.82	5	590	< 0.5	< 2	0.37	< 0.5	12	46	17	2.93	< 10	< 1	0.64	40	1.09	455
108105	208	294	< 0.002	< 0.2	0.59	< 5	120	< 0.5	2	0.19	< 0.5	5	109	13	1.15	< 10	< 1	0.11	10	0.42	270
108106	208	294	< 0.002	< 0.2	1.71	< 5	290	1.0	< 2	0.36	< 0.5	9	47	< 1	3.24	< 10	< 1	0.58	30	1.22	480
108107	208	294	< 0.002	< 0.2	1.22	< 5	310	< 0.5	< 2	0.49	< 0.5	6	47	5	2.16	< 10	< 1	0.40	20	0.88	450
108108	208	294	< 0.002	< 0.2	0.37	< 5	60	< 0.5	< 2	0.68	< 0.5	2	126	< 1	0.73	< 10	< 1	0.04	< 10	0.29	265
108109	208	294	< 0.002	< 0.2	1.38	< 5	330	0.5	< 2	0.37	< 0.5	7	72	6	2.27	< 10	< 1	0.31	20	0.87	480
108110	208	294	< 0.002	< 0.2	1.21	< 5	240	< 0.5	< 2	0.31	< 0.5	6	89	8	2.25	< 10	< 1	0.21	20	0.78	445
108111	208	294	< 0.002	< 0.2	1.31	5	310	< 0.5	< 2	0.29	< 0.5	6	104	7	2.14	< 10	< 1	0.27	20	0.71	395
108112	208	294	< 0.002	< 0.2	1.10	5	250	< 0.5	< 2	0.27	< 0.5	6	97	3	1.93	< 10	< 1	0.23	10	0.67	390
108113	208	294	< 0.002	< 0.2	1.34	5	280	< 0.5	< 2	0.33	< 0.5	7	68	4	2.33	< 10	< 1	0.29	20	0.90	410
108114	208	294	< 0.002	< 0.2	1.65	5	340	< 0.5	< 2	0.36	< 0.5	8	74	12	2.84	< 10	< 1	0.37	30	0.99	545
108115	208	294	< 0.002	< 0.2	1.57	20	350	0.5	< 2	0.37	< 0.5	8	65	11	2.69	< 10	< 1	0.44	20	0.94	480
108116	208	294	< 0.002	< 0.2	1.37	20	320	< 0.5	2	0.37	< 0.5	8	85	14	2.56	< 10	< 1	0.41	30	0.87	350
108117	208	294	< 0.002	< 0.2	1.20	15	330	< 0.5	< 2	0.31	< 0.5	7	86	13	2.16	< 10	< 1	0.37	20	0.65	340
108118	208	294	< 0.002	< 0.2	1.50	10	340	< 0.5	2	0.34	< 0.5	9	76	13	3.10	< 10	< 1	0.37	30	0.64	560
108119	208	294	< 0.002	< 0.2	1.43	20	470	< 0.5	2	0.38	< 0.5	10	61	25	2.76	< 10	< 1	0.47	30	0.66	470
108120	208	294	< 0.002	< 0.2	1.05	10	400	< 0.5	< 2	0.32	< 0.5	8	72	18	2.43	< 10	< 1	0.35	30	0.55	405
108121	208	294	< 0.002	< 0.2	1.00	< 5	400	< 0.5	< 2	0.31	< 0.5	8	73	11	2.33	< 10	< 1	0.32	30	0.51	535
108122	208	294	< 0.002	< 0.2	1.30	5	390	< 0.5	< 2	0.34	< 0.5	9	68	13	2.47	< 10	< 1	0.39	30	0.66	430
108123	208	294	< 0.002	< 0.2	1.35	5	400	< 0.5	< 2	0.34	< 0.5	9	67	20	2.79	< 10	< 1	0.45	30	0.61	525
108124	208	294	< 0.002	0.4	1.35	15	410	< 0.5	2	0.42	< 0.5	8	84	24	2.30	< 10	< 1	0.41	30	0.62	480
108125	208	294	< 0.002	0.4	1.18	20	400	< 0.5	4	0.32	< 0.5	8	66	23	2.25	< 10	< 1	0.36	20	0.57	425
108126	208	294	< 0.002	< 0.2	1.46	25	380	< 0.5	< 2	0.39	< 0.5	10	66	23	3.00	< 10	< 1	0.40	30	0.68	500
108127	208	294	< 0.002	< 0.2	1.16	10	370	< 0.5	< 2	0.33	< 0.5	8	72	17	2.24	< 10	< 1	0.37	20	0.48	475
108128	208	294	< 0.002	< 0.2	1.46	25	330	< 0.5	< 2	0.39	< 0.5	10	61	18	2.65	< 10	< 1	0.29	20	0.63	450
108129	208	294	< 0.002	< 0.2	1.57	20	360	< 0.5	2	0.46	< 0.5	13	75	15	2.60	< 10	< 1	0.20	10	0.77	520
108130	208	294	< 0.002	< 0.2	0.56	< 5	310	< 0.5	4	0.08	< 0.5	1	63	9	0.58	< 10	< 1	0.39	30	0.19	110
108131	208	294	< 0.002	< 0.2	0.73	5	330	< 0.5	4	0.12	< 0.5	4	71	6	1.13	< 10	< 1	0.39	30	0.33	255
108132	208	294	0.045	0.6	0.49	< 5	340	< 0.5	2	0.09	< 0.5	2	107	5	0.68	< 10	< 1	0.35	30	0.16	130
108133	208	294	0.095	< 0.2	0.34	< 5	260	< 0.5	< 2	0.08	< 0.5	1	133	4	0.52	< 10	< 1	0.24	20	0.11	170
108134	208	294	0.008	< 0.2	1.08	< 5	310	< 0.5	< 2	0.17	0.5	5	140	12	1.79	< 10	< 1	0.44	20	0.67	340
108135	208	294	< 0.002	< 0.2	1.34	10	310	< 0.5	< 2	0.19	< 0.5	6	123	16	2.25	< 10	< 1	0.48	20	0.93	455
108136	208	294	0.004	0.6	1.01	10	280	< 0.5	< 2	0.21	< 0.5	6	154	15	1.93	< 10	< 1	0.45	20	0.64	425
108137	208	294	0.006	0.6	0.97	10	310	< 0.5	< 2	0.16	< 0.5	6	149	19	1.68	< 10	< 1	0.49	20	0.55	350
108138	208	294	< 0.002	< 0.2	1.25	10	320	< 0.5	2	0.19	< 0.5	7	109	17	2.06	< 10	< 1	0.59	20	0.80	495
108139	208	294	< 0.002	1.0	0.80	10	290	< 0.5	< 2	0.25	< 0.5	5	122	11	1.29	< 10	< 1	0.35	20	0.46	310
108140	208	294	0.006	1.6	0.36	5	130	< 0.5	2	0.07	< 0.5	4	161	16	0.89	< 10	< 1	0.13	< 10	0.22	220
108141	208	294	0.016	1.2	1.72	30	310	< 0.5	< 2	0.34	0.5	13	37	19	3.90	< 10	< 1	0.50	30	1.18	745
108142	208	294	0.002	< 0.2	0.59	< 5	150	< 0.5	< 2	0.12	< 0.5	3	186	6	1.26	< 10	< 1	0.20	10	0.45	620
108143	208	294	0.016	1.0	1.25	10	390	< 0.5	< 2	0.25	< 0.5	9	93	44	2.66	< 10	< 1	0.56	30	0.89	1040

CERTIFICATION: B. Caryl

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Page [illegible]ber : 3-B
Total [illegible]es : 3
Invoice Date: 5-SEP-90
Invoice No. : I-9021703
P.O. Number :

CERTIFICATE OF ANALYSIS A9021703

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
108104	208	294	< 1	0.02	11	780	10	< 5	6	21	0.03	< 10	< 10	24	< 10	84
108105	208	294	< 1	0.01	5	420	24	< 5	3	9	0.02	< 10	< 10	11	< 10	30
108106	208	294	< 1	0.01	14	510	6	< 5	7	20	0.06	< 10	< 10	18	< 10	98
108107	208	294	< 1	0.02	10	590	10	< 5	7	23	0.05	< 10	< 10	7	< 10	58
108108	208	294	< 1	< 0.01	3	80	34	< 5	1	33	0.01	< 10	< 10	< 1	< 10	18
108109	208	294	< 1	0.02	10	580	22	< 5	5	17	0.09	< 10	< 10	9	< 10	68
108110	208	294	< 1	0.01	10	530	28	< 5	5	14	0.08	< 10	< 10	7	< 10	68
108111	208	294	< 1	0.02	10	490	24	< 5	5	14	0.05	< 10	< 10	9	< 10	62
108112	208	294	< 1	0.01	11	540	22	< 5	4	12	0.05	< 10	< 10	3	< 10	54
108113	208	294	< 1	0.02	11	620	24	< 5	5	14	0.09	< 10	< 10	5	< 10	66
108114	208	294	< 1	0.01	14	680	18	< 5	6	17	0.04	< 10	< 10	10	< 10	80
108115	208	294	< 1	0.01	14	750	4	< 5	6	18	0.06	< 10	< 10	14	< 10	70
108116	208	294	< 1	0.02	13	730	16	< 5	7	20	0.07	< 10	< 10	19	< 10	72
108117	208	294	< 1	0.02	11	680	12	< 5	5	16	0.02	< 10	< 10	17	< 10	58
108118	208	294	< 1	0.02	13	940	16	< 5	7	17	0.01	< 10	< 10	27	< 10	94
108119	208	294	< 1	0.01	16	960	10	< 5	7	19	0.02	< 10	< 10	23	< 10	80
108120	208	294	< 1	0.02	13	780	10	< 5	6	16	0.03	< 10	< 10	18	< 10	68
108121	208	294	< 1	0.03	11	780	20	< 5	6	16	0.03	< 10	< 10	16	< 10	64
108122	208	294	< 1	0.01	14	820	16	< 5	8	17	0.01	< 10	< 10	20	< 10	68
108123	208	294	< 1	0.02	14	850	20	< 5	9	16	0.05	< 10	< 10	23	< 10	70
108124	208	294	< 1	0.02	14	1110	6	< 5	6	27	0.05	< 10	< 10	20	< 10	56
108125	208	294	< 1	0.02	12	880	10	< 5	4	18	0.01	< 10	< 10	15	< 10	52
108126	208	294	< 1	0.02	16	1000	8	< 5	7	17	0.01	< 10	< 10	28	< 10	80
108127	208	294	< 1	0.01	13	830	14	< 5	6	16	0.03	< 10	< 10	20	< 10	58
108128	208	294	< 1	0.02	18	790	14	< 5	8	17	0.06	< 10	< 10	28	< 10	64
108129	208	294	< 1	0.02	18	650	2	< 5	7	18	0.13	< 10	< 10	39	< 10	48
108130	208	294	< 1	0.01	2	270	10	< 5	1	11	< 0.01	10	< 10	2	< 10	22
108131	208	294	< 1	0.02	3	360	24	< 5	1	19	< 0.01	< 10	< 10	3	< 10	38
108132	208	294	< 1	0.02	2	220	8	< 5	1	10	< 0.01	< 10	< 10	1	< 10	20
108133	208	294	< 1	0.01	2	90	8	< 5	1	9	< 0.01	< 10	< 10	1	< 10	20
108134	208	294	< 1	0.01	7	440	18	< 5	3	17	0.02	< 10	< 10	8	< 10	58
108135	208	294	< 1	0.01	8	510	12	< 5	3	18	0.02	< 10	< 10	11	< 10	70
108136	208	294	< 1	0.01	8	690	22	< 5	3	26	0.02	< 10	< 10	7	< 10	48
108137	208	294	< 1	0.01	6	530	10	< 5	2	20	0.01	< 10	< 10	6	< 10	44
108138	208	294	< 1	0.01	8	570	22	< 5	4	20	0.04	< 10	< 10	10	< 10	58
108139	208	294	< 1	0.01	6	340	168	< 5	2	16	0.01	< 10	< 10	6	< 10	36
108140	208	294	< 1	< 0.01	6	230	258	< 5	< 1	8	< 0.01	< 10	< 10	2	< 10	22
108141	208	294	1	0.01	14	960	14	< 5	6	51	0.01	< 10	< 10	12	< 10	88
108142	208	294	< 1	0.01	6	380	52	< 5	2	17	0.01	< 10	< 10	5	< 10	32
108143	208	294	1	0.01	11	780	34	< 5	4	36	0.02	< 10	< 10	9	< 10	72

CERTIFICATION: B. Caryl

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

A9021730

Comments:

CERTIFICATE A9021730

ARBOR RESOURCES INC.

Project: DAWSON
P.O. # :

Samples submitted to our lab in Vancouver, BC.
This report was printed on 5-SEP-90.

SAMPLE PREPARATION

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION
208	94	Assay ring to approx 150 mesh
294	94	Crush and split (0-10 pounds)

* NOTE 1:

The 32 element ICP package is suitable for trace metals in soil and rock samples. Elements for which the nitric-aqua regia digestion is possibly incomplete are: Al, Ba, Be, Ca, Cr, Ga, K, La, Mg, Na, Sr, Ti, Tl, W.

ANALYTICAL PROCEDURES

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION	METHOD	DETECTION LIMIT	UPPER LIMIT
398	94	Au oz/T: 1/2 assay ton	FA-AAS	0.002	20.00
922	94	Ag ppm: 32 element, soil & rock	ICP-AES	0.2	200
921	94	Al %: 32 element, soil & rock	ICP-AES	0.01	15.00
923	94	As ppm: 32 element, soil & rock	ICP-AES	5	10000
924	94	Ba ppm: 32 element, soil & rock	ICP-AES	10	10000
925	94	Be ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
926	94	Bi ppm: 32 element, soil & rock	ICP-AES	2	10000
927	94	Ca %: 32 element, soil & rock	ICP-AES	0.01	15.00
928	94	Cd ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
929	94	Co ppm: 32 element, soil & rock	ICP-AES	1	10000
930	94	Cr ppm: 32 element, soil & rock	ICP-AES	1	10000
931	94	Cu ppm: 32 element, soil & rock	ICP-AES	1	10000
932	94	Fe %: 32 element, soil & rock	ICP-AES	0.01	15.00
933	94	Ga ppm: 32 element, soil & rock	ICP-AES	10	10000
951	94	Hg ppm: 32 element, soil & rock	ICP-AES	1	10000
934	94	K %: 32 element, soil & rock	ICP-AES	0.01	10.00
935	94	La ppm: 32 element, soil & rock	ICP-AES	10	10000
936	94	Mg %: 32 element, soil & rock	ICP-AES	0.01	15.00
937	94	Mn ppm: 32 element, soil & rock	ICP-AES	5	10000
938	94	Mo ppm: 32 element, soil & rock	ICP-AES	1	10000
939	94	Na %: 32 element, soil & rock	ICP-AES	0.01	5.00
940	94	Ni ppm: 32 element, soil & rock	ICP-AES	1	10000
941	94	P ppm: 32 element, soil & rock	ICP-AES	10	10000
942	94	Pb ppm: 32 element, soil & rock	ICP-AES	2	10000
943	94	Sb ppm: 32 element, soil & rock	ICP-AES	5	10000
958	94	Sc ppm: 32 elements, soil & rock	ICP-AES	1	10000
944	94	Sr ppm: 32 element, soil & rock	ICP-AES	1	10000
945	94	Ti %: 32 element, soil & rock	ICP-AES	0.01	5.00
946	94	Tl ppm: 32 element, soil & rock	ICP-AES	10	10000
947	94	U ppm: 32 element, soil & rock	ICP-AES	10	10000
948	94	V ppm: 32 element, soil & rock	ICP-AES	1	10000
949	94	W ppm: 32 element, soil & rock	ICP-AES	10	10000
950	94	Zn ppm: 32 element, soil & rock	ICP-AES	2	10000

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Page Number : 1-A
Total Pages : 3
Invoice Date: 5-SEP-90
Invoice No. : I-9021730
P.O. Number :

CERTIFICATE OF ANALYSIS A9021730

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
108144	208	294	0.002	< 0.2	0.18	5	70	< 0.5	< 2	0.03	< 0.5	1	176	6	0.58	< 10	< 1	0.05	< 10	0.13	295
108145	208	294	0.006	0.6	1.23	10	330	< 0.5	< 2	0.23	< 0.5	9	45	23	2.34	10	< 1	0.52	30	0.88	555
108146	208	294	0.006	< 0.2	0.10	< 5	50	< 0.5	< 2	0.01	< 0.5	1	186	1	0.39	< 10	< 1	0.03	< 10	0.05	115
108147	208	294	0.109	7.8	0.09	< 5	50	< 0.5	< 2	0.01	< 0.5	1	131	1	0.35	< 10	< 1	0.04	< 10	0.04	80
108148	208	294	0.064	0.8	0.89	5	330	< 0.5	< 2	0.16	< 0.5	8	67	12	2.26	10	< 1	0.42	20	0.61	480
108149	208	294	0.004	< 0.2	0.49	< 5	170	< 0.5	< 2	0.53	< 0.5	3	123	3	0.94	< 10	< 1	0.20	10	0.36	285
108150	208	294	0.012	0.4	0.99	5	340	< 0.5	< 2	0.22	< 0.5	6	103	21	1.74	10	< 1	0.49	20	0.64	485
108151	208	294	0.656	10.6	0.10	5	60	< 0.5	4	0.01	< 0.5	1	231	1	0.71	< 10	< 1	0.04	< 10	0.04	85
108152	208	294	0.437	37.0	0.10	15	60	< 0.5	8	0.01	< 0.5	< 1	200	1	0.88	< 10	< 1	0.03	< 10	0.05	80
108153	208	294	0.516	15.6	0.07	15	30	< 0.5	8	< 0.01	< 0.5	< 1	199	3	0.56	< 10	< 1	0.03	< 10	0.03	60
108154	208	294	0.010	0.6	0.34	30	120	< 0.5	< 2	0.05	< 0.5	2	196	3	0.82	< 10	< 1	0.12	< 10	0.17	315
108155	208	294	0.050	2.8	0.12	10	50	< 0.5	< 2	0.01	< 0.5	< 1	182	2	0.55	< 10	< 1	0.06	< 10	0.05	115
108156	208	294	0.326	4.4	0.22	5	110	< 0.5	< 2	0.01	< 0.5	1	134	1	0.64	< 10	< 1	0.12	< 10	0.11	270
108157	208	294	0.092	2.0	0.21	5	100	< 0.5	< 2	0.01	< 0.5	1	179	1	0.52	< 10	< 1	0.12	< 10	0.08	125
108158	208	294	0.002	< 0.2	0.13	< 5	50	< 0.5	< 2	0.01	< 0.5	1	178	1	0.39	< 10	< 1	0.05	< 10	0.05	70
108159	208	294	0.008	< 0.2	0.12	5	140	< 0.5	< 2	0.01	< 0.5	< 1	163	2	0.42	< 10	< 1	0.09	< 10	0.01	45
108160	208	294	0.004	0.4	0.05	< 5	40	< 0.5	< 2	< 0.01	< 0.5	< 1	194	< 1	0.29	< 10	< 1	< 0.01	< 10	< 0.01	45
108161	208	294	0.014	< 0.2	0.03	< 5	30	< 0.5	< 2	< 0.01	< 0.5	< 1	231	< 1	0.25	< 10	< 1	< 0.01	< 10	< 0.01	25
108162	208	294	0.048	< 0.2	0.07	< 5	90	< 0.5	< 2	0.01	< 0.5	< 1	195	< 1	0.30	< 10	< 1	0.05	< 10	< 0.01	35
108163	208	294	0.002	< 0.2	0.05	< 5	270	< 0.5	< 2	0.12	0.5	< 1	207	1	0.28	< 10	< 1	0.02	< 10	< 0.01	60
108164	208	294	0.226	1.0	0.08	< 5	100	< 0.5	< 2	< 0.01	< 0.5	< 1	241	< 1	0.31	< 10	< 1	0.03	< 10	< 0.01	45
108165	208	294	0.012	0.4	1.23	5	380	< 0.5	< 2	0.28	< 0.5	11	79	14	2.48	< 10	< 1	0.50	30	0.81	790
108166	208	294	0.002	< 0.2	0.30	< 5	190	< 0.5	< 2	0.05	< 0.5	1	203	2	0.67	< 10	< 1	0.09	< 10	0.14	215
108167	208	294	< 0.002	< 0.2	0.48	< 5	1030	< 0.5	< 2	0.05	< 0.5	1	59	2	0.56	< 10	< 1	0.32	20	0.06	120
108168	208	294	0.002	< 0.2	0.41	< 5	850	< 0.5	< 2	0.03	< 0.5	1	43	1	0.50	< 10	< 1	0.30	< 10	0.05	85
108169	208	294	0.002	< 0.2	0.53	< 5	790	0.5	< 2	0.03	< 0.5	1	46	1	0.52	< 10	< 1	0.39	20	0.06	95
108170	208	294	< 0.002	< 0.2	0.42	< 5	570	< 0.5	< 2	0.04	< 0.5	1	44	2	0.72	< 10	< 1	0.31	< 10	0.06	100
108171	208	294	0.024	0.4	0.36	5	1470	< 0.5	2	0.02	< 0.5	1	73	1	0.73	< 10	< 1	0.36	< 10	0.03	70
108172	208	294	0.006	0.4	0.49	5	470	< 0.5	< 2	0.04	< 0.5	1	35	2	0.57	< 10	< 1	0.34	20	0.05	145
108173	208	294	0.004	< 0.2	0.61	10	590	0.5	< 2	0.07	< 0.5	< 1	42	3	0.62	< 10	< 1	0.34	30	0.06	205
108174	208	294	0.004	0.8	0.66	10	560	< 0.5	< 2	0.05	< 0.5	1	45	5	0.70	< 10	< 1	0.37	20	0.05	145
108175	208	294	0.002	0.4	0.60	10	470	0.5	< 2	0.08	< 0.5	2	47	5	0.84	< 10	< 1	0.35	< 10	0.13	140
108176	208	294	< 0.002	< 0.2	0.47	< 5	530	< 0.5	< 2	0.06	< 0.5	< 1	47	3	0.50	< 10	< 1	0.38	< 10	0.02	85
108177	208	294	0.002	< 0.2	0.45	< 5	450	< 0.5	< 2	0.06	< 0.5	< 1	48	3	0.47	< 10	< 1	0.33	20	0.02	85
108178	208	294	< 0.002	< 0.2	0.50	5	550	< 0.5	< 2	0.05	< 0.5	< 1	46	3	0.49	< 10	< 1	0.35	< 10	0.02	75
108179	208	294	0.002	< 0.2	0.40	5	410	< 0.5	< 2	0.05	< 0.5	1	64	2	0.46	< 10	< 1	0.32	< 10	0.02	55
108180	208	294	0.004	< 0.2	0.52	< 5	440	0.5	< 2	0.11	< 0.5	1	66	3	0.60	< 10	< 1	0.31	< 10	0.07	90
108181	208	294	0.004	< 0.2	0.39	5	360	< 0.5	2	0.02	< 0.5	< 1	97	2	0.49	< 10	< 1	0.36	< 10	0.02	85
108182	208	294	0.004	< 0.2	0.36	5	330	< 0.5	< 2	0.02	< 0.5	1	85	2	0.44	< 10	< 1	0.35	20	0.02	95
108183	208	294	< 0.002	< 0.2	0.35	< 5	350	< 0.5	< 2	0.03	0.5	1	85	3	0.46	< 10	< 1	0.32	< 10	0.02	105

CERTIFICATION: B. Campbell

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

[redacted]: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Invoice Date: 5-SEP-90
Invoice No. : I-9021730
P.O. Number :

CERTIFICATE OF ANALYSIS A9021730

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
108144	208	294	< 1	< 0.01	4	70	18	< 5	< 1	4	< 0.01	< 10	< 10	2	< 10	14
108145	208	294	< 1	0.01	11	660	10	< 5	3	22	0.02	< 10	< 10	8	< 10	62
108146	208	294	< 1	< 0.01	4	40	2	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	18
108147	208	294	< 1	< 0.01	3	10	6	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	26
108148	208	294	< 1	0.01	10	410	10	< 5	3	27	0.01	< 10	< 10	5	< 10	56
108149	208	294	< 1	0.01	5	240	4	< 5	1	31	< 0.01	< 10	< 10	3	< 10	24
108150	208	294	< 1	0.01	8	460	2	< 5	3	22	0.01	< 10	< 10	5	< 10	68
108151	208	294	1	< 0.01	3	20	1090	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	46
108152	208	294	1	< 0.01	2	40	1590	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	46
108153	208	294	1	< 0.01	2	20	1615	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	74
108154	208	294	1	0.01	4	150	90	< 5	< 1	4	< 0.01	< 10	< 10	1	< 10	22
108155	208	294	1	< 0.01	4	20	248	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	30
108156	208	294	< 1	< 0.01	3	30	28	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	24
108157	208	294	1	0.01	3	40	118	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	22
108158	208	294	< 1	0.01	2	40	10	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	10
108159	208	294	< 1	0.01	2	20	148	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	20
108160	208	294	< 1	0.01	2	10	20	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	6
108161	208	294	< 1	< 0.01	2	< 10	2	< 5	< 1	< 1	< 0.01	< 10	< 10	< 1	< 10	2
108162	208	294	< 1	< 0.01	1	10	12	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	12
108163	208	294	< 1	< 0.01	2	10	10	< 5	< 1	5	< 0.01	< 10	< 10	< 1	< 10	48
108164	208	294	< 1	< 0.01	3	10	14	< 5	< 1	< 1	< 0.01	< 10	< 10	< 1	< 10	6
108165	208	294	< 1	0.01	12	680	6	< 5	3	46	0.02	< 10	< 10	9	< 10	62
108166	208	294	< 1	< 0.01	3	150	8	< 5	1	6	< 0.01	< 10	10	2	< 10	16
108167	208	294	< 1	0.02	1	60	14	< 5	2	16	< 0.01	< 10	< 10	1	< 10	20
108168	208	294	< 1	0.02	1	50	12	< 5	2	11	< 0.01	< 10	< 10	< 1	< 10	18
108169	208	294	1	0.02	1	60	12	< 5	3	7	< 0.01	< 10	< 10	< 1	< 10	24
108170	208	294	< 1	0.02	1	50	14	< 5	3	7	< 0.01	< 10	< 10	1	< 10	38
108171	208	294	< 1	0.01	1	40	30	< 5	1	10	< 0.01	< 10	< 10	< 1	< 10	66
108172	208	294	< 1	0.01	< 1	70	22	< 5	1	6	< 0.01	< 10	< 10	< 1	< 10	42
108173	208	294	< 1	0.01	2	70	26	< 5	2	9	< 0.01	< 10	< 10	1	< 10	52
108174	208	294	< 1	0.02	1	80	20	< 5	3	9	< 0.01	< 10	< 10	1	< 10	48
108175	208	294	< 1	0.02	2	130	12	< 5	3	9	< 0.01	< 10	< 10	5	< 10	44
108176	208	294	< 1	0.02	< 1	50	16	< 5	3	11	< 0.01	< 10	< 10	< 1	< 10	34
108177	208	294	< 1	0.02	< 1	60	22	< 5	2	8	< 0.01	< 10	< 10	< 1	< 10	36
108178	208	294	< 1	0.02	< 1	50	18	< 5	2	10	< 0.01	< 10	< 10	< 1	< 10	40
108179	208	294	< 1	0.02	< 1	60	16	< 5	2	9	< 0.01	< 10	< 10	< 1	< 10	36
108180	208	294	< 1	0.02	3	80	16	< 5	2	16	< 0.01	< 10	< 10	3	< 10	44
108181	208	294	< 1	0.02	1	60	18	< 5	1	4	< 0.01	< 10	< 10	1	< 10	26
108182	208	294	< 1	0.03	2	60	44	< 5	1	3	< 0.01	< 10	< 10	< 1	< 10	26
108183	208	294	< 1	0.02	3	60	22	< 5	1	4	< 0.01	< 10	< 10	< 1	< 10	36

CERTIFICATION: B. Caplan

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

[redacted]: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Page [redacted]er : 2-A
Total Pages : 3
Invoice Date: 5-SEP-90
Invoice No. : I-9021730
P.O. Number :

CERTIFICATE OF ANALYSIS A9021730

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
108184	208	294	< 0.002	< 0.2	0.38	5	340	< 0.5	< 2	0.02	< 0.5	< 1	122	3	0.49	< 10	< 1	0.34	30	0.02	125
108185	208	294	< 0.002	< 0.2	0.47	10	530	< 0.5	2	0.03	< 0.5	1	157	3	0.64	< 10	< 1	0.37	40	0.03	155
108186	208	294	< 0.002	< 0.2	0.45	5	600	< 0.5	< 2	0.03	< 0.5	1	176	3	0.74	< 10	< 1	0.39	30	0.03	95
108187	208	294	0.024	< 0.2	0.43	10	990	< 0.5	< 2	0.04	0.5	1	117	2	0.76	< 10	< 1	0.42	30	0.03	125
108188	208	294	0.002	< 0.2	0.45	< 5	610	< 0.5	< 2	0.03	< 0.5	1	103	3	0.44	< 10	< 1	0.35	30	0.03	80
108189	208	294	0.038	< 0.2	0.38	< 5	520	< 0.5	< 2	0.04	< 0.5	< 1	123	3	0.47	< 10	< 1	0.28	30	0.02	100
108190	208	294	8.290	54.8	0.37	15	460	< 0.5	< 2	0.02	< 0.5	1	145	3	0.60	< 10	1	0.24	30	0.02	110
108191	208	294	< 0.002	< 0.2	0.36	10	580	< 0.5	< 2	0.02	< 0.5	2	102	2	0.87	< 10	< 1	0.29	30	0.03	135
108192	208	294	0.008	< 0.2	0.43	10	480	< 0.5	< 2	0.03	< 0.5	1	154	2	0.92	< 10	< 1	0.34	30	0.05	110
108193	208	294	0.002	< 0.2	0.37	10	310	< 0.5	< 2	0.02	< 0.5	1	177	1	0.79	< 10	< 1	0.27	40	0.03	105
108194	208	294	< 0.002	< 0.2	0.50	5	440	< 0.5	< 2	0.03	< 0.5	1	139	2	0.65	< 10	< 1	0.36	40	0.04	145
108195	208	294	0.178	< 0.2	0.48	5	510	< 0.5	< 2	0.04	< 0.5	1	134	1	0.59	< 10	< 1	0.36	30	0.03	120
108196	208	294	0.002	< 0.2	0.43	< 5	550	< 0.5	< 2	0.06	< 0.5	1	119	2	0.52	< 10	< 1	0.37	30	0.03	105
108197	208	294	< 0.002	< 0.2	0.49	< 5	440	< 0.5	< 2	0.03	< 0.5	1	127	3	0.51	< 10	< 1	0.36	40	0.04	65
108198	208	294	0.004	< 0.2	0.47	5	530	< 0.5	< 2	0.03	< 0.5	1	98	2	0.63	< 10	< 1	0.47	40	0.02	165
108199	208	294	< 0.002	< 0.2	0.46	10	590	0.5	< 2	0.04	< 0.5	< 1	100	1	0.55	< 10	< 1	0.31	30	0.02	85
108200	208	294	< 0.002	< 0.2	0.45	< 5	750	< 0.5	< 2	0.10	< 0.5	< 1	92	1	0.51	< 10	< 1	0.28	30	0.02	100
108213	208	294	< 0.002	< 0.2	1.63	5	270	< 0.5	< 2	0.21	0.5	13	168	28	2.68	< 10	< 1	0.20	10	1.28	580
108214	208	294	< 0.002	< 0.2	0.29	5	180	< 0.5	< 2	0.04	< 0.5	4	240	8	0.96	< 10	< 1	0.03	< 10	0.13	820
108215	208	294	< 0.002	< 0.2	1.26	< 5	170	< 0.5	< 2	0.18	0.5	8	217	21	2.60	< 10	< 1	0.15	< 10	1.05	435
108218	208	294	< 0.002	< 0.2	1.82	20	260	< 0.5	< 2	0.20	0.5	11	159	41	3.40	< 10	< 1	0.29	10	1.50	595
108219	208	294	< 0.002	0.6	2.11	15	330	< 0.5	< 2	0.24	1.0	13	152	59	4.28	< 10	< 1	0.34	10	1.68	685
108220	208	294	< 0.002	< 0.2	0.41	< 5	100	< 0.5	< 2	0.04	< 0.5	4	351	10	1.05	< 10	< 1	0.05	< 10	0.28	355
108221	208	294	< 0.002	< 0.2	1.84	5	280	< 0.5	< 2	0.19	0.5	14	198	34	2.98	< 10	< 1	0.25	10	1.59	930
108222	208	294	< 0.002	< 0.2	2.50	10	360	< 0.5	< 2	0.27	1.0	22	187	42	3.61	< 10	< 1	0.36	10	2.32	1305
108223	208	294	< 0.002	< 0.2	2.09	5	230	< 0.5	< 2	0.24	0.5	13	146	27	3.12	< 10	< 1	0.29	10	2.02	735
108224	208	294	< 0.002	< 0.2	1.88	30	300	< 0.5	< 2	0.23	< 0.5	13	216	32	2.70	< 10	< 1	0.32	< 10	1.69	785
108225	208	294	< 0.002	< 0.2	0.44	5	130	< 0.5	< 2	0.08	< 0.5	5	282	7	0.93	< 10	< 1	0.07	< 10	0.32	415
108226	208	294	< 0.002	< 0.2	1.30	20	370	< 0.5	< 2	0.24	< 0.5	10	142	15	2.51	< 10	< 1	0.42	20	0.87	450
108227	208	294	< 0.002	< 0.2	1.13	15	350	< 0.5	< 2	0.23	< 0.5	8	131	16	2.12	< 10	< 1	0.37	20	0.76	380
108228	208	294	< 0.002	< 0.2	1.16	15	420	< 0.5	< 2	0.25	< 0.5	7	168	11	2.16	< 10	< 1	0.34	20	0.73	360
108229	208	294	< 0.002	< 0.2	1.43	20	340	< 0.5	< 2	0.31	< 0.5	10	124	19	2.70	< 10	< 1	0.60	20	1.03	440
108230	208	294	< 0.002	< 0.2	1.41	15	370	< 0.5	< 2	0.27	< 0.5	9	119	17	2.50	< 10	< 1	0.52	30	0.97	425
108231	208	294	< 0.002	< 0.2	1.63	25	380	< 0.5	< 2	0.30	< 0.5	9	119	15	2.91	< 10	< 1	0.51	30	1.10	530
108232	208	294	< 0.002	< 0.2	1.28	20	410	< 0.5	< 2	0.27	< 0.5	8	152	17	2.36	< 10	< 1	0.43	30	0.64	450
108233	208	294	< 0.002	< 0.2	0.92	10	380	< 0.5	< 2	0.19	< 0.5	5	92	9	1.73	< 10	< 1	0.36	30	0.43	265
108234	208	294	< 0.002	< 0.2	0.74	10	490	< 0.5	< 2	0.12	0.5	3	144	8	1.28	< 10	< 1	0.38	30	0.23	180
108235	208	294	< 0.002	< 0.2	0.96	5	380	< 0.5	< 2	0.16	< 0.5	5	150	10	1.70	< 10	< 1	0.38	30	0.43	290
108236	208	294	< 0.002	< 0.2	1.58	15	520	< 0.5	< 2	0.26	< 0.5	8	128	19	2.46	< 10	< 1	0.65	30	0.79	480
108237	208	294	< 0.002	< 0.2	0.69	5	290	< 0.5	< 2	0.10	0.5	3	124	6	0.96	< 10	< 1	0.35	30	0.28	230

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

[redacted]: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Page [redacted]er : 2-B
Total Pages : 3
Invoice Date: 5-SEP-90
Invoice No. : I-9021730
P.O. Number :

CERTIFICATE OF ANALYSIS A9021730

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
108184	208	294	< 1	0.03	2	50	28	< 5	1	3	< 0.01	< 10	< 10	< 1	< 10	38
108185	208	294	< 1	0.02	3	80	38	< 5	2	6	< 0.01	< 10	< 10	< 1	< 10	48
108186	208	294	< 1	0.02	2	70	26	< 5	2	6	< 0.01	< 10	< 10	< 1	< 10	40
108187	208	294	< 1	0.01	2	80	20	< 5	2	10	< 0.01	< 10	< 10	< 1	< 10	44
108188	208	294	< 1	0.02	2	60	28	< 5	2	7	< 0.01	< 10	< 10	< 1	< 10	64
108189	208	294	< 1	0.02	2	50	22	< 5	1	7	< 0.01	< 10	< 10	< 1	< 10	34
108190	208	294	< 1	0.03	4	60	20	< 5	1	4	< 0.01	< 10	< 10	< 1	< 10	46
108191	208	294	< 1	0.02	2	90	16	< 5	1	5	< 0.01	< 10	< 10	< 1	< 10	36
108192	208	294	< 1	0.02	2	100	20	< 5	1	5	< 0.01	< 10	< 10	< 1	< 10	32
108193	208	294	1	0.02	2	90	30	< 5	1	4	< 0.01	< 10	< 10	< 1	< 10	24
108194	208	294	< 1	0.02	3	90	26	< 5	2	4	< 0.01	< 10	< 10	< 1	< 10	32
108195	208	294	< 1	0.02	2	80	22	< 5	2	7	< 0.01	< 10	< 10	< 1	< 10	30
108196	208	294	< 1	0.02	2	80	16	< 5	2	9	< 0.01	< 10	< 10	< 1	< 10	24
108197	208	294	< 1	0.02	2	80	16	< 5	2	4	< 0.01	< 10	< 10	< 1	< 10	32
108198	208	294	< 1	0.02	1	100	28	< 5	2	5	< 0.01	< 10	< 10	< 1	< 10	32
108199	208	294	< 1	0.02	1	90	20	< 5	2	7	< 0.01	< 10	< 10	< 1	< 10	26
108200	208	294	< 1	0.02	2	80	20	< 5	2	14	< 0.01	< 10	< 10	< 1	< 10	28
108213	208	294	2	0.01	29	760	18	< 5	2	12	< 0.01	< 10	< 10	14	< 10	90
108214	208	294	1	< 0.01	9	90	14	< 5	1	6	< 0.01	< 10	< 10	< 1	< 10	22
108215	208	294	2	0.01	15	520	50	< 5	2	16	< 0.01	< 10	< 10	8	< 10	92
108218	208	294	2	0.01	21	790	24	< 5	2	27	< 0.01	< 10	< 10	20	< 10	158
108219	208	294	2	0.01	21	880	20	5	3	56	< 0.01	< 10	< 10	27	< 10	142
108220	208	294	< 1	< 0.01	9	110	6	< 5	< 1	7	< 0.01	< 10	< 10	< 1	< 10	26
108221	208	294	1	0.01	22	640	54	< 5	3	28	0.01	< 10	< 10	19	< 10	124
108222	208	294	1	0.01	31	870	10	5	4	19	0.01	< 10	< 10	29	< 10	146
108223	208	294	< 1	0.01	20	690	24	< 5	3	17	< 0.01	< 10	< 10	23	< 10	94
108224	208	294	< 1	0.01	21	600	20	10	3	16	0.01	< 10	< 10	22	< 10	100
108225	208	294	< 1	< 0.01	13	200	10	< 5	1	6	< 0.01	< 10	< 10	1	< 10	22
108226	208	294	< 1	0.04	18	630	10	< 5	7	19	0.06	< 10	< 10	16	< 10	68
108227	208	294	< 1	0.02	15	590	14	< 5	6	17	0.03	< 10	< 10	10	< 10	58
108228	208	294	< 1	0.02	12	630	14	< 5	6	17	0.02	< 10	< 10	13	< 10	54
108229	208	294	1	0.02	14	730	14	< 5	8	22	0.05	< 10	< 10	15	< 10	72
108230	208	294	1	0.02	11	630	22	< 5	7	21	0.03	< 10	< 10	19	< 10	66
108231	208	294	< 1	0.02	13	680	16	< 5	7	27	0.03	< 10	< 10	22	< 10	82
108232	208	294	< 1	0.01	13	680	18	< 5	5	21	< 0.01	< 10	< 10	12	< 10	62
108233	208	294	< 1	0.01	7	490	16	< 5	3	17	< 0.01	< 10	< 10	6	< 10	50
108234	208	294	< 1	0.03	6	360	18	< 5	2	10	< 0.01	< 10	< 10	4	< 10	32
108235	208	294	< 1	0.02	6	450	26	< 5	3	14	0.01	< 10	< 10	7	< 10	46
108236	208	294	< 1	0.02	11	700	20	< 5	5	21	0.02	< 10	< 10	13	< 10	82
108237	208	294	< 1	0.01	3	280	50	< 5	2	16	< 0.01	< 10	< 10	3	< 10	36

CERTIFICATION: B. Caplette

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

[redacted]: ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Invoice Date: 5-SEP-90
Invoice No. : I-9021730
P.O. Number :

CERTIFICATE OF ANALYSIS A9021730

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
108238	208	294	< 0.002	< 0.2	1.13	10	440	< 0.5	2	0.23	< 0.5	7	67	9	1.79	< 10	< 1	0.49	30	0.65	370
108239	208	294	< 0.002	< 0.2	1.13	35	410	< 0.5	< 2	0.27	< 0.5	8	77	14	1.92	< 10	< 1	0.48	30	0.73	410
108240	208	294	< 0.002	< 0.2	1.02	15	400	< 0.5	2	0.22	< 0.5	7	59	14	1.63	< 10	< 1	0.50	30	0.63	355
108241	208	294	< 0.002	< 0.2	1.12	25	330	< 0.5	2	0.19	< 0.5	6	73	13	1.81	< 10	< 1	0.43	30	0.70	465
108242	208	294	< 0.002	< 0.2	1.37	15	430	< 0.5	2	0.25	< 0.5	8	78	9	2.26	< 10	< 1	0.60	30	1.03	505
108243	208	294	< 0.002	< 0.2	0.92	20	350	< 0.5	2	0.20	< 0.5	5	110	4	1.56	< 10	< 1	0.50	20	0.72	460
108244	208	294	< 0.002	< 0.2	1.12	30	380	< 0.5	2	0.24	< 0.5	7	66	12	1.92	< 10	< 1	0.61	30	0.82	450
108245	208	294	< 0.002	< 0.2	1.26	30	330	< 0.5	2	0.23	< 0.5	7	98	9	2.01	< 10	< 1	0.54	20	1.05	495
108246	208	294	< 0.002	< 0.2	1.21	125	300	< 0.5	2	0.26	< 0.5	7	86	10	2.01	< 10	< 1	0.53	20	1.02	480
108247	208	294	< 0.002	< 0.2	1.09	300	320	< 0.5	2	0.28	< 0.5	8	52	7	1.83	< 10	< 1	0.52	30	0.85	425
108248	208	294	< 0.002	< 0.2	1.24	85	280	< 0.5	< 2	0.33	< 0.5	7	73	13	2.19	< 10	< 1	0.45	20	1.04	585
108249	208	294	< 0.002	< 0.2	1.10	15	370	< 0.5	< 2	0.30	< 0.5	8	93	13	2.02	< 10	< 1	0.52	20	0.84	535
108250	208	294	< 0.002	< 0.2	1.26	5	420	< 0.5	< 2	0.32	< 0.5	9	58	19	2.15	< 10	< 1	0.58	30	0.90	470
#1 NO TAG	208	294	< 0.002	< 0.2	0.14	5	300	< 0.5	< 2	0.05	< 0.5	< 1	63	1	0.60	< 10	< 1	0.09	10	0.03	40

CERTIFICATION: B. Caplette

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.

2321 BELLEVUE AVE.
WEST VANCOUVER, BC
V7V 1C9

Project : DAWSON
Comments:

Invoice Date: 5-SEP-90
Invoice No. : I-9021730
P.O. Number :

CERTIFICATE OF ANALYSIS A9021730

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
108238	208	294	< 1	0.02	8	600	6	< 5	6	18	0.01	< 10	< 10	12	< 10	88
108239	208	294	< 1	0.02	8	720	14	< 5	6	20	0.02	10	< 10	13	< 10	62
108240	208	294	< 1	0.02	6	580	6	< 5	5	16	0.01	10	< 10	10	< 10	52
108241	208	294	< 1	0.02	5	460	12	< 5	5	16	0.01	< 10	< 10	9	< 10	58
108242	208	294	< 1	0.02	6	630	20	< 5	7	19	0.04	< 10	< 10	14	< 10	80
108243	208	294	< 1	0.01	5	470	26	< 5	5	14	0.03	< 10	< 10	10	< 10	52
108244	208	294	< 1	0.02	5	610	12	< 5	6	17	0.04	< 10	< 10	12	< 10	60
108245	208	294	< 1	0.02	8	590	22	< 5	6	16	0.04	< 10	< 10	14	< 10	68
108246	208	294	< 1	0.02	8	650	14	< 5	6	17	0.05	< 10	< 10	15	< 10	64
108247	208	294	< 1	0.01	7	650	10	< 5	5	18	0.05	< 10	< 10	13	< 10	56
108248	208	294	< 1	0.02	9	710	8	< 5	6	21	0.07	< 10	< 10	17	< 10	68
108249	208	294	< 1	0.02	11	740	16	< 5	6	19	0.06	< 10	< 10	18	< 10	58
108250	208	294	< 1	0.02	11	740	12	< 5	5	18	0.08	< 10	< 10	18	< 10	64
#1 NO TAG	208	294	1	0.02	1	240	42	< 5	< 1	30	< 0.01	< 10	< 10	< 1	< 10	4

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.

1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

A9022461

Comments:

CERTIFICATE A9022461

ARBOR RESOURCES INC.

Project: AOR/DAW
P.O. # :

Samples submitted to our lab in Vancouver, BC.
This report was printed on 30-APR-91.

SAMPLE PREPARATION

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION
208	77	Assay ring to approx 150 mesh
294	77	Crush and split (0-10 pounds)
238	77	NITRIC-AQUA REGIA DIGESTION

* NOTE 1:

The 32 element ICP package is suitable for trace metals in soil and rock samples. Elements for which the nitric-aqua regia digestion is possibly incomplete are: Al, Ba, Be, Ca, Cr, Ga, K, La, Mg, Na, Sr, Ti, Tl, W.

ANALYTICAL PROCEDURES

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION	METHOD	DETECTION LIMIT	UPPER LIMIT
398	77	Au oz/T: 1/2 assay ton	FA-AAS	0.002	20.00
922	77	Ag ppm: 32 element, soil & rock	ICP-AES	0.2	200
921	77	Al %: 32 element, soil & rock	ICP-AES	0.01	15.00
923	77	As ppm: 32 element, soil & rock	ICP-AES	5	10000
924	77	Ba ppm: 32 element, soil & rock	ICP-AES	10	10000
925	77	Be ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
926	77	Bi ppm: 32 element, soil & rock	ICP-AES	2	10000
927	77	Ca %: 32 element, soil & rock	ICP-AES	0.01	15.00
928	77	Cd ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
929	77	Co ppm: 32 element, soil & rock	ICP-AES	1	10000
930	77	Cr ppm: 32 element, soil & rock	ICP-AES	1	10000
931	77	Cu ppm: 32 element, soil & rock	ICP-AES	1	10000
932	77	Fe %: 32 element, soil & rock	ICP-AES	0.01	15.00
933	77	Ga ppm: 32 element, soil & rock	ICP-AES	10	10000
951	77	Hg ppm: 32 element, soil & rock	ICP-AES	1	10000
934	77	K %: 32 element, soil & rock	ICP-AES	0.01	10.00
935	77	La ppm: 32 element, soil & rock	ICP-AES	10	10000
936	77	Mg %: 32 element, soil & rock	ICP-AES	0.01	15.00
937	77	Mn ppm: 32 element, soil & rock	ICP-AES	5	10000
938	77	Mo ppm: 32 element, soil & rock	ICP-AES	1	10000
939	77	Na %: 32 element, soil & rock	ICP-AES	0.01	5.00
940	77	Ni ppm: 32 element, soil & rock	ICP-AES	1	10000
941	77	P ppm: 32 element, soil & rock	ICP-AES	10	10000
942	77	Pb ppm: 32 element, soil & rock	ICP-AES	2	10000
943	77	Sb ppm: 32 element, soil & rock	ICP-AES	5	10000
958	77	Sc ppm: 32 elements, soil & rock	ICP-AES	1	10000
944	77	Sr ppm: 32 element, soil & rock	ICP-AES	1	10000
945	77	Ti %: 32 element, soil & rock	ICP-AES	0.01	5.00
946	77	Tl ppm: 32 element, soil & rock	ICP-AES	10	10000
947	77	U ppm: 32 element, soil & rock	ICP-AES	10	10000
948	77	V ppm: 32 element, soil & rock	ICP-AES	1	10000
949	77	W ppm: 32 element, soil & rock	ICP-AES	10	10000
950	77	Zn ppm: 32 element, soil & rock	ICP-AES	2	10000

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC. ##
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR/DAW
Comments:

Page N[illegible]r :1-A
Total Pa[illegible] :2
Certificate Date: 17-SEP-90
Invoice No. :19022461
P.O. Number :

CERTIFICATE OF ANALYSIS A9022461

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
39081	208	294	< 0.002	0.8	0.36	10	240	0.5	< 2	0.05	< 0.5	< 1	68	262	0.76	10	< 1	0.37	40	0.04	80
39082	208	294	< 0.002	1.2	0.28	10	130	< 0.5	< 2	0.04	< 0.5	< 1	42	255	0.77	< 10	< 1	0.26	30	0.04	70
39083	208	294	< 0.002	1.0	0.30	10	210	< 0.5	2	0.03	< 0.5	< 1	69	174	0.66	< 10	< 1	0.33	30	0.03	75
39084	208	294	0.091	0.6	0.19	5	230	< 0.5	< 2	0.02	< 0.5	< 1	169	230	0.47	< 10	< 1	0.17	10	0.01	95
39085	208	294	< 0.002	0.8	0.21	5	170	< 0.5	2	0.03	< 0.5	< 1	53	90	0.42	< 10	< 1	0.23	30	0.02	55
39086	208	294	< 0.002	0.4	0.47	5	440	< 0.5	< 2	0.08	< 0.5	< 1	86	106	0.75	< 10	< 1	0.27	40	0.06	65
39087	208	294	< 0.002	1.0	0.45	5	550	< 0.5	2	0.04	< 0.5	< 1	72	46	0.57	10	< 1	0.29	40	0.08	40
39088	208	294	< 0.002	0.2	0.27	15	1860	< 0.5	< 2	0.09	< 0.5	< 1	30	46	0.88	< 10	< 1	0.18	20	0.03	35
39089	208	294	< 0.002	0.8	0.26	< 5	240	< 0.5	< 2	0.03	< 0.5	< 1	79	12	0.30	< 10	< 1	0.25	30	0.02	25
39090	208	294	< 0.002	1.2	0.18	15	160	< 0.5	< 2	0.04	< 0.5	< 1	90	50	0.82	< 10	< 1	0.14	40	0.02	285
39091	208	294	< 0.002	1.0	0.34	< 5	190	< 0.5	< 2	0.04	< 0.5	< 1	65	44	0.36	10	< 1	0.29	30	0.04	35
39092	208	294	< 0.002	0.4	0.19	15	90	< 0.5	< 2	0.02	< 0.5	< 1	142	30	0.52	< 10	< 1	0.17	10	0.01	30
39093	208	294	< 0.002	0.8	0.21	10	100	< 0.5	2	0.02	< 0.5	< 1	64	33	0.66	< 10	< 1	0.17	30	0.02	40
39094	208	294	0.002	0.6	0.15	5	90	< 0.5	< 2	0.01	< 0.5	< 1	138	24	0.46	< 10	< 1	0.13	10	0.01	25
39095	208	294	0.093	2.2	0.25	5	150	< 0.5	< 2	0.02	< 0.5	< 1	77	26	0.56	< 10	< 1	0.23	30	0.02	35
39096	208	294	< 0.002	1.2	0.26	< 5	150	< 0.5	< 2	0.03	< 0.5	< 1	74	16	0.38	< 10	< 1	0.23	40	0.02	20
39097	208	294	< 0.002	0.6	0.42	< 5	490	< 0.5	< 2	0.06	< 0.5	< 1	77	11	0.33	10	< 1	0.33	30	0.03	25
39098	208	294	< 0.002	< 0.2	0.39	< 5	340	< 0.5	< 2	0.15	< 0.5	< 1	90	8	0.31	< 10	< 1	0.22	20	0.02	30
39099	208	294	< 0.002	0.4	0.35	5	270	< 0.5	< 2	0.08	< 0.5	< 1	56	9	0.40	< 10	< 1	0.23	20	0.02	30
39100	208	294	0.003	1.2	0.44	< 5	370	< 0.5	< 2	0.03	< 0.5	< 1	97	9	0.28	10	< 1	0.36	50	0.02	20
39144	208	294	< 0.002	0.8	0.30	5	150	< 0.5	2	0.04	< 0.5	< 1	46	11	0.66	< 10	< 1	0.22	20	0.05	50
39145	208	294	< 0.002	0.6	0.39	5	230	< 0.5	2	0.05	< 0.5	< 1	70	12	0.50	< 10	< 1	0.29	20	0.05	35
39146	208	294	< 0.002	0.2	0.29	10	220	< 0.5	< 2	0.07	< 0.5	1	92	43	0.41	< 10	< 1	0.20	30	0.06	70
39147	208	294	0.004	0.6	0.53	5	580	< 0.5	2	0.05	< 0.5	1	84	13	0.45	< 10	< 1	0.35	40	0.11	135
39148	208	294	< 0.002	0.6	0.24	< 5	330	< 0.5	2	0.03	< 0.5	1	130	12	0.28	< 10	< 1	0.13	10	0.03	70
39149	208	294	< 0.002	1.2	0.49	5	500	< 0.5	2	0.04	< 0.5	< 1	91	10	0.45	10	< 1	0.38	40	0.06	70
39150	208	294	0.002	1.0	0.17	10	90	< 0.5	< 2	0.01	< 0.5	< 1	128	12	0.63	< 10	< 1	0.15	20	0.01	70
39151	208	294	0.089	1.0	0.07	< 5	140	< 0.5	< 2	< 0.01	< 0.5	< 1	193	11	0.26	< 10	< 1	0.03	< 10	< 0.01	20
39152	208	294	0.004	2.0	0.26	5	150	< 0.5	< 2	0.04	< 0.5	< 1	101	9	0.51	< 10	< 1	0.16	40	0.02	30
39153	208	294	0.006	1.2	0.41	5	270	< 0.5	< 2	0.04	< 0.5	< 1	85	22	0.35	10	< 1	0.34	40	0.04	20
39154	208	294	0.002	1.2	0.30	5	160	< 0.5	< 2	0.06	< 0.5	< 1	65	12	0.23	10	< 1	0.22	50	0.03	15
39155	208	294	0.082	18.4	0.54	20	390	< 0.5	28	0.08	< 0.5	2	108	75	1.47	< 10	< 1	0.34	30	0.05	65
39156	208	294	< 0.002	1.6	0.32	5	230	< 0.5	2	0.03	< 0.5	1	67	5	0.39	10	< 1	0.25	50	0.02	15
39157	208	294	< 0.002	1.0	0.28	10	280	< 0.5	< 2	0.03	< 0.5	< 1	82	9	0.51	< 10	< 1	0.20	20	0.01	15
39158	208	294	< 0.002	1.0	0.33	< 5	190	< 0.5	< 2	0.02	< 0.5	< 1	85	6	0.41	< 10	< 1	0.27	30	0.02	15
39159	208	294	< 0.002	0.8	0.32	< 5	200	< 0.5	< 2	0.04	< 0.5	< 1	61	7	0.40	< 10	< 1	0.25	30	0.04	20
39160	208	294	< 0.002	1.0	0.40	< 5	260	< 0.5	2	0.04	< 0.5	< 1	92	8	0.48	< 10	< 1	0.33	20	0.05	20
39161	208	294	< 0.002	0.8	0.24	5	120	< 0.5	< 2	0.03	< 0.5	< 1	65	6	0.49	< 10	< 1	0.22	20	0.04	20
39162	208	294	< 0.002	0.8	0.26	5	170	< 0.5	< 2	0.03	< 0.5	< 1	102	9	0.78	< 10	< 1	0.23	20	0.04	40
39163	208	294	< 0.002	0.4	1.01	15	520	< 0.5	2	0.16	1.5	3	78	8	1.70	< 10	< 1	0.39	20	0.44	295

CERTIFICATION: B. Campbell

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC. ##
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR/DAW
Comments:

Certificate Date: 17-SEP-90
Invoice No. :19022461
P.O. Number :

CERTIFICATE OF ANALYSIS A9022461

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
39081	208	294	< 1	0.02	1	70	20	< 5	1	5	< 0.01	< 10	< 10	1	< 10	30
39082	208	294	< 1	0.01	< 1	80	26	< 5	1	5	< 0.01	< 10	< 10	1	< 10	36
39083	208	294	< 1	0.03	< 1	90	24	< 5	1	4	< 0.01	< 10	< 10	1	< 10	22
39084	208	294	< 1	0.02	2	50	18	< 5	< 1	4	< 0.01	< 10	< 10	< 1	< 10	10
39085	208	294	< 1	0.01	< 1	70	16	< 5	1	4	< 0.01	< 10	< 10	< 1	< 10	16
39086	208	294	< 1	0.02	1	180	18	< 5	2	10	< 0.01	< 10	< 10	1	< 10	20
39087	208	294	< 1	0.01	< 1	70	18	< 5	2	5	< 0.01	< 10	< 10	1	< 10	26
39088	208	294	< 1	0.01	< 1	70	38	< 5	2	30	< 0.01	< 10	< 10	1	< 10	34
39089	208	294	< 1	0.03	< 1	60	12	< 5	< 1	4	< 0.01	< 10	< 10	< 1	< 10	14
39090	208	294	2	0.01	1	130	24	< 5	1	6	< 0.01	< 10	< 10	2	< 10	24
39091	208	294	< 1	0.02	< 1	70	12	< 5	1	5	< 0.01	< 10	< 10	< 1	< 10	20
39092	208	294	< 1	0.01	1	40	16	< 5	4	3	< 0.01	< 10	< 10	1	< 10	18
39093	208	294	< 1	0.01	< 1	60	20	< 5	1	3	< 0.01	< 10	< 10	1	< 10	28
39094	208	294	< 1	0.01	1	40	12	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	10
39095	208	294	< 1	0.02	< 1	70	24	< 5	1	4	< 0.01	< 10	< 10	1	< 10	14
39096	208	294	< 1	0.02	< 1	70	14	< 5	1	3	< 0.01	< 10	< 10	< 1	< 10	10
39097	208	294	< 1	0.02	< 1	70	16	< 5	1	6	< 0.01	< 10	< 10	< 1	< 10	18
39098	208	294	< 1	0.03	< 1	60	12	< 5	2	15	< 0.01	< 10	< 10	< 1	< 10	18
39099	208	294	< 1	0.02	< 1	60	20	< 5	1	9	< 0.01	< 10	< 10	< 1	< 10	22
39100	208	294	< 1	0.03	< 1	60	12	< 5	1	4	< 0.01	< 10	< 10	< 1	< 10	16
39144	208	294	< 1	0.02	< 1	70	4	< 5	2	5	< 0.01	< 10	< 10	< 1	< 10	28
39145	208	294	< 1	0.03	< 1	70	6	< 5	1	7	< 0.01	< 10	< 10	< 1	< 10	20
39146	208	294	< 1	0.01	2	100	18	< 5	< 1	5	< 0.01	< 10	< 10	< 1	10	16
39147	208	294	< 1	0.01	1	70	10	< 5	1	8	< 0.01	< 10	< 10	< 1	< 10	18
39148	208	294	< 1	0.01	2	30	18	< 5	< 1	6	< 0.01	< 10	< 10	< 1	< 10	10
39149	208	294	< 1	0.02	1	50	14	< 5	1	7	< 0.01	< 10	< 10	< 1	< 10	22
39150	208	294	< 1	0.01	2	40	10	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	16
39151	208	294	< 1	0.01	2	10	16	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	12
39152	208	294	< 1	0.01	2	80	48	< 5	1	6	< 0.01	< 10	< 10	1	< 10	40
39153	208	294	< 1	0.01	1	90	24	< 5	4	5	< 0.01	< 10	< 10	1	< 10	36
39154	208	294	< 1	0.01	1	90	30	< 5	1	7	< 0.01	< 10	< 10	< 1	< 10	50
39155	208	294	6	0.01	6	150	168	< 5	2	10	< 0.01	< 10	< 10	3	10	54
39156	208	294	< 1	0.01	1	100	26	< 5	18	4	< 0.01	< 10	< 10	1	< 10	20
39157	208	294	1	0.03	1	60	24	< 5	1	6	< 0.01	< 10	< 10	1	< 10	20
39158	208	294	1	0.03	1	70	14	< 5	1	5	< 0.01	< 10	< 10	1	< 10	14
39159	208	294	< 1	0.01	< 1	80	18	< 5	1	4	< 0.01	< 10	< 10	< 1	< 10	24
39160	208	294	< 1	0.02	1	80	22	< 5	1	4	< 0.01	< 10	< 10	< 1	< 10	28
39161	208	294	< 1	0.02	1	70	16	< 5	1	4	< 0.01	< 10	< 10	< 1	< 10	24
39162	208	294	2	0.02	1	70	12	< 5	1	5	< 0.01	< 10	< 10	1	< 10	30
39163	208	294	< 1	0.01	3	400	324	< 5	2	13	< 0.01	< 10	< 10	4	< 10	144

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC. ##

1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR/DAW
Comments:

Certificate Date: 17-SEP-90
Invoice No. :I9022461
P.O. Number :

CERTIFICATE OF ANALYSIS A9022461

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
39164	208	294	< 0.002	0.6	0.44	< 5	160	< 0.5	2	0.09	< 0.5	1	67	7	0.45	10	< 1	0.28	30	0.17	165
39165	208	294	< 0.002	0.4	0.39	< 5	180	< 0.5	< 2	0.06	< 0.5	1	46	8	0.46	< 10	< 1	0.29	30	0.12	125
39166	208	294	< 0.002	1.4	0.07	50	120	< 0.5	< 2	< 0.01	< 0.5	< 1	195	7	0.39	< 10	< 1	0.03	< 10	0.01	30
39167	208	294	< 0.002	0.4	3.99	185	1170	1.0	2	2.74	< 0.5	26	140	31	7.39	10	< 1	0.09	10	2.34	790
39168	208	294	0.179	7.4	0.08	5	100	< 0.5	< 2	0.02	< 0.5	< 1	195	6	0.34	< 10	< 1	0.01	< 10	0.01	30
39169	208	294	0.014	1.4	1.20	10	990	0.5	2	1.32	1.0	3	40	8	1.49	10	< 1	0.44	20	0.39	255
39170	208	294	< 0.002	< 0.2	0.14	20	120	< 0.5	< 2	0.05	< 0.5	1	221	8	0.51	< 10	< 1	0.02	< 10	0.06	180
39171	208	294	< 0.002	0.4	0.10	20	70	< 0.5	< 2	0.03	< 0.5	1	185	10	0.41	< 10	< 1	< 0.01	< 10	0.04	225
39172	208	294	< 0.002	0.2	0.63	5	240	< 0.5	2	0.05	< 0.5	3	99	15	0.50	< 10	< 1	0.12	20	0.02	30
39173	208	294	< 0.002	0.2	0.53	< 5	110	< 0.5	< 2	0.02	< 0.5	1	128	18	0.72	< 10	< 1	0.10	10	0.02	55
39174	208	294	< 0.002	< 0.2	0.72	45	220	< 0.5	2	0.07	< 0.5	9	188	56	6.07	< 10	< 1	0.23	< 10	0.05	55
39175	208	294	< 0.002	< 0.2	0.17	< 5	80	< 0.5	2	0.21	< 0.5	1	157	7	0.48	< 10	< 1	0.05	< 10	0.10	90
39176	208	294	< 0.002	< 0.2	0.37	< 5	30	< 0.5	2	0.19	< 0.5	1	168	7	0.98	< 10	< 1	< 0.01	< 10	0.32	355
39177	208	294	< 0.002	5.0	0.23	125	10	< 0.5	< 2	0.02	1.5	68	195	85	>15.00	< 10	< 1	0.01	< 10	0.04	25
39178	208	294	< 0.002	0.6	0.90	10	350	< 0.5	2	0.11	< 0.5	4	105	25	2.12	< 10	< 1	0.14	20	0.40	240
39179	208	294	< 0.002	0.2	0.69	45	60	< 0.5	2	0.05	< 0.5	31	2000	25	3.52	< 10	< 1	< 0.01	< 10	1.03	270
39180	208	294	< 0.002	0.4	2.88	75	170	0.5	4	0.26	0.5	22	515	197	7.98	< 10	< 1	0.13	20	1.11	515
39181	208	294	< 0.002	1.4	1.65	10	360	0.5	2	0.41	1.5	17	267	41	2.48	< 10	< 1	0.11	10	0.41	1465
39182	208	294	< 0.002	< 0.2	0.37	85	< 10	< 0.5	< 2	0.04	< 0.5	41	1440	34	2.14	< 10	< 1	< 0.01	< 10	4.69	265
39183	208	294	< 0.002	< 0.2	0.38	670	< 10	< 0.5	< 2	0.15	< 0.5	50	1290	6	3.29	< 10	< 1	< 0.01	< 10	9.50	545
39184	208	294	< 0.002	< 0.2	0.46	550	< 10	< 0.5	< 2	0.14	< 0.5	69	1595	9	3.36	< 10	< 1	< 0.01	< 10	12.80	465
39185	208	294	< 0.002	< 0.2	0.49	210	10	< 0.5	< 2	2.69	0.5	41	1260	19	2.53	< 10	< 1	< 0.01	< 10	6.57	945
39186	208	294	< 0.002	< 0.2	0.32	110	< 10	< 0.5	< 2	0.11	< 0.5	53	1395	11	3.37	< 10	< 1	< 0.01	< 10	>15.00	385
39187	208	294	< 0.002	0.6	0.64	20	260	< 0.5	4	0.09	< 0.5	7	901	23	0.41	< 10	< 1	< 0.01	10	0.33	25
39188	208	294	< 0.002	< 0.2	0.10	10	250	< 0.5	< 2	0.47	< 0.5	5	319	11	0.42	< 10	< 1	< 0.01	< 10	0.17	65
39189	208	294	< 0.002	0.4	0.09	20	150	< 0.5	2	0.01	< 0.5	7	217	9	0.36	< 10	< 1	< 0.01	< 10	0.29	60
39190	208	294	< 0.002	0.8	1.25	15	490	< 0.5	2	0.23	< 0.5	8	933	63	0.64	< 10	< 1	0.08	20	0.27	25
39191	208	294	< 0.002	< 0.2	6.39	30	20	1.0	< 2	0.19	< 0.5	21	2390	539	4.09	< 10	< 1	< 0.01	< 10	9.60	160
39192	208	294	< 0.002	< 0.2	0.49	405	580	< 0.5	< 2	4.09	< 0.5	50	1770	12	4.27	< 10	< 1	< 0.01	< 10	12.65	1080
39193	208	294	< 0.002	0.6	1.98	150	590	< 0.5	4	1.83	< 0.5	26	119	29	4.70	< 10	< 1	0.19	20	2.22	575
39194	208	294	< 0.002	1.2	2.42	125	200	< 0.5	4	0.27	< 0.5	18	130	55	3.67	< 10	< 1	0.23	20	1.76	365
39195	208	294	< 0.002	1.4	0.95	45	330	< 0.5	2	0.75	< 0.5	5	90	26	4.19	< 10	< 1	0.21	10	1.02	680
39196	208	294	< 0.002	0.6	0.53	10	900	< 0.5	< 2	0.46	< 0.5	2	100	5	0.71	10	< 1	0.28	30	0.32	130
39197	208	294	< 0.002	0.6	0.58	10	1910	< 0.5	2	1.05	< 0.5	2	89	5	0.72	10	< 1	0.28	30	0.32	150
39198	208	294	< 0.002	0.2	0.57	10	170	< 0.5	2	0.20	< 0.5	5	433	9	0.66	< 10	< 1	0.09	< 10	0.29	60
39199	208	294	< 0.002	0.6	0.33	15	310	< 0.5	< 2	0.06	< 0.5	5	546	22	0.51	< 10	< 1	0.01	< 10	0.19	35
39200	208	294	< 0.002	< 0.2	0.73	10	160	< 0.5	2	1.43	< 0.5	7	240	15	2.08	< 10	< 1	0.11	< 10	0.79	235

CERTIFICATION: B. Campbell

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC. ##

1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR/DAW
Comments:

Certificate Date: 17-SEP-90
Invoice No. :19022461
P.O. Number :

CERTIFICATE OF ANALYSIS A9022461

SAMPLE DESCRIPTION	PREP CODE	Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
39164	208 294	< 1	0.01	1	290	18	< 5	< 1	7	< 0.01	< 10	< 10	< 1	< 10	28
39165	208 294	< 1	0.01	1	140	16	< 5	6	5	< 0.01	< 10	< 10	< 1	< 10	26
39166	208 294	< 1	0.01	2	10	8	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	12
39167	208 294	< 1	0.08	57	2180	6	5	21	165	0.07	< 10	< 10	128	10	94
39168	208 294	< 1	0.01	2	30	26	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	42
39169	208 294	< 1	0.03	5	320	1030	< 5	3	95	< 0.01	< 10	< 10	3	< 10	340
39170	208 294	< 1	0.01	3	180	8	< 5	5	5	< 0.01	< 10	< 10	3	< 10	10
39171	208 294	< 1	0.01	3	70	6	< 5	< 1	2	< 0.01	< 10	< 10	2	< 10	8
39172	208 294	< 1	0.01	15	110	34	< 5	1	26	< 0.01	< 10	< 10	4	< 10	36
39173	208 294	< 1	0.01	22	90	18	< 5	1	3	< 0.01	< 10	< 10	9	< 10	40
39174	208 294	2	0.01	57	530	< 2	< 5	13	5	< 0.01	< 10	< 10	27	< 10	182
39175	208 294	< 1	0.01	3	20	30	< 5	< 1	13	< 0.01	< 10	< 10	< 1	< 10	8
39176	208 294	< 1	0.02	3	10	2	< 5	2	13	< 0.01	< 10	< 10	1	< 10	22
39177	208 294	6	0.01	59	< 10	466	5	1	3	< 0.01	< 10	< 10	< 1	80	96
39178	208 294	1	0.04	8	240	52	< 5	2	21	0.01	< 10	< 10	10	< 10	68
39179	208 294	< 1	0.01	685	420	< 2	10	8	6	< 0.01	< 10	< 10	31	< 10	66
39180	208 294	< 1	0.01	449	1290	30	< 5	25	31	< 0.01	< 10	< 10	93	< 10	178
39181	208 294	< 1	0.01	134	1450	20	< 5	8	15	< 0.01	< 10	< 10	35	< 10	84
39182	208 294	< 1	0.01	761	20	6	5	6	1	< 0.01	20	< 10	18	< 10	22
39183	208 294	< 1	0.01	464	< 10	< 2	< 5	8	16	< 0.01	10	< 10	12	< 10	20
39184	208 294	< 1	0.01	1065	< 10	< 2	5	5	13	< 0.01	10	< 10	17	< 10	20
39185	208 294	< 1	0.01	404	20	998	< 5	5	240	< 0.01	< 10	< 10	15	< 10	300
39186	208 294	< 1	0.01	764	< 10	< 2	5	5	12	< 0.01	20	< 10	15	< 10	22
39187	208 294	1	0.01	116	60	8	5	3	17	< 0.01	< 10	< 10	10	< 10	70
39188	208 294	< 1	0.02	74	50	4	< 5	< 1	15	< 0.01	< 10	< 10	3	< 10	24
39189	208 294	< 1	0.01	102	30	6	< 5	< 1	6	< 0.01	< 10	< 10	2	< 10	22
39190	208 294	< 1	0.01	131	1470	18	< 5	4	32	< 0.01	< 10	< 10	13	< 10	100
39191	208 294	< 1	0.01	549	570	< 2	5	5	1	< 0.01	< 10	< 10	19	< 10	290
39192	208 294	< 1	0.01	769	< 10	< 2	5	6	208	< 0.01	10	< 10	20	< 10	38
39193	208 294	1	0.19	56	1860	4	5	9	102	0.12	< 10	< 10	69	10	94
39194	208 294	6	0.01	51	710	556	< 5	4	33	< 0.01	< 10	< 10	43	< 10	472
39195	208 294	4	0.02	12	710	298	< 5	2	103	< 0.01	< 10	< 10	19	< 10	150
39196	208 294	< 1	0.01	9	100	14	< 5	2	43	< 0.01	< 10	< 10	2	< 10	26
39197	208 294	< 1	0.02	5	80	22	< 5	2	118	< 0.01	< 10	< 10	2	< 10	24
39198	208 294	< 1	0.01	36	510	6	< 5	1	8	< 0.01	< 10	< 10	8	< 10	28
39199	208 294	< 1	0.01	66	110	4	< 5	1	13	< 0.01	< 10	< 10	10	< 10	44
39200	208 294	1	0.03	17	1870	2	< 5	5	148	< 0.01	< 10	< 10	17	< 10	46

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

A9023250

Comments: CC: ART TROUP

CERTIFICATE A9023250

ARBOR RESOURCES INC.

Project: AOR-DAW
P.O. # :

Samples submitted to our lab in Vancouver, BC.
This report was printed on 27-SEP-90.

SAMPLE PREPARATION

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION
208	106	Assay ring to approx 150 mesh
294	106	Crush and split (0-10 pounds)
238	106	NITRIC-AQUA REGIA DIGESTION

* NOTE 1:

The 32 element ICP package is suitable for trace metals in soil and rock samples. Elements for which the nitric-aqua regia digestion is possibly incomplete are: Al, Ba, Be, Ca, Cr, Ga, K, La, Mg, Na, Sr, Ti, Tl, W.

ANALYTICAL PROCEDURES

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION	METHOD	DETECTION LIMIT	UPPER LIMIT
398	106	Au oz/T: 1/2 assay ton	FA-AAS	0.002	20.00
922	106	Ag ppm: 32 element, soil & rock	ICP-AES	0.2	200
921	106	Al %: 32 element, soil & rock	ICP-AES	0.01	15.00
923	106	As ppm: 32 element, soil & rock	ICP-AES	5	10000
924	106	Ba ppm: 32 element, soil & rock	ICP-AES	10	10000
925	106	Be ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
926	106	Bi ppm: 32 element, soil & rock	ICP-AES	2	10000
927	106	Ca %: 32 element, soil & rock	ICP-AES	0.01	15.00
928	106	Cd ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
929	106	Co ppm: 32 element, soil & rock	ICP-AES	1	10000
930	106	Cr ppm: 32 element, soil & rock	ICP-AES	1	10000
931	106	Cu ppm: 32 element, soil & rock	ICP-AES	1	10000
932	106	Fe %: 32 element, soil & rock	ICP-AES	0.01	15.00
933	106	Ga ppm: 32 element, soil & rock	ICP-AES	10	10000
951	106	Hg ppm: 32 element, soil & rock	ICP-AES	1	10000
934	106	K %: 32 element, soil & rock	ICP-AES	0.01	10.00
935	106	La ppm: 32 element, soil & rock	ICP-AES	10	10000
936	106	Mg %: 32 element, soil & rock	ICP-AES	0.01	15.00
937	106	Mn ppm: 32 element, soil & rock	ICP-AES	5	10000
938	106	Mo ppm: 32 element, soil & rock	ICP-AES	1	10000
939	106	Na %: 32 element, soil & rock	ICP-AES	0.01	5.00
940	106	Ni ppm: 32 element, soil & rock	ICP-AES	1	10000
941	106	P ppm: 32 element, soil & rock	ICP-AES	10	10000
942	106	Pb ppm: 32 element, soil & rock	ICP-AES	2	10000
943	106	Sb ppm: 32 element, soil & rock	ICP-AES	5	10000
958	106	Sc ppm: 32 elements, soil & rock	ICP-AES	1	10000
944	106	Sr ppm: 32 element, soil & rock	ICP-AES	1	10000
945	106	Ti %: 32 element, soil & rock	ICP-AES	0.01	5.00
946	106	Tl ppm: 32 element, soil & rock	ICP-AES	10	10000
947	106	U ppm: 32 element, soil & rock	ICP-AES	10	10000
948	106	V ppm: 32 element, soil & rock	ICP-AES	1	10000
949	106	W ppm: 32 element, soil & rock	ICP-AES	10	10000
950	106	Zn ppm: 32 element, soil & rock	ICP-AES	2	10000

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Page Number : 1-A
Total Pages : 3
Invoice Date: 27-SEP-90
Invoice No. : I-9023250
P.O. Number :

CERTIFICATE OF ANALYSIS A9023250

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
39201	208	294	0.006	0.6	0.22	65	440	< 0.5	< 2	0.03	0.5	1	271	4	0.66	< 10	< 1	0.07	< 10	0.03	150
39202	208	294	0.238	4.6	0.22	5	1400	< 0.5	2	0.02	0.5	1	340	3	0.77	< 10	< 1	0.08	< 10	0.02	75
39203	208	294	0.002	1.0	0.47	10	370	< 0.5	< 2	0.04	0.5	1	112	3	0.86	10	< 1	0.20	30	0.03	150
39204	208	294	0.002	0.6	0.36	5	350	< 0.5	< 2	0.02	0.5	1	213	2	0.86	< 10	< 1	0.23	10	0.02	85
39205	208	294	< 0.002	0.8	0.36	5	520	< 0.5	< 2	0.03	< 0.5	1	135	1	0.31	< 10	< 1	0.29	20	0.01	55
39206	208	294	< 0.002	0.2	0.10	< 5	60	< 0.5	< 2	0.01	< 0.5	1	330	1	0.39	< 10	< 1	0.03	< 10	0.01	45
39207	208	294	< 0.002	1.0	0.58	5	530	< 0.5	< 2	0.05	< 0.5	< 1	57	4	0.67	10	< 1	0.39	30	0.05	60
39208	208	294	< 0.002	0.6	0.44	5	370	< 0.5	< 2	0.04	< 0.5	< 1	151	3	0.59	< 10	< 1	0.28	20	0.03	60
39209	208	294	< 0.002	0.2	0.10	< 5	60	< 0.5	< 2	0.01	< 0.5	< 1	247	1	0.32	< 10	< 1	0.03	< 10	< 0.01	70
39210	208	294	0.002	0.8	0.51	< 5	410	< 0.5	< 2	0.03	0.5	1	83	2	0.58	< 10	< 1	0.36	30	0.03	85
39211	208	294	0.145	1.0	0.08	5	90	< 0.5	< 2	0.01	0.5	< 1	259	3	0.67	< 10	< 1	< 0.01	< 10	< 0.01	160
39212	208	294	0.004	0.2	0.44	15	390	< 0.5	< 2	0.03	< 0.5	< 1	70	5	0.66	< 10	< 1	0.31	20	0.03	85
39213	208	294	< 0.002	< 0.2	1.49	5	630	< 0.5	< 2	0.16	< 0.5	5	78	2	2.00	< 10	< 1	0.32	20	0.86	365
39214	208	294	< 0.002	< 0.2	1.53	< 5	750	< 0.5	< 2	0.18	< 0.5	4	89	< 1	2.00	< 10	< 1	0.38	20	0.88	390
39215	208	294	< 0.002	< 0.2	0.37	< 5	200	< 0.5	< 2	0.06	< 0.5	1	261	1	0.67	< 10	< 1	0.07	< 10	0.15	170
39216	208	294	< 0.002	< 0.2	0.76	< 5	440	< 0.5	< 2	0.06	< 0.5	2	232	< 1	0.96	< 10	< 1	0.25	10	0.32	160
39217	208	294	< 0.002	0.4	0.39	20	400	< 0.5	< 2	0.02	0.5	< 1	81	1	0.43	< 10	< 1	0.29	30	0.03	55
39218	208	294	< 0.002	< 0.2	0.51	< 5	4920	< 0.5	< 2	0.04	< 0.5	1	114	< 1	0.44	< 10	< 1	0.34	20	0.05	95
39219	208	294	< 0.002	0.4	0.86	< 5	2400	< 0.5	< 2	0.06	1.0	1	99	2	0.78	10	< 1	0.44	30	0.11	150
39220	208	294	< 0.002	< 0.2	0.25	< 5	370	< 0.5	< 2	0.01	< 0.5	< 1	320	< 1	0.38	< 10	< 1	0.13	< 10	0.02	50
39261	208	294	< 0.002	0.4	0.04	< 5	510	< 0.5	< 2	< 0.01	< 0.5	< 1	224	< 1	0.33	< 10	< 1	0.01	< 10	< 0.01	65
39262	208	294	< 0.002	0.4	0.08	< 5	3960	< 0.5	2	0.25	< 0.5	2	321	< 1	0.51	< 10	< 1	< 0.01	< 10	0.02	70
39271	208	294	< 0.002	0.4	0.07	< 5	1520	< 0.5	< 2	0.03	< 0.5	1	257	3	0.60	< 10	1	< 0.01	< 10	< 0.01	70
39272	208	294	0.048	>200	0.52	15	740	< 0.5	8	0.01	< 0.5	1	182	22	1.93	< 10	176	0.44	10	0.07	20
39273	208	294	0.002	3.0	0.38	125	240	< 0.5	< 2	0.04	0.5	2	276	114	7.39	< 10	< 1	0.10	10	0.03	115
39274	208	294	0.008	1.6	1.45	< 5	590	< 0.5	4	0.24	< 0.5	5	177	5	2.52	10	< 1	0.59	10	0.38	210
39275	208	294	0.014	1.0	0.32	5	90	< 0.5	< 2	0.05	0.5	7	356	11	0.97	< 10	< 1	0.03	< 10	0.03	230
39276	208	294	< 0.002	1.2	2.08	30	350	< 0.5	4	0.39	1.0	10	266	17	2.90	10	< 1	0.22	10	1.28	590
39277	208	294	< 0.002	1.4	0.27	5	70	< 0.5	< 2	0.02	< 0.5	1	371	22	1.37	< 10	< 1	0.03	< 10	0.06	110
39278	208	294	< 0.002	1.0	0.34	5	470	< 0.5	2	0.03	< 0.5	< 1	197	3	0.73	< 10	< 1	0.29	20	0.03	60
39279	208	294	< 0.002	10.2	0.15	50	240	< 0.5	< 2	0.01	< 0.5	1	370	1	1.62	< 10	< 1	0.19	< 10	0.01	75
39280	208	294	< 0.002	0.8	0.20	5	70	< 0.5	< 2	0.03	< 0.5	1	335	11	1.09	< 10	< 1	0.02	< 10	0.02	45
39281	208	294	< 0.002	1.0	0.84	90	3280	< 0.5	< 2	0.12	< 0.5	10	57	16	1.54	10	< 1	0.38	60	0.07	215
39282	208	294	< 0.002	0.6	0.61	945	1410	< 0.5	2	0.07	2.0	1	177	8	1.68	10	< 1	0.40	40	0.04	30
39283	208	294	< 0.002	0.8	0.37	5	270	< 0.5	< 2	0.53	< 0.5	1	101	< 1	0.60	10	< 1	0.27	50	0.09	245
39284	208	294	< 0.002	0.2	0.13	< 5	150	< 0.5	2	0.01	< 0.5	< 1	336	< 1	0.42	< 10	< 1	0.13	< 10	0.01	85
39285	208	294	< 0.002	0.8	0.12	< 5	80	< 0.5	2	< 0.01	< 0.5	< 1	348	2	0.69	< 10	< 1	< 0.01	< 10	< 0.01	30
39286	208	294	0.047	2.4	0.23	< 5	1660	< 0.5	2	< 0.01	< 0.5	1	356	1	1.56	< 10	< 1	0.07	10	< 0.01	40
39287	208	294	< 0.002	0.6	0.22	< 5	1160	< 0.5	2	< 0.01	< 0.5	1	232	< 1	0.49	< 10	< 1	0.22	< 10	0.01	110
39288	208	294	0.012	3.4	0.41	< 5	860	< 0.5	2	0.01	< 0.5	< 1	199	1	0.92	< 10	< 1	0.23	20	< 0.01	35

CERTIFICATION: B. Caybl

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Invoice Date: 27-SEP-90
Invoice No. : I-9023250
P.O. Number :

CERTIFICATE OF ANALYSIS A9023250

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
39201	208	294	< 1	0.01	3	20	70	< 5	1	5	< 0.01	< 10	< 10	2	< 10	36
39202	208	294	1	< 0.01	4	30	60	< 5	< 1	17	< 0.01	< 10	< 10	1	< 10	38
39203	208	294	< 1	0.05	1	80	18	< 5	3	6	< 0.01	< 10	< 10	2	< 10	56
39204	208	294	1	0.02	3	50	6	< 5	1	4	< 0.01	10	< 10	< 1	< 10	26
39205	208	294	< 1	0.02	1	30	12	< 5	1	6	< 0.01	< 10	< 10	< 1	< 10	16
39206	208	294	< 1	< 0.01	4	10	2	< 5	< 1	1	< 0.01	10	< 10	1	< 10	8
39207	208	294	< 1	0.03	< 1	100	16	< 5	4	5	< 0.01	< 10	< 10	1	< 10	20
39208	208	294	< 1	0.03	2	80	14	< 5	2	4	< 0.01	< 10	< 10	1	< 10	18
39209	208	294	< 1	< 0.01	3	< 10	< 2	< 5	< 1	< 1	< 0.01	< 10	< 10	< 1	< 10	4
39210	208	294	< 1	0.04	1	80	8	< 5	2	4	< 0.01	10	< 10	1	< 10	20
39211	208	294	< 1	< 0.01	3	20	18	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	16
39212	208	294	< 1	0.04	< 1	80	10	< 5	2	4	< 0.01	< 10	< 10	< 1	< 10	26
39213	208	294	< 1	0.01	1	370	8	< 5	3	15	< 0.01	< 10	< 10	6	< 10	68
39214	208	294	< 1	0.02	1	400	6	< 5	4	17	< 0.01	< 10	< 10	7	< 10	62
39215	208	294	< 1	< 0.01	2	140	4	< 5	1	5	< 0.01	< 10	< 10	2	< 10	14
39216	208	294	< 1	0.02	3	110	< 2	< 5	2	8	< 0.01	< 10	< 10	4	< 10	26
39217	208	294	< 1	0.04	< 1	60	18	< 5	1	7	< 0.01	< 10	< 10	< 1	< 10	32
39218	208	294	< 1	0.04	1	70	10	< 5	3	65	< 0.01	< 10	< 10	< 1	< 10	16
39219	208	294	< 1	0.02	< 1	100	20	< 5	5	28	< 0.01	< 10	< 10	< 1	< 10	44
39220	208	294	< 1	0.01	3	10	8	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	8
39261	208	294	< 1	< 0.01	2	10	36	< 5	< 1	2	< 0.01	10	< 10	< 1	< 10	8
39262	208	294	< 1	< 0.01	4	70	4	< 5	< 1	105	< 0.01	< 10	< 10	1	< 10	8
39271	208	294	1	0.03	5	90	2	< 5	< 1	15	< 0.01	< 10	< 10	< 1	< 10	6
39272	208	294	2	0.04	1	530	408	45	2	111	< 0.01	< 10	< 10	5	< 10	16
39273	208	294	< 1	< 0.01	6	1630	20	5	1	15	0.01	< 10	< 10	10	< 10	134
39274	208	294	1	0.03	3	520	2	< 5	6	15	0.01	< 10	< 10	10	< 10	66
39275	208	294	< 1	0.02	7	250	2	< 5	1	4	< 0.01	< 10	< 10	3	< 10	60
39276	208	294	1	0.01	19	1410	16	< 5	4	20	< 0.01	< 10	< 10	43	< 10	146
39277	208	294	< 1	< 0.01	4	220	< 2	< 5	1	4	< 0.01	< 10	< 10	3	< 10	38
39278	208	294	< 1	0.01	1	40	28	< 5	1	7	< 0.01	< 10	< 10	1	< 10	38
39279	208	294	4	0.01	4	260	34	5	1	55	< 0.01	< 10	< 10	3	< 10	6
39280	208	294	< 1	< 0.01	6	230	< 2	< 5	< 1	4	< 0.01	< 10	< 10	1	< 10	20
39281	208	294	2	< 0.01	1	220	24	< 5	4	47	< 0.01	< 10	< 10	1	< 10	136
39282	208	294	2	< 0.01	2	240	32	5	1	44	< 0.01	< 10	< 10	< 1	< 10	30
39283	208	294	< 1	0.05	1	30	8	< 5	1	42	< 0.01	< 10	< 10	< 1	< 10	16
39284	208	294	< 1	< 0.01	3	20	10	< 5	< 1	3	< 0.01	< 10	< 10	1	< 10	4
39285	208	294	1	< 0.01	3	20	26	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	6
39286	208	294	5	< 0.01	3	60	154	< 5	< 1	8	< 0.01	< 10	< 10	< 1	< 10	16
39287	208	294	< 1	< 0.01	3	30	10	< 5	< 1	18	< 0.01	10	10	1	< 10	8
39288	208	294	8	< 0.01	1	100	600	< 5	< 1	8	< 0.01	< 10	< 10	< 1	< 10	4

CERTIFICATION: B. Caplan

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Invoice Date: 27-SEP-90
Invoice No. : I-9023250
P.O. Number :

CERTIFICATE OF ANALYSIS A9023250

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
39289	208	294	0.190	10.0	0.74	5	2560	< 0.5	< 2	0.06	< 0.5	4	153	66	3.04	10	< 1	0.28	20	0.07	235
39290	208	294	0.085	4.4	0.25	< 5	140	< 0.5	< 2	0.04	< 0.5	1	249	18	1.13	< 10	< 1	0.06	< 10	0.03	95
39291	208	294	0.012	2.0	0.11	< 5	150	< 0.5	< 2	< 0.01	< 0.5	1	331	1	0.72	< 10	< 1	< 0.01	< 10	< 0.01	40
39292	208	294	< 0.002	0.6	0.21	< 5	970	< 0.5	< 2	0.11	1.0	1	263	10	0.83	< 10	< 1	0.13	< 10	0.02	425
39293	208	294	0.002	0.4	1.07	< 5	380	< 0.5	< 2	0.14	< 0.5	3	186	3	1.40	10	< 1	0.49	20	0.41	210
39294	208	294	< 0.002	0.4	0.31	< 5	1790	< 0.5	< 2	0.02	< 0.5	3	246	5	1.95	< 10	< 1	0.05	10	0.03	655
39295	208	294	0.014	21.4	0.16	15	4850	< 0.5	4	0.47	4.5	2	229	434	0.45	< 10	1	0.05	10	0.02	250
39296	208	294	0.097	>200	0.09	120	3900	< 0.5	16	0.35	5.0	1	253	395	1.00	< 10	28	0.02	< 10	0.06	105
39298	208	294	0.014	21.2	0.16	5	3840	< 0.5	4	0.10	28.5	1	82	628	0.70	< 10	5	0.02	< 10	0.04	115
39299	208	294	0.144	128.0	0.04	140	1640	< 0.5	16	0.08	36.0	1	122	3630	0.60	< 10	32	< 0.01	< 10	< 0.01	105
39300	208	294	0.008	12.6	0.07	5	3630	< 0.5	< 2	0.41	8.0	1	44	555	0.47	< 10	1	0.01	< 10	0.02	210
39327	208	294	< 0.002	1.2	0.30	60	4900	< 0.5	2	0.51	0.5	3	325	40	0.76	< 10	< 1	0.18	10	0.03	160
39328	208	294	< 0.002	< 0.2	0.27	145	4010	< 0.5	2	4.24	0.5	23	190	12	2.47	< 10	< 1	0.01	< 10	0.06	715
39329	208	294	< 0.002	< 0.2	0.10	< 5	1620	< 0.5	< 2	0.10	< 0.5	2	345	6	0.66	< 10	< 1	< 0.01	< 10	0.04	115
39330	208	294	< 0.002	0.2	0.23	20	990	< 0.5	< 2	0.03	< 0.5	1	242	3	0.39	< 10	< 1	0.23	10	< 0.01	55
39331	208	294	< 0.002	0.2	0.03	< 5	240	< 0.5	< 2	1.07	< 0.5	1	288	2	0.91	< 10	< 1	< 0.01	< 10	0.08	205
39332	208	294	< 0.002	0.4	0.27	10	360	< 0.5	< 2	< 0.01	< 0.5	1	287	2	0.38	< 10	< 1	0.17	< 10	0.02	25
39333	208	294	< 0.002	< 0.2	0.29	< 5	90	< 0.5	2	5.78	< 0.5	3	163	9	0.82	< 10	< 1	0.01	< 10	0.27	805
39334	208	294	0.004	0.6	0.46	5	730	< 0.5	< 2	0.07	< 0.5	1	183	1	0.60	< 10	< 1	0.37	30	0.03	110
39335	208	294	< 0.002	0.2	0.19	< 5	180	< 0.5	< 2	0.50	< 0.5	1	314	< 1	0.51	< 10	< 1	0.06	< 10	0.03	210
39336	208	294	2.224	17.8	0.34	5	570	< 0.5	< 2	0.03	< 0.5	1	153	1	0.63	< 10	< 1	0.26	20	0.02	135
39337	208	294	0.002	0.6	0.34	5	470	< 0.5	< 2	0.03	0.5	2	121	< 1	0.75	< 10	< 1	0.25	20	0.02	70
39338	208	294	0.004	0.8	2.31	5	330	< 0.5	< 2	0.08	< 0.5	7	489	12	1.49	< 10	< 1	0.05	10	2.33	135
39339	208	294	< 0.002	0.8	0.47	< 5	270	< 0.5	< 2	0.04	< 0.5	1	108	2	0.65	< 10	< 1	0.36	30	0.06	30
39340	208	294	< 0.002	0.6	0.66	5	370	< 0.5	2	0.05	0.5	1	169	8	0.98	10	< 1	0.41	20	0.10	55
39341	208	294	< 0.002	4.8	1.63	< 5	190	< 0.5	< 2	0.08	1.0	82	232	3050	5.70	10	< 1	0.17	10	1.04	765
39342	208	294	< 0.002	0.8	3.67	< 5	630	< 0.5	< 2	0.13	< 0.5	13	804	64	2.32	10	< 1	0.15	< 10	3.85	235
39343	208	294	< 0.002	< 0.2	0.16	< 5	60	< 0.5	< 2	0.15	< 0.5	2	345	13	0.59	< 10	< 1	< 0.01	< 10	0.08	60
39344	208	294	< 0.002	0.6	1.63	< 5	410	0.5	2	0.18	< 0.5	2	109	6	0.84	10	< 1	0.11	50	0.16	15
39345	208	294	< 0.002	< 0.2	0.14	230	140	< 0.5	< 2	5.23	0.5	6	171	14	2.62	< 10	< 1	0.02	< 10	0.09	695
39346	208	294	< 0.002	0.2	0.57	< 5	2010	< 0.5	< 2	1.17	< 0.5	7	183	3	1.47	10	< 1	0.18	20	0.17	430
39347	208	294	< 0.002	< 0.2	0.14	5	270	< 0.5	< 2	0.13	< 0.5	1	175	3	0.62	< 10	< 1	0.09	< 10	0.02	170
39348	208	294	< 0.002	< 0.2	0.06	< 5	40	< 0.5	< 2	1.23	< 0.5	1	292	< 1	0.35	< 10	< 1	< 0.01	< 10	0.03	190
39349	208	294	< 0.002	0.2	0.08	< 5	140	< 0.5	< 2	0.02	< 0.5	< 1	265	< 1	0.34	< 10	< 1	0.01	< 10	< 0.01	75
39350	208	294	< 0.002	0.2	0.01	< 5	160	< 0.5	< 2	0.66	< 0.5	1	137	< 1	0.36	< 10	< 1	< 0.01	< 10	0.01	160
39352	208	294	< 0.002	0.6	0.78	< 5	460	< 0.5	< 2	0.02	< 0.5	3	200	18	0.96	10	< 1	0.23	50	0.03	15
39353	208	294	< 0.002	1.0	0.56	5	230	< 0.5	< 2	0.06	< 0.5	2	328	14	0.71	< 10	< 1	0.02	10	0.06	75
39354	208	294	< 0.002	0.4	0.16	< 5	90	< 0.5	< 2	< 0.01	< 0.5	< 1	187	< 1	0.24	< 10	< 1	0.08	< 10	0.01	25
39355	208	294	< 0.002	0.6	0.55	< 5	200	< 0.5	< 2	0.01	< 0.5	< 1	143	1	0.24	< 10	< 1	0.18	20	0.02	5
39356	208	294	< 0.002	0.4	0.39	< 5	190	< 0.5	< 2	0.03	< 0.5	< 1	188	< 1	0.31	< 10	< 1	0.22	10	0.01	20

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Invoice Date: 27-SEP-90
Invoice No. : I-9023250
P.O. Number :

CERTIFICATE OF ANALYSIS A9023250

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
39289	208	294	3	< 0.01	6	150	1010	5	3	38	< 0.01	< 10	< 10	3	< 10	36
39290	208	294	3	< 0.01	4	30	246	< 5	< 1	9	< 0.01	< 10	< 10	3	< 10	16
39291	208	294	2	< 0.01	4	10	32	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	2
39292	208	294	1	< 0.01	5	370	28	< 5	1	22	< 0.01	< 10	< 10	2	< 10	56
39293	208	294	< 1	0.06	4	330	2	< 5	3	13	0.03	< 10	< 10	29	< 10	20
39294	208	294	1	0.01	7	60	18	< 5	5	11	< 0.01	< 10	< 10	3	< 10	72
39295	208	294	< 1	< 0.01	3	20	4250	105	1	240	< 0.01	< 10	< 10	1	< 10	96
39296	208	294	1	< 0.01	6	60	4170	1055	< 1	96	< 0.01	< 10	10	1	10	36
39298	208	294	< 1	< 0.01	2	40	1560	80	1	295	< 0.01	< 10	< 10	< 1	< 10	246
39299	208	294	< 1	< 0.01	3	< 10	>10000	825	< 1	220	< 0.01	< 10	< 10	< 1	< 10	416
39300	208	294	< 1	< 0.01	1	20	578	45	1	196	< 0.01	< 10	< 10	< 1	< 10	140
39327	208	294	1	0.02	8	580	198	5	1	63	< 0.01	< 10	< 10	2	< 10	22
39328	208	294	2	0.09	35	100	30	< 5	3	51	< 0.01	< 10	< 10	8	< 10	60
39329	208	294	1	< 0.01	7	10	14	< 5	< 1	17	< 0.01	< 10	< 10	2	< 10	12
39330	208	294	< 1	0.01	4	30	14	< 5	< 1	11	< 0.01	< 10	< 10	1	< 10	6
39331	208	294	< 1	< 0.01	6	70	2	< 5	1	14	< 0.01	< 10	< 10	1	< 10	12
39332	208	294	1	< 0.01	4	30	16	< 5	< 1	5	< 0.01	< 10	< 10	2	< 10	4
39333	208	294	< 1	< 0.01	4	150	6	< 5	2	122	< 0.01	< 10	< 10	5	< 10	10
39334	208	294	< 1	0.03	3	50	14	< 5	1	7	< 0.01	< 10	< 10	< 1	< 10	28
39335	208	294	1	0.02	6	20	10	< 5	< 1	35	< 0.01	< 10	< 10	1	< 10	12
39336	208	294	< 1	0.02	3	50	14	< 5	1	6	< 0.01	< 10	< 10	< 1	< 10	28
39337	208	294	< 1	0.03	3	60	18	< 5	1	5	< 0.01	< 10	< 10	< 1	< 10	46
39338	208	294	< 1	0.02	79	200	2	5	7	8	< 0.01	< 10	< 10	37	< 10	32
39339	208	294	1	0.02	3	70	16	< 5	1	5	< 0.01	< 10	< 10	< 1	< 10	28
39340	208	294	1	0.03	2	70	20	< 5	2	7	< 0.01	< 10	< 10	2	< 10	38
39341	208	294	< 1	0.02	9	60	14	< 5	2	6	< 0.01	< 10	< 10	13	< 10	110
39342	208	294	< 1	0.01	166	< 10	< 2	5	6	13	0.04	< 10	< 10	46	< 10	64
39343	208	294	< 1	< 0.01	8	40	< 2	< 5	< 1	3	< 0.01	< 10	< 10	3	< 10	6
39344	208	294	< 1	0.02	3	100	22	< 5	2	22	< 0.01	< 10	< 10	4	< 10	38
39345	208	294	< 1	< 0.01	12	180	< 2	< 5	4	20	< 0.01	< 10	< 10	7	< 10	36
39346	208	294	< 1	0.01	8	100	6	< 5	2	50	< 0.01	< 10	< 10	8	< 10	48
39347	208	294	< 1	0.01	4	150	4	< 5	< 1	6	< 0.01	< 10	< 10	1	< 10	12
39348	208	294	< 1	< 0.01	4	50	< 2	< 5	< 1	44	< 0.01	< 10	< 10	1	< 10	2
39349	208	294	< 1	< 0.01	3	< 10	10	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	8
39350	208	294	< 1	< 0.01	4	20	< 2	< 5	< 1	5	< 0.01	< 10	< 10	< 1	< 10	4
39352	208	294	< 1	< 0.01	25	160	10	< 5	3	24	< 0.01	< 10	< 10	4	< 10	58
39353	208	294	3	< 0.01	29	140	10	< 5	1	26	< 0.01	< 10	< 10	11	< 10	24
39354	208	294	< 1	< 0.01	4	10	6	< 5	< 1	< 1	< 0.01	10	< 10	< 1	< 10	4
39355	208	294	< 1	0.05	2	30	16	< 5	< 1	5	< 0.01	< 10	< 10	1	< 10	8
39356	208	294	< 1	0.03	4	30	14	< 5	< 1	4	< 0.01	< 10	< 10	1	< 10	6

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Page Number : 3-A
Total Pages : 3
Invoice Date: 27-SEP-90
Invoice No. : I-9023250
P.O. Number :

CERTIFICATE OF ANALYSIS A9023250

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
39357	208	294	< 0.002	< 0.2	0.20	< 5	110	< 0.5	< 2	< 0.01	< 0.5	< 1	277	< 1	0.28	< 10	< 1	0.07	< 10	< 0.01	15
39358	208	294	< 0.002	0.2	1.27	140	360	0.5	2	0.07	0.5	1	71	30	1.42	10	< 1	0.28	40	0.18	15
39360	208	294	< 0.002	0.6	3.55	30	440	< 0.5	< 2	0.44	< 0.5	9	480	20	2.37	10	< 1	0.13	< 10	4.07	270
39361	208	294	< 0.002	0.2	0.15	< 5	180	< 0.5	< 2	0.01	< 0.5	1	191	3	0.26	< 10	< 1	< 0.01	< 10	0.05	25
39362	208	294	0.002	0.6	0.39	< 5	360	< 0.5	< 2	0.03	< 0.5	1	276	1	0.48	< 10	< 1	0.14	10	0.09	150
39363	208	294	< 0.002	0.4	0.16	250	110	< 0.5	< 2	2.25	< 0.5	3	345	11	1.42	10	< 1	0.04	< 10	0.03	350
39364	208	294	0.425	5.2	1.09	30	440	< 0.5	< 2	0.07	4.0	35	278	179	>15.00	< 10	< 1	0.07	10	0.23	1410
39365	208	294	0.002	2.0	0.09	160	70	< 0.5	2	0.07	0.5	3	387	3	1.16	< 10	< 1	< 0.01	< 10	0.01	265
39366	208	294	0.002	0.2	0.04	20	40	< 0.5	< 2	2.13	< 0.5	1	348	1	0.82	< 10	< 1	< 0.01	< 10	0.04	195
39367	208	294	< 0.002	< 0.2	0.08	305	70	< 0.5	2	4.86	2.0	4	215	2	1.49	< 10	< 1	< 0.01	< 10	0.15	550
39368	208	294	0.002	< 0.2	3.51	40	1340	< 0.5	< 2	0.46	3.0	50	52	175	>15.00	20	< 1	0.02	20	0.28	370
39369	208	294	< 0.002	0.6	1.71	35	320	0.5	4	0.11	< 0.5	2	96	11	1.05	10	< 1	0.32	40	0.28	25
39370	208	294	< 0.002	< 0.2	0.49	5	50	< 0.5	2	3.08	< 0.5	2	221	4	1.19	< 10	< 1	< 0.01	< 10	0.28	375
39371	208	294	< 0.002	1.0	1.16	5	790	< 0.5	< 2	0.09	0.5	2	103	7	1.03	10	< 1	0.41	50	0.09	275
39372	208	294	< 0.002	< 0.2	0.17	< 5	100	< 0.5	< 2	0.13	< 0.5	3	299	9	0.73	< 10	< 1	0.02	< 10	0.06	370
39373	208	294	< 0.002	0.2	0.14	< 5	30	< 0.5	< 2	0.01	< 0.5	1	457	2	0.51	< 10	< 1	< 0.01	< 10	0.01	65
39374	208	294	< 0.002	0.4	0.88	< 5	160	< 0.5	< 2	0.02	< 0.5	< 1	206	3	0.28	< 10	< 1	0.12	10	0.03	15
39375	208	294	0.078	14.4	0.03	< 5	1070	< 0.5	6	< 0.01	3.0	1	512	4	0.99	< 10	1	< 0.01	< 10	< 0.01	50
39376	208	294	< 0.002	1.0	0.91	5	670	< 0.5	< 2	0.06	< 0.5	1	142	12	0.75	10	< 1	0.37	40	0.07	165
39377	208	294	< 0.002	0.6	0.62	< 5	360	< 0.5	2	0.23	< 0.5	10	490	< 1	1.43	< 10	< 1	0.06	10	1.77	355
39378	208	294	< 0.002	0.2	3.26	10	370	< 0.5	< 2	0.12	< 0.5	11	707	28	2.25	< 10	< 1	0.20	< 10	3.45	215
39379	208	294	< 0.002	0.4	3.02	10	350	< 0.5	< 2	0.54	< 0.5	9	433	19	1.75	< 10	< 1	0.20	< 10	2.47	180
39380	208	294	< 0.002	< 0.2	0.19	< 5	130	< 0.5	< 2	0.01	< 0.5	3	291	1	1.21	< 10	< 1	0.01	< 10	0.08	125
39381	208	294	< 0.002	< 0.2	1.62	40	150	< 0.5	< 2	0.31	< 0.5	97	3470	14	8.46	10	< 1	< 0.01	< 10	8.64	690
39382	208	294	< 0.002	< 0.2	0.52	85	240	< 0.5	< 2	1.58	< 0.5	12	320	18	3.43	< 10	< 1	0.19	20	0.28	725
39383	208	294	0.028	25.4	0.05	< 5	4010	< 0.5	34	0.01	< 0.5	2	207	33	0.59	< 10	< 1	< 0.01	< 10	0.06	25

CERTIFICATION: B. Caughlin

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Invoice Date: 27-SEP-90
Invoice No. : I-9023250
P.O. Number :

CERTIFICATE OF ANALYSIS A9023250

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
39357	208	294	< 1	0.01	3	10	6	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	4
39358	208	294	2	0.03	4	370	52	< 5	3	29	< 0.01	< 10	< 10	14	< 10	32
39360	208	294	< 1	0.02	135	20	< 2	< 5	7	29	0.07	< 10	< 10	37	< 10	62
39361	208	294	< 1	< 0.01	4	20	4	< 5	< 1	3	< 0.01	< 10	< 10	6	< 10	2
39362	208	294	< 1	0.01	6	20	14	< 5	1	3	< 0.01	< 10	< 10	2	< 10	26
39363	208	294	1	< 0.01	7	3520	2	< 5	2	22	< 0.01	10	< 10	7	< 10	16
39364	208	294	10	< 0.01	50	1440	16	5	11	24	< 0.01	< 10	< 10	< 1	< 10	1930
39365	208	294	1	< 0.01	7	70	236	< 5	1	2	< 0.01	< 10	< 10	3	< 10	50
39366	208	294	1	< 0.01	5	20	6	< 5	1	11	< 0.01	10	< 10	2	< 10	14
39367	208	294	1	0.01	3	20	26	< 5	2	35	< 0.01	< 10	< 10	2	< 10	52
39368	208	294	2	0.04	108	4170	< 2	5	29	44	0.07	< 10	< 10	129	< 10	1045
39369	208	294	< 1	0.03	4	250	24	< 5	3	20	< 0.01	< 10	< 10	10	< 10	42
39370	208	294	< 1	< 0.01	5	180	4	< 5	1	81	< 0.01	< 10	< 10	7	< 10	22
39371	208	294	< 1	0.01	3	90	64	< 5	5	11	< 0.01	< 10	< 10	5	< 10	92
39372	208	294	< 1	< 0.01	9	330	14	< 5	1	4	< 0.01	< 10	< 10	3	< 10	16
39373	208	294	< 1	< 0.01	17	30	2	< 5	< 1	1	< 0.01	< 10	< 10	2	< 10	8
39374	208	294	< 1	< 0.01	7	50	18	< 5	2	4	0.01	< 10	< 10	5	< 10	8
39375	208	294	< 1	< 0.01	5	10	282	< 5	< 1	13	< 0.01	< 10	< 10	1	< 10	228
39376	208	294	< 1	0.01	2	70	46	< 5	3	8	< 0.01	< 10	< 10	3	< 10	78
39377	208	294	< 1	0.01	124	100	16	< 5	2	20	0.07	< 10	< 10	16	< 10	16
39378	208	294	< 1	0.01	152	10	< 2	5	6	9	0.04	< 10	< 10	40	< 10	60
39379	208	294	< 1	0.02	73	170	4	< 5	6	43	0.05	< 10	< 10	33	< 10	40
39380	208	294	< 1	< 0.01	9	30	2	< 5	< 1	4	< 0.01	< 10	< 10	2	< 10	48
39381	208	294	< 1	< 0.01	1940	< 10	< 2	10	14	20	0.01	< 10	< 10	40	< 10	376
39382	208	294	< 1	0.04	65	500	2	< 5	8	19	< 0.01	< 10	< 10	15	< 10	82
39383	208	294	< 1	< 0.01	19	10	1265	10	< 1	254	< 0.01	< 10	< 10	< 1	< 10	48

CERTIFICATION: B. Caglione

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

A9023700

Comments: ATTN: LARRY McLEAN CC: A. TROUP

CERTIFICATE A9023700

ARBOR RESOURCES INC.

Project: AORDAW
P.O. # :

Samples submitted to our lab in Vancouver, BC.
This report was printed on 3-OCT-90.

SAMPLE PREPARATION

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION
208	192	Assay ring to approx 150 mesh
294	192	Crush and split (0-10 pounds)
238	192	NITRIC-AQUA REGIA DIGESTION
* NOTE	1:	

The 32 element ICP package is suitable for trace metals in soil and rock samples. Elements for which the nitric-aqua regia digestion is possibly incomplete are: Al, Ba, Be, Ca, Cr, Ga, K, La, Mg, Na, Sr, Ti, Tl, W.

ANALYTICAL PROCEDURES

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION	METHOD	DETECTION LIMIT	UPPER LIMIT
398	192	Au oz/T: 1/2 assay ton	FA-AAS	0.002	20.00
922	192	Ag ppm: 32 element, soil & rock	ICP-AES	0.2	200
921	192	Al %: 32 element, soil & rock	ICP-AES	0.01	15.00
923	192	As ppm: 32 element, soil & rock	ICP-AES	5	10000
924	192	Ba ppm: 32 element, soil & rock	ICP-AES	10	10000
925	192	Be ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
926	192	Bi ppm: 32 element, soil & rock	ICP-AES	2	10000
927	192	Ca %: 32 element, soil & rock	ICP-AES	0.01	15.00
928	192	Cd ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
929	192	Co ppm: 32 element, soil & rock	ICP-AES	1	10000
930	192	Cr ppm: 32 element, soil & rock	ICP-AES	1	10000
931	192	Cu ppm: 32 element, soil & rock	ICP-AES	1	10000
932	192	Fe %: 32 element, soil & rock	ICP-AES	0.01	15.00
933	192	Ga ppm: 32 element, soil & rock	ICP-AES	10	10000
951	192	Hg ppm: 32 element, soil & rock	ICP-AES	1	10000
934	192	K %: 32 element, soil & rock	ICP-AES	0.01	10.00
935	192	La ppm: 32 element, soil & rock	ICP-AES	10	10000
936	192	Mg %: 32 element, soil & rock	ICP-AES	0.01	15.00
937	192	Mn ppm: 32 element, soil & rock	ICP-AES	5	10000
938	192	Mo ppm: 32 element, soil & rock	ICP-AES	1	10000
939	192	Na %: 32 element, soil & rock	ICP-AES	0.01	5.00
940	192	Ni ppm: 32 element, soil & rock	ICP-AES	1	10000
941	192	P ppm: 32 element, soil & rock	ICP-AES	10	10000
942	192	Pb ppm: 32 element, soil & rock	ICP-AES	2	10000
943	192	Sb ppm: 32 element, soil & rock	ICP-AES	5	10000
958	192	Sc ppm: 32 elements, soil & rock	ICP-AES	1	10000
944	192	Sr ppm: 32 element, soil & rock	ICP-AES	1	10000
945	192	Ti %: 32 element, soil & rock	ICP-AES	0.01	5.00
946	192	Tl ppm: 32 element, soil & rock	ICP-AES	10	10000
947	192	U ppm: 32 element, soil & rock	ICP-AES	10	10000
948	192	V ppm: 32 element, soil & rock	ICP-AES	1	10000
949	192	W ppm: 32 element, soil & rock	ICP-AES	10	10000
950	192	Zn ppm: 32 element, soil & rock	ICP-AES	2	10000

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Page Number : 1-A
Total Pages : 5
Invoice Date: 3-OCT-90
Invoice No. : I-9023700
P.O. Number :

Project : AORDAW
Comments: ATTN: LARRY McLEAN CC: A. TROUP

CERTIFICATE OF ANALYSIS A9023700

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
1858	208	294	< 0.002	0.2	0.80	< 5	1080	< 0.5	< 2	1.19	< 0.5	4	139	< 1	1.49	10	< 1	0.36	20	0.27	225
1859	208	294	0.002	0.2	0.76	5	320	< 0.5	< 2	0.16	< 0.5	4	208	< 1	2.02	< 10	< 1	0.17	10	0.20	125
1860	208	294	< 0.002	< 0.2	1.98	< 5	620	< 0.5	< 2	0.59	< 0.5	6	115	< 1	3.27	< 10	< 1	0.36	20	0.91	210
1861	208	294	< 0.002	< 0.2	0.09	< 5	40	< 0.5	< 2	0.03	< 0.5	1	413	< 1	0.49	< 10	< 1	< 0.01	< 10	0.02	40
1862	208	294	< 0.002	< 0.2	2.01	5	470	< 0.5	< 2	1.15	0.5	10	129	16	3.90	< 10	< 1	0.34	20	1.01	350
1863	208	294	0.004	< 0.2	1.19	< 5	550	< 0.5	< 2	1.94	0.5	5	142	< 1	3.07	< 10	< 1	0.37	20	0.59	580
1864	208	294	< 0.002	< 0.2	1.69	< 5	550	< 0.5	< 2	1.10	< 0.5	6	125	< 1	3.03	< 10	< 1	0.29	20	0.64	455
1865	208	294	0.002	< 0.2	1.03	< 5	410	< 0.5	< 2	0.89	< 0.5	3	203	< 1	2.25	< 10	< 1	0.22	20	0.36	385
1866	208	294	< 0.002	< 0.2	1.31	< 5	710	< 0.5	< 2	1.23	< 0.5	5	158	< 1	2.14	10	< 1	0.14	10	0.50	480
1867	208	294	0.002	0.2	0.64	15	320	< 0.5	< 2	0.06	< 0.5	1	213	< 1	1.15	< 10	< 1	0.47	20	0.05	55
1868	208	294	0.011	0.4	0.24	< 5	260	< 0.5	< 2	0.03	< 0.5	1	348	1	0.55	< 10	< 1	0.17	< 10	0.02	35
1869	208	294	< 0.002	0.2	0.47	< 5	310	< 0.5	< 2	0.06	< 0.5	1	261	1	0.81	< 10	< 1	0.37	10	0.03	45
1870	208	294	< 0.002	0.2	0.54	5	330	< 0.5	2	0.06	< 0.5	1	160	< 1	0.73	< 10	< 1	0.48	20	0.04	45
1871	208	294	< 0.002	0.4	0.65	10	360	< 0.5	2	0.07	< 0.5	1	166	< 1	0.98	10	< 1	0.50	30	0.06	60
1872	208	294	< 0.002	< 0.2	4.15	15	340	< 0.5	< 2	3.01	1.0	28	56	15	5.64	20	< 1	0.14	10	2.82	750
1873	208	294	< 0.002	< 0.2	4.61	< 5	630	< 0.5	< 2	2.24	1.0	35	53	18	7.04	20	< 1	0.18	20	3.95	715
1874	208	294	< 0.002	0.4	0.74	< 5	260	< 0.5	< 2	0.14	< 0.5	2	78	< 1	1.48	10	< 1	0.49	20	0.19	100
1875	208	294	< 0.002	1.0	0.41	< 5	1200	< 0.5	2	0.03	< 0.5	1	219	1	0.71	< 10	< 1	0.38	20	0.04	35
1877	208	294	0.020	1.0	0.43	< 5	500	< 0.5	< 2	0.02	< 0.5	1	217	< 1	0.86	< 10	< 1	0.40	20	0.04	35
1878	208	294	0.004	0.8	0.60	< 5	770	< 0.5	2	0.03	< 0.5	1	155	< 1	1.07	< 10	< 1	0.46	30	0.05	45
1879	208	294	0.002	1.0	0.39	< 5	450	0.5	2	0.02	< 0.5	1	135	3	0.63	< 10	< 1	0.44	30	0.03	20
1880	208	294	0.065	1.4	0.25	< 5	460	0.5	< 2	0.01	< 0.5	< 1	231	< 1	0.62	< 10	< 1	0.30	10	0.01	20
1881	208	294	0.002	0.6	0.04	< 5	230	< 0.5	< 2	< 0.01	< 0.5	< 1	408	< 1	0.42	< 10	< 1	< 0.01	< 10	< 0.01	25
1882	208	294	< 0.002	0.8	0.80	< 5	360	< 0.5	2	0.14	< 0.5	1	170	1	0.77	< 10	< 1	0.18	10	0.40	55
1883	208	294	< 0.002	0.8	0.95	< 5	930	< 0.5	2	0.32	< 0.5	1	210	< 1	1.04	10	< 1	0.29	20	0.43	55
1884	208	294	< 0.002	0.4	0.89	< 5	610	< 0.5	2	0.15	< 0.5	1	210	< 1	0.94	10	< 1	0.27	10	0.29	50
1885	208	294	< 0.002	0.6	0.77	5	880	< 0.5	4	0.11	< 0.5	1	177	< 1	0.94	10	< 1	0.29	10	0.17	55
1886	208	294	< 0.002	0.8	0.74	< 5	760	< 0.5	2	0.33	< 0.5	1	152	< 1	0.91	10	< 1	0.31	30	0.20	55
1888	208	294	< 0.002	0.2	0.58	< 5	710	< 0.5	< 2	0.05	< 0.5	1	211	2	0.82	< 10	< 1	0.25	20	0.09	40
1889	208	294	< 0.002	0.2	0.42	5	670	< 0.5	< 2	0.04	< 0.5	< 1	133	1	0.60	< 10	< 1	0.21	20	0.04	20
1890	208	294	< 0.002	< 0.2	0.42	5	420	< 0.5	< 2	0.05	< 0.5	< 1	142	1	0.69	< 10	< 1	0.20	10	0.04	20
1891	208	294	< 0.002	< 0.2	0.42	< 5	400	< 0.5	< 2	0.04	< 0.5	1	193	2	0.65	< 10	< 1	0.23	10	0.04	25
1892	208	294	< 0.002	< 0.2	0.49	5	480	< 0.5	< 2	0.04	< 0.5	< 1	206	3	0.78	< 10	< 1	0.27	20	0.04	35
1893	208	294	< 0.002	< 0.2	0.44	5	510	< 0.5	< 2	0.05	< 0.5	< 1	236	1	0.67	< 10	< 1	0.17	10	0.04	35
1894	208	294	< 0.002	< 0.2	0.50	5	540	< 0.5	< 2	0.03	< 0.5	< 1	182	1	0.59	< 10	< 1	0.25	10	0.05	25
1895	208	294	< 0.002	0.2	0.38	< 5	580	< 0.5	< 2	0.01	< 0.5	< 1	190	< 1	0.35	< 10	< 1	0.41	20	0.02	35
1896	208	294	< 0.002	0.2	0.51	5	570	< 0.5	< 2	0.02	< 0.5	1	171	2	0.69	< 10	< 1	0.42	20	0.06	50
1897	208	294	< 0.002	0.2	0.56	5	2260	< 0.5	< 2	0.03	< 0.5	1	192	1	0.71	< 10	< 1	0.36	30	0.08	70
1898	208	294	< 0.002	0.4	0.38	10	3600	< 0.5	2	0.03	< 0.5	1	259	2	0.59	< 10	< 1	0.21	20	0.03	45
1899	208	294	< 0.002	0.6	0.50	5	860	< 0.5	2	0.03	< 0.5	< 1	225	1	0.63	< 10	< 1	0.26	20	0.04	45

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Invoice Date: 3-OCT-90
Invoice No. : I-9023700
P.O. Number :

Project : AORDAW
Comments: ATTN: LARRY McLEAN CC: A. TROUP

CERTIFICATE OF ANALYSIS A9023700

SAMPLE DESCRIPTION	PREP CODE	Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
1858	208 294	< 1	0.02	1	300	14	< 5	3	65	< 0.01	< 10	< 10	3	< 10	52
1859	208 294	< 1	0.04	3	350	6	< 5	5	13	< 0.01	< 10	< 10	11	< 10	46
1860	208 294	< 1	0.03	3	460	10	< 5	6	36	< 0.01	< 10	< 10	10	< 10	70
1861	208 294	< 1	< 0.01	4	20	4	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	2
1862	208 294	< 1	0.03	4	430	20	< 5	5	84	< 0.01	< 10	< 10	8	< 10	82
1863	208 294	< 1	0.04	2	500	10	< 5	6	121	< 0.01	< 10	< 10	9	< 10	90
1864	208 294	< 1	0.05	3	480	8	< 5	6	70	0.02	< 10	< 10	13	< 10	78
1865	208 294	< 1	0.06	3	410	2	< 5	5	64	0.01	< 10	< 10	11	< 10	52
1866	208 294	< 1	0.08	3	480	6	< 5	5	87	0.09	< 10	< 10	15	< 10	74
1867	208 294	1	0.01	3	120	20	< 5	1	9	< 0.01	< 10	< 10	2	< 10	20
1868	208 294	< 1	0.01	3	50	12	< 5	< 1	4	< 0.01	< 10	< 10	1	< 10	8
1869	208 294	< 1	0.02	2	100	4	< 5	2	8	0.01	< 10	< 10	4	< 10	24
1870	208 294	< 1	0.02	1	120	10	< 5	1	6	< 0.01	< 10	< 10	2	< 10	24
1871	208 294	< 1	0.03	2	140	16	< 5	3	7	< 0.01	< 10	< 10	3	< 10	32
1872	208 294	< 1	0.38	31	980	< 2	5	18	206	0.16	< 10	< 10	123	< 10	84
1873	208 294	< 1	0.15	41	1240	< 2	< 5	16	190	0.08	< 10	< 10	150	< 10	102
1874	208 294	< 1	0.02	1	150	12	< 5	3	14	0.03	< 10	< 10	8	< 10	38
1875	208 294	< 1	0.02	2	70	4	< 5	1	9	< 0.01	< 10	< 10	2	< 10	10
1877	208 294	< 1	0.01	2	80	12	< 5	1	6	< 0.01	< 10	< 10	2	< 10	18
1878	208 294	< 1	0.01	1	110	12	< 5	2	9	< 0.01	< 10	< 10	2	< 10	28
1879	208 294	< 1	0.01	2	70	6	< 5	1	6	< 0.01	< 10	< 10	1	< 10	10
1880	208 294	< 1	< 0.01	2	40	6	< 5	< 1	3	< 0.01	< 10	< 10	1	< 10	6
1881	208 294	< 1	< 0.01	5	10	2	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	2
1882	208 294	< 1	0.03	3	80	10	< 5	2	16	< 0.01	< 10	< 10	< 1	< 10	68
1883	208 294	< 1	0.03	2	70	18	< 5	3	43	< 0.01	< 10	< 10	1	< 10	66
1884	208 294	< 1	0.04	3	80	14	< 5	3	35	< 0.01	< 10	< 10	< 1	< 10	54
1885	208 294	< 1	0.04	2	80	18	< 5	4	27	< 0.01	< 10	< 10	1	< 10	64
1886	208 294	< 1	0.03	2	70	12	< 5	3	38	< 0.01	< 10	< 10	< 1	< 10	56
1888	208 294	< 1	0.05	2	80	12	< 5	3	11	< 0.01	< 10	< 10	< 1	< 10	38
1889	208 294	< 1	0.03	1	60	12	< 5	3	10	< 0.01	< 10	< 10	< 1	< 10	20
1890	208 294	< 1	0.04	1	60	26	< 5	3	10	< 0.01	< 10	< 10	< 1	< 10	24
1891	208 294	< 1	0.03	3	50	16	< 5	3	7	< 0.01	< 10	< 10	< 1	< 10	18
1892	208 294	< 1	0.03	2	50	14	< 5	3	6	< 0.01	< 10	< 10	< 1	< 10	24
1893	208 294	< 1	0.03	3	50	12	< 5	3	12	< 0.01	< 10	< 10	< 1	< 10	20
1894	208 294	< 1	0.03	2	60	8	< 5	2	6	< 0.01	< 10	< 10	< 1	< 10	20
1895	208 294	< 1	0.03	2	50	12	< 5	1	6	< 0.01	< 10	< 10	< 1	< 10	14
1896	208 294	< 1	0.02	2	80	20	< 5	2	5	< 0.01	< 10	< 10	< 1	< 10	34
1897	208 294	< 1	0.01	3	80	24	< 5	3	17	< 0.01	< 10	< 10	< 1	< 10	38
1898	208 294	< 1	0.02	3	50	14	< 5	1	26	< 0.01	< 10	< 10	1	< 10	26
1899	208 294	< 1	0.04	3	60	14	< 5	2	7	< 0.01	10	< 10	< 1	< 10	32

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Invoice Date: 3-OCT-90
Invoice No. : I-9023700
P.O. Number :

Project : AORDAW
Comments: ATTN: LARRY McLEAN CC: A. TROUP

CERTIFICATE OF ANALYSIS A9023700

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
1900	208	294	< 0.002	0.4	0.59	15	750	< 0.5	< 2	0.03	< 0.5	< 1	105	1	0.75	< 10	< 1	0.31	20	0.07	55
24477	208	294	< 0.002	0.2	0.46	< 5	380	< 0.5	< 2	0.03	< 0.5	1	227	1	0.63	< 10	< 1	0.25	10	0.07	60
24478	208	294	< 0.002	0.6	0.58	5	400	< 0.5	< 2	0.04	< 0.5	1	157	7	0.85	< 10	< 1	0.25	10	0.15	45
24479	208	294	< 0.002	1.0	0.71	< 5	2060	< 0.5	2	0.04	0.5	1	164	5	1.22	< 10	< 1	0.35	10	0.16	45
24480	208	294	0.010	0.4	0.29	< 5	260	< 0.5	< 2	0.01	< 0.5	< 1	192	< 1	0.44	< 10	< 1	0.15	10	0.06	25
24481	208	294	0.189	0.4	0.22	< 5	240	< 0.5	< 2	< 0.01	< 0.5	< 1	292	< 1	0.39	< 10	< 1	0.13	< 10	0.02	20
24482	208	294	0.006	1.0	0.84	< 5	490	< 0.5	< 2	0.04	< 0.5	1	142	9	1.03	< 10	< 1	0.29	20	0.32	45
24483	208	294	< 0.002	0.8	0.96	< 5	630	< 0.5	< 2	0.05	0.5	1	167	9	1.13	< 10	< 1	0.32	10	0.42	55
24484	208	294	0.021	3.8	0.43	5	320	< 0.5	< 2	0.03	< 0.5	1	144	4	0.66	< 10	< 1	0.17	10	0.17	35
24485	208	294	0.060	14.2	0.11	5	200	< 0.5	< 2	< 0.01	2.0	< 1	241	4	1.05	< 10	< 1	0.03	< 10	0.01	30
24486	208	294	0.024	1.8	0.68	< 5	570	< 0.5	< 2	0.24	0.5	1	101	4	0.97	10	< 1	0.39	30	0.13	55
24487	208	294	< 0.002	1.2	0.84	5	570	< 0.5	< 2	0.04	0.5	1	112	10	1.09	10	< 1	0.38	20	0.27	45
24488	208	294	< 0.002	3.8	0.95	5	710	< 0.5	< 2	0.15	< 0.5	1	83	19	1.08	< 10	< 1	0.32	30	0.37	55
24489	208	294	< 0.002	3.0	0.90	5	650	< 0.5	< 2	0.13	< 0.5	1	108	14	1.05	10	< 1	0.34	20	0.31	50
24490	208	294	< 0.002	0.6	4.54	30	640	< 0.5	< 2	0.74	1.0	21	57	17	4.89	10	< 1	0.21	20	1.60	435
24491	208	294	< 0.002	< 0.2	3.88	< 5	280	< 0.5	< 2	1.55	0.5	30	39	21	5.53	10	< 1	0.12	20	2.48	420
24492	208	294	< 0.002	0.8	1.81	< 5	440	< 0.5	< 2	0.48	< 0.5	9	70	15	2.57	10	< 1	0.25	20	0.99	170
24493	208	294	< 0.002	0.4	0.68	5	410	< 0.5	< 2	0.11	< 0.5	5	144	5	1.38	< 10	< 1	0.30	10	0.13	90
24494	208	294	1.248	2.2	0.10	< 5	100	< 0.5	< 2	0.01	< 0.5	< 1	100	2	0.73	< 10	< 1	0.03	< 10	0.02	35
24495	208	294	0.002	0.8	0.46	35	770	< 0.5	< 2	0.02	< 0.5	1	84	3	0.98	< 10	< 1	0.29	10	0.04	40
24496	208	294	< 0.002	0.2	0.70	< 5	400	< 0.5	< 2	0.32	< 0.5	2	130	1	1.46	< 10	< 1	0.28	10	0.25	175
24497	208	294	< 0.002	< 0.2	1.19	5	400	< 0.5	< 2	0.25	0.5	5	99	5	2.34	10	< 1	0.26	20	0.30	150
24498	208	294	< 0.002	0.2	1.29	10	550	< 0.5	2	0.24	< 0.5	6	83	8	2.66	10	< 1	0.29	20	0.36	175
24499	208	294	< 0.002	0.2	1.37	< 5	970	< 0.5	2	1.51	0.5	6	62	6	2.42	10	< 1	0.24	20	0.82	285
24500	208	294	< 0.002	0.2	1.21	< 5	630	< 0.5	< 2	1.17	< 0.5	6	110	6	2.14	10	< 1	0.28	20	0.58	260
37801	208	294	0.121	2.8	0.11	< 5	580	< 0.5	2	0.48	< 0.5	1	236	1	0.74	< 10	< 1	0.02	< 10	0.25	250
37802	208	294	< 0.002	0.6	0.55	< 5	250	< 0.5	< 2	0.10	< 0.5	1	47	6	0.74	10	< 1	0.24	40	0.27	75
37803	208	294	< 0.002	0.6	0.51	< 5	420	< 0.5	< 2	0.19	< 0.5	1	86	4	0.51	10	< 1	0.33	40	0.16	80
37804	208	294	< 0.002	0.4	0.58	60	610	< 0.5	2	0.09	0.5	19	467	19	1.41	< 10	< 1	0.16	20	0.14	255
37805	208	294	< 0.002	0.4	0.99	< 5	1050	< 0.5	< 2	1.43	0.5	10	114	25	3.00	10	< 1	0.53	40	0.95	560
38956	208	294	< 0.002	0.8	0.77	< 5	580	< 0.5	2	0.08	< 0.5	1	99	3	0.66	10	< 1	0.40	30	0.08	185
39222	208	294	< 0.002	0.2	0.37	5	580	< 0.5	< 2	0.04	< 0.5	< 1	158	1	0.45	< 10	< 1	0.27	10	0.04	45
39223	208	294	< 0.002	0.4	0.40	< 5	570	< 0.5	< 2	0.03	< 0.5	< 1	95	1	0.49	< 10	< 1	0.30	20	0.04	35
39224	208	294	0.004	0.2	0.39	10	610	< 0.5	< 2	0.02	< 0.5	< 1	172	1	0.70	< 10	< 1	0.28	20	0.03	30
39226	208	294	< 0.002	0.2	0.31	< 5	430	< 0.5	< 2	0.02	< 0.5	< 1	154	1	0.45	< 10	< 1	0.23	10	0.03	25
39227	208	294	< 0.002	0.4	0.49	< 5	680	< 0.5	2	0.03	< 0.5	< 1	125	2	0.71	< 10	< 1	0.32	20	0.06	35
39228	208	294	< 0.002	0.4	0.42	< 5	500	< 0.5	< 2	0.03	< 0.5	< 1	105	1	0.58	< 10	< 1	0.29	20	0.04	35
39230	208	294	< 0.002	0.2	0.44	< 5	910	< 0.5	< 2	0.03	< 0.5	< 1	88	1	0.68	< 10	< 1	0.28	20	0.04	25
39231	208	294	< 0.002	0.2	0.46	< 5	1360	< 0.5	2	0.03	< 0.5	< 1	79	1	0.77	< 10	< 1	0.24	30	0.06	35
39232	208	294	< 0.002	0.4	0.40	< 5	710	< 0.5	2	0.02	< 0.5	< 1	71	1	0.68	< 10	< 1	0.27	20	0.04	25

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AORDAW
Comments: ATTN: LARRY McLEAN CC: A. TROUP

Invoice Date: 3-OCT-90
Invoice No. : I-9023700
P.O. Number :

CERTIFICATE OF ANALYSIS A9023700

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
39233	208	294	< 0.002	0.4	0.73	< 5	870	< 0.5	2	0.04	< 0.5	< 1	66	1	0.79	< 10	< 1	0.42	20	0.07	30
39235	208	294	< 0.002	0.2	0.43	< 5	560	< 0.5	< 2	0.13	< 0.5	< 1	70	< 1	0.56	< 10	< 1	0.20	20	0.12	40
39237	208	294	< 0.002	< 0.2	0.14	< 5	140	< 0.5	2	0.01	< 0.5	< 1	416	< 1	0.43	< 10	< 1	0.03	< 10	0.01	25
39238	208	294	< 0.002	0.4	0.21	5	400	< 0.5	2	0.01	< 0.5	< 1	143	< 1	0.41	< 10	< 1	0.13	10	0.02	25
39239	208	294	< 0.002	0.6	0.26	< 5	420	< 0.5	2	0.01	< 0.5	< 1	339	< 1	0.51	< 10	< 1	0.12	< 10	0.02	30
39240	208	294	< 0.002	0.4	0.15	< 5	750	< 0.5	2	0.01	< 0.5	< 1	253	1	0.44	< 10	< 1	0.09	< 10	0.02	25
39241	208	294	0.006	0.8	0.26	< 5	310	< 0.5	< 2	0.01	< 0.5	< 1	373	< 1	0.56	< 10	< 1	0.11	< 10	0.01	25
39242	208	294	0.002	0.4	0.14	< 5	170	< 0.5	2	0.01	< 0.5	< 1	257	1	0.50	< 10	< 1	0.07	< 10	0.01	25
39244	208	294	0.004	0.2	0.56	45	570	< 0.5	2	0.07	< 0.5	1	237	1	0.52	< 10	< 1	0.30	20	0.05	105
39245	208	294	0.002	0.2	0.10	40	170	< 0.5	< 2	0.01	< 0.5	< 1	220	1	0.37	< 10	< 1	0.04	< 10	0.01	40
39246	208	294	< 0.002	0.4	0.59	75	620	< 0.5	2	0.02	0.5	< 1	186	1	0.51	< 10	< 1	0.37	20	0.04	70
39247	208	294	< 0.002	0.6	0.37	60	840	< 0.5	< 2	0.03	0.5	< 1	95	< 1	0.43	< 10	< 1	0.31	30	0.02	60
39248	208	294	< 0.002	0.6	0.63	30	570	0.5	2	0.16	< 0.5	< 1	116	1	0.52	< 10	< 1	0.45	30	0.05	85
39250	208	294	0.002	0.8	0.39	30	340	< 0.5	2	0.70	< 0.5	< 1	100	< 1	0.48	10	< 1	0.31	40	0.03	75
39251	208	294	< 0.002	0.6	1.11	< 5	720	1.0	2	0.53	< 0.5	10	108	20	1.97	10	< 1	0.82	30	0.51	300
39252	208	294	< 0.002	0.4	0.44	5	290	1.0	2	0.07	< 0.5	1	118	9	0.92	< 10	< 1	0.19	30	0.07	55
39253	208	294	< 0.002	0.6	0.63	5	320	0.5	2	0.04	< 0.5	1	164	13	1.04	< 10	< 1	0.51	20	0.15	55
39254	208	294	0.002	0.6	0.48	< 5	1160	< 0.5	2	0.02	< 0.5	1	105	4	0.73	< 10	< 1	0.25	20	0.33	90
39255	208	294	< 0.002	0.6	0.69	< 5	1360	0.5	2	0.02	< 0.5	1	201	3	0.75	< 10	< 1	0.37	20	0.35	90
39256	208	294	0.069	2.4	0.05	< 5	70	< 0.5	2	< 0.01	< 0.5	< 1	295	1	0.39	< 10	< 1	< 0.01	< 10	0.01	15
39257	208	294	0.029	2.0	0.24	5	690	< 0.5	< 2	0.03	0.5	1	154	3	1.21	< 10	< 1	0.19	< 10	0.02	45
39258	208	294	0.002	0.2	0.25	435	160	< 0.5	< 2	0.03	< 0.5	< 1	150	3	0.66	< 10	< 1	0.19	10	0.08	75
39259	208	294	< 0.002	0.2	0.45	450	220	< 0.5	2	0.09	< 0.5	1	271	5	0.88	< 10	< 1	0.25	10	0.11	110
39260	208	294	< 0.002	< 0.2	0.12	25	120	< 0.5	< 2	< 0.01	< 0.5	< 1	200	< 1	0.44	< 10	< 1	0.09	< 10	< 0.01	55
39263	208	294	0.002	0.4	0.55	90	450	0.5	< 2	0.02	0.5	< 1	179	1	0.54	< 10	< 1	0.49	40	0.03	65
39264	208	294	0.008	0.6	0.07	5	110	< 0.5	< 2	< 0.01	< 0.5	< 1	256	1	0.38	< 10	< 1	0.02	< 10	< 0.01	30
39265	208	294	< 0.002	< 0.2	0.43	10	400	< 0.5	< 2	0.05	< 0.5	< 1	157	1	0.79	< 10	< 1	0.36	20	0.02	45
39266	208	294	< 0.002	< 0.2	0.05	< 5	100	< 0.5	2	< 0.01	< 0.5	< 1	286	< 1	0.33	< 10	< 1	< 0.01	< 10	< 0.01	25
39267	208	294	0.017	>200	0.06	5	2890	< 0.5	< 2	0.04	9.5	1	359	482	0.50	< 10	< 1	< 0.01	< 10	0.01	35
39268	208	294	< 0.002	5.8	0.17	< 5	3770	< 0.5	< 2	3.52	< 0.5	1	250	9	0.64	< 10	< 1	0.02	< 10	0.10	430
39269	208	294	0.006	3.0	0.02	< 5	520	< 0.5	2	0.04	1.0	< 1	418	3	0.49	< 10	< 1	< 0.01	< 10	< 0.01	30
39270	208	294	< 0.002	< 0.2	0.07	20	170	< 0.5	< 2	0.05	< 0.5	3	368	4	0.95	< 10	< 1	< 0.01	< 10	0.02	555
39301	208	294	< 0.002	0.6	0.57	135	460	< 0.5	< 2	0.04	< 0.5	1	217	3	0.53	< 10	< 1	0.38	30	0.05	85
39302	208	294	0.002	0.6	0.36	90	650	< 0.5	< 2	0.49	< 0.5	1	177	2	0.51	< 10	< 1	0.29	20	0.06	250
39303	208	294	< 0.002	< 0.2	2.65	35	900	< 0.5	< 2	2.80	< 0.5	24	113	21	5.02	20	< 1	0.16	20	2.22	775
39304	208	294	0.002	0.6	0.41	85	310	< 0.5	< 2	0.22	< 0.5	1	121	1	0.56	< 10	< 1	0.34	40	0.07	295
39305	208	294	0.002	0.6	0.57	170	400	< 0.5	< 2	0.14	< 0.5	2	150	5	0.78	< 10	< 1	0.26	40	0.22	125
39306	208	294	0.002	0.8	1.78	160	3190	< 0.5	2	0.62	< 0.5	7	113	12	1.84	10	< 1	0.54	30	0.40	495
39307	208	294	0.002	0.2	2.05	130	960	< 0.5	< 2	0.41	< 0.5	10	139	9	2.93	10	< 1	0.38	30	1.03	490
39308	208	294	0.002	0.6	0.33	315	250	< 0.5	< 2	0.05	< 0.5	< 1	138	2	0.57	< 10	< 1	0.25	30	0.05	75

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Invoice Date: 3-OCT-90
Invoice No. : I-9023700
P.O. Number :

Project : AORDAW
Comments: ATTN: LARRY McLEAN CC: A. TROUP

CERTIFICATE OF ANALYSIS A9023700

SAMPLE DESCRIPTION	PREP CODE	Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
39233	208 294	< 1	0.06	< 1	70	18	< 5	4	8	< 0.01	< 10	< 10	1	< 10	38
39235	208 294	1	0.02	2	60	10	< 5	2	14	< 0.01	< 10	< 10	< 1	< 10	32
39237	208 294	< 1	0.01	3	10	6	< 5	< 1	1	< 0.01	< 10	10	1	< 10	4
39238	208 294	< 1	0.01	3	20	14	< 5	< 1	3	< 0.01	< 10	< 10	< 1	< 10	16
39239	208 294	1	0.01	4	20	6	< 5	< 1	3	< 0.01	< 10	< 10	1	< 10	10
39240	208 294	1	< 0.01	4	20	6	< 5	< 1	5	< 0.01	< 10	10	< 1	< 10	14
39241	208 294	< 1	0.03	4	20	10	< 5	< 1	3	< 0.01	< 10	< 10	1	< 10	10
39242	208 294	1	0.01	3	20	42	< 5	< 1	3	< 0.01	< 10	10	1	< 10	14
39244	208 294	< 1	0.03	3	20	14	< 5	1	7	< 0.01	< 10	< 10	1	< 10	16
39245	208 294	< 1	0.01	3	< 10	14	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	12
39246	208 294	< 1	0.06	3	30	14	< 5	2	4	< 0.01	< 10	< 10	< 1	< 10	20
39247	208 294	< 1	0.02	2	30	20	< 5	1	5	< 0.01	< 10	< 10	< 1	< 10	16
39248	208 294	< 1	0.04	1	30	18	< 5	2	15	< 0.01	< 10	< 10	< 1	< 10	18
39250	208 294	< 1	0.02	2	40	14	< 5	2	54	< 0.01	< 10	< 10	< 1	< 10	10
39251	208 294	1	0.02	9	760	6	< 5	3	50	0.18	< 10	< 10	13	< 10	34
39252	208 294	< 1	0.05	3	70	14	< 5	2	9	0.01	< 10	< 10	1	< 10	28
39253	208 294	< 1	0.05	1	80	14	< 5	< 1	7	< 0.01	< 10	< 10	< 1	< 10	12
39254	208 294	< 1	0.03	< 1	60	12	< 5	1	10	0.01	< 10	< 10	< 1	< 10	14
39255	208 294	< 1	0.07	2	50	10	< 5	1	10	0.01	< 10	< 10	1	< 10	14
39256	208 294	< 1	< 0.01	2	< 10	54	< 5	< 1	1	< 0.01	10	< 10	< 1	< 10	8
39257	208 294	1	0.01	2	210	60	< 5	< 1	10	< 0.01	< 10	< 10	< 1	< 10	50
39258	208 294	< 1	0.03	2	20	16	< 5	1	4	< 0.01	< 10	< 10	< 1	< 10	18
39259	208 294	< 1	0.08	3	30	14	< 5	1	10	< 0.01	< 10	< 10	1	< 10	22
39260	208 294	< 1	0.02	3	< 10	2	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	8
39263	208 294	< 1	0.06	1	20	24	< 5	1	4	< 0.01	< 10	< 10	3	< 10	18
39264	208 294	< 1	< 0.01	3	< 10	86	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	14
39265	208 294	< 1	0.06	1	60	16	< 5	1	10	< 0.01	< 10	< 10	1	< 10	16
39266	208 294	< 1	< 0.01	3	< 10	2	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	2
39267	208 294	3	< 0.01	3	< 10	290	180	< 1	23	< 0.01	< 10	< 10	< 1	20	428
39268	208 294	< 1	< 0.01	2	10	12	5	3	270	< 0.01	< 10	< 10	< 1	< 10	22
39269	208 294	< 1	< 0.01	5	< 10	550	< 5	< 1	5	< 0.01	< 10	< 10	< 1	< 10	74
39270	208 294	1	< 0.01	14	50	18	< 5	2	5	< 0.01	< 10	< 10	1	< 10	38
39301	208 294	1	0.05	2	40	16	< 5	1	6	< 0.01	< 10	< 10	1	< 10	16
39302	208 294	< 1	0.03	4	40	12	< 5	1	40	< 0.01	< 10	< 10	1	< 10	20
39303	208 294	< 1	0.14	45	1620	2	< 5	16	160	0.10	< 10	< 10	96	< 10	84
39304	208 294	< 1	0.02	3	60	6	< 5	1	15	< 0.01	< 10	< 10	3	< 10	18
39305	208 294	< 1	0.01	9	80	14	< 5	3	12	< 0.01	< 10	< 10	5	< 10	26
39306	208 294	2	0.01	14	310	22	< 5	6	66	< 0.01	< 10	< 10	17	< 10	74
39307	208 294	1	0.02	21	530	14	< 5	6	35	0.02	< 10	< 10	37	< 10	62
39308	208 294	< 1	0.03	2	30	16	< 5	1	6	< 0.01	< 10	< 10	< 1	< 10	22

CERTIFICATION: B. Caughlin

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Page Number : 4-A
Total Pages : 5
Invoice Date: 3-OCT-90
Invoice No. : I-9023700
P.O. Number :

Project : AORDAW
Comments: ATTN: LARRY McLEAN CC: A. TROUP

CERTIFICATE OF ANALYSIS A9023700

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
39309	208	294	< 0.002	1.0	3.35	85	740	< 0.5	< 2	1.97	< 0.5	26	133	26	5.79	10	< 1	0.14	30	2.70	830
39310	208	294	0.006	0.8	2.94	85	600	< 0.5	< 2	2.19	< 0.5	19	198	34	4.34	< 10	< 1	0.25	20	2.48	660
39311	208	294	< 0.002	0.4	2.73	20	1630	< 0.5	< 2	3.68	< 0.5	28	335	49	3.91	< 10	< 1	0.11	< 10	3.98	670
39312	208	294	< 0.002	0.4	2.38	10	240	< 0.5	< 2	3.66	< 0.5	27	333	40	4.34	< 10	< 1	0.10	< 10	4.11	840
39313	208	294	< 0.002	0.2	2.36	5	340	< 0.5	< 2	4.94	< 0.5	30	359	46	4.41	< 10	< 1	0.28	< 10	4.01	785
39314	208	294	< 0.002	0.2	2.38	< 5	1720	< 0.5	< 2	4.44	< 0.5	24	271	36	4.07	< 10	< 1	0.25	< 10	3.41	710
39315	208	294	< 0.002	0.2	2.56	< 5	780	< 0.5	< 2	2.83	< 0.5	30	425	46	3.38	< 10	< 1	0.13	< 10	3.55	535
39316	208	294	< 0.002	< 0.2	2.66	< 5	200	< 0.5	< 2	0.64	< 0.5	24	461	41	3.92	< 10	< 1	0.07	10	3.35	390
39317	208	294	< 0.002	0.6	1.81	< 5	320	< 0.5	< 2	8.18	< 0.5	19	298	41	2.36	< 10	< 1	0.13	< 10	2.46	880
39318	208	294	< 0.002	0.4	1.03	< 5	220	< 0.5	< 2	4.62	< 0.5	7	150	20	1.77	< 10	< 1	0.23	< 10	0.85	585
39319	208	294	< 0.002	< 0.2	1.08	< 5	440	< 0.5	< 2	1.43	< 0.5	9	127	6	1.96	< 10	< 1	0.39	20	0.54	275
39320	208	294	< 0.002	< 0.2	1.17	< 5	340	< 0.5	< 2	0.88	< 0.5	7	100	5	1.89	< 10	< 1	0.21	10	0.61	245
39321	208	294	< 0.002	< 0.2	1.15	< 5	340	< 0.5	< 2	1.10	< 0.5	3	98	3	1.51	< 10	< 1	0.21	10	0.67	200
39322	208	294	< 0.002	0.2	0.87	< 5	490	< 0.5	< 2	1.14	< 0.5	2	151	4	1.15	< 10	< 1	0.28	10	0.43	175
39323	208	294	< 0.002	0.4	0.99	< 5	400	< 0.5	< 2	2.11	< 0.5	3	150	5	1.72	< 10	< 1	0.18	20	0.40	280
39324	208	294	< 0.002	0.4	1.30	< 5	670	< 0.5	2	1.64	< 0.5	4	132	4	2.31	< 10	< 1	0.16	20	0.66	265
39325	208	294	< 0.002	0.2	1.14	< 5	480	< 0.5	< 2	1.37	< 0.5	4	134	8	2.06	< 10	< 1	0.30	20	0.44	230
39326	208	294	< 0.002	0.8	0.98	< 5	570	< 0.5	< 2	2.53	< 0.5	3	107	5	1.73	< 10	< 1	0.37	10	0.34	290
39551	208	294	< 0.002	0.6	0.63	5	760	< 0.5	< 2	0.11	< 0.5	5	316	8	1.28	< 10	< 1	0.27	10	0.20	630
39552	208	294	0.010	2.4	0.35	< 5	800	< 0.5	2	0.05	< 0.5	1	252	5	1.52	< 10	< 1	0.06	10	0.02	50
39553	208	294	< 0.002	0.2	0.06	< 5	60	< 0.5	< 2	0.01	< 0.5	< 1	317	1	0.37	< 10	< 1	< 0.01	< 10	0.01	60
39554	208	294	0.036	2.6	0.02	< 5	790	< 0.5	2	< 0.01	< 0.5	< 1	158	23	1.05	< 10	< 1	< 0.01	< 10	< 0.01	30
39555	208	294	0.320	>200	0.06	45	1920	< 0.5	44	< 0.01	1.0	1	261	327	3.10	< 10	40	< 0.01	< 10	< 0.01	40
39556	208	294	0.032	12.6	0.01	< 5	4600	< 0.5	2	< 0.01	< 0.5	1	362	19	0.69	< 10	2	< 0.01	< 10	< 0.01	40
39601	208	294	0.002	1.6	0.04	< 5	1280	< 0.5	< 2	0.03	< 0.5	< 1	194	3	0.26	< 10	< 1	0.02	< 10	< 0.01	70
39602	208	294	0.002	1.6	0.67	< 5	1180	< 0.5	< 2	0.14	< 0.5	3	151	9	1.23	10	< 1	0.35	40	0.14	260
39603	208	294	0.002	1.0	0.57	< 5	840	< 0.5	< 2	0.05	< 0.5	1	167	4	0.81	10	< 1	0.23	30	0.05	175
39604	208	294	< 0.002	0.8	1.07	< 5	880	< 0.5	< 2	0.15	< 0.5	5	132	9	2.08	10	< 1	0.50	30	0.25	345
39605	208	294	0.002	0.8	0.94	< 5	370	< 0.5	< 2	0.08	< 0.5	2	160	7	0.98	10	< 1	0.32	40	0.10	225
39606	208	294	0.006	1.2	0.23	< 5	290	< 0.5	< 2	0.03	< 0.5	2	262	4	0.93	< 10	< 1	0.05	< 10	0.03	470
39607	208	294	< 0.002	0.8	0.61	< 5	260	< 0.5	< 2	0.05	< 0.5	2	153	7	0.77	10	< 1	0.27	40	0.09	210
39608	208	294	0.030	5.8	0.47	< 5	690	< 0.5	< 2	0.03	0.5	2	221	10	1.30	10	< 1	0.15	40	0.05	285
39609	208	294	0.002	1.4	0.75	< 5	800	< 0.5	< 2	0.05	< 0.5	1	158	8	0.82	10	< 1	0.33	40	0.09	160
39610	208	294	< 0.002	1.4	0.95	< 5	370	< 0.5	< 2	0.06	< 0.5	3	104	73	0.90	10	< 1	0.34	40	0.09	210
39611	208	294	0.041	32.8	0.21	55	140	< 0.5	2	0.02	< 0.5	1	366	681	1.25	< 10	< 1	0.05	< 10	0.01	65
39612	208	294	< 0.002	1.4	1.04	< 5	1370	< 0.5	< 2	0.81	0.5	5	84	43	1.94	< 10	< 1	0.37	30	0.19	395
39613	208	294	0.024	4.2	0.76	< 5	2750	< 0.5	< 2	0.08	< 0.5	5	208	83	2.56	< 10	< 1	0.15	10	0.07	105
39614	208	294	0.002	1.2	0.72	< 5	1380	< 0.5	< 2	0.12	< 0.5	3	101	33	1.28	10	< 1	0.28	30	0.16	205
39615	208	294	< 0.002	0.8	1.47	< 5	410	< 0.5	< 2	0.21	< 0.5	7	108	13	2.29	10	< 1	0.66	40	0.58	310
39616	208	294	< 0.002	0.6	0.60	< 5	940	< 0.5	< 2	1.27	< 0.5	1	138	4	0.79	< 10	< 1	0.37	20	0.09	290

CERTIFICATION: B. Campbell

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

[redacted]: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Page N[redacted]r : 4-B
Total Pa[redacted]: 5
Invoice Date: 3-OCT-90
Invoice No. : I-9023700
P.O. Number :

Project : AORDAW
Comments: ATTN: LARRY McLEAN CC: A. TROUP

CERTIFICATE OF ANALYSIS A9023700

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
39309	208	294	1	0.09	50	1840	6	< 5	17	108	0.07	< 10	< 10	122	< 10	84
39310	208	294	1	0.01	67	960	8	< 5	14	194	< 0.01	< 10	< 10	78	< 10	92
39311	208	294	< 1	0.01	116	610	2	< 5	11	305	0.04	< 10	< 10	68	< 10	68
39312	208	294	< 1	0.01	123	550	< 2	5	16	432	< 0.01	< 10	< 10	71	< 10	80
39313	208	294	< 1	0.02	133	510	4	< 5	21	461	< 0.01	< 10	< 10	74	< 10	78
39314	208	294	< 1	0.02	112	540	< 2	< 5	17	331	< 0.01	< 10	< 10	66	< 10	74
39315	208	294	< 1	0.02	114	520	8	< 5	6	725	0.05	< 10	< 10	67	< 10	46
39316	208	294	< 1	0.02	125	580	10	< 5	5	59	0.09	< 10	< 10	65	< 10	44
39317	208	294	< 1	0.02	85	430	22	< 5	3	969	0.03	< 10	< 10	39	< 10	36
39318	208	294	< 1	0.02	21	390	10	< 5	5	523	0.01	< 10	< 10	15	< 10	36
39319	208	294	< 1	0.04	8	480	8	< 5	6	96	0.01	< 10	< 10	11	< 10	50
39320	208	294	< 1	0.03	4	480	4	< 5	4	62	0.02	< 10	< 10	10	< 10	70
39321	208	294	< 1	0.04	2	410	2	< 5	3	68	0.03	< 10	< 10	9	< 10	62
39322	208	294	< 1	0.02	3	250	4	< 5	3	66	< 0.01	< 10	< 10	7	< 10	38
39323	208	294	< 1	0.05	4	340	8	< 5	6	110	< 0.01	< 10	< 10	13	< 10	52
39324	208	294	< 1	0.05	3	430	8	< 5	6	122	< 0.01	< 10	< 10	18	< 10	74
39325	208	294	< 1	0.04	3	400	2	< 5	7	86	< 0.01	< 10	< 10	14	< 10	68
39326	208	294	< 1	0.03	2	440	4	< 5	7	176	0.01	< 10	< 10	11	< 10	54
39551	208	294	< 1	0.02	9	240	16	< 5	2	12	< 0.01	< 10	< 10	7	< 10	30
39552	208	294	1	0.02	4	80	458	< 5	< 1	9	< 0.01	< 10	< 10	1	< 10	18
39553	208	294	< 1	0.01	4	20	10	< 5	< 1	7	< 0.01	< 10	< 10	1	< 10	2
39554	208	294	2	< 0.01	3	30	650	5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	12
39555	208	294	2	< 0.01	5	< 10	1650	300	< 1	10	< 0.01	< 10	< 10	< 1	10	236
39556	208	294	1	< 0.01	5	< 10	196	20	< 1	122	< 0.01	< 10	< 10	< 1	< 10	8
39601	208	294	< 1	< 0.01	2	20	16	< 5	< 1	15	< 0.01	< 10	< 10	1	< 10	2
39602	208	294	< 1	0.04	4	290	18	< 5	3	17	0.01	< 10	< 10	5	< 10	46
39603	208	294	< 1	0.03	2	90	22	< 5	2	11	< 0.01	< 10	< 10	2	< 10	10
39604	208	294	< 1	0.03	6	440	24	< 5	5	21	0.01	< 10	< 10	8	< 10	72
39605	208	294	< 1	0.01	4	110	86	< 5	2	13	< 0.01	< 10	< 10	2	< 10	32
39606	208	294	1	< 0.01	6	40	152	< 5	1	6	< 0.01	< 10	< 10	3	< 10	38
39607	208	294	< 1	0.03	3	120	54	< 5	2	8	< 0.01	< 10	< 10	3	< 10	26
39608	208	294	< 1	0.02	5	40	258	< 5	2	6	< 0.01	< 10	< 10	3	< 10	138
39609	208	294	< 1	0.02	2	70	86	< 5	2	7	< 0.01	< 10	< 10	2	< 10	52
39610	208	294	1	0.02	3	100	268	< 5	3	16	< 0.01	< 10	< 10	2	< 10	42
39611	208	294	2	< 0.01	4	30	5340	80	< 1	11	< 0.01	< 10	< 10	2	< 10	38
39612	208	294	< 1	< 0.01	6	490	72	< 5	3	29	< 0.01	< 10	< 10	4	< 10	90
39613	208	294	3	< 0.01	8	80	1045	5	4	24	< 0.01	< 10	< 10	4	< 10	94
39614	208	294	1	0.01	3	160	260	< 5	2	17	< 0.01	< 10	< 10	3	< 10	40
39615	208	294	< 1	0.02	9	530	22	< 5	5	18	0.02	< 10	< 10	15	< 10	74
39616	208	294	< 1	0.01	2	50	14	< 5	2	34	< 0.01	< 10	< 10	2	< 10	36

CERTIFICATION: B. Caplan

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AORDAW
Comments: ATTN: LARRY McLEAN CC: A. TROUP

Invoice Date: 3-OCT-90
Invoice No. : I-9023700
P.O. Number :

CERTIFICATE OF ANALYSIS A9023700

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
39617	208	294	< 0.002	0.8	1.00	< 5	2200	< 0.5	< 2	0.17	< 0.5	5	199	10	1.69	10	< 1	0.46	40	0.44	510
39618	208	294	< 0.002	1.0	0.64	< 5	1070	< 0.5	< 2	0.07	< 0.5	2	224	7	1.11	10	< 1	0.31	40	0.16	315
39619	208	294	< 0.002	0.6	0.95	< 5	600	< 0.5	< 2	0.14	< 0.5	4	220	5	1.20	10	< 1	0.46	40	0.35	255
39620	208	294	0.006	0.8	0.55	< 5	630	< 0.5	< 2	0.52	< 0.5	1	204	7	0.74	< 10	< 1	0.30	40	0.09	195
39621	208	294	< 0.002	0.4	0.94	< 5	700	< 0.5	< 2	0.16	< 0.5	4	195	9	1.43	10	< 1	0.46	30	0.45	300
39622	208	294	< 0.002	0.6	0.07	< 5	90	< 0.5	< 2	5.66	< 0.5	< 1	253	2	0.36	< 10	< 1	< 0.01	< 10	0.04	645
39623	208	294	0.024	25.0	0.06	10	4140	< 0.5	< 2	1.99	6.5	1	247	465	0.36	< 10	2	< 0.01	< 10	0.02	385
39624	208	294	< 0.002	1.2	0.87	< 5	6140	< 0.5	< 2	0.39	5.5	3	254	21	1.16	10	< 1	0.34	30	0.27	510
39625	208	294	< 0.002	1.4	3.26	< 5	2750	< 0.5	< 2	1.94	< 0.5	20	119	21	4.56	10	< 1	0.38	50	1.60	2640
39626	208	294	< 0.002	0.2	0.20	< 5	3140	< 0.5	< 2	0.03	< 0.5	1	255	2	0.48	< 10	< 1	0.09	< 10	0.05	180
39627	208	294	< 0.002	0.2	0.19	< 5	360	< 0.5	< 2	0.03	< 0.5	< 1	259	2	0.41	< 10	< 1	0.07	< 10	0.04	110
39628	208	294	< 0.002	0.6	1.06	< 5	490	< 0.5	< 2	0.54	< 0.5	5	133	12	1.51	10	< 1	0.55	40	0.61	365
39629	208	294	< 0.002	0.6	0.88	< 5	420	< 0.5	< 2	0.12	< 0.5	3	153	6	1.25	10	< 1	0.53	40	0.44	275
39630	208	294	< 0.002	0.4	0.76	< 5	340	< 0.5	< 2	0.11	< 0.5	3	134	5	1.13	< 10	< 1	0.48	30	0.36	225
39631	208	294	< 0.002	0.2	0.45	< 5	470	< 0.5	< 2	0.80	< 0.5	4	274	9	1.27	< 10	< 1	0.27	30	0.20	565
39632	208	294	< 0.002	0.6	0.73	< 5	330	< 0.5	< 2	0.09	< 0.5	2	114	5	1.10	10	< 1	0.38	50	0.26	220
39633	208	294	< 0.002	0.6	1.04	5	520	< 0.5	2	0.17	< 0.5	6	141	8	1.84	10	< 1	0.68	50	0.57	375
39634	208	294	< 0.002	0.6	1.05	5	440	< 0.5	< 2	0.17	< 0.5	6	126	10	1.83	10	< 1	0.75	50	0.62	410
39635	208	294	< 0.002	0.6	0.70	< 5	980	< 0.5	< 2	0.11	< 0.5	3	130	4	1.23	10	< 1	0.45	50	0.27	340
39636	208	294	< 0.002	0.4	0.90	< 5	520	< 0.5	< 2	0.17	< 0.5	5	158	15	1.50	10	< 1	0.63	30	0.54	330
39637	208	294	< 0.002	0.6	0.81	< 5	510	< 0.5	< 2	0.12	< 0.5	3	193	4	1.17	10	< 1	0.53	40	0.32	265
39638	208	294	< 0.002	0.6	0.96	5	580	< 0.5	< 2	0.14	< 0.5	6	247	15	1.70	10	< 1	0.57	30	0.38	360
39639	208	294	< 0.002	0.8	0.72	5	450	< 0.5	< 2	0.09	< 0.5	5	202	10	1.43	10	< 1	0.40	50	0.15	370
39640	208	294	< 0.002	0.6	0.72	10	650	< 0.5	< 2	0.10	< 0.5	6	214	10	1.55	10	< 1	0.43	40	0.16	490
39641	208	294	0.002	0.4	0.57	< 5	300	< 0.5	< 2	0.06	< 0.5	2	191	4	0.83	< 10	1	0.33	30	0.09	115
39642	208	294	0.006	3.0	0.40	10	4900	< 0.5	4	0.03	< 0.5	3	175	150	1.20	< 10	1	0.16	20	0.04	145
39643	208	294	< 0.002	0.8	0.56	< 5	1500	< 0.5	< 2	0.06	< 0.5	4	156	20	1.18	< 10	< 1	0.32	40	0.08	315
39644	208	294	< 0.002	0.4	0.49	< 5	360	< 0.5	< 2	0.06	< 0.5	1	124	7	0.79	< 10	< 1	0.31	10	0.05	160
39645	208	294	< 0.002	0.8	0.76	< 5	460	< 0.5	4	0.08	< 0.5	2	201	8	1.22	10	< 1	0.43	40	0.10	310
39648	208	294	0.034	5.8	0.07	< 5	40	< 0.5	2	< 0.01	< 0.5	< 1	286	16	1.21	< 10	< 1	< 0.01	< 10	0.01	45
39649	208	294	0.023	7.0	0.17	5	1700	< 0.5	< 2	0.01	< 0.5	1	215	44	1.10	< 10	< 1	0.09	10	0.01	55
39650	208	294	0.008	15.2	0.09	25	2760	< 0.5	4	0.26	19.0	1	176	796	0.37	< 10	3	0.01	< 10	0.02	195

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Invoice Date: 3-OCT-90
Invoice No. : I-9023700
P.O. Number :

Project : AORDAW
Comments: ATTN: LARRY McLEAN CC: A. TROUP

CERTIFICATE OF ANALYSIS A9023700

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
39617	208	294	< 1	0.02	7	360	16	< 5	4	14	0.01	< 10	< 10	10	< 10	52
39618	208	294	< 1	0.03	5	160	22	< 5	3	11	< 0.01	< 10	< 10	3	< 10	34
39619	208	294	< 1	0.03	6	310	16	< 5	2	11	0.01	< 10	< 10	6	< 10	36
39620	208	294	< 1	0.02	3	110	30	< 5	1	15	< 0.01	< 10	< 10	1	< 10	26
39621	208	294	< 1	0.02	7	330	16	< 5	3	11	0.01	< 10	< 10	9	< 10	40
39622	208	294	< 1	< 0.01	2	10	8	5	< 1	269	< 0.01	< 10	< 10	1	< 10	6
39623	208	294	< 1	< 0.01	2	< 10	2890	75	< 1	187	< 0.01	< 10	< 10	1	< 10	76
39624	208	294	< 1	0.01	4	130	102	< 5	2	69	< 0.01	< 10	< 10	3	< 10	36
39625	208	294	< 1	0.05	32	1110	22	< 5	13	110	0.13	< 10	< 10	84	< 10	90
39626	208	294	< 1	< 0.01	4	20	14	< 5	< 1	14	< 0.01	< 10	< 10	1	< 10	10
39627	208	294	< 1	< 0.01	4	30	10	< 5	< 1	6	< 0.01	< 10	< 10	1	< 10	6
39628	208	294	< 1	0.02	7	360	18	< 5	3	34	0.01	< 10	< 10	8	< 10	46
39629	208	294	< 1	0.03	7	320	16	< 5	3	11	0.01	< 10	< 10	8	< 10	36
39630	208	294	< 1	0.04	6	300	10	< 5	2	8	0.02	< 10	< 10	12	< 10	28
39631	208	294	< 1	0.02	6	290	10	< 5	3	26	0.01	< 10	< 10	17	< 10	24
39632	208	294	< 1	0.03	4	220	8	< 5	4	6	0.01	< 10	< 10	8	< 10	22
39633	208	294	< 1	0.04	10	510	8	< 5	6	10	0.03	< 10	< 10	20	< 10	40
39634	208	294	< 1	0.03	11	520	14	< 5	6	12	0.03	< 10	< 10	20	< 10	46
39635	208	294	< 1	0.03	6	340	14	< 5	4	15	0.01	< 10	< 10	8	< 10	34
39636	208	294	< 1	0.03	11	430	12	< 5	4	11	0.02	< 10	< 10	16	< 10	44
39637	208	294	< 1	0.05	5	310	10	< 5	3	12	0.01	< 10	< 10	9	< 10	30
39638	208	294	1	0.03	12	410	12	< 5	5	27	0.01	< 10	< 10	19	< 10	46
39639	208	294	< 1	0.03	8	310	12	< 5	5	35	< 0.01	< 10	< 10	10	< 10	46
39640	208	294	< 1	0.03	8	370	18	< 5	4	24	< 0.01	< 10	< 10	11	< 10	48
39641	208	294	< 1	0.05	4	200	10	< 5	2	10	< 0.01	< 10	< 10	3	< 10	22
39642	208	294	< 1	0.01	4	160	876	20	2	29	< 0.01	< 10	< 10	3	< 10	64
39643	208	294	< 1	0.03	5	260	100	< 5	4	19	< 0.01	< 10	< 10	3	< 10	34
39644	208	294	< 1	0.02	2	180	40	< 5	3	6	< 0.01	< 10	< 10	3	< 10	12
39645	208	294	< 1	0.01	5	250	22	< 5	3	13	< 0.01	< 10	< 10	4	< 10	36
39648	208	294	< 1	< 0.01	4	50	2310	< 5	< 1	1	< 0.01	< 10	< 10	5	< 10	10
39649	208	294	3	< 0.01	3	80	966	5	1	9	< 0.01	< 10	< 10	6	< 10	20
39650	208	294	< 1	< 0.01	2	20	1405	150	< 1	150	< 0.01	< 10	< 10	1	< 10	366

CERTIFICATION: B. Cargill

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers
212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

A9024237

Comments: CC: ART TROUP

CERTIFICATE A9024237

ARBOR RESOURCES INC.

Project: AOR-DAW
P.O. # :

Samples submitted to our lab in Vancouver, BC.
This report was printed on 11-OCT-90.

SAMPLE PREPARATION

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION
208	14	Assay ring to approx 150 mesh
294	14	Crush and split (0-10 pounds)
238	14	NITRIC-AQUA REGIA DIGESTION

* NOTE 1:

The 32 element ICP package is suitable for trace metals in soil and rock samples. Elements for which the nitric-aqua regia digestion is possibly incomplete are: Al, Ba, Be, Ca, Cr, Ga, K, La, Mg, Na, Sr, Ti, Tl, W.

ANALYTICAL PROCEDURES

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION	METHOD	DETECTION LIMIT	UPPER LIMIT
398	14	Au oz/T: 1/2 assay ton	FA-AAS	0.002	20.00
922	14	Ag ppm: 32 element, soil & rock	ICP-AES	0.2	200
921	14	Al %: 32 element, soil & rock	ICP-AES	0.01	15.00
923	14	As ppm: 32 element, soil & rock	ICP-AES	5	10000
924	14	Ba ppm: 32 element, soil & rock	ICP-AES	10	10000
925	14	Be ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
926	14	Bi ppm: 32 element, soil & rock	ICP-AES	2	10000
927	14	Ca %: 32 element, soil & rock	ICP-AES	0.01	15.00
928	14	Cd ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
929	14	Co ppm: 32 element, soil & rock	ICP-AES	1	10000
930	14	Cr ppm: 32 element, soil & rock	ICP-AES	1	10000
931	14	Cu ppm: 32 element, soil & rock	ICP-AES	1	10000
932	14	Fe %: 32 element, soil & rock	ICP-AES	0.01	15.00
933	14	Ga ppm: 32 element, soil & rock	ICP-AES	10	10000
951	14	Hg ppm: 32 element, soil & rock	ICP-AES	1	10000
934	14	K %: 32 element, soil & rock	ICP-AES	0.01	10.00
935	14	La ppm: 32 element, soil & rock	ICP-AES	10	10000
936	14	Mg %: 32 element, soil & rock	ICP-AES	0.01	15.00
937	14	Mn ppm: 32 element, soil & rock	ICP-AES	5	10000
938	14	Mo ppm: 32 element, soil & rock	ICP-AES	1	10000
939	14	Na %: 32 element, soil & rock	ICP-AES	0.01	5.00
940	14	Ni ppm: 32 element, soil & rock	ICP-AES	1	10000
941	14	P ppm: 32 element, soil & rock	ICP-AES	10	10000
942	14	Pb ppm: 32 element, soil & rock	ICP-AES	2	10000
943	14	Sb ppm: 32 element, soil & rock	ICP-AES	5	10000
958	14	Sc ppm: 32 elements, soil & rock	ICP-AES	1	10000
944	14	Sr ppm: 32 element, soil & rock	ICP-AES	1	10000
945	14	Ti %: 32 element, soil & rock	ICP-AES	0.01	5.00
946	14	Tl ppm: 32 element, soil & rock	ICP-AES	10	10000
947	14	U ppm: 32 element, soil & rock	ICP-AES	10	10000
948	14	V ppm: 32 element, soil & rock	ICP-AES	1	10000
949	14	W ppm: 32 element, soil & rock	ICP-AES	10	10000
950	14	Zn ppm: 32 element, soil & rock	ICP-AES	2	10000

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Page Number : 1-A
Total Pages : 1
Invoice Date: 11-OCT-90
Invoice No. : I-9024237
P.O. Number :

CERTIFICATE OF ANALYSIS A9024237

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
39651 G	208	294	< 0.002	< 0.2	0.24	< 5	370	< 0.5	< 2	0.09	< 0.5	1	197	4	0.50	< 10	1	0.14	10	0.03	65
39652 G	208	294	< 0.002	< 0.2	0.04	< 5	50	< 0.5	< 2	0.02	< 0.5	< 1	241	1	0.24	< 10	< 1	< 0.01	< 10	< 0.01	55
39653 G	208	294	< 0.002	< 0.2	0.15	5	150	< 0.5	< 2	0.01	< 0.5	< 1	250	2	0.87	< 10	1	0.08	10	0.01	65
39654 G	208	294	< 0.002	< 0.2	0.05	< 5	40	< 0.5	< 2	< 0.01	< 0.5	1	344	2	0.32	< 10	< 1	< 0.01	< 10	< 0.01	35
39655 G	208	294	< 0.002	< 0.2	0.11	< 5	120	< 0.5	< 2	< 0.01	< 0.5	< 1	294	1	0.35	< 10	1	0.07	< 10	< 0.01	40
39656 G	208	294	< 0.002	< 0.2	0.15	< 5	180	< 0.5	< 2	< 0.01	< 0.5	< 1	214	1	0.29	< 10	1	0.14	10	< 0.01	45
39657 G	208	294	< 0.002	< 0.2	0.36	< 5	330	< 0.5	< 2	0.01	< 0.5	1	99	2	0.51	10	< 1	0.31	30	0.02	50
39658 G	208	294	< 0.002	0.4	0.39	5	410	< 0.5	< 2	0.02	< 0.5	1	82	2	0.53	10	1	0.30	40	0.02	65
39659 G	208	294	< 0.002	0.4	0.52	5	420	< 0.5	< 2	0.02	0.5	< 1	105	5	0.56	10	< 1	0.37	40	0.03	365
39660 G	208	294	< 0.002	< 0.2	0.25	5	220	< 0.5	< 2	0.01	< 0.5	1	110	2	0.76	< 10	< 1	0.20	30	0.01	110
39661 G	208	294	< 0.002	< 0.2	0.25	10	190	< 0.5	< 2	0.01	< 0.5	< 1	66	2	0.90	10	< 1	0.18	40	0.01	65
39662 G	208	294	< 0.002	0.6	0.25	5	240	< 0.5	< 2	< 0.01	< 0.5	< 1	73	1	0.96	< 10	< 1	0.22	30	< 0.01	40
39749 G	208	294	< 0.002	0.4	0.73	5	530	< 0.5	< 2	0.06	0.5	1	63	11	0.84	10	< 1	0.35	40	0.06	170
39750 G	208	294	< 0.002	< 0.2	0.61	< 5	450	< 0.5	< 2	0.04	< 0.5	1	62	9	0.55	10	< 1	0.34	40	0.05	155

CERTIFICATION: B. Caplette

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Page Number : 1-B
Total Pages : 1
Invoice Date: 11-OCT-90
Invoice No. : I-9024237
P.O. Number :

CERTIFICATE OF ANALYSIS A9024237

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
39651 G	208	294	< 1	0.01	2	30	10	< 5	1	5	< 0.01	< 10	< 10	2	< 10	16
39652 G	208	294	< 1	< 0.01	2	< 10	4	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	2
39653 G	208	294	< 1	0.02	2	30	26	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	18
39654 G	208	294	< 1	< 0.01	2	< 10	2	< 5	< 1	< 1	< 0.01	< 10	< 10	1	< 10	2
39655 G	208	294	< 1	< 0.01	2	< 10	4	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	4
39656 G	208	294	< 1	0.01	2	10	6	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	4
39657 G	208	294	< 1	0.03	1	30	10	< 5	1	3	< 0.01	< 10	< 10	< 1	< 10	28
39658 G	208	294	< 1	0.01	1	40	12	< 5	1	4	< 0.01	< 10	< 10	1	< 10	20
39659 G	208	294	< 1	0.01	2	50	52	< 5	2	4	< 0.01	< 10	< 10	1	< 10	26
39660 G	208	294	< 1	0.02	2	40	22	< 5	1	3	< 0.01	< 10	< 10	< 1	< 10	32
39661 G	208	294	1	0.02	1	70	22	< 5	1	3	< 0.01	< 10	< 10	< 1	< 10	56
39662 G	208	294	1	0.04	< 1	60	20	< 5	< 1	3	< 0.01	< 10	< 10	< 1	< 10	22
39749 G	208	294	< 1	0.01	1	80	40	< 5	3	6	< 0.01	< 10	< 10	2	< 10	44
39750 G	208	294	< 1	0.01	1	50	24	< 5	2	5	< 0.01	< 10	< 10	1	< 10	38

CERTIFICATION: B. Caryl

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

A9024260

Comments: CC: ART TROUP

CERTIFICATE A9024260

ARBOR RESOURCES INC.

Project: AOR-DAW
P.O. # :

Samples submitted to our lab in Vancouver, BC.
This report was printed on 11-OCT-90.

SAMPLE PREPARATION

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION
208	74	Assay ring to approx 150 mesh
294	74	Crush and split (0-10 pounds)
238	74	NITRIC-AQUA REGIA DIGESTION

* NOTE 1:

The 32 element ICP package is suitable for trace metals in soil and rock samples. Elements for which the nitric-aqua regia digestion is possibly incomplete are: Al, Ba, Be, Ca, Cr, Ga, K, La, Mg, Na, Sr, Ti, Tl, W.

ANALYTICAL PROCEDURES

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION	METHOD	DETECTION LIMIT	UPPER LIMIT
398	74	Au oz/T: 1/2 assay ton	FA-AAS	0.002	20.00
922	74	Ag ppm: 32 element, soil & rock	ICP-AES	0.2	200
921	74	Al %: 32 element, soil & rock	ICP-AES	0.01	15.00
923	74	As ppm: 32 element, soil & rock	ICP-AES	5	10000
924	74	Ba ppm: 32 element, soil & rock	ICP-AES	10	10000
925	74	Be ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
926	74	Bi ppm: 32 element, soil & rock	ICP-AES	2	10000
927	74	Ca %: 32 element, soil & rock	ICP-AES	0.01	15.00
928	74	Cd ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
929	74	Co ppm: 32 element, soil & rock	ICP-AES	1	10000
930	74	Cr ppm: 32 element, soil & rock	ICP-AES	1	10000
931	74	Cu ppm: 32 element, soil & rock	ICP-AES	1	10000
932	74	Fe %: 32 element, soil & rock	ICP-AES	0.01	15.00
933	74	Ga ppm: 32 element, soil & rock	ICP-AES	10	10000
951	74	Hg ppm: 32 element, soil & rock	ICP-AES	1	10000
934	74	K %: 32 element, soil & rock	ICP-AES	0.01	10.00
935	74	La ppm: 32 element, soil & rock	ICP-AES	10	10000
936	74	Mg %: 32 element, soil & rock	ICP-AES	0.01	15.00
937	74	Mn ppm: 32 element, soil & rock	ICP-AES	5	10000
938	74	Mo ppm: 32 element, soil & rock	ICP-AES	1	10000
939	74	Na %: 32 element, soil & rock	ICP-AES	0.01	5.00
940	74	Ni ppm: 32 element, soil & rock	ICP-AES	1	10000
941	74	P ppm: 32 element, soil & rock	ICP-AES	10	10000
942	74	Pb ppm: 32 element, soil & rock	ICP-AES	2	10000
943	74	Sb ppm: 32 element, soil & rock	ICP-AES	5	10000
958	74	Sc ppm: 32 elements, soil & rock	ICP-AES	1	10000
944	74	Sr ppm: 32 element, soil & rock	ICP-AES	1	10000
945	74	Ti %: 32 element, soil & rock	ICP-AES	0.01	5.00
946	74	Tl ppm: 32 element, soil & rock	ICP-AES	10	10000
947	74	U ppm: 32 element, soil & rock	ICP-AES	10	10000
948	74	V ppm: 32 element, soil & rock	ICP-AES	1	10000
949	74	W ppm: 32 element, soil & rock	ICP-AES	10	10000
950	74	Zn ppm: 32 element, soil & rock	ICP-AES	2	10000

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Page Number : 1-A
Total Pages : 2
Invoice Date: 11-OCT-90
Invoice No. : I-9024260
P.O. Number :

CERTIFICATE OF ANALYSIS A9024260

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
37851	208	294	< 0.002	0.8	0.25	< 5	70	< 0.5	2	0.04	< 0.5	1	177	6	0.53	< 10	< 1	0.06	< 10	0.08	90
37852	208	294	< 0.002	0.4	1.02	< 5	480	< 0.5	4	0.20	< 0.5	4	39	4	1.64	10	< 1	0.37	10	0.31	125
37853	208	294	< 0.002	0.4	1.11	< 5	420	< 0.5	4	0.23	< 0.5	4	58	2	1.88	10	< 1	0.37	10	0.35	150
37854	208	294	< 0.002	0.2	1.01	< 5	360	< 0.5	2	0.20	< 0.5	4	47	3	1.85	10	< 1	0.36	20	0.32	155
37855	208	294	< 0.002	0.4	0.87	< 5	400	< 0.5	4	0.17	< 0.5	4	44	6	1.70	10	< 1	0.36	20	0.25	175
37856	208	294	0.004	1.0	0.50	< 5	310	< 0.5	2	0.05	< 0.5	1	34	6	0.65	< 10	< 1	0.29	30	0.07	120
37857	208	294	< 0.002	0.2	0.38	< 5	230	< 0.5	< 2	0.04	< 0.5	< 1	77	4	0.53	< 10	< 1	0.25	10	0.04	40
37858	208	294	< 0.002	0.2	0.55	5	180	0.5	2	0.03	< 0.5	1	31	4	0.66	10	< 1	0.37	50	0.07	90
37859	208	294	< 0.002	0.4	0.66	5	220	0.5	4	0.04	< 0.5	1	36	4	0.57	10	< 1	0.37	30	0.07	65
37860	208	294	< 0.002	0.2	0.42	< 5	190	< 0.5	2	0.03	< 0.5	< 1	35	3	0.55	10	< 1	0.27	30	0.05	40
37861	208	294	< 0.002	0.2	0.64	< 5	330	0.5	< 2	0.06	< 0.5	1	37	7	0.82	< 10	< 1	0.27	20	0.14	60
37862	208	294	< 0.002	0.4	0.43	< 5	320	< 0.5	< 2	0.03	< 0.5	1	72	4	0.66	< 10	< 1	0.19	10	0.11	40
37863	208	294	< 0.002	0.4	0.50	< 5	380	< 0.5	2	0.04	< 0.5	1	53	2	0.59	< 10	< 1	0.22	10	0.15	40
37864	208	294	< 0.002	0.4	0.51	< 5	380	< 0.5	2	0.04	< 0.5	1	72	3	0.67	< 10	< 1	0.29	20	0.12	40
37865	208	294	< 0.002	0.4	0.66	< 5	360	0.5	2	0.09	< 0.5	1	57	7	0.88	< 10	< 1	0.40	30	0.13	60
37866	208	294	0.009	0.8	0.49	< 5	290	< 0.5	< 2	0.02	< 0.5	< 1	70	2	0.36	< 10	< 1	0.35	20	0.04	20
37867	208	294	< 0.002	0.2	0.38	< 5	180	< 0.5	< 2	0.02	< 0.5	< 1	72	1	0.33	< 10	< 1	0.24	20	0.04	25
37868	208	294	< 0.002	< 0.2	0.52	< 5	390	< 0.5	2	0.02	< 0.5	1	67	1	0.35	< 10	< 1	0.36	20	0.06	20
37869	208	294	< 0.002	< 0.2	1.28	15	460	< 0.5	2	0.17	< 0.5	3	66	3	2.06	< 10	< 1	0.45	10	0.38	225
37870	208	294	< 0.002	< 0.2	1.09	5	370	< 0.5	2	0.19	< 0.5	5	48	< 1	1.87	10	< 1	0.39	10	0.36	205
37871	208	294	< 0.002	< 0.2	0.24	< 5	260	< 0.5	< 2	0.02	< 0.5	< 1	89	< 1	0.38	< 10	< 1	0.20	30	0.03	90
37872	208	294	0.008	4.2	0.06	5	410	< 0.5	< 2	< 0.01	< 0.5	< 1	168	4	0.78	< 10	< 1	< 0.01	< 10	< 0.01	80
37873	208	294	0.002	2.0	0.07	< 5	660	< 0.5	2	< 0.01	< 0.5	< 1	177	< 1	0.55	< 10	< 1	0.01	< 10	< 0.01	40
37874	208	294	0.015	< 0.2	0.14	< 5	330	< 0.5	< 2	0.01	< 0.5	< 1	171	< 1	0.38	< 10	< 1	0.05	20	0.01	50
37875	208	294	< 0.002	< 0.2	0.44	5	970	< 0.5	2	0.03	0.5	< 1	50	1	0.74	10	< 1	0.29	30	0.05	55
37876	208	294	< 0.002	< 0.2	0.68	< 5	680	< 0.5	< 2	0.06	< 0.5	1	50	2	0.64	10	< 1	0.31	40	0.09	65
37877	208	294	< 0.002	< 0.2	0.78	5	620	< 0.5	< 2	0.08	< 0.5	1	47	8	0.98	10	< 1	0.23	40	0.14	120
37878	208	294	< 0.002	< 0.2	0.59	< 5	800	0.5	< 2	0.04	< 0.5	< 1	70	2	0.61	10	< 1	0.36	30	0.07	105
37879	208	294	< 0.002	< 0.2	0.58	5	890	< 0.5	< 2	0.05	< 0.5	< 1	47	2	0.65	< 10	< 1	0.31	40	0.06	120
37880	208	294	< 0.002	0.4	0.34	< 5	30	< 0.5	< 2	0.01	0.5	10	215	36	1.97	< 10	< 1	< 0.01	< 10	0.02	250
37881	208	294	< 0.002	< 0.2	0.80	< 5	80	< 0.5	< 2	0.33	< 0.5	3	117	4	1.18	< 10	< 1	0.06	< 10	0.45	160
39385	208	294	< 0.002	< 0.2	0.44	< 5	1000	< 0.5	< 2	0.04	< 0.5	1	52	< 1	0.29	< 10	< 1	0.39	20	0.06	25
39386	208	294	< 0.002	0.4	0.34	930	90	< 0.5	< 2	0.34	1.0	3	251	9	1.24	< 10	< 1	0.03	< 10	0.30	275
39387	208	294	< 0.002	0.4	0.09	15	10	< 0.5	< 2	0.01	< 0.5	2	232	6	0.41	< 10	< 1	< 0.01	< 10	0.03	50
39557	208	294	< 0.002	< 0.2	0.80	< 5	650	< 0.5	2	0.14	< 0.5	4	59	11	1.30	10	< 1	0.48	30	0.42	245
39558	208	294	< 0.002	< 0.2	0.52	< 5	230	< 0.5	< 2	0.05	< 0.5	2	62	1	0.82	10	< 1	0.31	30	0.16	145
39559	208	294	< 0.002	< 0.2	1.01	< 5	1450	< 0.5	2	0.13	< 0.5	5	57	5	1.66	10	< 1	0.59	30	0.47	295
39560	208	294	< 0.002	< 0.2	0.23	< 5	240	< 0.5	< 2	0.01	< 0.5	2	181	1	0.56	< 10	< 1	0.10	< 10	0.06	270
39561	208	294	< 0.002	< 0.2	1.06	< 5	630	< 0.5	< 2	0.12	< 0.5	5	49	6	1.70	10	< 1	0.65	30	0.51	280
39562	208	294	< 0.002	< 0.2	0.27	< 5	200	< 0.5	< 2	0.03	< 0.5	2	189	5	0.72	< 10	< 1	0.14	< 10	0.12	120

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Page Number : 1-B
Total Pages : 2
Invoice Date: 11-OCT-90
Invoice No. : I-9024260
P.O. Number :

CERTIFICATE OF ANALYSIS A9024260

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
37851	208	294	< 1	< 0.01	3	100	256	< 5	< 1	2	< 0.01	< 10	< 10	2	< 10	46
37852	208	294	< 1	0.01	3	570	70	< 5	2	9	0.01	< 10	< 10	7	< 10	68
37853	208	294	< 1	0.01	3	570	82	< 5	3	10	0.01	< 10	< 10	9	< 10	70
37854	208	294	< 1	0.01	3	550	56	< 5	3	8	0.01	< 10	< 10	7	< 10	66
37855	208	294	< 1	0.01	4	510	42	< 5	2	8	< 0.01	< 10	< 10	7	< 10	74
37856	208	294	< 1	0.01	2	160	72	< 5	< 1	4	< 0.01	< 10	< 10	1	< 10	40
37857	208	294	< 1	0.02	3	90	28	< 5	< 1	5	< 0.01	< 10	< 10	< 1	< 10	34
37858	208	294	< 1	< 0.01	2	80	38	< 5	1	4	< 0.01	< 10	< 10	1	< 10	54
37859	208	294	< 1	0.02	2	60	22	< 5	1	4	< 0.01	< 10	< 10	< 1	< 10	42
37860	208	294	< 1	0.02	2	60	24	< 5	< 1	4	< 0.01	< 10	< 10	1	< 10	38
37861	208	294	< 1	0.03	1	70	26	< 5	2	5	< 0.01	< 10	< 10	1	< 10	58
37862	208	294	< 1	0.01	< 1	40	22	< 5	1	3	< 0.01	< 10	< 10	< 1	< 10	34
37863	208	294	< 1	0.01	< 1	60	20	< 5	1	4	< 0.01	< 10	< 10	< 1	< 10	38
37864	208	294	< 1	0.01	< 1	70	22	< 5	< 1	4	< 0.01	< 10	< 10	< 1	< 10	40
37865	208	294	< 1	0.01	< 1	250	42	< 5	< 1	6	< 0.01	< 10	< 10	2	< 10	48
37866	208	294	< 1	0.02	< 1	50	66	< 5	< 1	3	< 0.01	< 10	< 10	< 1	< 10	26
37867	208	294	< 1	0.02	1	40	34	< 5	< 1	3	< 0.01	< 10	< 10	< 1	< 10	22
37868	208	294	< 1	0.01	< 1	40	26	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	16
37869	208	294	< 1	0.02	2	510	12	< 5	2	13	< 0.01	< 10	< 10	9	< 10	52
37870	208	294	< 1	0.01	1	520	4	< 5	2	8	< 0.01	< 10	< 10	7	< 10	50
37871	208	294	< 1	< 0.01	2	30	14	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	14
37872	208	294	1	< 0.01	4	10	174	< 5	< 1	3	< 0.01	< 10	< 10	< 1	< 10	18
37873	208	294	< 1	< 0.01	3	< 10	84	< 5	< 1	5	< 0.01	< 10	< 10	< 1	< 10	12
37874	208	294	< 1	< 0.01	3	10	16	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	6
37875	208	294	< 1	0.01	2	40	20	< 5	< 1	7	< 0.01	< 10	< 10	1	< 10	24
37876	208	294	< 1	0.01	1	50	24	< 5	1	6	< 0.01	< 10	< 10	1	< 10	36
37877	208	294	1	0.02	1	70	64	< 5	1	8	< 0.01	< 10	< 10	2	< 10	88
37878	208	294	< 1	0.02	1	30	12	< 5	< 1	7	< 0.01	< 10	< 10	1	< 10	30
37879	208	294	< 1	0.01	1	50	20	< 5	1	9	< 0.01	< 10	< 10	1	< 10	46
37880	208	294	1	< 0.01	8	240	< 2	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	148
37881	208	294	< 1	< 0.01	3	720	< 2	< 5	< 1	15	0.07	< 10	< 10	5	< 10	52
39385	208	294	< 1	0.01	1	230	10	< 5	< 1	28	< 0.01	< 10	< 10	< 1	< 10	6
39386	208	294	< 1	< 0.01	10	100	4	5	< 1	16	< 0.01	< 10	< 10	9	< 10	22
39387	208	294	< 1	< 0.01	6	20	2	< 5	< 1	< 1	< 0.01	< 10	< 10	< 1	< 10	8
39557	208	294	< 1	0.02	4	410	10	< 5	2	7	0.02	< 10	< 10	7	< 10	46
39558	208	294	< 1	0.02	2	190	8	< 5	1	3	0.01	< 10	< 10	3	< 10	26
39559	208	294	< 1	0.02	6	480	10	< 5	4	12	0.03	< 10	< 10	10	< 10	58
39560	208	294	< 1	0.01	3	60	6	< 5	< 1	4	< 0.01	< 10	< 10	1	< 10	12
39561	208	294	< 1	0.02	6	470	8	< 5	3	10	0.05	< 10	< 10	11	< 10	62
39562	208	294	< 1	0.01	4	120	< 2	< 5	< 1	4	0.01	< 10	< 10	3	< 10	14

CERTIFICATION: B. Caughlin

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Page Number : 2-A
Total Pages : 2
Invoice Date: 11-OCT-90
Invoice No. : I-9024260
P.O. Number :

CERTIFICATE OF ANALYSIS A9024260

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
39563	208	294	< 0.002	< 0.2	1.11	< 5	650	< 0.5	< 2	0.15	< 0.5	6	125	9	2.02	10	< 1	0.62	30	0.53	360
39564	208	294	< 0.002	< 0.2	0.96	< 5	960	0.5	< 2	0.15	< 0.5	5	90	6	1.80	< 10	< 1	0.62	20	0.51	305
39565	208	294	< 0.002	< 0.2	0.92	5	490	< 0.5	2	0.16	< 0.5	6	100	7	1.75	< 10	< 1	0.64	20	0.49	295
39566	208	294	< 0.002	0.8	0.22	< 5	180	< 0.5	4	0.05	< 0.5	1	214	< 1	0.44	< 10	< 1	0.16	< 10	0.07	135
39567	208	294	< 0.002	< 0.2	0.14	< 5	120	< 0.5	< 2	0.03	< 0.5	1	325	1	0.49	< 10	< 1	0.05	< 10	0.04	125
39568	208	294	< 0.002	< 0.2	0.48	< 5	500	< 0.5	< 2	0.07	< 0.5	3	176	3	0.89	< 10	< 1	0.28	10	0.22	195
39569	208	294	< 0.002	0.4	1.10	< 5	550	< 0.5	2	0.20	< 0.5	5	126	9	1.72	10	< 1	0.69	30	0.46	315
39570	208	294	< 0.002	< 0.2	0.59	< 5	290	< 0.5	< 2	0.09	< 0.5	3	88	1	1.16	10	< 1	0.33	40	0.17	200
39571	208	294	< 0.002	< 0.2	0.77	< 5	490	< 0.5	< 2	0.08	< 0.5	3	100	2	1.16	10	< 1	0.48	40	0.33	250
39572	208	294	< 0.002	< 0.2	0.77	< 5	420	< 0.5	2	0.09	< 0.5	3	75	1	1.23	10	< 1	0.48	40	0.39	250
39573	208	294	< 0.002	0.4	0.88	< 5	630	< 0.5	< 2	0.12	< 0.5	5	106	< 1	1.58	10	< 1	0.41	30	0.30	235
39574	208	294	< 0.002	0.6	0.43	< 5	580	< 0.5	< 2	0.08	< 0.5	4	79	< 1	1.61	< 10	< 1	0.18	30	0.06	265
39575	208	294	< 0.002	0.4	0.10	< 5	120	< 0.5	< 2	0.01	< 0.5	1	186	< 1	0.50	< 10	< 1	0.06	< 10	< 0.01	115
39576	208	294	< 0.002	< 0.2	0.63	< 5	330	< 0.5	2	0.08	< 0.5	3	67	2	1.20	10	< 1	0.36	40	0.22	320
39577	208	294	< 0.002	< 0.2	0.23	< 5	190	< 0.5	< 2	0.02	< 0.5	2	154	< 1	0.71	< 10	< 1	0.16	< 10	0.02	210
39578	208	294	< 0.002	< 0.2	0.77	< 5	350	< 0.5	< 2	0.08	< 0.5	3	66	4	1.49	10	< 1	0.37	50	0.29	320
39579	208	294	< 0.002	< 0.2	0.67	< 5	270	< 0.5	< 2	0.07	1.0	3	108	10	1.25	10	< 1	0.35	30	0.27	260
39580	208	294	< 0.002	< 0.2	0.68	< 5	220	< 0.5	< 2	0.06	< 0.5	2	85	4	1.05	10	< 1	0.41	40	0.30	205
39581	208	294	< 0.002	< 0.2	1.00	5	390	< 0.5	< 2	0.12	< 0.5	5	96	7	1.31	10	< 1	0.58	40	0.49	280
39582	208	294	< 0.002	< 0.2	0.79	< 5	280	< 0.5	< 2	0.08	< 0.5	3	97	5	1.17	10	< 1	0.49	40	0.26	260
39583	208	294	< 0.002	< 0.2	0.88	< 5	300	< 0.5	< 2	0.08	< 0.5	3	77	2	1.49	10	< 1	0.48	40	0.31	240
39584	208	294	< 0.002	< 0.2	0.67	< 5	260	< 0.5	< 2	0.05	< 0.5	2	55	3	1.22	10	< 1	0.43	50	0.27	240
39585	208	294	< 0.002	< 0.2	0.16	< 5	100	< 0.5	< 2	0.01	< 0.5	1	131	< 1	0.45	< 10	< 1	0.11	10	0.05	130
39586	208	294	< 0.002	< 0.2	0.64	< 5	220	< 0.5	< 2	0.05	< 0.5	3	67	1	1.45	10	< 1	0.36	60	0.23	240
39587	208	294	< 0.002	< 0.2	0.69	< 5	210	< 0.5	< 2	0.05	< 0.5	3	67	< 1	1.60	10	< 1	0.40	60	0.28	230
39588	208	294	< 0.002	< 0.2	0.84	< 5	410	< 0.5	< 2	0.06	< 0.5	3	93	< 1	1.73	10	< 1	0.47	50	0.33	275
39589	208	294	< 0.002	< 0.2	0.98	< 5	360	< 0.5	2	0.14	< 0.5	4	83	< 1	1.75	10	< 1	0.60	30	0.46	315
39590	208	294	< 0.002	< 0.2	0.28	< 5	3510	< 0.5	< 2	0.01	< 0.5	1	36	< 1	0.44	< 10	< 1	0.28	< 10	0.03	140
39591	208	294	< 0.002	< 0.2	0.03	< 5	170	< 0.5	< 2	< 0.01	< 0.5	< 1	249	< 1	0.40	< 10	< 1	< 0.01	< 10	< 0.01	95
39592	208	294	< 0.002	0.8	0.27	< 5	770	< 0.5	< 2	< 0.01	< 0.5	< 1	99	< 1	1.54	< 10	< 1	0.27	< 10	0.03	15
39593	208	294	< 0.002	< 0.2	0.45	< 5	940	< 0.5	< 2	< 0.01	< 0.5	< 1	104	< 1	1.62	< 10	< 1	0.25	10	0.07	25
39594	208	294	< 0.002	< 0.2	0.78	< 5	240	< 0.5	2	< 0.01	< 0.5	< 1	105	< 1	0.95	< 10	< 1	0.56	30	0.45	75
39599	208	294	< 0.002	< 0.2	1.19	< 5	540	< 0.5	< 2	0.18	< 0.5	3	154	1	2.00	< 10	< 1	0.55	20	0.24	95
39600	208	294	< 0.002	< 0.2	0.89	< 5	410	< 0.5	< 2	0.26	< 0.5	3	82	2	1.72	10	< 1	0.32	30	0.27	135

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Invoice Date: 11-OCT-90
Invoice No. : I-9024260
P.O. Number :

CERTIFICATE OF ANALYSIS A9024260

SAMPLE DESCRIPTION	PREP CODE	Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
39563	208 294	< 1	0.01	9	520	10	< 5	4	9	0.04	< 10	< 10	12	< 10	64
39564	208 294	< 1	0.02	6	480	8	< 5	3	15	0.05	< 10	< 10	12	< 10	62
39565	208 294	2	0.02	7	500	10	< 5	2	15	0.05	< 10	< 10	10	< 10	80
39566	208 294	< 1	< 0.01	3	180	54	< 5	< 1	7	< 0.01	< 10	< 10	2	< 10	10
39567	208 294	< 1	0.01	4	110	8	< 5	< 1	3	< 0.01	< 10	< 10	2	< 10	6
39568	208 294	< 1	0.01	4	230	10	< 5	< 1	16	0.01	< 10	< 10	6	< 10	26
39569	208 294	< 1	0.03	5	460	32	< 5	3	16	0.05	< 10	< 10	11	< 10	112
39570	208 294	< 1	0.02	3	270	10	< 5	2	5	0.01	< 10	< 10	2	< 10	36
39571	208 294	< 1	0.03	4	250	12	< 5	2	8	0.02	< 10	< 10	3	< 10	40
39572	208 294	< 1	0.02	4	300	12	< 5	3	6	0.02	< 10	< 10	4	< 10	42
39573	208 294	< 1	0.01	5	360	30	< 5	2	12	0.01	< 10	< 10	4	< 10	40
39574	208 294	< 1	0.02	3	260	40	< 5	2	9	< 0.01	10	< 10	< 1	< 10	46
39575	208 294	< 1	< 0.01	2	40	10	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	8
39576	208 294	< 1	0.02	2	260	10	< 5	1	6	0.01	< 10	< 10	1	< 10	36
39577	208 294	< 1	< 0.01	2	70	14	< 5	< 1	5	< 0.01	< 10	< 10	< 1	< 10	18
39578	208 294	< 1	0.02	2	260	14	< 5	2	8	0.01	< 10	< 10	2	< 10	48
39579	208 294	< 1	0.02	4	270	12	< 5	1	6	0.02	< 10	< 10	7	< 10	36
39580	208 294	< 1	0.03	3	240	10	< 5	2	4	0.02	< 10	< 10	5	< 10	34
39581	208 294	< 1	0.02	9	340	20	< 5	2	6	0.03	< 10	< 10	9	< 10	40
39582	208 294	< 1	0.02	4	290	16	< 5	< 1	4	0.02	< 10	< 10	3	< 10	38
39583	208 294	< 1	0.02	2	310	12	< 5	1	5	0.03	< 10	< 10	6	< 10	48
39584	208 294	< 1	0.02	2	260	20	< 5	1	4	0.03	< 10	< 10	4	< 10	40
39585	208 294	< 1	< 0.01	2	60	30	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	8
39586	208 294	< 1	0.03	3	240	12	< 5	1	5	0.03	< 10	< 10	4	< 10	44
39587	208 294	< 1	0.04	2	260	6	< 5	1	5	0.03	< 10	< 10	5	< 10	46
39588	208 294	< 1	0.04	3	260	10	< 5	2	9	0.04	< 10	< 10	7	< 10	56
39589	208 294	< 1	0.04	4	360	2	< 5	2	16	0.06	< 10	< 10	12	< 10	48
39590	208 294	< 1	< 0.01	1	40	26	< 5	< 1	83	< 0.01	< 10	< 10	3	< 10	6
39591	208 294	< 1	< 0.01	3	< 10	2	< 5	< 1	4	< 0.01	< 10	< 10	1	< 10	6
39592	208 294	< 1	< 0.01	< 1	< 10	84	< 5	< 1	7	< 0.01	< 10	< 10	< 1	< 10	8
39593	208 294	2	0.03	1	< 10	4	< 5	< 1	11	< 0.01	< 10	< 10	< 1	< 10	42
39594	208 294	< 1	0.02	2	90	< 2	< 5	< 1	14	0.03	< 10	< 10	1	< 10	40
39599	208 294	< 1	0.03	3	590	2	< 5	4	8	0.02	< 10	< 10	11	< 10	58
39600	208 294	< 1	0.01	3	540	16	< 5	2	14	0.01	< 10	< 10	6	< 10	72

CERTIFICATION: B. Caryl

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

A9024261

Comments: CC: ART TROUP

CERTIFICATE A9024261

ARBOR RESOURCES INC.

Project: AOR-DAW
P.O. # :

Samples submitted to our lab in Vancouver, BC.
This report was printed on 11-OCT-90.

SAMPLE PREPARATION

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION
208	68	Assay ring to approx 150 mesh
294	68	Crush and split (0-10 pounds)
238	68	NITRIC-AQUA REGIA DIGESTION
* NOTE	1:	

The 32 element ICP package is suitable for trace metals in soil and rock samples. Elements for which the nitric-aqua regia digestion is possibly incomplete are: Al, Ba, Be, Ca, Cr, Ga, K, La, Mg, Na, Sr, Ti, Tl, W.

ANALYTICAL PROCEDURES

CHEMEX CODE	NUMBER SAMPLES	DESCRIPTION	METHOD	DETECTION LIMIT	UPPER LIMIT
398	68	Au oz/T: 1/2 assay ton	FA-AAS	0.002	20.00
922	68	Ag ppm: 32 element, soil & rock	ICP-AES	0.2	200
921	68	Al %: 32 element, soil & rock	ICP-AES	0.01	15.00
923	68	As ppm: 32 element, soil & rock	ICP-AES	5	10000
924	68	Ba ppm: 32 element, soil & rock	ICP-AES	10	10000
925	68	Be ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
926	68	Bi ppm: 32 element, soil & rock	ICP-AES	2	10000
927	68	Ca %: 32 element, soil & rock	ICP-AES	0.01	15.00
928	68	Cd ppm: 32 element, soil & rock	ICP-AES	0.5	100.0
929	68	Co ppm: 32 element, soil & rock	ICP-AES	1	10000
930	68	Cr ppm: 32 element, soil & rock	ICP-AES	1	10000
931	68	Cu ppm: 32 element, soil & rock	ICP-AES	1	10000
932	68	Fe %: 32 element, soil & rock	ICP-AES	0.01	15.00
933	68	Ga ppm: 32 element, soil & rock	ICP-AES	10	10000
951	68	Hg ppm: 32 element, soil & rock	ICP-AES	1	10000
934	68	K %: 32 element, soil & rock	ICP-AES	0.01	10.00
935	68	La ppm: 32 element, soil & rock	ICP-AES	10	10000
936	68	Mg %: 32 element, soil & rock	ICP-AES	0.01	15.00
937	68	Mn ppm: 32 element, soil & rock	ICP-AES	5	10000
938	68	Mo ppm: 32 element, soil & rock	ICP-AES	1	10000
939	68	Na %: 32 element, soil & rock	ICP-AES	0.01	5.00
940	68	Ni ppm: 32 element, soil & rock	ICP-AES	1	10000
941	68	P ppm: 32 element, soil & rock	ICP-AES	10	10000
942	68	Pb ppm: 32 element, soil & rock	ICP-AES	2	10000
943	68	Sb ppm: 32 element, soil & rock	ICP-AES	5	10000
958	68	Sc ppm: 32 elements, soil & rock	ICP-AES	1	10000
944	68	Sr ppm: 32 element, soil & rock	ICP-AES	1	10000
945	68	Ti %: 32 element, soil & rock	ICP-AES	0.01	5.00
946	68	Tl ppm: 32 element, soil & rock	ICP-AES	10	10000
947	68	U ppm: 32 element, soil & rock	ICP-AES	10	10000
948	68	V ppm: 32 element, soil & rock	ICP-AES	1	10000
949	68	W ppm: 32 element, soil & rock	ICP-AES	10	10000
950	68	Zn ppm: 32 element, soil & rock	ICP-AES	2	10000

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Page Number : 1-A
Total Pages : 2
Invoice Date: 11-OCT-90
Invoice No. : I-9024261
P.O. Number :

CERTIFICATE OF ANALYSIS A9024261

SAMPLE DESCRIPTION	PREP CODE		Au oz/T	Ag ppm	Al %	As ppm	Ba ppm	Be ppm	Bi ppm	Ca %	Cd ppm	Co ppm	Cr ppm	Cu ppm	Fe %	Ga ppm	Hg ppm	K %	La ppm	Mg %	Mn ppm
37882	208	294	0.010	1.6	0.34	< 5	80	< 0.5	< 2	0.02	< 0.5	1	288	4	0.71	< 10	< 1	0.12	< 10	0.04	45
37883	208	294	< 0.002	0.6	0.53	< 5	320	< 0.5	< 2	0.03	< 0.5	1	253	3	0.61	< 10	< 1	0.22	20	0.09	40
37884	208	294	< 0.002	0.4	0.56	< 5	190	< 0.5	< 2	0.05	< 0.5	1	167	6	0.95	< 10	< 1	0.29	10	0.08	75
37885	208	294	< 0.002	1.6	2.08	< 5	360	< 0.5	< 2	0.24	1.0	15	163	36	3.73	< 10	< 1	0.33	20	0.75	365
37886	208	294	< 0.002	3.4	2.31	15	280	< 0.5	< 2	0.39	3.5	21	120	56	4.46	< 10	< 1	0.15	10	1.09	1265
37887	208	294	< 0.002	1.2	2.36	20	420	< 0.5	2	0.48	2.0	11	127	28	3.48	< 10	< 1	0.24	20	1.03	505
37888	208	294	< 0.002	1.0	2.93	< 5	420	< 0.5	< 2	0.79	1.5	12	100	22	3.75	< 10	< 1	0.31	10	1.37	590
37889	208	294	< 0.002	3.0	2.37	20	290	< 0.5	< 2	0.56	4.0	23	77	58	4.61	< 10	< 1	0.18	10	0.96	1555
37890	208	294	< 0.002	64.8	5.61	100	2100	< 0.5	< 2	0.32	81.0	229	36	452	13.20	< 10	< 1	0.37	30	0.53	>10000
37891	208	294	0.002	15.4	1.97	850	660	< 0.5	< 2	0.21	6.5	12	63	354	>15.00	< 10	< 1	0.46	70	0.10	295
37892	208	294	< 0.002	5.4	2.86	15	360	< 0.5	< 2	0.46	3.5	27	50	48	4.68	< 10	< 1	0.34	20	1.12	1185
37893	208	294	0.110	80.0	0.72	10	280	< 0.5	10	0.07	1.5	4	133	140	3.72	< 10	23	0.11	< 10	0.64	495
37894	208	294	0.002	7.2	0.84	< 5	2730	< 0.5	2	0.02	0.5	3	168	14	1.87	< 10	5	0.47	10	0.14	270
37895	208	294	0.002	6.6	0.82	10	510	< 0.5	< 2	0.10	1.5	4	117	35	4.60	< 10	< 1	0.31	10	0.33	355
37896	208	294	0.002	6.0	3.44	< 5	690	< 0.5	2	0.24	4.5	12	178	74	3.80	< 10	< 1	0.37	20	3.62	1905
37897	208	294	0.010	20.4	1.72	< 5	370	< 0.5	6	0.16	12.0	14	163	134	2.60	< 10	< 1	0.18	10	1.96	2560
37898	208	294	0.044	54.6	2.24	5	770	< 0.5	12	0.10	2.0	2	162	163	3.89	< 10	< 1	0.38	20	2.16	430
37899	208	294	0.042	97.8	1.12	20	450	< 0.5	4	0.07	0.5	2	109	167	4.25	< 10	4	0.22	20	0.91	160
37900	208	294	0.101	77.4	2.22	20	680	< 0.5	8	0.13	0.5	3	131	225	5.07	< 10	10	0.32	10	1.83	240
37901	208	294	0.010	33.6	1.15	10	560	< 0.5	12	0.10	2.0	8	124	161	3.59	< 10	2	0.34	20	0.75	730
37902	208	294	0.048	47.6	1.66	15	510	< 0.5	12	0.12	6.5	12	150	181	3.04	< 10	1	0.26	10	1.82	1480
37903	208	294	0.006	17.0	0.24	< 5	130	< 0.5	4	0.10	2.5	8	195	41	0.57	< 10	< 1	0.04	< 10	0.19	855
37904	208	294	0.008	14.4	0.88	10	570	< 0.5	14	0.07	1.0	2	142	129	3.67	< 10	< 1	0.32	20	0.45	180
37905	208	294	0.008	19.2	0.55	50	490	< 0.5	6	0.05	0.5	2	140	167	4.66	< 10	3	0.32	20	0.22	140
37906	208	294	0.002	11.0	0.71	55	630	< 0.5	4	0.04	< 0.5	1	154	53	3.77	< 10	< 1	0.44	10	0.21	50
37907	208	294	0.002	8.0	0.86	75	520	< 0.5	< 2	0.06	0.5	1	121	72	5.58	< 10	< 1	0.38	10	0.14	85
37908	208	294	0.008	30.8	0.56	< 5	1570	< 0.5	< 2	0.01	< 0.5	< 1	172	6	1.83	< 10	1	0.32	10	0.03	35
37909	208	294	0.043	21.8	0.70	390	500	< 0.5	< 2	0.09	0.5	5	133	82	>15.00	< 10	2	0.25	10	0.07	175
37910	208	294	0.004	16.0	0.80	55	580	< 0.5	< 2	0.03	< 0.5	2	163	49	4.54	< 10	7	0.50	10	0.09	75
37911	208	294	0.006	35.4	0.44	25	970	< 0.5	2	0.01	< 0.5	2	144	23	2.34	< 10	13	0.24	10	0.06	55
37912	208	294	< 0.002	7.6	0.54	40	450	< 0.5	2	0.01	< 0.5	1	145	7	2.30	< 10	1	0.36	10	0.05	20
37913	208	294	0.010	38.0	0.52	20	800	< 0.5	4	0.03	0.5	1	130	40	2.96	< 10	< 1	0.37	10	0.16	90
37914	208	294	0.004	10.6	1.70	75	710	< 0.5	4	0.20	1.0	7	106	127	3.12	< 10	< 1	0.34	20	0.46	200
37915	208	294	0.002	22.2	0.44	35	550	< 0.5	< 2	0.04	0.5	3	168	59	2.38	< 10	< 1	0.20	10	0.06	60
37916	208	294	< 0.002	6.4	2.13	50	640	< 0.5	6	0.25	2.0	9	114	45	3.72	< 10	< 1	0.32	20	1.37	285
37917	208	294	< 0.002	3.6	2.15	100	380	< 0.5	4	0.21	3.0	10	148	62	3.47	< 10	< 1	0.15	10	1.88	630
37918	208	294	< 0.002	2.6	2.06	60	480	< 0.5	4	0.14	4.5	10	238	49	3.20	< 10	< 1	0.18	10	1.76	940
37919	208	294	< 0.002	0.6	0.29	< 5	610	< 0.5	< 2	0.01	< 0.5	1	104	2	1.72	< 10	< 1	0.15	< 10	0.05	145
37920	208	294	1.377	>200	0.15	30	1670	< 0.5	76	< 0.01	1.5	2	301	328	4.93	< 10	60	< 0.01	< 10	0.01	40
37921	208	294	0.040	22.8	0.40	< 5	290	< 0.5	4	1.21	< 0.5	15	168	36	1.81	< 10	2	0.01	10	0.29	175

CERTIFICATION: B. Caughlin

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

To: ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Invoice Date: 11-OCT-90
Invoice No. : I-9024261
P.O. Number :

CERTIFICATE OF ANALYSIS A9024261

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
37882	208	294	1	< 0.01	4	10	42	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	34
37883	208	294	< 1	0.02	3	100	10	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	28
37884	208	294	1	0.02	3	100	38	< 5	2	8	< 0.01	< 10	< 10	2	< 10	44
37885	208	294	1	0.02	12	850	< 2	< 5	3	12	< 0.01	< 10	< 10	15	< 10	214
37886	208	294	3	< 0.01	26	1230	< 2	< 5	3	19	0.02	< 10	< 10	21	< 10	408
37887	208	294	1	0.02	21	950	2	< 5	4	25	0.09	< 10	< 10	32	< 10	270
37888	208	294	< 1	0.02	9	1070	< 2	< 5	4	45	0.21	< 10	< 10	20	< 10	250
37889	208	294	3	0.01	18	1200	< 2	< 5	3	37	0.13	< 10	< 10	16	< 10	542
37890	208	294	51	0.02	162	2350	28	15	10	94	0.02	< 10	< 10	26	10	3830
37891	208	294	18	0.04	24	5760	10	50	6	328	< 0.01	< 10	< 10	34	< 50	206
37892	208	294	2	0.01	16	1230	4	< 5	5	25	0.01	< 10	< 10	27	< 10	336
37893	208	294	2	< 0.01	6	680	444	30	1	13	0.03	< 10	< 10	9	< 10	270
37894	208	294	2	0.02	4	370	48	< 5	1	54	0.04	< 10	< 10	10	< 10	90
37895	208	294	3	0.03	5	840	112	5	2	63	0.04	< 10	< 10	9	< 10	256
37896	208	294	2	0.01	12	800	102	5	4	21	0.02	< 10	< 10	24	< 10	654
37897	208	294	1	< 0.01	12	620	264	5	3	28	< 0.01	< 10	< 10	11	< 10	958
37898	208	294	1	0.01	7	690	424	30	3	45	< 0.01	< 10	< 10	18	< 10	500
37899	208	294	2	0.01	3	770	586	60	1	30	< 0.01	< 10	< 10	10	< 10	296
37900	208	294	3	0.01	7	750	352	30	3	24	0.01	< 10	< 10	14	< 10	530
37901	208	294	2	< 0.01	7	710	792	10	2	53	0.03	< 10	< 10	9	< 10	466
37902	208	294	1	< 0.01	10	640	564	15	2	23	0.01	< 10	< 10	14	< 10	1180
37903	208	294	< 1	< 0.01	6	500	108	5	< 1	7	< 0.01	< 10	< 10	2	< 10	192
37904	208	294	1	0.02	5	810	220	5	2	28	0.02	< 10	< 10	11	< 10	214
37905	208	294	1	0.02	4	880	774	230	1	39	0.02	< 10	< 10	10	< 10	244
37906	208	294	1	0.02	3	750	100	10	1	30	0.03	< 10	< 10	11	< 10	58
37907	208	294	1	0.01	3	1200	28	10	4	49	0.03	< 10	< 10	14	< 10	42
37908	208	294	1	0.18	2	1000	178	5	1	47	< 0.01	< 10	< 10	6	< 10	16
37909	208	294	17	0.12	9	3880	102	70	1	164	< 0.01	< 10	< 10	21	< 50	432
37910	208	294	3	0.02	3	630	88	15	2	28	< 0.01	< 10	< 10	10	< 10	48
37911	208	294	3	0.01	3	500	108	20	< 1	28	< 0.01	< 10	< 10	5	< 10	66
37912	208	294	4	0.06	2	320	36	5	< 1	46	< 0.01	< 10	< 10	5	< 10	12
37913	208	294	3	0.05	5	600	216	10	< 1	68	< 0.01	< 10	< 10	5	< 10	78
37914	208	294	6	0.01	18	760	32	5	2	25	< 0.01	< 10	< 10	34	< 10	204
37915	208	294	4	0.02	8	470	46	5	< 1	103	< 0.01	< 10	< 10	9	< 10	110
37916	208	294	3	0.01	19	870	64	5	2	24	< 0.01	< 10	< 10	33	< 10	344
37917	208	294	2	< 0.01	46	660	118	5	2	25	< 0.01	< 10	< 10	34	< 10	430
37918	208	294	2	0.01	40	490	16	5	2	14	< 0.01	< 10	< 10	43	< 10	336
37919	208	294	3	0.01	4	100	14	< 5	< 1	6	< 0.01	< 10	< 10	< 1	< 10	18
37920	208	294	4	< 0.01	7	< 10	2850	220	< 1	6	< 0.01	< 10	10	< 1	50	518
37921	208	294	< 1	0.04	20	290	198	5	1	161	0.07	< 10	< 10	26	< 10	30

CERTIFICATION: B. Caufield

Chemex Labs Ltd.

Analytical Chemists * Geochemists * Registered Assayers

212 Brooksbank Ave., North Vancouver
British Columbia, Canada V7J 2C1
PHONE: 604-984-0221

ARBOR RESOURCES INC.
ATTN: LARRY MCLEAN
1000 - 675 W. HASTINGS ST.
VANCOUVER, BC
V6B 1N2

Project : AOR-DAW
Comments: CC: ART TROUP

Page Number : 2-B
Total Pages : 2
Invoice Date: 11-OCT-90
Invoice No. : I-9024261
P.O. Number :

CERTIFICATE OF ANALYSIS A9024261

SAMPLE DESCRIPTION	PREP CODE		Mo ppm	Na %	Ni ppm	P ppm	Pb ppm	Sb ppm	Sc ppm	Sr ppm	Ti %	Tl ppm	U ppm	V ppm	W ppm	Zn ppm
37922	208	294	< 1	< 0.01	1	30	114	< 5	< 1	8	< 0.01	< 10	< 10	< 1	< 10	12
37923	208	294	2	0.01	4	520	34	< 5	9	22	< 0.01	< 10	< 10	7	< 10	106
39384	208	294	< 1	0.01	3	370	14	< 5	< 1	20	< 0.01	< 10	< 10	2	< 10	28
39388 + 39389	208	294	12	< 0.01	5	130	594	5	< 1	4	< 0.01	< 10	< 10	2	< 10	108
39390	208	294	< 1	< 0.01	4	< 10	18	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	6
39391	208	294	1	0.01	1	70	66	< 5	< 1	4	< 0.01	< 10	< 10	< 1	20	24
39392	208	294	< 1	< 0.01	4	10	14	< 5	< 1	< 1	< 0.01	< 10	< 10	< 1	< 10	2
39393	208	294	< 1	< 0.01	3	30	6	< 5	< 1	< 1	< 0.01	< 10	< 10	< 1	< 10	2
39394	208	294	1	< 0.01	4	90	66	< 5	< 1	24	< 0.01	< 10	< 10	< 1	< 10	6
39395	208	294	< 1	< 0.01	4	10	< 2	< 5	< 1	< 1	< 0.01	< 10	< 10	< 1	< 10	< 2
39396	208	294	6	0.01	7	400	>10000	10	3	15	0.02	< 10	< 10	23	< 50	1450
39397	208	294	9	0.02	14	400	4700	< 5	4	9	0.02	< 10	< 10	28	< 50	3360
39398	208	294	24	0.01	15	1000	>10000	< 5	5	14	0.01	10	70	27	< 50	9190
39399	208	294	2	0.03	19	200	4810	< 5	2	7	0.01	< 10	< 10	27	< 50	3550
39400	208	294	2	< 0.01	8	130	4070	< 5	< 1	17	< 0.01	< 10	< 10	7	< 10	2940
39401	208	294	1	< 0.01	4	< 10	356	< 5	< 1	< 1	< 0.01	< 10	< 10	1	< 10	120
39402	208	294	< 1	< 0.01	5	40	242	< 5	< 1	2	< 0.01	< 10	< 10	< 1	< 10	42
39403	208	294	< 1	< 0.01	4	< 10	134	< 5	< 1	< 1	< 0.01	< 10	< 10	< 1	< 10	18
39404	208	294	< 1	0.04	1	40	122	< 5	< 1	13	< 0.01	< 10	< 10	< 1	< 10	24
39405	208	294	7	0.03	2	100	174	< 5	2	14	0.04	< 10	< 10	8	< 10	50
39406	208	294	< 1	0.04	1	< 10	66	< 5	< 1	36	< 0.01	< 10	< 10	< 1	< 10	10
39407	208	294	< 1	< 0.01	3	< 10	52	< 5	< 1	1	< 0.01	< 10	< 10	< 1	< 10	4
39408	208	294	< 1	< 0.01	4	< 10	50	< 5	< 1	< 1	< 0.01	< 10	< 10	< 1	< 10	4
39409	208	294	< 1	< 0.01	4	< 10	44	< 5	< 1	< 1	< 0.01	< 10	< 10	< 1	< 10	4
39410	208	294	< 1	< 0.01	6	< 10	54	< 5	< 1	1	< 0.01	< 10	< 10	1	< 10	102
39411	208	294	< 1	< 0.01	10	110	44	< 5	< 1	15	< 0.01	< 10	< 10	8	< 10	24
39412	208	294	1	< 0.01	5	310	822	< 5	< 1	2	< 0.01	< 10	< 10	1	< 10	196
39413	208	294	1	0.01	76	460	24	< 5	1	19	0.13	< 10	< 10	33	< 10	50

CERTIFICATION: B. Caplin

Northern Analytical Laboratories ltd.

October 23,1990

Work Order # 08473

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 08473a

Sample: Rock

Assay Certificate for Samples Provided

Sample	ppb Au
39677	<10
39678	<10
39679	<10
39680	<10
39681	<10
39682	<10
39683	<10
39684	15
39685	<10
39686	<10
39687	12
39688	<10
39689	<10
39690	<10
39691	13
39692	<10
39693	<10
39694	11
39695	<10
39696	46
39697	<10
39698	35
39699	232
39700	322
37946	<10
37947	20
37969	16
37970	<10
37971	<10
37973	18

Au -- 15g Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

October 23,1990

Work Order # 08473

File # 08473b

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

Sample: Rock

Assay Certificate for Samples Provided

Sample	ppb Au
37975	10
37976	<10
37977	<10
37978	<10
37979	<10
37981	20
01805	17
01806	162
01807	27
01808	2114
01809	691
01810	1955
01811	317
01812	74
01813	312
01814	<10
01815	<10
01816	<10
01817	138
01818	10
01819	<10
01820	<10
01821	<10

Au -- 15g Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

APPENDIX IV

ROTARY DRILL LOGS

PERCUSSION DRILL LOG

Gay Gulch	30 m. @ 080° from the Freegold Vein	2250 ft.	Oct. 27 1990	90 R 1
Location	Northing	Easting	Elevation	Date Drilled	Hole Number

-60°	250°	Nil	100 ft.	0 ft. - Floor of Creek
Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth

To intersect Freegold Vein below surface outcrop with visible gold showing.
Purpose

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) QUARTZ BIOTITE MUSCOVITE SCHIST							
5	10	MEDIUM BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST							
10	15	PALE BROWN (WEAKLY OXIDIZED) QUARTZ MUSCOVITE SCHIST							
15	20	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
20	25	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
25	30	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
30	35	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
35	40	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
40	45	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST WITH TRACE PYRITE							
45	50	WHITE QUARTZ MUSCOVITE SCHIST							
50	55	WHITE QUARTZ MUSCOVITE SCHIST							
55	60	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
60	65	BROWN QUARTZ BIOTITE MUSCOVITE SCHIST - WET SAMPLE WATER FLOW? - POSSIBLE FRACTURE OR FAULT ZONE?							
65	70	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
70	75	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
75	80	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
80	85	PALE BROWN QUARTZ BIOTITE MUSCOVITE SCHIST							
85	90	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
90	95	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
95	100	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
GAY GULCH	GAY G. I.P.L.	13+32.5E		OCT 27, 28 1990	90R2

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			100 ft	

Purpose: To test I.P anomaly thought to represent quartz veins

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST							
5	10	" " " " "							
10	15	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
15	20	LIGHT BROWN (WEAKLY OXIDIZED) QUARTZ MUSCOVITE SCHIST							
20	25	" " " " " " "							
25	30	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
30	35	" " " " " "							
35	40	" " " " " " WITH MUCH WATER - POSSIBLE FRACTURE OR FAULT ZONE							
40	45	WHITE QUARTZ MUSCOVITE SCHIST							
45	50	" " " "							
50	55	LIGHT BROWN (WEAKLY OXIDIZED) QUARTZ MUSCOVITE SCHIST							
55	60	" " " " " " "							
60	65	" " " " " " "							
65	70	" " " " " " WITH MUCH WATER - POSSIBLE FRACTURE OR FAULT ZONE							
70	75	LIGHT BROWN (WEAKLY OXIDIZED) QUARTZ MUSCOVITE SCHIST WITH MUCH WATER POSSIBLE FRACTURE OR FAULT ZONE							
75	86	LIGHT BROWN (WEAKLY OXIDIZED) QUARTZ MUSCOVITE SCHIST WITH MUCH WATER - POSSIBLE FRACTURE OR FAULT ZONE							
86	85	LIGHT BROWN (WEAKLY OXIDIZED) QUARTZ MUSCOVITE SCHIST WITH MUCH WATER - POSSIBLE FRACTURE OR FAULT ZONE							
85	90	LIGHT BROWN (WEAKLY OXIDIZED) QUARTZ MUSCOVITE SCHIST WITH MUCH WATER - POSSIBLE FRACTURE OR FAULT ZONE							
96	95	LIGHT BROWN (WEAKLY OXIDIZED) QUARTZ MUSCOVITE SCHIST WITH MUCH WATER - POSSIBLE FRACTURE OR FAULT ZONE							
95	100	LIGHT BROWN (WEAKLY OXIDIZED) QUARTZ MUSCOVITE SCHIST WITH MUCH WATER POSSIBLE FRACTURE OR FAULT ZONE							
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
GAY GULCH	GAY GULCH	I.P. L 12+90E		OCT. 28, 1990	90R3

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-60°	240°		100 ft	

Purpose: To test I.P. anomally thought to represent quartz veins

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST							
5	10	" " " " "							
10	15	PALE GREY/WHITE " " "							
15	20	" " " " " "							
20	25	" " " " " "							
25	30	WHITE " " "							
30	35	" " " " " WITH							
		MUCH WATER - POSSIBLE FRACTURE OR FAULT ZONE							
35	40	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
40	45	" " " " " "							
45	50	" " " " " "							
50	55	" " " " " "							
55	60	" " " " " WITH							
		MUCH WATER - POSSIBLE FRACTURE OR FAULT ZONE							
60	65	AS FOR 55-60							
65	70	" " " "							
70	75	" " " "							
75	80	" " " "							
80	85	" " " " WITH 1% FINELY DISSEMINATED BLACK MINERAL							
85	90	" " " " " 10% " COARSER " "							
90	95	" " " " " 1% " " " "							
95	100	" " " " " " " " " "							
		END OF HOLE							
		BLACK MINERAL MAY BE SPHALERITE, MAGNETITE OR MAFIC							

PERCUSSION DRILL LOG

GAY GULCH	15 m E 080°	FROM FREEGOLD VN IN CK		OCT 28, 1990	90 R4
Location	Northing	Easting	Elevation	Date Drilled	Hole Number
-45°	250°		80 ft		
Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth	

To intersect quartz vein with v.g. at depth.
Purpose

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST							
5	10	LIGHT BROWN (WEAKLY OXIDIZED) QUARTZ MUSCOVITE SCHIST							
10	15	" " " " " " "							
15	20	" " " " " " "							
20	25	" " " " " " "							
		TRACE RUSTY PYRITE SEEDS							
25	30	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
30	35	" " " " " "							
35	40	" " " " " "							
40	45	" " " " " "							
45	50	" " " " " "							
50	55	" " " " " "							
55	60	" " " " " "							
60	65	WHITE " " " "							
65	70	" " " " "							
70	75	" " " " "							
75	80	" " " " "							
		END OF HOLE							

PERCUSSION DRILL LOG

GAY GULCH	15m @ 260° FROM FREE GOLD VN IN CK			OCT 28-29, 1990	90 RS
Location	Northing	Easting	Elevation	Date Drilled	Hole Number
-45°	070°		125 ft		
Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth	

To intersect quartz vein with v.g at depth.
Purpose

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST							
5	10	PALE BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST							
10	15	PALE GREY/WHITE " " "							
15	20	" " "							
20	25	" " "							
25	30	" " "							
30	35	" " "							
35	40	" " "							
40	45	" " "							
45	50	" " "							
50	55	WHITE " "							
55	60	" " "							
60	65	" " "							
65	70	" " "							
70	75	PALE BROWN " "							
75	80	VERY PALE BROWN " "							
80	85	DARK GREY/WHITE (WET SAMPLE) QTZ " "	MUCH WATER						
85	90	PALE BROWN QUARTZ BIOTITE MUSCOVITE SCHIST							
90	95	" " " " " WITH MUCH WATER - POSSIBLE FRACTURE OR FAULT ZONE							
95	100	WHITE QUARTZ BIOTITE MUSCOVITE SCHIST							
100	105	" " " " "							
105	110	BROWN (WET) QUARTZ BIOTITE MUSCOVITE SCHIST WITH MUCH WATER - POSSIBLE FRACTURE OR FAULT ZONE							
110	115	as for 105-110							
115	120	as for 105-110							
120	125	DARK BROWN QUARTZ BIOTITE MUSCOVITE SCHIST							
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
GAY GULCH	30m @ 090°	FROM TOP OF 90GGTR02		OCT 29, 1990	90R6

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-60°	210°		150 ft	

Purpose: To test for Free gold vein interpolation between Gay Gulch & 90GGTR02

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	RED BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST							
5	10	as for 0-5							
10	15	PALE BROWN QUARTZ MUSCOVITE SCHIST							
15	20	" " " " "							
20	25	" " " " "							
25	30	" " " " "							
30	35	PALE GREY/WHITE " " "							
35	40	" " " " "							
40	45	" " " " "							
45	50	PALE BROWN " " "							
50	55	" " " " "							
55	60	" " " " "							
60	65	" " " " "							
65	70	" " " " "							
70	75	" " " " "							
75	80	" " " " "							
80	85	" " " " "							
85	90	" " " " "							
90	95	" " " " "							
95	100	" " " " "							
100	105	" " " " "							
105	110	" " " " "							
110	115	" " " " "							
115	120	" " " " "							
120	125	" " " " "							
125	130	" " " " "							
130	135	" " " " "							
135	140	" " " " "							
140	145	" " " " "							
145	150	" " " " "							

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
GAY GULCH	30m @ 090° FROM TOP OF 9066TR02			OCT. 29, 1990	90R7

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°	-		200'	

Purpose: To test for Free gold vein interpolation between Gay Gulch & 9066TR02.

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST							
5	10	" " " " " "							
10	15	" " " " " "							
15	20	" " " " " "							
20	25	" " " " " "							
25	30	" " " " " "							
30	35	PALE " " " " "							
35	40	" " " " " "							
40	45	" " " " " "							
45	50	" " " " " "							
50	55	" " " " " "							
55	60	" " " " " "							
60	65	" " " " " "							
65	70	" " " " " "							
70	75	" " " " " "							
75	80	" " " " " "							
80	85	PALE GREY/WHITE " " "							
85	90	" " " " " "							
90	95	PALE BROWN " " "							
95	100	" " " " " "							
100	105	PALE GREY/WHITE " " "							
105	110	" " " " " "							
110	115	" " " " " "							
115	120	" " " " " "							
120	125	" " " " " "							
125	130	" " " " " "							
		END OF HOLE							

PERCUSSION DRILL LOG

90R1
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
130	135	PALE GREY/WHITE QUARTZ MUSCOVITE SCHIST							
135	140	" " " " " "							
140	145	" " " " " "							
145	150	" " " " " "							
150	155	" " " " " "							
155	160	" " " " " "							
160	165	" " " " " "							
165	170	" " " " " "							
170	175	" " " " " "							
175	180	" " " " " "							
180	185	" " " " " "							
185	190	" " " " " "							
190	195	" " " " " "							
195	200	" " " " " "							
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD I.P.L. 2+755	0+00	+28 ft	OCT 29 1990	90 RS

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			150' ft	

Purpose: Pattern drilling for mineralized horizon.

Footage From	Footage To	Description	Sample Number	Assays oz/ton Au ~~ppb~~	Ag	As	Cu	Pb	Zn
0	5	MEDIUM GREEN QUARTZ MUSCOVITE SERICITE TRACE RUSTY PYRITE							
5	10	" " " " " " "							
10	15	PALE GREY/WHITE " " "	2% PYRITE						
15	20	PALE GREY/WHITE QUARTZ " "	" "						
20	25	PALE GREY/GREEN " " "	" "						
25	30	" " " " "	" "						
30	35	" " " " "	" "						
35	40	" " " " "	" "						
40	45	PALE GREY/WHITE " "	" "						
45	50	" " " " "	TRACE "						
50	55	PALE GREY/GREEN " "	1% "						
55	60	PALE GREY/WHITE " "	2% "						
60	65	" " " " "	" "						
65	70	" " " " "	" "		AVERAGE				
70	75	MEDIUM GREY " "	" "						
75	80	PALE GREY/WHITE " "	" "						
80	85	MEDIUM GREY (DARK) " "	" "						
85	90	PALE GREY/WHITE " "	" "						
90	95	" " " " "	" "						
95	100	PALE GREY/GREEN " "	" "						
100	105	" " " " "	" "						
105	110	" " " " "	" "		0.078				
110	115	" " " " "	TRACE MAGNET						
115	120	PALE GREY/GREEN " "	2% PYRITE						
120	125	PALE GREY/GREEN " "	" "						
125	130	" " " " "	" "						
130	135	" " " " "	" "						
135	140	PALE GREY/WHITE " "	" "						
140	145	" " " " "	" "						
145	150	" " " " "	" "	0.336					

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD IPL 2+75S	0+50W	+53 ft	Oct 29-30, 1990	90R9

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			150 ft	

Purpose: Pattern drilling for mineralized horizon.

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Assays Ag	Assays As	Assays Cu	Assays Pb	Assays Zn
0	5	RED BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST							
5	10	〃							
10	15	〃							
15	20	PALE GREY/WHITE							
20	25	〃							
25	30	〃							
30	35	〃							
35	40	〃							
40	45	〃							
45	50	〃							
50	55	〃							
55	60	〃	TRACE PYRITE						
60	65	〃	〃						
65	70	〃	〃						
70	75	〃	〃						
75	80	〃	〃						
80	85	〃	〃						
85	90	〃	〃						
90	95	〃	〃		AVERAGE				
95	100	〃	〃		0.424				
100	105	〃	〃						
105	110	〃	〃						
110	115	〃	〃		0.132				
115	120	〃	〃						
120	125	〃	〃						
125	130	〃	〃						
130	135	〃	〃						
135	140	〃	〃						
140	145	〃	〃						
145	150	〃	〃						

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD I.P.L.	2+755 1+00W	+71 ft.	OCT 30, 1990	90R10

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			150 ft	

Purpose: Pattern drilling for mineralized horizon.

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Assays ~~Ag~~	Assays As	Assays Cu	Assays Pb	Assays Zn
0	5	BROWN (OXIDIZED) QUARTZ, MUSCOVITE SCHIST							
5	10	PALE BROWN " " " " "							
10	15	" " " " " "							
15	20	" " " " " "	TRACE PYRITE						
20	25	" " " " " "	" "						
25	30	PALE GREY/WHITE " " " "	" "						
30	35	" " " " " "	" "						
35	40	" " " " " "	" "						
40	45	" " " " " "	" "		AVERAGE				
45	50	" " " " " "	" "		0.05				
50	55	" " " " " "	" "						
55	60	" " " " " "	" "						
60	65	" " " " " "	" "						
65	70	" " " " " "	" "						
70	75	" " " " " "	" "						
75	80	" " " " " "	" "						
80	85	" " " " " "	" "						
85	90	" " " " " "	" "						
90	95	" " " " " "	" "						
95	100	" " " " " "	" "						
100	105	" " " " " "	" "						
105	110	" " " " " "	" "						
110	115	" " " " " "	" "						
115	120	" " " " " "	" "						
120	125	" " " " " "	" "						
125	130	" " " " " "	" "						
130	135	" " " " " "	" "						
135	140	" " " " " "	" "						
140	145	" " " " " "	" "						
145	150	" " " " " "	" "						

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD IPL 2+255	0+00	+0 ft	OCT 30 1990	90 R 11

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			150 ft	

Purpose: Pattern drilling for mineralized horizon

Footage From	Footage To	Description	Sample Number	oz/Ton Au ~~ppb~~	Average Ag	Assays As	Assays Cu	Assays Pb	Assays Zn
0	5	CHLORITIC BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE PYRITE						
5	10	RED BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	" "						
10	15	" " " " " "	" "						
15	20	" " " " " "	TRACE "	0.290	0.69				
20	25	" " " " " "	" "						
25	30	SLIGHTLY " " " " "	" "						
30	35	" " " " " "	1% PYRITE						
35	40	PALE GREEN QUARTZ MUSCOVITE SCHIST	" "						
40	45	" " " " " "	" "						
45	50	" " " " " "	" "						
50	55	" " " " " "	" "						
55	60	" " " " " "	" "						
60	65	" " " " " "	" "						
~~65~~	70	" " " " " "	" "						
70	75	" " " " " "	" "						
75	80	" " " " " "	" "						
80	85	" " " " " "	" "						
85	90	" " " " " "	" "						
90	95	" " " " " "	" "						
95	100	" " " " " "	" "						
100	105	" " " " " "	" "						
105	110	" " " " " "	" (W2T)						
110	115	" " " " " "	" (W2T)						
115	120	" " " " " "	" (W=T)						
120	125	" " " " " "	" "						
125	130	" " " " " "	" "						
130	135	" " " " " "	" "						
135	140	" " " " " "	" "						
140	145	" " " " " "	" "						
145	150	" " " " " "	" "						

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD IPL	2+255 0+50W	+28 ft	OCT. 30 1990	90R12

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			150 ft	

Purpose: Pattern drilling for mineralized horizon

Footage From	Footage To	Description	Sample Number	Assays oz/ton Au ~~ppb~~	Ag	As	Cu	Pb	Zn
0	5	RUSTY BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE RUSTY PYRITE						
5	10	" " " " " "	" "						
10	15	" " " " " "	" "						
15	20	" " " " " "	1930 "						
20	25	SLIGHTLY RUSTY " " " "	1920 "						
25	30	PALE GREY/WHITE " " " "	" PYRITE						
30	35	" " " " " "	" "						
35	40	" " " " " "	" "						
40	45	" " " " " "	" "						
45	50	" " " " " "	" "						
50	55	" " " " " "	" "						
55	60	" " " " " "	" "						
60	65	" " " " " "	" "						
65	70	" " " " " "	" "						
70	75	" " " " " "	" "						
75	80	" " " " " "	" "						
80	85	" " " " " "	" "						
85	90	" " " " " "	" "						
90	95	" " " " " "	" "						
95	100	" " " " " "	" "						
100	105	" " " " " "	" "						
105	110	" " " " " "	" "						
110	115	" " " " " "	" "						
115	120	" " " " " "	" "						
120	125	" " " " " "	" "						
125	130	" " " " " "	" "						
130	135	" " " " " "	" "	0.062					
135	140	DARK BROWN (OXI) QUARTZ CHLORITE MUSCOVITE SCHIST	2320 "						
140	145	" " " " " "	" "						
145	150	" " " " " "	" "						

END OF HOLE

PERCUSSION DRILL LOG

90 R 12
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
135	150	NOTE - CUTTINGS ARE VERY FINE GRAINED - POSSIBLE FAULT GOUGE (?) ASSOCIATED WITH THE WATER INFLOW							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD IOL 2+25S	1+00W	+60 ft	OCT 30, 1990	90 R 15

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			150 ft	

Purpose: Pattern drilling for mineralized horizon

Footage From	Footage To	Description	Sample Number	Assays oz/ton Au	Assays ppb Au	Assays Ag	As	Cu	Pb	Zn
0	5	RUSTY BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE PYRITE							
5	10	" " " " " "	" "							
10	15	PALE BROWN (OXIDIZED) " " "	" "							
15	20	" " " " " "	" "							
20	25	" " " " " "								
25	30	" " " " " "								
30	35	" " " " " "	TRACE FRESH PYRITE							
35	40	" " " " " "	" "							
40	45	PALE GREY/GREEN QUARTZ SERICITE MUSCOVITE SCHIST	" "							
45	50	" " " " " "	230 "							
50	55	" " " " " "	190 "							
55	60	" " " " " "	190 "							
60	65	" " " " " "	190 "							
65	70	" " " " " "	190 "							
70	75	" " " " " "	190 "							
75	80	" " " " " "	190 "							
80	85	" " " " " "	190 "							
85	90	" " " " " "	190 "							
90	95	" " " " " "	190 "							
95	100	" " " " " "	190 "							
100	105	" " " " " "	190 "			AVERAGE				
105	110	" " " " " "	190 "	0.163		↑ 0.060 ↓				
110	115	" " " " " "	190 "							
115	120	" " " " " "	190 "							
120	125	" " " " " "	190 "							
125	130	" " " " " "	190 "							
130	135	" " " " " "	190 "							
135	140	" " " " " "	190 "							
140	145	" " " " " "	190 "							
145	150	" " " " " "	190 "							

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD IPL 2+25S	1+50W	+68 ft	OCT 31, 1990	90 R 14

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			150 ft	

Purpose: Pattern drilling for mineralized horizon

Footage From	Footage To	Description	Sample Number	Assays oz/ton Au ~~ppb~~	Ag	As	Cu	Pb	Zn
0	5	BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST							
5	10	" " " " "			AVERAGE				
10	15	SLIGHTLY BROWN " " " "	TRACE RUSTY PYRITE						
15	20	" " " SOFTER " " "	15						
20	25	REDDISH " " " " "	20						
25	30	SLIGHTLY BROWN SOFTER " "	25						
30	35	" " " " " "	30						
35	40	" " " " " "	35						
40	45	" " " " " "	40 PYRITE						
45	50	PALE GREY/WHITE " " "	" "						
50	55	SLIGHTLY RUSTY " " "	" "						
55	60	" " " " "	" "						
60	65	" " " " "	" "						
65	70	PALE GREY/WHITE " " "	" "						
70	75	" " " " "	" "						
75	80	" " " " "	" "						
80	85	" " " " "	" "						
85	90	SLIGHTLY RUSTY " " "	" "						
90	95	PALE GREY/WHITE " " "	" "						
95	100	PALE GREY/GREEN QUARTZ SERICITE MUSCOVITE SCHIST	" "						
100	105	" " " " "	" "						
105	110	" " " " "	" "						
110	115	" " " " "	" "						
115	120	" " " " "	" "						
120	125	" " " " "	" "						
125	130	" " " " "	" "						
130	135	" " " " "	" "						
135	140	" " " " "	TRACE "						
140	145	" " " " "	145 "						
145	150	" " " " "	" "						

AVERAGE 58.0 ft

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD IPL 2+25S	2+00W	+68 ft	OCT 31, 1990	90 K15

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			150 ft	

Purpose: Pattern drilling for mineralized horizon.

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	RUSTY BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	1% PYRITE						
5	10	" " " " "	TRACE "						
10	15	" " " " "	1% "						
15	20	" " " " "	" "						
20	25	SLIGHTLY " " " "	" "						
25	30	" " " " "	" "						
30	35	" " " " "	" "		AVERAGE				
35	40	PALE GREY/WHITE " " "	2% "						
40	45	" " " " "	" "						
45	50	" " " " "	" "						
50	55	" " " " "	" "						
55	60	" " " " "	TRACE MAGNET		0.096%				
60	65	" " " " "	2% PYRITE TRACE MAG.						
65	70	" " " " "	2% PYRITE						
70	75	" " " " "	" "						
75	80	PALE GREY/GREEN (WET) QUARTZ SERICITE	" "		0.365				
80	85	" " " " "	" "						
85	90	" " " " "	" "						
90	95	" " " " "	" "						
95	100	" " " " QUARTZ MUSCOVITE SCHIST	" "						
100	105	" " " " "	" "						
105	110	" " " " "	" "						
110	115	" " " " "	" "						
115	120	" " " " "	" "						
120	125	" " " " "	" "						
125	130	" " " " "	" "						
130	135	" " " " "	" "						
135	140	" " " " "	" "						
140	145	" " " " "	" "						
145	150	" " " " "	" "						

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	CRD IPL 2+255	2+50W	+68 ft	OCT. 31, 1990	90 R 16

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			150 ft	

Purpose: Pattern drilling for mineralized horizon

Footage From	Footage To	Description	Sample Number	Assays: Au ppb	Ag	As	Cu	Pb	Zn
0	5	RUSTY BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE RUSTY PYRITE						
5	10	" " " " " "	" "						
10	15	" " " " " "	" "						
15	20	" " " " " "	" "						
20	25	" " " " " "	" "		AVERAGE				
25	30	" " " " " "	" "		↑				
30	35	" " " " " "	" "		0.03				
35	40	" " " " " "	" "		↓				
40	45	" " " " " "							
45	50	" " " " " "							
50	55	PALE GREY/WHITE " " " "	1% PYRITE						
55	60	" " " " " "	" "						
60	65	" " " " " "	" "						
65	70	" " " " " "	" "						
70	75	" " " " " "	1% PYRITE 1% MAGNETITE						
75	80	" " " " " "	1% PYRITE						
80	85	" " " " " "	1% PYRITE TRACE MAGNET						
85	90	" " " " " "	2% PYRITE						
90	95	" " " " " "	" "						
95	100	" " " " " "	1% "						
100	105	" " " " " "	" "						
105	110	" " " " " "	" "						
110	115	" " " " " "	" "						
115	120	" " " " " "	1% PYRITE TRACE MAGNET						
120	125	" " " " " "	1% PYRITE						
125	130	" " " " " "	" "						
130	135	" " " " " "	" "						
135	140	" " " " " "	" "						
140	145	" " " " " "	" "						
145	150	" " " " " "	" "						

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD IPL 2+75S	2+50W	+97 ft	OCT 31, 1990	90R17

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			150 ft	

Purpose: Pattern drilling for mineralized horizon

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	RUSTY BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE RUSTY PYRITE						
5	10	" " " " " "	" "						
10	15	PALE GREY/GREEN QUARTZ MUSCOVITE SCHIST	" "						
15	20	" " " " " "	1% PYRITE						
20	25	" " " " " "	" "						
25	30	" " " " " "	" "						
30	35	" " " " " "	" "						
35	40	" " " " " "	" "						
40	45	" " " " " "	" "						
45	50	" " " " " "	" "						
50	55	" " " " " "	" "						
55	60	" " " " " "	" "						
60	65	" " " " " "	" "						
65	70	" " " " " "	" "						
70	75	" " " " " "	" "						
75	80	" " " " " "	" "						
80	85	" " " " " "	3% "						
85	90	RUSTY (OXIDIZED)	1% "						
90	95	SLIGHTLY RUSTY "	2% "						
95	100	" " " " " "	" "						
100	105	" " " " " "	" "		AVERAGE				
105	110	" " " " " "	" "		↑				
110	115	" " " " " "	" "		2000				
115	120	PALE GREY/WHITE " " " "	" "		↓				
120	125	" " " " " "	" "						
125	130	" " " " " "	" "						
130	135	" " " " " "	" "						
135	140	" " " " " "	" "						
140	145	" " " " " "	" "						
145	150	" " " " " "	" "						

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD IPL 2+65 S	1+93 W	+105 ft	OCT. 31 - NOV. 1, 1980	90 R 18

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			395 ft	

Purpose: Pattern drilling for mineralized horizon and to test deep I.P. anomaly

Footage From	Footage To	Description	Sample Number	Assays: Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK IRON(OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE PYRITE						
5	10	〃 〃 〃 〃 〃 〃	〃 〃						
10	15	RED BROWN 〃 〃 〃 〃	1% 〃						
15	20	〃 〃 〃 〃 〃 〃	〃 〃						
20	25	SLIGHTLY 〃 〃 〃 〃 〃	〃 〃						
25	30	〃 〃 〃 〃 〃 〃	〃 〃						
30	35	〃 〃 〃 〃 〃 〃	2% 〃						
35	40	PALE GREY/GREEN 〃 〃 〃	〃 〃						
40	45	〃 〃 〃 〃 〃 〃	〃 〃						
45	50	〃 〃 〃 〃 〃 〃	〃 〃						
50	55	LIGHT BROWN 〃 〃 〃	〃 〃		AVERAGE				
55	60	PALE GREY/GREEN 〃 〃	〃 〃						
60	65	〃 〃 〃 〃 〃 〃	〃 〃						
65	70	〃 〃 〃 〃 〃 〃	〃 〃						
70	75	〃 〃 〃 〃 〃 〃	〃 〃						
75	80	〃 〃 〃 〃 〃 〃	〃 〃						
80	85	〃 〃 〃 〃 〃 〃	〃 〃						
85	90	〃 〃 〃 〃 〃 〃	〃 〃						
90	95	〃 〃 〃 〃 〃 〃	〃 〃						
** 95	100	〃 〃 〃 〃 2 PIECES V.G.*	〃 〃	0.014					
** 100	105	〃 〃 〃 〃 6 PIECES V.G.*	〃 〃	0.019					
** 105	110	SLIGHTLY BROWN (OXIDIZED) 〃 〃 16 PIECES V.G.*	〃 〃	0.158	0.672				
110	115	〃 〃 〃 〃 〃 〃	〃 〃	0.139					
115	120	PALE GREY/GREEN 〃 〃 〃	〃 〃	0.019	0.359				
120	125	〃 〃 〃 〃 〃 〃	〃 〃	0.501					
125	130	〃 〃 〃 〃 〃 〃	〃 〃	0.217					
130	135	〃 〃 〃 〃 〃 〃	〃 〃						
135	140	SLIGHTLY BROWN (OXIDIZED) 〃 〃 〃	〃 〃						
140	145	〃 〃 〃 〃 〃 〃	〃 〃						
145	150	〃 〃 〃 〃 〃 〃	〃 〃 X						

** PANNED SPLIT FROM LARGE BAG

* POSSIBLE V.G. ON SOME PYRITE X'LS? OR GOLD COLORED IRON OXIDE?

PERCUSSION DRILL LOG

90 R 18
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	BROWN/ORANGE (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE PYRITE		↓				
155	160	" " " WET (FAULT GOUGE?) QUARTZ MUSCO SCHIST	" "						
160	165	" " " QUARTZ MUSCOVITE SCHIST	" "						
165	170	" " " " "	" "						
170	175	PALE GREY/GREEN " " "	2% "						
175	180	" " " " " "	" "						
180	185	" " " (WET) " " "	" "						
185	190	DARK GREY/GREEN (DAMP) " " "	" "						
190	195	SLIGHTLY BROWN (WET) " " "	" "						
195	200	" " " QUARTZ CHLORITE MUSCOVITE SCHIST	" "						
200	205	DARK GREY/GREEN (WET) QUARTZ CHLORITE MUSCO SCHIST TRACE MAGNET 2% PYRITE							
205	210	PALE GREY/GREEN (DAMP) " " " " "	" "						
210	215	" " " (WET) " " " " "	" "						
215	220	" " " (WET) " " " " "	" "						
220	225	" " " (WET) " " " "	2% PYRITE						
225	230	" " " (DAMP) " " " "	" "						
230	235	" " " (DAMP) " " " "	1% PYRITE						
235	240	" " " (DAMP) " " " "	" "						
240	245	" " " (VERY WET) (GOUGE) " " " "	" "						
245	250	" " " " " " " "	" "						
250	255	" " " " " " " "	" "						
255	260	" " " " " " " "	" "						
260	265	" " " " " " " "	1% "						
265	270	PALE BROWN VERY WET GOUGE " " "	2% "						
270	275	" " " " " QUARTZ MUSCOVITE SCHIST	2% "						
275	280	PALE GREY/GREEN " " " " "	5% TRACE MAGNET "						
280	285	" " " " " " "	" "						
285	290	" " " " " QUARTZ VEINLET QUARTZ MUSCO SCHIST TRACE GALENA/MAGNES 5% "							
290	295	" " " " " QUARTZ MUSCOVITE SCHIST	3% "						
295	300	" " " " " QUARTZ MUSCO SCHIST TRACE GALENA	3% "						
300	305	VERY PALE " " " " " " " TRACE MAGNETITE	3% "						
305	310	" " " " " " " " " TRACE GALENA	3% "						
* 310	315	" " " " " " " " " TRACE GALENA + GOLD	3% "						
315	320	" " " " " " " " " " GALENA	3% "						
* 320	325	" " " " " " " " " " GALENA + GOLD	5%						
325	330	" " " " " " " " " "	TRACE PYRITE						

PERCUSSION DRILL LOG

90 R 18
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
330	335	VERY PALE GREY/GREEN VERY HOST QUARTZ MUSCOVITE SCHIST	1% PYRITE						
335	340	" " " " QUARTZ MUSCO SCHIST TRACE GALENA	1% PYRITE						
340	345	" " " " QUARTZ MUSCOVITE SCHIST	" "						
345	350	" " " " " " "	TRACE PYRITE						
350	355	" " " " " " "	" "						
355	360	" " " " " " "	" "						
360	365	" " " " " QUARTZ MUSCO SCHIST TRACE GALENA	" "						
365	370	" " " " (DAMP) QUARTZ MUSCO SCHIST TRACE GALENA	" "						
370	375	" " " " QUARTZ MUSCOVITE SCHIST	" "						
375	380	" " " " QUARTZ MUSCO SCHIST TRACE GALENA	" "						
380	385	" " " " " " "	" "						
385	390	" " " " " " "	" "						
390	395	" " " " " " "	" "						
		HOLE LOST TO WATER							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD IPL 2+75S	1+50W	+94 ft	OCT 31/1990	90 R 19

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			150 ft	

Purpose: Pattern drilling for mineralized horizon

Footage From	Footage To	Description	Sample Number	Assays oz/ton Au ppb	Ag	As	Cu	Pb	Zn
0	5	RUSTY BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE PYRITE						
5	10	" " " " " "	" "						
10	15	" " " " " "	" "						
15	20	" " " " " "	" "						
20	25	SLIGHTLY " " " " "	2% PYRITE						
25	30	PALE GREY/GREEN " " " "	" "						
30	35	" " " " " "	" "						
35	40	PALE GREY/WHITE " " " "	" "						
40	45	" " " " " "	" "						
45	50	SLIGHTLY BROWN " " " "	" "						
50	55	" " " " " "	" "						
55	60	" " " " " "	" "						
60	65	" " " " " "	" "						
65	70	" " " " " "	" "						
70	75	PALE GREY/GREEN " " " "	" "						
75	80	" " " " " "	" "						
80	85	" " " " " "	" "						
85	90	PALE GREY/WHITE " " " "	" "						
90	95	" " " " " "	" "	0.044					
95	100	" " " " " "	" "						
100	105	" " " " " "	" "						
105	110	" " " " " "	" "						
110	115	MEDIUM GREY/GREEN " " " "	" "						
115	120	" " " " " "	" "						
120	125	" " " " " "	" "						
125	130	" " " " " "	1% "						
130	135	" " " " " "	2% "						
135	140	" " " " " "	" "						
140	145	PALE GREY/WHITE " " " "	1% "						
145	150	" " " " " "	<1% "						

END OF HOLE

PERCUSSION DRILL LOG

LONE STAR	OLD IPL 2355	0+00	0 ft	Nov 1-2 1990	90 R 20
Location	Northing	Easting	Elevation	Date Drilled	Hole Number
-65°	030°		200 ft		
Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth	

Purpose: Boulder Lode vein extension to depth.

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) QUARTZ MUSCO SCHIST TRACE GALENA	TRACE PYRITE						
5	10	RED BROWN " QUARTZ MUSCOVITE SCHIST	TRACE "						
10	15	" " " " " "	" "						
15	20	" " " " " "	" "						
20	25	" " " " " "	< " "						
25	30	" " " " " "	" "						
30	35	" " " " " "	" "						
35	40	PALE GREY/GREEN " " " "	2% PYRITE						
40	45	" " " " " "	2% "						
45	50	" " " " " "	" "						
50	55	" " " " " "	3% "						
55	60	" " " " " "	" "						
60	65	" " " " " "	" "						
65	70	" " " " " "	" "						
70	75	PALE GREY " " "	2% "						
75	80	" " " " " "	" "						
80	85	" " QUARTZ CHLORITE(?) MUSCOVITE SCHIST TRACE GALENA	" "						
85	90	" " " " " "	" "						
90	95	" " " " " "	" "						
95	100	" " " " " "	" "						
100	105	" " " " " "	" "						
105	110	" " " " " "	" "						
110	115	NO SAMPLE BIT ADIT @ 106'							
115	120	" " " " " "							
120	125	" " " " " "							
125	130	MEDIUM GREEN/BROWN (WET) QUARTZ CHLORITE MUSCO SCHIST	2% PYRITE						
130	135	" " " " " "	" "						
135	140	" " " " " " QUARTZ MUSCOVITE SCHIST SYCAMORE	TRACE ?? " "						
140	145	PALE GREY/WHITE " " "	" "						
145	150	" " " " " "	" "						

PERCUSSION DRILL LOG

90 R 20
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	PALE GREY/GREEN QUARTZ MUSCOVITE SCHIST	23 PYRITE						
155	160	MEDIUM GREEN (DAMP) " " "	" "						
160	165	PALE GREY/GREEN " " "	" "						
165	170	MEDIUM GREY " " "	" "						
170	175	" " " " "	" "						
175	180	PALE BROWN (WET) " " "	" "						
180	185	" " " " "	" "						
185	190	PALE GREY/BROWN " " "	" "						
190	195	" " " " "	" "						
195	200	PALE BROWN " " "	" "						
		END OF HOLE							

PERCUSSION DRILL LOG

90 R21

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD IPL 2+05S	0+25E	-30 ft	Nov. 2, 1990	

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-65°	210°		150 ft	

Purpose: Boulder Lode vein extension to depth.

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE PYRITE						
5	10	" " " "	" "						
10	15	PALE " " QUARTZ CHLORITE	" "						
15	20	" " " "	" "						
20	25	" " " "	" "						
25	30	PALE GREY/GREEN " "	" "						
30	35	" " " "	" "						
35	40	" " " "	190 "						
40	45	" " " "	" "						
45	50	" " " "	" "						
50	55	" " " "	" "						
55	60	" " " "	" "						
60	65	" " " "	" "						
65	70	BLUE " "	" "						
70	75	" " " "	" "						
75	80	PALE GREY/GREEN " "	" "						
80	85	PALE GREY/WHITE " "	" "						
85	90	" " " "	2% "						
90	95	" " " "	" "						
95	100	BROWN (VERY WET) " (w/ POSSIBLE VEIN QTZ)	" "						
* 100	105	" " " (" " " ")	" SCHIST VG						
105	110	PALE GREY/GREEN " "	" "						
110	115	" " " "	" "						
115	120	BROWN (VERY WET) " "	" "						
120	125	" " " "	" "						
** 125	130	" " " "	" VG						
130	135	" " " "	" CHLORITE " "						
135	140	" " " "	" "						
140	145	" " " "	" "						
145	150	" " " "	" "						

* NUGGET w/ 5% MILKY QUARTZ 25% BLACK FINE CUBIC GALENA 70% YELLOW GOLD

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD IPL 1+90S	0+05W	-15 ft	Nov. 2, 1990	90 R22

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-65°	210°		150 ft	

Purpose: Boulder Lode vein extension to depth

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	MEDIUM BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST							
5	10	" " " " " "							
10	15	PALE GREY/GREEN " " "							
15	20	" " " " " "							
20	25	" " " " " TRACE PYRITE							
25	30	" " " " " "							
30	35	" " " " " 1% "							
35	40	PALE GREY/WHITE " " 1% "							
40	45	PALE GREY/GREEN " " " "							
45	50	" " " " " "							
50	55	" " " " " "							
55	60	" " " " " "							
60	65	" " " " " "							
65	70	" " " " " "							
70	75	" " " " " "							
75	80	" " " " " "							
80	85	" " " " " "							
85	90	NO SAMPLE - HIT ADIT							
90	95	MEDIUM " " QUARTZ CHLORITE MUSCOVITE SCHIST							
95	100	" " " " " "							
100	105	" " " " " "							
105	110	PALE " " " " "							
110	115	" " " " " "							
115	120	DARK " " (WATER) " " "							
120	125	MEDIUM " " " " "							
125	130	PALE " " " " "							
130	135	" " " " " "							
135	140	DARK " " (WATER) " "							
140	145	" " " " " "							
145	150	" " " " " "							

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR	OLD IPL 2+355	0+30W	+22 ft	Nov. 1, 1990	90 R23

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-65°	030°		150 ft	

Purpose: Boulder Lode vein extension to depth.

ALL SAMPLES - PANNED FROM ½ SAMPLE SPLIT ± 5 lbs. / 5'

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST 2 PIECES V.G.	1% PYRITE						
5	10	" " " " " " 1 V.G.	1% PYRITE						
10	15	" " " " " " 2 V.G.	1% "						
15	20	" " " " " " 2 V.G	1% "						
20	25	" " " " " "	1% "						
25	30	LIGHT " " " " 2 3 V.G.	2% "						
30	35	" " " " " " 5 V.G	2% "						
35	40	" " " " " "	2% "						
40	45	" " " " " " 1 V.G	" "						
45	50	PALE GREY/GREEN QUARTZ CHLORITE MUSCOVITE SCHIST	3% "						
50	55	" " " " " "	5% "						
55	60	" " " " " "	3% "						
60	65	" " " " " "	5% "						
65	70	" " " " " " 2 V.G.	5% "						
70	75	" " " " " "	" "						
75	80	" " " " " "	" "						
80	85	" " " " " "	" "						
85	90	" " " " " "	" "						
90	95	" " " " " "	" "						
95	100	" " " " " "	" "						
100	105	" " " " MUSCOVITE SCHIST 2 V.G.	" "						
105	110	" " " " " " 1 V.G.	" "						
110	115	" " " " " "	" "						
115	120	" " " " " " 1 V.G.	" "						
120	125	" " " " " "	" "						
125	130	" " " " " "	" "						
130	135	" " " " " "	" "						
135	140	" " " " " "	" "						
140	145	" " " " " " 1 V.G.	" "						
145	150	" " " " " "	" "						

END OF HOLE

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
LONE STAR BOULDER LODE	OLD IPL 1+70E	2+80S	~ - 30 ft	Nov 2/90	90 R 24

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-45°	040°		200'	

Purpose: TO TEST JUNCTION OF S.E. EXTENSION OF BOULDER LODE AND LARGE DYKE.

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	19 PYR%						
5	10	" " " " " "	" "						
10	15	" " " " " "	TRACE "						
15	20	" " " " " "	" "						
20	25	" " " " " "	" "						
25	30	" " " " " "	" "						
30	35	ORANGE-BROWN " " "	" "						
35	40	PALE ORANGE BROWN " " NGR	" "						
40	45	" " " " " "	" "						
45	50	PALE GREY/WHITE " " "	" "						
50	55	" " " " " "	1% "						
55	60	PALE GREY/GREEN " " "	" "						
60	65	" " " " " "	2% "						
65	70	" " " " " "	" "						
70	75	" " " " " "	" "						
75	80	" " " " " "	1% "						
80	85	WHITE " " "	TRACE PYRITE						
85	90	" " " " "	" "						
90	95	PALE GREY/GREEN " " "	" "						
95	100	WHITE " " "	1% "						
100	105	" " " " "	<1% "						
105	110	" " " " "	1% "						
110	115	" " " " "	1% "						
115	120	SLIGHTLY RUSTY TRACE (OX. ED) " "	<1% "						
120	125	WHITE " " "	TRACE "						
125	130	SLIGHTLY RUSTY BROWN (OXIDIZED) " "	" "						
130	135	WHITE " " "	" "						
135	140	" " " " "	" "						
140	145	" " " " "	" "						
145	150	" " " " "	" "						

PERCUSSION DRILL LOG

90 R 24
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	WHITE QUARTZ MUSCOVITE SCHIST	TRACE PYRITE						
155	160	〃 〃 〃	〃 〃						
160	165	BUFF 〃 〃	〃 〃						
165	170	〃 〃 〃	〃 〃						
170	175	PALE GREY/GREEN 〃 〃	〃 〃						
175	180	〃 〃 〃 〃 〃	〃 〃						
180	185	〃 〃 〃 〃 〃	〃 〃						
185	190	〃 〃 〃 〃 〃	〃 〃						
190	195	〃 〃 〃 〃 〃	190 〃						
195	200	〃 〃 〃 〃 〃	〃 〃						
		END OF HOLE							

PERCUSSION DRILL LOG

7 PUP	NEAR HILCHEY'S OLD HOLE ON 90 SUN 7 PUP TROI			NOV. 2, 1990	90 R 25
Location	Northing	Easting	Elevation	Date Drilled	Hole Number
90			157 ft		
Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth	

To replicate Hilchey's drill results
Purpose

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OX 10YR3/2) QUARTZ CHLORITE MUSCOVITE SCHIST	Ø						
5	10	〃 〃 〃 〃 〃 〃 〃	Ø						
10	15	〃 〃 〃 〃 〃 〃 〃	Ø						
15	20	〃 〃 〃 (CLAY ALTERED?) 〃 〃 〃 〃	TRACE PYRITE						
20	25	〃 〃 〃 〃 〃 〃 〃	Ø						
25	30	〃 〃 〃 〃 〃 〃 〃	TRACE PYRITE						
30	35	LIGHT 〃 〃 〃 〃 〃 〃	〃 〃						
35	40	〃 〃 〃 〃 〃 〃 〃	〃 〃						
40	45	〃 〃 〃 〃 〃 〃 〃	〃 〃						
45	50	〃 〃 〃 〃 〃 〃 〃	Ø						
50	55	〃 〃 〃 〃 〃 〃 〃	TRACE PYRITE						
55	60	〃 〃 〃 〃 〃 〃 〃	〃 〃						
60	65	〃 〃 〃 〃 〃 〃 〃	〃 〃						
65	70	〃 〃 〃 〃 〃 〃 〃	〃 〃						
70	75	〃 〃 〃 〃 〃 〃 〃	〃 〃						
75	80	〃 〃 〃 〃 〃 〃 〃	〃 〃						
80	85	〃 〃 〃 〃 〃 〃 〃	〃 〃						
85	90	〃 〃 〃 〃 〃 〃 〃	〃 〃						
90	95	〃 〃 〃 〃 〃 〃 〃	〃 〃						
95	100	VERY MINOR 〃 (MINOR) 〃 〃 〃	〃 〃						
100	105	〃 〃 〃 〃 〃 〃 〃	〃 〃						
105	110	〃 〃 〃 〃 〃 〃 〃	〃 〃						
110	115	〃 〃 〃 〃 〃 〃 〃	〃 〃						
115	120	〃 〃 〃 〃 〃 〃 〃	〃 〃						
120	125	〃 〃 〃 〃 〃 〃 〃	〃 〃						
125	130	〃 〃 〃 〃 〃 〃 〃	〃 〃						
130	135	〃 〃 〃 〃 〃 〃 〃	〃 〃						
135	140	〃 〃 〃 〃 〃 〃 〃	〃 〃						
140	145	〃 〃 〃 〃 〃 〃 〃	〃 〃						
145	150	〃 〃 〃 〃 〃 〃 〃	〃 〃						

PERCUSSION DRILL LOG

90 R 25
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	VERY PALE BROWN (OX, 2.5Y 7/3) QUARTZ MINOR CHLORITE MUSCOVITE SCHIST	TRACE PYRITE						
155	157	〃 〃 〃 〃 〃 〃 〃 〃	〃 〃						
		END OF HOLE							

PERCUSSION DRILL LOG

7PUP	7PUP IPL	3+80E 1+10N		Nov. 2-3 1990	90 R 26
Location	Northing	Easting	Elevation	Date Drilled	Hole Number
-90°			300'		
Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth	

Purpose: To test IP anomaly

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	RUSTY BROWN (OXIDIZED) QUARTZ CHLORITE MUSCOVITE SCHIST	TRACE PYRITE						
5	10	" " " " " " "	" "						
10	15	" " " " " " "	ϕ						
15	20	PALE " " " " "	TRACE MAGNET						
20	25	PALE GREY/GREEN " " " " "	TRACE PYRITE TRACE MAGNET						
25	30	" " " " " " "	" "						
30	35	" " " " " " "	TRACE MAGNET						
35	40	" " " " " " "	" "						
40	45	" " " " " " "	TRACE PYRITE 1% MAGNET						
45	50	" " " " " " "	1% MAGNET						
50	55	" " " " " " "	TRACE PYRITE 1% MAGNET						
55	60	" " " " " " "	TRACE PYRITE 2% MAGNET						
60	65	" " " " " " "	TRACE PYRITE 3% MAGNET						
65	70	PALE RUSTY BROWN (OXIDIZED) " " " " "	2% MAGNET						
70	75	PALE GREY/GREEN " " " " "	" "						
75	80	" " " " " " "	" "						
80	85	" " " " " " "	" "						
85	90	" " " " " " "	TRACE " TRACE PYRITE						
90	95	" " " " " " "	1% MAGNET						
95	100	" " " " " " "	2% MAGNET						
100	105	" " " " " " "	" "						
105	110	" " " " " " "	" "						
110	115	" " " " " " "	" "						
115	120	" " " " " " "	" "						
120	125	" " " " " " "	" "						
125	130	" " " " " " "	" "						
130	135	" " " " " " "	" "						
135	140	MEDIUM GREY " " " " "	" "						
140	145	" " " " " " "	" "						
145	150	" " " " " " "	" "						

PERCUSSION DRILL LOG

90 R 26
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	MEDIUM GREY QUARTZ CHLORITE MUSCOVITE SCHIST	TR PYRITE 2% MAGNET						
155	160	PALE GREY/GREEN " " " "	" "						
160	165	" " " " " " "	" "						
165	170	" " " " " " "	TRACE PYRITE TRACE MAGNET						
170	175	" " " " " " "	" "						
175	180	" " " " " " "	" "						
180	185	DARK GREEN (VERY DAMP-WET) QUARTZ " " "	" "						
185	190	" " " " " " "	" "						
190	195	" " " " " " "	<1% PYRITE TRACE MAGNET						
195	200	" " " " " " "	<1% PYRITE						
200	205	" " " " " " "	" "						
205	210	" " " " " " "	" "						
210	215	MEDIUM GREEN " " " " " "	1% "						
215	220	" " " " " " "	" "						
220	225	" " " " " " "	" "						
225	230	DARK GREEN " " " " " "	" "						
230	235	" " " " " " "	" "						
235	240	" " " " " " "	" "						
240	245	" " " " " " "	" "						
245	250	" " " " " " "	" "						
250	255	" " " " " " "	2% "						
255	260	" " " " " " "	TRACE "						
260	265	" " " " " " "	" "						
265	270	" " " " " " "	" "						
270	275	" " " " " " "	" "						
275	280	" " " " " " "	" "						
280	285	" " " " " " "	" "						
285	290	" " " " " " "	" "						
290	295	" " " " " " "	" "						
295	300	" " " " " " "	" "						
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
7 PUP	7 PUP IPL	3+80E 14605		NOV. 4 1990	90 R 27

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			200'	

Purpose: To test IP anomaly

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	VERY DARK BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE PYRITE TRACE MAGNET						
5	10	" " " " " " "	TRACE PYRITE						
10	15	" " " " " " "	" "						
15	20	" " " " " " "	" "						
20	25	" " " " " " "	" "						
25	30	" " " " " " "	" "						
30	35	" " " " " " "	" "						
35	40	" " " " " " "	" "						
40	45	BROWN (OXIDIZED)	" "						
45	50	LIGHT BROWN (OXIDIZED)	" "						
50	55	" " "	" "						
55	60	" " "	" "						
60	65	" " "	" "						
65	70	" " "	" "						
70	75	" " "	" "						
75	80	PALE GREY (WEATHERED)	" "						
80	85	" " "	" "						
85	90	" " "	" "						
90	95	" " "	" "						
95	100	" " " QUARTZ MUSCOVITE CHLORITE MUSCOVITE SCHIST	1% PYRITE						
100	105	GREY " " " " "	2% "						
105	110	" " " " " "	3% PYRITE						
110	115	" " " " " "	TRACE MAGNET						
115	120	" " " " " "	" "						
120	125	" " " " " "	1% MAGNET						
125	130	" " " " " "	" "						
130	135	" " " " " "	1% PYRITE 1% MAGNET						
135	140	" " " " " "	1% PYRITE						
140	145	" " " " " "	" "						
145	150	" " " " " "	" "						

PERCUSSION DRILL LOG

90R27
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	GREY QUARTZ MINOR CHLORITE MUSCOVITE SCHIST	1 % PYRITE						
155	160	" " " " " "	" "						
160	165	" " " " " "	" "						
165	170	" " " " " "	" "						
170	175	" " " " " "	" "						
175	180	" " " " " "	" "						
180	185	" " " " " "	" "						
185	190	" " " " " "	" "						
190	195	" " " " " "	" "						
195	200	" " " " " "	" "						
		END OF HOLE							

PERCUSSION DRILL LOG

7 PUP	7 PUP IPL	0+60N 4+80E		NOV 3-4, 1990	90 R 28
Location	Northing	Easting	Elevation	Date Drilled	Hole Number
-60°	000°		200'		
Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth	

To test IP anomally
Purpose

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXID-ZED) QUARTZ MUSCOVITE SCHIST	TRACE PYRITE						
5	10	" " " " " "	" "						
10	15	" " " QUARTZ CHLORITE MUSCOVITE SCHIST	TRACE PYRITE						
15	20	MEDIUM " " " " " "	" "						
20	25	" " " " " " "	" "						
25	30	" " " " " " "	" "						
30	35	" " " " " " "	" "						
35	40	" " " " " " "	TRACE PYRITE 1% MAGNET						
40	45	PALE GREY / GREEN " " " "	" "						
45	50	" " " " " " "	" "						
50	55	MEDIUM " " " " " "	1% PYRITE MAGNET						
55	60	PALE GREY " " " " "	" "						
60	65	" " " " " " "	" "						
65	70	" " " " " " "	TRACE PYRITE						
70	75	" " " " " " "	1% PYRITE MAGNET						
75	80	MEDIUM GREY (DAMP) " " " "	" "						
80	85	MEDIUM GREY " " " "	" "						
85	90	DARK GREEN (WET) " " " "	" "						
90	95	" " " " " " "	1% PYRITE MAGNET						
95	100	MEDIUM GREY " " " "	" "						
100	105	" " " " " " "	" "						
105	110	" " " " " " "	" "						
110	115	" " " " " " "	" "						
115	120	DARK GREEN (WET) " " " "	" "						
120	125	" " " " " " "	" "						
125	130	" " " " " " "	" "						
130	135	" " " " " " "	" "						
135	140	" " " " " " "	" "						
140	145	" " " " " " "	" "						
145	150	" " " " " " "	" "						

PERCUSSION DRILL LOG

90 R 28
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	DARK GREEN (WET) QUARTZ CHLORITE MUSCOVITE SCHIST	1% PYRITE TRACE MAGNET						
155	160	" " " " " " "	" "						
160	165	WHITISH " " QUARTZ WITH MINOR CHLORITE = VEIN?	TRACE PYRITE						
165	170	DARK " " QUARTZ CHLORITE MUSCOVITE SCHIST	" "						
170	175	" " " " " " "	" "						
175	180	" " " " " " "	1% PYRITE						
180	185	" " " " " " "	" "						
185	190	" " " " " " "	" "						
190	195	" " " " " " "	" "						
195	200	" " " " " " "	" "						
		END OF HOLE							

PERCUSSION DRILL LOG

ELDORADO Ck	GRAY Ck IPL	3000E		Nov 4-5, 1990	90 R 29
Location	Northing	Easting	Elevation	Date Drilled	Hole Number
-45°	260°		500 ft		
Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth	

To test I.P anomally & Eldorado Ck Step fault.
Purpose

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE PYRITE						
5	10	LIGHT " " " " "	" "						
10	15	" " " " " "	TRACE MAGNET						
15	20	" " " " " "	" "						
20	25	DARK " " " "	" "						
25	30	LIGHT GREY/WHITE " "	" "						
30	35	" " " " "	" "						
35	40	" " " " "	" "						
40	45	" " " " "	" "						
45	50	" " " " "	" "						
50	55	RED/BROWN (OXIDIZED) " "	" "						
55	60	LIGHT GREY/WHITE " "	" "						
60	65	" " " " "	" "						
65	70	" " " " "	" "						
70	75	BROWN (WET) " "	" "						
75	80	BROWN " "	" "						
80	85	" (WET) " "	" "						
85	90	" " " " "	" "						
90	95	" " " " "	" "						
95	100	" " " " "	TRACE GALENA 1% PYRITE						
100	105	PALE GREY/GREEN (OXIDIZED) QUARTZ CHLORITE	1% PYRITE						
105	110	" " " " " "	" "						
110	115	" " " " " "	" "						
115	120	" " " " " "	" "						
120	125	" " " " " "	" "						
125	130	" " " " " "	" "						
130	135	" " " " " "	" "						
135	140	" " " " " "	" "						
140	145	" " " " " "	" "						
145	150	LIGHT BROWN (WET) " "	" "						

PERCUSSION DRILL LOG

90 R 29
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	LIGHT BROWN (WET) QUARTZ CHLORITE MUSCOVITE SCHIST	1% PYRITE						
155	160	" " " " " "	" "						
160	165	" " " (PALE QUARTZ VEIN) " " "	" "						
165	170	PALE GREY/GREEN (WET) " " " "	" "						
170	175	" " " " " "	" "						
175	180	" " " " " "	" "						
180	185	" " " " " "	" "						
185	190	GREEN (DAMP) " " " " "	TRACE GALENA 1% PYRITE						
190	195	" " " " " "	1% PYRITE						
195	200	" " " " " "	" "						
200	205	PALE GREEN (WET) " " " "	TRACE GALENA 1% PYRITE						
205	210	" " (DAMP) " " "	1% PYRITE						
210	215	" " " (PALE QUARTZ VEIN) " "	" "						
215	220	" " (WET) " " "	" "						
220	225	BRICK RED/BROWN (DAMP) & MINOR LIGHT QCMS W/ RUSTY FRACTURES	" "						
225	230	DARK GREEN QUARTZ CHLORITE MUSCOVITE SCHIST	TRACE PYRITE						
230	255	LIGHT GREEN (WET) " " " "	" "						
255	240	" " " " " "	" "						
240	245	" " " " " "	" "						
245	250	" " " " " "	" "						
250	255	" " " " " "	" "						
255	260	" " " " " "	" "						
260	265	" " " " " "	" "						
265	270	" " " " " "	" "						
270	275	" " " " " "	" "						
275	280	" " " " " "	" "						
280	285	" " (DAMP) " " "	TRACE GALENA PYRITE						
285	290	" " " " " "	TRACE GALENA "						
290	295	" " " " " "	" "						
295	300	" " " " " "	1% PYRITE						
300	305	" " (WET) " " "	GALENA						
305	310	" " (DAMP) " " "	" PYRITE						
310	315	" " (WET) " " "	" PYRITE						
315	320	" " " " " "	1% PYRITE						
320	325	" " " " " "	" "						
325	330	PALE GREEN (DAMP) " " " "	" "						

PERCUSSION DRILL LOG

90 R 29
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
330	335	PALE GREEN (DAMP) QUARTZ CHLORITE MUSCOVITE SCHIST	1% PYRITE						
335	340	GREENISH/BROWN " " " "	" "						
340	345	" " " "	TRACE "						
345	350	" " (DAMP) " " " "	" "						
* 350	355	PALE GREEN (DAMP) " " " "	TRACE PYRITE						
355	360	" " " " " SCHIST	" "						
360	365	" " (WET) " " " "	" "						
365	370	" " (DAMP) " " " "	TRACE PYRITE						
370	375	" " (WET) " " " "	" "						
375	380	" " (DAMP) " " " "	" "						
380	385	" " " " " "	" "						
385	390	" " " " " "	" "						
390	395	" " " " " "	" "						
395	400	" " " " " "	" "						
400	405	" " " " " "	" "						
405	410	" " " " " "	" "						
410	415	" " " " " "	" "						
415	420	" " " " " "	" "						
420	425	" " " " " "	" "						
425	430	" " (WET) " " " "	" "						
430	435	" " " " " "	" "						
435	440	" " (DAMP) " " " "	" "						
440	445	" " " " " "	" "						
445	450	" " (WET) " " " "	" "						
		END OF HOLE							
* POSSIBLE	V-6. 1st	HIGHLY OXIDIZED MAGNETITE (?) OR MnO_2 (?) OR GALENA (?)							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
ELDORADO CREEK	GRAY GULCH I.P. LINE 220N	200 E		NOV. 6 1990	90 R 30

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-45°	260°		490'	

Purpose: TO TEST I.P. GEOPHYSICAL TARGET & ELDORADO CU STEEP FAULT

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE PYRITE MINERALIZ.						
5	10	" " " " " "	" "						
10	15	" " " " " "	" "						
15	20	" " " " " "	" "						
20	25	" " " " " "	" "						
25	30	" " " " " "	" "						
30	35	" " " " " "	" "						
35	40	" " " " " "	" "						
40	45	" " " QUARTZ CHLORITE " "	" "						
45	50	" " " " " "	" "						
50	55	" " " " " "	" "						
55	60	" " " " " "	" "						
60	65	" " " " " "	" "						
65	70	PALE GREY/WHITE " " " "	" "						
70	75	" " " " " "	" "						
75	80	" " " QUARTZ MUSCOVITE SCHIST	" "						
80	85	" " " " "	" "						
85	90	" " " QUARTZ CHLORITE MUSCOVITE SCHIST	" "						
90	95	DARK BROWN (OXIDIZED) " " "	" "						
95	100	" " " " " "	" "						
100	105	PALE GREY/GREEN " " "	" "						
105	110	MEDIUM GREEN (WET) " " "	" "						
110	115	" " " " " "	" "						
115	120	PALE GREY/WHITE " " "	" "						
120	125	BROWN (WET) " " "	" "						
125	130	" " " " "	" "						
130	135	" " " " "	" "						
135	140	" " " " "	" "						
140	145	" " " " "	" "						
145	150	" " " " "	" "						

PERCUSSION DRILL LOG

90 R 80
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
155	160	BROWN (DAMP) QUARTZ CHLORITE MUSCOVITE SCHIST	1% PYRITE						
160	165	" (WET) " " " "	" "						
165	170	LIGHT BROWN (WET) " " " "	" "						
170	175	BROWN (WET) " " " "	" "						
175	180	" " " " " "	" "						
180	185	" (DAMP) " " " "	" "						
185	190	" (WET) " " " "	" "						
190	195	" " " " " "	TRACE PYRITE						
195	200	" " " " " "	" "						
200	205	PALE GREY/WHITE (WET) " " " "	" "						
205	210	" " " (DAMP) " " " "	" "						
210	215	PALE BROWN (WET) " " " "	" "						
215	220	" " " " " "	" "						
220	225	GREENISH/BROWN (DAMP) " " " "	" "						
225	230	" " " " " "	" "						
230	235	" " " " " "	" "						
235	240	" " (WET) " " " "	" "						
240	245	" " (DAMP) " " " "	" "						
245	250	" " " " " "	" "						
250	255	" " " " " "	" "						
255	260	" " " " " "	" "						
260	265	" " " " " "	" "						
265	270	PALE GREY/WHITE (DAMP) " " " "	" "						
270	275	" " " " QUARTZ RICH " "	1% PYRITE						
275	280	" " " " QUARTZ CHLORITE " "	" "						
280	285	" " " " " " "	" "						
285	290	" " " " " " "	" "						
290	295	BROWNISH (DAMP) " " " "	" "						
295	300	PALE GREY/WHITE (DAMP) " " " "	" "						
300	305	LIGHT BROWN (WET) " " " "	" "						
305	310	PALE GREY/GREEN (WET) " " " "	" "						
310	315	DARK GREEN (DAMP) " " " "	" "						
315	320	" " " " " "	" "						
320	325	" " " " " "	2% PYRITE						
325	330	" " " " " "	" "						
330	335	" " " " " "	" "						

PERCUSSION DRILL LOG

90 R 30
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
335	340	DARK GREEN (DAMP) QUARTZ CHLORITE MUSCOVITE SCHIST	23 PYRITE						
340	345	" " " " " " "	1% "						
345	350	" " " " " " "	TRACE "						
350	355	" " " " " " "	" "						
355	360	" " " " " " "	1% "						
360	365	" " " " " " "	" "						
365	370	" " " " " " "	" "						
370	375	" " " " " " "	TRACE "						
375	380	" " " " " " "	1% "						
380	385	" " " " " " "	2% "						
385	390	" " " " " " "	TRACE "						
390	395	" " " " " " "	1% "						
395	400	" " " " " " "	TRACE "						
400	405	" " " " " " "	" "						
405	410	" " " " " " "	1% "						
410	415	LIGHT GREEN DAMP " " " " "	" "						
415	420	" " " " " " "	" "						
420	425	PALE GREEN/WHITE (DAMP) " " " "	TRACE "						
425	430	" " " " " " "	" "						
430	435	" " " " " " "	" "						
435	440	" " " " QUARTZ RICH " " "	" "						
440	445	" " " " " " "	" "						
445	450	" " " " " " "	1% "						
450	455	" " " " " " "	2% "						
455	460	" " " " " " "	" "						
460	465	" " " " " " "	" "						
465	470	" " " " " " "	1% "						
470	475	" " " " " " "	TRACE "						
475	480	" " " " " " "	" "						
480	485	" " " " " " "	" "						
485	490	" " " " " " "	" "						
490		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
ELDORADO CK	EL IPL 45+00S			NOV. 7 1990	90R31

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-45°	200°		300 ft	

Purpose: To test I.P. anomaly + Eldorado Ck step fault

Footage From	Footage To	Description	Sample Number	Assays: Au ppb	Ag	As	Cu	Pb	Zn
0	5'	RED/BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE PYR.						
5	10	" " " QUARTZ CHLORITE MUSCOVITE SCHIST	" "						
10	15	" " " " " " "	VERY " "						
15	20	" " " " " " "	TRACE "						
20	25	" " " " " " "	- "						
25	30	PALE BROWN " " " " "	" "						
30	35	GREY/WHITE " " " " "	" "						
35	40	" " " " " " "	" "						
40	45	" " " " " " "	" "						
45	50	" " " " " " "	" "						
50	55	" " " " " " "	1% PYR.						
55	60	" " " " " " "	" "						
60	65	" " " " " " "	2% "						
65	70	" " " " " " "	2% "						
70	75	" " " " " " "	" "						
75	80	" " " " " " "	" "						
80	85	" " " " " " "	" "						
85	90	" " " " " " "	1% "						
90	95	" " " " " " "	" "						
95	100	" " " " " " "	" "						
100	105	" " " " " " "	" "						
105	110	" " " " " " "	>1% "						
110	115	" " " " " " "	TRACE "						
115	120	BUFF " " " " "	VERY TRACE "						
120	125	BROWN (WET) " " " "	" " "						
125	130	BUFF " " " " "	" " "						
130	135	GREY/WHITE " " " "	1% PYR.						
135	140	" " " " " " "	" "						
140	145	BROWN (WET) " " " "	TRACE PYR.						
145	150	BUFF " " " " "	" " "						

← 12 MAGNETITE

PERCUSSION DRILL LOG

90 RJ1
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	BLUE QUARTZ CHLORITE MUSCOVITE SCHIST	19 PYR+LIM						
155	160	REDDISH/BLUE	29 PYR+LIM						
160	165	GREEN	〃						
165	170	RED/BROWN	〃						
170	175	GREENISH/GREY	〃						
175	180	〃 〃	19 PYR+LIM						
180	185	〃 〃	〃						
185	190	〃 〃	TRACE 〃						
190	195	〃 〃	TRACE 〃						
195	200	〃 〃	〃						
200	205	〃 〃	〃						
205	210	GREY/WHITE	〃						
210	215	〃 〃 (WET)	〃						
215	220	〃 〃 (WET)	〃						
220	225	〃 〃	〃						
225	230	〃 〃	〃						
230	235	〃 〃	〃						
235	240	〃 〃 (WET)	〃						
240	245	GREY/GREEN (WET)	〃						
245	250	〃 〃 (WET)	〃						
250	255	〃 〃 (WET)	〃						
255	260	〃 〃 (WET)	〃						
260	265	〃 〃 (WET)	〃						
265	270	〃 〃 (WET)	〃						
270	275	REDDISH BLUE (WET)	〃						
275	280	GREY/GREEN (WET)	〃						
280	285	〃 〃 (WET)	〃						
285	290	〃 〃 (WET)	〃						
290	295	〃 〃 (WET)	〃						
295	300	〃 〃 (WET)	〃						
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
27 Pup				Nov. 8, 1990	90 R32

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			102 Ft	

Purpose: High-grade pyritic veins extension to depth.

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) Quartz Muscovite Schist	TAKE PYRITE TRACE MINERAL						
5	10	" " " " " "	" "						
10	15	" " " " " "	" "						
15	20	" " " " " "	" "						
20	25	" " " " " "	" "						
25	30	" " " " " "	" "						
30	35	ORANGE BROWN (OXIDIZED) " " "	" "						
35	40	" " " " " "	" "						
40	45	" " " " " "	19. MINERALIZE						
45	50	" " " " " "	" "						
50	55	DARK BROWN " " " "	19. MINERALIZE TRACE PYRITE						
55	60	PALE BROWN " " " "	" "						
60	65	" " " " " "	" "						
65	70	" " " " " "	" "						
70	75	" " " " " "	" "						
75	80	" " " " " "	" "						
80	85	" " " " " "	" "						
85	90	" " " " " "	" "						
90	95	" " " " " "	" "						
95	100	" " " " " "	" "						
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
27 PUP				Nov. 8, 1990	90 R 33

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			100 ft	

Purpose: High-grade pyritic veins Extension To depth.

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (EXPOSED) QUARTZ MUSCOVITE SCHIST	TRACE PYRITE TRACE MAGNET						
5	10	PALE BROWN " " " "	" "						
10	15	" " " " " "	" "						
15	20	" " " " " "	TRACE PYRITE						
20	25	" " " " " "	" "						
25	30	" " " " " "	" "						
30	35	" " " " " "	" "						
35	40	" " " " " "	" "						
40	45	DARK BROWN " " "	" "						
45	50	PALE BROWN " " "	" "						
50	55	" " " " "	" "						
55	60	" " " " "	" "						
60	65	DARK BROWN " " "	" "						
65	70	MEDIUM " " "	" "						
70	75	PALE GREY/WHITE " "	" "						
75	80	" " " " "	" "						
80	85	ORANGE BROWN " (WET) "	" "						
85	90	DARK BROWN " (WET) QUARTZ CHLORITE MUSCOVITE SCHIST	" "						
90	95	" " " " " "	" "						
95	100	BRICK RED/DARK BROWN " " " "	" "						
		(RED COLORING DUE TO OXIDATION OF CHLORITE TO BRIGHT RED MINERAL)							
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
27 PUP				Nov. 8, 1990	90 R 54

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			100 ft	

Purpose: High grade pyritic veins extension to depth

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	MEDIUM BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE MOLY						
5	10	" " "	" "						
10	15	" " "	" "						
15	20	" " "	" "						
20	25	" " "	" "						
25	30	" " "	" "						
30	35	" " "	" "						
35	40	" " "	" "						
40	45	" " "	" "						
45	50	" " "	" "						
50	55	PALE BROWN (OXIDIZED)	Ø Ø						
55	60	" " "	TRACE MOLY						
60	65	" " "	" "						
65	70	" " "	" "						
70	75	" " "	TRACE MOLY TRACE PYRITE						
75	80	" " "							
80	85	" " "	" "						
85	90	" " "	" "						
90	95	" " "	" "						
95	100	PALE GREY SILICIFIED							
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
27 RVP				Nov. 7 1986	90R35

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			100 ft	

Purpose: High-grade pyritic vein extension to depth

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	PALE BROWN Quartz Muscovite Schist	NIL						
5	10	" " Quartz Chlorite Muscovite Schist	TRACE PYRITE						
10	15	" " " " " "	" "						
15	20	PALE GREY/GREEN " " " "	" "						
20	25	" " " " " "	" "						
25	30	" " " " " "	1% PYRITE 1% MAGNET						
30	35	" " " " " "	" "						
35	40	" " " " " "	" "						
40	45	" " " " " "	" "						
45	50	" " " " " "	" "						
50	55	" " " " " "	TRACE						
55	60	" " " " " "	" "						
60	65	" " " " " "	" "						
65	70	" " " " " "	" "						
70	75	" " " " " "	" "						
75	80	" " " " " "	" "						
80	85	" " " " " "	1% PYRITE						
85	90	MEDIUM GREY " " " "	2% PYRITE						
90	95	" " " " " "	" "						
95	100	" " " " " "	" "						
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
FRENCH GULCH	FG IPL 6+60S	8+60E		Nov. 8-9 1990	90R36

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-50°	180°		400	

Purpose: I.P. anomally

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) (WET) QUARTZ CHLORITE MUSCOVE SCHIST	TRACE PYRITE TRACE MALACHITE						
5	10	" " " " " " "	" "						
10	15	" " " " " " "	" "						
15	20	" " " " " " "	" "						
20	25	" " " (WET) " " "	" "						
25	30	MEDIUM " " " " " "	" "						
30	35	PALE GREY/WHITE " " " "	" "						
35	40	" " " " " " "	" "						
40	45	PALE GREY/GREEN " " " "	" "						
45	50	MEDIUM BROWN (WET) " " "	" "						
50	55	" " " " " "	" "						
55	60	LIGHT BROWN " " " "	" "						
60	65	DARK BROWN (WET) " " "	190 "						
65	70	" " " " " "	" "						
70	75	GREY/GREEN (WET) " " "	TRACE "						
75	80	" " " " " "	" "						
80	85	" " " " " "	" "						
85	90	" " " " " "	" "						
90	95	" " " " " "	" "						
95	100	" " " " " "	120 PYRITE MALACHITE						
100	105	DARK GREY " " " "	130 MALACHITE 230 PYRITE MALACHITE						
105	110	" " " " " "	" "						
110	115	GREY/GREEN (WET) " " "	" "						
115	120	" " " " " "	" "						
120	125	DARK GREY " " " "	" "						
125	130	" " " " " "	" "						
130	135	GREY GREEN " " " "	" "						
135	140	" " (WET) " " "	" "						
140	145	" " " " " "	390 PYRITE TRACE MALACHITE						
145	150	" " " " " "	" "						

PERCUSSION DRILL LOG

90R36
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	GREY/GREEN QUARTZ CHLORITE MUSCOVITE SCHIST	5% PYRITE						
155	160	" " " " " "	" "						
160	165	" " " " " "	1% PYRITE						
165	170	" " " " " "	" "						
170	175	" " (WET) " " " "	" "						
175	180	" " " " " "	" "						
180	185	" " " " " "	" "						
185	190	" " " " " "	" "						
190	195	" " " " " "	" "						
195	200	" " " " " "	" "						
200	205	" " " (VEIN QUARTZ?) " " "	" "						
205	210	" " " " " "	" "						
210	215	" " " (VEIN QUARTZ?) " " "	" "						
215	220	" " " " " "	" "						
220	225	" " " " " "	" "						
225	230	" " " " " "	2% PYRITE						
230	235	" " " " " "	1% PYRITE						
235	240	" " " " " "	TRACE PYRITE						
240	245	" " " " " "	" "						
245	250	" " " " " "	TRACE PYRITE						
250	255	" " " " " "	1% PYRITE						
255	260	" " " " " "	TRACE PYRITE						
260	265	" " " " " "	" "						
265	270	" " " " " "	TRACE PYRITE						
270	275	" " " " " "	1% PYRITE						
275	280	" " " " " "	TRACE PYRITE						
280	285	" " " " " "	" "						
285	290	" " " " " "	2% PYRITE						
290	295	" " " " " "	" "						
295	300	" " " " " "	" "						
300	305	" " " " " "	" "						
305	310	" " " " " "	" "						
310	315	DARK GREEN " " " "	" "						
315	320	" " " " " "	" "						
320	325	" " " " " "	1% PYRITE						
325	330	" " " " " "	" "						

PERCUSSION DRILL LOG

90 R 36
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
330	335	DARK GREEN QUARTZ CHLORITE MUSCOVITE SCHIST	1% PYRITE						
335	340	〃	〃						
340	345	〃	〃						
345	350	〃	〃						
350	355	〃	〃						
355	360	〃	〃						
360	365	〃	〃						
365	370	〃	〃						
370	375	〃	〃						
375	380	〃	〃						
380	385	〃	〃						
385	390	〃	〃						
390	395	〃	1% PYRITE TRACE PYRRHO						
395	400	BLACK QUARTZ GRAPHITE SCHIST	7% PYRITE						
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
FRENCH GULCH	FL IPL 3+60E	5+50S		Nov. 9 1990	90R37

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-75°	030°		300 ft	

Purpose: I.P. anomally

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	RED BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE ARSENY TRACE PYRITE						
5	10	" " " " " "	" "						
10	15	" " " " " "	" "						
15	20	" " " " " "	" "						
20	25	MEDIUM GREEN " " " "	TRACE PYRITE						
25	30	" " QUARTZ CHLORITE MUSCOVITE SCHIST	" "						
30	35	" " " " " "	" "						
35	40	" " " " " "	" "						
40	45	" " " " " "	1% "						
45	50	PALE GREEN/GREY (WHITE VEINLETS) " " "	2% "						
50	55	" " " " " "	1% "						
55	60	" " " " " "	" "						
60	65	" " " " " "	" "						
65	70	" " " MINOR " "	" "						
70	75	" " " GRAPHITE " "	TRACE "						
75	80	" " " /BLACK GRAPHITE " "	" "						
80	85	DARK GREY " " " "	1% PYRITE TRACE MINERAL						
85	90	" " " " " "	" "						
90	95	BLACK GRAPHITE SCHIST	TRACE MINERAL						
95	100	DARK GREY QUARTZ CHLORITE MUSCOVITE SCHIST	TRACE PYRITE						
100	105	PALE GREY " " " "	1% MINERAL TRACE PYRITE						
105	110	PALE GREY/GREEN " " " "	" "						
110	115	PALE GREY " " " "	" "						
115	120	MEDIUM GREY " " " "	1% MINERAL						
120	125	PALE BROWN " " " "	1% PYRITE						
125	130	PALE GREY/BROWN " " " "	" "						
130	135	PALE GREY " " " "	" "						
135	140	" " " " " "	1% PYRITE						
140	145	" " " " " "	" "						
145	150	" " " " " "	3% "						

PERCUSSION DRILL LOG

90R37
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	MEDIUM GREY/GREEN QUARTZ CHLORITE MUSCOVITE SCHIST	3% PYRITE						
155	160	GREEN (WET)	" "						
160	165	" "	" "						
165	170	" "	" "						
170	175	PALE GREY/GREEN	" "						
175	180	GREEN (DAMP)	" "						
180	185	" (WET)	" "						
185	190	" "	" "						
190	195	" "	[illegible]						
195	200	" "	" "						
200	205	" "	1% MICAS. 1% PYRITE						
205	210	" "	" "						
210	215	" "	" "						
215	220	" "	" "						
220	225	BLACK (WET) GRAPHITE SCHIST ± QCM SCHIST	" "						
225	230	" "	" "						
230	235	" " ± MUSC "	2% PYRITE 1% MICAS						
235	240	" "	" "						
240	245	" "	" "						
* 245	250	DARK GREENISH BLACK (WET) QUARTZ CHLOR/MUS SCHIST ± GR. SCH	2% PYRITE						
* 250	255	" " " " " " " "	" "						
* 255	260	BLACK (DAMP) GRAPHITE SCHIST ± QCMS	" "						
260	265	" " QUARTZ CHLORITE MUSC SCH ± GRAPH SCHIST	3% "						
265	270	DARK GREY " "	" "						
270	275	" "	" "						
275	280	BLACK " "	" "						
280	285	DARK GREY " "	" "						
285	290	BLACK " "	" "						
290	295	" "	" "						
295	300	" "	" "						
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
FRENCH GULCH	FG IPL 3+40E	3+60S		NOV 9-10, 1990	90 R 38

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-50°	040°		250' ft	

Purpose: I.P. anomally

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	ORANGE/BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	TRACE PYRITE						
5	10	BROWN/GREY QUARTZ MUSCOVITE GRAPHITE SCHIST	"						
10	15	" " " GRAPHITE MUSCOVITE SCHIST	"						
15	20	LIGHT ORANGE/BROWN (OXIDIZED) QUARTZ MUSCOVITE SCHIST	"						
20	25	LIGHT BROWN/GREY QUARTZ MUSCOVITE CHLORITE "	"						
25	30	LIGHT ORANGE/BROWN (OXIDIZED) QUARTZ MUSCOVITE "	"						
30	35	" " " " QUARTZ MUSCOVITE CHLORITE "	"						
35	40	" " " " QUARTZ CHLORITE MUSCOVITE "	"						
40	45	" " " " " MUSCOVITE "	"						
45	50	" " " " " " "	"						
50	55	ORANGE/BROWN & BROWN/GREY QUARTZ MUSCOVITE SCHIST + DIABASE DYKE	"						
55	60	BROWN/GREY QUARTZ MUSCOVITE GRAPHITE SCHIST	"						
60	65	" " " " " "	"						
65	70	" " " " " "	"						
70	75	LIGHT ORANGE BROWN " " "	"						
75	80	ORANGE/BROWN & BROWN/GREY " " "	"						
80	85	DARK GREY QUARTZ " "	"						
85	90	BLACK " " "	"						
90	95	PALE GREY/WHITE TRACE GRAPHITE QUARTZ MUSCOVITE SCHIST	"						
95	100	BROWN/GREY QUARTZ MUSCOVITE GRAPHITE SCHIST	"						
100	105	BROWN/BLACK " " " "	"						
105	110	ORANGE/BROWN " " " "	TRACE PYRITE						
110	115	LIGHT ORANGE/BROWN " " " "	" "						
115	120	" " " QUARTZ MUSCOVITE SCHIST	" "						
120	125	" " " " " "	" "						
125	130	" " " " " "	" "						
130	135	" " " " GRAPHITE " "	" "						
135	140	LIGHT GREY " " " "	" "						
140	145	" " " " " "	" "						
145	150	" " " " " "	" "						

PERCUSSION DRILL LOG

90R38
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	LIGHT GREY/BROWN QUARTZ CHLORITE MUSCOVITE SCHIST	1% PYRITE						
155	160	" " " " " "	" "						
160	165	" " " " " "	" "						
165	170	PALE GREY " " " "	" "						
170	175	LIGHT GREY/BROWN " " "	1% PYRITE 1% MAGNETITE						
175	180	LIGHT GREY " " "	" "						
180	185	" " QUARTZ CHLORITE SCHIST	1% PYRITE 2% ARSENOPYRITE						
185	190	" " " " "	" "						
190	195	" " " " "	1% PYRITE 2% ARSENOPYRITE						
195	200	" " " " "	1% PYRITE 1% ARSENOPYRITE						
200	205	" " " " "	" "						
205	210	" " " " "	" "						
210	215	" " " " "	" "						
215	220	" " " " "	3% PYRITE						
220	225	" " " " "	" "						
225	230	DARK GREY/BLACK QUARTZ CHLORITE CARBONATE SCHIST	" "						
230	235	" " " " " "	" "						
235	240	" " " " " "	" "						
240	245	" " " " " "	" "						
245	250	DARK GREY " " " "	" "						
		END OF HOLE							

PERCUSSION DRILL LOG

O'NEIL GULCH	O'NEIL/McKAY	ONEIL I PL 1400E	0+20S	NOV. 10-11, 1990	90 R 39
Location	Northing	Easting	Elevation	Date Drilled	Hole Number
-60°	160°		300' ft		
Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth	

Purpose: I.P. anomally near old adit

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	ORANGE/BROWN (WEATHERED) QUARTZ CHLORITE MUSCOVITE SCHIST	TRACE PYRITE						
5	10	" " " " " " "	" "						
10	15	RED/BROWN " " " " " "	" "						
15	20	" " " " " " "	TRACE MINERAL						
20	25	DARK BROWN " " " " "	" "						
25	30	DARK GREY QUARTZ SERICITE SCHIST	1% PYRITE						
30	35	WHITISH QUARTZ VEIN	2% PYRITE						
35	40	" QUARTZ VEIN IN CONTACT W/ DIABASE DYKE	2% PYRITE						
40	45	BLACK DIABASE DYKE W/ PEAK PORPHYRY	1% PYRITE						
45	50	WHITISH DIABASE DYKE IN CONTACT W/ QUARTZ VEIN	2% PYRITE						
50	55	DARK GREY DIABASE DYKE	2% "						
55	60	WHITISH QUARTZ VEIN	2% "						
60	65	PALE GREY DIABASE DYKE	1% "						
65	70	" " DIABASE DYKE W/ MINOR QUARTZ VEIN	1% "						
70	75	WHITISH QUARTZ VEIN	2% "						
75	80	" QUARTZ VEIN W/ MINOR DIABASE DYKE	2% "						
80	85	" QUARTZ MUSCOVITE CHLORITE SCHIST	3% "						
85	90	PALE GREEN " " " "	3% "						
90	95	WHITISH " " " " W/ QUARTZ VEIN	" "						
95	100	" " " " " "	TRACE PBS						
100	105	" " " " " "	" "						
105	110	" " " " " "	" "						
110	115	" " " " " "	" "						
115	120	" " " " " "	TRACE PBS						
120	125	" " " " " "	" "						
125	130	" " " " " " W/ QUARTZ VEIN	" "						
130	135	" " " " " "	" "						
135	140	" " " " " "	3% PYRITE						
140	145	PALE GREY/GREEN " " " "	" "						
145	150	WHITISH " " " "	" "						

PERCUSSION DRILL LOG

90R59
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	WHITISH " QUARTZ MUSCOVITE CHLORITE SCHIST	3% PYRITE						
155	160	" " " " "	" "						
160	165	DARK GREY " " " "	" "						
165	170	" " " " "	" "						
170	175	" " (DAMP) " " " "	" "						
175	180	" " " " " "	" "						
180	185	" " (WET) " " " "	" "						
185	190	DARK GREY/GREEN (WET) " " " "	" "						
190	195	" " " " " " "	" "						
195	200	" " " " " " "	" "						
200	205	PALE " " " " " "	" "						
205	210	" " " (DAMP) " " "	" "						
X 210	215	MEDIUM " " " " " "	TRACE PYS						
215	220	PALE " " " " " "	3% PYRITE						
220	225	" " " " " " "	" "						
225	230	MEDIUM " " " " " "	" "						
230	235	" " " " " " "	" "						
235	240	WHITISH (DAMP) QUARTZ VEIN	2% PYRITE						
240	245	" " " "	" "						
245	250	" " " "	" "						
250	255	" " " "	" "						
255	260	" " " "	TRACE "						
260	265	" " " "	" "						
265	270	" " " "	" "						
270	275	PALE GREEN (DAMP) QUARTZ CHLORITE MUSCOVITE SCHIST	" "						
275	280	" " " " " "	" "						
X 280	285	" " " " " "	" "						
285	290	WHITISH/GREY " " " "	" "						
290	295	GREYISH " " " "	" "						
295	300	" " " "	" "						
		END OF HOLE							

PERCUSSION DRILL LOG

FRENCH GULCH	ELDORADO CK IPL	29+40S		NOV. 16, 1990	90 R 45
Location	Northing	Easting	Elevation	Date Drilled	Hole Number
-60°	345°		350 ft		
Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth	

I.P. anomaly
Purpose

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) QUARTZ MUSCOVITE CHLORITE SCHIST	TRACE PYRITE TRACE MAGNET						
5	10	" " " " " " "	" "						
10	15	" " " " " " "	TRACE PYRITE						
15	20	" " " (WET) " " " "	" "						
20	25	GREY/GREEN " " " "	" "						
25	30	" " " " " " "	" "						
30	35	GREY (WET) " " " "	" "						
35	40	" " " " " " "	2% PYRITE						
40	45	PALE GREY/WHITE " " " "	" "						
45	50	" " " " " " "	" "						
50	55	" " " " " " "	" "						
55	60	DARK GREY (DAMP) " " " "	TRACE MAGNET						
60	65	DARK GREY/GREEN " " " "	2% PYRITE						
65	70	" " " QUARTZ CHLORITE SCHIST	" "						
70	75	DARK GREY/GREEN " " "	" "						
75	80	DARK GREY (WET) QUARTZ SERICITE CHLORITE SCHIST	5% PYRITE						
80	85	" " " " " " "	" "						
85	90	" " " " " " "	" "						
90	95	" " " " " " "	" "						
95	100	" " " " " " "	" "						
100	105	MEDIUM GREEN " " " "	" "						
105	110	" " (WET) " " " "	" "						
110	115	" " " " " " "	" "						
115	120	DARK GREY " " " "	" "						
120	125	" " " QUARTZ SERICITE CHLORITE & GRAPHITE "	" "						
125	130	" " /BLACK " " " "	" "						
130	135	" " " " " " "	" "						
135	140	DARK GREY/GREEN " /MINOR LIMONITE QS CHLORITE "	" "						
140	145	" " " " " " "	" "						
145	150	DARK GREY " " " "	" "						

PERCUSSION DRILL LOG

90 R 45
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	DARK GREY/GREEN (WET) MINOR GRANITE + QUARTZ SER/CHLOR SCHIST	5% PYRITE						
155	160	" " " " " " " " " "	" "						
160	165	" " " " " " " " " "	" "						
165	170	PALE GREENISH/WHITE (WET)	" "						
* 170	175	DARK GREY/BLACK (WET) MINOR QSC SCHIST + DIABASE DYKE	1% PYRITE						
175	180	" " " " MINOR DIABASE + QUARTZ SER/CHL SCHIST	" "						
180	185	DARK GREY/GREEN " " QUARTZ SERICITE CHLORITE SCHIST	" "						
185	190	" " " " " " " "	" "						
190	195	" " " " " " " "	1% PYRITE 1% MAGNETITE						
195	200	" " " " " " " "	" "						
200	205	" " " " " " " "	" "						
205	210	MEDIUM GREEN " " " " " "	TRACE PYRITE 1% MAGNETITE						
210	215	" " " " " " " "	" "						
215	220	" " " " " " " "	1% PYRITE 1% MAGNETITE						
220	225	WHITE & GREEN CHLORITE QUARTZ SERICITE SCHIST	" "						
225	230	WHITE & GREEN " CHLORITE QUARTZ SERICITE SCHIST	" "						
230	235	MEDIUM GREEN " QUARTZ SERICITE CHLORITE SCHIST	" "						
235	240	" " " " " " "	" "						
240	245	MISSING							
245	250	" " " " " " "	" "						
250	255	" " " " " " "	" "						
255	260	" " " " " " "	" "						
260	265	" " " " " " "	1% PYRITE						
265	270	" " " " " " "	" "						
270	275	" " " " " " "	TRACE PYRITE						
275	280	" " " " " " "	1% "						
280	285	" " " " " " "	" "						
285	290	" " " " " " "	" "						
290	295	" " " " " " "	" "						
295	300	" " " " " " "	TRACE MAGNETITE 2% PYRITE						
300	305	" " " " " " "	TRACE MAGNETITE						
305	310	" " " " " " "	" "						
310	315	" " " " " " "	2% PYRITE						
315	320	" " " " " " "	" "						
320	325	" " " " " " "	" "						
325	330	" " " " " " "	TRACE MAGNETITE						

* 1 SMALL GREY METALLIC BALL BEARING ? NOT MAGNETIC

PERCUSSION DRILL LOG

90R45
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
330	335	MEDIUM GREEN (WET) QUARTZ SERICITE CHLORITE SCHIST	1% PYRITE						
335	340	MEDIUM GREEN (WET) QUARTZ SERICITE CHLORITE SCHIST	1% PYRITE TRACE MINERAL						
340	345	" " " MINOR GRAPHITE + QSC "	" "						
345	350	" " " " " "	TRACE PYRITE						
~~350~~		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
FRENCH GULCH	FG IPL 6+61S	7+60E		NOV. 17-18, 1990	90 R46

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-50°	080°		500 ft	

Purpose: I.P. anomally

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	ORANGE/BROWN (LIMONITE) QUARTZ CHLORITE SCHIST	TRACE PYRITE TRACE MAGNET						
5	10	" " " " " "	" "						
10	15	" " " " " "	" "						
15	20	" " " " " "	CA						
20	25	" " " " " "	TRACE PYRITE TRACE MAGNET						
25	30	" " " " " "	" "						
30	35	" " " " " "	" "						
35	40	" " " " " "	" "						
40	45	" " " (LIMONITE) " " "	" "						
45	50	" " " " " "	" "						
50	55	PALE GREY/GREEN " " " " "	" "						
55	60	" " " " " "	" "						
60	65	" " " " " "	" "						
65	70	" " " " " "	" "						
70	75	" " " QUARTZ GRAPHITIC CHLORITE "	CA						
75	80	" " " " " "	1% MAGNETITE						
80	85	" " " " " "	TRACE PYRITE						
85	90	" " " " " "	1% LIMONITE 1% PYRITE						
90	95	" " " " " "	" "						
95	100	" " " " " "	" "						
100	105	" " " " " "	" "						
105	110	" " " " " "	2% PYRITE						
110	115	" " " QUARTZ CHLORITE SCHIST	2% PYRITE						
115	120	" " " " " "	1% MAGNET						
120	125	" " " " " "	" "						
125	130	" " " " " "	" "						
130	135	" " " " " "	" "						
135	140	" " " " " "	" "						
140	145	MEDIUM " " " " "	" "						
145	150	PALE " " " " "	" "						

PERCUSSION DRILL LOG

90 R46
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	PALE GREY/GREEN QUARTZ SERICITE SCHIST	1% PYRITE TRACE MAGNETITE						
155	160	" " " QUARTZ CHLORITE SERICITE SCHIST	2% " "						
160	165	" " " " " " "	TRACE PYRITE MAGNETITE						
165	170	" " " " " " "	1% " "						
170	175	" " GRAPHITIC " " "	" "						
175	180	" " " " " " "	" "						
180	185	DARK GREY/BLACK QUARTZ CHLORITE GRAPHITE SCHIST	1% PYRITE						
185	190	" " " " " "	" "						
190	195	PALE GREY/GREEN (WET) QUARTZ CHLORITE SCHIST	" "						
195	200	DARK GREY QUARTZ CHLORITE GRAPHITIC SCHIST	" "						
200	205	BLACK (WET) CHLORITIC QUARTZ GRAPHITE SCHIST	TRACE MAGNETITE						
205	210	" " " QUARTZ GRAPHITE SCHIST	" "						
210	215	" " " " "	" "						
215	220	" " " " "	2% PYRITE						
220	225	" " " " "	" "						
225	230	PALE GREY/GREEN (WET) MUSCOVITE QUARTZ CHLORITE SCHIST	1% PYRITE						
230	235	" " " " QUARTZ CHLORITE SERICITE SCHIST	TRACE "						
235	240	" " " " " " "	1% "						
240	245	BLACK (WET) QUARTZ CHLORITE GRAPHITIC SCHIST	1% "						
245	250	" " QUARTZ-GRAPHITIC CHLORITE SCHIST	TRACE "						
250	255	PALE GREY/GREEN (WET) QUARTZ CHLORITE SERICITE SCHIST	" "						
255	260	" " " " " " "	" "						
260	265	" " " MINOR GRAPHITE " " "	" "						
265	270	BLACK (WET) MUSCOVITE CHLORITE QUARTZ GRAPHITE "	" "						
270	275	" " " " " " "	" "						
275	280	DARK GREEN (DAMP) QUARTZ CHLORITE SCHIST	TRACE MAGNETITE						
280	285	" " " MINOR GRAPHITE " "	" "						
285	290	" " " " " "	2% PYRITE						
290	295	" " (WET) " " "	1% "						
295	300	" " (DAMP) " " "	" "						
300	305	BLACK (DAMP) QUARTZ CHLORITE GRAPHITE "	" "						
305	310	PALE GREEN/WHITE (DAMP) QUARTZ GRAPHITE CHLORITE "	1% PYRITE TRACE MAGNETITE						
310	315	" " " " " " "	" "						
315	320	DARK GREEN (DAMP) " " " "	" "						
320	325	" " (WET) " " "	" "						
325	330	" " " " " "	" "						

PERCUSSION DRILL LOG

90 R 46
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
330	335	DARK GREEN (DAMP) QUARTZ GRAPHITE CHLORITE SCHIST	1% PYRITE 1% MAGNET						
* 335	340	" " " " " " "	" "						
* 340	345	" " " BAND QUARTZ VEINLETS " " " "	" "						
345	350	" " " " " " "	" "						
350	355	" " " " " " "	2% PYRITE						
355	360	" " " " " " "	" "						
360	365	" " " " " " "	" "						
365	370	" " " " " " "	" "						
370	375	" " " " " " "	" "						
375	380	" " " " " " "	3% "						
380	385	" " " QUARTZ CHLORITE GRAPHITE "	2% "						
385	390	" " " QUARTZ GRAPHITE CHLORITE "	" "						
390	395	" " " " " " "	" "						
395	400	GREEN/BLACK " " " " " "	- "						
400	405	BLACK " " " " " "	" "						
405	410	" " QUARTZ GRAPHITE SCHIST	2% PYRITE						
410	415	" " " " "	" "						
415	420	" (WET) " " "	2% PYRITE 1% MAGNET						
420	425	" (DAMP) " " "	" "						
425	430	" " " " "	" "						
430	435	GREEN/BLACK (DAMP) QUARTZ GRAPHITE SERICITE SCHIST	" "						
435	440	" " " QUARTZ GRAPHITE SCHIST	" "						
440	445	" " " QUARTZ GRAPHITE SERICITE SCHIST	2% PYRITE						
445	450	" " " " " "	2% PYRITE 1% MAGNET						
450	455	BLACK (DAMP) MINOR CHLORITE QUARTZ GRAPHITE "	" "						
455	460	" " " " " " "	" "						
460	465	" " " " " " "	" "						
465	470	" " " " " " "	3% PYRITE TRACE MAGNET						
470	475	" " " " " " "	" "						
475	480	" " " " " " "	" "						
480	485	" " " " " " "	" "						
485	490	" " " " " " "	1% PYRITE						
490	495	" " " QUARTZ GRAPHITE CHLORITE "	" "						
495	500	" " " " " " "	TRACE "						
		END OF HOLE							

NOTE: MOST MAGNETIC MATERIAL IN THIS HOLE IS REDDISH-BROWN PYRRHOTITE

* ONE PIECE ASSAY PYRITE

PERCUSSION DRILL LOG

FRENCH GULCH	FG IPL 3+80E	3+15S		NOV. 18, 1990	90 R47
Location	Northing	Easting	Elevation	Date Drilled	Hole Number
-50°	220°		250' ft		
Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth	

I.P. anomally
Purpose

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	ORANGE/BROWN (OXIDIZED) QUARTZ MUSCOVITE CHLORITE	SCHIST						
5	10	" " " QUARTZ GRAPHITE CHLORITE SCHIST	TRACE PYRITE						
10	15	" " " " " " "	Ø						
15	20	" " " " " " "	Ø						
20	25	" " " " " " "	Ø						
25	30	" " " " " " "	Ø						
30	35	" " " " " " "	Ø						
35	40	" " " " " " "	Ø						
40	45	PALE BROWN " " " " "	Ø						
45	50	" " " " " " "	TRACE PYRITE						
50	55	WHITISH/BUFF QUARTZ MUSCOVITE CHLORITE SCHIST	Ø						
55	60	ORANGE BROWN " " " " "	TRACE PYRITE						
60	65	PALE BROWN " QUARTZ MUSCO/CHL/GRAPHITE SCHIST	Ø						
65	70	BROWN/BLACK " QUARTZ GRAPHITE SCHIST	Ø						
70	75	" " " " " "	TRACE PYRITE						
75	80	" " (WET) " " "	" "						
80	85	WHITE/GREY/GREEN MARBLE GRAPHITE - QUARTZ MUSCO/CHLOR "	Ø						
85	90	" " " QUARTZ MUSCOVITE CHLORITE SCHIST	Ø						
90	95	" " " " " " "	TRACE PYRITE						
95	100	" " " " " " "	" "						
100	105	" " " " " " "	Ø						
105	110	PALE BROWN " " " "	Ø						
110	115	ORANGE/BROWN (OXIDIZED) QMC + GRAPHITE SCHIST	TRACE PYRITE						
115	120	BROWN/BLACK (") " " " "	" "						
120	125	PALE BROWN " " " " "	" "						
125	130	" " QUARTZ MUSCOVITE CHLORITE SCHIST	" "						
130	135	WHITE/GREY/GREEN " " " "	" "						
135	140	" " " " " "	TRACE PYRITE TRACE MAGNET						
140	145	ORANGE/BROWN (OXIDIZED) " " "	" "						
145	150	WHITE/GREY/GREEN QUARTZ " " "	2% MAGNA						

PERCUSSION DRILL LOG

90 R 47
Hole Number

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
150	155	WHITE/GREY/GREEN QUARTZ MUSCOVITE CHLORITE SCHIST	TRACE PYRITE						
155	160	" " " " " " "	1% MAGNES 1% PYRITE 1% MAGNET						
160	165	" " " " " " "	" "						
165	170	" " " " " " "	" "						
170	175	" " " " " " "	2% PYRITE						
175	180	" " " " " " "	" "						
180	185	" " " " " " "	" "						
185	190	" " " " " " "	" "						
190	195	" " " " " " "	" "						
195	200	" " " " " " "	1% MAGNET						
200	205	" " " " " " "	" "						
205	210	" " " " " " "	3% PYRITE						
210	215	" " " " " " "	" "						
215	220	" " " " " " "	" "						
220	225	" " " " " " "	" "						
225	230	" " " " " " "	" "						
230	235	" " " " " " "	" "						
235	240	" " " " " " "	" "						
240	245	" " " " " " "	2% PYRITE 1% MAGNET						
245	250	" " " " " " "	3% PYRITE						
		END OF HOLE							
		* NOTE: MAGNETIC MINERAL OBSERVED THROUGHOUT THIS HOLE IS MAINLY REDDISH-BRONZE COLOURED PYRRHOTITE(?).							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
ELDORADO CK	ORO GRANDE IPL	494705 0+00W		NOV. 18, 1990	90 R48

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°	-		100' ft	

Purpose: I.P. anomaley

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK GREENISH/BROWN (GRAVEL) QUARTZ CHLORITE SCHIST	TRACE PYRITE						
5	10	" " " " " " "	" "						
10	15	" " " " " " "	" "						
15	20	" " " "	" "						
20	25	PALE GREENISH/WHITE " " " "	" "						
25	30	~~ALTERED~~ " " " " "	" "						
30	35	PALE GREENISH/WHITE QUARTZ CHLORITE MUSCOVITE "	" "						
35	40	PALE BROWNISH/WHITE (OXIDIZED) " " " "	" "						
40	45	" " " " " " " "	" "						
45	50	PALE BROWN (WET) " " " "	" "						
50	55	" " " " " " "	1% PYRITE						
55	60	PALE GREENISH/GREY " " " "	" "						
60	65	" " " (WET) " " " "	" "						
65	70	" " " " " " " "	" "						
70	75	MEDIUM GREEN (DAMP) QUARTZ MUSCOVITE CHLORITE "	" "						
75	80	" " (WET) " " " "	" "						
80	85	" " " " " " "	" "						
85	90	" " " " " " "	2% "						
90	95	" " " " " " "	" "						
95	100	" " " " " " "	" "						
		END OF HOLE							

PERCUSSION DRILL LOG

Location	Northing	Easting	Elevation	Date Drilled	Hole Number
ELDORADO CK	ORO GRANDE IPL	49+70S 0+30W		NOV. 19, 1990	90R49

Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth
-90°			100' ft	

Purpose: I.P. anomally

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) QUARTZ CHLOR/MUSCOV/SCHIST	TRACE PYRITE						
5	10	GRAVEL " " " " " " "	" "						
10	15	" " " " " " "	" "						
15	20	" " " " " " "	" "						
20	25	DARK GREY/GREEN (WET) " " " "	" "						
25	30	PALE GREY/GREEN " " " "	TRACE PYRITE						
30	35	" " " MINOR GRAPHITE " " "	" "						
35	40	BLACK QUARTZ GRAPHITE SCHIST	2% PYRITE						
40	45	" (DAMP) " " "	" "						
45	50	" " " " "	" "						
50	55	DARK GREY/BLACK " " "	" "						
55	60	BLACK " " "	" "						
60	65	" (WET) MINOR GRAPHITE QUARTZ CHLOR/MUSCOV/SCHIST	1% "						
65	70	" " " " " " " "	" "						
70	75	" " " " " " " "	" "						
75	80	" " " " " " " "	" "						
80	85	DARK GREY/GREEN (WET) MINOR GRAPHITE " " " "	" "						
85	90	" " " " " " " "	" "						
90	95	" " " " " " " "	" "						
95	100	" " " " " " " "	" "						
		END OF HOLE							

PERCUSSION DRILL LOG

ELDORADO CK	ORO GRANDE IPL	49+70S 0+60W		NOV 19, 1990	90R50
Location	Northing	Easting	Elevation	Date Drilled	Hole Number
-90°			115 ft		
Dip	Bearing	Casing Depth	Hole Depth	Overburden Depth	

Purpose: I.P. anomally

Footage From	Footage To	Description	Sample Number	Assays Au ppb	Ag	As	Cu	Pb	Zn
0	5	DARK BROWN (OXIDIZED) QUARTZ MUSCOVITE/CHLORITE SCHIST	TRACE PYRITE						
5	10	" " " " " " " "	2% "						
10	15	PALE GREENISH/GREY QUARTZ MUSCOVITE SCHIST	" "						
15	20	" " " (WET) " " "	" "						
20	25	" " " QUARTZ CHLORITE MUSCOVITE SCHIST	1% "						
25	30	PALE GREENISH/WHITE " " " "	" "						
30	35	" " " " " "	" "						
35	40	PALE GREENISH/BROWN (WET) " " " "	" "						
40	45	" " " " " " "	" "						
45	50	" " " " " " "	" "						
50	55	" " " (WET) " " "	" "						
55	60	" " " " " " "	" "						
60	65	PALE GREENISH/GREY (WET) " " " "	" "						
65	70	" " " " " " "	" "						
70	75	" " " " " " "	" "						
75	80	" " " " " " "	" "						
80	85	PALE GREY (WET) MINOR GRAPHITE " " "	" "						
85	90	BLACK (WET) QUARTZ GRAPHITE SCHIST	2% PYRITE						
90	95	" " MINOR " " "	" "						
95	100	" " QMC SCHIST " " "	" "						
100	105	DARK GREY " MINOR GRAPHITE QUARTZ CHLORITE MUSCOVITE SCHIST	" "						
105	110	PALE GREENISH/GREY (WET) " " " "	1% "						
110	115	" " " " " " "	" "						
		END OF HOLE							

APPENDIX V

ROTARY DRILL SAMPLES CERTIFICATES OF ANALYSES

Northern Analytical Laboratories ltd.

November 5,1990

Work Order # 08495

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3


File # 08495a

Sample: Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R1-0-5	0.007
90-R1-5-10	0.003
90-R1-10-15	<0.002
90-R1-15-20	<0.002
90-R1-20-25	<0.002
90-R1-25-30	<0.002
90-R1-30-35	<0.002
90-R1-35-40	<0.002
90-R1-40-45	<0.002
90-R1-45-50	<0.002
90-R1-50-55	<0.002
90-R1-55-60	<0.002
90-R1-60-65	<0.002
90-R1-65-70	<0.002
90-R1-70-75	<0.002
90-R1-75-80	<0.002
90-R1-80-85	<0.002
90-R1-85-90	<0.002
90-R1-90-95	<0.002
90-R1-95-100	<0.002

Au -- 1AT Fire Assay/Grav.



105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 5,1990

Work Order # 08495

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.

File # 08495b

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R2-0-5	<0.002
90-R2-5-10	<0.002
90-R2-10-15	<0.002
90-R2-15-20	<0.002
90-R2-20-25	0.012
90-R2-25-30	<0.002
90-R2-30-35	0.024
90-R2-35-40	0.015
90-R2-40-45	<0.002
90-R2-45-50	<0.002
90-R2-50-55	0.003
90-R2-55-60	<0.002
90-R2-60-65	<0.002
90-R2-65-70	<0.002
90-R2-70-75	<0.002
90-R2-75-80	<0.002
90-R2-80-85	0.006
90-R2-85-90	<0.002
90-R2-90-95	<0.002
90-R2-95-100	<0.002

Au -- 1AT Fire Assay/Grav.

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 5,1990

Work Order # 08495

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.

File # 08495c

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R3-0-5	0.004
90-R3-5-10	<0.002
90-R3-10-15	0.003
90-R3-15-20	<0.002
90-R3-20-25	<0.002
90-R3-25-30	<0.002
90-R3-30-35	<0.002
90-R3-35-40	<0.002
90-R3-40-45	<0.002
90-R3-45-50	<0.002
90-R3-55-60	<0.002
90-R3-60-65	<0.002
90-R3-65-70	<0.002
90-R3-70-75	<0.002
90-R3-75-80	<0.002
90-R3-80-85	<0.002
90-R3-85-90	0.004
90-R3-90-95	<0.002
90-R3-95-100	<0.002

Au -- 1AT Fire Assay/Grav.

Applied Science Technologists and Technicians of British Columbia
6992
CERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 5,1990

Work Order # 08495

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.

File # 08495d

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R4-0-5	<0.002
90-R4-5-10	<0.002
90-R4-10-15	<0.002
90-R4-15-20	<0.002
90-R4-20-25	0.006
90-R4-25-30	<0.002
90-R4-30-35	<0.002
90-R4-35-40	0.002
90-R4-40-45	<0.002
90-R4-45-50	<0.002
90-R4-50-55	<0.002
90-R4-55-60	<0.002
90-R4-60-65	<0.002
90-R4-65-70	<0.002
90-R4-70-75	<0.002
90-R4-75-80	<0.002

Au -- 1AT Fire Assay/Grav.

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 6,1990

Work Order # 13006

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13006a

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R5-0-5	0.004
90-R5-5-10	<0.002
90-R5-10-15	<0.002
90-R5-15-20	<0.002
90-R5-20-25	0.007
90-R5-25-30	<0.002
90-R5-30-35	<0.002
90-R5-35-40	<0.002
90-R5-40-45	<0.002
90-R5-45-50	<0.002
90-R5-50-55	<0.002
90-R5-55-60	<0.002
90-R5-60-65	<0.002
90-R5-65-70	<0.002
90-R5-70-75	<0.002
90-R5-75-80	<0.002
90-R5-85-90	<0.002
90-R5-90-95	<0.002
90-R5-95-100	<0.002
90-R5-100-105	<0.002
90-R5-105-110	<0.002
90-R5-110-115	<0.002
90-R5-115-120	<0.002
90-R5-120-125	<0.002

Au -- 1AT Fire Assay/Grav.

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 6,1990

Work Order # 13006

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13006b

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R6-0-5	<0.002
90-R6-5-10	<0.002
90-R6-10-15	<0.002
90-R6-15-20	<0.002
90-R6-20-25	<0.002
90-R6-25-30	<0.002
90-R6-30-35	<0.002
90-R6-35-40	<0.002
90-R6-40-45	<0.002
90-R6-45-50	0.002
90-R6-50-55	<0.002
90-R6-55-60	<0.002
90-R6-60-65	<0.002
90-R6-65-70	<0.002
90-R6-70-75	<0.002
90-R6-75-80	<0.002
90-R6-80-85	0.005
90-R6-85-90	0.006
90-R6-90-95	0.005
90-R6-95-100	<0.002
90-R6-100-105	<0.002
90-R6-105-110	<0.002
90-R6-110-115	0.009
90-R6-115-120	0.007
90-R6-120-125	<0.002
90-R6-125-130	<0.002
90-R6-130-135	<0.002
90-R6-135-140	<0.002
90-R6-140-145	<0.002
90-R6-145-150	<0.002

Au -- 1AT Fire Assay/Grav.

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 6,1990

Work Order # 13006

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13006c

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R7-0-5	<0.002
90-R7-5-10	<0.002
90-R7-10-15	<0.002
90-R7-15-20	<0.002
90-R7-20-25	<0.002
90-R7-25-30	<0.002
90-R7-30-35	<0.002
90-R7-35-40	0.011
90-R7-40-45	0.003
90-R7-45-50	0.003
90-R7-50-55	<0.002
90-R7-55-60	<0.002
90-R7-60-65	<0.002
90-R7-65-70	0.003
90-R7-70-75	0.062
90-R7-75-80	0.005
90-R7-80-85	<0.002
90-R7-85-90	0.003
90-R7-90-95	<0.002
90-R7-95-100	<0.002
90-R7-100-105	<0.002
90-R7-105-110	<0.002
90-R7-110-115	<0.002
90-R7-115-120	<0.002
90-R7-120-125	<0.002
90-R7-125-130	<0.002

Au -- 1AT Fire Assay/Grav.

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 15,1990

Work Order # 13009

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13009b

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R5-80-85	<0.002
90-R7-130-135	<0.002
90-R7-135-140	0.002
90-R7-140-145	<0.002
90-R7-145-150	<0.002
90-R7-150-155	<0.002
90-R7-155-160	0.027
90-R7-160-165	<0.002
90-R7-165-170	<0.002
90-R7-170-175	<0.002
90-R7-175-180	<0.002
90-R7-180-185	<0.002
90-R7-185-190	<0.002
90-R7-190-195	<0.002
90-R7-195-200	<0.002

Au -- 1AT Fire Assay/Grav

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 15,1990

Work Order # 13012

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13012a

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R8-0-5	<0.002	<0.002	<0.002	<0.002
90-R8-5-10	<0.002	<0.002	<0.002	<0.002
90-R8-10-15	<0.002	<0.002	<0.002	<0.002
90-R8-15-20	<0.002	<0.002	<0.002	<0.002
90-R8-20-25	<0.002	<0.002	<0.002	<0.002
90-R8-25-30	<0.002	<0.002	<0.002	<0.002
90-R8-30-35	<0.002	<0.002	<0.002	<0.002
90-R8-35-40	0.007	<0.002	0.007	0.008
90-R8-40-45	0.055	0.009	0.036	0.044
90-R8-45-50	0.008	<0.002	<0.002	0.002
90-R8-50-55	<0.002	<0.002	<0.002	<0.002
90-R8-55-60	<0.002	<0.002	0.017	0.016
90-R8-60-65	<0.002	<0.002	<0.002	<0.002
90-R8-65-70	0.025	0.003	<0.002	0.003
90-R8-70-75	0.060	0.010	0.024	0.032
90-R8-75-80	0.186	0.032	0.014	0.045
90-R8-80-85	0.672	0.091	0.206	0.283
90-R8-85-90	0.014	0.003	0.011	0.013
90-R8-90-95	0.057	0.006	0.030	0.035
90-R8-95-100	<0.002	<0.002	0.009	0.009
90-R8-100-105	<0.002	<0.002	<0.002	<0.002
90-R8-105-110	0.003	<0.002	0.014	0.014
90-R8-110-115	<0.002	<0.002	0.007	0.007
90-R8-115-120	0.044	0.010	0.086	0.090
90-R8-120-125	<0.002	<0.002	<0.002	<0.002
90-R8-125-130	<0.002	<0.002	<0.002	<0.002
90-R8-130-135	0.156	0.015	0.028	0.041
90-R8-135-140	0.687	0.131	0.125	0.250
90-R8-140-145	0.004	<0.002	0.002	0.003
90-R8-145-150	0.347	0.061	0.292	0.336

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 13,1990

Work Order # 13009

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13009b

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R9-0-5	0.003	<0.002	0.008	0.008
90-R9-5-10	<0.002	<0.002	0.006	0.005
90-R9-10-15	0.004	<0.002	0.002	0.002
90-R9-15-20	<0.002	<0.002	<0.002	<0.002
90-R9-20-25	0.006	<0.002	0.033	0.032
90-R9-25-30	<0.002	<0.002	0.007	0.006
90-R9-30-35	<0.002	<0.002	<0.002	<0.002
90-R9-35-40	0.073	0.007	0.015	0.022
90-R9-40-45	<0.002	<0.002	<0.002	<0.002
90-R9-45-50	<0.002	<0.002	0.007	0.007
90-R9-50-55	<0.002	<0.002	<0.002	<0.002
90-R9-55-60	<0.002	<0.002	<0.002	<0.002
90-R9-60-65	<0.002	<0.002	<0.002	<0.002
90-R9-65-70	0.031	0.005	0.016	0.020
90-R9-70-75	<0.002	<0.002	0.002	0.002
90-R9-75-80	<0.002	<0.002	<0.002	<0.002
90-R9-80-85	0.002	<0.002	0.014	0.014
90-R9-85-90	0.003	<0.002	0.007	0.007
90-R9-90-95	<0.002	<0.002	0.010	0.009
90-R9-95-100	3.816	0.616	0.236	0.837
90-R9-100-105	0.002	<0.002	0.012	0.011
90-R9-105-110	<0.002	<0.002	0.010	0.009
90-R9-110-115	0.019	0.003	0.017	0.019
90-R9-115-120	0.049	0.004	0.033	0.039
90-R9-120-125	0.030	0.005	0.013	0.018
90-R9-125-130	0.003	<0.002	0.032	0.031
90-R9-130-135	0.191	0.017	0.065	0.094
90-R9-135-140	0.049	0.008	<0.002	0.008
90-R9-140-145	<0.002	<0.002	0.004	0.004
90-R9-145-150	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
CERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: [illegible]

Northern Analytical Laboratories ltd.

November 13,1990

Work Order # 13009

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13009c

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R10-0-5	<0.002	<0.002	<0.002	<0.002
90-R10-5-10	<0.002	<0.002	<0.002	<0.002
90-R10-10-15	0.002	<0.002	<0.002	<0.002
90-R10-15-20	<0.002	<0.002	0.021	0.020
90-R10-20-25	0.025	0.003	0.005	0.008
90-R10-25-30	<0.002	<0.002	0.002	0.002
90-R10-30-35	<0.002	<0.002	<0.002	<0.002
90-R10-35-40	<0.002	<0.002	<0.002	<0.002
90-R10-40-45	<0.002	<0.002	0.002	0.002
90-R10-45-50	0.005	<0.002	0.008	0.008
90-R10-50-55	0.915	0.072	0.021	0.093
90-R10-55-60	<0.002	<0.002	0.007	0.007
90-R10-60-65	<0.002	<0.002	0.004	0.004
90-R10-65-70	0.003	<0.002	<0.002	<0.002
90-R10-70-75	<0.002	<0.002	<0.002	<0.002
90-R10-75-80	<0.002	<0.002	<0.002	<0.002
90-R10-80-85	0.094	0.022	<0.002	0.022
90-R10-85-90	<0.002	<0.002	<0.002	<0.002
90-R10-90-95	<0.002	<0.002	<0.002	<0.002
90-R10-95-100	<0.002	<0.002	<0.002	<0.002
90-R10-100-105	<0.002	<0.002	0.004	0.004
90-R10-105-110	<0.002	<0.002	<0.002	<0.002
90-R10-110-115	<0.002	<0.002	<0.002	<0.002
90-R10-115-120	<0.002	<0.002	<0.002	<0.002
90-R10-120-125	<0.002	<0.002	<0.002	<0.002
90-R10-125-130	<0.002	<0.002	<0.002	<0.002
90-R10-130-135	<0.002	<0.002	<0.002	<0.002
90-R10-135-140	0.004	<0.002	<0.002	<0.002
90-R10-140-145	<0.002	<0.002	<0.002	<0.002
90-R10-145-150	<0.002	<0.002	0.002	0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 14,1990

Work Order # 13009

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13009d

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R11-0-5	0.063	0.009	0.016	0.025
90-R11-5-10	<0.002	<0.002	0.010	0.010
90-R11-10-15	0.105	0.014	0.025	0.038
90-R11-15-20	2.538	0.232	0.060	0.290
90-R11-20-25	<0.002	<0.002	0.006	0.006
90-R11-25-30	<0.002	<0.002	0.005	0.005
90-R11-30-35	0.204	0.052	0.016	0.068
90-R11-35-40	0.029	0.003	0.016	0.018
90-R11-40-45	0.023	0.004	0.018	0.021
90-R11-45-50	0.004	<0.002	0.036	0.035
90-R11-50-55	<0.002	<0.002	<0.002	<0.002
90-R11-55-60	<0.002	<0.002	<0.002	<0.002
90-R11-60-65	<0.002	<0.002	<0.002	<0.002
90-R11-65-70	<0.002	<0.002	<0.002	<0.002
90-R11-70-75	<0.002	<0.002	<0.002	<0.002
90-R11-75-80	<0.002	<0.002	<0.002	<0.002
90-R11-80-85	<0.002	<0.002	<0.002	<0.002
90-R11-85-90	<0.002	<0.002	<0.002	<0.002
90-R11-90-95	<0.002	<0.002	<0.002	<0.002
90-R11-95-100	<0.002	<0.002	<0.002	<0.002
90-R11-100-105	<0.002	<0.002	<0.002	<0.002
90-R11-105-110	<0.002	<0.002	<0.002	<0.002
90-R11-110-115	<0.002	<0.002	<0.002	<0.002
90-R11-115-120	0.028	0.004	0.027	0.030
90-R11-120-125	<0.002	<0.002	<0.002	<0.002
90-R11-125-130	<0.002	<0.002	<0.002	<0.002
90-R11-130-135	<0.002	<0.002	0.012	0.011
90-R11-135-140	0.438	0.046	<0.002	0.046
90-R11-140-145	<0.002	<0.002	0.007	0.007
90-R11-145-150	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 15,1990

Work Order # 13012

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13012b

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R12-0-5	<0.002	<0.002	0.002	0.002
90-R12-5-10	<0.002	<0.002	<0.002	<0.002
90-R12-10-15	0.013	0.003	<0.002	0.003
90-R12-15-20	<0.002	<0.002	<0.002	<0.002
90-R12-20-25	<0.002	<0.002	<0.002	<0.002
90-R12-25-30	<0.002	<0.002	0.031	0.029
90-R12-30-35	0.014	0.003	0.011	0.013
90-R12-35-40	<0.002	<0.002	0.018	0.017
90-R12-40-45	<0.002	<0.002	<0.002	<0.002
90-R12-45-50	<0.002	<0.002	<0.002	<0.002
90-R12-50-55	<0.002	<0.002	<0.002	<0.002
90-R12-55-60	<0.002	<0.002	<0.002	<0.002
90-R12-60-65	<0.002	<0.002	<0.002	<0.002
90-R12-65-70	<0.002	<0.002	<0.002	<0.002
90-R12-70-75	<0.002	<0.002	<0.002	<0.002
90-R12-75-80	0.003	<0.002	<0.002	<0.002
90-R12-80-85	<0.002	<0.002	<0.002	<0.002
90-R12-85-90	<0.002	<0.002	<0.002	<0.002
90-R12-90-95	<0.002	<0.002	<0.002	<0.002
90-R12-95-100	<0.002	<0.002	<0.002	<0.002
90-R12-100-105	<0.002	<0.002	<0.002	<0.002
90-R12-105-110	<0.002	<0.002	0.037	0.035
90-R12-110-115	<0.002	<0.002	<0.002	<0.002
90-R12-115-120	0.005	<0.002	0.024	0.023
90-R12-120-125	<0.002	<0.002	<0.002	<0.002
90-R12-125-130	<0.002	<0.002	<0.002	<0.002
90-R12-130-135	0.002	<0.002	0.066	0.062
90-R12-135-140	<0.002	<0.002	<0.002	<0.002
90-R12-140-145	<0.002	<0.002	<0.002	<0.002
90-R12-145-150	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 14,1990

Work Order # 13009

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13009e

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R13-0-5	0.006	<0.002	0.007	0.007
90-R13-5-10	0.003	<0.002	0.004	0.004
90-R13-10-15	<0.002	<0.002	<0.002	<0.002
90-R13-15-20	<0.002	<0.002	<0.002	<0.002
90-R13-20-25	<0.002	<0.002	<0.002	<0.002
90-R13-25-30	<0.002	<0.002	<0.002	<0.002
90-R13-30-35	<0.002	<0.002	<0.002	<0.002
90-R13-35-40	<0.002	<0.002	<0.002	<0.002
90-R13-40-45	0.003	<0.002	0.009	0.009
90-R13-45-50	<0.002	<0.002	<0.002	<0.002
90-R13-50-55	<0.002	<0.002	0.004	0.004
90-R13-55-60	<0.002	<0.002	0.004	0.004
90-R13-60-65	<0.002	<0.002	<0.002	<0.002
90-R13-65-70	<0.002	<0.002	0.002	0.002
90-R13-70-75	<0.002	<0.002	<0.002	<0.002
90-R13-75-80	<0.002	<0.002	0.005	0.005
90-R13-80-85	<0.002	<0.002	<0.002	<0.002
90-R13-85-90	<0.002	<0.002	0.002	0.002
90-R13-90-95	<0.002	<0.002	<0.002	<0.002
90-R13-95-100	<0.002	<0.002	<0.002	<0.002
90-R13-100-105	<0.002	<0.002	<0.002	<0.002
90-R13-105-110	0.479	0.084	0.081	0.163
90-R13-110-115	<0.002	<0.002	0.010	0.009
90-R13-115-120	0.002	<0.002	0.004	0.004
90-R13-120-125	<0.002	<0.002	<0.002	<0.002
90-R13-125-130	0.694	0.071	0.004	0.075
90-R13-130-135	<0.002	<0.002	<0.002	<0.002
90-R13-135-140	<0.002	<0.002	<0.002	<0.002
90-R13-140-145	0.005	<0.002	<0.002	<0.002
90-R13-145-150	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 14,1990

Work Order # 13009

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13009f

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R14-0-5	0.031	0.003	0.025	0.027
90-R14-5-10	0.004	<0.002	<0.002	<0.002
90-R14-10-15	0.254	0.048	0.044	0.090
90-R14-15-20	0.154	0.018	0.132	0.145
90-R14-20-25	0.044	0.008	0.054	0.060
90-R14-25-30	0.005	<0.002	0.063	0.062
90-R14-30-35	0.070	0.008	0.050	0.055
90-R14-35-40	<0.002	<0.002	0.004	0.004
90-R14-40-45	<0.002	<0.002	0.009	0.009
90-R14-45-50	<0.002	<0.002	<0.002	<0.002
90-R14-50-55	<0.002	<0.002	<0.002	<0.002
90-R14-55-60	<0.002	<0.002	0.004	0.004
90-R14-60-65	0.071	0.009	0.015	0.023
90-R14-65-70	0.037	0.006	0.011	0.017
90-R14-70-75	0.009	0.002	0.019	0.020
90-R14-75-80	0.015	0.002	0.051	0.050
90-R14-80-85	0.573	0.108	0.070	0.175
90-R14-85-90	0.118	0.013	0.008	0.020
90-R14-90-95	<0.002	<0.002	0.003	0.003
90-R14-95-100	<0.002	<0.002	<0.002	<0.002
90-R14-100-105	<0.002	<0.002	<0.002	<0.002
90-R14-105-110	0.003	<0.002	0.018	0.017
90-R14-110-115	<0.002	<0.002	0.013	0.012
90-R14-115-120	<0.002	<0.002	<0.002	<0.002
90-R14-120-125	<0.002	<0.002	<0.002	<0.002
90-R14-125-130	<0.002	<0.002	<0.002	<0.002
90-R14-130-135	<0.002	<0.002	<0.002	<0.002
90-R14-135-140	<0.002	<0.002	<0.002	<0.002
90-R14-140-145	<0.002	<0.002	<0.002	<0.002
90-R14-145-150	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
CERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 15,1990

Work Order # 13012

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13012c

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R15-0-5	<0.002	<0.002	0.004	0.004
90-R15-5-10	<0.002	<0.002	0.005	0.005
90-R15-10-15	<0.002	<0.002	0.011	0.010
90-R15-15-20	<0.002	<0.002	<0.002	<0.002
90-R15-20-25	<0.002	<0.002	<0.002	<0.002
90-R15-25-30	<0.002	<0.002	<0.002	<0.002
90-R15-30-35	<0.002	<0.002	0.006	0.006
90-R15-35-40	0.009	0.002	0.043	0.042
90-R15-40-45	0.036	0.008	0.125	0.129
90-R15-45-50	0.004	<0.002	0.020	0.019
90-R15-50-55	<0.002	<0.002	<0.002	<0.002
90-R15-55-60	0.107	0.013	0.007	0.019
90-R15-60-65	0.005	<0.002	0.012	0.012
90-R15-65-70	<0.002	<0.002	0.002	0.002
90-R15-70-75	0.004	<0.002	<0.002	<0.002
90-R15-75-80	0.022	0.003	0.009	0.011
90-R15-80-85	4.401	0.639	0.086	0.719
90-R15-85-90	<0.002	<0.002	<0.002	<0.002
90-R15-90-95	0.023	0.003	0.004	0.007
90-R15-95-100	<0.002	<0.002	<0.002	<0.002
90-R15-100-105	0.066	0.007	0.004	0.011
90-R15-105-110	<0.002	<0.002	0.007	0.007
90-R15-110-115	<0.002	<0.002	<0.002	<0.002
90-R15-115-120	<0.002	<0.002	<0.002	<0.002
90-R15-120-125	<0.002	<0.002	<0.002	<0.002
90-R15-125-130	<0.002	<0.002	<0.002	<0.002
90-R15-130-135	<0.002	<0.002	<0.002	<0.002
90-R15-135-140	<0.002	<0.002	<0.002	<0.002
90-R15-140-145	<0.002	<0.002	<0.002	<0.002
90-R15-145-150	0.003	<0.002	0.002	0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 14,1990

Work Order # 13009

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13009g

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R16-0-5	0.028	0.003	<0.002	0.003
90-R16-5-10	0.002	<0.002	0.022	0.021
90-R16-10-15	<0.002	<0.002	<0.002	<0.002
90-R16-15-20	<0.002	<0.002	0.008	0.007
90-R16-20-25	<0.002	<0.002	<0.002	<0.002
90-R16-25-30	0.064	0.012	0.021	0.032
90-R16-30-35	0.734	0.142	0.026	0.167
90-R16-35-40	<0.002	<0.002	<0.002	<0.002
90-R16-40-45	0.114	0.026	0.017	0.042
90-R16-45-50	<0.002	<0.002	<0.002	<0.002
90-R16-50-55	<0.002	<0.002	<0.002	<0.002
90-R16-55-60	<0.002	<0.002	<0.002	<0.002
90-R16-60-65	<0.002	<0.002	<0.002	<0.002
90-R16-65-70	<0.002	<0.002	0.003	0.003
90-R16-70-75	<0.002	<0.002	<0.002	<0.002
90-R16-75-80	<0.002	<0.002	<0.002	<0.002
90-R16-80-85	0.006	<0.002	0.014	0.014
90-R16-85-90	<0.002	<0.002	0.003	0.003
90-R16-90-95	<0.002	<0.002	<0.002	<0.002
90-R16-95-100	<0.002	<0.002	<0.002	<0.002
90-R16-100-105	<0.002	<0.002	<0.002	<0.002
90-R16-105-110	0.007	<0.002	0.008	0.009
90-R16-110-115	<0.002	<0.002	0.012	0.011
90-R16-115-120	<0.002	<0.002	0.006	0.006
90-R16-120-125	0.013	0.002	0.011	0.012
90-R16-125-130	<0.002	<0.002	<0.002	<0.002
90-R16-130-135	<0.002	<0.002	0.021	0.020
90-R16-135-140	0.041	0.005	0.020	0.024
90-R16-140-145	0.096	0.010	0.008	0.018
90-R16-145-150	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 19,1990

Work Order # 13012

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13012d

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R17-0-5	<0.002	<0.002	<0.002	<0.002
90-R17-5-10	<0.002	<0.002	<0.002	<0.002
90-R17-10-15	<0.002	<0.002	0.002	0.002
90-R17-15-20	0.010	<0.002	0.011	0.012
90-R17-20-25	0.043	0.005	<0.002	0.005
90-R17-25-30	<0.002	<0.002	<0.002	<0.002
90-R17-30-35	<0.002	<0.002	<0.002	<0.002
90-R17-35-40	<0.002	<0.002	<0.002	<0.002
90-R17-40-45	<0.002	<0.002	0.003	0.003
90-R17-45-50	0.016	0.004	0.020	0.022
90-R17-50-55	0.198	0.045	0.018	0.062
90-R17-55-60	<0.002	<0.002	0.010	0.009
90-R17-60-65	<0.002	<0.002	0.002	0.002
90-R17-65-70	<0.002	<0.002	<0.002	<0.002
90-R17-70-75	<0.002	<0.002	<0.002	<0.002
90-R17-75-80	<0.002	<0.002	<0.002	<0.002
90-R17-80-85	<0.002	<0.002	<0.002	<0.002
90-R17-85-90	<0.002	<0.002	<0.002	<0.002
90-R17-90-95	<0.002	<0.002	0.005	0.005
90-R17-95-100	<0.002	<0.002	0.004	0.004
90-R17-100-105	<0.002	<0.002	<0.002	<0.002
90-R17-105-110	1.189	0.184	0.077	0.256
90-R17-110-115	<0.002	<0.002	0.002	0.002
90-R17-115-120	<0.002	<0.002	0.003	0.003
90-R17-120-125	0.004	<0.002	0.006	0.007
90-R17-125-130	0.062	0.011	0.034	0.044
90-R17-130-135	<0.002	<0.002	<0.002	<0.002
90-R17-135-140	<0.002	<0.002	<0.002	<0.002
90-R17-140-145	0.117	0.023	0.007	0.029
90-R17-145-150	<0.002	<0.002	0.002	0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
CERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 21,1990

Work Order # 13020

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13020a

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R18-0-5	0.003	<0.002	<0.002	<0.002
90-R18-5-10	<0.002	<0.002	0.005	0.005
90-R18-10-15	<0.002	<0.002	<0.002	<0.002
90-R18-15-20	<0.002	<0.002	<0.002	<0.002
90-R18-20-25	<0.002	<0.002	<0.002	<0.002
90-R18-25-30	<0.002	<0.002	<0.002	<0.002
90-R18-30-35	0.004	<0.002	<0.002	<0.002
90-R18-35-40	0.068	0.011	0.052	0.061
90-R18-40-45	0.002	<0.002	0.015	0.015
90-R18-45-50	<0.002	<0.002	<0.002	<0.002
90-R18-50-55	<0.002	<0.002	0.008	0.008
90-R18-55-60	0.130	0.023	0.041	0.062
90-R18-60-65	<0.002	<0.002	0.011	0.011
90-R18-65-70	0.250	0.046	<0.002	0.046
90-R18-70-75	<0.002	<0.002	0.011	0.011
90-R18-75-80	<0.002	<0.002	<0.002	<0.002
90-R18-80-85	0.025	0.003	<0.002	0.003
90-R18-85-90	<0.002	<0.002	0.012	0.011
90-R18-90-95	<0.002	<0.002	0.015	0.014
90-R18-95-100	0.017	0.002	0.018	0.019
90-R18-100-105	0.197	0.031	0.134	0.158
90-R18-105-110	0.127	0.024	0.121	0.139
90-R18-110-115	0.006	<0.002	0.019	0.019
90-R18-115-120	2.241	0.370	0.139	0.501
90-R18-120-125	0.269	0.052	0.170	0.217
90-R18-125-130	<0.002	<0.002	0.009	0.009
90-R18-130-135	0.061	0.008	0.018	0.025
90-R18-135-140	<0.002	<0.002	0.009	0.009
90-R18-140-145	<0.002	<0.002	0.019	0.019
90-R18-145-150	0.304	0.043	0.054	0.095

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-8890

Northern Analytical Laboratories ltd.

November 21,1990

Work Order # 13020

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13020b

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R18-150-155	0.251	0.039	0.042	0.080
90-R18-155-160	<0.002	<0.002	<0.002	<0.002
90-R18-160-165	0.013	0.002	0.026	0.028
90-R18-165-170	<0.002	<0.002	0.019	0.018
90-R18-170-175	<0.002	<0.002	0.005	0.005
90-R18-175-180	<0.002	<0.002	0.002	0.002
90-R18-180-185	0.129	0.022	0.041	0.062
90-R18-185-190	<0.002	<0.002	0.009	0.009
90-R18-190-195	<0.002	<0.002	0.010	0.010
90-R18-195-200	0.078	0.011	0.029	0.039
90-R18-200-205	0.017	0.003	0.012	0.015
90-R18-205-210	0.020	0.003	0.009	0.012
90-R18-210-215	0.004	<0.002	0.008	0.008
90-R18-215-220	0.429	0.057	0.012	0.068
90-R18-220-225	<0.002	<0.002	<0.002	<0.002
90-R18-225-230	<0.002	<0.002	<0.002	<0.002
90-R18-230-235	<0.002	<0.002	<0.002	<0.002
90-R18-235-240	<0.002	<0.002	<0.002	<0.002
90-R18-240-245	<0.002	<0.002	<0.002	<0.002
90-R18-245-250	<0.002	<0.002	<0.002	<0.002
90-R18-250-255	<0.002	<0.002	<0.002	<0.002
90-R18-255-260	0.012	0.002	<0.002	0.002
90-R18-260-265	<0.002	<0.002	<0.002	<0.002
90-R18-265-270	0.003	<0.002	<0.002	<0.002
90-R18-270-275	<0.002	<0.002	0.003	0.003
90-R18-275-280	0.049	0.008	0.019	0.027
90-R18-280-285	<0.002	<0.002	0.004	0.004
90-R18-285-290	<0.002	<0.002	0.005	0.005
90-R18-290-295	<0.002	<0.002	<0.002	<0.002
90-R18-295-300	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
CERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 21,1990

Work Order # 13020

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13020c

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R18-300-305	<0.002	<0.002	0.006	0.006
90-R18-305-310	<0.002	<0.002	<0.002	<0.002
90-R18-310-315	<0.002	<0.002	<0.002	<0.002
90-R18-315-320	<0.002	<0.002	<0.002	<0.002
90-R18-320-325	<0.002	<0.002	<0.002	<0.002
90-R18-325-330	<0.002	<0.002	0.004	0.004
90-R18-330-335	<0.002	<0.002	<0.002	<0.002
90-R18-335-340	<0.002	<0.002	<0.002	<0.002
90-R18-340-345	<0.002	<0.002	<0.002	<0.002
90-R18-345-350	<0.002	<0.002	<0.002	<0.002
90-R18-350-355	<0.002	<0.002	<0.002	<0.002
90-R18-355-360	<0.002	<0.002	<0.002	<0.002
90-R18-360-365	<0.002	<0.002	0.004	0.004
90-R18-365-370	<0.002	<0.002	<0.002	<0.002
90-R18-370-375	<0.002	<0.002	<0.002	<0.002
90-R18-375-380	<0.002	<0.002	<0.002	<0.002
90-R18-380-385	<0.002	<0.002	<0.002	<0.002
90-R18-385-390	<0.002	<0.002	0.003	0.003
90-R18-390-395	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 20,1990

Work Order # 13012

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13012e

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R19-0-5	<0.002	<0.002	0.002	0.002
90-R19-5-10	<0.002	<0.002	<0.002	<0.002
90-R19-10-15	0.004	<0.002	<0.002	<0.002
90-R19-15-20	<0.002	<0.002	<0.002	<0.002
90-R19-20-25	<0.002	<0.002	<0.002	<0.002
90-R19-25-30	<0.002	<0.002	<0.002	<0.002
90-R19-30-35	<0.002	<0.002	<0.002	<0.002
90-R19-35-40	<0.002	<0.002	<0.002	<0.002
90-R19-40-45	<0.002	<0.002	<0.002	<0.002
90-R19-45-50	<0.002	<0.002	<0.002	<0.002
90-R19-50-55	<0.002	<0.002	<0.002	<0.002
90-R19-55-60	<0.002	<0.002	0.004	0.004
90-R19-60-65	<0.002	<0.002	<0.002	<0.002
90-R19-65-70	<0.002	<0.002	<0.002	<0.002
90-R19-70-75	0.049	0.008	0.010	0.018
90-R19-75-80	0.005	<0.002	0.021	0.020
90-R19-80-85	0.046	0.009	0.014	0.022
90-R19-85-90	<0.002	<0.002	0.004	0.004
90-R19-90-95	0.114	0.016	0.028	0.044
90-R19-95-100	0.003	<0.002	0.002	0.002
90-R19-100-105	0.017	0.003	<0.002	0.003
90-R19-105-110	<0.002	<0.002	0.003	0.003
90-R19-110-115	0.019	0.004	0.013	0.016
90-R19-115-120	0.002	<0.002	0.005	0.005
90-R19-120-125	<0.002	<0.002	<0.002	<0.002
90-R19-125-130	<0.002	<0.002	<0.002	<0.002
90-R19-130-135	<0.002	<0.002	<0.002	<0.002
90-R19-135-140	<0.002	<0.002	<0.002	<0.002
90-R19-140-145	<0.002	<0.002	<0.002	<0.002
90-R19-145-150	0.023	0.003	0.005	0.008

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 23,1990

Work Order # 13020

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3


File # 13020d

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R20-0-5	<0.002	<0.002	0.009	0.008
90-R20-5-10	0.002	<0.002	0.013	0.013
90-R20-10-15	0.003	<0.002	0.007	0.007
90-R20-15-20	<0.002	<0.002	0.006	0.006
90-R20-20-25	0.023	0.004	0.023	0.026
90-R20-25-30	0.039	0.008	0.046	0.053
90-R20-30-35	<0.002	<0.002	0.011	0.011
90-R20-35-40	<0.002	<0.002	0.008	0.007
90-R20-40-45	0.031	0.005	0.022	0.025
90-R20-45-50	0.016	0.002	0.011	0.013
90-R20-50-55	<0.002	<0.002	<0.002	<0.002
90-R20-55-60	<0.002	<0.002	<0.002	<0.002
90-R20-60-65	<0.002	<0.002	<0.002	<0.002
90-R20-65-70	0.016	0.002	<0.002	0.002
90-R20-70-75	0.007	<0.002	<0.002	<0.002
90-R20-75-80	<0.002	<0.002	<0.002	<0.002
90-R20-80-85	<0.002	<0.002	<0.002	<0.002
90-R20-85-90	<0.002	<0.002	<0.002	<0.002
90-R20-90-95	<0.002	<0.002	<0.002	<0.002
90-R20-95-100	<0.002	<0.002	<0.002	<0.002
90-R20-100-105	<0.002	<0.002	<0.002	<0.002
90-R20-105-110	<0.002	<0.002	0.004	0.004
90-R20-110-115				
90-R20-115-120				
90-R20-120-125				
90-R20-125-130	<0.002	<0.002	0.003	0.003
90-R20-130-135	0.011	0.002	0.008	0.010
90-R20-135-140	<0.002	<0.002	<0.002	<0.002
90-R20-140-145	<0.002	<0.002	<0.002	<0.002
90-R20-145-150	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay



105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 21,1990

Work Order # 13020

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13020e

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R20-150-155	<0.002	<0.002	<0.002	<0.002
90-R20-155-160	<0.002	<0.002	<0.002	<0.002
90-R20-160-165	<0.002	<0.002	<0.002	<0.002
90-R20-165-170	<0.002	<0.002	<0.002	<0.002
90-R20-170-175	<0.002	<0.002	<0.002	<0.002
90-R20-175-180	0.026	0.004	0.005	0.009
90-R20-180-185	<0.002	<0.002	<0.002	<0.002
90-R20-185-190	0.009	<0.002	<0.002	<0.002
90-R20-190-195	<0.002	<0.002	<0.002	<0.002
90-R20-195-200	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 29,1990

Work Order # 13023

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13023a

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	mg +100 Au	+100 Au	-100 Au	oz/t Au
90-R21-0-5	<0.002	<0.002	<0.002	<0.002
90-R21-5-10	<0.002	<0.002	<0.002	<0.002
90-R21-10-15	<0.002	<0.002	<0.002	<0.002
90-R21-15-20	<0.002	<0.002	<0.002	<0.002
90-R21-20-25	<0.002	<0.002	<0.002	<0.002
90-R21-25-30	<0.002	<0.002	<0.002	<0.002
90-R21-30-35	<0.002	<0.002	<0.002	<0.002
90-R21-35-40	<0.002	<0.002	<0.002	<0.002
90-R21-40-45	<0.002	<0.002	<0.002	<0.002
90-R21-45-50	<0.002	<0.002	<0.002	<0.002
90-R21-50-55	0.145	0.021	0.012	0.032
90-R21-55-60	<0.002	<0.002	<0.002	<0.002
90-R21-60-65	<0.002	<0.002	<0.002	<0.002
90-R21-65-70	<0.002	<0.002	<0.002	<0.002
90-R21-70-75	<0.002	<0.002	<0.002	<0.002
90-R21-75-80	<0.002	<0.002	<0.002	<0.002
90-R21-80-85	<0.002	<0.002	<0.002	<0.002
90-R21-85-90	<0.002	<0.002	<0.002	<0.002
90-R21-90-95	<0.002	<0.002	<0.002	<0.002
90-R21-95-100	0.015	0.003	0.016	0.019
90-R21-100-105	0.045	0.005	0.012	0.017
90-R21-105-110	<0.002	<0.002	<0.002	<0.002
90-R21-110-115	<0.002	<0.002	0.004	0.004
90-R21-115-120	<0.002	<0.002	0.005	0.005
90-R21-120-125	<0.002	<0.002	0.010	0.010
90-R21-125-130	0.002	<0.002	<0.002	<0.002
90-R21-130-135	<0.002	<0.002	<0.002	<0.002
90-R21-135-140	<0.002	<0.002	<0.002	<0.002
90-R21-140-145	<0.002	<0.002	<0.002	<0.002
90-R21-145-150	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
CERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 29,1990

Work Order # 13023

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13023b

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	mg +100 Au	+100 Au	-100 Au	oz/t Au
90-R22-0-5	<0.002	<0.002	<0.002	<0.002
90-R22-5-10	<0.002	<0.002	<0.002	<0.002
90-R22-10-15	<0.002	<0.002	<0.002	<0.002
90-R22-15-20	<0.002	<0.002	<0.002	<0.002
90-R22-20-25	<0.002	<0.002	<0.002	<0.002
90-R22-25-30	<0.002	<0.002	<0.002	<0.002
90-R22-30-35	<0.002	<0.002	<0.002	<0.002
90-R22-35-40	<0.002	<0.002	0.005	0.005
90-R22-40-45	<0.002	<0.002	0.003	0.003
90-R22-45-50	0.069	0.017	0.029	0.045
90-R22-50-55	<0.002	<0.002	0.003	0.003
90-R22-55-60	<0.002	<0.002	<0.002	<0.002
90-R22-60-65	<0.002	<0.002	0.005	0.005
90-R22-65-70	0.005	<0.002	0.007	0.008
90-R22-70-75	<0.002	<0.002	0.008	0.008
90-R22-75-80	<0.002	<0.002	0.007	0.007
90-R22-80-85	0.006	<0.002	0.008	0.008
90-R22-85-90		Missing		
90-R22-90-95	<0.002	<0.002	<0.002	<0.002
90-R22-95-100	<0.002	<0.002	0.007	0.007
90-R22-100-105	0.037	0.008	0.008	0.016
90-R22-105-110	<0.002	<0.002	0.003	0.003
90-R22-110-115	<0.002	<0.002	<0.002	<0.002
90-R22-115-120	<0.002	<0.002	<0.002	<0.002
90-R22-120-125	<0.002	<0.002	0.018	0.018
90-R22-125-130	<0.002	<0.002	<0.002	<0.002
90-R22-130-135	<0.002	<0.002	0.026	0.026
90-R22-135-140	0.006	<0.002	0.023	0.024
90-R22-140-145	<0.002	<0.002	0.003	0.003
90-R22-145-150	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
CERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 23,1990

Work Order # 13020

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13020f

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R23-0-5	0.024	0.004	0.011	0.015
90-R23-5-10	<0.002	<0.002	<0.002	<0.002
90-R23-10-15	0.003	<0.002	0.008	0.008
90-R23-15-20	<0.002	<0.002	0.008	0.008
90-R23-20-25	<0.002	<0.002	0.002	0.002
90-R23-25-30	0.643	0.161	0.101	0.258
90-R23-30-35	0.685	0.116	0.179	0.284
90-R23-35-40	0.101	0.016	0.066	0.079
90-R23-40-45	<0.002	<0.002	0.003	0.003
90-R23-45-50	<0.002	<0.002	<0.002	<0.002
90-R23-50-55	<0.002	<0.002	0.009	0.009
90-R23-55-60	0.024	0.005	0.020	0.024
90-R23-60-65	0.020	0.004	0.017	0.020
90-R23-65-70	0.054	0.011	0.012	0.022
90-R23-70-75	0.119	0.025	0.004	0.029
90-R23-75-80	<0.002	<0.002	0.007	0.007
90-R23-80-85	<0.002	<0.002	0.008	0.008
90-R23-85-90	0.026	0.004	<0.002	0.004
90-R23-90-95	0.384	0.062	0.025	0.087
90-R23-95-100	0.034	0.004	0.040	0.043
90-R23-100-105	0.018	0.003	0.034	0.036
90-R23-105-110	<0.002	<0.002	<0.002	<0.002
90-R23-110-115	0.026	0.004	0.014	0.017
90-R23-115-120	<0.002	<0.002	<0.002	<0.002
90-R23-120-125	<0.002	<0.002	<0.002	<0.002
90-R23-125-130	<0.002	<0.002	<0.002	<0.002
90-R23-130-135	<0.002	<0.002	0.003	0.003
90-R23-135-140	0.027	0.007	0.020	0.026
90-R23-140-145	0.178	0.027	0.023	0.050
90-R23-145-150	0.030	0.005	<0.002	0.005

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 29,1990

Work Order # 13023

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13023c

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	mg +100 Au	+100 Au	-100 Au	oz/t Au
90-R24-0-5	0.004	<0.002	0.006	0.006
90-R24-5-10	<0.002	<0.002	0.003	0.003
90-R24-10-15	<0.002	<0.002	<0.002	<0.002
90-R24-15-20	0.002	<0.002	0.004	0.004
90-R24-20-25	<0.002	<0.002	0.014	0.013
90-R24-25-30	<0.002	<0.002	0.006	0.006
90-R24-30-35	0.668	0.097	0.028	0.123
90-R24-35-40	0.103	0.019	0.050	0.068
90-R24-40-45	<0.002	<0.002	0.004	0.004
90-R24-45-50	<0.002	<0.002	<0.002	<0.002
90-R24-50-55	<0.002	<0.002	<0.002	<0.002
90-R24-55-60	<0.002	<0.002	<0.002	<0.002
90-R24-60-65	<0.002	<0.002	<0.002	<0.002
90-R24-65-70	<0.002	<0.002	<0.002	<0.002
90-R24-70-75	<0.002	<0.002	<0.002	<0.002
90-R24-75-80	<0.002	<0.002	0.007	0.007
90-R24-80-85	0.003	<0.002	<0.002	<0.002
90-R24-85-90	0.006	<0.002	<0.002	<0.002
90-R24-90-95	<0.002	<0.002	0.014	0.013
90-R24-95-100	<0.002	<0.002	<0.002	<0.002
90-R24-100-105	<0.002	<0.002	<0.002	<0.002
90-R24-105-110	0.004	<0.002	0.017	0.017
90-R24-110-115	<0.002	<0.002	0.002	0.002
90-R24-115-120	<0.002	<0.002	<0.002	<0.002
90-R24-120-125	<0.002	<0.002	<0.002	<0.002
90-R24-125-130	<0.002	<0.002	<0.002	<0.002
90-R24-130-135	<0.002	<0.002	<0.002	<0.002
90-R24-135-140	<0.002	<0.002	<0.002	<0.002
90-R24-140-145	<0.002	<0.002	<0.002	<0.002
90-R24-145-150	<0.002	<0.002	0.004	0.004

Au -- Metallics Fire Assay

Science Technologists and Technicians of British Columbia Applied
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 29,1990

Work Order # 13023

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13023d

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	mg +100 Au	+100 Au	-100 Au	oz/t Au
90-R24-150-155	<0.002	<0.002	<0.002	<0.002
90-R24-155-160	<0.002	<0.002	<0.002	<0.002
90-R24-160-165	<0.002	<0.002	0.006	0.006
90-R24-165-170	<0.002	<0.002	<0.002	<0.002
90-R24-170-175	<0.002	<0.002	0.003	0.003
90-R24-175-180	0.030	0.003	0.006	0.009
90-R24-180-185	<0.002	<0.002	0.004	0.004
90-R24-185-190	<0.002	<0.002	<0.002	<0.002
90-R24-190-195	<0.002	<0.002	<0.002	<0.002
90-R24-195-200	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 30,1990

Work Order # 13023

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13023e

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R25-0-5	0.0009
90-R25-5-10	0.0010
90-R25-10-15	0.0014
90-R25-15-20	0.0018
90-R25-20-25	0.0009
90-R25-25-30	0.0011
90-R25-30-35	0.0005
90-R25-35-40	0.0003
90-R25-40-45	0.0008
90-R25-45-50	0.0002
90-R25-50-55	0.0011
90-R25-55-60	0.0007
90-R25-60-65	0.0004
90-R25-65-70	0.0005
90-R25-70-75	0.0006
90-R25-75-80	0.0003
90-R25-80-85	0.0010
90-R25-85-90	0.0011
90-R25-90-95	0.0009
90-R25-95-100	0.0010
90-R25-100-105	0.0003
90-R25-105-110	0.0004
90-R25-110-115	0.0005
90-R25-115-120	<0.0002
90-R25-120-125	<0.0002
90-R25-125-130	<0.0002
90-R25-130-135	<0.0002
90-R25-135-140	<0.0002
90-R25-140-145	<0.0002
90-R25-145-150	<0.0002
90-R25-150-155	<0.0002
90-R25-155-160	0.0006

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 30,1990

Work Order # 13023

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3


File # 13023f

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R26-0-5	<0.0002
90-R26-5-10	<0.0002
90-R26-10-15	<0.0002
90-R26-15-20	0.0002
90-R26-20-25	<0.0002
90-R26-25-30	0.0002
90-R26-30-35	0.0002
90-R26-35-40	0.0003
90-R26-40-45	<0.0002
90-R26-45-50	<0.0002
90-R26-50-55	<0.0002
90-R26-55-60	<0.0002
90-R26-60-65	<0.0002
90-R26-65-70	<0.0002
90-R26-70-75	<0.0002
90-R26-75-80	<0.0002
90-R26-80-85	<0.0002
90-R26-85-90	0.0004
90-R26-90-95	<0.0002
90-R26-95-100	<0.0002
90-R26-100-105	<0.0002
90-R26-105-110	0.0022
90-R26-110-115	<0.0002
90-R26-115-120	<0.0002
90-R26-120-125	<0.0002
90-R26-125-130	0.0015
90-R26-130-135	0.0006
90-R26-135-140	<0.0002
90-R26-140-145	<0.0002
90-R26-145-150	<0.0002

Au -- 1AT Fire Assay/AAS



105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 30,1990

Work Order # 13023

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3


File # 13023g

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R26-150-155	<0.0002
90-R26-155-160	<0.0002
90-R26-160-165	<0.0002
90-R26-165-170	0.0010
90-R26-170-175	<0.0002
90-R26-175-180	<0.0002
90-R26-180-185	<0.0002
90-R26-185-190	<0.0002
90-R26-190-195	<0.0002
90-R26-195-200	<0.0002
90-R26-200-205	<0.0002
90-R26-205-210	0.0005
90-R26-210-215	<0.0002
90-R26-215-220	<0.0002
90-R26-220-225	<0.0002
90-R26-225-230	<0.0002
90-R26-230-235	<0.0002
90-R26-235-240	<0.0002
90-R26-240-245	<0.0002
90-R26-245-250	0.0003
90-R26-250-255	<0.0002
90-R26-255-260	<0.0002
90-R26-260-265	<0.0002
90-R26-265-270	<0.0002
90-R26-270-275	<0.0002
90-R26-275-280	<0.0002
90-R26-280-285	<0.0002
90-R26-285-290	<0.0002
90-R26-290-295	0.0002
90-R26-295-300	<0.0002

Au -- 1AT Fire Assay/AAS



105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 3,1990

Work Order # 13024

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3


File # 13024a

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R27-0-5	0.0008
90-R27-5-10	<0.0002
90-R27-10-15	<0.0002
90-R27-15-20	<0.0002
90-R27-20-25	<0.0002
90-R27-25-30	<0.0002
90-R27-30-35	<0.0002
90-R27-35-40	<0.0002
90-R27-40-45	0.0002
90-R27-45-50	0.0002
90-R27-50-55	0.0005
90-R27-55-60	0.0008
90-R27-60-65	0.0003
90-R27-65-70	0.0007
90-R27-70-75	<0.0002
90-R27-75-80	<0.0002
90-R27-80-85	<0.0002
90-R27-85-90	<0.0002
90-R27-90-95	<0.0002
90-R27-95-100	<0.0002
90-R27-100-105	0.0003
90-R27-105-110	<0.0002
90-R27-110-115	<0.0002
90-R27-115-120	<0.0002
90-R27-120-125	<0.0002
90-R27-125-130	<0.0002
90-R27-130-135	<0.0002
90-R27-135-140	<0.0002
90-R27-140-145	<0.0002
90-R27-145-150	<0.0002

Au -- 1AT Fire Assay/AAS



105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: [403] 668-4968 Fax: [403] 668-4890

Northern Analytical Laboratories ltd.

December 3,1990

Work Order # 13024

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13024b

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R27-150-155	0.0005
90-R27-155-160	<0.0002
90-R27-160-165	<0.0002
90-R27-165-170	<0.0002
90-R27-170-175	<0.0002
90-R27-175-180	<0.0002
90-R27-180-185	<0.0002
90-R27-185-190	<0.0002
90-R27-190-195	<0.0002
90-R27-195-200	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 3,1990

Work Order # 13024

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13024c

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R28-0-5	<0.0002
90-R28-5-10	<0.0002
90-R28-10-15	<0.0002
90-R28-15-20	<0.0002
90-R28-20-25	0.0149
90-R28-25-30	<0.0002
90-R28-30-35	<0.0002
90-R28-35-40	<0.0002
90-R28-40-45	<0.0002
90-R28-45-50	<0.0002
90-R28-50-55	<0.0002
90-R28-55-60	0.0072
90-R28-60-65	<0.0002
90-R28-65-70	<0.0002
90-R28-70-75	<0.0002
90-R28-75-80	<0.0002
90-R28-80-85	<0.0002
90-R28-85-90	<0.0002
90-R28-90-95	<0.0002
90-R28-95-100	<0.0002
90-R28-100-105	<0.0002
90-R28-105-110	<0.0002
90-R28-110-115	<0.0002
90-R28-115-120	<0.0002
90-R28-120-125	<0.0002
90-R28-125-130	<0.0002
90-R28-130-135	<0.0002
90-R28-135-140	<0.0002
90-R28-140-145	<0.0002
90-R28-145-150	0.0018

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 3,1990

Work Order # 13024

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13024d

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R28-150-155	<0.0002
90-R28-155-160	0.0002
90-R28-160-165	0.0002
90-R28-165-170	0.0004
90-R28-170-175	<0.0002
90-R28-175-180	<0.0002
90-R28-180-185	0.0004
90-R28-185-190	0.0005
90-R28-190-195	<0.0002
90-R28-195-200	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
0992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 5,1990

Work Order # 13032

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13032a

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R29-0-5	0.0023
90-R29-5-10	0.0009
90-R29-10-15	<0.0002
90-R29-15-20	<0.0002
90-R29-20-25	<0.0002
90-R29-25-30	<0.0002
90-R29-30-35	0.0008
90-R29-35-40	<0.0002
90-R29-40-45	0.0004
90-R29-45-50	<0.0002
90-R29-50-55	<0.0002
90-R29-55-60	0.0009
90-R29-60-65	0.0006
90-R29-65-70	0.0006
90-R29-70-75	0.0005
90-R29-75-80	0.0027
90-R29-80-85	0.0012
90-R29-85-90	0.0008
90-R29-90-95	0.0010
90-R29-95-100	0.0011
90-R29-100-105	0.0014
90-R29-105-110	0.0004
90-R29-110-115	<0.0002
90-R29-115-120	0.0104
90-R29-120-125	0.0012
90-R29-125-130	<0.0002
90-R29-130-135	<0.0002
90-R29-135-140	<0.0002
90-R29-140-145	0.0002
90-R29-145-150	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 4,1990

Work Order # 13032

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13032b

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R29-150-155	0.0006
90-R29-155-160	0.0005
90-R29-160-165	0.0091
90-R29-165-170	0.0054
90-R29-170-175	<0.0002
90-R29-175-180	<0.0002
90-R29-180-185	<0.0002
90-R29-185-190	0.0009
90-R29-190-195	<0.0002
90-R29-195-200	0.0055
90-R29-200-205	0.0090
90-R29-205-210	0.0024
90-R29-210-215	0.0026
90-R29-215-220	0.0011
90-R29-220-225	0.0065
90-R29-225-230	0.0006
90-R29-230-235	<0.0002
90-R29-235-240	<0.0002
90-R29-240-245	<0.0002
90-R29-245-250	<0.0002
90-R29-250-255	0.0009
90-R29-255-260	<0.0002
90-R29-260-265	<0.0002
90-R29-265-270	0.0014
90-R29-270-275	<0.0002
90-R29-275-280	<0.0002
90-R29-280-285	0.0016
90-R29-285-290	<0.0002
90-R29-290-295	<0.0002
90-R29-295-300	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
CERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 5,1990

Work Order # 13032

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3


File # 13032c

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R29-300-305	0.0040
90-R29-305-310	0.0011
90-R29-310-315	0.0005
90-R29-315-320	0.0110
90-R29-320-325	0.0010
90-R29-325-330	0.0036
90-R29-330-335	0.0024
90-R29-335-340	0.0004
90-R29-340-345	0.0008
90-R29-345-350	0.0007
90-R29-350-355	0.0006
90-R29-355-360	0.0002
90-R29-360-365	<0.0002
90-R29-365-370	0.0008
90-R29-370-375	0.0005
90-R29-375-380	0.0004
90-R29-380-385	0.0003
90-R29-385-390	<0.0002
90-R29-390-395	<0.0002
90-R29-395-400	0.0006
90-R29-400-405	<0.0002
90-R29-405-410	<0.0002
90-R29-410-415	<0.0002
90-R29-415-420	<0.0002
90-R29-420-425	0.0004
90-R29-425-430	0.0005
90-R29-430-435	<0.0002
90-R29-435-440	0.0009
90-R29-440-445	0.0216
90-R29-445-450	0.0064

Au -- 1AT Fire Assay/AAS



105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 3,1990

Work Order # 13024

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13024e

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R30-0-5	<0.0002
90-R30-5-10	<0.0002
90-R30-10-15	<0.0002
90-R30-15-20	<0.0002
90-R30-20-25	<0.0002
90-R30-25-30	<0.0002
90-R30-30-35	0.0002
90-R30-35-40	<0.0002
90-R30-40-45	<0.0002
90-R30-45-50	0.0083
90-R30-50-55	<0.0002
90-R30-55-60	0.0008
90-R30-60-65	0.0004
90-R30-65-70	<0.0002
90-R30-70-75	<0.0002
90-R30-75-80	<0.0002
90-R30-80-85	0.0002
90-R30-85-90	<0.0002
90-R30-90-95	0.0010
90-R30-95-100	<0.0002
90-R30-100-105	<0.0002
90-R30-105-110	<0.0002
90-R30-110-115	<0.0002
90-R30-115-120	<0.0002
90-R30-120-125	<0.0002
90-R30-125-130	<0.0002
90-R30-130-135	0.0012
90-R30-135-140	0.0014
90-R30-140-145	0.0015
90-R30-145-150	0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 3,1990

Work Order # 13024

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13024f

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R30-150-155	0.0239
90-R30-155-160	0.0005
90-R30-160-165	0.0007
90-R30-165-170	0.0031
90-R30-170-175	0.0010
90-R30-175-180	<0.0002
90-R30-180-185	0.0094
90-R30-185-190	<0.0002
90-R30-190-195	0.0003
90-R30-195-200	<0.0002
90-R30-200-205	0.0012
90-R30-205-210	0.0146
90-R30-210-215	0.0003
90-R30-215-220	<0.0002
90-R30-220-225	0.0003
90-R30-225-230	0.0004
90-R30-230-235	<0.0002
90-R30-235-240	0.0009
90-R30-240-245	<0.0002
90-R30-245-250	0.0002
90-R30-250-255	<0.0002
90-R30-255-260	0.0002
90-R30-260-265	0.0350
90-R30-265-270	0.0004
90-R30-270-275	0.0006
90-R30-275-280	0.0005
90-R30-280-285	0.0003
90-R30-285-290	<0.0002
90-R30-290-295	0.0003
90-R30-295-300	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: [403] 668-4968 Fax: [403] 668-4890

Northern Analytical Laboratories ltd.

December 3,1990

Work Order # 13024

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13024g

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R30-300-305	<0.0002
90-R30-305-310	0.0004
90-R30-310-315	0.0004
90-R30-315-320	0.0003
90-R30-320-325	0.0068
90-R30-325-330	0.0010
90-R30-330-335	0.0047
90-R30-335-340	0.0007
90-R30-340-345	0.0008
90-R30-345-350	0.0005
90-R30-350-355	0.0023
90-R30-355-360	0.0103
90-R30-360-365	0.0210
90-R30-365-370	0.0183
90-R30-370-375	0.0009
90-R30-375-380	0.0012
90-R30-380-385	0.0005
90-R30-385-390	0.0003
90-R30-390-395	<0.0002
90-R30-395-400	<0.0002
90-R30-400-405	<0.0002
90-R30-405-410	0.0035
90-R30-410-415	0.0007
90-R30-415-420	0.0005
90-R30-420-425	<0.0002
90-R30-425-430	<0.0002
90-R30-430-435	0.0004
90-R30-435-440	<0.0002
90-R30-440-445	0.0011
90-R30-445-450	0.0160

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
CERALD R. NAVES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 3,1990

Work Order # 13024

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13024h

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R30-450-455	0.0364
90-R30-455-460	0.0077
90-R30-460-465	0.0016
90-R30-465-470	0.0037
90-R30-470-475	0.0008
90-R30-475-480	0.0019
90-R30-480-485	0.0005
90-R30-485-490	0.0004

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 7,1990

Work Order # 13032

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13032d

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R31-0-5	0.0004
90-R31-5-10	<0.0002
90-R31-10-15	0.0003
90-R31-15-20	<0.0002
90-R31-20-25	0.0002
90-R31-25-30	0.0002
90-R31-30-35	<0.0002
90-R31-35-40	<0.0002
90-R31-40-45	<0.0002
90-R31-45-50	<0.0002
90-R31-50-55	<0.0002
90-R31-55-60	0.0005
90-R31-60-65	<0.0002
90-R31-65-70	<0.0002
90-R31-70-75	<0.0002
90-R31-75-80	<0.0002
90-R31-80-85	<0.0002
90-R31-85-90	<0.0002
90-R31-90-95	<0.0002
90-R31-95-100	<0.0002
90-R31-100-105	<0.0002
90-R31-105-110	<0.0002
90-R31-110-115	<0.0002
90-R31-115-120	<0.0002
90-R31-120-125	<0.0002
90-R31-125-130	<0.0002
90-R31-130-135	<0.0002
90-R31-135-140	<0.0002
90-R31-140-145	<0.0002
90-R31-145-150	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 4,1990

Work Order # 13032

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13032e

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R31-150-155	<0.0002
90-R31-155-160	<0.0002
90-R31-160-165	<0.0002
90-R31-165-170	<0.0002
90-R31-170-175	<0.0002
90-R31-175-180	<0.0002
90-R31-180-185	<0.0002
90-R31-185-190	<0.0002
90-R31-190-195	<0.0002
90-R31-195-200	<0.0002
90-R31-200-205	<0.0002
90-R31-205-210	<0.0002
90-R31-210-215	<0.0002
90-R31-215-220	<0.0002
90-R31-220-225	<0.0002
90-R31-225-230	<0.0002
90-R31-230-235	<0.0002
90-R31-235-240	<0.0002
90-R31-240-245	<0.0002
90-R31-245-250	<0.0002
90-R31-250-255	0.0002
90-R31-255-260	<0.0002
90-R31-260-265	0.0004
90-R31-265-270	0.0002
90-R31-270-275	<0.0002
90-R31-275-280	0.0003
90-R31-280-285	0.0002
90-R31-285-290	0.0004
90-R31-290-295	<0.0002
90-R31-295-300	0.0009

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
CERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 6,1990

Work Order # 13032

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13032f

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R32-0-5	0.0006
90-R32-5-10	0.0020
90-R32-10-15	0.0005
90-R32-15-20	0.0009
90-R32-20-25	0.0005
90-R32-25-30	0.0004
90-R32-30-35	0.0004
90-R32-35-40	<0.0002
90-R32-40-45	0.0003
90-R32-45-50	0.0003
90-R32-50-55	0.1236
90-R32-55-60	0.0143
90-R32-60-65	0.0010
90-R32-65-70	0.0011
90-R32-70-75	0.0003
90-R32-75-80	0.0011
90-R32-80-85	0.0004
90-R32-85-90	0.0004
90-R32-90-95	0.0003
90-R32-95-100	0.0004

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 6,1990

Work Order # 13035

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13035a

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R33-0-5	0.0008
90-R33-5-10	<0.0002
90-R33-10-15	<0.0002
90-R33-15-20	<0.0002
90-R33-20-25	<0.0002
90-R33-25-30	<0.0002
90-R33-30-35	<0.0002
90-R33-35-40	<0.0002
90-R33-40-45	0.0003
90-R33-45-50	0.0010
90-R33-50-55	<0.0002
90-R33-55-60	0.0002
90-R33-60-65	<0.0002
90-R33-65-70	<0.0002
90-R33-70-75	<0.0002
90-R33-75-80	0.0006
90-R33-80-85	0.0002
90-R33-85-90	<0.0002
90-R33-90-95	<0.0002
90-R33-95-100	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: [403] 668-4968 Fax: [403] 668-4890

Northern Analytical Laboratories ltd.

December 6,1990

Work Order # 13032

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13032g

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R34-0-5	0.0007
90-R34-5-10	0.0158
90-R34-10-15	0.0006
90-R34-15-20	0.0005
90-R34-20-25	0.0006
90-R34-25-30	0.0011
90-R34-30-35	0.0005
90-R34-35-40	0.0006
90-R34-40-45	0.0006
90-R34-45-50	0.0006
90-R34-50-55	0.0002
90-R34-55-60	<0.0002
90-R34-60-65	<0.0002
90-R34-65-70	0.0007
90-R34-70-75	0.0031
90-R34-75-80	0.0181
90-R34-80-85	0.0002
90-R34-85-90	<0.0002
90-R34-90-95	<0.0002
90-R34-95-100	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 10,1990

Work Order # 13035

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3


File # 13035b

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R35-0-5	0.0202
90-R35-5-10	0.0099
90-R35-10-15	0.0903
90-R35-15-20	0.0138
90-R35-20-25	0.0031
90-R35-25-30	<0.0002
90-R35-30-35	0.0046
90-R35-35-40	0.0007
90-R35-40-45	0.0094
90-R35-45-50	0.0015
90-R35-50-55	0.0004
90-R35-55-60	<0.0002
90-R35-60-65	<0.0002
90-R35-65-70	0.0007
90-R35-70-75	0.0002
90-R35-75-80	0.0003
90-R35-80-85	<0.0002
90-R35-85-90	0.0002
90-R35-90-95	0.0003
90-R35-95-100	0.0004

Au -- 1AT Fire Assay/AAS



105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 5,1990

Work Order # 13032

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13032h

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R36-0-5	<0.0002
90-R36-5-10	0.0066
90-R36-10-15	<0.0002
90-R36-15-20	0.0036
90-R36-20-25	<0.0002
90-R36-25-30	0.0018
90-R36-30-35	0.0005
90-R36-35-40	0.0004
90-R36-40-45	0.0002
90-R36-45-50	0.0015
90-R36-50-55	0.0002
90-R36-55-60	0.0004
90-R36-60-65	<0.0002
90-R36-65-70	0.0005
90-R36-70-75	<0.0002
90-R36-75-80	<0.0002
90-R36-80-85	<0.0002
90-R36-85-90	<0.0002
90-R36-90-95	<0.0002
90-R36-95-100	<0.0002
90-R36-100-105	<0.0002
90-R36-105-110	<0.0002
90-R36-110-115	<0.0002
90-R36-115-120	<0.0002
90-R36-120-125	<0.0002
90-R36-125-130	0.0002
90-R36-130-135	<0.0002
90-R36-135-140	<0.0002
90-R36-140-145	0.0003
90-R36-145-150	0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: [403] 668-4968 Fax: [403] 668-4890

Northern Analytical Laboratories ltd.

December 4,1990

Work Order # 13032

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3


File # 13032i

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R36-150-155	<0.0002
90-R36-155-160	<0.0002
90-R36-160-165	<0.0002
90-R36-165-170	<0.0002
90-R36-170-175	<0.0002
90-R36-175-180	0.0002
90-R36-180-185	<0.0002
90-R36-185-190	0.0007
90-R36-190-195	<0.0002
90-R36-195-200	<0.0002
90-R36-200-205	<0.0002
90-R36-205-210	<0.0002
90-R36-210-215	<0.0002
90-R36-215-220	<0.0002
90-R36-220-225	<0.0002
90-R36-225-230	<0.0002
90-R36-230-235	<0.0002
90-R36-235-240	<0.0002
90-R36-240-245	<0.0002
90-R36-245-250	<0.0002
90-R36-250-255	<0.0002
90-R36-255-260	0.0029
90-R36-260-265	<0.0002
90-R36-265-270	<0.0002
90-R36-270-275	0.0006
90-R36-275-280	<0.0002
90-R36-280-285	<0.0002
90-R36-285-290	<0.0002
90-R36-290-295	0.0011
90-R36-295-300	0.0035

Au -- 1AT Fire Assay/AAS



105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 6,1990

Work Order # 13032

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13032j

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R36-300-305	0.0070
90-R36-305-310	0.0003
90-R36-310-315	0.0003
90-R36-315-320	0.0004
90-R36-320-325	0.0004
90-R36-325-330	0.0005
90-R36-330-335	0.0004
90-R36-335-340	0.0003
90-R36-340-345	0.0004
90-R36-345-350	0.0006
90-R36-350-355	0.0002
90-R36-355-360	<0.0002
90-R36-360-365	<0.0002
90-R36-365-370	<0.0002
90-R36-370-375	0.0003
90-R36-375-380	0.0002
90-R36-380-385	<0.0002
90-R36-385-390	<0.0002
90-R36-390-395	<0.0002
90-R36-395-400	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 12,1990

Work Order # 13035

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13035c

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R37-0-5	<0.0002
90-R37-5-10	<0.0002
90-R37-10-15	<0.0002
90-R37-15-20	<0.0002
90-R37-20-25	<0.0002
90-R37-25-30	<0.0002
90-R37-30-35	<0.0002
90-R37-35-40	<0.0002
90-R37-40-45	0.0003
90-R37-45-50	<0.0002
90-R37-50-55	<0.0002
90-R37-55-60	<0.0002
90-R37-60-65	0.0002
90-R37-65-70	0.0002
90-R37-70-75	<0.0002
90-R37-75-80	<0.0002
90-R37-80-85	<0.0002
90-R37-85-90	0.0002
90-R37-90-95	<0.0002
90-R37-95-100	0.0002
90-R37-100-105	<0.0002
90-R37-105-110	<0.0002
90-R37-110-115	<0.0002
90-R37-115-120	<0.0002
90-R37-120-125	<0.0002
90-R37-125-130	<0.0002
90-R37-130-135	<0.0002
90-R37-135-140	<0.0002
90-R37-140-145	<0.0002
90-R37-145-150	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 12,1990

Work Order # 13035

File # 13035d

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R37-150-155	<0.0002
90-R37-155-160	<0.0002
90-R37-160-165	<0.0002
90-R37-165-170	<0.0002
90-R37-170-175	<0.0002
90-R37-175-180	0.0002
90-R37-180-185	0.0002
90-R37-185-190	<0.0002
90-R37-190-195	<0.0002
90-R37-195-200	<0.0002
90-R37-200-205	<0.0002
90-R37-205-210	<0.0002
90-R37-210-215	<0.0002
90-R37-215-220	<0.0002
90-R37-220-225	<0.0002
90-R37-225-230	<0.0002
90-R37-230-235	<0.0002
90-R37-235-240	<0.0002
90-R37-240-245	<0.0002
90-R37-245-250	<0.0002
90-R37-250-255	<0.0002
90-R37-255-260	<0.0002
90-R37-260-265	<0.0002
90-R37-265-270	0.0004
90-R37-270-275	0.0002
90-R37-275-280	<0.0002
90-R37-280-285	<0.0002
90-R37-285-290	0.0002
90-R37-290-295	0.0003
90-R37-295-300	0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 12,1990

Work Order # 13035

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13035e

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R38-0-5	0.0003
90-R38-5-10	0.0005
90-R38-10-15	0.0004
90-R38-15-20	<0.0002
90-R38-20-25	0.0003
90-R38-25-30	0.0004
90-R38-30-35	0.0005
90-R38-35-40	0.0004
90-R38-40-45	0.0002
90-R38-45-50	<0.0002
90-R38-50-55	<0.0002
90-R38-55-60	<0.0002
90-R38-60-65	<0.0002
90-R38-65-70	<0.0002
90-R38-70-75	0.0002
90-R38-75-80	0.0002
90-R38-80-85	0.0003
90-R38-85-90	0.0381
90-R38-90-95	0.0003
90-R38-95-100	0.0004
90-R38-100-105	0.0004
90-R38-105-110	<0.0002
90-R38-110-115	<0.0002
90-R38-115-120	<0.0002
90-R38-120-125	<0.0002
90-R38-125-130	<0.0002
90-R38-130-135	<0.0002
90-R38-135-140	<0.0002
90-R38-140-145	0.0002
90-R38-145-150	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 12,1990

Work Order # 13035

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13035f

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R38-150-155	0.0031
90-R38-155-160	0.0011
90-R38-160-165	0.0006
90-R38-165-170	0.0002
90-R38-170-175	<0.0002
90-R38-175-180	<0.0002
90-R38-180-185	0.0003
90-R38-185-190	0.0002
90-R38-190-195	<0.0002
90-R38-195-200	<0.0002
90-R38-200-205	0.0003
90-R38-205-210	<0.0002
90-R38-210-215	<0.0002
90-R38-215-220	0.0002
90-R38-220-225	0.0004
90-R38-225-230	0.0007
90-R38-230-235	0.0006
90-R38-235-240	0.0008
90-R38-240-245	<0.0002
90-R38-245-250	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
CERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 12,1990

Work Order # 13035

File # 13035g

Sample : Perc. Cuttings

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R39-0-5	0.0002
90-R39-5-10	0.0004
90-R39-10-15	0.0003
90-R39-15-20	0.0007
90-R39-20-25	0.0011
90-R39-25-30	0.0005
90-R39-30-35	<0.0002
90-R39-35-40	<0.0002
90-R39-40-45	<0.0002
90-R39-45-50	<0.0002
90-R39-50-55	<0.0002
90-R39-55-60	0.0004
90-R39-60-65	<0.0002
90-R39-65-70	0.0004
90-R39-70-75	0.0003
90-R39-75-80	0.0005
90-R39-80-85	0.0002
90-R39-85-90	0.0004
90-R39-90-95	0.0003
90-R39-95-100	0.0005
90-R39-100-105	0.0007
90-R39-105-110	0.0003
90-R39-110-115	0.0005
90-R39-115-120	0.0005
90-R39-120-125	0.0008
90-R39-125-130	0.0005
90-R39-130-135	0.0005
90-R39-135-140	<0.0002
90-R39-140-145	0.0004
90-R39-145-150	0.0003

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

Northern Analytical Laboratories ltd.

December 12,1990

Work Order # 13035

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13035h

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R39-150-155	0.0004
90-R39-155-160	<0.0002
90-R39-160-165	0.0004
90-R39-165-170	<0.0002
90-R39-170-175	0.0005
90-R39-175-180	0.0004
90-R39-180-185	0.0007
90-R39-185-190	0.0003
90-R39-190-195	0.0010
90-R39-195-200	0.0015
90-R39-200-205	0.0003
90-R39-205-210	0.0010
90-R39-210-215	0.0007
90-R39-215-220	0.0006
90-R39-220-225	0.0007
90-R39-225-230	<0.0002
90-R39-230-235	0.0002
90-R39-235-240	<0.0002
90-R39-240-245	0.0002
90-R39-245-250	0.0003
90-R39-250-255	0.0003
90-R39-255-260	0.0004
90-R39-260-265	<0.0002
90-R39-265-270	0.0010
90-R39-270-275	0.0014
90-R39-275-280	<0.0002
90-R39-280-285	<0.0002
90-R39-285-290	<0.0002
90-R39-290-295	<0.0002
90-R39-295-300	<0.0002

Au -- 1AT Fire Assay/AAS

Northern Analytical Laboratories ltd.

December 21,1990

Work Order # 13037

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 130371

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R45-0-5	0.0007
90-R45-5-10	<0.0002
90-R45-10-15	<0.0002
90-R45-15-20	0.0002
90-R45-20-25	0.0015
90-R45-25-30	0.0020
90-R45-30-35	0.0007
90-R45-35-40	<0.0002
90-R45-40-45	<0.0002
90-R45-45-50	0.0006
90-R45-50-55	<0.0002
90-R45-55-60	0.0030
90-R45-60-65	0.0034
90-R45-65-70	0.0008
90-R45-70-75	0.0031
90-R45-75-80	0.0036
90-R45-80-85	0.0009
90-R45-85-90	0.0007
90-R45-90-95	0.0004
90-R45-95-100	0.0004
90-R45-100-105	0.0009
90-R45-105-110	0.0010
90-R45-110-115	0.0006
90-R45-115-120	0.0004
90-R45-120-125	0.0005
90-R45-125-130	0.0003
90-R45-130-135	0.0004
90-R45-135-140	0.0009
90-R45-140-145	<0.0002
90-R45-145-150	0.0005

Au -- 1AT Fire Assay/AAS

Certified Science Technologists and Technicians of British Columbia, Applied
6992
CERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 21,1990

Work Order # 13037

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13037m

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R45-150-155	0.0004
90-R45-155-160	<0.0002
90-R45-160-165	<0.0002
90-R45-165-170	0.0005
90-R45-170-175	0.0002
90-R45-175-180	0.0004
90-R45-180-185	0.0024
90-R45-185-190	0.0004
90-R45-190-195	0.0002
90-R45-195-200	0.0004
90-R45-200-205	0.0003
90-R45-205-210	<0.0002
90-R45-210-215	0.0003
90-R45-215-220	0.0002
90-R45-220-225	0.0003
90-R45-225-230	0.0003
90-R45-230-235	<0.0002
90-R45-235-240	<0.0002
90-R45-240-245	missing
90-R45-245-250	<0.0002
90-R45-250-255	<0.0002
90-R45-255-260	<0.0002
90-R45-260-265	<0.0002
90-R45-265-270	<0.0002
90-R45-270-275	<0.0002
90-R45-275-280	<0.0002
90-R45-280-285	<0.0002
90-R45-285-290	<0.0002
90-R45-290-295	0.0002
90-R45-295-300	0.0009

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 21,1990

Work Order # 13037

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13037n

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R45-300-305	<0.0002
90-R45-305-310	<0.0002
90-R45-310-315	0.0002
90-R45-315-320	<0.0002
90-R45-320-325	<0.0002
90-R45-325-330	<0.0002
90-R45-330-335	<0.0002
90-R45-335-340	0.0002
90-R45-340-345	<0.0002
90-R45-345-350	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: [403] 668-4968 Fax: [403] 668-4890

Northern Analytical Laboratories ltd.

December 18,1990

Work Order # 13038

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3


File # 13038a

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R46-0-5	<0.0002
90-R46-5-10	<0.0002
90-R46-10-15	<0.0002
90-R46-15-20	<0.0002
90-R46-20-25	<0.0002
90-R46-25-30	<0.0002
90-R46-30-35	<0.0002
90-R46-35-40	<0.0002
90-R46-40-45	<0.0002
90-R46-45-50	<0.0002
90-R46-50-55	0.0003
90-R46-55-60	<0.0002
90-R46-60-65	<0.0002
90-R46-65-70	<0.0002
90-R46-70-75	<0.0002
90-R46-75-80	<0.0002
90-R46-80-85	<0.0002
90-R46-85-90	0.0009
90-R46-90-95	<0.0002
90-R46-95-100	<0.0002
90-R46-100-105	<0.0002
90-R46-105-110	<0.0002
90-R46-110-115	<0.0002
90-R46-115-120	0.0003
90-R46-120-125	<0.0002
90-R46-125-130	<0.0002
90-R46-130-135	<0.0002
90-R46-135-140	<0.0002
90-R46-140-145	<0.0002
90-R46-145-150	<0.0002

Au -- 1AT Fire Assay/AAS



105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 18,1990

Work Order # 13038

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3


File # 13038b

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R46-150-155	<0.0002
90-R46-155-160	<0.0002
90-R46-160-165	<0.0002
90-R46-165-170	<0.0002
90-R46-170-175	<0.0002
90-R46-175-180	0.0002
90-R46-180-185	<0.0002
90-R46-185-190	0.0004
90-R46-190-195	<0.0002
90-R46-195-200	0.0007
90-R46-200-205	<0.0002
90-R46-205-210	<0.0002
90-R46-210-215	<0.0002
90-R46-215-220	<0.0002
90-R46-220-225	<0.0002
90-R46-225-230	<0.0002
90-R46-230-235	<0.0002
90-R46-235-240	<0.0002
90-R46-240-245	<0.0002
90-R46-245-250	<0.0002
90-R46-250-255	0.0008
90-R46-255-260	<0.0002
90-R46-260-265	<0.0002
90-R46-265-270	<0.0002
90-R46-270-275	<0.0002
90-R46-275-280	<0.0002
90-R46-280-285	0.0010
90-R46-285-290	<0.0002
90-R46-290-295	<0.0002
90-R46-295-300	<0.0002

Au -- 1AT Fire Assay/AAS



105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 19,1990

Work Order # 13038

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13038c

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R46-300-305	<0.0002
90-R46-305-310	<0.0002
90-R46-310-315	<0.0002
90-R46-315-320	0.0058
90-R46-320-325	<0.0002
90-R46-325-330	<0.0002
90-R46-330-335	<0.0002
90-R46-335-340	<0.0002
90-R46-340-345	<0.0002
90-R46-345-350	<0.0002
90-R46-350-355	<0.0002
90-R46-355-360	<0.0002
90-R46-360-365	<0.0002
90-R46-365-370	<0.0002
90-R46-370-375	<0.0002
90-R46-375-380	<0.0002
90-R46-380-385	<0.0002
90-R46-385-390	0.0004
90-R46-390-395	<0.0002
90-R46-395-400	<0.0002
90-R46-400-405	<0.0002
90-R46-405-410	<0.0002
90-R46-410-415	<0.0002
90-R46-415-420	<0.0002
90-R46-420-425	0.0024
90-R46-425-430	0.0015
90-R46-430-435	<0.0002
90-R46-435-440	0.0003
90-R46-440-445	<0.0002
90-R46-445-450	0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
CERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 19,1990

Work Order # 13038

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13038d

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R46-450-455	0.0004
90-R46-455-460	0.0014
90-R46-460-465	0.0049
90-R46-465-470	0.0005
90-R46-470-475	0.0007
90-R46-475-480	0.0027
90-R46-480-485	<0.0002
90-R46-485-490	<0.0002
90-R46-490-495	<0.0002
90-R46-495-500	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 19,1990

Work Order # 13038

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13038e

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R47-0-5	<0.0002
90-R47-5-10	<0.0002
90-R47-10-15	<0.0002
90-R47-15-20	<0.0002
90-R47-20-25	<0.0002
90-R47-25-30	<0.0002
90-R47-30-35	<0.0002
90-R47-35-40	<0.0002
90-R47-40-45	<0.0002
90-R47-45-50	<0.0002
90-R47-50-55	<0.0002
90-R47-55-60	0.0004
90-R47-60-65	0.0002
90-R47-65-70	<0.0002
90-R47-70-75	<0.0002
90-R47-75-80	<0.0002
90-R47-80-85	0.0003
90-R47-85-90	<0.0002
90-R47-90-95	0.0003
90-R47-95-100	<0.0002
90-R47-100-105	<0.0002
90-R47-105-110	0.0008
90-R47-110-115	<0.0002
90-R47-115-120	<0.0002
90-R47-120-125	<0.0002
90-R47-125-130	<0.0002
90-R47-130-135	<0.0002
90-R47-135-140	<0.0002
90-R47-140-145	0.0004
90-R47-145-150	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
CERALD F. HAYES
A. Sc. T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 19,1990

Work Order # 13038

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13038f

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R47-150-155	<0.0002
90-R47-155-160	<0.0002
90-R47-160-165	<0.0002
90-R47-165-170	<0.0002
90-R47-170-175	0.0004
90-R47-175-180	0.0024
90-R47-180-185	0.0075
90-R47-185-190	0.0011
90-R47-190-195	<0.0002
90-R47-195-200	<0.0002
90-R47-200-205	0.0128
90-R47-205-210	0.0391
90-R47-210-215	0.0170
90-R47-215-220	0.0068
90-R47-220-225	0.0180
90-R47-225-230	0.0392
90-R47-230-235	0.0239
90-R47-235-240	0.0011
90-R47-240-245	0.0033
90-R47-245-250	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 19,19901

Work Order # 13038

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13038g

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R48-0-5	<0.0002
90-R48-5-10	<0.0002
90-R48-10-15	<0.0002
90-R48-15-20	<0.0002
90-R48-20-25	<0.0002
90-R48-25-30	<0.0002
90-R48-30-35	<0.0002
90-R48-35-40	<0.0002
90-R48-40-45	<0.0002
90-R48-45-50	<0.0002
90-R48-50-55	<0.0002
90-R48-55-60	<0.0002
90-R48-60-65	<0.0002
90-R48-65-70	<0.0002
90-R48-70-75	0.0002
90-R48-75-80	<0.0002
90-R48-80-85	<0.0002
90-R48-85-90	<0.0002
90-R48-90-95	<0.0002
90-R48-95-100	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 19,1990

Work Order # 13038

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13038h

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R49-0-5	<0.0002
90-R49-5-10	<0.0002
90-R49-10-15	<0.0002
90-R49-15-20	<0.0002
90-R49-20-25	<0.0002
90-R49-25-30	<0.0002
90-R49-30-35	<0.0002
90-R49-35-40	<0.0002
90-R49-40-45	<0.0002
90-R49-45-50	<0.0002
90-R49-50-55	<0.0002
90-R49-55-60	0.0002
90-R49-60-65	<0.0002
90-R49-65-70	<0.0002
90-R49-70-75	<0.0002
90-R49-75-80	<0.0002
90-R49-80-85	<0.0002
90-R49-85-90	<0.0002
90-R49-90-95	<0.0002
90-R49-95-100	<0.0002

Au -- 1AT Fire Assay/AAS

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 20,1990

Work Order # 13038

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3


File # 13038i

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	oz/t Au
90-R50-0-5	<0.0002
90-R50-5-10	<0.0002
90-R50-10-15	<0.0002
90-R50-15-20	0.0004
90-R50-20-25	0.0005
90-R50-25-30	0.0003
90-R50-30-35	0.0002
90-R50-35-40	0.0004
90-R50-40-45	0.0004
90-R50-45-50	0.0006
90-R50-50-55	<0.0002
90-R50-55-60	<0.0002
90-R50-60-65	<0.0002
90-R50-65-70	<0.0002
90-R50-70-75	0.0002
90-R50-75-80	<0.0002
90-R50-80-85	0.0004
90-R50-85-90	0.0003
90-R50-90-95	0.0003
90-R50-95-100	0.0004
90-R50-100-105	0.0002
90-R50-105-110	0.0004
90-R50-110-115	0.0004

Au -- 1AT Fire Assay/AAS



105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 5,1990

Work Order # 08495

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.

File # 08495e

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	mg +100 Au	+100 Au	-100 Au	oz/t Au
90-R2-20-25	<0.002	<0.002	0.035	0.032
90-R2-30-35	0.003	<0.002	<0.002	<0.002
90-R2-35-40	<0.002	<0.002	0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 7,1990

Work Order # 13006

File # 13006d

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	mg +100 Au	+100 Au	-100 Au	oz/t Au
90-R7-35-40	<0.002	<0.002	<0.002	<0.002
90-R7-70-75	<0.002	<0.002	0.005	0.005

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

November 16,1990

Work Order # 13009

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13009h

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	+100 wt	+100 Au	-100 Au	oz/t Au
90-R7-155-160	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
GERALD F. [illegible]
A.Sc.T

Northern Analytical Laboratories ltd.

December 3,1990

Work Order # 13024

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13024i

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	mg +100 Au	+100 Au	-100 Au	oz/t Au
90-R28-20-25	<0.002	<0.002	<0.002	<0.002
90-R30-150-155	<0.002	<0.002	0.005	0.005
90-R30-205-210	<0.002	<0.002	<0.002	<0.002
90-R30-260-265	<0.002	<0.002	<0.002	<0.002
90-R30-355-360	0.431	0.052	0.034	0.085
90-R30-360-365	0.373	0.060	0.016	0.076
90-R30-365-370	<0.002	<0.002	0.008	0.008
90-R30-445-450	<0.002	<0.002	0.012	0.012
90-R30-450-455	0.015	0.002	0.025	0.027

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 13,1990

Work Order # 13032

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13032k

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	mg +100 Au	+100 Au	-100 Au	oz/t Au
90-R29-115-120	0.093	0.015	0.008	0.022
90-R29-315-320	0.002	<0.002	0.007	0.007
90-R29-440-445	<0.002	<0.002	<0.002	<0.002
90-R29-445-450	<0.002	<0.002	<0.002	<0.002
90-R32-50-55	0.304	0.046	0.105	0.142
90-R32-55-60	0.120	0.027	0.030	0.055
90-R34-5-10	0.008	<0.002	0.017	0.017
90-R34-75-80	<0.002	<0.002	<0.002	<0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 21,1990

Work Order # 13035

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13035i

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	mg +100 Au	+100 Au	-100 Au	oz/t Au
90-R35-0-5	0.376	0.082	0.047	0.124
90-R35-5-10	0.132	0.025	0.016	0.039
90-R35-10-15	0.807	0.150	0.084	0.227
90-R35-15-20	<0.002	<0.002	0.015	0.014
90-R38-85-90	<0.002	<0.002	0.002	0.002

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

Northern Analytical Laboratories ltd.

December 21,1990

Work Order # 13038

Arbor Resources
1000 - 675 W. Hastings St.
Vancouver, B.C.
V6E 2K3

File # 13038j

Sample : Perc. Cuttings

Assay Certificate for Samples Provided

Sample	mg +100 Au	+100 Au	-100 Au	oz/t Au
90-R47-200-205	0.002	<0.002	0.012	0.012
90-R47-205-210	0.002	<0.002	0.051	0.050
90-R47-210-215	0.011	0.002	0.028	0.029
90-R47-215-220	0.010	0.002	0.013	0.014
90-R47-220-225	0.011	0.002	0.028	0.028
90-R47-225-230	0.039	0.007	0.026	0.033
90-R47-230-235	0.013	0.002	0.030	0.031

Au -- Metallics Fire Assay

Applied Science Technologists and Technicians of British Columbia
6992
GERALD F. HAYES
A.Sc.T.

105 Copper Road, Whitehorse, YT, Y1A 2Z7 Ph: (403) 668-4968 Fax: (403) 668-4890

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#08495 File # 90-5731

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R1 0-5	3	17	39	53	.2	6	4	186	1.13	14	5	ND	13	18	.2	3	2	6	.17	.036	23	28	.47	251	.03	4	.65	.02	.23	1
90R1 5-10	2	24	46	66	.3	6	4	167	1.02	4	5	ND	14	16	.2	2	2	4	.16	.035	17	20	.70	195	.04	4	.68	.01	.30	1
90R1 10-15	3	15	39	62	.2	7	4	220	1.11	6	5	ND	15	18	.2	3	2	4	.14	.033	16	30	.83	370	.05	3	.80	.02	.41	1
90R1 15-20	2	14	37	52	.2	5	4	284	1.00	2	5	ND	13	52	.2	2	2	3	.47	.031	12	22	.73	355	.04	5	.69	.01	.39	2
90R1 20-25	2	15	27	42	.2	5	5	406	.77	8	5	ND	14	123	.2	2	2	2	1.02	.036	12	25	.44	728	.02	5	.53	.01	.32	2
90R1 25-30	2	9	33	38	.5	4	4	332	.81	3	5	ND	15	62	.3	2	2	2	.59	.035	14	24	.37	211	.01	4	.51	.01	.25	1
90R1 30-35	6	40	70	56	.4	5	4	332	.81	5	5	ND	12	12	.3	2	2	2	.11	.020	19	61	.31	210	.01	2	.45	.01	.22	1
90R1 35-40	2	22	42	89	.6	4	4	390	.98	9	5	ND	15	14	.4	2	2	2	.14	.035	19	16	.56	215	.01	4	.66	.01	.24	1
90R1 40-45	3	15	31	49	1.0	4	4	282	.86	2	5	ND	12	52	.2	2	2	2	.39	.029	14	34	.46	155	.01	4	.49	.01	.21	1
90R1 45-50	2	16	52	56	.4	4	5	250	.92	6	5	ND	13	90	.2	2	2	2	.58	.031	13	20	.65	359	.01	2	.59	.01	.28	1
90R1 50-55	3	8	30	42	.2	4	5	267	.81	2	5	ND	14	101	.2	2	2	3	.56	.032	14	40	.59	996	.02	5	.64	.01	.32	1
90R1 55-60	4	13	45	52	.3	4	4	245	.92	4	5	ND	14	34	.2	2	2	3	.25	.033	14	32	.64	283	.02	3	.67	.01	.31	1
90R1 60-65	2	20	51	63	.2	6	4	348	1.05	5	5	ND	15	24	.2	2	2	3	.18	.034	18	18	.65	223	.02	3	.67	.01	.24	1
90R1 65-70	2	11	36	62	.3	3	3	311	.82	2	5	ND	14	27	.2	2	2	2	.19	.031	20	18	.48	181	.01	3	.57	.02	.24	1
90R1 70-75	3	11	39	66	.3	4	4	219	.81	2	5	ND	14	25	.2	2	2	2	.19	.030	20	34	.37	176	.02	3	.55	.02	.27	1
90R1 75-80	1	7	27	34	.2	3	2	173	.69	3	5	ND	16	13	.2	2	2	3	.09	.027	34	17	.30	112	.01	3	.45	.01	.16	1
90R1 80-85	2	10	31	43	.1	4	3	248	1.04	4	5	ND	17	42	.2	2	2	4	.30	.034	40	21	.42	138	.02	3	.61	.02	.26	1
90R1 85-90	1	14	26	57	.1	6	5	298	1.49	26	5	ND	16	21	.2	2	2	8	.18	.041	39	22	.60	145	.03	4	.81	.02	.34	1
90R1 90-95	2	14	27	70	.2	11	6	424	2.02	24	5	ND	14	24	.2	2	2	13	.20	.049	37	36	.88	166	.04	2	1.08	.02	.43	1
90R1 95-100	2	8	32	46	.1	6	4	442	1.30	12	5	ND	17	19	.2	2	2	6	.15	.037	43	25	.50	161	.03	3	.73	.02	.32	1
STANDARD C	18	57	39	130	7.0	73	31	1053	3.97	37	23	7	40	56	19.7	14	18	58	.46	.094	39	59	.89	183	.07	34	1.90	.06	.14	13

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER. THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: NOV 5 1990 **DATE REPORT MAILED:** Nov 7/90 **SIGNED BY**.....C. Leong.D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#08495 File # 90-5732

105 Copper Road, Whitehorse YT Y1A 227

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R2 0-5	4	29	52	48	.2	7	4	207	1.19	11	5	ND	14	18	.2	2	2	4	.14	.029	24	39	.36	272	.03	2	.56	.01	.24	2
90R2 5-10	2	12	30	60	.1	8	3	123	1.28	9	5	ND	17	17	.2	2	2	4	.12	.033	31	19	.50	140	.07	2	.66	.01	.37	1
90R2 10-15	2	13	32	50	.2	8	3	181	1.19	6	7	ND	16	46	.2	2	2	3	.26	.028	22	25	.52	179	.06	2	.67	.02	.42	2
90R2 15-20	3	29	40	63	.2	5	3	103	1.05	7	5	ND	18	21	.3	2	2	3	.13	.025	28	29	.37	165	.04	3	.58	.01	.34	1
90R2 20-25	3	44	38	73	.1	4	3	88	1.11	6	5	ND	17	15	.4	2	2	3	.10	.026	30	35	.37	185	.04	3	.63	.02	.38	2
90R2 25-30	3	92	48	125	.4	5	3	98	1.13	9	8	ND	17	18	1.5	2	2	3	.11	.030	34	24	.38	162	.04	2	.59	.01	.34	1
90R2 30-35	2	14	30	57	.2	5	3	164	1.40	7	5	ND	17	21	.2	2	2	4	.12	.033	36	26	.59	189	.08	2	.85	.02	.48	1
90R2 35-40	2	16	32	59	.2	5	3	217	1.39	8	5	ND	18	22	.2	2	2	5	.13	.035	37	21	.58	162	.08	2	.82	.01	.46	1
90R2 40-45	4	12	28	50	.2	6	3	195	1.41	10	6	ND	17	25	.2	2	2	4	.15	.031	32	37	.60	210	.08	2	.82	.02	.48	2
90R2 45-50	4	12	34	61	.1	5	4	199	1.54	3	9	ND	17	28	.6	2	2	5	.18	.034	31	27	.65	235	.07	3	.87	.02	.48	1
90R2 50-55	2	14	26	72	.1	6	4	162	1.51	10	5	ND	15	23	.3	2	2	4	.13	.033	28	20	.48	203	.03	2	.75	.02	.27	1
90R2 55-60	2	10	26	62	.1	4	4	168	1.37	7	5	ND	15	23	.3	2	2	4	.14	.032	25	14	.55	160	.04	2	.75	.01	.29	1
90R2 60-65	1	13	26	54	.1	4	4	168	1.37	7	5	ND	16	24	.2	2	2	4	.13	.032	34	16	.57	164	.04	2	.78	.01	.31	1
90R2 65-70	2	14	23	52	.2	5	4	180	1.27	7	5	ND	14	23	.2	2	2	4	.14	.033	30	15	.52	160	.03	2	.71	.01	.26	2
90R2 70-75	2	7	20	59	.1	5	3	178	1.19	4	5	ND	9	21	.4	2	2	3	.13	.028	23	18	.58	129	.03	4	.71	.01	.24	1
90R2 75-80	1	13	22	66	.1	5	4	171	1.45	17	5	ND	12	22	.2	2	2	4	.13	.029	30	17	.61	119	.01	2	.79	.01	.16	1
90R2 80-85	1	15	26	63	.1	4	3	152	1.46	16	5	ND	12	21	.2	2	2	4	.11	.029	30	15	.63	117	.01	2	.78	.01	.16	1
90R2 85-90	1	10	20	72	.1	6	3	128	1.26	15	5	ND	10	26	.2	2	2	3	.13	.029	28	19	.55	106	.01	3	.72	.01	.17	1
90R2 90-95	2	7	21	52	.1	3	4	133	1.20	6	5	ND	13	21	.2	2	2	3	.11	.029	31	12	.54	104	.02	3	.68	.01	.19	1
90R2 95-100	2	7	24	51	.1	3	3	166	1.23	3	5	ND	13	21	.2	2	2	4	.11	.031	30	11	.59	112	.04	2	.69	.01	.27	1
STANDARD C	17	57	36	131	6.5	69	31	1050	3.95	36	18	7	38	53	18.3	18	20	55	.45	.091	37	55	.92	181	.08	34	1.91	.06	.14	13

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: NOV 5 1990 **DATE REPORT MAILED:** Nov 7/90. **SIGNED BY.** C. Leong .D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#08495 File # 90-5733

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R3 0-5	3	11	23	39	.1	5	6	174	1.23	23	5	ND	11	17	.2	2	2	5	.13	.033	21	31	.30	321	.02	2	.51	.01	.19	1
90R3 5-10	2	7	23	22	.1	4	3	98	.62	8	5	ND	12	10	.2	2	2	3	.07	.019	28	25	.14	185	.01	2	.32	.01	.14	1
90R3 10-15	2	4	21	12	.1	3	1	36	.27	7	5	ND	13	6	.2	2	2	1	.03	.010	33	24	.05	151	.01	2	.19	.01	.13	1
90R3 15-20	2	6	24	10	.1	3	2	39	.28	6	5	ND	15	6	.2	2	2	1	.06	.024	36	25	.04	155	.01	2	.20	.01	.15	1
90R3 20-25	3	10	28	10	.1	2	2	36	.28	8	5	ND	16	8	.2	2	2	1	.10	.033	35	31	.03	189	.01	2	.26	.01	.22	1
90R3 25-30	2	8	26	11	.1	2	2	124	.28	4	5	ND	16	65	.2	2	2	1	.72	.032	42	25	.03	225	.01	4	.29	.02	.26	1
90R3 30-35	2	8	38	16	.3	3	3	115	.42	9	5	ND	18	29	.2	2	2	2	.32	.034	46	20	.06	215	.01	7	.32	.01	.23	1
90R3 35-40	2	7	24	10	.1	2	2	158	.31	8	5	ND	15	75	.2	2	2	1	.87	.023	39	20	.05	186	.01	2	.26	.01	.21	1
90R3 40-45	2	8	22	14	.1	2	1	51	.33	7	5	ND	15	13	.2	2	2	1	.12	.020	38	24	.06	193	.01	2	.28	.02	.20	1
90R3 45-50	2	7	30	13	.1	3	2	80	.37	10	5	ND	16	17	.2	2	2	1	.18	.030	41	25	.06	193	.01	2	.29	.01	.21	1
90R3 50-55	2	5	24	11	.1	3	2	196	.32	7	5	ND	16	74	.2	2	2	1	.75	.026	42	22	.06	220	.01	4	.31	.02	.24	1
90R3 55-60	3	5	25	13	.1	2	2	172	.37	11	5	ND	13	33	.2	2	2	2	.34	.029	37	30	.06	191	.01	2	.30	.02	.22	1
90R3 60-65	2	5	28	13	.1	2	2	308	.33	10	5	ND	13	18	.2	2	2	1	.19	.030	32	20	.05	152	.01	2	.25	.01	.17	1
90R3 65-70	1	4	20	12	.2	2	2	232	.32	6	5	ND	13	54	.2	2	2	1	.61	.028	32	17	.05	159	.01	2	.25	.01	.18	1
90R3 70-75	2	3	18	12	.2	2	2	132	.34	2	5	ND	12	17	.2	2	2	1	.18	.020	34	19	.08	155	.01	2	.27	.01	.18	1
90R3 75-80	2	4	18	12	.1	2	2	457	.34	4	5	ND	11	72	.3	2	2	1	.79	.024	28	22	.07	203	.01	2	.30	.02	.23	1
90R3 80-85	3	7	31	17	.2	2	3	1264	.38	15	5	ND	11	74	.5	2	2	1	.74	.026	27	21	.08	226	.01	2	.31	.02	.22	1
90R3 85-90	6	8	50	24	.1	4	5	2994	.45	29	5	ND	12	53	1.2	2	2	1	.46	.028	33	27	.07	256	.01	2	.30	.02	.21	1
90R3 90-95	3	5	26	15	.1	2	3	1101	.31	18	5	ND	11	45	.5	2	2	1	.45	.022	31	17	.06	167	.01	2	.23	.01	.16	1
90R3 95-100	3	4	23	11	.1	2	2	417	.32	13	5	ND	11	24	.2	2	2	1	.26	.025	26	33	.06	189	.01	2	.28	.02	.20	1
STANDARD C	18	58	37	129	6.8	73	32	1052	3.96	42	21	7	39	55	19.5	15	20	57	.45	.094	39	59	.89	183	.07	34	1.89	.06	.14	11

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: NOV 5 1990 **DATE REPORT MAILED:** Nov 7/90. **SIGNED BY.....** D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#08495 File # 90-5734

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R4 0-5	2	15	29	63	.3	5	6	241	1.16	10	5	ND	13	17	.5	2	2	5	.16	.035	20	24	.57	199	.02	5	.68	.01	.22	1
90R4 5-10	3	7	38	45	.3	6	3	118	.75	6	5	ND	13	13	.3	2	2	3	.13	.028	17	28	.49	145	.02	8	.57	.01	.21	1
90R4 10-15	5	8	42	42	.3	4	3	106	.78	5	5	ND	10	13	.2	2	2	3	.13	.033	16	55	.45	126	.01	8	.55	.01	.18	1
90R4 15-20	3	10	22	58	.3	5	5	132	.96	6	5	ND	15	18	.3	2	2	3	.17	.048	26	25	.52	174	.01	4	.66	.01	.22	1
90R4 20-25	5	6	16	33	.4	5	4	230	.92	5	5	ND	14	10	.4	2	3	3	.10	.019	26	51	.41	194	.01	6	.54	.01	.21	2
90R4 25-30	3	7	15	33	.5	4	4	290	.77	4	5	ND	12	52	.4	2	2	2	.43	.027	13	38	.42	200	.01	6	.55	.01	.24	1
90R4 30-35	3	8	21	52	.2	4	4	210	.96	4	5	ND	14	22	.3	2	2	3	.18	.030	19	33	.59	179	.01	2	.74	.01	.29	1
90R4 35-40	2	7	59	44	.6	2	5	569	1.40	7	5	ND	14	231	.2	2	2	3	1.79	.028	8	18	.98	145	.01	7	.85	.01	.29	1
90R4 40-45	2	6	17	29	.4	2	5	460	1.08	6	5	ND	13	187	.8	2	2	3	1.34	.033	11	24	.71	186	.01	4	.74	.01	.28	1
90R4 45-50	4	9	20	39	.4	5	4	233	.77	5	5	ND	14	17	.4	2	2	3	.15	.036	22	39	.40	207	.01	5	.60	.01	.27	2
90R4 50-55	3	12	29	51	.2	3	4	267	.87	5	5	ND	14	17	.6	2	2	3	.15	.032	21	36	.51	249	.02	4	.66	.01	.28	1
90R4 55-60	2	8	31	46	.2	6	4	255	.95	5	5	ND	15	15	.3	2	3	4	.14	.031	20	26	.59	188	.02	2	.70	.01	.30	1
90R4 60-65	3	9	36	38	.3	2	3	150	.63	4	5	ND	15	13	.2	2	2	2	.10	.028	28	33	.27	204	.01	6	.51	.02	.26	1
90R4 65-70	2	8	49	39	.3	4	3	148	.59	4	5	ND	15	19	.8	2	2	2	.23	.027	26	17	.26	138	.02	5	.42	.01	.28	1
90R4 70-75	2	8	39	43	.2	3	4	221	.74	3	5	ND	15	28	.9	2	2	2	.35	.030	29	15	.30	127	.02	6	.44	.01	.25	1
90R4 75-80	1	12	1123	162	3.9	3	4	218	.99	4	5	ND	16	16	.9	2	2	4	.12	.032	36	12	.41	127	.04	8	.55	.02	.30	1
STANDARD C	18	59	42	131	6.8	72	32	1056	3.98	44	20	7	38	53	18.8	14	19	56	.46	.096	38	59	.90	182	.07	35	1.89	.06	.14	11

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: NOV 5 1990 **DATE REPORT MAILED:** Nov 8/90. **SIGNED BY.** C. Leong .D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

[illegible] 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#13006 File # 90-5804

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R5 0-5	3	11	20	47	.1	7	5	279	1.07	6	5	ND	12	17	.3	2	2	5	.16	.038	20	24	.47	160	.02	2	.59	.01	.19	1
90R5 5-10	3	10	20	41	.6	5	4	301	.83	4	5	ND	13	13	.2	2	2	3	.13	.035	15	22	.40	125	.01	3	.46	.01	.18	1
90R5 10-15	3	11	26	45	.9	4	5	171	.90	4	5	ND	14	14	.2	2	2	3	.13	.031	18	31	.41	144	.01	4	.54	.01	.21	1
90R5 15-20	2	24	22	36	2.7	5	6	430	1.11	2	5	ND	15	14	.4	2	2	3	.11	.027	13	19	.47	152	.01	2	.51	.01	.21	1
90R5 20-25	4	11	29	31	.4	3	3	208	.68	3	5	ND	13	13	.2	2	2	2	.10	.030	22	42	.28	164	.01	2	.48	.01	.23	1
90R5 25-30	3	10	31	35	.3	1	3	77	.56	4	5	ND	13	20	.2	2	2	2	.12	.042	23	25	.20	129	.01	3	.36	.01	.17	1
90R5 30-35	2	17	51	21	.1	2	1	59	.27	2	5	ND	17	8	.2	2	2	1	.06	.021	29	20	.11	94	.01	3	.24	.01	.14	1
90R5 35-40	3	8	35	22	.2	1	2	72	.35	3	5	ND	16	10	.2	2	2	1	.07	.025	27	27	.13	137	.01	2	.30	.01	.18	1
90R5 40-45	3	11	35	73	.2	4	4	239	1.01	3	5	ND	16	19	.2	2	2	3	.13	.037	25	24	.47	216	.01	2	.69	.01	.22	1
90R5 45-50	2	8	40	40	.2	3	2	178	.53	2	5	ND	15	24	.2	2	2	2	.18	.028	20	20	.24	160	.01	3	.42	.02	.23	1
90R5 50-55	3	7	34	13	.1	2	1	87	.32	2	5	ND	19	9	.2	2	2	1	.07	.014	35	28	.15	136	.01	2	.30	.02	.19	1
90R5 55-60	2	7	34	24	.2	1	3	130	.65	2	5	ND	14	32	.2	2	2	2	.29	.026	17	16	.33	114	.01	5	.43	.01	.24	1
90R5 60-65	2	8	34	26	.2	3	3	179	.59	2	5	ND	14	13	.2	2	2	2	.09	.029	24	18	.23	132	.01	2	.39	.01	.20	1
90R5 65-70	2	6	30	24	.1	1	2	182	.52	2	5	ND	16	12	.2	2	2	2	.08	.024	25	23	.21	144	.01	3	.39	.02	.21	1
90R5 70-75	2	10	29	39	.1	3	3	181	.81	2	5	ND	16	13	.2	2	2	3	.09	.031	30	15	.33	108	.01	2	.49	.01	.22	1
90R5 75-80	2	6	32	34	.1	3	4	212	.97	2	5	ND	18	13	.2	2	2	4	.10	.033	41	14	.34	102	.01	2	.53	.01	.21	2
90R5 85-90	2	14	28	51	.1	4	6	350	1.39	21	5	ND	14	68	.2	2	2	8	.61	.040	35	20	.59	110	.03	2	.76	.02	.39	1
90R5 90-95	3	10	23	36	.1	4	4	327	1.07	13	5	ND	15	45	.2	2	2	5	.40	.033	35	27	.40	131	.04	3	.61	.02	.32	1
90R5 95-100	1	7	21	34	.1	4	3	213	1.02	18	5	ND	17	51	.2	2	2	4	.41	.032	44	12	.34	104	.03	2	.56	.02	.26	1
90R5 100-105	2	9	27	30	.1	3	4	268	.92	13	5	ND	16	37	.2	2	2	4	.29	.033	38	16	.30	128	.01	2	.53	.02	.22	1
90R5 105-110	4	13	19	44	.3	4	5	800	1.19	14	6	ND	15	45	.3	2	2	6	.31	.036	37	34	.45	175	.03	2	.64	.01	.27	1
90R5 110-115	2	8	27	44	.2	4	5	540	1.09	15	6	ND	14	49	.2	2	2	5	.40	.033	29	20	.45	136	.02	2	.58	.01	.21	1
90R5 115-120	2	6	23	37	.1	3	4	400	1.03	19	5	ND	14	93	.2	2	2	4	.81	.034	35	18	.43	105	.03	2	.57	.01	.28	1
90R5 120-125	2	8	22	37	.1	3	4	326	1.05	9	5	ND	14	34	.2	2	2	4	.26	.029	37	22	.39	116	.02	4	.55	.02	.27	1
STANDARD C	18	58	38	132	7.1	72	32	1056	3.97	42	22	7	38	53	18.9	15	19	56	.44	.099	38	56	.90	182	.07	36	1.89	.06	.13	11

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: NOV 7 1990 **DATE REPORT MAILED:** Nov 9/90 **SIGNED BY** ..... D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#13009 File # 90-5925 Page 1

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R5 80-85	3	16	29	40	.2	9	5	445	1.25	3	5	ND	10	86	.2	2	2	7	1.01	.039	31	34	.76	163	.03	12	1.03	.01	.36	1

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: NOV 16 1990 **DATE REPORT MAILED:** Nov 23/90 **SIGNED BY** C. Leong D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#13006 File # 90-5805

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R6 0-5	3	26	29	93	.2	10	5	345	1.51	41	5	ND	15	15	.2	2	2	8	.15	.033	32	40	.37	261	.02	3	.80	.02	.22	1
90R6 5-10	3	22	29	73	.1	9	6	434	1.28	21	5	ND	14	12	.2	2	4	7	.10	.029	31	29	.25	219	.01	2	.67	.01	.18	1
90R6 10-15	3	16	50	83	.1	8	3	242	.91	4	5	ND	15	10	.2	2	3	4	.08	.026	27	31	.28	182	.01	2	.53	.01	.21	1
90R6 15-20	3	34	115	124	.1	4	2	132	.74	6	5	ND	14	8	.5	2	2	1	.05	.018	31	25	.10	124	.01	4	.27	.01	.13	1
90R6 20-25	2	25	50	73	.1	6	3	224	.88	5	5	ND	15	11	.2	2	2	3	.10	.032	32	22	.18	189	.01	4	.42	.01	.20	1
90R6 25-30	2	17	26	67	.1	7	4	338	1.26	4	5	ND	16	12	.2	2	2	4	.13	.039	38	17	.29	223	.02	4	.59	.01	.23	1
90R6 30-35	2	14	29	47	.1	6	4	385	1.24	2	5	ND	15	40	.2	2	2	3	.77	.038	36	27	.30	189	.02	2	.56	.01	.22	2
90R6 35-40	3	9	32	51	.1	5	4	336	1.45	2	5	ND	16	17	.2	2	2	5	.29	.035	37	31	.45	186	.02	5	.69	.02	.24	1
90R6 40-45	2	11	22	52	.2	5	4	418	1.28	2	5	ND	15	14	.2	2	4	4	.16	.038	26	20	.58	134	.03	2	.64	.01	.24	1
90R6 45-50	2	13	24	48	.1	6	4	331	1.25	3	5	ND	16	14	.2	2	2	4	.15	.038	25	24	.55	163	.03	4	.67	.01	.26	2
90R6 50-55	2	11	27	45	.1	7	5	416	1.20	2	5	ND	14	15	.2	2	4	3	.18	.036	23	24	.59	175	.01	2	.66	.01	.24	1
90R6 55-60	3	9	19	36	.2	5	4	352	.97	2	5	ND	14	13	.2	2	2	3	.17	.040	24	39	.43	208	.01	2	.55	.01	.21	1
90R6 60-65	3	9	17	37	.1	4	5	381	.94	2	5	ND	14	13	.2	2	2	3	.14	.041	22	30	.45	196	.01	2	.53	.01	.21	1
90R6 65-70	3	10	22	45	.1	6	4	353	1.07	4	7	ND	13	12	.2	2	2	4	.14	.039	21	31	.67	185	.02	2	.64	.01	.24	1
90R6 70-75	3	13	29	63	.1	12	6	357	1.53	2	5	ND	10	17	.2	2	2	7	.16	.040	19	44	1.09	154	.03	3	.91	.01	.30	1
90R6 75-80	5	12	17	55	.3	11	5	375	1.41	4	5	ND	9	15	.2	2	2	6	.13	.031	19	56	.82	182	.02	4	.71	.01	.26	1
90R6 80-85	2	10	53	44	.2	6	5	364	1.10	2	5	ND	12	14	.2	2	2	4	.13	.035	21	26	.68	164	.02	2	.61	.01	.24	1
90R6 85-90	3	8	20	40	.4	4	4	437	.97	2	5	ND	12	11	.3	2	3	3	.13	.038	19	27	.52	175	.02	5	.51	.01	.22	1
90R6 90-95	4	10	19	40	.2	5	4	408	1.02	2	5	ND	13	11	.2	2	5	3	.12	.033	21	39	.50	260	.02	2	.56	.01	.26	1
90R6 95-100	4	9	21	41	.1	6	4	344	.95	2	5	ND	14	12	.3	2	2	3	.30	.034	23	48	.41	260	.02	2	.54	.01	.29	2
90R6 100-105	4	15	28	53	.2	7	4	262	1.05	2	5	ND	15	12	.2	2	2	4	.13	.033	23	45	.59	207	.02	2	.64	.01	.30	1
90R6 105-110	2	7	21	41	.2	4	4	348	1.08	5	5	ND	15	12	.2	2	6	3	.11	.032	24	23	.47	184	.01	2	.56	.01	.23	1
90R6 110-115	3	9	41	48	.2	5	4	390	1.27	2	5	ND	15	14	.2	2	2	4	.13	.035	25	32	.62	214	.02	2	.65	.01	.28	1
90R6 115-120	2	6	29	57	.1	4	4	292	1.51	2	5	ND	13	14	.2	2	2	6	.14	.031	23	27	.89	176	.03	2	.78	.02	.30	1
90R6 120-125	3	10	37	53	.1	4	3	263	1.13	2	5	ND	15	13	.2	2	3	4	.11	.030	22	36	.59	194	.04	3	.67	.02	.37	1
90R6 125-130	5	8	32	45	.2	8	4	313	1.08	3	5	ND	15	13	.2	2	3	4	.12	.030	25	51	.39	188	.03	3	.56	.02	.32	1
90R6 130-135	5	17	47	52	.2	5	3	277	1.13	2	5	ND	16	13	.2	2	2	4	.12	.034	29	49	.45	188	.06	4	.62	.02	.37	1
90R6 135-140	2	12	31	37	.2	3	3	198	.85	2	5	ND	16	12	.2	2	2	3	.09	.032	33	26	.28	146	.03	6	.43	.01	.27	1
90R6 140-145	2	8	31	33	.1	5	2	218	.89	2	5	ND	15	13	.3	2	2	3	.09	.032	33	24	.31	124	.03	3	.46	.01	.25	1
90R6 145-150	3	10	24	34	.3	4	3	217	.96	2	5	ND	18	14	.2	2	4	4	.10	.034	40	28	.36	139	.04	6	.51	.01	.29	2
STANDARD C	18	58	35	130	6.9	73	31	1056	3.97	43	22	7	38	53	19.2	14	18	55	.44	.096	38	56	.90	182	.07	32	1.89	.06	.13	11

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER. THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: NOV 7 1990 **DATE REPORT MAILED:** Nov 9/90 . **SIGNED BY.** C. Leong D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#13006 File # 90-5806

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R7 0-5	4	18	41	57	.1	7	4	294	1.18	10	5	ND	13	14	.2	2	2	6	.11	.027	29	41	.30	206	.02	3	.65	.01	.22	1
90R7 5-10	3	15	66	62	.1	4	2	171	.68	2	5	ND	14	9	.3	2	2	2	.07	.024	24	31	.23	238	.01	2	.37	.01	.19	1
90R7 10-15	3	40	53	95	.1	5	4	331	1.10	7	5	ND	14	14	.2	2	2	3	.13	.041	24	27	.28	311	.01	2	.50	.01	.21	1
90R7 15-20	3	17	33	58	.1	8	5	400	1.33	8	5	ND	16	13	.2	2	2	4	.14	.042	34	31	.26	253	.02	2	.57	.01	.22	1
90R7 20-25	2	12	27	55	.2	4	5	398	1.44	5	5	ND	16	14	.2	2	4	5	.15	.044	34	27	.29	254	.02	2	.64	.01	.25	1
90R7 25-30	4	12	30	61	.1	10	4	430	1.32	12	5	ND	17	14	.2	2	2	4	.13	.041	41	34	.22	241	.01	2	.58	.01	.20	1
90R7 30-35	3	12	42	65	.1	4	5	449	1.38	15	5	ND	16	15	.2	2	2	4	.14	.039	36	36	.35	218	.02	2	.67	.01	.23	1
90R7 35-40	3	12	23	61	.1	5	4	347	1.31	17	5	ND	15	16	.2	2	2	4	.17	.042	32	28	.45	162	.01	2	.70	.01	.18	1
90R7 40-45	2	10	25	46	.1	5	5	365	1.15	8	5	ND	15	14	.3	2	2	3	.14	.037	27	25	.44	137	.01	2	.59	.01	.16	1
90R7 45-50	2	9	26	43	.1	4	4	338	.97	3	5	ND	14	11	.2	2	2	3	.12	.040	22	21	.57	126	.02	2	.57	.01	.22	1
90R7 50-55	2	8	28	45	.1	3	4	285	1.06	2	5	ND	14	12	.2	2	4	4	.12	.035	21	30	.71	136	.03	2	.65	.01	.26	1
90R7 55-60	2	8	22	41	.2	4	4	294	.94	2	5	ND	13	11	.2	2	2	3	.11	.032	23	25	.62	119	.02	2	.57	.01	.21	1
90R7 60-65	3	12	22	38	.2	4	5	376	.99	3	5	ND	15	13	.3	2	2	3	.12	.039	25	29	.53	143	.01	2	.56	.01	.21	1
90R7 65-70	4	7	25	42	.1	3	4	326	.97	2	5	ND	15	13	.2	2	2	3	.11	.032	24	36	.55	151	.01	4	.56	.01	.25	1
90R7 70-75	3	12	37	78	.3	3	4	273	1.08	2	5	ND	15	13	.2	2	2	3	.10	.027	25	34	.55	144	.01	3	.57	.01	.24	1
90R7 75-80	3	23	42	51	.3	2	3	209	.97	4	5	ND	16	11	.3	2	2	2	.08	.023	27	29	.45	149	.01	3	.51	.01	.23	1
90R7 80-85	3	14	37	37	.3	2	3	252	.80	3	5	ND	14	11	.2	2	3	3	.08	.026	24	31	.37	155	.01	2	.48	.01	.21	1
90R7 85-90	2	12	35	39	.3	3	3	256	.95	2	5	ND	14	13	.2	2	2	3	.11	.030	23	23	.37	137	.01	2	.47	.01	.20	2
90R7 90-95	3	10	28	34	.1	2	3	241	.88	2	5	ND	13	13	.2	2	2	3	.10	.032	22	24	.29	151	.01	2	.42	.01	.21	1
90R7 95-100	3	9	28	29	.1	3	3	186	.81	2	5	ND	15	12	.2	2	2	3	.10	.032	27	29	.25	140	.02	2	.42	.01	.24	1
90R7 100-105	3	6	31	36	.1	2	3	184	.85	3	5	ND	16	12	.2	2	2	3	.09	.023	22	25	.45	111	.02	2	.52	.01	.24	1
90R7 105-110	3	6	26	32	.1	2	2	192	.71	2	5	ND	17	11	.3	2	2	3	.08	.022	29	27	.36	125	.02	2	.46	.01	.25	1
90R7 110-115	4	10	22	40	.3	4	4	230	1.02	2	5	ND	14	15	.2	2	3	4	.12	.032	23	39	.37	190	.02	3	.53	.02	.30	1
90R7 115-120	5	10	25	30	.3	3	3	221	.85	2	5	ND	15	18	.2	2	2	4	.20	.030	25	32	.32	169	.02	2	.47	.01	.27	1
90R7 120-125	10	6	29	31	.2	4	3	206	.84	3	5	ND	16	12	.2	2	2	4	.09	.021	21	106	.41	113	.02	2	.46	.01	.23	1
90R7 125-130	3	8	30	40	.2	3	3	188	.93	2	5	ND	18	15	.2	2	3	4	.10	.025	27	30	.49	165	.03	2	.60	.01	.32	1
STANDARD C	19	58	38	131	7.1	72	31	1056	3.97	43	22	7	38	53	20.1	14	17	55	.46	.097	38	56	.90	182	.07	31	1.89	.06	.14	11

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: NOV 7 1990 DATE REPORT MAILED: Nov 9/90 SIGNED BY ..... D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R7 130-135	2	10	29	48	.8	4	4	288	1.13	5	12	ND	22	17	.3	2	2	5	.16	.032	27	16	.51	175	.03	2	.59	.01	.29	2
90R7 135-140	2	10	29	39	.3	3	3	232	1.10	3	5	ND	18	24	.2	2	2	4	.12	.029	21	18	.56	158	.03	4	.65	.01	.35	1
90R7 140-145	1	14	24	37	.5	4	4	234	1.07	3	5	ND	19	21	.2	2	2	4	.12	.029	17	10	.58	118	.03	2	.59	.01	.28	1
90R7 145-150	1	7	28	37	.4	3	4	199	.95	4	7	ND	19	21	.2	2	2	3	.12	.025	19	10	.59	126	.03	2	.59	.01	.27	1
90R7 150-155	1	11	27	45	.1	6	4	274	1.27	2	5	ND	12	22	.2	2	2	5	.24	.033	16	11	.55	145	.04	2	.59	.01	.30	1
90R7 155-160	2	30	25	44	.4	4	5	262	1.27	2	5	ND	14	17	.2	2	2	5	.16	.032	17	20	.47	192	.03	2	.56	.01	.30	1
90R7 160-165	3	26	29	68	.7	14	8	377	1.85	7	5	ND	13	32	.5	2	2	12	.61	.051	11	21	.85	217	.08	3	.88	.01	.49	1
90R7 165-170	2	9	24	70	.1	10	7	435	2.15	2	5	ND	10	35	.2	2	2	13	.52	.045	11	24	1.15	195	.07	2	1.15	.01	.42	1
90R7 170-175	1	19	20	66	.4	8	7	445	2.12	2	5	ND	15	51	.2	2	5	14	.48	.048	17	21	1.10	306	.06	2	1.09	.01	.34	1
90R7 175-180	2	18	23	71	.3	10	8	451	2.25	2	5	ND	14	38	.2	2	2	15	.53	.051	13	24	1.22	191	.08	3	1.19	.01	.45	1
90R7 180-185	1	11	25	57	.2	7	7	308	1.65	2	5	ND	14	28	.2	2	4	8	.41	.041	16	14	1.05	155	.04	2	.93	.01	.36	1
90R7 185-190	1	18	18	67	.5	8	9	388	2.13	3	5	ND	15	33	.2	2	2	14	.41	.048	15	23	1.26	165	.05	3	1.19	.01	.39	1
90R7 190-195	1	21	26	73	.8	9	8	491	2.13	8	5	ND	15	45	.2	3	2	16	.40	.049	18	26	1.20	154	.04	2	1.08	.01	.32	1
90R7 195-200	1	17	38	66	.4	8	7	460	2.09	2	5	ND	14	52	.2	2	2	15	.50	.050	21	27	1.21	172	.04	2	1.13	.01	.31	1
STANDARD C	19	61	41	131	7.0	70	32	1054	3.97	45	20	8	40	55	19.2	15	22	57	.46	.092	39	56	.90	183	.07	35	1.89	.06	.14	11

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#13012 File # 90-6052 Page 1

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R8 0-5	3	21	27	91	.5	19	11	910	2.46	5	5	ND	9	17	.6	2	2	10	.36	.065	19	43	.89	275	.02	8	1.25	.01	.24	1
90R8 5-10	4	33	18	124	.6	24	13	1393	3.01	5	5	ND	7	32	1.2	2	2	13	.57	.077	18	59	1.03	168	.01	6	1.49	.01	.19	1
90R8 10-15	5	33	15	89	.6	18	11	1140	3.20	2	5	ND	6	69	.2	2	2	10	1.65	.061	10	57	1.10	42	.02	9	1.19	.01	.19	1
90R8 15-20	3	54	18	106	.5	18	10	1094	3.15	2	5	ND	6	76	.2	2	2	12	2.65	.073	10	42	1.19	99	.01	7	1.39	.01	.24	1
90R8 20-25	4	32	17	147	.5	25	17	1413	3.47	2	5	ND	6	41	.5	2	2	14	.96	.077	12	53	1.35	86	.01	9	1.68	.02	.24	1
90R8 25-30	4	39	16	111	.5	20	13	1168	3.13	3	5	ND	6	48	.2	2	2	11	1.12	.075	10	54	1.10	58	.01	6	1.30	.01	.22	1
90R8 30-35	2	32	19	83	.4	12	9	856	2.37	3	5	ND	6	93	.2	2	2	10	2.90	.066	11	39	.71	183	.01	6	1.10	.02	.32	1
90R8 35-40	3	56	11	84	.9	15	10	933	1.94	9	5	ND	7	56	.2	2	2	6	1.82	.057	11	39	.68	218	.03	6	.81	.01	.28	1
90R8 40-45	2	33	5	77	.9	16	11	811	2.16	19	5	ND	7	51	1.0	2	2	12	1.20	.061	11	36	.69	179	.06	7	.82	.02	.31	2
90R8 45-50	3	18	11	90	.2	16	11	713	1.71	17	5	ND	7	40	.5	3	2	9	.90	.058	13	38	.74	185	.07	5	.86	.03	.24	2
90R8 50-55	3	21	21	74	.4	14	10	656	1.68	4	5	ND	8	64	.7	3	2	7	1.89	.069	11	39	.76	181	.05	5	.83	.02	.29	1
90R8 55-60	3	28	18	49	.6	14	11	531	1.77	4	5	ND	6	63	.4	3	2	4	1.45	.059	7	46	.49	53	.02	2	.61	.03	.30	1
90R8 60-65	2	23	17	29	.3	15	10	314	1.75	4	5	ND	6	27	.7	5	2	1	.93	.061	5	21	.24	31	.02	7	.37	.02	.18	2
90R8 65-70	3	35	29	57	.5	12	11	520	1.82	5	5	ND	5	58	.9	4	2	4	1.98	.068	4	32	.28	42	.02	8	.45	.02	.28	1
90R8 70-75	5	49	64	137	1.1	13	8	462	1.81	9	5	ND	6	52	2.6	3	2	3	1.40	.054	7	40	.44	44	.02	4	.50	.03	.26	1
90R8 75-80	5	28	46	64	.5	12	9	583	1.68	9	5	ND	7	79	1.2	2	2	3	1.94	.054	7	40	.57	56	.03	8	.56	.02	.28	1
90R8 80-85	3	30	9	39	1.7	10	8	586	1.60	4	5	ND	5	99	.5	3	2	4	1.68	.058	7	36	.54	52	.02	9	.57	.02	.27	1
90R8 85-90	3	21	11	31	.3	13	9	316	1.77	4	5	ND	8	32	.5	3	2	4	.90	.060	8	39	.33	51	.03	7	.58	.02	.30	2
90R8 90-95	3	25	49	76	.6	14	10	760	1.66	8	5	ND	9	32	1.0	2	2	3	.72	.041	9	31	.56	138	.04	8	.63	.01	.23	2
90R8 95-100	3	28	43	90	.6	13	10	540	1.89	6	5	ND	7	36	1.1	2	2	4	1.11	.058	9	40	.56	87	.04	8	.67	.02	.28	2
90R8 100-105	6	42	40	62	.8	12	8	490	1.79	7	5	ND	7	50	.4	2	2	5	1.28	.050	12	49	.66	76	.02	9	.81	.03	.37	2
90R8 105-110	2	25	28	60	.3	10	7	559	1.58	6	5	ND	8	56	.6	2	2	4	1.07	.036	10	31	.54	110	.01	5	.65	.02	.23	1
90R8 110-115	3	42	35	64	.4	10	7	658	1.45	9	5	ND	8	87	.4	2	2	6	1.07	.043	14	37	.48	159	.02	5	.68	.04	.28	2
90R8 115-120	3	23	14	58	1.5	10	8	501	1.71	3	5	3	6	120	.6	2	2	7	1.59	.071	12	37	.61	81	.01	3	.75	.06	.30	2
90R8 120-125	4	45	227	229	.8	13	9	481	2.00	36	5	ND	8	42	1.8	2	3	8	.75	.060	16	43	.39	60	.01	7	.79	.06	.38	2
90R8 125-130	4	22	28	86	.3	11	8	536	2.75	3	5	ND	7	80	.2	2	2	6	1.92	.056	13	31	.78	54	.01	5	.89	.03	.27	1
90R8 130-135	2	20	33	66	.5	14	8	512	1.93	2	5	ND	6	106	.7	2	2	5	2.24	.054	7	29	.76	145	.02	7	.72	.02	.24	3
90R8 135-140	3	16	6	45	.3	15	8	512	2.05	2	5	ND	5	110	.8	2	2	4	2.81	.044	6	33	.90	80	.04	7	.77	.02	.28	2
90R8 140-145	4	17	24	48	.3	14	8	450	2.05	2	5	ND	5	86	.4	2	2	4	2.74	.048	6	37	.71	78	.03	6	.63	.02	.28	2
90R8 145-150	3	16	8	74	.3	16	13	664	2.71	3	5	ND	3	139	.8	2	2	11	3.84	.051	5	118	1.41	78	.04	5	.93	.01	.22	1
STANDARD C	20	61	42	133	7.3	74	32	1044	3.97	42	17	7	37	52	18.6	16	19	60	.46	.094	39	58	.87	180	.08	38	1.90	.06	.13	11

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: NOV 23 1990 DATE REPORT MAILED: Nov 27/90 SIGNED BY..... D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R9 0-5	2	24	31	41	.5	6	3	125	1.56	8	5	ND	8	48	.2	2	2	5	.15	.047	10	38	.39	600	.01	3	.51	.02	.11	1
90R9 5-10	2	27	18	29	.5	7	4	116	1.75	4	6	ND	8	48	.2	2	2	5	.08	.059	9	38	.25	697	.02	3	.39	.02	.14	1
90R9 10-15	4	32	24	41	.5	9	7	265	1.80	5	5	ND	8	34	.2	2	2	7	.12	.058	8	41	.29	708	.02	3	.51	.01	.13	1
90R9 15-20	2	34	15	66	.6	14	9	516	1.55	40	5	ND	9	44	.4	3	2	6	.69	.060	9	29	.61	146	.02	3	.63	.01	.14	1
90R9 20-25	1	34	23	58	1.0	13	9	582	1.66	13	5	ND	8	78	.4	2	2	5	1.31	.058	8	29	.65	54	.01	2	.64	.01	.13	1
90R9 25-30	2	34	11	59	.4	12	8	579	1.98	30	5	ND	8	36	.3	2	2	8	.77	.052	8	28	.55	33	.01	3	.61	.01	.14	1
90R9 30-35	2	39	12	53	.7	13	10	586	1.99	28	5	ND	9	48	.3	2	2	7	1.03	.049	9	28	.54	33	.01	2	.63	.02	.13	1
90R9 35-40	1	21	14	50	.4	9	6	429	1.36	2	5	ND	10	75	.2	2	2	4	1.03	.046	11	25	.47	71	.01	2	.56	.02	.12	2
90R9 40-45	2	35	15	63	.3	13	7	454	1.63	3	5	ND	11	83	.2	2	2	7	1.26	.047	14	33	.53	100	.01	2	.67	.02	.11	1
90R9 45-50	2	36	9	37	.4	11	8	398	1.72	2	5	ND	9	62	.2	2	2	5	1.04	.050	12	27	.34	28	.01	2	.48	.02	.13	2
90R9 50-55	2	17	15	42	.6	10	7	417	1.89	4	5	ND	10	68	.2	2	3	5	1.30	.042	12	37	.32	19	.01	2	.53	.03	.16	2
90R9 55-60	1	26	10	74	.4	17	12	644	2.47	2	5	ND	9	65	.3	2	2	7	1.50	.060	11	37	.45	29	.01	4	.74	.02	.14	1
90R9 60-65	2	27	14	91	.4	15	11	569	3.07	9	5	ND	8	111	.2	2	2	9	2.06	.058	8	59	.63	16	.01	4	.87	.02	.15	1
90R9 65-70	3	26	7	75	.5	20	14	518	3.20	2	5	ND	7	89	.2	2	2	9	2.20	.056	7	69	.61	14	.01	5	.70	.02	.16	1
90R9 70-75	3	23	8	63	.2	11	7	435	2.11	2	5	ND	9	87	.2	2	2	5	1.62	.051	9	37	.60	21	.01	3	.71	.02	.16	1
90R9 75-80	3	43	5	58	.3	16	9	422	2.19	2	5	ND	8	70	.3	2	2	6	1.92	.047	7	53	.54	19	.01	3	.68	.02	.21	1
90R9 80-85	3	27	7	52	1.1	19	13	547	2.91	3	5	ND	6	110	.2	2	2	7	2.69	.056	5	66	.76	17	.01	4	.65	.01	.21	1
90R9 85-90	4	32	8	53	1.0	16	10	593	2.68	11	5	ND	6	107	.2	2	2	7	2.89	.050	5	69	.79	15	.01	4	.61	.02	.15	1
90R9 90-95	4	36	16	55	.7	18	15	691	3.31	22	5	ND	5	113	.4	2	2	8	3.05	.058	5	71	.90	18	.01	5	.63	.01	.16	1
90R9 95-100	3	30	8	46	1.9	18	14	716	2.78	8	5	5	5	157	.4	2	2	7	3.69	.054	5	72	.84	31	.01	4	.57	.01	.15	1
90R9 100-105	1	24	10	51	.5	13	9	419	1.97	5	5	ND	10	70	.2	2	2	6	1.50	.055	10	33	.44	39	.01	3	.63	.02	.17	1
90R9 105-110	3	36	17	51	.4	13	8	512	2.04	5	5	ND	8	82	.3	2	2	7	1.95	.049	9	59	.60	28	.01	3	.70	.02	.19	1
90R9 110-115	3	35	10	51	.6	15	10	531	2.28	10	5	ND	7	93	.2	2	2	7	2.22	.050	8	55	.78	27	.01	3	.75	.02	.18	1
90R9 115-120	5	34	15	70	.5	14	9	610	2.28	2	5	ND	7	102	.2	2	2	8	2.70	.046	8	68	.85	28	.01	3	.81	.02	.17	1
90R9 120-125	3	41	11	57	.5	10	7	407	1.65	4	5	ND	9	71	.3	2	2	8	1.63	.046	13	47	.38	62	.01	3	.68	.03	.20	1
90R9 125-130	2	25	9	59	.5	8	7	430	1.59	7	5	ND	9	79	.2	2	2	8	1.50	.050	13	34	.38	110	.02	3	.68	.03	.18	1
90R9 130-135	2	49	10	42	1.0	9	7	433	1.73	2	5	ND	9	85	.3	2	2	6	1.46	.058	12	30	.38	45	.01	2	.60	.04	.18	1
90R9 135-140	4	23	21	59	.7	11	7	523	1.67	20	5	ND	10	70	.2	2	2	6	1.73	.053	16	44	.35	56	.01	4	.63	.02	.17	1
90R9 140-145	3	25	12	55	.6	10	7	397	1.72	4	5	ND	10	59	.2	2	2	6	1.43	.050	20	37	.28	34	.01	2	.68	.03	.21	1
90R9 145-150	1	29	9	48	.5	10	7	371	1.67	5	5	ND	10	63	.2	2	2	5	1.51	.052	21	21	.25	35	.01	3	.54	.02	.16	2
STANDARD C	18	57	36	132	7.1	71	31	1052	3.95	45	22	7	39	52	18.7	15	17	56	.46	.096	38	58	.89	180	.08	36	1.89	.06	.14	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R10 0-5	5	51	50	78	.4	9	6	447	1.36	7	5	ND	9	11	.2	2	2	5	.12	.038	13	69	.71	476	.01	3	.91	.02	.19	1
90R10 5-10	4	27	39	60	.3	8	3	173	1.22	2	5	ND	9	21	.2	2	2	3	.08	.039	10	44	.73	591	.01	2	.76	.01	.15	1
90R10 10-15	4	44	24	42	.4	7	2	143	1.62	14	5	ND	7	9	.2	2	2	4	.06	.053	11	58	.58	235	.01	2	.66	.01	.17	1
90R10 15-20	4	37	36	62	.5	7	3	185	1.78	15	5	ND	9	8	.2	2	2	4	.07	.045	13	55	.86	177	.01	6	.88	.01	.18	1
90R10 20-25	3	33	35	66	.7	8	5	223	1.69	30	5	ND	7	11	.2	2	4	5	.08	.051	12	46	.83	171	.01	2	.93	.01	.19	1
90R10 25-30	6	49	35	99	.8	12	9	437	1.75	40	5	ND	6	88	.3	2	2	4	.98	.053	7	69	.70	120	.01	2	.75	.02	.20	1
90R10 30-35	6	71	57	82	.9	14	9	381	1.81	13	5	ND	6	62	.2	2	2	3	.81	.062	6	52	.48	135	.01	3	.63	.02	.20	1
90R10 35-40	4	19	11	88	.4	12	9	459	2.54	34	5	ND	8	73	.2	2	2	6	1.43	.062	9	51	.69	109	.01	4	.90	.02	.22	1
90R10 40-45	3	32	10	65	.6	13	8	432	1.85	27	5	ND	7	87	.2	2	2	5	1.35	.052	9	46	.74	160	.01	3	.96	.01	.25	1
90R10 45-50	2	44	16	43	.8	9	8	418	1.60	16	5	ND	7	68	.2	2	2	4	1.03	.053	9	29	.55	130	.01	4	.68	.02	.19	1
90R10 50-55	2	36	12	38	.8	12	9	472	2.01	11	5	ND	6	68	.2	2	2	5	1.39	.052	7	37	.57	99	.01	2	.61	.02	.17	1
90R10 55-60	5	73	20	53	.4	9	6	312	1.17	12	5	ND	9	67	.2	2	2	3	.91	.035	11	61	.52	154	.01	3	.65	.03	.22	1
90R10 60-65	3	16	19	28	.1	4	2	190	.52	6	5	ND	13	51	.2	2	2	1	.55	.011	17	39	.33	343	.01	2	.45	.02	.19	1
90R10 65-70	4	26	34	46	.2	2	1	116	.42	2	5	ND	17	29	.2	2	2	1	.21	.006	34	41	.18	428	.01	2	.41	.02	.21	2
90R10 70-75	4	23	25	34	.1	2	1	221	.51	2	5	ND	15	29	.2	2	2	1	.37	.007	28	48	.23	336	.01	2	.45	.02	.22	1
90R10 75-80	4	15	31	29	.1	3	1	156	.39	2	5	ND	18	24	.2	2	2	1	.30	.004	32	49	.17	451	.01	2	.41	.02	.21	1
90R10 80-85	5	31	30	31	.2	3	2	195	.45	4	5	ND	17	39	.2	3	2	1	.45	.006	23	56	.23	501	.01	3	.60	.02	.31	1
90R10 85-90	3	29	29	45	.2	9	6	584	1.23	24	5	ND	10	57	.2	2	2	4	1.04	.028	12	76	.70	174	.01	2	.78	.01	.27	1
90R10 90-95	3	24	15	44	.3	9	8	515	1.58	19	5	ND	7	71	.2	2	2	6	1.50	.049	10	55	.51	120	.01	2	.76	.01	.29	1
90R10 95-100	3	23	41	78	.3	14	9	565	2.09	19	5	ND	7	71	.2	2	2	9	1.29	.057	13	60	.77	69	.01	2	1.05	.02	.30	1
90R10 100-105	2	25	38	108	.4	17	10	717	2.20	51	5	ND	6	90	.2	2	2	10	1.88	.055	17	61	1.11	83	.01	3	1.14	.01	.23	1
90R10 105-110	3	22	25	83	.3	15	8	675	1.92	27	5	ND	7	90	.2	2	2	8	1.94	.050	16	44	1.02	93	.01	3	1.10	.01	.26	1
90R10 110-115	3	21	20	96	.3	16	10	952	2.21	46	5	ND	5	92	.2	2	2	9	2.94	.050	10	64	1.10	102	.01	2	1.11	.01	.23	1
90R10 115-120	3	46	121	191	.4	14	9	913	2.10	53	5	ND	6	70	.2	3	2	7	2.00	.060	16	48	.74	117	.01	4	.88	.02	.24	1
90R10 120-125	3	22	323	349	.5	15	10	1044	2.49	66	5	ND	6	69	2.3	2	2	7	1.99	.058	17	60	.93	86	.01	2	1.00	.01	.21	1
90R10 125-130	3	24	22	60	.3	12	8	648	1.65	65	5	ND	8	62	.2	2	2	4	1.83	.050	22	42	.39	88	.01	2	.72	.02	.26	1
90R10 130-135	3	29	82	110	.4	15	10	940	2.24	117	5	ND	6	80	.2	5	2	7	2.40	.059	16	58	.67	91	.01	3	.83	.01	.21	1
90R10 135-140	3	24	366	589	.6	12	8	622	1.45	39	5	ND	9	64	4.5	2	2	4	1.60	.047	22	37	.41	127	.01	6	.64	.02	.20	1
90R10 140-145	4	22	207	336	.5	12	9	599	2.20	73	5	ND	7	57	2.5	2	2	6	1.16	.067	26	38	.35	102	.01	2	.65	.02	.25	1
90R10 145-150	3	32	44	99	.5	13	8	596	2.05	41	5	ND	8	62	.2	3	3	7	.99	.061	28	30	.44	139	.01	3	.73	.02	.22	1
STANDARD C	18	60	39	134	7.3	72	31	1062	3.98	42	18	8	36	51	18.9	15	19	55	.49	.099	35	61	.89	182	.08	35	1.91	.06	.14	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R11 0-5	6	46	62	77	.3	15	10	631	2.06	19	5	ND	1	18	.2	2	2	12	.21	.053	16	76	.57	390	.01	3	1.01	.01	.17	1
90R11 5-10	5	40	10	83	.3	12	5	299	1.63	34	5	ND	9	14	.2	2	2	2	.10	.042	14	64	.66	224	.01	5	.79	.01	.13	1
90R11 10-15	9	59	42	68	.5	9	2	127	1.78	9	5	ND	6	50	.2	2	2	3	.10	.044	12	104	.45	410	.01	3	.62	.01	.19	1
90R11 15-20	10	33	24	76	1.1	16	12	413	1.44	14	5	4	4	14	.2	2	2	3	.11	.026	11	116	.34	211	.01	6	.55	.01	.12	2
90R11 20-25	7	42	15	94	.5	17	16	575	2.04	14	5	ND	7	11	.2	2	2	3	.09	.050	12	93	.72	295	.01	4	1.03	.02	.24	1
90R11 25-30	8	59	28	82	1.4	15	10	456	1.77	14	5	ND	8	8	.2	2	2	2	.08	.039	12	86	.67	196	.01	4	.81	.02	.21	1
90R11 30-35	9	62	28	86	1.0	13	7	242	1.87	48	5	ND	7	13	.2	2	2	4	.11	.036	12	87	.74	87	.01	3	.86	.03	.27	1
90R11 35-40	6	50	15	98	.8	14	10	406	1.82	19	5	ND	5	48	.4	2	2	4	.91	.074	8	65	.72	100	.01	2	.68	.01	.19	1
90R11 40-45	5	47	24	143	1.6	16	9	526	1.96	13	5	2	6	83	1.1	2	2	3	.83	.039	8	50	1.04	70	.01	3	.75	.02	.23	1
90R11 45-50	3	44	63	113	1.2	17	12	900	2.95	18	5	ND	3	130	.6	2	2	6	2.99	.082	6	41	1.15	26	.01	3	.99	.01	.28	1
90R11 50-55	4	49	33	98	.6	14	8	674	2.04	133	5	ND	6	81	.3	2	2	4	2.22	.063	7	35	.84	37	.01	4	.80	.01	.25	1
90R11 55-60	3	39	26	102	.6	13	8	727	2.62	179	5	ND	6	68	.2	2	2	6	2.12	.066	6	40	1.18	38	.01	3	1.10	.01	.20	1
90R11 60-65	2	158	124	278	1.1	15	8	745	2.69	40	5	ND	6	56	1.6	2	2	6	1.70	.062	7	42	1.42	74	.01	4	1.26	.01	.19	1
90R11 65-70	3	146	219	459	1.1	14	8	735	2.78	18	5	ND	6	45	2.5	2	2	7	1.15	.062	7	40	1.67	90	.01	2	1.40	.01	.19	1
90R11 70-75	4	127	235	326	1.3	13	8	761	2.52	22	5	ND	6	61	2.1	2	2	6	2.00	.066	7	36	1.33	93	.01	2	1.25	.01	.18	1
90R11 75-80	3	26	36	127	.4	11	7	591	1.93	34	5	ND	8	46	.2	2	2	4	1.61	.055	9	39	.84	80	.01	3	.93	.01	.20	1
90R11 80-85	4	34	33	121	.4	13	8	705	2.50	7	5	ND	6	49	.2	2	2	6	1.66	.062	11	36	1.31	40	.01	2	1.22	.02	.19	1
90R11 85-90	4	48	91	191	.8	13	8	691	2.47	8	5	ND	6	55	.4	2	2	6	1.95	.059	11	42	1.28	36	.01	2	1.11	.02	.20	1
90R11 90-95	5	39	81	161	.6	14	7	934	2.37	7	5	ND	6	64	.5	2	2	5	2.51	.049	9	45	1.29	35	.01	4	1.06	.01	.19	1
90R11 95-100	4	56	60	142	.6	14	8	792	2.52	9	5	ND	6	60	.6	2	2	5	2.06	.055	7	38	1.35	32	.01	5	1.14	.02	.18	1
90R11 100-105	2	53	33	134	.4	14	8	776	2.41	12	5	ND	6	63	.2	2	2	5	2.33	.061	6	30	1.13	44	.01	2	1.01	.01	.17	1
90R11 105-110	2	109	52	159	.8	12	7	602	2.09	10	5	ND	7	44	.4	2	2	5	1.68	.056	7	32	.84	115	.01	3	.95	.01	.17	1
90R11 110-115	1	40	26	107	.4	10	7	704	1.99	9	5	ND	6	61	.3	2	2	4	2.39	.052	8	26	.97	114	.01	2	.93	.01	.17	1
90R11 115-120	2	55	21	84	1.1	11	8	938	2.24	14	5	2	5	94	.7	2	2	4	3.24	.053	6	38	.92	94	.01	4	.67	.01	.22	1
90R11 120-125	4	36	48	110	.5	13	7	827	2.16	24	5	ND	6	67	.8	2	2	4	2.09	.048	7	45	.83	88	.01	4	.84	.02	.22	1
90R11 125-130	4	40	54	163	.6	15	8	914	2.70	10	5	ND	6	79	.3	2	2	5	2.64	.050	6	33	1.23	85	.01	4	1.06	.02	.20	1
90R11 130-135	3	33	16	70	.5	11	7	489	1.64	31	5	ND	7	48	.2	2	2	3	1.36	.054	11	36	.53	104	.01	5	.63	.01	.24	1
90R11 135-140	2	30	23	65	.5	14	8	786	1.73	34	5	ND	7	62	.2	2	2	4	2.56	.053	9	29	.66	82	.01	4	.75	.01	.22	1
90R11 140-145	5	35	25	74	.8	16	9	852	2.02	46	5	ND	7	68	.3	2	2	4	2.31	.046	11	34	.75	91	.01	5	.69	.02	.21	1
90R11 145-150	3	43	22	97	.8	14	10	886	2.72	57	5	ND	7	75	.5	2	2	9	2.56	.052	10	31	.71	66	.01	5	.83	.01	.19	1
STANDARD C	18	63	40	131	6.7	67	29	1048	3.97	43	17	8	36	47	17.4	15	23	55	.44	.097	36	55	.87	175	.08	35	1.89	.07	.14	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R12 0-5	5	61	95	198	.5	23	13	1047	2.17	3	5	ND	7	11	.8	2	2	6	.19	.063	12	59	1.00	293	.01	5	1.18	.02	.25	1
90R12 5-10	4	73	62	249	.4	34	19	948	2.63	4	5	ND	8	14	.7	3	2	6	.26	.069	15	52	.84	182	.01	7	1.34	.01	.25	1
90R12 10-15	4	49	39	169	.5	24	14	846	2.30	5	5	ND	8	12	.2	2	2	6	.20	.068	13	58	.58	198	.01	5	1.03	.02	.30	1
90R12 15-20	4	62	30	148	.4	21	13	850	2.73	5	5	ND	8	13	.2	2	2	7	.27	.070	11	53	.73	202	.01	8	1.05	.02	.30	1
90R12 20-25	2	36	16	137	.2	20	9	807	2.59	2	5	ND	9	41	.2	2	2	7	.96	.069	10	38	1.00	160	.01	4	1.06	.02	.24	1
90R12 25-30	5	71	25	124	.5	18	9	815	2.25	11	5	ND	8	70	.2	2	2	4	1.91	.059	7	40	1.00	131	.01	4	.70	.02	.27	1
90R12 30-35	4	49	69	264	1.1	16	9	801	2.23	3	5	ND	6	89	2.5	2	2	5	2.46	.058	6	48	.98	62	.01	5	.76	.02	.32	1
90R12 35-40	5	51	82	246	.8	17	9	604	2.06	2	5	ND	6	58	2.1	2	2	4	1.56	.043	7	50	.80	44	.01	4	.67	.02	.35	1
90R12 40-45	3	42	17	111	.6	17	8	608	1.95	2	5	ND	8	50	.2	2	2	4	1.49	.053	7	39	.75	127	.01	6	.65	.02	.27	1
90R12 45-50	4	39	41	94	.6	17	9	610	2.34	3	5	ND	8	50	.2	2	2	5	1.73	.064	6	39	.85	118	.01	6	.84	.02	.29	1
90R12 50-55	4	63	33	93	.8	18	9	591	2.27	5	5	ND	8	49	.2	2	2	2	1.76	.058	5	35	.74	84	.01	6	.56	.01	.19	2
90R12 55-60	6	105	189	145	1.6	18	8	422	1.92	3	5	ND	8	32	1.8	2	2	1	1.12	.044	5	30	.44	44	.01	10	.33	.01	.20	1
90R12 60-65	4	118	174	190	1.7	17	9	434	2.05	5	5	ND	8	34	1.2	2	3	2	1.29	.051	5	38	.48	45	.01	4	.41	.01	.22	2
90R12 65-70	7	111	250	539	2.3	15	8	377	1.73	4	5	ND	7	27	5.7	5	2	2	.94	.042	7	40	.37	47	.01	2	.42	.02	.24	3
90R12 70-75	6	95	116	129	1.3	18	9	420	2.04	3	5	ND	9	27	.6	5	2	2	.91	.062	10	31	.47	90	.01	9	.47	.01	.19	3
90R12 75-80	2	24	22	87	.3	15	9	464	1.91	2	5	ND	10	33	.2	2	2	5	1.12	.068	13	37	.80	119	.01	3	.94	.02	.21	1
90R12 80-85	4	25	46	49	.4	14	8	443	1.68	3	5	ND	9	30	.2	2	2	3	1.12	.056	8	39	.43	117	.01	6	.50	.02	.20	1
90R12 85-90	4	35	21	56	.4	16	9	488	1.86	3	5	ND	8	37	.2	2	2	3	1.59	.051	7	32	.41	70	.01	4	.54	.02	.25	2
90R12 90-95	4	39	11	70	.4	16	8	543	1.80	2	5	ND	9	44	.2	2	2	3	1.64	.052	8	34	.53	93	.01	6	.57	.02	.23	2
90R12 95-100	4	38	20	61	.5	18	9	578	1.81	5	5	ND	8	47	.2	2	2	3	1.81	.052	6	29	.52	113	.01	7	.53	.01	.21	2
90R12 100-105	5	35	30	49	.3	14	8	676	1.89	2	5	ND	7	68	.2	2	2	3	2.15	.044	7	35	.53	117	.01	2	.56	.02	.24	2
90R12 105-110	4	42	21	53	.4	14	8	549	1.83	3	5	ND	8	61	.2	2	2	4	1.73	.057	8	35	.50	120	.01	5	.54	.02	.26	2
90R12 110-115	3	24	15	64	.3	11	9	577	1.54	25	5	ND	7	35	.2	2	2	5	.94	.067	12	40	.49	159	.01	2	.58	.02	.23	1
90R12 115-120	3	27	32	59	1.2	13	10	673	1.84	62	5	ND	8	20	.2	2	2	6	.55	.068	14	42	.38	121	.01	5	.52	.03	.22	1
90R12 120-125	3	19	15	75	.6	13	9	718	2.25	40	5	ND	8	64	.2	2	2	7	1.54	.066	11	36	.61	120	.01	3	.67	.02	.18	2
90R12 125-130	2	21	17	68	.1	13	8	539	1.65	2	5	ND	9	77	.2	2	2	5	1.50	.066	13	31	.62	153	.01	3	.69	.03	.21	1
90R12 130-135	2	19	11	50	.7	12	8	575	1.55	2	5	ND	7	119	.2	2	2	3	1.56	.062	9	32	.61	155	.01	5	.57	.03	.19	3
90R12 135-140	3	15	19	83	.2	16	9	788	2.48	4	5	ND	9	55	.2	2	2	6	1.15	.059	11	27	.99	55	.01	6	.88	.02	.15	2
90R12 140-145	3	19	17	90	.2	17	10	833	2.64	5	5	ND	10	47	.2	2	2	9	1.39	.064	16	34	.84	88	.01	2	.91	.02	.19	1
90R12 145-150	4	23	26	62	.3	15	9	754	2.47	4	5	ND	10	54	.2	2	2	6	1.61	.062	20	38	.47	39	.01	6	.61	.02	.23	3
STANDARD C	20	62	43	133	7.3	73	32	1045	3.98	42	15	7	39	52	18.4	15	22	58	.46	.097	38	61	.87	181	.08	38	1.90	.07	.14	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R13 0-5	1	18	21	64	.7	11	7	457	2.12	151	5	ND	12	12	.4	4	2	11	.09	.047	25	37	.59	209	.01	3	.79	.02	.10	1
90R13 5-10	1	18	16	73	.9	11	5	392	2.02	163	5	ND	12	7	.2	3	2	12	.08	.050	30	59	.72	66	.01	5	.88	.05	.07	1
90R13 10-15	2	19	20	36	.7	6	2	193	1.70	65	6	ND	11	7	.2	2	2	7	.04	.053	23	38	.28	169	.01	4	.60	.03	.23	1
90R13 15-20	3	27	35	30	.4	5	1	139	1.66	50	5	ND	12	5	.2	3	2	6	.03	.049	22	47	.20	209	.01	4	.61	.03	.27	1
90R13 20-25	2	44	40	24	.7	2	1	96	1.61	18	5	ND	10	6	.2	2	2	4	.02	.045	16	34	.13	170	.01	4	.45	.03	.24	2
90R13 25-30	4	28	25	24	.7	4	1	109	1.46	23	6	ND	10	8	.2	2	2	5	.03	.044	19	53	.16	299	.01	4	.52	.04	.27	1
90R13 30-35	2	36	18	30	.4	6	3	155	1.51	21	5	ND	11	11	.2	2	2	4	.07	.060	17	34	.26	156	.01	4	.59	.03	.24	1
90R13 35-40	4	15	27	24	.5	6	4	113	1.42	21	5	ND	10	8	.2	2	2	4	.09	.047	14	37	.17	149	.01	3	.54	.02	.29	1
90R13 40-45	2	24	23	45	.7	12	8	362	1.80	45	5	ND	9	30	.7	2	2	4	.59	.055	14	24	.40	70	.01	5	.74	.02	.25	2
90R13 45-50	1	24	22	38	.5	13	9	411	2.28	24	5	ND	8	43	.6	2	2	5	.94	.056	8	21	.28	24	.01	4	.55	.02	.24	1
90R13 50-55	1	8	21	21	.5	10	8	449	1.36	10	5	ND	9	58	.2	2	2	3	1.09	.048	11	23	.27	18	.01	4	.57	.02	.25	1
90R13 55-60	2	35	23	51	.9	14	8	479	1.98	13	5	ND	8	60	.9	3	2	5	1.27	.060	8	34	.42	15	.01	3	.63	.02	.26	1
90R13 60-65	2	26	25	33	.6	11	7	442	1.66	12	6	ND	8	55	.5	3	2	4	1.10	.053	8	25	.42	21	.01	4	.58	.02	.21	1
90R13 65-70	2	20	26	18	.4	7	7	291	1.07	8	5	ND	9	32	.3	2	2	3	.76	.048	10	21	.14	104	.01	4	.41	.02	.24	1
90R13 70-75	1	24	21	26	.3	8	6	338	1.24	16	5	ND	9	36	.5	2	2	3	.95	.045	10	23	.20	79	.01	3	.42	.02	.23	1
90R13 75-80	2	27	69	48	.7	8	6	532	1.65	17	5	ND	8	57	.4	2	2	5	1.17	.047	11	24	.42	33	.01	3	.62	.02	.22	1
90R13 80-85	2	17	32	26	.6	9	6	386	1.50	12	5	ND	9	36	.2	2	2	5	.68	.045	12	25	.28	84	.01	3	.55	.02	.24	1
90R13 85-90	1	29	35	36	1.0	10	8	473	1.98	17	5	ND	8	54	.4	3	2	6	1.26	.062	13	24	.22	42	.01	3	.52	.02	.29	1
90R13 90-95	2	43	43	46	1.1	9	7	469	1.74	14	5	ND	11	42	.3	4	2	6	1.26	.062	22	24	.25	69	.01	3	.55	.02	.29	1
90R13 95-100	2	23	43	69	1.1	12	8	507	1.83	39	5	ND	9	54	.4	2	2	7	1.57	.062	25	27	.29	91	.01	3	.62	.01	.27	1
90R13 100-105	2	20	51	46	.6	11	8	501	1.84	11	5	ND	9	61	.3	2	2	7	1.79	.060	21	29	.28	57	.01	4	.65	.02	.27	1
90R13 105-110	2	24	21	46	1.3	11	8	499	1.83	6	5	3	8	65	.2	2	2	8	1.46	.074	14	32	.40	23	.01	3	.74	.03	.28	2
90R13 110-115	1	22	65	73	.8	12	8	600	2.16	9	5	ND	9	71	.4	3	2	11	1.60	.062	16	28	.42	35	.02	5	.83	.02	.23	1
90R13 115-120	1	21	43	85	.7	17	10	689	2.42	11	5	ND	8	82	.3	2	2	11	2.22	.056	16	67	.76	52	.01	4	1.05	.02	.19	1
90R13 120-125	1	26	19	75	.6	16	8	410	2.55	10	5	ND	9	40	.3	2	2	8	1.05	.055	14	30	.48	30	.01	4	.77	.03	.14	1
90R13 125-130	1	26	15	56	.6	14	8	271	1.73	7	5	ND	8	37	.2	2	2	6	.98	.057	12	24	.27	26	.01	5	.54	.02	.15	1
90R13 130-135	2	31	16	35	.3	15	8	245	2.05	7	5	ND	8	32	.2	2	2	5	1.09	.054	9	22	.20	15	.01	4	.45	.02	.14	1
90R13 135-140	2	14	44	94	.4	12	7	483	2.12	9	5	ND	8	71	.3	2	2	9	2.14	.054	10	29	.82	78	.01	5	1.12	.02	.15	1
90R13 140-145	1	16	88	86	.6	10	7	502	2.26	11	5	ND	8	96	.3	3	2	8	2.38	.053	13	27	.84	60	.01	6	1.02	.02	.17	1
90R13 145-150	1	27	107	98	1.1	13	8	536	2.50	8	5	ND	8	71	.3	4	2	10	2.07	.059	16	40	.96	41	.01	5	1.25	.02	.17	1
STANDARD C	18	57	40	132	7.1	72	31	1053	3.95	42	22	7	38	53	19.1	15	22	56	.46	.096	38	59	.89	181	.07	36	1.89	.06	.13	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R14 0-5	2	17	24	55	.6	9	7	402	1.28	5	5	ND	11	22	.2	2	2	5	.23	.037	19	29	.64	379	.02	2	.77	.01	.19	1
90R14 5-10	2	17	18	72	.2	15	7	435	1.64	4	5	ND	10	30	.5	2	2	8	.30	.043	22	40	.92	350	.03	2	1.04	.02	.27	1
90R14 10-15	3	25	16	56	.4	13	8	498	1.31	3	5	ND	8	48	.3	2	2	6	.32	.036	17	43	.81	571	.01	3	.85	.02	.30	1
90R14 15-20	2	33	33	95	2.3	18	10	546	1.33	3	5	5	7	34	.4	2	2	4	.34	.029	10	51	.81	377	.01	2	.68	.01	.22	1
90R14 20-25	3	34	76	155	.9	22	14	571	3.02	4	5	ND	3	23	.2	3	2	11	.18	.062	5	93	1.78	74	.01	4	1.34	.01	.22	1
90R14 25-30	4	20	20	74	.9	9	6	333	1.01	5	5	ND	10	23	.2	2	2	1	.14	.020	12	45	.53	393	.01	2	.57	.01	.19	1
90R14 30-35	6	88	319	64	4.2	6	3	319	.61	6	5	ND	10	23	.7	2	2	1	.07	.008	12	59	.26	804	.01	2	.36	.01	.14	1
90R14 35-40	5	61	40	58	.3	5	4	332	.64	7	5	ND	13	10	.3	2	2	1	.06	.010	17	58	.31	438	.01	2	.57	.01	.20	1
90R14 40-45	2	53	24	159	.4	16	13	667	2.10	16	5	ND	5	49	.2	2	2	5	.54	.054	7	60	1.18	141	.01	2	1.13	.01	.15	1
90R14 45-50	6	44	60	90	.5	15	9	218	2.12	6	5	ND	6	22	.2	2	2	3	.19	.052	7	51	.52	48	.01	2	.77	.01	.20	1
90R14 50-55	4	69	23	84	.3	10	6	186	2.08	7	5	ND	5	31	.2	2	2	2	.16	.057	7	41	.61	101	.01	2	.73	.01	.19	1
90R14 55-60	4	36	41	101	.4	8	5	384	1.77	9	5	ND	6	17	.2	2	2	2	.16	.045	8	42	.71	156	.01	2	.79	.01	.15	1
90R14 60-65	3	56	33	97	.7	9	6	201	1.78	6	5	ND	7	18	.2	2	2	2	.15	.041	8	38	.78	131	.01	2	.80	.01	.16	1
90R14 65-70	4	133	76	124	1.1	16	8	200	1.87	3	5	ND	6	30	.2	2	2	2	.17	.041	10	42	.88	122	.01	2	.83	.01	.19	1
90R14 70-75	4	47	21	93	.9	16	9	208	2.18	6	5	ND	6	39	.2	2	2	3	.26	.048	9	45	.63	101	.01	2	.76	.01	.21	1
90R14 75-80	4	45	32	59	1.4	14	8	323	1.82	8	5	2	6	34	.2	2	2	2	.37	.043	7	35	.48	54	.01	2	.59	.01	.16	1
90R14 80-85	3	39	7	50	1.1	13	9	806	1.86	6	5	2	4	84	.2	2	2	3	1.96	.058	6	39	.77	95	.01	2	.58	.01	.22	1
90R14 85-90	3	27	39	77	1.0	18	10	534	1.97	15	5	ND	6	31	.2	2	2	2	.58	.067	10	25	.53	69	.01	2	.76	.01	.17	1
90R14 90-95	3	33	11	23	.5	13	10	702	1.64	15	5	ND	8	52	.2	2	2	2	2.04	.069	10	31	.15	46	.01	2	.48	.01	.22	1
90R14 95-100	2	61	18	60	1.0	15	10	571	2.29	29	5	ND	8	60	.2	2	2	2	1.76	.067	13	26	.33	34	.01	2	.61	.01	.23	1
90R14 100-105	3	39	14	107	.6	19	10	520	2.44	29	5	ND	6	87	.2	2	2	5	2.02	.047	14	74	.95	43	.01	2	.98	.01	.19	1
90R14 105-110	3	18	231	144	1.2	8	4	264	.93	10	5	ND	13	31	.9	2	2	1	.50	.026	16	41	.23	123	.01	3	.40	.02	.18	1
90R14 110-115	2	14	67	121	.4	8	5	226	1.20	7	5	ND	10	35	.2	2	2	1	.43	.037	10	31	.11	93	.01	2	.33	.03	.17	1
90R14 115-120	3	14	25	172	.2	11	7	316	1.10	3	5	ND	10	32	1.1	2	2	1	.57	.033	11	40	.29	80	.01	3	.47	.01	.22	1
90R14 120-125	5	8	29	156	.2	7	5	258	.91	5	5	ND	10	26	.5	2	2	1	.50	.024	13	60	.13	133	.01	2	.33	.01	.18	2
90R14 125-130	2	34	113	103	.2	5	4	133	.78	5	5	ND	15	17	1.9	2	2	1	.31	.020	15	22	.06	167	.01	2	.28	.02	.18	1
90R14 130-135	3	10	70	57	.1	4	2	100	.46	3	5	ND	17	21	.6	2	2	1	.26	.013	17	27	.06	325	.01	2	.31	.02	.19	1
90R14 135-140	3	8	38	24	.2	4	3	206	.43	2	5	ND	15	35	.2	2	2	1	.60	.013	15	25	.14	410	.01	2	.34	.03	.18	2
90R14 140-145	2	20	2	80	.2	10	6	607	1.20	21	5	ND	7	68	.2	2	2	3	1.78	.042	8	28	.75	130	.01	2	.74	.01	.20	1
90R14 145-150	3	44	6	79	.3	12	7	659	1.54	35	5	ND	5	79	.2	2	2	3	2.56	.046	7	29	.71	65	.01	2	.71	.01	.20	1
STANDARD C	18	60	39	131	7.3	72	32	1087	3.97	44	18	8	36	50	18.5	14	18	56	.50	.098	37	61	.90	181	.08	32	1.91	.06	.14	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R15 0-5	5	46	69	44	.9	7	1	313	1.70	18	5	ND	8	128	.5	2	2	5	.13	.039	12	54	.61	355	.01	5	.75	.01	.26	2
90R15 5-10	3	72	55	119	1.2	9	2	533	2.68	73	5	ND	9	134	.2	2	2	7	.04	.067	16	40	1.72	198	.01	9	1.65	.01	.22	1
90R15 10-15	4	76	62	78	1.9	7	2	219	1.67	30	5	ND	9	44	.4	2	2	7	.02	.045	16	56	.89	578	.01	7	1.18	.02	.29	2
90R15 15-20	6	49	96	49	1.1	5	1	174	1.61	12	5	ND	10	47	.2	2	2	3	.03	.051	13	39	.66	226	.01	7	.81	.02	.23	1
90R15 20-25	6	66	131	61	1.3	4	1	128	1.69	9	5	ND	10	44	.2	2	2	3	.01	.054	13	40	.72	211	.01	8	.91	.02	.27	1
90R15 25-30	4	62	42	59	.7	6	2	104	1.75	7	5	ND	10	99	.2	2	2	4	.01	.047	13	50	.51	523	.01	8	.93	.03	.34	1
90R15 30-35	3	43	41	63	.7	8	4	162	1.61	14	5	ND	9	149	.2	2	2	4	.03	.050	16	45	.38	300	.01	6	.89	.01	.31	1
90R15 35-40	3	39	12	68	.5	13	8	399	2.03	20	5	ND	7	40	.4	2	2	6	.37	.062	10	40	.36	236	.01	6	.72	.02	.25	1
90R15 40-45	4	26	45	31	1.7	8	3	171	1.68	10	5	ND	9	49	.2	2	2	5	.32	.069	13	49	.14	345	.01	8	.50	.05	.31	1
90R15 45-50	4	13	39	20	.9	5	2	58	1.31	7	5	ND	10	41	.2	2	2	4	.05	.040	14	40	.06	332	.01	6	.31	.05	.26	1
90R15 50-55	4	17	21	31	.4	12	8	383	1.52	3	5	ND	8	35	.8	2	2	3	.58	.059	10	34	.02	44	.01	5	.33	.04	.23	2
90R15 55-60	3	21	13	32	.7	9	6	386	1.88	5	5	ND	8	61	.2	2	2	7	.93	.062	10	41	.26	173	.02	7	.49	.04	.26	3
90R15 60-65	3	21	13	58	.4	13	9	708	1.94	4	5	ND	9	79	.7	2	2	7	1.65	.063	11	38	.48	173	.01	6	.71	.02	.24	1
90R15 65-70	3	25	11	81	.5	16	9	650	1.93	18	5	ND	9	94	.2	2	2	6	1.43	.068	15	53	.82	132	.01	7	.96	.03	.27	1
90R15 70-75	2	22	11	78	.5	15	8	644	2.07	16	5	ND	9	101	.4	2	2	7	1.52	.066	13	38	.94	98	.03	6	.97	.02	.25	1
90R15 75-80	2	21	16	59	.5	11	9	616	1.65	5	5	ND	8	85	.2	2	2	5	1.68	.068	10	36	.67	91	.02	9	.73	.02	.25	2
90R15 80-85	3	20	16	33	.9	10	8	373	1.45	4	5	ND	8	46	.4	2	2	4	.94	.060	11	39	.27	62	.01	5	.50	.03	.24	1
90R15 85-90	4	22	19	30	.3	13	8	420	1.36	3	5	ND	10	49	1.0	2	2	3	1.48	.060	11	39	.20	52	.01	5	.43	.03	.23	2
90R15 90-95	3	23	22	60	.4	11	9	477	1.73	3	5	ND	7	47	.5	2	2	4	1.50	.054	7	35	.49	55	.01	8	.62	.02	.18	1
90R15 95-100	3	16	14	38	.4	9	7	406	1.60	12	5	ND	9	47	.6	2	2	4	1.13	.055	19	49	.21	60	.01	7	.52	.04	.26	2
90R15 100-105	2	29	14	45	.4	11	9	553	2.62	3	5	ND	10	59	.2	2	2	6	1.41	.053	24	36	.27	31	.01	8	.51	.03	.21	3
90R15 105-110	3	34	27	57	.6	15	9	558	1.95	8	5	ND	7	64	.3	2	2	4	1.70	.058	13	31	.55	52	.01	6	.63	.02	.20	2
90R15 110-115	4	59	13	76	.6	16	9	563	2.03	6	5	ND	7	79	.4	2	2	6	1.80	.060	19	46	.64	46	.01	7	.77	.02	.25	1
90R15 115-120	2	21	17	68	.4	14	9	521	1.75	3	5	ND	7	59	.8	2	2	5	1.18	.062	18	41	.42	51	.01	8	.63	.02	.25	1
90R15 120-125	3	18	16	27	.3	9	8	578	1.21	5	5	ND	8	57	.4	2	2	3	1.64	.042	19	41	.20	72	.01	4	.48	.02	.27	1
90R15 125-130	3	18	20	27	.3	12	9	583	2.06	12	5	ND	7	48	.7	2	2	3	1.37	.054	15	33	.23	41	.01	7	.42	.02	.22	2
90R15 130-135	4	24	14	57	.4	10	7	779	1.54	28	5	ND	7	57	.6	2	2	3	1.15	.044	14	40	.48	97	.01	6	.63	.02	.24	2
90R15 135-140	2	18	16	73	.5	13	10	721	1.74	43	5	ND	7	57	.6	2	2	5	1.21	.071	20	47	.50	109	.01	6	.77	.01	.32	1
90R15 140-145	1	25	20	59	.6	9	8	509	1.40	28	5	ND	7	56	.7	2	2	3	1.18	.055	19	30	.29	96	.01	6	.47	.01	.21	1
90R15 145-150	2	17	13	43	.4	10	8	338	1.45	28	5	ND	8	38	.9	2	2	3	.91	.048	16	38	.21	110	.01	4	.49	.02	.25	2
STANDARD C	19	62	42	132	7.6	72	32	1045	3.98	44	19	6	38	52	19.0	16	19	57	.46	.096	37	61	.87	180	.07	40	1.89	.06	.13	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R16 0-5	3	36	11	24	.6	5	2	75	1.90	11	5	ND	8	86	.2	4	2	3	.04	.059	12	48	.09	144	.01	4	.34	.04	.22	1
90R16 5-10	3	12	14	19	.5	6	2	36	1.66	6	5	ND	9	50	.2	2	2	4	.03	.045	10	41	.04	133	.01	5	.26	.05	.22	1
90R16 10-15	5	9	43	14	.5	7	1	32	1.73	8	5	ND	9	91	.2	2	2	4	.01	.052	12	54	.03	114	.01	3	.28	.09	.19	1
90R16 15-20	4	16	17	27	.8	5	2	40	1.94	13	5	ND	9	97	.2	2	2	4	.02	.072	14	55	.04	335	.01	4	.30	.06	.19	1
90R16 20-25	3	32	28	28	.5	6	3	29	1.55	8	5	ND	9	46	.2	2	2	3	.02	.066	14	30	.02	375	.01	2	.25	.04	.18	1
90R16 25-30	6	47	28	67	.7	9	2	132	2.28	26	5	ND	8	74	.2	2	2	5	.02	.071	14	79	.20	255	.01	3	.65	.03	.18	1
90R16 30-35	4	81	20	116	1.4	11	6	346	2.04	15	5	2	9	72	.2	3	2	6	.09	.072	16	56	.45	202	.01	3	.95	.02	.22	1
90R16 35-40	2	39	16	115	.5	17	12	533	1.88	10	6	ND	9	25	.4	2	2	5	.10	.068	15	36	.48	279	.01	3	.84	.02	.16	1
90R16 40-45	3	28	18	50	.8	7	3	86	1.32	7	5	ND	10	29	.2	2	2	4	.03	.049	18	52	.15	666	.01	2	.51	.03	.19	1
90R16 45-50	2	36	10	65	.4	12	4	217	1.75	23	5	ND	12	49	.2	2	2	5	.06	.058	21	46	.28	352	.01	2	.75	.02	.24	1
90R16 50-55	3	31	12	63	.2	10	7	460	1.35	6	5	ND	9	41	.2	2	2	5	.75	.049	13	44	.28	270	.01	2	.59	.02	.17	1
90R16 55-60	3	23	16	62	.2	12	8	482	1.79	5	5	ND	9	63	.2	2	2	7	1.10	.050	12	42	.30	156	.01	3	.60	.02	.17	1
90R16 60-65	2	13	20	22	.1	7	6	343	1.00	2	5	ND	10	53	.3	2	2	3	1.14	.047	11	31	.14	91	.01	2	.38	.02	.19	1
90R16 65-70	2	12	21	23	.3	6	6	273	.90	3	5	ND	8	55	.2	2	2	3	.89	.045	11	22	.14	133	.01	2	.35	.02	.18	1
90R16 70-75	1	15	9	33	.1	7	6	456	1.59	3	5	ND	9	60	.3	2	2	5	.99	.044	10	23	.18	42	.01	2	.41	.02	.19	1
90R16 75-80	2	21	16	32	.2	8	7	332	1.15	2	5	ND	9	60	.4	2	2	5	.94	.044	11	22	.20	57	.01	2	.42	.02	.19	2
90R16 80-85	2	36	9	28	.4	7	7	405	1.34	2	5	ND	8	68	.2	2	2	5	1.09	.048	9	28	.21	55	.01	2	.47	.03	.22	1
90R16 85-90	2	50	7	32	.5	7	6	344	1.38	7	5	ND	9	64	.2	2	2	5	.96	.045	11	38	.23	34	.01	2	.53	.03	.25	1
90R16 90-95	4	25	36	51	.3	10	7	572	1.62	9	5	ND	8	84	.3	2	2	5	1.69	.049	11	32	.42	33	.01	2	.61	.03	.21	1
90R16 95-100	2	30	31	95	.6	14	8	755	2.22	69	5	ND	10	49	.6	2	2	8	.85	.058	16	52	.33	22	.01	2	.63	.02	.22	1
90R16 100-105	3	40	51	100	.8	12	7	752	1.79	44	5	ND	9	57	.8	2	2	7	1.64	.060	13	37	.23	28	.01	2	.53	.02	.22	1
90R16 105-110	3	41	25	73	.7	13	8	723	1.96	20	5	ND	9	68	.6	2	2	9	1.87	.058	12	38	.28	27	.01	3	.64	.02	.22	1
90R16 110-115	2	32	18	53	.5	12	9	560	1.89	5	5	ND	8	72	.2	2	2	8	1.67	.060	11	31	.24	38	.01	2	.57	.02	.21	1
90R16 115-120	1	47	16	66	.1	12	7	547	1.77	7	5	ND	9	67	.3	2	2	6	1.52	.056	9	22	.27	76	.01	3	.55	.02	.15	1
90R16 120-125	2	16	11	61	.3	10	7	396	1.66	7	5	ND	11	70	.2	2	2	7	1.39	.053	15	27	.33	72	.01	2	.57	.03	.15	1
90R16 125-130	3	18	14	87	.3	16	10	513	2.54	4	5	ND	9	105	.2	2	2	7	1.79	.054	13	51	.45	22	.01	2	.64	.02	.15	1
90R16 130-135	3	21	13	61	.5	17	11	505	2.44	6	5	ND	8	94	.2	2	2	7	1.92	.060	8	53	.52	12	.01	2	.58	.02	.15	1
90R16 135-140	4	18	23	94	.2	18	9	579	2.05	5	5	ND	9	76	.2	2	2	10	1.69	.054	14	75	.87	40	.02	2	.94	.02	.14	1
90R16 140-145	2	21	19	89	.2	17	9	611	2.41	14	5	ND	9	61	.2	2	2	10	1.73	.058	16	50	.80	68	.01	2	1.00	.02	.12	1
90R16 145-150	2	21	17	89	.2	20	11	622	2.58	10	5	ND	8	69	.2	2	2	9	2.49	.054	16	87	.85	64	.01	2	1.11	.02	.11	1
STANDARD C	18	58	36	132	7.3	73	31	1054	3.95	44	21	7	40	55	19.4	15	17	57	.46	.100	40	60	.90	187	.07	36	1.89	.06	.14	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R17 0-5	4	30	21	117	.5	18	12	688	1.89	3	5	ND	10	19	.2	2	2	7	.30	.066	18	57	.85	309	.03	15	1.01	.03	.22	1
90R17 5-10	3	25	19	96	.3	18	11	574	1.58	5	5	ND	8	21	.2	2	2	8	.40	.062	13	49	.85	170	.06	12	.88	.03	.19	1
90R17 10-15	3	80	210	175	.8	22	32	1407	1.74	13	5	ND	8	32	.2	2	2	8	.65	.071	13	48	.92	140	.04	6	.99	.02	.20	1
90R17 15-20	2	39	42	81	.4	13	12	698	1.54	3	5	ND	6	52	.2	2	2	6	1.16	.068	8	34	.81	175	.04	4	.75	.02	.27	2
90R17 20-25	3	56	11	51	.9	11	8	641	1.76	6	5	ND	6	57	.2	2	2	4	1.52	.064	6	34	.66	168	.03	6	.65	.02	.30	2
90R17 25-30	5	51	45	72	.5	11	9	590	1.75	5	5	ND	6	50	.2	2	2	3	1.89	.063	5	36	.53	68	.02	4	.54	.02	.31	1
90R17 30-35	3	25	19	94	.3	12	10	613	1.99	3	5	ND	8	45	.2	2	2	4	1.56	.065	7	36	.59	77	.03	6	.64	.02	.27	1
90R17 35-40	3	19	16	43	.3	13	9	322	1.68	2	5	ND	8	34	.2	2	2	3	.97	.066	10	29	.23	66	.01	5	.42	.03	.25	4
90R17 40-45	2	20	13	55	.3	11	9	522	1.53	5	5	ND	8	35	.2	2	2	5	.88	.067	10	38	.47	284	.02	3	.62	.03	.33	1
90R17 45-50	3	35	19	83	.7	10	10	675	1.97	4	5	ND	6	45	.2	2	2	9	1.17	.070	9	51	.71	234	.06	7	.76	.03	.42	1
90R17 50-55	5	30	23	90	1.2	13	9	699	1.74	18	5	ND	5	59	.2	2	2	5	1.47	.068	6	69	.49	76	.02	4	.52	.03	.31	1
90R17 55-60	4	48	22	90	.6	12	10	831	2.06	9	5	ND	5	79	.5	2	2	5	2.16	.076	4	60	.64	99	.03	4	.62	.02	.37	1
90R17 60-65	4	148	24	91	.2	12	9	422	1.50	6	5	ND	6	36	.2	2	2	3	1.02	.070	6	40	.51	141	.03	4	.54	.03	.26	3
90R17 65-70	3	46	21	73	.4	12	9	393	1.57	4	5	ND	6	34	.2	2	2	3	1.07	.073	6	39	.42	101	.03	3	.47	.03	.25	2
90R17 70-75	3	54	69	151	.5	15	10	706	1.98	4	5	ND	8	38	.2	2	2	2	1.28	.073	7	33	.53	136	.02	3	.56	.02	.23	1
90R17 75-80	8	22	60	56	.6	19	10	629	2.03	5	5	ND	7	24	.2	2	2	1	.84	.051	7	43	.45	67	.01	5	.53	.02	.24	1
90R17 80-85	4	21	21	87	.4	14	7	444	1.57	3	5	ND	7	23	.2	2	2	1	.72	.047	8	41	.37	128	.01	3	.49	.01	.24	1
90R17 85-90	6	29	53	144	.6	11	9	595	1.83	8	5	ND	6	21	.2	2	2	2	.24	.068	10	51	.12	259	.01	2	.42	.03	.27	1
90R17 90-95	3	71	32	150	.7	16	9	538	2.03	4	5	ND	5	37	.2	2	2	2	.58	.064	6	49	.59	58	.01	4	.61	.02	.23	1
90R17 95-100	4	85	128	134	.7	11	4	188	1.78	7	5	ND	7	18	.2	2	2	1	.13	.042	11	47	.82	246	.01	3	.87	.02	.23	1
90R17 100-105	6	92	47	123	.6	12	6	245	1.96	5	5	ND	6	28	.2	2	2	1	.18	.060	10	53	.98	118	.01	6	.96	.01	.24	1
90R17 105-110	4	89	29	105	5.4	12	6	375	1.75	9	5	4	5	67	.5	2	2	1	.58	.039	7	51	.72	156	.01	5	.64	.01	.22	1
90R17 110-115	5	59	43	76	.5	16	10	292	1.92	9	5	ND	5	31	.2	2	2	1	.46	.065	6	44	.62	57	.01	4	.62	.01	.26	1
90R17 115-120	4	22	21	41	.3	10	8	680	1.58	4	5	ND	5	57	.2	2	2	1	1.31	.062	6	41	.58	65	.01	3	.40	.02	.24	1
90R17 120-125	5	25	53	73	.4	12	8	540	1.78	5	5	ND	5	55	.2	2	2	1	1.29	.047	6	58	.51	66	.01	4	.44	.02	.28	1
90R17 125-130	4	27	39	122	.9	12	8	559	1.63	8	5	ND	5	55	.2	2	2	2	1.03	.043	7	48	.46	101	.01	3	.48	.02	.27	1
90R17 130-135	5	49	90	331	.4	12	6	408	1.68	20	5	ND	7	44	3.3	2	2	1	.50	.062	10	44	.23	96	.01	2	.52	.02	.32	1
90R17 135-140	4	41	115	261	.6	15	9	1016	1.87	7	5	ND	7	40	2.3	2	2	3	1.20	.057	7	47	.44	82	.01	5	.58	.01	.25	1
90R17 140-145	3	22	31	75	.4	11	8	733	1.57	2	5	ND	5	56	.2	2	2	2	1.96	.048	4	41	.29	76	.01	2	.43	.01	.24	1
90R17 145-150	4	26	40	87	.3	13	8	623	1.94	3	5	ND	4	93	.2	2	2	4	1.89	.049	4	53	.80	60	.01	2	.67	.02	.25	2
STANDARD C	20	62	40	131	7.3	72	32	1045	3.98	41	19	6	36	52	18.5	14	18	58	.46	.095	36	55	.87	180	.07	38	1.90	.06	.13	13

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#13020 File # 90-6068 Page 1

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R18 0-5	12	39	143	99	.5	12	7	383	2.19	4	6	ND	6	20	.2	2	2	15	.11	.042	24	145	.51	343	.02	2	.84	.02	.16	1
90R18 5-10	8	28	113	76	.4	12	7	329	1.68	2	5	ND	2	16	.2	2	2	13	.10	.048	19	102	.37	310	.01	2	.67	.01	.13	1
90R18 10-15	9	23	26	51	.2	16	8	418	1.55	2	5	ND	8	18	.2	2	2	6	.15	.057	16	111	.31	351	.01	2	.51	.02	.17	1
90R18 15-20	8	28	28	82	.3	20	11	531	1.85	5	5	ND	8	15	.3	2	2	5	.13	.063	13	94	.47	308	.01	2	.61	.01	.15	1
90R18 20-25	8	40	16	90	.5	20	15	903	2.00	2	5	ND	9	25	.6	2	2	5	.22	.068	17	98	.29	223	.01	2	.54	.02	.19	1
90R18 25-30	10	43	52	110	.6	18	10	727	2.13	2	5	ND	8	34	.6	2	2	6	.71	.065	12	87	.77	188	.01	2	.75	.02	.17	1
90R18 30-35	9	32	14	92	.5	16	9	707	2.05	4	5	ND	8	45	.4	2	2	7	1.04	.061	12	93	.53	196	.01	2	.66	.02	.21	1
90R18 35-40	9	30	14	57	1.0	9	5	477	1.81	2	5	ND	8	53	.2	2	2	6	.95	.058	11	105	.38	242	.01	2	.49	.02	.18	1
90R18 40-45	7	28	8	76	.3	13	8	726	1.89	9	5	ND	7	54	.5	2	2	8	1.28	.060	11	89	.53	229	.01	2	.64	.02	.20	1
90R18 45-50	8	38	16	65	.3	14	8	710	2.04	4	5	ND	7	86	.4	2	2	5	1.91	.060	7	77	.68	79	.01	2	.57	.02	.19	1
90R18 50-55	8	45	21	99	.7	13	7	532	2.13	7	6	ND	9	31	.2	2	2	6	.46	.062	13	77	.57	248	.01	2	.66	.02	.17	1
90R18 55-60	8	35	7	63	.8	13	7	739	2.20	19	5	ND	7	64	.6	2	2	6	1.54	.063	8	93	.67	129	.01	2	.57	.01	.19	1
90R18 60-65	8	31	6	60	.2	14	7	645	2.00	2	5	ND	6	83	.6	2	2	5	2.06	.055	7	93	.81	122	.01	2	.61	.02	.22	1
90R18 65-70	8	34	8	52	.9	14	8	604	2.09	4	5	2	7	50	.4	2	2	5	1.14	.063	9	97	.44	124	.01	2	.54	.02	.21	1
90R18 70-75	6	26	11	40	.4	14	8	682	2.00	10	5	ND	7	69	.3	2	2	5	1.95	.064	6	67	.50	108	.01	2	.49	.02	.20	2
90R18 75-80	10	46	15	67	.6	16	9	717	2.05	2	5	ND	8	55	.5	2	2	5	1.87	.058	7	104	.55	71	.01	2	.51	.02	.20	1
90R18 80-85	7	39	16	73	.3	15	8	758	2.05	5	5	ND	7	75	.6	2	2	4	2.42	.059	6	72	.69	90	.01	2	.51	.01	.18	1
90R18 85-90	8	25	23	52	.2	13	8	640	1.61	2	5	ND	8	63	.3	2	2	3	1.51	.057	8	84	.49	160	.01	2	.49	.01	.19	1
90R18 90-95	6	29	4	52	.5	15	8	673	1.71	2	5	ND	6	75	.6	2	2	4	1.42	.061	9	73	.59	166	.01	2	.56	.02	.17	1
90R18 95-100	6	35	8	43	.9	16	8	705	2.09	4	5	ND	6	80	.4	2	2	5	1.66	.066	7	72	.66	97	.01	2	.53	.02	.17	1
90R18 100-105	8	67	62	70	2.3	18	11	767	2.77	2	5	3	6	74	1.1	2	2	6	1.51	.088	6	89	.61	84	.01	3	.59	.02	.21	1
90R18 105-110	7	60	56	68	2.1	16	10	730	2.58	4	5	4	5	72	1.1	2	2	6	1.44	.085	6	85	.58	90	.01	2	.59	.02	.22	1
90R18 110-115	8	25	11	47	1.7	11	4	212	2.41	2	6	ND	9	83	.3	2	2	6	.31	.085	11	104	.24	257	.01	2	.46	.03	.23	1
90R18 115-120	7	34	7	59	2.2	12	9	225	2.55	2	5	4	7	45	.3	2	2	6	.20	.087	10	89	.20	179	.01	2	.43	.03	.22	1
90R18 120-125	9	38	6	44	2.7	12	9	618	2.24	3	5	5	6	66	.4	2	2	5	1.11	.083	7	104	.37	84	.01	2	.47	.02	.23	1
90R18 125-130	9	24	28	52	.4	13	8	593	1.76	2	5	ND	8	63	.3	2	2	4	1.41	.061	8	97	.48	75	.01	3	.43	.02	.19	1
90R18 130-135	7	23	8	50	.2	11	7	661	1.74	8	5	ND	8	81	.6	2	2	3	2.04	.053	7	77	.65	111	.01	3	.44	.02	.21	1
90R18 135-140	13	22	15	60	1.3	16	7	513	2.05	9	5	ND	7	45	.6	2	2	3	.57	.051	7	144	.21	72	.01	3	.30	.03	.17	1
90R18 140-145	11	35	18	107	1.0	15	7	317	2.10	20	5	ND	8	25	.7	2	2	4	.26	.065	10	121	.28	145	.01	2	.51	.02	.21	1
90R18 145-150	7	26	9	116	1.2	12	6	505	1.94	8	5	2	9	66	1.0	2	2	4	.81	.057	11	84	.31	167	.01	2	.45	.03	.19	1
90R18 150-155	9	22	31	110	1.9	7	3	123	1.82	15	5	4	10	64	.4	2	2	4	.11	.046	17	106	.14	359	.01	2	.38	.04	.18	1
90R18 155-160	6	28	34	88	.8	8	4	165	1.96	14	5	ND	10	97	.3	2	2	4	.16	.055	14	70	.18	228	.01	2	.40	.03	.21	1
90R18 160-165	16	20	39	87	.6	6	1	142	2.16	21	5	ND	6	80	.5	2	2	5	.07	.046	11	195	.12	261	.01	2	.28	.03	.18	1
90R18 165-170	9	25	68	124	.3	8	2	236	2.61	22	5	ND	8	137	.4	2	2	9	.11	.062	17	118	.23	276	.01	2	.52	.03	.27	1
90R18 170-175	5	21	25	112	.3	15	9	562	2.63	19	5	ND	7	77	.9	2	2	6	1.45	.060	10	72	.48	79	.01	2	.50	.02	.16	1
90R18 175-180	7	18	13	92	.2	13	6	484	2.10	3	5	ND	8	78	.5	2	2	4	1.69	.054	10	80	.72	107	.01	3	.70	.02	.17	1
STANDARD C	21	61	40	133	7.5	74	32	1060	3.97	44	17	8	37	56	19.7	15	21	61	.50	.095	38	61	.84	180	.08	35	1.90	.05	.14	11

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: NOV 26 1990 **DATE REPORT MAILED:** Nov 29/90. **SIGNED BY** ..... D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R18 180-185	9	22	16	81	.8	12	7	569	2.18	6	5	ND	6	88	.2	2	2	2	1.73	.057	5	95	.67	89	.01	4	.69	.03	.18	1
90R18 185-190	7	24	12	61	.2	13	8	521	2.10	7	5	ND	6	83	.2	2	2	3	1.68	.060	6	85	.52	89	.01	4	.66	.03	.21	1
90R18 190-195	7	23	25	64	.3	14	9	416	1.89	6	5	ND	8	72	.2	2	2	3	1.23	.061	7	82	.42	82	.01	3	.60	.03	.21	1
90R18 195-200	6	22	26	56	1.0	11	8	404	1.82	23	5	ND	7	67	.2	2	2	2	.75	.056	10	73	.37	105	.01	2	.55	.03	.21	1
90R18 200-205	9	21	25	60	.3	12	8	443	1.68	5	5	ND	8	80	.4	2	2	3	1.06	.047	9	105	.33	113	.01	2	.53	.03	.20	1
90R18 205-210	8	19	28	41	.1	14	10	419	1.79	17	5	ND	8	73	.3	2	2	3	1.31	.049	8	98	.41	98	.01	5	.57	.03	.18	1
90R18 210-215	11	22	42	127	1.1	27	15	624	2.84	10	5	2	4	82	.9	2	2	5	1.72	.058	5	147	.93	86	.01	4	.95	.02	.14	1
90R18 215-220	8	18	46	82	.1	18	11	409	2.05	6	5	ND	6	50	.4	2	2	4	.85	.053	12	101	.54	150	.01	3	.71	.02	.16	1
90R18 220-225	9	25	21	96	.2	20	13	601	2.38	17	5	ND	5	56	.6	2	2	5	1.33	.057	15	160	.76	94	.01	4	.92	.02	.17	1
90R18 225-230	10	26	47	102	.4	23	14	631	2.70	23	5	ND	5	53	.2	2	2	8	1.28	.060	12	183	.81	55	.01	4	.94	.03	.16	1
90R18 230-235	6	22	34	130	.2	21	13	633	2.88	22	5	ND	5	47	.6	2	2	8	1.13	.063	13	116	.76	81	.01	4	.96	.02	.16	1
90R18 235-240	6	23	32	166	.3	19	12	620	2.65	7	5	ND	5	59	.3	2	2	6	1.74	.058	15	95	.77	111	.01	4	1.04	.02	.14	1
90R18 240-245	7	31	13	120	.3	22	13	537	2.69	10	5	ND	8	58	.4	2	2	6	1.53	.056	20	100	.99	115	.01	5	1.20	.02	.14	1
90R18 245-250	5	33	29	165	.4	21	14	963	2.83	29	5	ND	4	88	.7	2	2	6	2.71	.054	14	130	1.29	89	.01	5	1.36	.01	.12	1
90R18 250-255	10	45	129	485	.4	22	12	941	2.71	19	5	ND	4	84	5.0	2	2	4	2.59	.054	15	125	1.21	85	.01	4	1.26	.02	.15	1
90R18 255-260	7	26	40	513	.3	17	10	659	2.16	12	5	ND	6	62	3.5	2	2	4	1.53	.055	19	84	.83	85	.01	3	1.01	.02	.16	1
90R18 260-265	5	29	189	580	.5	21	10	520	2.19	38	8	ND	8	34	5.1	2	2	6	.70	.057	22	106	.73	121	.01	3	.95	.02	.20	1
90R18 265-270	5	155	826	663	2.1	21	9	377	2.16	45	11	ND	8	64	7.0	2	2	7	.31	.055	28	139	.72	196	.01	4	.95	.02	.22	1
90R18 270-275	8	150	578	1032	1.7	13	7	474	1.96	31	5	ND	8	45	7.8	2	2	5	.28	.053	26	100	.41	177	.01	2	.72	.03	.22	1
90R18 275-280	8	672	2128	3544	5.5	18	12	626	2.86	39	5	ND	5	40	32.8	2	2	6	.67	.065	17	101	.48	44	.01	5	.73	.02	.20	1
90R18 280-285	10	49	750	859	1.3	11	6	368	1.80	29	5	ND	6	37	8.0	2	2	1	.66	.043	13	100	.25	60	.01	2	.48	.01	.17	1
90R18 285-290	10	15	367	300	.6	5	2	121	.83	24	5	ND	13	16	2.4	2	4	1	.27	.011	25	100	.10	137	.01	7	.33	.01	.16	1
90R18 290-295	9	8	126	149	.5	3	1	182	.55	17	5	ND	17	22	1.3	2	6	1	.42	.005	28	86	.11	285	.01	4	.29	.01	.16	1
90R18 295-300	12	9	54	79	.5	4	1	272	.63	40	5	ND	18	35	.6	2	6	1	.71	.006	33	120	.17	338	.01	5	.40	.01	.22	1
90R18 300-305	7	8	64	74	.4	2	1	240	.55	28	5	ND	16	32	.6	2	6	1	.65	.005	31	69	.14	327	.01	4	.29	.01	.16	1
90R18 305-310	8	8	65	57	.3	3	1	128	.49	18	5	ND	19	20	.6	2	7	1	.34	.005	37	77	.09	393	.01	4	.33	.01	.18	1
90R18 310-315	7	10	159	120	.4	3	1	64	.48	10	5	ND	17	13	1.1	2	7	1	.15	.005	38	73	.06	356	.01	4	.24	.01	.18	1
90R18 315-320	7	9	98	77	.3	2	1	101	.39	2	5	ND	18	22	.8	2	7	1	.34	.004	42	67	.08	236	.01	4	.31	.01	.22	3
90R18 320-325	9	10	96	88	.3	3	1	90	.42	4	5	ND	18	23	.7	2	6	1	.31	.005	39	79	.08	245	.01	4	.28	.01	.19	1
90R18 325-330	11	7	68	60	.2	3	1	101	.34	2	13	ND	18	20	.6	2	7	1	.22	.003	44	104	.13	205	.01	4	.38	.01	.25	1
90R18 330-335	10	8	53	39	.3	2	1	96	.50	4	5	ND	17	24	.3	2	6	1	.31	.005	39	96	.08	237	.01	4	.32	.01	.23	2
90R18 335-340	7	5	39	29	.2	3	1	51	.51	8	5	ND	16	28	.4	2	5	1	.29	.004	34	74	.05	271	.01	4	.28	.02	.21	6
90R18 340-345	9	10	38	28	.2	4	1	69	.50	5	5	ND	13	28	.4	2	5	1	.33	.005	31	93	.07	242	.01	6	.34	.01	.24	2
90R18 345-350	11	5	40	16	.2	3	1	38	.38	5	5	ND	9	28	.3	2	3	1	.43	.003	12	113	.07	334	.01	4	.37	.01	.23	1
90R18 350-355	10	5	70	78	.3	2	1	58	.38	5	5	ND	13	52	.3	2	4	1	.57	.004	22	97	.08	607	.01	4	.36	.02	.24	1
90R18 355-360	8	13	260	355	.8	2	1	72	.58	9	5	ND	9	28	.9	2	3	1	.33	.004	11	80	.06	258	.01	5	.31	.02	.21	2
STANDARD C	19	62	37	133	7.6	73	31	1056	3.98	42	16	8	38	52	18.6	18	21	55	.45	.094	36	58	.90	187	.08	39	1.90	.06	.13	12

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R18 360-365	16	8	240	319	.1	4	1	78	.59	5	5	ND	11	23	.8	2	2	1	.31	.003	33	177	.16	317	.01	3	.35	.01	.23	1
90R18 365-370	14	6	37	42	.1	3	7	74	.47	2	5	ND	9	41	.4	2	2	1	.46	.004	24	153	.17	360	.01	3	.35	.02	.21	25
90R18 370-375	14	6	42	34	.1	2	2	52	.42	2	5	ND	5	30	.2	2	2	1	.25	.005	12	146	.24	317	.01	3	.38	.01	.20	10
90R18 375-380	18	8	77	50	.2	4	1	105	.77	2	5	ND	11	47	.3	2	2	1	.68	.005	28	186	.46	277	.01	3	.48	.01	.20	1
90R18 380-385	12	10	60	48	.1	2	14	123	.64	2	5	ND	14	57	.5	2	2	1	.74	.005	38	122	.76	250	.01	3	.58	.01	.17	50
90R18 385-390	11	38	276	209	.1	8	16	160	1.24	28	5	ND	8	27	1.9	2	2	1	.37	.017	22	93	.18	45	.01	3	.32	.02	.14	60
90R18 390-395	9	32	102	71	.2	4	16	71	.64	12	5	ND	13	34	.6	2	2	1	.33	.006	31	85	.09	214	.01	4	.27	.02	.18	75
STANDARD C	20	62	37	133	7.4	73	32	1060	3.97	41	18	8	37	56	19.5	14	21	59	.48	.094	37	60	.87	180	.08	33	1.90	.06	.13	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R19 0-5	7	34	82	43	.7	4	2	135	1.90	9	5	ND	7	50	.2	3	3	4	.05	.042	14	60	.40	233	.01	7	.62	.02	.21	2
90R19 5-10	4	41	61	68	.7	9	2	163	2.09	12	5	ND	8	58	.2	2	2	6	.02	.050	14	70	.96	146	.01	8	.92	.01	.15	1
90R19 10-15	5	51	59	74	.8	8	3	129	2.11	7	5	ND	7	22	.2	2	2	5	.01	.036	13	66	.89	155	.01	10	.83	.01	.15	1
90R19 15-20	8	43	92	43	.9	4	1	89	1.97	10	5	ND	9	13	.2	2	2	4	.01	.042	16	40	.50	124	.01	8	.61	.01	.16	2
90R19 20-25	5	61	47	78	.9	13	9	378	2.09	13	5	ND	9	10	.3	2	2	4	.12	.061	11	37	.64	116	.01	9	.82	.01	.23	1
90R19 25-30	2	80	13	105	.4	16	12	737	1.79	4	5	ND	7	51	.7	2	2	5	.83	.067	8	35	.79	109	.01	7	.75	.01	.20	1
90R19 30-35	2	46	16	173	.3	21	14	1059	2.60	2	5	ND	6	79	.4	2	2	7	.97	.074	6	37	1.41	106	.01	9	1.20	.01	.19	1
90R19 35-40	6	79	69	131	.6	12	8	653	2.21	2	5	ND	8	48	.2	2	2	5	.86	.049	6	37	1.12	89	.01	10	.98	.01	.16	1
90R19 40-45	4	66	41	91	.6	13	9	728	1.87	4	5	ND	8	38	.6	2	2	4	.57	.053	9	37	.77	93	.01	8	.76	.01	.20	1
90R19 45-50	4	48	76	72	.6	11	7	356	1.65	3	5	ND	8	12	.5	2	2	3	.16	.055	9	33	.55	96	.01	7	.66	.01	.20	1
90R19 50-55	2	68	17	133	.3	19	11	1235	2.29	5	5	ND	7	17	.7	2	2	9	.25	.078	15	42	1.08	114	.01	9	1.12	.02	.23	1
90R19 55-60	2	57	15	147	.7	21	12	1047	2.42	3	5	ND	6	32	.2	2	2	9	.65	.086	13	38	1.21	92	.01	11	1.26	.01	.22	1
90R19 60-65	2	54	17	138	.7	16	12	865	3.13	2	5	ND	6	58	.2	2	2	11	1.35	.088	11	41	1.42	83	.01	10	1.37	.01	.19	2
90R19 65-70	1	78	13	167	.4	20	12	981	2.97	4	5	ND	7	17	.2	2	2	12	.27	.085	15	38	1.45	109	.01	9	1.50	.01	.23	1
90R19 70-75	1	78	15	119	.4	17	12	615	3.11	2	5	ND	5	68	.2	2	2	10	1.41	.084	8	32	1.26	99	.01	10	1.19	.01	.24	2
90R19 75-80	1	32	15	95	.4	15	11	679	2.92	3	5	ND	5	57	.4	2	2	9	1.32	.079	7	32	1.16	92	.01	11	1.08	.01	.21	1
90R19 80-85	1	55	12	82	.6	13	9	599	2.04	5	5	ND	6	70	.2	2	2	6	1.33	.069	6	31	.92	114	.01	10	.94	.01	.24	2
90R19 85-90	3	84	36	128	.5	11	7	614	1.95	11	5	ND	6	68	.2	2	2	5	1.25	.053	5	39	1.03	109	.01	10	.92	.01	.20	2
90R19 90-95	2	32	18	113	1.5	15	9	583	2.26	10	5	ND	6	119	.2	2	2	5	1.89	.078	7	36	1.22	94	.01	9	.92	.02	.19	1
90R19 95-100	5	103	119	119	1.4	12	7	521	1.81	10	5	ND	6	59	1.7	2	2	3	1.28	.051	6	31	.77	78	.01	9	.70	.01	.21	2
90R19 100-105	3	70	48	66	.9	11	7	456	1.53	14	5	ND	7	42	.4	2	2	4	1.15	.059	8	32	.53	115	.01	9	.60	.02	.22	1
90R19 105-110	2	37	16	50	.4	10	7	560	1.36	4	5	ND	7	59	.2	2	2	4	1.44	.060	11	32	.60	212	.01	8	.69	.02	.25	2
90R19 110-115	3	94	62	118	.8	13	10	626	2.03	25	5	ND	7	48	.5	2	2	5	.84	.059	10	47	.59	75	.01	8	.82	.02	.27	1
90R19 115-120	2	44	23	68	.7	11	8	682	1.43	28	5	ND	9	75	.2	2	2	3	1.21	.037	12	46	.57	70	.01	8	.75	.01	.26	1
90R19 120-125	2	33	7	91	.4	23	12	1049	2.13	36	5	ND	10	95	.7	2	2	6	1.57	.037	17	85	.81	60	.01	7	.75	.01	.22	1
90R19 125-130	3	40	20	48	.5	9	7	425	1.75	30	5	ND	10	41	.2	2	2	5	.39	.059	23	36	.21	136	.01	10	.48	.03	.25	2
90R19 130-135	3	68	23	57	.3	11	8	505	1.86	24	5	ND	9	40	.2	2	2	5	.81	.052	19	49	.35	106	.01	8	.61	.03	.26	1
90R19 135-140	3	45	20	78	.3	11	8	699	1.61	27	5	ND	8	62	.7	2	2	5	1.36	.050	19	46	.44	135	.01	8	.60	.02	.22	1
90R19 140-145	3	66	54	63	.1	2	2	167	.46	8	5	ND	15	17	.5	2	2	1	.28	.008	23	34	.14	254	.01	3	.37	.01	.19	1
90R19 145-150	3	39	43	23	.1	1	1	63	.21	2	5	ND	18	13	.2	2	2	1	.11	.002	25	26	.08	376	.01	4	.30	.02	.22	2
STANDARD C	20	61	44	133	7.3	73	32	1045	3.98	43	19	6	38	52	18.7	14	21	57	.46	.095	36	61	.87	180	.07	39	1.89	.06	.13	12

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R20 0-5	10	34	45	72	.3	15	9	582	2.31	7	5	ND	4	19	.4	2	2	15	.15	.051	17	112	.58	288	.02	3	1.14	.02	.18	4
90R20 5-10	10	38	43	57	.4	12	9	507	2.18	10	5	ND	4	28	.3	2	2	13	.09	.051	17	112	.46	701	.02	5	.96	.02	.15	4
90R20 10-15	10	51	29	66	.5	11	4	293	1.89	14	5	ND	8	32	.3	2	2	6	.08	.047	17	96	.27	348	.01	3	.66	.03	.22	1
90R20 15-20	12	51	74	59	.7	9	2	191	1.73	6	5	ND	9	38	.4	2	2	5	.10	.045	15	113	.29	230	.01	4	.65	.03	.26	1
90R20 20-25	8	41	55	82	.8	11	2	230	1.86	2	5	ND	9	38	.5	2	2	3	.13	.048	15	71	.36	229	.01	4	.69	.03	.23	1
90R20 25-30	15	59	65	66	1.5	16	9	438	2.05	6	5	ND	8	22	.3	2	2	5	.06	.037	16	134	.25	278	.01	4	.65	.03	.25	1
90R20 30-35	10	39	65	76	1.5	16	9	321	2.02	17	5	ND	8	12	.3	2	2	4	.10	.052	12	92	.29	107	.01	5	.70	.03	.25	2
90R20 35-40	7	75	27	99	2.5	20	12	811	1.95	21	5	ND	9	22	1.2	2	2	6	.34	.068	15	72	.57	120	.01	5	.92	.03	.29	1
90R20 40-45	7	60	17	96	1.3	18	10	337	1.93	12	5	ND	8	18	1.0	2	2	6	.23	.076	14	79	.38	99	.01	5	.82	.04	.26	1
90R20 45-50	9	41	46	96	1.3	19	10	146	1.77	23	5	ND	9	17	.7	2	2	6	.19	.065	12	82	.21	149	.01	4	.71	.04	.24	2
90R20 50-55	9	34	38	76	1.0	18	9	110	1.75	37	5	ND	9	15	.5	2	2	5	.21	.072	11	78	.19	76	.01	3	.61	.04	.19	1
90R20 55-60	7	26	20	65	.5	20	9	257	2.05	33	5	ND	9	31	1.0	2	2	5	.58	.076	11	64	.24	43	.01	4	.54	.05	.16	1
90R20 60-65	7	24	21	51	.2	16	9	139	1.53	8	5	ND	10	16	.5	2	2	4	.34	.071	11	70	.16	106	.01	4	.55	.04	.20	1
90R20 65-70	6	46	72	139	.6	17	9	773	2.35	27	5	ND	9	66	.9	2	2	5	1.71	.067	8	56	.77	97	.01	3	.92	.01	.20	1
90R20 70-75	9	82	202	312	1.0	16	9	829	2.90	20	5	ND	8	63	1.6	3	2	8	.96	.069	8	78	1.69	194	.01	4	1.65	.03	.21	1
90R20 75-80	9	137	189	305	1.6	16	9	863	3.15	2	5	ND	8	32	1.7	2	2	10	1.11	.074	8	72	1.92	140	.01	3	1.81	.02	.19	1
90R20 80-85	9	57	230	316	1.0	17	9	865	3.09	2	5	ND	8	27	1.7	3	2	10	1.20	.075	7	76	1.86	121	.01	4	1.75	.03	.18	1
90R20 85-90	8	114	181	315	1.3	14	9	843	2.81	3	5	ND	8	25	1.8	2	2	9	1.24	.069	6	62	1.72	126	.01	5	1.63	.03	.17	1
90R20 90-95	8	84	132	289	.7	16	9	982	2.89	2	5	ND	7	31	1.5	3	2	9	1.63	.067	6	82	1.75	68	.01	6	1.60	.02	.19	1
90R20 95-100	8	109	277	239	1.0	15	8	907	2.69	2	5	ND	8	32	1.6	3	2	8	1.36	.069	6	53	1.58	88	.01	4	1.49	.02	.19	1
90R20 100-105	7	48	57	166	.6	14	8	1003	2.45	20	5	ND	8	54	1.2	2	2	6	1.73	.069	7	73	1.34	69	.01	3	1.17	.02	.20	1
90R20 105-110	7	43	50	160	.3	13	8	1137	2.32	2	5	ND	6	59	1.2	2	2	6	2.06	.076	6	78	1.34	126	.01	3	1.06	.02	.18	1
90R20 125-130	6	52	41	140	.4	15	8	683	2.10	35	5	ND	7	66	.9	2	2	5	.99	.070	8	62	1.10	63	.01	2	.96	.01	.18	1
90R20 130-135	7	38	43	107	.7	16	9	533	2.14	334	5	ND	9	67	.6	2	2	5	.85	.066	8	64	.88	55	.01	5	.86	.02	.18	1
90R20 135-140	8	27	115	97	.6	18	10	462	2.26	168	5	ND	8	77	.6	2	2	5	.62	.067	9	54	.82	67	.01	4	.85	.02	.16	1
90R20 140-145	9	24	115	82	.6	17	8	447	2.07	55	5	ND	9	103	.5	2	2	5	.61	.061	11	58	.84	119	.01	6	.95	.03	.21	1
90R20 145-150	5	28	36	99	.3	15	8	518	1.74	74	5	ND	8	76	.5	2	2	5	.68	.059	12	62	.70	135	.01	4	.84	.02	.24	1
90R20 150-155	7	22	51	113	.6	15	8	701	2.05	70	5	ND	8	60	.8	2	2	6	.63	.057	11	65	1.07	128	.01	4	1.07	.02	.25	1
90R20 155-160	7	30	78	107	.6	17	10	619	2.26	85	5	ND	8	77	.8	2	2	5	.73	.070	9	59	.99	96	.01	4	.96	.02	.19	1
90R20 160-165	10	19	53	101	.4	15	7	523	2.40	60	5	ND	9	35	1.0	2	2	5	.40	.052	8	88	1.15	90	.01	4	1.06	.02	.21	1
90R20 165-170	8	22	31	74	.5	15	8	564	2.01	60	5	ND	8	53	.6	2	2	4	.68	.057	8	77	.96	69	.01	4	.87	.02	.19	1
90R20 170-175	8	22	63	84	.5	15	7	436	2.07	30	5	ND	8	39	.6	2	2	4	.50	.055	8	69	.93	71	.01	5	.85	.02	.20	1
90R20 175-180	10	20	49	62	.6	16	8	403	2.20	31	5	ND	7	46	.4	2	2	4	.63	.053	7	85	.71	86	.01	4	.69	.01	.18	1
90R20 180-185	8	24	58	95	.5	15	8	459	2.19	40	5	ND	9	36	.5	2	2	3	.44	.053	8	60	.96	95	.01	5	.87	.01	.19	1
90R20 185-190	8	21	21	98	.4	16	8	463	1.87	56	5	ND	9	42	.4	2	2	3	.47	.049	8	63	.99	101	.01	5	.88	.01	.18	1
90R20 190-195	8	24	30	103	.5	18	8	387	2.04	31	5	ND	9	39	.5	2	2	3	.52	.051	8	67	.94	104	.01	6	.85	.02	.18	1
90R20 195-200	8	36	37	79	.7	19	9	495	2.41	32	5	ND	7	78	.8	2	2	4	.93	.049	8	78	.79	53	.01	4	.65	.02	.17	1
STANDARD C	20	63	44	133	7.6	73	32	1061	3.98	43	24	8	38	56	19.3	18	17	59	.47	.094	38	60	.91	183	.07	34	2.00	.06	.14	11

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#13023 File # 90-6209 Page 1

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R21 0-5	9	25	45	99	.4	17	7	860	1.82	19	5	ND	8	17	.5	2	2	11	.17	.052	21	101	.82	440	.01	2	1.01	.01	.22	1
90R21 5-10	10	17	29	91	.3	13	6	709	2.05	9	5	ND	8	19	.5	2	2	14	.18	.059	22	117	.92	191	.01	2	1.10	.03	.18	1
90R21 10-15	5	13	26	60	.2	14	6	430	1.54	5	5	ND	9	20	.2	2	2	9	.23	.062	24	56	.83	209	.01	2	.96	.02	.23	1
90R21 15-20	5	22	30	60	.2	9	7	424	1.63	37	5	ND	10	19	.2	2	2	9	.18	.057	26	74	.91	332	.01	2	.96	.01	.26	1
90R21 20-25	7	17	118	58	.5	10	5	383	1.27	13	5	ND	9	28	.2	2	4	7	.35	.031	18	90	.91	192	.01	2	.80	.01	.17	1
90R21 25-30	7	23	24	54	.2	12	5	341	1.36	19	5	ND	9	46	.2	2	2	7	.61	.037	20	91	1.11	255	.01	2	.93	.02	.21	1
90R21 30-35	8	26	43	69	.3	11	4	396	1.33	24	5	ND	8	56	.2	2	2	6	.68	.034	16	105	1.09	153	.01	2	.91	.02	.20	1
90R21 35-40	5	22	19	61	.3	9	6	331	1.48	83	5	ND	9	53	.2	2	2	9	.67	.059	15	64	.87	141	.01	2	.83	.02	.18	1
90R21 40-45	5	16	21	58	.4	14	8	353	1.38	90	5	ND	8	73	.3	2	2	8	.85	.056	13	63	.69	155	.01	3	.70	.02	.21	1
90R21 45-50	5	5	15	32	.1	5	3	228	.90	4	5	ND	8	82	.2	2	2	4	.86	.039	16	59	.62	171	.01	2	.59	.01	.22	1
90R21 50-55	7	7	29	51	3.3	6	4	228	1.16	3	5	11	8	61	.2	2	2	5	.69	.034	21	87	.89	155	.01	2	.71	.01	.21	2
90R21 55-60	8	8	28	54	.1	7	4	258	1.24	2	5	ND	10	51	.2	2	2	5	.61	.036	20	101	1.02	195	.01	2	.89	.02	.25	1
90R21 60-65	10	9	11	60	.1	7	5	269	1.30	9	5	ND	10	53	.2	2	2	5	.57	.036	22	123	1.07	198	.01	2	1.01	.02	.25	1
90R21 65-70	9	10	24	63	.3	7	4	283	1.18	38	5	ND	11	43	.3	2	2	5	.39	.030	22	109	.99	170	.01	2	.89	.01	.22	1
90R21 70-75	12	11	137	50	.8	8	3	217	.87	53	5	ND	12	16	.2	2	2	6	.07	.016	17	144	.68	140	.01	3	.59	.01	.18	1
90R21 75-80	8	17	71	83	.8	7	3	284	.92	31	5	ND	13	23	.5	2	2	7	.24	.014	15	98	.81	165	.01	3	.60	.02	.17	1
90R21 80-85	9	47	27	94	.5	9	7	353	1.60	28	5	ND	9	33	.2	2	2	9	.31	.043	11	115	1.32	143	.01	2	.88	.02	.20	1
90R21 85-90	12	48	16	108	.6	10	7	382	1.86	9	5	ND	7	53	.2	2	2	10	.42	.046	11	147	1.47	166	.01	2	.97	.02	.24	1
90R21 90-95	11	55	35	94	1.1	10	6	327	1.62	7	5	ND	7	77	.6	2	2	8	.48	.035	10	119	1.07	162	.01	2	.75	.02	.23	1
90R21 95-100	15	29	30	46	.9	9	4	285	1.12	15	5	ND	3	68	.2	2	2	5	.79	.014	6	179	.45	137	.01	2	.35	.01	.12	1
90R21 100-105	11	30	29	46	.9	7	4	296	1.13	9	5	ND	4	95	.3	2	2	5	.86	.021	7	109	.69	173	.01	2	.45	.01	.14	1
90R21 105-110	9	24	21	43	.2	5	3	267	.83	9	5	ND	10	53	.2	2	2	6	.37	.015	10	105	.67	264	.01	2	.51	.02	.19	1
90R21 110-115	9	17	40	50	.5	5	3	258	.95	17	5	ND	11	38	.7	2	2	5	.34	.014	10	86	.64	163	.01	2	.50	.02	.18	1
90R21 115-120	13	21	47	63	.6	10	6	320	1.50	11	5	ND	7	69	.2	2	2	7	.61	.026	10	149	.96	153	.01	2	.65	.02	.16	1
90R21 120-125	8	22	56	101	.7	14	10	448	2.18	9	5	ND	7	52	1.1	4	2	13	.52	.050	10	144	1.93	132	.01	2	1.11	.02	.15	1
90R21 125-130	10	22	60	127	.8	15	10	547	2.02	10	5	ND	5	118	.2	2	2	11	1.17	.041	10	148	1.62	107	.01	3	.88	.02	.16	1
90R21 130-135	10	19	61	103	.5	13	10	454	1.97	5	5	ND	6	110	.4	2	2	11	.71	.057	11	133	1.67	131	.01	2	.91	.02	.18	1
90R21 135-140	5	29	36	94	.6	12	7	407	1.62	16	5	ND	8	76	.4	3	2	10	.50	.039	10	65	1.30	166	.01	2	.78	.01	.15	1
90R21 140-145	7	36	47	92	.6	13	9	470	1.72	10	5	ND	7	75	.8	2	2	10	.65	.041	10	106	1.48	202	.01	2	.90	.02	.18	1
90R21 145-150	9	36	36	79	.4	13	8	491	1.75	8	5	ND	7	77	.2	2	2	9	.68	.041	11	114	1.22	159	.01	4	.83	.02	.21	1
STANDARD C	19	63	42	133	7.3	73	31	1046	4.00	40	18	7	36	53	18.9	15	22	58	.47	.097	36	60	.86	179	.08	36	1.89	.06	.13	13

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: DEC 3 1990 **DATE REPORT MAILED:** Dec 6/90 **SIGNED BY..** D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R22 0-5	6	6	40	53	.2	7	1	230	.57	9	5	ND	15	10	.2	2	2	5	.04	.005	25	61	.72	376	.01	2	.61	.01	.15	1
90R22 5-10	7	5	24	39	.2	9	2	183	.51	6	5	ND	15	7	.2	2	2	5	.02	.004	27	83	.61	258	.01	2	.55	.01	.16	1
90R22 10-15	6	4	32	40	.2	11	1	203	.40	6	5	ND	16	12	.2	2	2	6	.09	.004	30	66	.59	136	.01	2	.45	.01	.13	1
90R22 15-20	10	6	21	27	.2	6	1	127	.30	2	5	ND	17	14	.2	2	2	7	.10	.002	30	111	.28	193	.01	2	.34	.01	.16	2
90R22 20-25	8	4	25	22	.1	4	1	114	.22	2	6	ND	17	17	.2	2	2	5	.10	.002	32	85	.18	188	.01	2	.25	.01	.14	2
90R22 25-30	8	2	19	20	.1	3	1	129	.34	6	5	ND	15	18	.2	2	2	5	.12	.002	25	78	.39	145	.01	2	.34	.01	.14	1
90R22 30-35	12	13	27	48	.3	8	4	206	.89	9	5	ND	10	21	.4	2	2	7	.12	.017	12	133	.61	138	.01	2	.51	.02	.15	2
90R22 35-40	9	19	35	79	.4	9	5	280	1.44	40	5	ND	8	40	.2	2	2	8	.24	.035	8	102	.87	140	.01	2	.62	.02	.17	1
90R22 40-45	7	17	32	104	.4	10	8	333	1.66	5	5	ND	7	68	.5	2	2	9	.37	.040	9	97	1.13	128	.01	2	.73	.02	.18	1
90R22 45-50	9	25	14	111	.6	12	7	384	1.57	7	5	ND	9	77	.6	2	2	10	.44	.034	9	139	1.31	185	.01	2	.83	.02	.20	1
90R22 50-55	9	16	39	57	.3	10	4	255	.96	26	5	ND	11	51	.4	2	2	6	.28	.020	10	96	.84	223	.01	2	.56	.01	.16	1
90R22 55-60	8	20	18	38	.3	7	3	214	.88	15	5	ND	12	51	.2	2	2	4	.30	.020	12	84	.59	227	.01	2	.43	.02	.17	1
90R22 60-65	9	16	41	54	.3	7	3	223	1.06	36	5	ND	13	42	.2	2	2	5	.26	.017	13	94	.75	175	.01	2	.53	.02	.18	2
90R22 65-70	10	19	30	127	2.0	19	11	656	2.36	57	5	ND	5	187	1.0	4	2	9	1.54	.035	7	97	2.43	91	.01	2	.95	.01	.18	1
90R22 70-75	8	32	37	112	.6	16	9	427	1.89	297	5	ND	8	74	.5	4	2	9	.53	.039	8	90	1.73	94	.01	2	.90	.01	.17	1
90R22 75-80	10	22	28	96	1.3	14	8	583	1.81	50	5	ND	6	271	.6	4	2	7	2.04	.031	8	88	1.80	91	.01	2	.62	.01	.18	1
90R22 80-85	6	26	42	87	.7	11	8	377	1.46	18	5	ND	8	98	.4	2	2	6	.70	.045	9	67	1.19	137	.01	2	.65	.01	.15	1
90R22 90-95	7	41	8	73	.5	25	10	192	2.58	8	5	ND	5	32	.2	2	2	34	.37	.074	17	83	1.27	272	.11	2	1.31	.01	.50	1
90R22 95-100	10	26	48	83	.8	11	7	419	1.54	24	5	ND	8	103	.5	2	2	7	.69	.036	8	86	1.21	121	.01	2	.69	.01	.16	1
90R22 100-105	9	41	35	87	.6	12	7	411	1.61	14	5	ND	8	78	.3	2	2	8	.58	.039	10	101	1.19	145	.01	2	.77	.01	.19	1
90R22 105-110	8	26	55	67	.6	11	7	399	1.37	9	5	ND	9	110	.7	2	2	7	.70	.035	10	82	.97	155	.01	2	.60	.01	.16	1
90R22 110-115	10	13	15	34	.2	7	5	313	.90	6	5	ND	11	65	.5	2	2	5	.49	.030	14	114	.63	264	.01	2	.55	.02	.24	1
90R22 115-120	10	22	59	93	.6	11	7	475	1.59	18	5	ND	9	69	.7	2	2	9	.53	.038	11	103	1.25	176	.01	2	.84	.02	.17	1
90R22 120-125	7	35	24	98	.5	12	8	549	1.88	18	5	ND	8	61	.7	2	3	9	.50	.056	9	88	1.36	141	.01	3	.93	.02	.18	1
90R22 125-130	6	31	8	95	.4	10	7	453	1.74	22	5	ND	8	60	.5	2	2	8	.42	.051	9	81	1.27	148	.01	2	.82	.02	.17	1
90R22 130-135	5	29	3	92	1.0	10	7	407	1.69	17	5	2	8	82	.4	2	2	7	.53	.036	7	69	1.21	132	.01	3	.75	.01	.17	1
90R22 135-140	8	44	69	76	1.1	13	8	405	1.85	16	5	ND	8	97	.7	2	2	7	.61	.040	9	92	.93	71	.01	3	.60	.01	.17	1
90R22 140-145	9	23	91	115	1.1	14	7	369	2.13	30	5	ND	7	75	.6	2	2	7	.45	.039	8	72	.74	50	.01	2	.54	.01	.16	1
90R22 145-150	9	25	92	121	.6	13	8	706	2.36	58	5	ND	6	74	.6	3	2	8	.81	.062	8	79	1.22	92	.01	2	.81	.01	.20	1
STANDARD C	19	62	41	140	7.4	72	31	1043	3.98	42	15	7	36	51	18.7	15	21	55	.44	.096	36	58	.86	179	.08	37	1.91	.06	.14	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R23 0-5	11	26	42	70	.1	16	10	536	2.42	14	5	ND	4	13	.2	3	2	14	.13	.055	19	124	.55	239	.02	3	.98	.02	.15	1
90R23 5-10	9	32	19	93	.1	18	11	925	2.26	196	5	ND	7	12	1.2	2	2	10	.14	.065	24	101	.74	245	.01	5	1.00	.02	.21	1
90R23 10-15	6	32	7	89	.1	18	15	1136	2.27	501	5	ND	7	10	.9	2	2	6	.15	.075	22	69	.74	168	.01	4	.88	.01	.22	1
90R23 15-20	6	46	18	120	.3	22	16	1077	2.73	361	5	ND	7	11	1.1	2	2	6	.17	.084	18	64	.76	148	.01	4	.95	.01	.20	1
90R23 20-25	6	37	15	91	.3	17	12	1278	2.44	90	5	ND	8	18	.8	2	2	7	.36	.075	14	74	.87	163	.01	2	.99	.01	.23	1
90R23 25-30	10	37	246	91	4.0	21	13	1020	2.64	45	5	2	5	14	1.1	2	2	7	.20	.060	12	120	.74	158	.01	3	.90	.02	.24	1
90R23 30-35	7	102	67	77	2.9	19	13	1043	2.51	27	5	6	3	63	1.1	3	2	6	.94	.078	8	82	.60	62	.01	2	.75	.01	.23	1
90R23 35-40	5	46	25	161	.5	21	12	1111	3.21	45	5	ND	6	73	1.3	2	2	7	.73	.075	10	63	1.27	91	.01	4	1.13	.02	.21	1
90R23 40-45	10	103	137	218	.6	21	12	947	2.67	3	5	ND	7	37	1.2	2	2	8	.35	.070	12	105	1.44	100	.01	4	1.44	.02	.25	1
90R23 45-50	8	40	15	140	.1	23	15	835	2.41	8	5	ND	7	28	.8	2	2	8	.32	.079	12	95	1.18	168	.01	4	1.28	.02	.23	1
90R23 50-55	9	25	23	71	.1	20	11	563	2.29	7	5	ND	7	70	.5	2	2	5	.65	.062	9	82	.68	59	.01	3	.65	.03	.17	2
90R23 55-60	10	25	16	53	.6	19	10	376	2.08	5	5	ND	6	77	.5	2	2	4	.64	.053	8	99	.54	37	.01	6	.46	.03	.18	1
90R23 60-65	8	20	8	67	.1	19	10	336	2.44	5	5	ND	6	59	.5	2	2	4	.51	.059	7	89	.54	40	.01	4	.54	.02	.23	1
90R23 65-70	11	20	7	40	.3	16	10	272	1.64	4	5	ND	6	53	.3	2	2	3	.42	.049	7	125	.41	76	.01	2	.43	.02	.20	2
90R23 70-75	10	23	5	58	.1	16	9	328	1.56	17	5	ND	6	51	.2	2	2	4	.44	.062	8	112	.67	93	.01	3	.61	.03	.22	1
90R23 75-80	11	24	6	29	.2	16	9	403	1.54	5	5	ND	6	54	.2	2	2	4	.63	.062	8	125	.50	56	.01	3	.52	.02	.24	1
90R23 80-85	8	21	5	40	.1	15	9	371	1.42	17	5	ND	7	62	.3	2	2	5	.53	.061	10	100	.58	92	.01	3	.66	.02	.23	1
90R23 85-90	7	18	9	73	.5	18	8	528	2.16	16	5	ND	6	77	.2	2	2	7	.83	.052	9	87	1.06	70	.01	3	.83	.03	.15	1
90R23 90-95	7	26	5	79	.9	17	8	788	2.38	7	5	ND	6	195	.6	2	2	9	1.75	.044	10	89	1.09	65	.01	3	.84	.04	.15	1
90R23 95-100	5	34	7	87	1.1	17	7	932	2.39	37	5	ND	7	184	.9	2	2	7	2.22	.027	8	71	1.24	81	.01	4	.77	.03	.12	1
90R23 100-105	8	51	84	107	1.2	16	8	594	2.35	108	5	ND	8	81	.6	5	2	7	.71	.034	8	93	1.20	49	.01	2	.83	.03	.14	1
90R23 105-110	9	84	53	102	.6	13	7	439	2.09	26	5	ND	7	63	.5	2	2	4	.48	.048	7	89	1.04	72	.01	2	.76	.02	.16	1
90R23 110-115	7	79	43	95	.8	15	7	401	1.93	11	5	ND	7	76	.4	2	2	3	.55	.045	6	65	1.03	84	.01	3	.72	.02	.15	1
90R23 115-120	10	48	13	88	.2	15	7	415	1.95	3	5	ND	6	60	.2	2	2	4	.42	.051	8	96	1.10	67	.01	3	.83	.02	.17	1
90R23 120-125	11	42	28	105	.1	15	7	403	1.95	2	5	ND	6	45	.2	2	2	4	.29	.050	9	99	1.21	84	.01	3	.87	.02	.16	1
90R23 125-130	7	49	15	79	.4	15	8	479	2.19	2	5	ND	6	71	.2	2	2	3	.48	.052	7	74	.90	80	.01	4	.66	.01	.17	1
90R23 130-135	10	32	15	80	.2	14	7	474	2.18	2	5	ND	5	69	.4	2	2	4	.51	.049	7	110	1.04	70	.01	3	.76	.02	.20	1
90R23 135-140	10	37	11	88	.4	14	7	619	2.10	2	5	ND	6	111	.6	2	2	4	.80	.049	8	112	.94	53	.01	2	.70	.02	.23	1
90R23 140-145	8	57	12	87	.8	13	6	436	1.82	5	5	ND	6	141	.4	2	2	3	.91	.040	7	82	.98	62	.01	3	.55	.01	.16	1
90R23 145-150	10	99	38	88	1.0	16	7	398	2.11	17	5	ND	6	86	.4	2	2	4	.63	.048	7	96	.95	58	.01	3	.64	.01	.17	1
STANDARD C	20	62	40	134	7.2	73	31	1058	3.97	42	19	7	36	55	19.2	14	19	59	.45	.094	37	60	.90	183	.07	35	1.92	.06	.14	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R24 0-5	5	33	54	65	.5	10	7	466	1.38	16	5	ND	10	28	.2	2	2	8	.18	.033	21	57	.57	497	.01	5	.75	.01	.15	1
90R24 5-10	6	28	46	66	.5	9	6	298	1.08	9	5	ND	9	33	.6	2	2	8	.13	.027	18	65	.49	741	.01	3	.68	.01	.13	1
90R24 10-15	8	21	32	32	.3	8	3	161	.78	9	5	ND	8	18	.2	2	2	7	.12	.019	16	94	.28	393	.01	2	.49	.01	.12	1
90R24 15-20	6	25	46	73	.5	12	6	421	1.26	32	5	ND	10	18	.2	2	2	9	.16	.032	22	65	.54	325	.01	2	.77	.01	.14	1
90R24 20-25	4	35	44	80	.4	11	7	454	1.57	38	5	ND	12	15	.7	2	2	9	.15	.040	35	44	.52	231	.01	3	.79	.01	.17	1
90R24 25-30	4	34	23	88	.5	25	12	887	2.21	41	5	ND	10	16	.7	2	2	20	.19	.040	34	67	1.01	229	.01	2	1.27	.01	.17	1
90R24 30-35	6	27	39	72	.6	7	4	359	1.19	22	5	ND	14	15	.4	2	2	8	.12	.020	34	62	.51	210	.01	3	.69	.01	.18	1
90R24 35-40	9	23	54	46	.9	6	2	205	1.04	13	5	ND	13	11	.2	2	2	8	.08	.018	29	105	.43	251	.01	2	.57	.01	.19	1
90R24 40-45	9	7	18	15	.1	5	1	88	.50	12	5	ND	20	5	.2	2	2	6	.04	.007	24	99	.24	169	.01	2	.42	.01	.20	1
90R24 45-50	13	4	27	15	.3	5	2	76	.36	5	5	ND	20	6	.2	2	2	7	.07	.002	28	125	.22	148	.01	2	.39	.01	.21	2
90R24 50-55	8	5	17	42	.3	4	1	101	.68	19	5	ND	20	7	.2	2	2	3	.09	.005	29	80	.79	176	.01	4	.86	.01	.19	1
90R24 55-60	4	11	46	72	.5	11	5	173	1.05	123	5	ND	14	39	.6	2	2	5	.44	.022	34	49	1.32	152	.01	4	1.13	.01	.17	1
90R24 60-65	13	7	20	42	.1	8	4	113	.86	16	5	ND	16	17	.2	3	2	5	.22	.021	38	146	.78	180	.01	2	.88	.02	.23	1
90R24 65-70	6	15	27	63	.4	14	8	170	1.86	47	5	ND	13	22	.4	4	2	12	.17	.039	23	75	1.69	173	.01	5	1.55	.02	.24	1
90R24 70-75	5	16	20	64	.2	13	8	152	1.66	45	5	ND	11	22	.5	4	2	10	.18	.037	20	77	1.74	140	.01	3	1.52	.02	.20	1
90R24 75-80	5	7	15	52	.1	6	4	120	.84	17	5	ND	14	21	.4	2	2	4	.22	.022	27	52	1.01	146	.01	2	.88	.01	.19	1
90R24 80-85	6	2	11	47	.1	3	1	133	.53	3	5	ND	19	40	.2	2	2	1	.61	.003	38	61	.81	133	.01	4	.69	.01	.17	1
90R24 85-90	6	3	9	56	.2	1	1	91	.58	5	5	ND	21	22	.2	2	2	1	.33	.003	40	65	.88	144	.01	4	.73	.01	.18	1
90R24 90-95	7	3	19	42	.3	3	2	63	.52	26	6	ND	19	15	.7	2	2	3	.14	.003	34	78	.60	1179	.01	2	.69	.02	.21	2
90R24 95-100	13	12	34	13	.3	3	2	153	.39	20	5	ND	16	30	.2	2	2	4	.46	.003	22	137	.18	960	.01	2	.40	.01	.23	1
90R24 100-105	16	4	20	11	.1	4	2	157	.36	14	5	ND	16	27	.2	2	2	4	.45	.002	22	174	.13	1101	.01	3	.36	.01	.23	2
90R24 105-110	6	10	10	52	.6	5	3	323	.68	40	5	ND	13	53	.4	2	2	5	1.15	.014	16	66	.24	328	.01	2	.37	.01	.21	1
90R24 110-115	11	6	63	19	.3	3	2	91	.41	23	5	ND	18	16	.2	2	2	5	.26	.002	21	124	.19	809	.01	4	.39	.01	.22	1
90R24 115-120	5	3	14	27	.2	2	2	309	.41	11	5	ND	15	27	.2	2	2	2	.56	.003	28	46	.27	1471	.01	2	.48	.01	.19	1
90R24 120-125	17	6	20	53	.2	4	1	140	.68	2	5	ND	19	63	.2	2	2	1	.69	.003	41	173	.75	273	.01	2	.61	.01	.22	1
90R24 125-130	5	9	33	53	.2	1	1	370	.56	6	5	ND	19	28	.2	2	2	1	.27	.002	40	49	.62	389	.01	2	.61	.01	.18	1
90R24 130-135	7	8	20	52	.1	2	1	124	.52	2	5	ND	18	45	.2	2	2	1	.40	.002	41	78	.78	201	.01	3	.58	.01	.17	1
90R24 135-140	8	9	16	39	.1	2	1	152	.46	3	5	ND	17	68	.2	2	2	1	.54	.002	36	77	.68	503	.01	2	.48	.01	.17	1
90R24 140-145	7	4	29	52	.2	1	1	134	.49	3	5	ND	19	43	.2	2	2	1	.42	.002	37	65	.62	393	.01	2	.52	.01	.18	1
90R24 145-150	12	5	16	31	.1	3	1	217	.43	4	5	ND	19	69	.3	2	2	1	.65	.002	38	128	.50	284	.01	2	.41	.02	.22	1
90R24 150-155	6	2	13	29	.1	1	1	88	.38	3	5	ND	18	58	.2	2	2	1	.48	.002	40	69	.65	272	.01	3	.49	.01	.17	1
90R24 155-160	6	5	10	29	.1	1	1	89	.39	2	5	ND	19	43	.2	2	2	1	.38	.002	41	59	.50	193	.01	2	.41	.01	.17	1
90R24 160-165	9	11	27	36	.1	2	2	302	.34	5	5	ND	19	14	.2	2	2	2	.04	.003	40	97	.08	608	.01	2	.26	.03	.16	2
90R24 165-170	8	18	35	18	.2	3	2	43	.32	6	5	ND	18	24	.2	2	2	4	.02	.003	31	87	.04	1768	.01	2	.21	.04	.15	3
90R24 170-175	9	5	135	12	1.2	2	2	27	.38	4	5	ND	13	55	.4	2	2	4	.02	.002	25	93	.03	1779	.01	2	.20	.04	.15	4
90R24 175-180	5	5	37	7	.3	2	2	26	.25	3	5	ND	14	41	.2	2	2	4	.02	.002	20	58	.04	1488	.01	3	.20	.04	.13	3
STANDARD C	20	62	43	133	7.3	72	32	1047	4.00	44	16	7	36	52	18.4	15	18	58	.47	.096	37	60	.87	179	.07	37	1.90	.06	.13	12

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R24 180-185	6	4	36	12	.1	4	1	27	.27	3	5	ND	15	23	.2	3	2	3	.03	.008	37	74	.05	895	.01	2	.24	.04	.16	4
90R24 185-190	6	3	64	11	.2	4	1	28	.28	2	5	ND	15	46	.2	2	2	2	.04	.007	32	72	.05	1327	.01	2	.20	.03	.13	4
90R24 190-195	6	3	24	7	.1	4	1	103	.32	7	5	ND	15	17	.2	3	2	2	.21	.005	32	74	.09	462	.01	2	.24	.01	.16	3
90R24 195-200	10	7	18	16	.1	4	2	189	.57	26	5	ND	12	68	.4	3	2	2	.89	.012	23	125	.39	307	.01	2	.40	.01	.21	2

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R25 0-5	6	9	35	31	.2	5	2	135	.61	25	5	ND	14	10	.6	2	2	6	.07	.015	40	67	.10	533	.01	5	.39	.01	.16	1
90R25 5-10	6	7	30	22	.1	5	2	118	.55	33	5	ND	17	6	.2	2	2	4	.02	.014	49	70	.06	216	.01	2	.33	.01	.17	1
90R25 10-15	9	7	41	21	.1	6	3	203	.56	28	5	ND	16	6	.2	2	2	4	.02	.013	45	103	.07	282	.01	2	.35	.02	.19	1
90R25 15-20	5	9	50	20	.1	5	4	318	.62	40	5	ND	15	7	.2	2	2	4	.04	.016	46	51	.06	309	.01	3	.35	.01	.15	1
90R25 20-25	7	8	43	18	.1	3	3	245	.74	47	6	ND	20	6	.7	2	3	7	.02	.021	52	70	.06	240	.01	2	.43	.01	.18	1
90R25 25-30	10	8	34	17	.1	4	4	307	.67	39	5	ND	17	6	.5	2	2	6	.02	.016	45	114	.06	291	.01	3	.43	.02	.21	1
90R25 30-35	11	7	23	15	.1	4	3	213	.52	19	5	ND	16	9	.2	2	2	4	.02	.014	52	124	.09	295	.01	4	.38	.02	.23	1
90R25 35-40	7	6	22	17	.1	3	2	151	.54	17	5	ND	15	14	.2	2	2	3	.03	.016	59	80	.11	468	.01	2	.40	.02	.21	1
90R25 40-45	7	8	27	19	.1	3	2	128	.66	28	5	ND	15	11	.2	2	2	4	.02	.017	54	83	.09	280	.01	2	.39	.02	.21	1
90R25 45-50	12	8	27	20	.2	6	3	449	.46	11	5	ND	18	8	.5	2	2	5	.03	.011	50	123	.10	357	.01	3	.42	.02	.23	1
90R25 50-55	8	4	22	8	.1	4	1	278	.36	16	5	ND	22	7	.2	2	2	5	.01	.010	64	94	.06	204	.01	2	.33	.01	.20	1
90R25 55-60	7	4	36	6	.1	4	1	205	.33	14	5	ND	23	7	.2	2	2	4	.02	.009	61	73	.05	192	.01	2	.29	.01	.18	1
90R25 60-65	7	4	34	7	.1	4	1	64	.25	5	5	ND	23	4	.2	2	2	4	.01	.006	50	80	.05	157	.01	2	.26	.01	.19	1
90R25 65-70	7	4	32	16	.2	3	1	82	.35	9	5	ND	22	6	.2	2	2	4	.02	.007	59	80	.07	198	.01	3	.34	.02	.19	1
90R25 70-75	9	5	32	35	.2	4	1	154	.65	18	5	ND	17	9	.4	2	2	4	.04	.010	52	109	.11	293	.01	2	.45	.02	.20	1
90R25 75-80	6	5	29	28	.2	4	1	124	.47	10	5	ND	18	7	.2	3	2	4	.03	.008	52	70	.10	257	.01	2	.36	.02	.18	1
90R25 80-85	9	4	28	27	.2	3	2	106	.51	10	5	ND	17	8	.4	2	2	4	.03	.009	44	106	.09	209	.01	2	.40	.02	.19	1
90R25 85-90	8	9	25	15	.1	3	1	91	.44	14	5	ND	17	6	.2	2	2	3	.02	.009	51	86	.05	211	.01	2	.34	.02	.18	1
90R25 90-95	7	7	21	14	.2	2	1	87	.46	21	6	ND	18	6	.2	2	2	3	.02	.011	60	72	.04	183	.01	2	.32	.02	.17	1
90R25 95-100	6	13	81	20	.6	2	2	179	.43	21	5	ND	20	13	.2	2	2	5	.02	.010	44	68	.05	2385	.01	2	.31	.02	.16	1
90R25 100-105	5	14	78	18	.5	3	1	120	.34	17	5	ND	21	8	.2	2	2	5	.01	.008	45	54	.04	1236	.01	3	.26	.02	.15	2
90R25 105-110	9	10	62	17	.3	2	1	144	.36	17	5	ND	22	6	.2	2	2	5	.02	.007	49	100	.05	353	.01	3	.31	.03	.18	1
90R25 110-115	6	4	34	6	.2	3	1	88	.33	18	5	ND	23	5	.3	2	2	5	.01	.008	49	66	.04	331	.01	2	.26	.02	.16	1
90R25 115-120	5	3	34	7	.2	2	1	88	.30	15	5	ND	22	5	.4	2	2	5	.02	.007	46	57	.03	260	.01	2	.25	.02	.16	1
90R25 120-125	7	4	58	13	.2	3	1	166	.32	17	5	ND	21	6	.2	2	2	5	.02	.007	47	66	.04	339	.01	2	.28	.02	.17	1
90R25 125-130	4	8	64	15	.3	2	1	81	.30	17	5	ND	22	5	.2	2	2	4	.02	.007	41	46	.04	391	.01	2	.25	.02	.16	1
90R25 130-135	7	10	132	18	.2	2	2	184	.47	22	5	ND	20	10	.2	2	2	6	.03	.009	50	74	.05	1526	.01	2	.29	.02	.16	1
90R25 135-140	6	9	111	18	.3	4	2	123	.45	25	5	ND	21	7	.2	2	2	4	.02	.008	42	75	.04	1069	.01	2	.27	.02	.16	2
90R25 140-145	5	9	85	27	.3	3	1	129	.44	24	5	ND	22	9	.2	2	2	2	.04	.007	56	49	.03	296	.01	2	.27	.02	.15	2
90R25 145-150	6	7	32	17	.3	3	2	176	.35	12	5	ND	22	17	.2	2	2	2	.02	.006	33	55	.03	1559	.01	2	.24	.02	.17	2
90R25 150-155	5	5	41	6	.2	3	1	102	.27	8	5	ND	21	7	.2	2	2	4	.02	.006	47	53	.03	753	.01	2	.24	.02	.16	2
90R25 155-160	9	12	48	17	.2	11	2	172	.53	19	5	ND	23	9	.9	2	2	4	.03	.009	58	81	.06	812	.01	2	.32	.02	.18	2
STANDARD C	20	62	38	135	7.4	72	32	1051	3.99	43	18	7	36	53	18.4	15	21	59	.51	.097	37	59	.87	179	.08	37	1.89	.06	.13	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R26 0-5	3	32	31	77	.4	28	14	454	3.27	25	5	ND	3	12	.2	3	5	47	.25	.061	12	55	2.01	160	.07	3	1.91	.02	.09	1
90R26 5-10	4	34	13	83	.4	31	13	398	3.28	22	5	ND	2	12	.2	3	2	46	.27	.063	7	74	2.29	179	.09	2	2.09	.03	.12	1
90R26 10-15	4	35	13	77	.4	30	11	348	3.23	22	5	ND	2	15	.2	2	2	40	.31	.064	6	62	1.84	166	.09	2	1.78	.04	.11	1
90R26 15-20	3	39	44	79	.4	33	14	363	3.19	18	5	ND	2	17	.2	2	2	38	.36	.067	6	53	1.80	188	.08	2	1.78	.02	.11	1
90R26 20-25	6	42	15	79	.4	32	13	329	3.18	19	5	ND	1	32	.2	2	2	41	.69	.066	3	87	1.71	176	.10	2	1.74	.03	.10	1
90R26 25-30	3	34	16	86	.6	30	13	371	3.17	17	5	ND	1	35	.2	2	2	47	.64	.060	3	62	1.77	129	.09	3	1.78	.05	.07	1
90R26 30-35	3	35	31	84	.9	31	15	498	3.51	43	5	ND	1	32	.2	3	2	60	.49	.058	7	74	1.99	118	.08	2	2.01	.05	.06	1
90R26 35-40	3	33	15	69	.7	30	15	466	3.41	27	5	ND	1	85	.2	2	2	55	1.04	.053	6	75	2.09	118	.08	2	2.02	.03	.07	1
90R26 40-45	4	33	12	75	.4	32	15	364	3.07	18	5	ND	1	31	.2	2	2	36	.62	.061	3	68	1.74	155	.09	3	1.76	.04	.10	1
90R26 45-50	4	35	14	83	.4	32	13	338	3.15	12	5	ND	1	37	.2	2	2	37	.79	.064	3	74	1.54	149	.10	2	1.66	.05	.11	1
90R26 50-55	4	34	14	79	.4	32	12	351	3.25	13	5	ND	1	42	.2	2	2	45	.85	.061	5	67	1.62	121	.09	2	1.71	.05	.10	1
90R26 55-60	4	28	10	71	.3	28	10	320	2.80	8	5	ND	2	26	.2	2	2	34	.51	.057	9	58	1.81	112	.06	2	1.61	.01	.10	1
90R26 60-65	5	33	27	137	.6	33	12	382	3.40	13	5	ND	4	42	.2	2	3	37	.63	.064	10	71	2.15	157	.07	2	1.93	.01	.15	1
90R26 65-70	4	37	9	111	.6	32	11	312	3.45	39	5	ND	4	45	.2	2	2	55	.56	.069	15	54	1.71	139	.06	4	1.67	.03	.17	1
90R26 70-75	6	34	12	76	.8	31	11	308	3.44	78	5	ND	4	50	.4	2	2	63	.56	.067	14	87	1.65	256	.07	2	1.66	.04	.41	1
90R26 75-80	5	33	18	63	.2	31	11	308	3.36	13	5	ND	4	71	.2	2	2	57	.64	.068	14	68	1.59	317	.09	2	1.56	.02	.52	1
90R26 80-85	4	33	21	87	.4	27	10	334	3.60	8	5	ND	4	119	.2	2	2	55	1.24	.069	15	66	2.11	259	.07	2	1.88	.02	.30	1
90R26 85-90	4	29	15	97	.3	17	10	238	3.69	12	5	ND	5	57	.2	2	2	50	.68	.074	18	62	2.21	250	.13	2	2.01	.05	.41	1
90R26 90-95	6	47	11	55	.4	28	11	164	2.82	8	5	ND	4	31	.2	2	3	43	.41	.073	16	71	1.36	253	.12	2	1.29	.03	.43	1
90R26 95-100	7	28	7	62	.3	20	9	227	2.71	8	5	ND	5	35	.2	2	2	38	.39	.080	18	95	1.30	446	.14	2	1.45	.02	.70	1
90R26 100-105	5	20	8	83	.4	13	9	254	3.10	8	5	ND	5	52	.4	2	2	33	.49	.082	19	64	1.58	539	.15	2	1.64	.02	.79	1
90R26 105-110	6	23	8	88	.5	20	10	242	3.38	10	5	ND	5	28	.2	3	3	41	.34	.078	18	90	1.77	365	.15	3	1.82	.04	.76	1
90R26 110-115	6	43	37	71	.6	32	11	193	2.70	11	5	ND	5	34	.2	2	2	32	.42	.072	19	72	1.35	309	.11	2	1.41	.01	.47	1
90R26 115-120	4	20	20	81	.4	21	14	229	3.29	17	5	ND	4	46	.2	2	2	42	.49	.076	18	65	1.78	274	.12	2	1.76	.03	.57	1
90R26 120-125	4	18	9	76	.3	11	10	203	3.06	9	5	ND	5	44	.2	2	2	42	.50	.078	18	59	1.63	281	.14	2	1.59	.04	.62	1
90R26 125-130	5	19	15	86	.4	17	11	239	3.27	14	5	ND	4	69	.2	2	2	45	.75	.074	17	67	1.72	316	.13	2	1.71	.04	.71	1
90R26 130-135	6	28	28	82	.4	24	10	242	3.41	12	5	ND	5	49	.2	2	2	50	.53	.075	17	83	1.77	306	.12	2	1.78	.03	.70	1
90R26 135-140	4	35	16	77	.5	26	12	251	3.12	11	5	ND	4	67	.2	2	2	45	.76	.070	14	57	1.57	274	.11	2	1.55	.02	.54	1
90R26 140-145	5	36	8	77	.5	32	16	229	3.28	23	5	ND	4	40	.2	2	2	47	.49	.071	13	64	1.56	200	.10	2	1.56	.02	.35	1
90R26 145-150	7	42	13	75	.7	32	12	284	3.21	36	5	ND	4	55	.2	2	2	46	.87	.068	11	81	1.58	187	.10	4	1.58	.03	.25	1
90R26 150-155	7	36	26	85	.6	25	10	304	3.27	28	5	ND	4	67	.2	2	2	40	.94	.072	14	92	1.78	217	.11	2	1.70	.02	.35	1
90R26 155-160	6	20	14	73	.4	15	8	243	3.00	12	5	ND	4	37	.2	2	2	29	.59	.074	11	82	1.81	168	.10	2	1.77	.03	.20	1
90R26 160-165	3	16	9	72	.5	12	7	198	2.72	10	5	ND	4	31	.2	2	2	20	.55	.077	14	52	1.58	185	.09	4	1.62	.01	.25	1
90R26 165-170	6	14	2	69	.3	12	7	224	2.36	10	5	ND	4	64	.2	2	2	23	1.17	.068	18	79	1.05	187	.03	4	1.25	.02	.23	1
90R26 170-175	3	16	15	72	.6	10	7	279	2.60	9	5	ND	5	91	.2	2	2	30	1.50	.082	19	50	.98	171	.07	4	1.20	.04	.21	1
90R26 175-180	3	15	13	57	.4	10	5	272	1.76	6	5	ND	4	100	.6	2	2	21	1.93	.077	18	46	.81	184	.08	2	.93	.03	.21	1
STANDARD C	19	60	41	132	7.3	72	31	1046	3.98	42	18	7	36	51	19.0	14	20	56	.47	.095	36	60	.86	178	.07	35	1.89	.06	.13	12

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R26 180-185	4	23	15	72	.3	17	8	330	2.19	15	5	ND	4	106	.8	2	2	25	1.82	.075	16	56	1.05	180	.05	3	1.16	.01	.20	1
90R26 185-190	4	17	15	82	.2	14	8	363	2.80	6	5	ND	4	150	1.1	2	2	27	2.83	.078	18	60	1.25	191	.01	2	1.52	.01	.21	1
90R26 190-195	5	20	13	85	.2	19	10	344	3.01	13	5	ND	3	149	.5	2	2	30	2.74	.078	15	66	1.30	138	.01	2	1.47	.01	.15	1
90R26 195-200	3	25	4	88	.9	20	13	536	3.85	15	5	ND	1	198	.2	2	2	55	3.71	.064	13	67	1.82	85	.01	2	1.96	.01	.12	1
90R26 200-205	3	19	15	81	.1	18	11	437	3.30	5	5	ND	3	147	.2	2	2	38	2.93	.074	15	54	1.56	112	.02	2	1.68	.01	.15	1
90R26 205-210	3	18	6	66	.1	11	9	307	1.99	5	5	ND	2	78	.2	2	2	22	1.38	.073	10	56	1.00	153	.08	2	1.09	.01	.14	1
90R26 210-215	4	30	2	67	.3	22	14	406	2.66	4	5	ND	1	68	.2	2	2	31	1.53	.060	4	78	1.48	209	.10	4	1.58	.01	.08	1
90R26 215-220	3	32	12	62	.5	18	12	472	2.77	2	5	ND	1	131	.3	2	2	39	2.57	.057	6	62	1.49	106	.06	2	1.47	.01	.08	1
90R26 220-225	4	16	5	70	.2	13	9	275	2.06	2	5	ND	1	45	.6	2	2	20	.85	.069	6	64	1.02	156	.10	3	1.12	.01	.13	1
90R26 225-230	2	16	60	80	.2	9	8	210	2.44	2	5	ND	2	36	.2	2	2	18	.57	.080	9	47	1.42	144	.09	3	1.39	.01	.12	1
90R26 230-235	2	29	9	74	.3	10	7	233	2.26	2	5	ND	3	103	.5	2	2	19	1.18	.082	16	44	1.49	172	.05	4	1.31	.01	.13	1
90R26 235-240	3	23	6	88	.3	13	10	474	3.08	3	5	ND	2	75	.2	2	2	24	1.02	.086	9	59	1.64	141	.07	4	1.60	.02	.10	1
90R26 240-245	3	20	9	81	.3	15	11	397	3.13	5	5	ND	1	65	.2	2	2	25	1.09	.080	7	57	1.83	132	.07	4	1.71	.01	.10	1
90R26 245-250	3	19	13	81	.4	14	10	291	3.10	3	5	ND	2	56	.2	2	2	30	.75	.074	8	67	1.84	148	.08	3	1.67	.02	.10	1
90R26 250-255	3	13	5	81	.2	12	9	361	3.21	4	5	ND	2	89	.2	2	2	32	.99	.070	13	66	1.71	120	.04	3	1.59	.02	.08	1
90R26 255-260	2	14	3	81	.2	11	9	316	2.87	2	5	ND	2	46	.2	2	2	28	.68	.070	9	48	1.64	147	.07	4	1.53	.01	.07	1
90R26 260-265	2	17	2	71	.2	12	8	234	2.59	2	5	ND	1	42	.2	2	2	24	.66	.070	7	44	1.64	164	.07	4	1.43	.01	.08	1
90R26 265-270	3	15	7	73	.2	12	9	203	2.60	3	5	ND	1	40	.2	2	2	22	.57	.070	7	59	1.61	176	.08	3	1.44	.01	.10	1
90R26 270-275	2	13	12	82	.3	11	8	384	2.82	12	5	ND	2	111	.2	2	2	27	1.31	.071	8	49	1.77	109	.04	3	1.48	.01	.08	1
90R26 275-280	2	13	13	75	.2	12	8	416	2.92	5	5	ND	2	70	.2	2	2	27	.73	.076	11	46	1.59	132	.05	2	1.47	.01	.09	1
90R26 280-285	2	13	7	69	.3	11	7	423	2.06	2	5	ND	1	93	.2	2	2	16	1.22	.070	10	46	.99	134	.05	2	1.09	.01	.14	1
90R26 285-290	2	9	7	82	.2	9	8	501	3.06	4	5	ND	1	55	.2	2	2	19	.95	.076	8	55	1.75	126	.04	2	1.74	.01	.10	1
90R26 290-295	2	11	12	76	.4	12	9	513	2.91	9	5	ND	1	74	.2	2	2	19	1.41	.073	12	41	1.56	101	.02	2	1.57	.01	.09	1
90R26 295-300	3	20	3	70	.3	11	7	342	2.51	7	5	ND	1	127	.2	2	2	19	1.45	.071	11	50	.95	337	.06	2	1.08	.01	.15	1
STANDARD C	19	60	40	133	7.4	73	32	1050	3.96	42	19	7	36	53	18.4	14	20	60	.51	.098	39	60	.87	179	.07	38	1.90	.06	.13	13

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#13024 File # 90-6211 Page 1

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R27 0-5	3	20	19	107	.3	15	9	736	3.58	38	5	ND	3	20	.4	4	3	41	.45	.080	21	45	1.26	318	.01	2	2.08	.01	.14	1
90R27 5-10	2	21	12	118	.3	20	11	1050	4.55	41	5	ND	1	23	.2	2	2	61	.52	.104	15	47	1.60	305	.01	2	2.48	.02	.11	1
90R27 10-15	2	23	12	117	.4	19	11	1093	4.68	24	5	ND	1	19	.2	3	2	58	.49	.081	13	50	1.77	270	.05	2	2.52	.01	.11	1
90R27 15-20	1	25	10	122	.3	19	12	1122	5.18	38	5	ND	1	20	.2	3	2	68	.56	.108	17	54	1.86	282	.05	2	2.71	.02	.11	1
90R27 20-25	2	28	14	120	.3	19	10	1211	4.86	67	5	ND	1	21	.8	5	2	59	.58	.154	21	52	1.57	324	.01	3	2.45	.02	.13	1
90R27 25-30	2	30	15	113	.3	20	12	908	4.60	130	5	ND	1	19	.2	2	2	60	.51	.105	20	43	1.32	304	.01	2	2.26	.01	.14	1
90R27 30-35	2	15	9	124	.5	12	9	1137	5.02	74	5	ND	2	20	.2	2	2	50	.55	.110	21	46	1.70	420	.01	3	2.71	.02	.21	1
90R27 35-40	2	26	21	97	.4	15	9	1320	3.65	56	5	ND	2	20	.7	2	2	39	.47	.079	23	32	1.30	387	.01	2	2.07	.01	.19	1
90R27 40-45	1	28	22	86	.4	13	6	534	2.67	54	5	ND	3	16	.4	3	2	28	.33	.057	25	33	.88	286	.01	2	1.50	.01	.18	1
90R27 45-50	2	23	21	66	.4	17	5	401	1.97	247	5	ND	5	14	.2	2	2	20	.23	.046	27	39	.80	261	.01	2	1.23	.01	.20	1
90R27 50-55	2	23	12	90	.8	17	7	497	2.95	1107	5	ND	3	22	.4	5	2	23	.29	.060	21	36	.82	292	.01	3	1.46	.01	.23	1
90R27 55-60	4	25	21	92	.8	16	7	595	2.65	921	5	ND	4	38	.2	6	2	16	.53	.091	23	33	.70	200	.01	3	1.19	.01	.22	1
90R27 60-65	4	20	18	84	.5	16	6	364	2.48	243	5	ND	4	54	.2	2	2	16	.80	.068	26	23	.72	204	.01	3	1.16	.01	.20	1
90R27 65-70	4	19	10	82	.4	14	7	349	2.18	143	5	ND	9	68	.2	3	2	20	1.04	.067	37	31	.87	346	.01	2	1.28	.01	.32	1
90R27 70-75	2	8	21	39	.3	6	3	222	.91	198	5	ND	12	61	.5	2	2	6	.86	.016	39	14	.38	196	.01	2	.55	.01	.17	1
90R27 75-80	3	6	27	30	.2	3	2	260	.65	151	5	ND	13	47	.3	2	2	3	.75	.012	43	22	.32	273	.01	2	.55	.01	.22	1
90R27 80-85	4	5	58	23	.5	4	2	319	.56	137	5	ND	10	15	.2	2	3	4	.18	.012	33	33	.28	206	.01	2	.43	.01	.16	2
90R27 85-90	6	10	23	26	.4	5	2	301	.70	81	5	ND	9	9	.5	2	2	6	.07	.008	28	64	.19	275	.01	2	.42	.01	.17	2
90R27 90-95	4	19	14	44	.4	12	4	335	1.31	159	5	ND	8	39	.5	2	2	12	.51	.019	31	46	.49	246	.01	2	.71	.01	.19	1
90R27 95-100	3	23	20	65	.6	23	7	452	1.65	144	5	ND	3	91	.2	2	2	17	1.69	.034	16	47	.81	271	.01	2	.96	.01	.16	1
90R27 100-105	2	17	25	79	1.0	19	8	1238	2.72	192	5	ND	1	201	.5	2	2	37	4.01	.057	10	43	1.34	196	.01	2	1.39	.01	.15	1
90R27 105-110	1	11	15	99	.2	9	9	1149	3.86	26	5	ND	1	224	.2	2	2	42	5.63	.087	13	38	2.21	119	.01	2	2.31	.01	.13	1
90R27 110-115	2	13	12	104	.4	8	8	863	3.60	34	5	ND	2	162	.2	2	2	46	3.96	.096	16	53	2.14	149	.01	2	2.24	.02	.15	1
90R27 115-120	1	22	13	93	.3	12	8	807	3.41	95	5	ND	1	160	.2	2	2	42	3.77	.086	17	49	1.92	137	.01	2	1.97	.02	.13	1
90R27 120-125	2	24	11	80	.4	21	7	437	2.39	23	5	ND	3	67	.2	2	2	24	1.50	.054	17	49	1.09	136	.04	3	1.22	.01	.11	1
90R27 125-130	1	29	10	89	.4	20	10	412	3.01	9	5	ND	4	52	.2	2	2	33	1.13	.078	26	61	1.72	196	.08	2	1.82	.02	.16	1
90R27 130-135	12	25	17	80	.4	20	8	588	2.45	19	5	ND	3	67	.2	2	2	22	1.52	.065	21	153	1.05	195	.02	2	1.30	.02	.13	1
90R27 135-140	2	23	33	85	.4	12	8	848	3.00	9	5	ND	1	144	.2	2	2	26	4.52	.082	16	45	1.63	169	.02	2	1.76	.01	.14	1
90R27 140-145	1	23	24	97	.4	11	9	1047	3.47	4	5	ND	1	168	.2	2	2	34	5.76	.112	15	39	1.97	112	.04	2	2.10	.01	.09	1
90R27 145-150	1	13	21	61	.3	7	5	670	1.53	13	5	ND	5	167	.2	2	2	10	4.82	.059	20	27	.97	163	.01	2	1.05	.01	.12	1
90R27 150-155	3	7	19	47	.4	4	2	213	.86	16	5	ND	7	84	.2	2	2	3	1.20	.013	23	41	.83	254	.01	4	.86	.01	.13	1
90R27 155-160	2	11	25	54	.3	5	3	343	1.37	20	5	ND	6	121	.3	2	2	8	2.07	.027	22	28	1.13	193	.01	2	1.17	.01	.12	1
90R27 160-165	3	5	11	51	.2	3	2	119	.78	3	5	ND	4	43	.2	2	2	1	.40	.010	15	42	1.17	216	.01	2	1.12	.02	.12	1
90R27 165-170	1	8	21	42	.1	5	2	459	.96	9	5	ND	2	135	.8	2	2	3	6.76	.020	12	20	1.06	151	.01	2	1.00	.01	.09	1
90R27 170-175	1	7	15	41	.3	2	3	754	.96	8	5	ND	1	194	.4	2	2	3	11.92	.037	8	22	1.04	158	.01	2	.96	.01	.07	1
90R27 175-180	2	11	22	49	.2	2	2	125	.76	6	5	ND	8	90	.4	2	2	1	.87	.011	22	20	1.00	319	.01	2	.95	.02	.10	1
STANDARD C	19	63	40	133	6.7	73	32	1051	3.99	43	17	7	36	53	18.4	15	21	58	.50	.097	37	60	.87	179	.08	36	1.89	.06	.13	11

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: DEC 4 1990 **DATE REPORT MAILED:** Dec 6/90 **SIGNED BY.** D. Toye .D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R27 180-185	2	7	16	51	.2	3	2	117	.83	5	5	ND	6	65	.2	2	2	1	.66	.014	21	25	1.08	225	.01	3	1.02	.02	.11	1
90R27 185-190	2	9	19	47	.2	3	1	108	.82	12	5	ND	8	73	.2	2	2	1	.68	.011	28	21	.95	194	.01	2	.89	.02	.10	1
90R27 190-195	3	11	18	42	.3	5	1	114	.84	9	5	ND	7	77	.2	2	2	1	.69	.010	22	29	.98	223	.01	3	.93	.02	.10	2
90R27 195-200	3	8	18	43	.2	4	1	148	.85	6	5	ND	7	104	.2	2	2	2	.90	.011	24	24	.98	323	.01	2	.94	.02	.11	3

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R28 0-5	7	13	14	48	.2	11	5	286	1.38	18	5	ND	6	11	.7	2	3	16	.13	.028	18	84	.55	315	.02	2	.79	.01	.10	1
90R28 5-10	7	9	16	53	.1	11	5	257	1.30	18	5	ND	6	13	.2	2	2	14	.11	.026	18	85	.49	303	.01	2	.74	.01	.11	1
90R28 10-15	4	21	21	97	.2	21	9	528	2.07	27	5	ND	7	21	.3	2	2	24	.35	.090	30	55	.99	295	.01	2	1.42	.01	.15	1
90R28 15-20	6	37	29	91	.3	31	15	511	3.88	20	5	ND	3	17	.2	2	2	54	.32	.065	12	100	2.52	273	.07	3	2.52	.02	.11	1
90R28 20-25	4	46	58	92	.4	33	14	498	3.85	35	5	ND	2	13	.2	2	2	59	.28	.068	12	70	2.50	198	.06	2	2.40	.01	.08	1
90R28 25-30	5	44	18	109	.3	36	16	504	4.08	21	5	ND	2	24	.2	2	2	65	.38	.072	8	86	2.26	222	.09	4	2.43	.03	.07	1
90R28 30-35	4	39	17	97	.6	37	17	521	3.90	39	5	ND	2	24	.2	2	2	64	.39	.071	11	85	2.00	214	.06	3	2.31	.02	.08	1
90R28 35-40	5	44	16	106	.4	35	16	481	4.00	35	5	ND	2	26	.9	2	2	59	.45	.071	11	87	2.10	208	.08	3	2.33	.03	.11	1
90R28 40-45	7	42	19	94	.4	31	14	461	3.92	24	5	ND	3	33	1.0	2	2	48	.83	.071	14	101	2.79	154	.05	3	2.57	.02	.15	1
90R28 45-50	6	43	22	126	.6	42	15	409	3.64	56	5	ND	4	18	.2	2	2	38	.35	.075	19	70	2.50	134	.02	2	2.23	.01	.15	1
90R28 50-55	8	47	27	254	.4	38	13	324	3.53	17	5	ND	4	39	2.8	2	2	33	.72	.074	17	85	1.68	182	.04	2	1.58	.01	.22	1
90R28 55-60	8	54	13	86	.6	36	13	250	3.53	10	5	ND	4	60	.7	2	2	53	.83	.075	15	107	1.70	141	.07	2	1.61	.03	.17	1
90R28 60-65	7	53	37	89	.7	38	13	281	4.18	36	5	ND	4	62	.3	2	2	82	.81	.077	17	104	2.18	104	.03	2	2.08	.04	.14	1
90R28 65-70	7	43	14	80	.7	37	13	238	3.74	29	5	ND	4	51	.2	2	2	77	.75	.075	16	100	1.96	105	.04	2	1.81	.03	.15	1
90R28 70-75	6	47	23	110	.9	35	13	414	4.25	63	5	ND	4	52	.3	2	2	61	.82	.075	17	84	2.65	167	.04	2	2.35	.02	.18	1
90R28 75-80	6	36	25	101	.7	23	10	372	4.16	5	5	ND	4	95	.2	2	2	38	1.41	.079	15	78	2.15	141	.05	2	2.05	.02	.17	1
90R28 80-85	5	42	21	117	.5	35	12	446	4.11	17	5	ND	4	69	.2	2	2	49	.92	.074	16	63	2.48	116	.05	2	2.15	.02	.13	1
90R28 85-90	5	54	34	146	.7	39	12	517	4.36	25	5	ND	4	70	.2	2	2	44	1.01	.074	18	49	2.38	123	.05	4	2.04	.01	.13	1
90R28 90-95	5	42	18	111	.7	32	13	426	3.91	32	5	ND	4	86	.2	2	2	37	1.28	.073	18	64	2.06	151	.04	2	1.95	.02	.17	1
90R28 95-100	7	35	19	91	1.3	25	10	449	3.44	45	5	ND	4	84	.3	2	2	39	1.39	.072	14	85	1.92	181	.01	3	1.92	.01	.19	1
90R28 100-105	6	45	17	93	.4	36	12	383	3.69	22	5	ND	3	97	.2	2	2	35	1.66	.074	17	76	2.08	154	.02	2	2.00	.01	.16	1
90R28 105-110	6	33	23	95	.4	33	12	328	3.45	19	5	ND	4	81	.4	2	2	31	1.26	.074	13	69	1.99	162	.01	2	1.98	.01	.17	1
90R28 110-115	5	31	12	98	.3	23	10	318	3.59	31	5	ND	4	76	.2	2	2	34	1.31	.074	14	65	2.05	151	.01	2	1.93	.01	.16	1
90R28 115-120	5	23	21	98	.3	19	9	297	3.37	24	5	ND	4	73	.2	2	2	38	1.10	.074	17	76	1.93	249	.03	3	1.78	.02	.21	1
90R28 120-125	2	22	12	88	.3	17	10	264	3.23	27	5	ND	4	60	.2	2	2	37	.82	.076	16	49	1.87	246	.07	2	1.70	.02	.37	1
90R28 125-130	4	17	14	96	.3	12	9	223	3.08	12	5	ND	4	60	.2	2	2	33	.67	.075	18	67	2.05	261	.09	3	1.79	.02	.44	1
90R28 130-135	3	27	13	95	.2	12	9	242	3.24	11	5	ND	4	54	.2	2	2	33	.64	.078	16	53	2.11	205	.08	2	1.86	.02	.31	1
90R28 135-140	3	23	24	83	.3	10	8	251	3.00	11	5	ND	4	104	.2	2	2	32	1.00	.074	17	54	1.76	168	.08	2	1.60	.02	.41	1
90R28 140-145	2	22	29	91	.3	9	8	208	3.28	7	5	ND	4	62	.2	2	2	38	.77	.076	17	47	2.11	133	.05	2	1.84	.02	.32	1
90R28 145-150	3	15	14	107	.3	8	9	223	3.55	4	5	ND	5	63	.2	2	2	55	.84	.077	19	71	2.22	89	.03	2	1.99	.06	.11	1
90R28 150-155	2	20	14	88	.1	11	8	193	3.16	6	5	ND	4	46	.2	2	2	30	.67	.073	15	48	2.32	90	.02	2	1.88	.02	.15	1
90R28 155-160	3	22	7	78	.2	11	9	296	2.93	8	5	ND	3	84	.4	2	2	29	1.48	.073	12	54	1.66	110	.01	2	1.44	.02	.13	1
90R28 160-165	3	26	15	80	.5	13	12	319	2.99	8	5	ND	3	139	.3	2	2	37	1.88	.067	13	57	1.31	108	.02	2	1.31	.03	.12	1
90R28 165-170	8	5	16	14	.3	6	3	92	.60	2	5	ND	1	36	.2	2	2	9	.85	.012	2	102	.32	41	.01	2	.29	.01	.03	2
90R28 170-175	4	20	11	56	.2	21	12	310	2.60	7	5	ND	1	87	.2	2	2	35	1.55	.048	5	76	1.67	102	.08	2	1.50	.02	.10	1
90R28 175-180	3	28	15	75	.5	21	14	321	2.73	6	5	ND	1	63	.2	2	2	37	1.16	.055	4	67	1.76	106	.08	3	1.61	.02	.10	1
STANDARD C	19	61	42	133	7.6	73	32	1048	3.99	43	17	7	36	52	18.4	14	21	57	.48	.097	36	60	.86	179	.07	35	1.90	.06	.13	12

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R28 180-185	5	26	10	74	.4	17	12	430	2.72	5	5	ND	1	63	.3	2	2	26	1.21	.060	5	58	1.47	130	.06	4	1.47	.01	.09	1
90R28 185-190	3	22	3	65	.4	13	13	340	2.21	7	5	ND	1	42	.2	4	2	21	.90	.062	2	50	1.20	107	.08	2	1.22	.01	.08	1
90R28 190-195	4	11	13	98	.3	12	12	292	2.03	8	5	ND	1	53	.4	3	2	19	1.33	.078	5	54	1.06	140	.06	2	1.09	.01	.09	1
90R28 195-200	4	14	9	100	.4	20	12	176	1.73	11	5	ND	2	58	.6	3	2	17	1.03	.079	10	52	.90	199	.09	6	.84	.01	.12	1

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#13032 File # 90-6250 Page 1

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R29 0-5	7	12	39	49	.3	11	3	262	.94	20	5	ND	8	22	.5	2	2	7	.23	.014	26	61	.22	540	.01	5	.42	.01	.09	1
90R29 5-10	4	5	26	28	.2	5	1	96	.47	6	5	ND	12	13	.4	2	3	2	.07	.006	30	32	.06	423	.01	2	.25	.01	.09	1
90R29 10-15	4	7	30	23	.3	7	1	239	.39	7	5	ND	10	16	.2	2	2	2	.11	.006	21	33	.07	436	.01	2	.21	.01	.07	1
90R29 15-20	8	9	28	21	.2	5	2	197	.37	4	5	ND	7	27	.2	2	2	3	.22	.007	20	78	.06	274	.01	2	.30	.01	.12	1
90R29 20-25	6	9	34	24	.2	6	1	160	.35	8	5	ND	7	20	.2	2	2	3	.14	.006	19	54	.05	256	.01	3	.26	.01	.09	1
90R29 25-30	4	6	28	26	.5	4	1	78	.26	4	5	ND	6	21	.3	2	2	2	.16	.006	16	37	.03	198	.02	3	.24	.02	.09	1
90R29 30-35	5	7	27	22	.4	3	1	60	.27	3	5	ND	9	18	.3	2	2	1	.13	.004	19	45	.03	181	.01	2	.22	.01	.10	1
90R29 35-40	4	4	27	20	.2	4	1	66	.31	4	5	ND	13	44	.2	2	2	1	.32	.005	34	41	.02	441	.01	2	.21	.01	.11	1
90R29 40-45	7	5	18	42	.3	4	1	56	.41	5	5	ND	9	19	.6	2	2	1	.12	.004	22	73	.07	323	.01	2	.33	.02	.10	2
90R29 45-50	9	7	20	44	.3	5	1	60	.52	9	5	ND	7	24	.3	2	2	1	.26	.005	20	55	.10	310	.01	2	.32	.02	.09	2
90R29 50-55	5	4	17	27	.3	3	1	55	.57	11	5	ND	13	23	.2	2	2	1	.26	.006	36	30	.05	258	.01	4	.25	.01	.09	1
90R29 55-60	6	4	12	21	.2	2	1	53	.42	9	5	ND	11	19	.8	2	4	1	.13	.004	28	60	.03	354	.01	2	.29	.02	.12	1
90R29 60-65	4	4	22	19	.5	3	1	59	.33	7	5	ND	12	31	.2	2	2	1	.23	.004	36	41	.02	278	.01	2	.22	.01	.11	2
90R29 65-70	8	5	25	23	.4	3	1	91	.37	4	5	ND	11	31	.2	2	2	1	.27	.004	33	84	.03	251	.01	2	.26	.02	.15	3
90R29 70-75	5	3	35	26	.4	3	1	70	.36	7	5	ND	12	28	.2	2	3	1	.25	.004	36	49	.04	397	.01	2	.21	.01	.10	1
90R29 75-80	4	3	26	22	.3	2	1	36	.34	4	5	ND	14	9	.2	2	2	1	.06	.003	35	42	.02	195	.01	2	.20	.01	.11	1
90R29 80-85	4	3	19	17	.8	2	1	39	.27	7	6	ND	14	14	.2	2	2	1	.08	.004	38	31	.02	415	.01	3	.18	.01	.11	1
90R29 85-90	6	3	15	16	.5	4	1	42	.28	6	5	ND	13	16	.2	2	2	1	.10	.004	36	60	.02	378	.01	2	.21	.02	.13	2
90R29 90-95	7	3	17	17	.3	2	1	42	.30	4	5	ND	11	15	.2	2	2	1	.09	.003	30	59	.05	550	.01	2	.22	.01	.11	1
90R29 95-100	5	3	23	18	.3	2	1	50	.36	14	5	ND	13	13	.3	2	2	1	.07	.003	24	35	.09	503	.01	4	.22	.01	.10	1
90R29 100-105	8	3	67	17	.5	2	1	35	.45	11	7	ND	11	12	.2	2	2	1	.05	.005	21	52	.05	294	.01	3	.20	.01	.11	1
90R29 105-110	5	7	18	38	.4	3	3	140	.83	8	5	ND	6	81	1.2	2	2	2	.43	.019	15	45	.32	234	.01	2	.40	.01	.14	1
90R29 110-115	4	9	24	57	.4	5	3	215	1.11	8	5	ND	6	155	1.0	3	2	4	.71	.021	15	42	.55	195	.01	3	.54	.01	.10	1
90R29 115-120	5	8	18	51	.9	1	3	170	1.12	7	5	ND	4	113	.7	3	2	3	.54	.022	12	56	.47	292	.02	2	.50	.01	.18	1
90R29 120-125	5	8	15	70	.3	4	3	133	1.16	8	5	ND	5	73	.9	2	2	3	.31	.023	13	52	.53	313	.02	2	.57	.01	.20	1
90R29 125-130	5	9	23	75	.4	2	2	100	1.11	8	5	ND	5	42	.3	4	2	3	.15	.021	14	49	.47	257	.01	2	.54	.01	.17	1
90R29 130-135	6	5	22	62	.3	2	2	144	1.08	7	5	ND	5	65	.5	2	2	3	.29	.022	14	61	.46	268	.01	2	.54	.01	.15	1
90R29 135-140	5	3	14	22	.2	1	1	55	.42	4	5	ND	9	13	.2	2	2	1	.05	.007	24	53	.15	228	.01	2	.25	.01	.11	1
90R29 140-145	8	4	18	24	.3	2	1	69	.37	4	5	ND	10	35	.2	2	2	1	.37	.005	35	78	.08	268	.01	3	.26	.02	.13	1
90R29 145-150	6	6	16	24	.3	2	1	53	.33	3	5	ND	11	39	.2	2	2	1	.37	.003	40	55	.08	325	.01	2	.25	.01	.10	1
90R29 150-155	6	3	16	13	.4	2	1	81	.38	10	5	ND	9	73	.2	2	2	1	.86	.003	28	60	.03	243	.01	4	.18	.01	.10	1
90R29 155-160	5	3	16	15	.3	1	1	59	.23	7	5	ND	10	57	.2	2	2	1	.54	.002	26	49	.03	258	.01	5	.17	.01	.11	1
90R29 160-165	6	3	39	20	.4	1	1	95	.32	7	5	ND	9	18	.2	2	2	1	.11	.002	17	56	.06	485	.01	7	.18	.01	.09	1
90R29 165-170	6	3	66	31	.6	2	1	115	.39	7	5	ND	7	52	.5	2	2	1	.41	.005	14	62	.09	399	.01	3	.19	.01	.09	1
90R29 170-175	5	8	29	35	1.1	2	1	129	.40	8	5	ND	6	72	.7	2	2	1	.61	.010	23	45	.09	536	.01	2	.23	.01	.12	1
90R29 175-180	3	6	24	34	.6	1	1	152	.59	10	5	ND	7	88	.3	2	2	1	.64	.009	21	39	.15	342	.01	2	.29	.01	.15	1
STANDARD C	19	61	35	133	7.3	73	32	1058	3.98	43	17	8	36	53	18.6	15	20	60	.50	.096	37	59	.86	179	.08	36	1.90	.06	.13	12

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: DEC 7 1990 **DATE REPORT MAILED:** Dec 11/90 **SIGNED BY** ..... D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R29 180-185	4	6	25	26	.3	1	1	88	.44	2	5	ND	8	51	.4	2	2	1	.38	.008	20	40	.08	371	.01	2	.24	.02	.18	1
90R29 185-190	10	5	49	28	.6	1	1	92	.60	11	5	ND	7	47	.2	2	2	1	.32	.008	16	40	.11	268	.01	2	.22	.01	.13	1
90R29 190-195	6	4	41	25	.3	1	1	35	.40	6	5	ND	7	8	.2	2	2	1	.05	.011	16	42	.06	429	.01	2	.18	.01	.13	1
90R29 195-200	9	4	21	14	.1	2	1	38	.37	5	5	ND	5	8	.2	2	2	1	.05	.007	16	105	.03	503	.01	3	.18	.01	.15	1
90R29 200-205	4	4	78	18	.7	1	1	47	.42	4	5	ND	7	43	.2	2	2	1	.34	.007	18	39	.02	297	.01	3	.16	.01	.14	1
90R29 205-210	7	4	20	12	.3	1	1	64	.55	9	5	ND	7	53	.2	2	2	1	.47	.006	13	74	.02	274	.01	3	.17	.02	.15	1
90R29 210-215	4	7	18	13	.8	1	1	89	.39	6	5	ND	7	84	.2	2	2	1	.70	.007	17	42	.02	453	.01	3	.17	.02	.14	1
90R29 215-220	5	3	19	13	.4	1	1	68	.42	6	5	ND	7	64	.2	2	2	1	.50	.005	18	60	.01	411	.01	2	.16	.02	.16	4
90R29 220-225	3	4	12	12	.4	1	1	77	.38	6	5	ND	7	94	.2	3	2	1	.69	.007	16	35	.01	358	.01	2	.17	.02	.15	4
90R29 225-230	4	4	14	15	.4	1	1	69	.40	6	5	ND	8	80	.2	2	2	1	.66	.006	16	46	.02	304	.01	2	.17	.01	.15	2
90R29 230-235	3	3	16	9	.4	1	1	51	.31	5	5	ND	7	61	.2	2	3	1	.41	.005	13	38	.06	585	.01	2	.18	.01	.14	9
90R29 235-240	6	7	18	12	.2	1	1	66	.40	4	5	ND	8	62	.2	2	2	1	.47	.004	19	69	.10	576	.01	2	.23	.02	.18	6
90R29 240-245	3	4	12	13	.3	1	1	62	.31	2	5	ND	8	74	.2	2	2	1	.58	.007	22	36	.09	664	.01	2	.21	.01	.15	1
90R29 245-250	5	4	23	21	.3	1	1	71	.42	4	5	ND	7	68	.3	2	2	1	.49	.005	14	54	.12	322	.01	2	.23	.01	.15	1
90R29 250-255	6	5	27	21	.7	1	1	131	.61	2	5	ND	7	88	.2	2	2	1	.79	.007	12	54	.21	279	.01	2	.29	.01	.17	1
90R29 255-260	5	2	9	29	.1	1	1	104	.53	3	5	ND	7	95	.2	2	2	1	.56	.004	11	54	.23	288	.01	2	.30	.01	.17	1
90R29 260-265	5	5	14	65	.4	1	1	169	.77	8	5	ND	8	152	.4	2	2	1	.68	.004	10	30	.64	281	.01	2	.51	.01	.16	1
90R29 265-270	9	6	16	79	.5	1	1	218	.77	7	5	ND	8	144	.8	2	2	1	.99	.005	10	74	.41	292	.01	3	.40	.01	.19	1
90R29 270-275	4	4	12	35	.2	1	1	47	.34	2	5	ND	7	24	.4	2	2	1	.15	.005	14	42	.07	208	.01	2	.17	.01	.13	3
90R29 275-280	4	4	13	27	.3	1	1	65	.44	2	5	ND	8	35	.2	2	2	1	.17	.007	20	34	.10	446	.01	2	.23	.02	.13	2
90R29 280-285	4	4	14	27	.7	1	1	108	.60	5	5	ND	7	40	.2	2	2	1	.34	.006	17	47	.11	449	.01	2	.25	.02	.14	1
90R29 285-290	5	6	16	22	.4	1	1	101	.53	7	5	ND	8	67	.2	2	2	1	.49	.007	19	54	.11	395	.01	3	.27	.02	.17	1
90R29 290-295	5	7	20	34	.3	1	1	171	.60	5	5	ND	8	144	.4	2	2	1	1.06	.006	17	53	.22	321	.01	2	.30	.02	.17	2
90R29 295-300	6	3	25	9	.2	1	1	35	.28	4	5	ND	8	20	.2	2	2	1	.19	.001	17	71	.03	590	.01	2	.18	.02	.16	2
90R29 300-305	6	1	17	16	.3	1	1	120	.45	2	5	ND	7	55	.2	2	2	1	.45	.003	12	58	.11	313	.01	3	.21	.02	.13	2
90R29 305-310	5	4	16	39	.3	1	1	333	.69	3	5	ND	7	147	.3	2	2	1	.95	.006	12	55	.38	279	.01	2	.29	.01	.17	1
90R29 310-315	7	5	21	17	.6	1	1	155	.40	8	5	ND	11	83	.3	2	3	1	.64	.004	25	51	.23	371	.01	2	.22	.02	.17	1
90R29 315-320	9	6	8	15	.6	1	1	140	.61	2	5	ND	6	62	.2	2	2	1	.50	.004	9	81	.12	331	.01	2	.21	.02	.14	2
90R29 320-325	6	4	14	10	.2	1	1	98	.54	7	5	ND	8	93	.3	2	2	1	.85	.006	20	64	.03	420	.01	2	.22	.01	.18	1
90R29 325-330	4	3	13	12	.4	1	1	90	.59	13	5	ND	7	52	.2	2	3	1	.49	.007	17	47	.02	289	.01	2	.18	.01	.14	1
90R29 330-335	5	5	13	12	.3	1	1	92	.53	8	5	ND	7	71	.2	2	2	1	.53	.006	19	39	.02	383	.01	2	.19	.01	.13	7
90R29 335-340	6	6	15	28	.2	1	1	188	.65	2	5	ND	8	81	.2	2	2	1	.73	.007	23	58	.08	327	.01	2	.28	.02	.16	2
90R29 340-345	3	7	19	44	.5	1	1	164	.74	6	5	ND	9	53	.3	2	2	1	.39	.007	24	39	.08	435	.01	2	.28	.02	.16	3
90R29 345-350	4	6	20	24	.4	1	1	232	.62	2	5	ND	7	141	.4	2	2	1	1.16	.006	19	39	.07	486	.01	2	.23	.01	.12	1
90R29 350-355	3	5	16	25	.3	1	1	146	.46	2	5	ND	8	74	.3	2	2	1	.56	.007	21	29	.12	535	.01	2	.23	.02	.14	2
90R29 355-360	5	4	19	45	.3	1	1	184	.70	2	5	ND	9	120	.4	2	2	1	1.17	.008	24	38	.29	524	.01	2	.39	.01	.15	1
STANDARD C	18	59	39	131	6.7	73	31	1056	3.96	41	21	7	36	52	19.0	19	17	56	.47	.093	36	58	.87	179	.07	32	1.89	.05	.14	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R29 360-365	4	4	16	51	.4	1	2	234	.90	2	5	ND	8	118	.5	2	2	3	1.01	.009	22	39	.39	346	.01	5	.44	.01	.13	2
90R29 365-370	4	5	24	65	.6	2	2	78	.66	4	5	ND	7	44	.9	2	2	1	.48	.006	19	40	.08	162	.01	2	.21	.01	.12	2
90R29 370-375	7	5	13	42	.7	2	2	115	.75	3	5	ND	7	50	.7	2	2	1	.39	.006	22	69	.14	270	.01	2	.30	.03	.15	2
90R29 375-380	3	3	17	32	.5	1	1	80	.53	6	5	ND	8	54	.3	2	2	1	.32	.007	25	33	.13	446	.01	3	.27	.02	.15	1
90R29 380-385	5	3	20	36	.5	1	1	82	.43	5	5	ND	8	52	.4	2	2	1	.41	.006	21	52	.06	400	.01	5	.23	.02	.15	2
90R29 385-390	5	3	21	11	.3	1	1	102	.37	2	5	ND	8	71	.2	2	2	1	.60	.006	26	56	.04	401	.01	2	.23	.02	.16	1
90R29 390-395	8	4	17	58	.4	2	2	239	.83	7	5	ND	7	135	.3	2	2	1	1.06	.005	15	73	.42	239	.01	4	.40	.01	.14	3
90R29 395-400	6	4	16	76	.5	2	2	203	1.13	3	5	ND	8	98	.2	2	2	1	.97	.006	24	52	.84	626	.01	6	.87	.01	.11	1
90R29 400-405	5	4	17	59	.5	2	2	243	.89	3	5	ND	8	121	.2	2	2	1	1.59	.006	26	49	.46	511	.01	6	.57	.01	.11	1
90R29 405-410	5	6	15	16	.5	2	2	171	.61	2	5	ND	8	130	.5	2	3	1	1.43	.004	24	44	.09	776	.01	4	.25	.01	.12	1
90R29 410-415	6	4	18	10	.4	1	1	139	.46	2	5	ND	9	102	.6	2	2	1	.99	.004	25	71	.04	614	.01	5	.23	.02	.16	1
90R29 415-420	5	5	18	38	.6	4	2	180	.66	4	5	ND	9	83	.5	3	2	1	.74	.005	26	47	.28	642	.01	3	.41	.01	.12	1
90R29 420-425	6	3	18	47	.6	2	2	109	.60	2	5	ND	7	93	.2	2	2	1	.62	.004	19	54	.48	773	.01	4	.46	.01	.11	1
90R29 425-430	4	5	27	23	.6	2	3	67	.42	3	5	ND	8	76	.5	2	2	1	.52	.004	20	46	.17	545	.01	4	.27	.02	.13	5
90R29 430-435	8	5	33	29	.6	4	2	69	.45	3	5	ND	7	63	.5	2	2	1	.44	.003	16	76	.17	312	.01	4	.28	.01	.14	5
90R29 435-440	6	4	17	40	.5	5	7	144	.91	3	5	ND	6	98	.2	2	2	1	.62	.005	10	61	.36	257	.01	3	.40	.01	.14	11
90R29 440-445	7	4	28	25	.6	8	3	82	.57	4	5	ND	7	70	.4	2	2	1	.33	.007	14	60	.27	269	.01	4	.34	.01	.15	7
90R29 445-450	6	5	27	50	8.4	4	4	210	1.34	4	5	20	6	69	.2	2	2	4	.39	.030	15	67	.86	354	.01	5	.82	.02	.13	5
STANDARD C	17	57	40	129	7.0	70	32	1055	3.97	39	20	6	36	53	18.3	15	17	55	.46	.100	37	59	.87	179	.07	38	1.84	.06	.13	12

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90-R30 0-5	6	11	76	62	.3	6	3	178	.86	9	5	ND	5	16	.5	2	2	7	.19	.018	16	65	.26	418	.01	2	.39	.01	.12	1
90-R30 5-10	5	10	51	51	.5	5	1	45	.70	7	5	ND	7	10	.2	2	2	5	.06	.008	23	47	.11	338	.01	2	.40	.01	.14	1
90-R30 10-15	4	5	29	45	.3	4	2	77	.70	5	5	ND	7	14	.3	2	2	6	.07	.012	22	39	.13	364	.01	2	.39	.01	.15	1
90-R30 15-20	5	6	25	48	.2	7	2	129	.87	4	5	ND	6	93	.2	2	2	6	.08	.017	22	45	.53	1376	.01	2	.59	.01	.14	1
90-R30 20-25	3	8	19	44	.3	8	3	129	.96	7	5	ND	6	28	.2	2	2	11	.14	.019	24	33	.46	361	.02	2	.66	.01	.12	1
90-R30 25-30	4	5	30	66	.4	4	3	188	1.38	7	5	ND	6	17	.2	2	2	7	.10	.022	24	45	.62	248	.01	2	.80	.01	.16	1
90-R30 30-35	4	8	36	64	.4	5	3	167	1.31	6	5	ND	6	20	.2	2	2	10	.13	.025	24	39	.44	329	.02	2	.70	.01	.19	1
90-R30 35-40	3	7	20	68	.2	3	4	244	1.67	3	5	ND	5	17	.3	2	2	9	.14	.036	23	31	.49	276	.04	2	.71	.02	.21	1
90-R30 40-45	7	5	15	72	.2	4	3	232	1.66	6	5	ND	6	20	.3	2	2	8	.13	.032	23	75	.49	427	.03	2	.73	.03	.23	1
90-R30 45-50	4	7	18	60	.3	6	4	192	1.45	7	5	ND	6	16	.5	2	2	9	.14	.031	22	38	.42	311	.03	2	.66	.02	.17	1
90-R30 50-55	7	12	29	67	.1	10	4	229	1.63	8	5	ND	6	19	.2	2	2	12	.19	.034	23	63	.50	356	.03	2	.78	.02	.19	1
90-R30 55-60	5	26	22	83	.2	7	4	182	1.48	9	5	ND	6	14	.5	2	2	8	.14	.028	22	43	.46	337	.01	2	.73	.01	.16	1
90-R30 60-65	4	9	18	68	.3	5	4	183	1.40	8	5	ND	5	14	.5	2	2	8	.16	.030	21	39	.44	291	.01	3	.67	.01	.15	1
90-R30 65-70	5	8	17	78	.2	4	2	172	1.57	3	5	ND	6	15	.2	2	2	6	.16	.027	24	54	.47	311	.01	2	.76	.03	.13	1
90-R30 70-75	4	6	19	91	.2	6	3	160	1.52	6	5	ND	6	9	.5	2	2	5	.10	.027	24	42	.55	316	.01	2	.78	.02	.13	1
90-R30 75-80	9	10	29	113	.3	7	3	230	1.80	10	5	ND	6	12	.6	2	2	6	.13	.029	28	93	.69	409	.01	3	1.05	.02	.20	1
90-R30 80-85	7	7	22	83	.2	5	3	279	1.60	4	5	ND	5	14	.6	2	2	5	.18	.028	23	79	.71	318	.01	2	.96	.01	.17	1
90-R30 85-90	10	8	16	77	.2	7	3	367	1.55	2	5	ND	5	13	.2	2	2	4	.17	.028	20	104	.70	320	.01	2	.91	.01	.18	1
90-R30 90-95	8	10	29	93	.2	6	3	294	1.75	9	5	ND	6	14	.8	2	2	7	.13	.028	24	80	.56	286	.01	2	.88	.02	.16	1
90-R30 95-100	4	8	20	90	.2	4	2	282	1.52	6	5	ND	5	12	.2	2	2	5	.11	.027	20	43	.47	177	.01	2	.70	.01	.11	1
90-R30 100-105	5	7	20	84	.3	3	3	334	1.76	5	5	ND	5	19	.5	2	2	7	.21	.026	24	59	.51	141	.01	2	.81	.04	.10	1
90-R30 105-110	5	8	18	86	.2	4	3	299	1.78	5	5	ND	6	16	.5	2	2	6	.16	.025	22	53	.47	129	.01	3	.76	.04	.09	1
90-R30 110-115	4	7	18	82	.3	4	3	286	1.63	6	5	ND	5	19	.3	2	2	6	.18	.027	21	41	.45	147	.01	2	.71	.02	.09	1
90-R30 115-120	5	8	23	89	.1	5	3	302	1.80	4	5	ND	5	11	.4	2	2	6	.10	.025	23	54	.47	189	.01	2	.80	.03	.12	1
90-R30 120-125	4	7	31	102	.3	4	3	298	1.98	8	5	ND	6	19	.6	2	2	7	.14	.027	23	41	.50	172	.01	2	.82	.02	.11	1
90-R30 125-130	4	7	28	122	.3	5	3	299	1.88	6	5	ND	6	17	.3	2	2	6	.13	.026	21	44	.48	160	.01	2	.79	.02	.09	1
90-R30 130-135	7	7	23	79	.1	4	2	257	1.59	4	5	ND	5	17	.4	2	2	5	.14	.024	19	84	.42	219	.01	2	.68	.03	.11	1
90-R30 135-140	8	6	31	68	.3	3	2	217	1.40	4	5	ND	4	13	.7	2	2	4	.11	.022	16	94	.39	197	.01	2	.61	.03	.12	1
90-R30 140-145	6	7	35	73	.6	4	2	206	1.41	6	5	ND	5	13	.4	2	2	5	.12	.023	16	65	.40	177	.01	2	.62	.03	.13	1
90-R30 145-150	4	6	19	86	.4	2	3	226	1.67	4	5	ND	5	10	.5	2	2	5	.09	.025	17	44	.48	134	.01	2	.75	.04	.10	1
90-R30 150-155	7	7	38	63	.3	2	2	185	1.24	6	5	ND	4	18	.6	2	2	4	.13	.020	13	79	.31	197	.01	3	.50	.03	.13	1
90-R30 155-160	4	7	28	69	.3	1	3	248	1.44	5	5	ND	5	29	.3	2	2	4	.20	.025	16	47	.37	209	.01	2	.59	.03	.12	1
90-R30 160-165	4	7	33	69	.4	2	2	205	1.38	10	5	ND	5	12	.6	2	2	4	.09	.019	16	49	.38	146	.01	2	.55	.02	.12	1
90-R30 165-170	5	10	21	66	.3	3	2	226	1.34	8	5	ND	5	20	.2	2	2	4	.12	.020	15	47	.55	135	.01	2	.65	.02	.13	1
90-R30 170-175	6	7	37	74	.4	4	2	141	1.08	8	5	ND	4	32	.6	2	2	4	.21	.022	13	52	.46	159	.01	2	.54	.01	.13	1
90-R30 175-180	8	8	23	69	.2	4	2	129	1.31	31	5	ND	5	40	.4	2	2	5	.27	.024	15	71	.62	190	.01	2	.70	.02	.18	1
STANDARD C	20	62	39	132	7.4	72	32	1049	3.99	42	18	8	36	53	18.4	14	21	58	.49	.097	37	61	.86	179	.07	35	1.90	.06	.13	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R30 180-185	5	13	23	72	.2	4	3	142	1.34	32	5	ND	4	30	.7	2	2	5	.21	.021	13	48	.61	162	.01	5	.69	.01	.15	1
90R30 185-190	4	6	25	69	.1	2	3	110	1.18	12	5	ND	4	34	.7	2	2	5	.24	.022	15	38	.65	255	.01	3	.68	.01	.17	1
90R30 190-195	8	7	23	69	.3	1	3	149	1.20	17	5	ND	4	69	.4	2	2	4	.51	.024	13	61	.61	189	.01	4	.65	.01	.17	1
90R30 195-200	6	7	19	61	.2	2	3	484	1.30	25	5	ND	3	174	.6	2	2	5	1.65	.021	12	59	.68	178	.01	2	.71	.01	.15	1
90R30 200-205	6	5	18	51	.2	3	3	222	1.31	60	5	ND	4	61	.2	2	2	6	.49	.023	11	69	.68	176	.01	5	.69	.01	.19	1
90R30 205-210	4	5	12	46	.2	3	4	164	1.26	20	5	ND	5	35	.5	2	2	6	.29	.022	12	46	.56	155	.01	4	.61	.02	.16	1
90R30 210-215	7	10	14	64	.2	2	3	120	1.35	13	5	ND	4	29	.4	2	2	6	.21	.023	9	71	.64	183	.01	5	.66	.02	.21	1
90R30 215-220	5	6	13	62	.2	2	2	117	1.21	7	5	ND	4	32	.6	2	2	4	.23	.022	11	42	.76	174	.01	2	.72	.01	.16	1
90R30 220-225	7	5	11	61	.1	1	3	173	1.30	4	5	ND	4	20	.4	2	2	4	.14	.025	15	64	.54	423	.02	4	.65	.01	.20	1
90R30 225-230	6	5	24	86	.2	3	3	267	1.54	8	5	ND	5	29	.2	2	2	5	.14	.028	19	57	.52	748	.03	4	.64	.02	.21	1
90R30 230-235	5	6	24	92	.2	2	3	256	1.47	6	5	ND	5	32	.2	2	2	6	.13	.025	17	50	.50	1040	.03	2	.62	.02	.17	1
90R30 235-240	4	7	18	99	.4	1	3	342	1.55	5	5	ND	5	49	.5	2	2	5	.28	.027	17	44	.51	701	.04	2	.62	.02	.23	1
90R30 240-245	6	6	8	54	.2	3	3	204	1.11	4	5	ND	4	24	.2	2	2	4	.18	.022	17	70	.37	316	.02	2	.52	.02	.15	1
90R30 245-250	5	5	14	63	.3	2	2	212	1.02	4	5	ND	5	24	.2	2	2	3	.18	.017	21	63	.45	456	.01	5	.57	.02	.16	1
90R30 250-255	4	7	20	64	.3	2	3	332	1.28	4	5	ND	4	50	.3	2	2	4	.46	.025	17	41	.48	237	.02	3	.60	.02	.14	1
90R30 255-260	4	5	21	58	.2	2	3	339	1.21	3	5	ND	4	71	.4	2	2	3	.56	.025	17	46	.46	258	.02	2	.60	.01	.16	1
90R30 260-265	6	5	12	36	.2	1	2	126	.72	2	5	ND	5	43	.2	2	3	2	.32	.014	17	61	.19	238	.01	6	.33	.02	.12	1
90R30 265-270	5	3	11	7	1.0	1	1	51	.34	2	5	ND	6	27	.3	2	2	2	.28	.013	22	53	.05	314	.01	6	.23	.02	.13	1
90R30 270-275	7	2	6	4	.1	1	1	39	.31	2	5	ND	2	7	.4	2	2	1	.05	.006	6	91	.06	98	.01	5	.11	.01	.04	1
90R30 275-280	4	4	6	37	.1	1	2	194	.75	2	5	ND	5	52	.6	2	2	1	.36	.009	15	50	.22	172	.01	2	.34	.01	.11	1
90R30 280-285	6	6	19	64	.4	1	3	312	1.23	2	5	ND	5	52	.2	2	2	3	.37	.017	18	71	.41	286	.02	4	.58	.02	.17	1
90R30 285-290	5	5	15	49	.2	1	2	270	.93	4	5	ND	4	63	.2	2	2	2	.46	.016	14	60	.44	198	.01	2	.53	.01	.12	1
90R30 290-295	7	6	13	59	.1	4	2	260	1.12	5	5	ND	4	47	.7	2	2	4	.35	.021	15	83	.51	275	.01	4	.62	.02	.13	1
90R30 295-300	5	2	9	37	.1	3	2	244	.77	2	5	ND	3	102	.5	2	2	2	.72	.011	9	59	.40	273	.01	2	.43	.01	.12	1
90R30 300-305	12	4	20	46	.3	2	2	286	.87	4	5	ND	3	108	.2	2	2	2	.92	.010	11	111	.63	202	.01	3	.50	.01	.14	1
90R30 305-310	6	5	14	62	.1	2	4	358	1.66	2	5	ND	3	67	.2	2	2	6	.65	.025	15	61	.70	167	.01	4	.83	.01	.13	1
90R30 310-315	6	12	11	107	.4	2	4	394	2.10	2	5	ND	3	52	.6	2	2	10	.51	.033	20	62	.60	198	.04	4	.84	.03	.16	1
90R30 315-320	6	12	8	103	.4	1	4	467	2.08	3	5	ND	3	53	.6	2	2	10	.57	.036	19	67	.45	188	.03	3	.80	.03	.11	1
90R30 320-325	6	5	33	63	.3	2	4	368	1.66	3	5	ND	3	68	.2	2	2	5	.71	.037	13	70	.28	189	.02	4	.53	.03	.14	1
90R30 325-330	5	14	20	71	.2	1	4	422	1.76	2	5	ND	3	68	.5	2	2	7	.74	.037	16	47	.33	178	.03	2	.67	.02	.13	1
90R30 330-335	5	8	7	61	.4	2	4	330	1.73	5	5	ND	3	46	.3	2	2	8	.52	.036	16	43	.31	152	.01	3	.60	.03	.10	1
90R30 335-340	4	5	10	61	.2	2	5	338	1.91	3	5	ND	3	33	.2	2	2	10	.36	.037	18	49	.40	173	.01	2	.79	.02	.10	1
90R30 340-345	5	5	8	72	.1	1	4	344	1.97	2	5	ND	3	27	.2	2	2	8	.28	.040	20	50	.46	163	.01	4	.86	.02	.10	1
90R30 345-350	6	9	3	76	.3	1	4	382	2.01	2	5	ND	3	30	.2	2	2	8	.38	.038	19	61	.45	240	.01	2	.85	.02	.10	1
90R30 350-355	9	7	10	62	.3	2	3	289	1.71	2	5	ND	3	34	.2	2	2	10	.31	.029	16	81	.40	229	.01	3	.73	.03	.10	1
90R30 355-360	5	10	5	67	.4	2	4	375	1.98	6	5	ND	3	57	.2	2	2	8	.62	.036	18	49	.42	332	.01	2	.70	.02	.09	1
STANDARD C	19	62	38	133	7.4	72	32	1050	4.00	41	18	7	36	52	18.9	15	21	57	.49	.096	37	61	.87	179	.07	34	1.89	.06	.13	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R30 360-365	3	6	2	70	.1	1	3	480	2.05	7	5	ND	3	85	.3	2	3	8	.84	.037	16	31	.49	138	.01	3	.74	.01	.07	1
90R30 365-370	7	8	2	64	.2	1	4	465	2.05	17	5	ND	3	69	.2	2	2	7	.83	.037	17	70	.38	181	.01	5	.73	.02	.11	1
90R30 370-375	22	11	12	67	.1	3	4	401	2.08	7	5	ND	3	56	.2	2	2	8	.66	.036	18	254	.40	265	.02	4	.78	.02	.12	1
90R30 375-380	7	5	2	64	.1	1	3	461	2.02	6	5	ND	3	58	.3	2	2	8	.65	.041	20	80	.37	237	.01	4	.78	.02	.13	1
90R30 380-385	6	6	9	71	.1	1	3	478	2.08	7	5	ND	3	37	.2	2	2	7	.49	.038	18	67	.41	142	.01	6	.83	.02	.11	1
90R30 385-390	5	5	8	82	.1	1	3	410	1.97	3	5	ND	3	61	.2	2	2	9	.66	.038	19	56	.31	267	.02	6	.70	.02	.12	1
90R30 390-395	5	4	11	72	.1	1	3	425	1.85	3	5	ND	4	100	.2	2	2	7	1.16	.039	19	50	.26	426	.02	5	.65	.02	.17	1
90R30 395-400	5	4	10	80	.1	2	3	469	1.97	4	5	ND	3	107	.2	2	2	7	1.16	.037	20	61	.34	236	.04	6	.65	.02	.15	1
90R30 400-405	3	3	10	69	.1	2	4	441	1.95	3	5	ND	3	95	.2	2	2	6	1.12	.035	18	34	.44	209	.03	4	.72	.01	.11	1
90R30 405-410	8	8	12	81	.1	1	4	474	2.35	2	5	ND	4	95	.2	2	2	7	1.00	.046	21	78	.48	261	.01	6	.87	.02	.15	1
90R30 410-415	5	5	14	70	.1	1	4	468	1.90	5	5	ND	3	133	.2	2	3	6	1.06	.034	15	43	.70	213	.02	7	.77	.01	.13	1
90R30 415-420	7	4	13	72	.3	1	1	144	1.09	4	5	ND	6	47	.2	2	2	2	.38	.015	13	67	.96	241	.01	8	.82	.01	.13	1
90R30 420-425	6	3	16	76	.2	1	2	223	.90	2	5	ND	6	70	.6	3	2	1	.43	.006	13	76	.92	1105	.01	4	.81	.01	.14	1
90R30 425-430	8	3	17	65	.4	1	1	182	.66	3	5	ND	5	35	.5	2	2	1	.35	.005	11	81	.59	390	.01	6	.58	.01	.14	1
90R30 430-435	9	3	37	106	.5	1	1	87	.71	4	5	ND	4	13	1.5	2	2	1	.08	.005	9	113	.46	162	.01	6	.48	.01	.11	1
90R30 435-440	7	3	12	80	.3	1	1	144	.93	3	5	ND	5	53	.2	2	2	1	.33	.008	19	74	.96	568	.01	7	.83	.01	.11	1
90R30 440-445	11	4	15	63	.3	1	1	219	.89	3	5	ND	5	73	.9	2	2	1	.62	.007	17	76	.77	358	.01	7	.70	.01	.11	1
90R30 445-450	11	7	14	73	.6	2	4	210	1.44	6	5	ND	3	66	.2	2	2	2	.60	.019	8	80	.51	166	.01	2	.55	.01	.12	1
90R30 450-455	8	6	20	76	.5	2	3	328	1.60	3	5	ND	4	96	.2	2	2	3	.84	.023	12	69	.59	252	.01	7	.69	.01	.13	1
90R30 455-460	6	6	7	89	.2	1	3	390	1.47	4	5	ND	4	102	.7	2	2	3	.90	.027	15	58	.65	241	.01	4	.72	.01	.13	1
90R30 460-465	8	5	24	72	.3	2	3	336	1.40	2	5	ND	4	84	.6	2	2	3	.72	.023	16	84	.66	301	.01	5	.77	.01	.15	1
90R30 465-470	6	5	10	58	.5	1	1	292	1.24	3	5	ND	4	89	.3	2	2	2	.71	.020	14	60	.70	257	.01	4	.70	.01	.12	1
90R30 470-475	5	4	20	65	.3	1	1	264	1.08	4	5	ND	5	97	.5	3	2	2	.68	.013	15	51	.86	354	.01	4	.77	.01	.11	1
90R30 475-480	5	3	11	70	.3	1	1	161	.81	2	5	ND	5	74	.2	2	2	1	.39	.006	15	52	.89	246	.01	6	.74	.01	.11	1
90R30 480-485	5	2	25	55	.3	1	1	164	.76	3	5	ND	5	49	.3	2	3	1	.31	.007	18	45	.65	215	.01	6	.61	.01	.11	1
90R30 485-490	5	4	24	52	.3	1	1	170	.65	2	5	ND	6	62	1.8	2	2	1	.39	.007	17	49	.51	217	.01	2	.50	.01	.12	1
STANDARD C	19	61	38	131	7.3	73	31	1044	3.98	41	18	7	36	52	18.4	14	21	56	.45	.096	36	59	.86	179	.07	34	1.92	.06	.13	12

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R31 0-5	7	15	20	50	.3	10	4	339	1.42	13	5	ND	8	20	.3	2	2	7	.20	.029	17	71	.27	454	.02	2	.58	.02	.16	1
90R31 5-10	4	13	11	52	.2	7	4	299	1.61	4	5	ND	6	24	.3	2	2	9	.25	.034	15	31	.27	328	.05	2	.66	.02	.12	1
90R31 10-15	4	8	9	53	.1	5	3	222	1.74	7	5	ND	6	24	.2	2	2	7	.19	.030	13	31	.30	492	.02	2	.70	.02	.13	1
90R31 15-20	5	12	12	54	.2	5	3	216	1.93	12	5	ND	7	31	.2	2	2	9	.39	.033	17	48	.35	371	.01	2	.80	.03	.15	1
90R31 20-25	4	15	13	58	.3	6	4	212	2.12	12	5	ND	7	25	.2	2	2	7	.28	.031	15	34	.35	387	.01	2	.83	.02	.15	1
90R31 25-30	5	10	6	55	.1	4	4	228	1.88	14	5	ND	7	36	.2	2	2	5	.51	.024	20	47	.32	390	.02	2	.89	.04	.24	1
90R31 30-35	4	11	10	45	.2	4	3	196	1.35	8	5	ND	5	40	.2	2	2	3	.60	.021	11	42	.32	246	.02	2	.68	.03	.15	5
90R31 35-40	6	10	10	61	.1	5	2	231	1.19	9	5	ND	3	93	.2	2	2	4	1.42	.021	9	59	.32	213	.01	2	.67	.03	.13	5
90R31 40-45	6	9	10	65	.2	6	3	229	1.41	11	5	ND	3	57	.2	2	2	3	1.13	.023	4	63	.46	227	.04	3	.73	.02	.13	6
90R31 45-50	5	8	7	55	.2	5	3	220	1.10	6	5	ND	2	40	.2	2	2	3	1.08	.023	4	50	.32	197	.03	4	.60	.02	.12	7
90R31 50-55	4	7	7	64	.1	5	3	313	1.65	13	5	ND	4	34	.2	2	2	3	1.13	.024	6	48	.51	304	.03	2	.81	.02	.19	1
90R31 55-60	6	10	13	65	.2	8	4	309	1.62	22	5	ND	7	57	.7	2	2	4	1.52	.025	15	55	.37	328	.01	2	.78	.01	.21	1
90R31 60-65	5	7	36	71	.5	6	4	351	1.78	114	5	ND	6	133	.6	2	2	3	2.64	.030	10	50	.35	216	.01	2	.62	.01	.20	1
90R31 65-70	3	9	11	77	.1	5	4	313	2.22	12	5	ND	6	95	.2	2	2	6	2.09	.041	11	36	.53	261	.02	2	.95	.02	.22	1
90R31 70-75	4	7	4	76	.1	6	6	244	2.10	2	5	ND	3	49	.2	2	2	7	1.08	.041	5	40	.59	273	.06	2	.88	.04	.19	1
90R31 75-80	4	8	5	78	.1	5	5	288	2.10	15	5	ND	2	55	.2	2	2	6	1.31	.040	5	37	.71	295	.04	2	.96	.03	.18	1
90R31 80-85	4	6	4	82	.1	6	5	267	2.17	24	5	ND	2	53	.2	2	2	7	1.04	.039	5	33	.66	256	.02	2	.91	.02	.15	1
90R31 85-90	5	9	3	88	.1	7	5	287	2.01	16	5	ND	3	63	.2	3	2	7	1.28	.039	6	47	.68	356	.03	2	1.03	.03	.21	1
90R31 90-95	4	7	7	72	.1	5	4	291	1.76	3	5	ND	2	62	.2	2	2	6	1.70	.041	4	37	.71	255	.04	2	.90	.02	.16	1
90R31 95-100	3	8	7	83	.1	7	4	301	2.11	9	5	ND	4	113	.2	2	2	7	2.40	.040	8	29	.94	294	.02	2	1.32	.02	.17	1
90R31 100-105	4	8	6	110	.1	9	5	306	2.50	8	5	ND	6	58	.2	2	2	14	1.05	.043	12	37	1.31	317	.02	3	1.77	.04	.19	1
90R31 105-110	3	8	11	103	.1	7	4	288	2.23	5	5	ND	6	93	.2	2	2	10	1.89	.041	8	25	1.10	304	.03	2	1.52	.03	.18	1
90R31 110-115	4	7	6	82	.1	7	4	239	1.95	2	5	ND	5	67	.2	2	2	8	1.17	.036	7	33	1.04	385	.05	3	1.45	.03	.20	1
90R31 115-120	6	9	6	76	.1	6	4	336	1.92	2	5	ND	6	122	.2	2	2	11	1.89	.040	20	36	.59	249	.02	2	1.20	.04	.22	1
90R31 120-125	5	11	11	77	.1	7	4	270	1.82	2	5	ND	6	91	.2	2	2	9	1.40	.036	17	45	.60	320	.01	2	1.07	.04	.20	1
90R31 125-130	6	11	7	74	.1	6	4	304	1.99	5	5	ND	6	87	.2	2	2	12	1.32	.041	19	56	.57	345	.02	2	1.30	.07	.26	1
90R31 130-135	4	8	11	70	.1	4	4	397	2.13	9	5	ND	6	129	.2	2	2	10	2.27	.043	19	36	.45	294	.02	4	1.12	.04	.26	1
90R31 135-140	6	11	24	90	.1	5	3	393	1.90	4	5	ND	6	155	.4	2	2	10	2.76	.033	19	26	.34	153	.01	2	.74	.02	.23	2
90R31 140-145	4	11	11	71	.1	6	3	291	1.86	4	5	ND	7	121	.2	2	2	8	2.00	.031	22	35	.54	203	.01	2	.93	.02	.21	1
90R31 145-150	2	9	5	64	.1	6	4	334	2.01	2	5	ND	7	155	.2	2	2	11	2.52	.039	23	25	.66	231	.01	3	1.09	.02	.22	1
90R31 150-155	5	10	4	66	.1	4	5	472	2.19	22	5	ND	6	127	.2	2	2	19	2.06	.042	19	40	.42	134	.01	2	.83	.05	.16	1
90R31 155-160	3	16	8	78	.1	3	4	540	2.33	27	5	ND	5	214	.2	2	2	18	3.37	.042	18	23	.42	186	.01	2	.87	.03	.19	1
90R31 160-165	3	11	7	73	.1	4	5	476	2.04	45	5	ND	5	186	.3	2	2	16	3.07	.040	18	24	.42	306	.01	2	.80	.02	.16	1
90R31 165-170	3	16	7	74	.1	4	5	355	2.13	42	5	ND	5	111	.4	2	2	15	1.68	.043	18	32	.43	482	.01	2	.89	.03	.22	1
90R31 170-175	3	10	8	77	.1	4	5	460	2.13	61	5	ND	5	165	.2	2	2	16	2.85	.039	18	27	.44	327	.01	2	.87	.02	.21	1
90R31 175-180	3	12	5	68	.1	4	5	483	2.39	10	5	ND	6	146	.2	2	2	17	2.21	.042	20	28	.47	565	.01	2	.97	.03	.17	1
STANDARD C	20	62	39	134	7.1	72	31	1057	3.97	42	21	7	39	52	20.0	16	20	59	.47	.094	39	61	.87	181	.08	34	1.90	.06	.13	12

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R31 180-185	3	9	5	56	.1	4	5	608	1.90	6	5	ND	3	108	.4	2	2	12	2.22	.042	19	42	.39	333	.01	2	.94	.01	.21	1
90R31 185-190	3	9	17	38	.1	4	3	441	1.14	6	5	ND	6	129	.2	2	2	6	3.14	.022	24	30	.23	429	.01	2	.62	.01	.14	1
90R31 190-195	4	7	9	34	.1	3	3	289	1.00	2	5	ND	6	119	.2	2	2	6	2.05	.023	27	40	.24	1087	.01	2	.64	.01	.15	1
90R31 195-200	3	16	12	81	.3	5	5	384	1.75	2	5	ND	3	110	.8	3	2	17	2.08	.040	18	40	.52	247	.01	2	.86	.02	.18	1
90R31 200-205	6	8	9	71	.3	4	6	265	1.69	2	5	ND	2	98	.6	2	2	18	1.24	.049	10	78	.47	349	.04	4	.94	.03	.21	2
90R31 205-210	3	10	4	75	.3	4	6	304	1.75	2	5	ND	3	106	.8	3	2	22	1.95	.044	17	47	.45	144	.02	2	.83	.02	.12	1
90R31 210-215	3	8	7	66	.2	4	5	335	1.47	4	5	ND	3	109	.7	2	2	14	2.03	.038	14	37	.42	382	.02	2	.77	.02	.12	1
90R31 215-220	4	6	7	61	.1	5	5	215	1.29	2	5	ND	1	82	.2	2	2	11	1.14	.038	4	44	.54	366	.07	2	.83	.01	.16	1
90R31 220-225	5	6	11	67	.1	5	5	266	1.59	2	5	ND	2	78	.4	3	2	14	1.50	.039	9	74	.60	302	.06	2	1.09	.02	.22	1
90R31 225-230	4	8	6	56	.1	5	5	198	1.25	3	5	ND	1	74	.8	2	2	11	1.37	.037	6	46	.51	324	.06	2	.79	.01	.17	1
90R31 230-235	4	8	7	58	.1	4	4	176	1.32	5	5	ND	1	67	.2	2	2	11	1.08	.039	5	54	.59	307	.06	2	.78	.01	.17	1
90R31 235-240	3	8	6	62	.2	4	5	182	1.42	12	5	ND	1	70	.3	2	2	11	1.16	.042	5	48	.59	294	.04	3	.85	.01	.15	1
90R31 240-245	3	7	22	59	.1	3	6	290	1.33	13	5	ND	2	108	.4	2	2	9	2.13	.037	13	35	.42	397	.02	2	.71	.01	.11	1
90R31 245-250	4	9	12	73	.2	3	5	245	1.48	2	5	ND	1	87	.5	2	2	15	1.39	.046	6	48	.55	218	.09	3	.91	.02	.10	1
90R31 250-255	4	11	5	74	.3	5	6	289	1.59	3	5	ND	2	106	.8	2	2	14	1.97	.047	8	42	.50	267	.07	3	.88	.01	.12	2
90R31 255-260	4	9	3	59	.3	4	5	258	1.39	2	5	ND	1	68	.2	3	2	13	1.29	.040	7	39	.47	234	.08	2	.89	.01	.11	1
90R31 260-265	19	13	8	57	.3	5	5	340	1.50	3	5	ND	2	87	.2	2	2	18	1.83	.040	11	46	.47	243	.07	2	.94	.02	.11	2
90R31 265-270	17	11	11	51	.3	3	4	282	1.30	10	5	ND	3	68	.4	3	2	12	1.50	.037	16	32	.32	141	.03	2	.68	.01	.12	2
90R31 270-275	7	9	63	107	.4	3	3	302	1.05	8	5	ND	4	126	1.0	2	2	8	2.42	.021	18	38	.19	385	.01	2	.50	.01	.13	1
90R31 275-280	9	7	20	58	.1	3	4	241	.98	6	5	ND	2	82	.2	2	2	10	1.49	.033	10	44	.29	217	.05	2	.63	.01	.09	1
90R31 280-285	5	10	69	101	.3	3	4	278	1.13	4	5	ND	4	84	.9	2	2	10	1.61	.029	16	33	.28	209	.02	2	.64	.01	.11	1
90R31 285-290	4	8	17	87	.2	2	3	231	.93	5	5	ND	2	78	.2	2	2	8	1.41	.026	10	43	.25	185	.03	2	.51	.01	.10	1
90R31 290-295	6	6	10	53	.1	3	4	230	1.03	5	5	ND	2	77	.2	3	2	9	1.31	.032	9	58	.31	306	.05	2	.61	.01	.12	1
90R31 295-300	4	6	8	58	.1	3	4	261	1.26	6	5	ND	2	124	.5	2	2	9	2.03	.032	10	38	.35	214	.03	2	.61	.01	.11	1
STANDARD C	17	62	37	133	7.5	72	32	1053	3.97	43	15	7	35	51	18.5	15	19	59	.50	.096	37	61	.86	182	.07	38	1.89	.06	.14	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R32 0-5	5	11	14	51	.1	11	6	464	1.58	11	5	ND	6	14	.2	2	2	15	.21	.034	17	62	.33	297	.03	5	.78	.01	.15	1
90R32 5-10	3	10	14	75	.1	8	4	464	1.65	8	5	ND	6	11	.3	2	2	9	.19	.045	17	35	.30	277	.01	5	.79	.01	.17	1
90R32 10-15	2	4	9	58	.1	6	4	592	1.19	4	5	ND	6	10	.2	2	2	5	.16	.043	15	25	.24	319	.01	3	.60	.01	.15	1
90R32 15-20	4	6	11	66	.1	7	4	530	1.43	6	5	ND	6	9	.2	2	2	8	.17	.041	19	40	.26	282	.01	3	.72	.01	.18	1
90R32 20-25	4	7	11	70	.2	5	5	395	1.61	6	5	ND	5	10	.3	2	2	8	.19	.046	16	45	.27	279	.02	4	.78	.02	.21	1
90R32 25-30	3	6	9	66	.2	6	5	438	1.57	4	5	ND	5	11	.2	2	2	7	.19	.045	21	53	.30	337	.01	5	.85	.02	.22	1
90R32 30-35	7	9	8	60	.3	5	4	177	1.57	6	5	ND	7	21	.2	2	2	5	.13	.045	22	48	.31	250	.01	5	.70	.01	.20	1
90R32 35-40	7	5	4	48	.2	4	4	177	1.42	3	5	ND	4	15	.2	2	2	7	.19	.042	15	76	.27	208	.01	5	.64	.02	.19	2
90R32 40-45	4	4	2	52	.2	3	5	207	1.70	3	5	ND	5	12	.2	2	2	9	.20	.048	15	47	.35	241	.01	7	.73	.02	.23	1
90R32 45-50	4	4	5	49	.2	3	4	198	1.51	3	5	ND	5	12	.2	2	2	6	.19	.048	18	39	.27	219	.01	6	.69	.01	.20	1
90R32 50-55	7	31	53	46	.6	5	3	180	1.35	5	7	ND	6	10	.3	2	2	6	.10	.034	21	62	.11	217	.01	4	.57	.01	.15	2
90R32 55-60	5	25	25	51	.6	3	3	116	1.25	4	5	ND	5	13	.2	2	2	4	.15	.044	17	55	.18	405	.01	5	.60	.01	.22	1
90R32 60-65	5	6	17	55	.2	4	3	130	1.36	5	5	ND	5	13	.2	2	2	5	.16	.044	26	48	.20	343	.01	4	.67	.01	.22	1
90R32 65-70	4	6	8	64	.2	4	4	129	1.49	3	6	ND	5	12	.2	2	2	5	.17	.045	18	39	.23	273	.01	5	.68	.01	.20	1
90R32 70-75	3	4	5	56	.2	3	3	107	1.31	3	5	ND	6	12	.2	3	2	5	.17	.048	20	39	.19	215	.01	9	.66	.01	.21	1
90R32 75-80	4	7	4	61	.3	3	4	155	1.56	2	5	ND	5	12	.2	2	2	7	.19	.048	17	54	.29	237	.01	5	.74	.02	.22	1
90R32 80-85	5	6	8	53	.2	3	4	119	1.38	3	5	ND	5	12	.2	2	2	6	.18	.048	20	52	.24	310	.01	6	.68	.02	.22	1
90R32 85-90	3	6	5	54	.2	2	4	113	1.27	2	5	ND	5	11	.2	2	2	5	.18	.049	19	36	.23	205	.01	5	.64	.01	.21	1
90R32 90-95	4	8	7	58	.2	4	3	99	1.22	2	5	ND	6	11	.2	2	2	5	.18	.049	29	41	.22	203	.01	7	.68	.01	.21	1
90R32 95-100	3	5	3	50	.2	3	4	101	1.27	2	5	ND	5	9	.2	2	2	6	.16	.046	20	43	.23	210	.01	4	.58	.01	.19	1
STANDARD C	17	57	39	131	6.7	69	32	1056	3.95	40	21	7	36	52	18.3	19	18	56	.46	.099	36	58	.86	178	.08	38	1.88	.06	.13	13

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#13035 File # 90-6339 Page 1

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R33 0-5	5	10	19	45	.1	9	5	185	.93	7	5	ND	8	9	.2	2	2	4	.10	.017	22	38	.19	320	.01	3	.44	.01	.15	1
90R33 5-10	3	5	19	26	.1	5	1	59	.51	4	5	ND	11	7	.2	2	2	1	.04	.005	23	31	.05	566	.01	2	.28	.01	.18	1
90R33 10-15	2	4	22	22	.1	5	1	38	.44	3	5	ND	11	4	.2	2	2	1	.03	.005	23	21	.04	334	.01	2	.24	.01	.15	1
90R33 15-20	3	5	28	32	.2	5	1	54	.53	3	5	ND	12	6	.2	2	2	1	.05	.006	39	29	.05	413	.01	2	.32	.01	.16	1
90R33 20-25	2	4	18	30	.1	1	1	34	.39	3	5	ND	11	4	.2	2	2	1	.03	.004	33	18	.04	240	.01	2	.25	.01	.15	1
90R33 25-30	2	5	22	32	.1	3	1	37	.50	6	5	ND	12	4	.2	2	2	1	.04	.005	26	19	.05	231	.01	2	.26	.01	.15	1
90R33 30-35	3	7	20	47	.3	3	1	55	.77	7	5	ND	10	7	.2	2	2	1	.06	.006	18	20	.08	284	.01	2	.29	.01	.16	2
90R33 35-40	4	7	16	41	.3	3	1	54	.66	6	5	ND	11	9	.2	2	2	1	.05	.005	22	30	.08	395	.01	2	.34	.02	.21	2
90R33 40-45	3	5	17	35	.3	3	1	58	.59	6	5	ND	11	6	.2	2	2	1	.03	.004	30	22	.07	305	.01	2	.27	.01	.17	1
90R33 45-50	2	5	24	42	.2	3	1	52	.59	8	5	ND	10	6	.2	2	2	1	.04	.004	26	20	.07	271	.01	2	.26	.02	.17	1
90R33 50-55	3	8	14	59	.2	3	1	55	.73	6	5	ND	11	8	.2	2	2	1	.06	.004	30	24	.05	279	.01	2	.30	.02	.17	3
90R33 55-60	3	4	22	29	.2	2	1	26	.39	4	5	ND	11	7	.2	2	2	1	.04	.004	35	24	.02	373	.01	2	.24	.02	.15	1
90R33 60-65	3	6	22	39	.2	4	1	38	.54	5	5	ND	12	9	.2	2	2	1	.07	.006	32	27	.07	275	.01	2	.33	.01	.20	1
90R33 65-70	4	7	23	41	.5	5	2	74	.81	7	5	ND	12	10	.3	3	2	2	.07	.009	35	32	.08	328	.01	3	.37	.02	.19	2
90R33 70-75	2	5	26	30	.2	3	1	33	.48	2	5	ND	12	12	.2	2	2	1	.10	.006	43	22	.05	227	.01	2	.36	.02	.16	1
90R33 75-80	3	4	25	29	.1	4	1	25	.42	4	5	ND	11	7	.2	2	2	1	.04	.003	29	31	.04	253	.01	2	.25	.02	.17	2
90R33 80-85	2	3	13	33	.1	2	1	46	.51	7	5	ND	11	15	.2	2	2	1	.07	.007	34	18	.06	695	.01	2	.27	.01	.17	1
90R33 85-90	2	4	15	26	.3	1	1	22	.44	5	5	ND	11	6	.2	2	2	1	.04	.006	34	14	.03	261	.01	2	.22	.01	.16	1
90R33 90-95	2	3	15	25	.1	2	1	40	.43	4	5	ND	10	8	.2	2	2	1	.06	.006	32	22	.05	267	.01	2	.27	.01	.18	1
90R33 95-100	2	2	15	19	.1	2	1	24	.37	2	5	ND	10	6	.2	2	2	1	.04	.005	30	19	.03	316	.01	2	.21	.01	.15	1
STANDARD C	20	64	38	134	7.3	73	32	1064	3.95	39	18	8	37	52	17.0	14	21	58	.47	.096	39	60	.88	185	.09	36	1.89	.07	.14	13

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: DEC 17 1990 **DATE REPORT MAILED:** Dec 19/90. **SIGNED BY** C. Leong D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R34 0-5	4	11	15	70	.1	5	3	173	1.58	8	5	ND	6	9	.2	2	2	5	.20	.040	28	35	.26	319	.01	3	.75	.01	.18	1
90R34 5-10	4	30	6	49	1.1	6	3	101	1.22	7	5	ND	6	12	.2	2	2	4	.16	.041	19	41	.22	599	.01	3	.58	.01	.18	1
90R34 10-15	4	8	14	52	.1	5	3	99	1.23	3	5	ND	6	8	4.5	2	2	4	.15	.044	21	46	.16	348	.01	2	.57	.01	.19	1
90R34 15-20	6	10	9	39	.1	7	3	79	1.16	3	5	ND	6	6	.2	2	2	4	.14	.042	18	62	.14	257	.01	2	.50	.01	.20	1
90R34 20-25	4	8	13	71	.1	4	4	144	1.57	7	5	ND	6	10	.2	2	2	7	.18	.050	28	39	.29	323	.01	2	.72	.01	.19	1
90R34 25-30	3	6	22	79	.1	5	4	116	1.59	6	5	ND	7	10	.2	2	2	7	.19	.051	32	34	.25	234	.01	2	.74	.01	.19	1
90R34 30-35	7	8	14	80	.1	5	4	149	1.74	4	5	ND	6	11	.2	2	2	8	.18	.045	26	83	.31	294	.01	4	.82	.02	.25	1
90R34 35-40	4	7	23	96	.1	3	4	149	1.79	4	5	ND	5	15	.2	2	2	8	.21	.045	19	40	.25	299	.01	5	.70	.02	.21	1
90R34 40-45	5	7	24	89	.1	4	4	121	1.69	6	5	ND	5	13	.2	2	2	7	.18	.045	20	45	.26	448	.02	2	.70	.01	.33	1
90R34 45-50	4	6	18	47	.1	4	1	46	.76	3	5	ND	9	7	.2	2	2	3	.10	.024	33	44	.08	273	.01	2	.39	.01	.19	1
90R34 50-55	9	5	21	29	.1	3	1	31	.50	2	5	ND	11	8	.2	2	2	1	.05	.007	31	94	.04	388	.01	2	.34	.02	.19	2
90R34 55-60	5	7	36	62	.2	4	2	42	.49	5	5	ND	12	7	.2	2	2	2	.05	.008	36	54	.04	368	.01	2	.32	.01	.15	1
90R34 60-65	6	6	28	41	.1	3	1	29	.44	2	5	ND	10	6	.2	2	2	1	.04	.005	24	65	.02	159	.01	2	.24	.01	.16	2
90R34 65-70	3	4	19	37	.2	4	1	24	.37	3	5	ND	11	7	.2	2	2	1	.04	.005	28	34	.03	180	.01	2	.26	.02	.15	1
90R34 70-75	6	4	23	26	.1	3	1	27	.39	2	5	ND	9	5	.2	2	2	1	.02	.004	23	60	.03	155	.01	2	.22	.01	.15	3
90R34 75-80	7	5	51	39	.4	3	1	30	.61	5	5	ND	8	4	.2	2	2	1	.02	.004	21	63	.03	136	.01	2	.20	.01	.13	3
90R34 80-85	5	3	25	40	.2	3	1	32	.47	2	5	ND	10	10	.2	2	2	1	.04	.005	23	49	.08	435	.01	3	.33	.02	.16	2
90R34 85-90	6	4	30	44	.2	3	1	37	.57	2	5	ND	11	6	.2	2	2	1	.04	.004	23	62	.11	329	.01	2	.36	.02	.17	2
90R34 90-95	7	4	24	34	.1	3	1	27	.50	2	5	ND	10	10	.2	2	2	1	.07	.004	25	76	.09	365	.01	2	.36	.01	.18	2
90R34 95-100	6	4	17	22	.4	3	1	25	.38	2	5	ND	9	12	.2	2	2	1	.09	.004	29	66	.05	379	.01	2	.29	.02	.17	2
STANDARD C	18	59	42	132	7.4	72	31	1061	3.98	39	18	6	36	53	18.5	16	19	57	.46	.095	37	60	.87	180	.07	40	1.85	.07	.14	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R35 0-5	7	7	285	56	1.7	4	4	360	1.33	2	5	ND	3	84	.6	2	2	4	.93	.025	14	55	.34	188	.01	5	.56	.01	.17	1
90R35 5-10	4	5	83	51	.7	4	3	486	1.15	2	5	ND	3	56	.2	2	2	4	.62	.028	15	47	.37	165	.01	3	.55	.01	.18	1
90R35 10-15	6	10	127	49	3.2	7	3	294	1.37	5	5	7	4	30	.2	2	2	4	.25	.029	12	48	.36	134	.01	2	.53	.01	.19	1
90R35 15-20	6	10	40	41	.5	3	3	511	1.29	6	5	ND	3	55	.4	2	2	5	.54	.032	14	62	.39	157	.01	3	.59	.01	.22	1
90R35 20-25	6	10	11	47	.2	3	4	389	1.62	8	5	ND	4	28	.2	2	2	6	.29	.036	19	71	.44	183	.01	3	.73	.01	.21	1
90R35 25-30	4	7	6	42	.1	2	4	436	1.45	3	5	ND	3	71	.2	2	2	5	.62	.034	15	47	.41	215	.01	4	.61	.01	.19	2
90R35 30-35	6	9	9	37	.4	5	4	488	1.61	8	5	ND	3	100	.2	2	2	5	.87	.034	15	72	.42	246	.01	3	.65	.01	.23	1
90R35 35-40	7	8	5	36	.4	2	3	464	1.21	3	5	ND	3	99	.7	2	2	3	.93	.032	12	83	.40	196	.01	5	.55	.01	.21	1
90R35 40-45	4	5	14	50	.4	2	4	243	1.38	9	5	ND	4	24	.6	2	2	4	.22	.042	15	48	.36	222	.01	4	.60	.01	.18	1
90R35 45-50	3	4	11	65	.2	5	4	432	1.34	12	5	ND	4	27	.4	2	2	4	.28	.036	16	43	.36	579	.01	4	.61	.01	.18	1
90R35 50-55	4	4	3	49	.2	5	3	646	1.12	9	5	ND	4	51	.8	2	2	3	.52	.029	14	51	.33	334	.01	2	.54	.01	.18	1
90R35 55-60	3	5	5	54	.3	7	4	770	1.35	7	5	ND	3	40	.2	2	2	5	.60	.036	13	43	.38	165	.01	2	.60	.01	.18	1
90R35 60-65	4	4	7	25	.2	4	2	580	.73	2	5	ND	5	50	.2	2	2	2	.74	.025	18	44	.16	170	.01	2	.34	.01	.18	2
90R35 65-70	5	4	5	27	.1	2	3	440	1.00	3	5	ND	5	45	.4	2	2	3	.55	.029	18	53	.30	625	.01	2	.49	.01	.17	1
90R35 70-75	5	5	9	50	.2	4	4	451	1.68	5	5	ND	4	27	.3	2	2	8	.28	.037	22	68	.45	202	.01	2	.76	.01	.23	1
90R35 75-80	5	6	12	52	.1	4	4	395	1.44	4	5	ND	4	17	.2	2	2	6	.20	.035	19	60	.54	144	.01	2	.75	.01	.21	1
90R35 80-85	5	7	10	44	.1	3	3	259	1.21	9	5	ND	6	13	.5	2	2	4	.12	.030	20	58	.41	309	.01	2	.64	.01	.21	1
90R35 85-90	7	11	12	51	.2	5	5	416	1.90	8	5	ND	4	13	.3	2	2	9	.14	.038	19	66	.70	280	.01	2	.94	.01	.20	1
90R35 90-95	11	7	2	59	.3	3	5	392	1.76	6	5	ND	4	10	.5	2	2	7	.15	.036	19	52	.57	144	.01	2	.85	.01	.18	1
90R35 95-100	6	7	67	54	.4	5	2	110	.63	6	6	ND	10	11	1.4	2	2	3	.08	.012	28	55	.15	262	.01	2	.33	.02	.13	1
STANDARD C	21	65	39	136	7.5	72	32	1078	3.99	42	18	7	38	53	17.3	14	18	60	.49	.094	40	55	.89	181	.09	35	1.90	.07	.14	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R36 0-5	7	10	11	49	.1	11	4	205	1.26	6	5	ND	7	32	.5	2	2	12	.40	.031	14	76	.42	379	.02	3	.58	.03	.14	1
90R36 5-10	6	8	11	24	.1	9	3	128	.86	3	5	ND	8	18	.2	2	2	6	.25	.017	10	61	.24	198	.01	2	.36	.03	.12	2
90R36 10-15	6	5	9	26	.1	8	3	117	.82	2	5	ND	8	13	.2	2	2	6	.13	.018	10	67	.19	229	.01	3	.35	.03	.13	2
90R36 15-20	7	8	14	31	.2	7	4	139	1.00	5	5	ND	9	14	.2	2	2	7	.13	.020	12	76	.24	278	.01	2	.41	.03	.14	1
90R36 20-25	6	14	15	38	.1	8	4	177	1.25	9	5	ND	7	24	.2	2	2	12	.30	.024	12	78	.46	309	.01	3	.56	.02	.13	1
90R36 25-30	7	16	16	58	.2	10	8	314	2.42	2	5	ND	7	54	.5	2	2	33	1.02	.037	14	87	1.49	171	.01	2	1.47	.02	.12	1
90R36 30-35	5	18	15	80	.2	13	9	358	3.03	2	5	ND	6	59	.4	2	2	33	1.26	.057	11	73	2.24	121	.02	2	2.07	.02	.14	1
90R36 35-40	5	18	18	98	.3	17	9	314	2.78	4	5	ND	7	58	.3	2	2	26	1.17	.061	10	64	1.81	192	.02	2	1.73	.02	.15	1
90R36 40-45	6	24	10	87	.4	22	10	517	3.20	13	5	ND	5	72	.4	2	2	32	1.27	.061	7	72	1.97	149	.02	2	1.98	.02	.19	1
90R36 45-50	8	26	14	91	.4	22	11	543	3.29	13	5	ND	5	66	.5	2	2	34	1.13	.059	6	94	2.07	149	.03	2	2.02	.02	.19	1
90R36 50-55	8	28	13	82	.2	24	9	503	2.85	22	5	ND	5	72	.4	2	2	25	1.16	.058	5	95	1.52	124	.02	2	1.52	.02	.17	1
90R36 55-60	6	29	29	128	.4	19	11	647	3.49	8	5	ND	4	68	.9	2	2	33	1.07	.062	4	74	2.20	107	.04	3	2.09	.02	.16	1
90R36 60-65	5	27	15	95	.2	22	11	554	3.38	4	5	ND	4	61	.6	2	2	34	1.05	.061	5	60	1.95	98	.02	2	1.88	.01	.14	1
90R36 65-70	5	30	10	68	.3	21	10	396	2.57	7	5	ND	4	52	.4	2	2	26	1.00	.061	6	69	1.41	93	.02	3	1.39	.02	.12	1
90R36 70-75	6	28	11	72	.3	13	12	442	2.57	9	5	ND	5	79	.3	2	2	29	1.75	.061	8	78	1.67	118	.02	2	1.69	.02	.14	1
90R36 75-80	5	21	11	70	.4	17	8	374	2.38	4	5	ND	6	57	.2	2	2	27	1.31	.068	10	70	1.61	124	.02	2	1.57	.03	.15	1
90R36 80-85	4	28	13	62	.3	18	10	452	2.30	19	5	ND	6	105	.4	2	2	19	2.70	.064	7	50	1.23	106	.01	2	1.31	.01	.13	1
90R36 85-90	4	24	7	73	.4	19	11	456	2.74	722	5	ND	5	128	.2	2	2	32	2.59	.059	6	60	1.57	103	.03	2	1.55	.02	.14	1
90R36 90-95	4	38	8	74	.3	21	17	523	3.36	147	5	ND	4	106	.5	2	2	63	2.87	.055	9	70	2.09	71	.04	2	2.18	.03	.11	1
90R36 95-100	2	38	6	73	.2	9	25	809	4.56	27	5	ND	3	123	.5	2	2	91	3.57	.049	6	31	1.93	64	.06	2	2.60	.05	.11	1
90R36 100-105	8	20	12	95	.6	29	10	479	3.09	55	5	ND	6	94	1.1	2	2	18	2.43	.076	10	63	.92	131	.02	2	1.04	.02	.15	1
90R36 105-110	7	32	21	94	.6	36	12	522	3.11	167	5	ND	4	93	.7	2	2	36	2.46	.057	7	59	1.21	108	.03	2	1.38	.02	.12	1
90R36 110-115	2	38	7	86	.4	9	20	827	5.27	19	5	ND	3	108	.7	2	2	129	3.22	.052	6	25	2.15	38	.03	2	2.83	.04	.08	1
90R36 115-120	5	32	15	75	.3	21	13	582	3.01	29	5	ND	5	114	.5	2	2	38	2.35	.061	7	67	1.62	113	.03	2	1.77	.04	.14	1
90R36 120-125	5	31	23	85	.4	29	12	443	3.02	31	5	ND	5	53	1.0	2	2	31	1.07	.067	6	56	1.67	92	.03	2	1.68	.02	.12	1
90R36 125-130	6	32	22	93	.3	32	12	484	3.28	23	5	ND	4	63	.4	2	2	28	1.06	.066	7	73	1.70	102	.04	3	1.65	.02	.13	1
90R36 130-135	3	18	8	78	.1	19	11	400	2.58	2	5	ND	5	130	.5	2	2	16	2.69	.067	13	40	.83	119	.03	2	.96	.03	.10	1
90R36 135-140	4	21	33	113	.6	27	10	612	3.02	34	5	ND	4	88	.7	2	2	24	2.05	.092	9	51	1.35	108	.01	2	1.54	.02	.10	1
90R36 140-145	6	30	37	83	.6	26	12	524	2.82	71	5	ND	4	78	.7	2	2	16	1.78	.060	4	45	1.15	85	.01	2	.97	.02	.11	1
90R36 145-150	7	32	28	69	.6	26	15	566	3.50	66	5	ND	3	68	.4	2	2	16	1.88	.054	2	72	1.13	99	.01	2	1.02	.02	.14	1
90R36 150-155	7	40	29	76	.7	25	13	601	3.16	51	5	ND	4	53	.4	2	2	23	1.93	.056	3	71	1.56	89	.01	2	1.33	.01	.12	1
90R36 155-160	6	38	32	76	.6	25	13	642	3.12	142	5	ND	3	62	.2	2	2	16	1.97	.059	3	60	1.37	83	.01	2	1.18	.01	.11	1
90R36 160-165	6	40	51	104	.8	27	13	627	3.08	98	5	ND	4	70	.7	3	2	17	1.95	.063	3	53	1.36	79	.01	2	1.18	.01	.10	1
90R36 165-170	4	23	42	85	.8	20	11	572	2.81	46	5	ND	4	84	.6	2	2	14	2.11	.060	3	46	1.07	81	.01	2	.90	.01	.09	1
90R36 170-175	5	23	29	81	.5	23	12	607	2.89	27	5	ND	3	110	.4	2	2	21	2.55	.066	4	58	1.52	98	.01	2	1.46	.01	.11	1
90R36 175-180	4	24	17	70	.4	19	12	604	2.61	20	5	ND	3	113	.3	2	2	20	2.55	.065	5	57	1.54	81	.01	2	1.46	.01	.09	1
STANDARD C	19	59	36	133	7.1	72	31	1058	3.98	45	20	7	39	55	19.8	15	20	58	.48	.099	38	60	.85	180	.07	33	1.90	.06	.13	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R36 180-185	4	26	12	72	.4	16	11	509	2.82	15	5	ND	4	113	.5	2	2	18	2.47	.067	9	50	1.29	91	.01	2	1.38	.02	.09	1
90R36 185-190	4	32	28	92	1.0	19	11	697	3.03	29	5	ND	4	145	.6	2	2	17	3.44	.065	6	37	1.15	63	.01	2	1.19	.01	.08	1
90R36 190-195	6	40	19	61	.8	27	13	860	3.10	47	5	ND	4	140	.4	2	2	14	3.56	.057	3	55	1.20	61	.01	2	.85	.01	.10	1
90R36 195-200	4	45	40	136	.7	33	14	496	3.23	131	5	ND	4	60	1.2	2	2	14	1.68	.057	6	37	1.05	43	.01	2	.83	.01	.06	1
90R36 200-205	6	30	26	56	.6	16	8	370	2.17	18	5	ND	4	40	.2	4	2	11	1.12	.038	4	56	.93	38	.01	2	.77	.01	.06	1
90R36 205-210	4	29	33	83	.5	19	10	451	2.47	12	5	ND	4	53	.9	2	2	14	1.57	.050	4	44	1.15	37	.01	3	.91	.01	.07	1
90R36 210-215	5	32	20	68	.4	22	10	652	2.63	145	5	ND	3	120	.4	2	2	23	2.53	.054	3	53	1.72	45	.01	2	1.41	.01	.06	1
90R36 215-220	4	32	11	72	.4	27	10	508	2.68	23	5	ND	4	62	.2	2	2	27	1.30	.058	3	49	1.53	42	.01	2	1.46	.01	.07	1
90R36 220-225	4	39	11	85	.4	27	10	466	2.79	47	5	ND	3	51	.4	2	2	28	1.12	.061	5	47	1.67	49	.01	2	1.60	.01	.08	1
90R36 225-230	4	25	10	70	.5	20	8	413	2.36	32	5	ND	5	62	.2	2	2	22	1.69	.058	8	44	1.27	59	.01	2	1.33	.01	.09	1
90R36 230-235	3	43	10	68	.3	10	16	668	4.11	19	5	ND	3	87	.4	2	2	77	2.79	.050	6	33	1.70	48	.04	2	2.14	.03	.09	1
90R36 235-240	3	50	7	62	.3	9	14	640	3.51	3	5	ND	1	64	.3	2	2	40	2.05	.055	2	33	1.83	61	.10	2	2.16	.03	.09	1
90R36 240-245	3	38	5	63	.3	8	15	644	3.77	2	5	ND	2	51	.2	2	2	48	2.11	.054	2	30	1.95	47	.08	2	2.21	.03	.06	1
90R36 245-250	3	35	6	61	.3	10	12	509	3.00	5	5	ND	2	50	.2	2	2	34	1.90	.057	2	30	1.60	54	.09	2	1.79	.02	.06	1
90R36 250-255	5	32	6	57	.3	16	11	628	2.39	8	5	ND	2	65	.2	2	2	26	2.34	.052	4	60	1.02	87	.06	3	1.21	.03	.08	1
90R36 255-260	3	24	12	57	.2	19	12	390	2.45	13	5	ND	3	76	.2	2	2	36	2.29	.048	6	44	1.21	68	.05	2	1.28	.02	.07	1
90R36 260-265	4	22	10	59	.2	15	8	557	2.20	2	5	ND	4	67	.2	2	2	26	2.21	.052	9	53	1.15	86	.03	2	1.28	.02	.09	1
90R36 265-270	3	28	7	62	.3	19	11	513	2.60	11	5	ND	3	79	.2	2	2	37	2.26	.049	7	45	1.20	73	.06	2	1.33	.02	.07	1
90R36 270-275	4	25	9	63	.3	21	12	358	2.63	9	5	ND	5	104	.3	2	2	40	2.70	.053	12	54	1.33	92	.03	2	1.42	.02	.09	1
90R36 275-280	3	18	8	70	.4	13	7	292	2.31	4	5	ND	7	65	.3	2	2	21	1.59	.069	17	39	1.28	86	.01	3	1.30	.02	.10	1
90R36 280-285	4	15	11	67	.3	17	8	341	2.37	86	5	ND	5	61	.3	2	2	22	1.39	.057	13	45	1.36	71	.01	3	1.34	.01	.08	1
90R36 285-290	3	17	16	76	.4	15	12	387	2.71	54	5	ND	5	77	.2	2	2	24	1.67	.056	13	44	1.53	70	.01	2	1.50	.01	.08	1
90R36 290-295	4	25	8	67	.2	22	12	485	3.03	34	5	ND	4	154	.5	2	2	46	3.28	.046	10	58	1.52	74	.02	2	1.65	.02	.08	1
90R36 295-300	4	27	17	72	.4	20	8	504	2.00	28	5	ND	8	107	.4	2	2	20	2.24	.076	21	42	1.05	101	.01	2	1.03	.01	.11	1
90R36 300-305	5	20	20	86	.5	18	6	615	1.76	9	5	ND	9	116	.3	2	2	14	2.14	.076	20	53	.87	134	.01	2	.87	.01	.14	1
90R36 305-310	5	25	25	82	.5	18	7	512	2.02	24	5	ND	7	114	.4	2	2	15	1.96	.067	13	52	1.03	134	.01	3	1.01	.01	.14	1
90R36 310-315	5	19	14	67	.6	18	8	443	1.93	9	5	ND	7	153	.3	2	2	15	2.47	.068	11	58	.85	151	.01	2	.77	.01	.18	1
90R36 315-320	5	17	12	59	.6	15	7	492	1.69	6	5	ND	7	211	.3	2	2	14	3.03	.055	8	53	.88	116	.01	4	.75	.01	.15	1
90R36 320-325	3	23	17	79	.4	18	11	407	2.74	13	5	ND	6	110	.2	2	2	28	1.59	.061	11	48	1.74	84	.01	2	1.63	.01	.09	1
90R36 325-330	4	28	9	69	.3	16	10	565	2.76	6	5	ND	5	88	.5	2	2	23	2.15	.056	11	39	1.19	68	.02	2	1.41	.01	.08	1
90R36 330-335	4	31	9	78	.3	16	11	585	3.19	2	5	ND	5	92	.2	2	2	27	2.13	.060	10	39	1.47	91	.01	2	1.75	.02	.10	1
90R36 335-340	3	25	9	73	.3	13	12	698	3.61	2	5	ND	4	96	.2	2	2	44	2.59	.054	9	31	1.76	60	.02	2	2.05	.01	.08	1
90R36 340-345	2	34	4	71	.4	8	18	749	4.60	3	5	ND	3	120	.3	2	2	86	3.02	.048	6	26	2.22	99	.04	2	2.71	.03	.08	1
90R36 345-350	4	36	7	72	.3	8	15	721	3.99	4	5	ND	3	104	.5	2	2	57	2.84	.045	7	38	1.95	79	.02	2	2.35	.01	.08	1
90R36 350-355	6	33	8	70	.4	17	11	486	2.83	7	5	ND	5	60	.2	2	2	28	1.64	.060	12	51	1.37	91	.01	2	1.54	.02	.09	1
90R36 355-360	3	32	8	65	.4	21	14	396	2.70	7	5	ND	3	88	.2	2	2	35	2.08	.049	5	55	1.44	75	.05	2	1.51	.01	.08	1
STANDARD C	19	60	39	133	7.2	72	31	1057	3.97	39	22	7	39	55	18.8	15	20	58	.48	.097	39	60	.84	180	.07	34	1.89	.06	.13	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R36 360-365	3	31	4	65	.3	32	17	368	2.77	7	5	ND	1	90	.2	2	2	38	2.27	.060	6	72	1.49	94	.02	3	1.60	.01	.07	1
90R36 365-370	2	32	6	69	.3	21	13	490	2.95	9	5	ND	1	86	1.0	2	2	40	2.22	.060	9	56	1.39	103	.01	4	1.56	.01	.07	1
90R36 370-375	4	33	11	67	.2	17	11	463	2.65	11	5	ND	1	71	.7	2	2	30	2.30	.060	12	52	1.42	79	.01	2	1.47	.01	.06	1
90R36 375-380	1	38	9	94	.4	10	18	682	5.11	4	5	ND	1	72	.2	2	2	74	2.15	.061	8	39	2.23	88	.03	3	2.61	.01	.08	1
90R36 380-385	3	27	10	74	.3	17	12	573	3.39	8	5	ND	1	63	.2	2	2	43	2.42	.061	14	62	1.52	88	.01	2	1.80	.01	.07	1
90R36 385-390	1	52	6	92	.5	18	21	884	4.91	12	5	ND	1	114	.2	2	2	71	4.46	.065	11	57	2.25	93	.01	2	2.55	.01	.06	1
90R36 390-395	1	58	19	123	.6	16	20	913	5.64	15	5	ND	1	89	.2	2	2	92	3.52	.058	9	43	2.86	76	.01	7	3.16	.01	.05	1
90R36 395-400	8	57	44	177	1.0	86	14	651	3.24	56	5	ND	1	87	1.2	7	2	37	3.32	.058	11	105	1.86	72	.01	4	1.59	.01	.05	1

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R37 0-5	10	13	10	30	.3	9	4	123	1.14	7	5	ND	9	31	.2	2	2	5	.35	.012	12	94	.22	388	.01	5	.38	.02	.12	1
90R37 5-10	6	11	12	29	.2	9	4	108	.91	6	5	ND	10	24	.2	2	2	4	.25	.012	16	64	.20	389	.01	4	.35	.01	.11	1
90R37 10-15	5	9	22	42	.1	8	3	137	.80	3	5	ND	10	17	.2	2	2	6	.15	.009	21	49	.21	385	.01	2	.41	.01	.13	1
90R37 15-20	5	7	27	41	.3	6	1	110	.60	5	5	ND	12	9	.2	2	2	3	.09	.006	30	52	.22	261	.01	4	.38	.01	.14	2
90R37 20-25	4	10	26	49	.6	9	4	263	1.10	5	5	ND	10	81	.6	3	2	8	.95	.013	31	47	.51	209	.01	7	.71	.02	.16	1
90R37 25-30	4	43	50	100	.8	23	8	458	2.26	18	5	ND	6	136	.2	2	2	19	1.81	.023	21	61	1.00	267	.01	3	1.19	.01	.15	1
90R37 30-35	4	28	32	65	.5	13	5	298	1.83	8	5	ND	6	67	.2	2	2	17	.93	.034	22	58	.47	378	.01	2	.77	.01	.19	1
90R37 35-40	4	24	18	73	.5	18	6	386	1.73	44	5	ND	6	123	.2	2	2	13	1.72	.032	25	45	.73	288	.01	2	.90	.01	.14	1
90R37 40-45	4	18	12	57	.5	15	6	353	1.72	19	5	ND	7	156	.2	3	2	10	2.11	.029	20	49	.61	155	.01	4	.79	.01	.18	1
90R37 45-50	5	16	17	65	.2	20	7	332	1.92	11	5	ND	7	200	.4	2	2	6	2.83	.018	27	76	1.02	103	.01	2	.90	.01	.15	1
90R37 50-55	5	10	20	62	.2	14	2	224	1.25	5	5	ND	12	119	.2	2	2	2	1.74	.012	38	66	.61	145	.01	3	.64	.01	.18	1
90R37 55-60	5	11	30	73	.3	5	2	158	1.03	8	5	ND	16	70	.2	2	2	2	1.06	.008	43	58	.58	137	.01	4	.61	.01	.14	1
90R37 60-65	3	10	23	43	.5	2	4	257	1.14	17	5	ND	14	113	.2	2	2	13	2.02	.021	35	54	.48	98	.01	4	.56	.01	.17	1
90R37 65-70	3	7	18	27	.3	2	2	120	.57	8	5	ND	16	66	.2	2	2	2	.90	.008	42	35	.16	83	.01	3	.28	.01	.17	1
90R37 70-75	5	17	13	69	.4	16	6	431	2.02	13	5	ND	7	88	.2	2	2	19	1.59	.041	24	77	.89	87	.01	2	1.02	.01	.16	1
90R37 75-80	7	40	16	87	.8	33	10	361	2.13	20	5	ND	6	77	.2	2	2	18	1.84	.058	22	81	1.16	105	.01	3	1.11	.01	.12	1
90R37 80-85	8	42	17	106	.6	39	12	417	2.60	18	5	ND	5	92	.6	2	2	21	2.30	.063	21	56	1.31	126	.01	2	1.16	.01	.09	1
90R37 85-90	5	32	8	84	.6	26	13	604	3.84	44	5	ND	2	100	.2	3	2	43	2.87	.052	16	59	1.80	76	.01	2	1.90	.01	.10	1
90R37 90-95	9	66	15	162	.7	48	17	710	3.73	55	5	ND	1	102	.7	7	2	47	2.69	.055	9	60	1.94	70	.01	2	1.83	.01	.09	1
90R37 95-100	4	38	19	108	.5	17	13	705	4.25	16	5	ND	2	108	.5	4	2	54	2.75	.055	17	54	1.91	72	.01	2	2.01	.01	.10	1
90R37 100-105	6	42	16	94	.5	36	17	422	3.35	21	5	ND	4	78	.2	2	2	39	1.44	.061	20	79	1.56	110	.01	2	1.51	.01	.13	1
90R37 105-110	5	42	10	96	.6	38	14	404	3.48	18	5	ND	3	94	.2	2	2	44	1.76	.060	19	67	1.77	97	.01	2	1.65	.01	.11	1
90R37 110-115	6	46	14	93	.5	38	14	360	3.15	24	5	ND	4	104	.4	3	2	41	1.92	.062	14	73	1.44	99	.01	2	1.41	.01	.12	1
90R37 115-120	5	27	15	92	.5	27	13	601	3.21	300	5	ND	1	160	.7	2	2	33	2.38	.055	6	58	1.76	85	.01	2	1.61	.01	.11	1
90R37 120-125	7	37	23	86	1.3	27	14	500	3.31	74	5	ND	2	100	.6	3	2	24	1.67	.055	4	67	1.69	86	.01	2	1.37	.01	.11	1
90R37 125-130	6	36	43	92	.8	24	14	499	3.42	39	5	ND	2	74	.2	3	2	32	1.24	.058	7	71	2.12	77	.01	2	1.70	.01	.11	1
90R37 130-135	7	40	31	92	.8	29	14	522	2.97	35	5	ND	3	70	.5	3	2	19	1.41	.064	4	59	1.54	73	.01	4	1.05	.01	.09	1
90R37 135-140	8	37	25	114	.7	31	15	507	3.46	35	5	ND	2	49	.5	6	2	24	.89	.082	3	94	1.76	103	.01	2	1.39	.01	.13	1
90R37 140-145	9	42	11	100	.7	31	16	564	3.26	27	5	ND	3	70	.6	3	2	23	1.40	.063	5	87	1.82	93	.01	2	1.19	.01	.11	1
90R37 145-150	5	48	14	52	1.4	28	19	446	3.23	16	5	ND	2	76	.2	4	2	15	1.39	.052	3	59	1.60	64	.01	2	1.03	.01	.09	1
90R37 150-155	6	45	13	68	1.7	27	21	761	3.70	16	5	2	1	106	.3	5	2	18	1.94	.051	4	73	1.60	70	.01	3	1.10	.01	.12	1
90R37 155-160	4	24	8	105	.8	19	15	810	3.94	10	5	ND	2	112	.2	2	2	27	1.79	.065	10	68	1.73	101	.02	2	1.49	.01	.14	1
90R37 160-165	6	29	15	96	.7	22	15	796	3.80	19	5	ND	2	99	.7	2	2	26	1.73	.063	10	83	1.69	90	.01	2	1.44	.01	.13	1
90R37 165-170	3	31	2	54	1.0	22	19	795	3.39	9	5	ND	1	131	.2	3	2	12	3.78	.053	9	46	.98	58	.01	2	.77	.01	.10	1
90R37 170-175	5	32	8	58	.8	21	18	762	3.38	10	5	ND	1	106	.3	4	2	8	3.54	.058	12	61	1.00	66	.01	2	.82	.01	.12	1
90R37 175-180	7	23	5	76	.6	13	11	576	2.91	14	5	ND	3	72	.2	2	2	10	2.04	.059	16	80	1.18	97	.02	2	1.09	.01	.14	1
STANDARD C	21	62	41	135	7.5	76	32	1071	3.99	40	20	7	37	52	17.3	14	21	57	.48	.098	41	61	.89	182	.09	34	1.90	.07	.14	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R37 180-185	6	29	15	65	.6	18	13	507	2.57	19	5	ND	4	94	.2	2	2	11	2.26	.048	11	41	1.04	69	.01	2	.75	.01	.05	1
90R37 185-190	7	33	11	68	.4	25	14	509	2.99	18	5	ND	4	81	.4	3	2	18	1.81	.055	9	67	1.17	74	.01	4	.88	.01	.05	1
90R37 190-195	8	37	13	93	.4	32	13	481	2.83	91	5	ND	5	98	.2	4	2	18	1.81	.065	7	58	1.23	76	.01	5	.84	.01	.06	1
90R37 195-200	8	37	34	88	.6	27	12	500	2.61	46	5	ND	4	70	.3	2	2	15	1.62	.048	8	60	1.20	65	.01	3	.80	.01	.04	1
90R37 200-205	3	27	13	83	.4	21	11	495	2.69	10	5	ND	5	115	.2	2	2	28	2.77	.051	9	31	1.17	76	.02	2	1.05	.01	.05	1
90R37 205-210	3	25	32	83	.5	20	11	622	2.73	7	5	ND	4	108	.2	5	2	28	2.22	.052	11	28	1.54	84	.01	4	1.28	.01	.05	1
90R37 210-215	3	26	13	80	.3	23	12	519	2.89	6	5	ND	5	88	.2	2	2	27	1.67	.057	13	28	1.62	88	.01	3	1.41	.01	.06	1
90R37 215-220	2	23	10	74	.2	14	13	632	3.27	44	5	ND	4	126	.5	2	2	46	2.78	.047	11	23	1.64	92	.01	4	1.73	.01	.05	1
90R37 220-225	8	32	14	102	.4	56	10	456	2.43	21	5	ND	5	101	.6	2	2	30	2.18	.053	14	47	1.20	124	.01	4	1.09	.01	.06	1
90R37 225-230	5	24	12	69	.3	24	6	396	1.97	15	5	ND	6	69	.3	2	2	23	1.48	.044	16	47	.71	125	.01	3	.73	.01	.07	1
90R37 230-235	9	36	22	102	.7	63	9	453	2.14	28	5	ND	5	120	1.0	2	2	19	2.84	.048	12	34	1.03	84	.01	3	.79	.01	.04	1
90R37 235-240	7	31	16	109	.4	60	10	350	2.28	15	5	ND	6	76	.7	2	2	21	1.58	.038	14	49	1.14	99	.01	3	.90	.01	.05	1
90R37 240-245	8	26	21	98	.4	47	7	360	1.90	15	5	ND	6	91	.5	2	2	21	1.72	.038	11	41	1.14	145	.01	2	.88	.01	.06	1
90R37 245-250	6	19	18	73	.5	39	7	338	1.84	244	5	ND	6	187	.5	2	2	13	2.43	.026	10	32	.89	94	.01	4	.57	.01	.06	1
90R37 250-255	6	18	22	77	.3	29	5	224	1.34	545	5	ND	9	85	.7	2	2	8	1.40	.023	15	29	.53	148	.01	2	.46	.01	.08	1
90R37 255-260	11	28	23	128	.5	65	9	290	1.81	170	5	ND	6	135	.9	4	2	16	2.20	.049	13	39	1.09	125	.01	6	.77	.01	.10	1
90R37 260-265	5	28	16	110	.5	38	18	287	3.05	72	5	ND	6	148	.5	2	2	8	2.33	.036	8	37	.82	99	.01	4	.73	.01	.15	1
90R37 265-270	3	12	27	44	.7	12	3	170	.91	29	5	ND	7	80	.6	2	2	4	1.24	.042	10	15	.24	125	.01	2	.22	.01	.06	1
90R37 270-275	7	26	33	118	.6	21	5	293	1.44	467	5	ND	7	163	2.0	3	2	8	2.80	.057	11	24	.39	110	.01	4	.34	.01	.08	1
90R37 275-280	9	24	19	83	.5	30	8	263	1.88	426	5	ND	6	133	1.2	3	2	8	2.32	.034	9	28	.38	76	.01	4	.36	.01	.07	1
90R37 280-285	6	19	21	71	.4	24	7	188	1.38	51	5	ND	10	83	.7	2	2	10	1.34	.024	14	27	.40	126	.01	5	.41	.01	.10	1
90R37 285-290	6	23	23	87	.4	29	7	198	1.69	22	5	ND	9	119	.7	3	2	10	1.93	.043	9	33	.55	106	.02	4	.49	.01	.13	1
90R37 290-295	10	17	33	44	.4	18	4	120	1.12	131	5	ND	12	79	.2	2	2	7	.89	.024	21	42	.25	146	.01	3	.34	.01	.11	2
90R37 295-300	4	18	23	42	.6	17	5	207	1.15	31	5	ND	9	105	.2	2	2	7	1.59	.039	19	32	.31	134	.01	4	.35	.01	.08	1
STANDARD C	20	63	35	135	7.5	74	32	1077	3.92	44	19	7	37	52	17.3	15	22	60	.47	.094	39	60	.88	185	.09	38	1.87	.05	.14	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R38 0-5	8	41	25	66	.4	6	3	239	2.51	23	5	ND	5	23	.2	2	2	24	.13	.067	5	53	1.74	106	.01	4	1.36	.01	.13	1
90R38 5-10	13	31	127	54	1.2	8	2	142	1.91	47	5	ND	10	27	.2	2	2	19	.11	.055	9	58	1.37	162	.01	4	1.17	.02	.16	1
90R38 10-15	9	18	72	47	1.1	10	1	113	2.85	48	5	ND	9	27	.2	2	2	20	.09	.048	6	57	1.18	238	.01	6	1.02	.08	.27	1
90R38 15-20	4	22	16	58	1.1	11	2	235	3.98	25	5	ND	4	12	.2	2	2	32	.15	.043	4	56	1.43	274	.01	7	1.23	.06	.42	1
90R38 20-25	2	17	7	99	.3	9	3	445	3.72	6	5	ND	4	9	.2	2	2	17	.15	.085	8	34	1.66	166	.02	7	1.83	.03	.18	1
90R38 25-30	6	26	24	70	.7	13	2	173	4.10	32	5	ND	3	8	.2	2	2	25	.16	.042	6	55	1.49	274	.01	6	1.42	.05	.44	1
90R38 30-35	3	29	3	93	.4	13	3	357	4.14	13	5	ND	4	14	.2	2	2	26	.14	.080	10	44	1.41	230	.01	4	1.70	.04	.28	1
90R38 35-40	5	29	13	71	.6	10	2	237	4.34	14	5	ND	5	9	.2	3	2	18	.19	.051	7	51	1.23	298	.01	8	1.41	.04	.50	1
90R38 40-45	5	33	17	82	.4	8	2	188	3.29	41	5	ND	3	13	.2	4	2	27	.10	.069	6	56	1.75	212	.01	3	1.60	.03	.28	1
90R38 45-50	5	34	3	87	.3	9	2	192	3.67	38	5	ND	3	14	.2	6	2	29	.06	.071	7	54	1.67	222	.01	6	1.61	.03	.28	1
90R38 50-55	13	40	12	90	.5	23	3	178	3.65	68	5	ND	5	17	.2	3	2	39	.06	.077	11	81	1.77	179	.01	6	1.82	.02	.16	1
90R38 55-60	11	32	12	85	.4	21	2	155	3.11	42	5	ND	6	33	.2	2	2	26	.17	.079	20	70	1.31	176	.01	7	1.41	.02	.14	1
90R38 60-65	10	24	12	60	.5	9	1	95	2.16	33	5	ND	7	26	.2	2	2	13	.15	.050	18	44	.86	137	.01	3	.93	.02	.12	1
90R38 65-70	8	25	16	67	.3	11	2	140	2.39	21	5	ND	9	33	.2	2	2	20	.14	.054	19	59	.87	170	.01	7	1.05	.02	.14	1
90R38 70-75	7	20	20	71	.4	26	5	202	1.94	18	5	ND	10	23	.2	2	2	15	.14	.038	15	66	.88	213	.01	5	1.07	.03	.15	1
90R38 75-80	12	25	16	121	.4	66	9	227	2.55	35	5	ND	10	28	1.0	2	2	9	.42	.043	33	67	1.12	178	.01	3	1.25	.01	.16	1
90R38 80-85	15	43	23	159	.7	126	18	422	2.45	74	5	ND	9	68	1.1	3	2	12	1.55	.055	39	80	1.48	165	.01	2	1.36	.01	.14	1
90R38 85-90	12	36	53	176	.8	88	14	339	2.94	131	5	ND	13	51	.5	4	2	11	.61	.051	34	75	1.60	180	.01	5	1.76	.01	.18	1
90R38 90-95	5	13	56	55	.5	23	5	108	.98	78	5	ND	17	31	.5	2	2	1	.35	.014	37	41	.31	170	.01	2	.52	.03	.16	2
90R38 95-100	10	34	92	100	1.0	51	9	130	1.71	155	5	ND	14	25	1.5	2	2	6	.17	.031	35	62	.57	159	.01	7	.82	.02	.17	2
90R38 100-105	13	45	21	182	.5	85	17	355	3.38	225	5	ND	8	110	1.3	2	2	15	1.49	.073	40	81	1.38	171	.01	4	1.49	.02	.16	1
90R38 105-110	9	24	40	111	.7	49	9	215	1.86	126	5	ND	19	29	1.3	4	2	5	.18	.032	56	57	.80	240	.01	4	.99	.03	.20	1
90R38 110-115	7	18	26	98	.6	54	10	208	1.44	99	5	ND	14	18	.5	8	2	3	.12	.028	38	49	.74	172	.01	3	.85	.02	.18	1
90R38 115-120	3	6	41	84	.5	10	2	122	1.15	72	5	ND	19	20	.4	4	2	1	.29	.008	35	42	.63	223	.01	5	.75	.04	.26	1
90R38 120-125	3	6	30	69	.2	9	2	67	.77	59	5	ND	21	32	.6	2	2	1	.47	.009	35	30	.55	183	.01	3	.59	.03	.28	1
90R38 125-130	12	9	20	120	.3	28	4	198	1.73	54	5	ND	22	25	.2	3	2	5	.23	.022	34	38	1.24	280	.01	4	1.14	.04	.32	1
90R38 130-135	9	27	20	153	.3	54	11	254	2.59	143	5	ND	10	51	1.3	4	2	12	.68	.035	14	55	1.13	205	.02	2	1.23	.02	.30	1
90R38 135-140	8	38	8	118	.2	48	11	376	2.42	268	5	ND	6	68	.2	2	2	17	1.34	.055	9	45	.97	151	.02	4	1.05	.01	.25	1
90R38 140-145	4	27	18	95	.3	36	10	263	1.99	66	5	ND	7	32	.3	2	2	15	.57	.041	12	53	.97	190	.02	6	1.09	.02	.24	2
90R38 145-150	3	19	13	82	.2	27	9	238	1.73	33	5	ND	8	37	.2	2	2	10	.75	.037	11	45	.93	183	.02	6	.96	.02	.24	2
90R38 150-155	3	32	4	81	.3	37	12	255	2.20	16	5	ND	3	52	.5	2	2	19	.92	.076	10	51	.50	210	.04	2	.75	.03	.30	2
90R38 155-160	3	28	8	103	.3	51	16	342	2.77	22	5	ND	4	48	.7	2	2	26	.63	.106	15	61	.94	207	.03	6	1.06	.02	.32	1
90R38 160-165	9	41	16	133	.5	67	16	490	3.32	66	5	ND	5	72	.9	2	2	28	1.40	.087	11	59	1.45	165	.03	6	1.34	.01	.25	1
90R38 165-170	4	34	3	94	.2	33	14	521	3.28	14	5	ND	3	61	.3	3	2	43	1.00	.065	12	52	1.91	79	.02	7	1.67	.01	.12	1
90R38 170-175	5	36	18	116	.3	34	14	551	3.82	12	5	ND	3	39	.9	2	2	37	.74	.064	13	59	2.24	114	.01	3	2.05	.01	.17	1
90R38 175-180	3	32	13	101	.2	28	14	559	3.93	24	5	ND	2	51	.2	3	2	45	.89	.069	7	47	2.38	80	.02	5	2.12	.01	.13	1
STANDARD C	20	64	43	134	7.3	73	33	1076	3.96	43	17	7	38	52	18.6	15	18	58	.48	.094	39	60	.88	187	.09	41	1.88	.07	.14	12

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R38 180-185	3	36	11	86	.3	31	12	373	2.90	22	5	ND	3	64	.2	2	2	25	1.04	.051	6	36	1.73	79	.01	2	1.48	.01	.11	1
90R38 185-190	3	28	21	86	.7	27	12	425	2.33	47	5	ND	7	86	1.5	2	2	17	1.42	.070	18	43	1.34	112	.01	5	1.28	.01	.15	1
90R38 190-195	2	29	6	73	.3	22	11	409	2.78	17	5	ND	4	108	.2	2	2	29	2.23	.051	14	45	1.63	110	.02	2	1.52	.01	.13	1
90R38 195-200	2	25	10	71	.3	19	12	391	2.50	13	5	ND	4	101	.3	2	2	28	2.09	.056	16	43	1.43	111	.06	3	1.35	.01	.14	1
90R38 200-205	3	31	13	82	.4	29	13	376	2.89	124	5	ND	4	67	.2	3	2	25	1.31	.056	18	38	1.78	102	.04	3	1.56	.01	.13	1
90R38 205-210	2	32	9	76	.3	21	12	446	2.95	14	5	ND	2	60	.5	2	2	38	1.57	.059	11	38	1.58	100	.07	2	1.52	.01	.12	1
90R38 210-215	1	45	10	80	.5	9	19	641	4.29	11	5	ND	1	65	.2	4	2	62	2.15	.045	3	23	2.06	58	.08	2	2.14	.01	.07	1
90R38 215-220	2	47	14	85	.6	28	13	702	3.47	14	5	ND	1	110	.5	2	2	17	2.22	.053	11	35	1.43	102	.03	2	1.20	.01	.12	1
90R38 220-225	5	25	18	77	1.1	26	10	678	3.04	169	5	ND	2	171	.6	4	2	5	3.45	.061	6	25	.78	72	.01	2	.58	.01	.13	1
90R38 225-230	19	42	67	183	2.6	51	10	483	2.79	226	5	ND	4	112	2.0	6	2	9	2.56	.071	9	31	.86	73	.02	2	.62	.01	.15	1
90R38 230-235	13	32	25	127	2.4	41	10	431	2.84	1062	5	ND	3	119	2.2	8	2	5	2.79	.060	8	25	.40	73	.01	5	.32	.01	.15	1
90R38 235-240	9	55	35	162	3.1	29	9	586	2.87	170	5	ND	2	114	1.7	8	2	9	2.66	.063	8	33	1.09	70	.01	2	.75	.01	.12	1
90R38 240-245	4	58	17	123	.9	27	22	672	4.13	79	5	ND	1	112	.2	6	2	51	2.62	.044	6	29	2.32	64	.01	4	2.03	.01	.09	1
90R38 245-250	1	40	8	93	.6	11	21	728	5.82	22	5	ND	1	116	.2	4	2	103	2.84	.044	5	22	2.47	42	.01	3	2.71	.01	.07	1
STANDARD C	20	64	38	134	7.3	73	32	1064	3.95	39	18	8	37	52	17.0	14	21	58	.47	.096	39	60	.88	185	.09	36	1.89	.07	.14	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R39 0-5	5	13	182	171	.4	25	4	331	1.49	10	5	ND	3	12	.5	2	2	11	.15	.024	5	38	1.09	135	.01	2	.82	.01	.07	1
90R39 5-10	4	23	294	335	.7	16	5	353	1.73	20	5	ND	3	18	2.1	2	2	13	.26	.026	6	40	1.12	173	.01	3	.86	.01	.08	1
90R39 10-15	4	30	303	508	.8	13	10	416	2.20	15	5	ND	5	14	4.2	2	2	14	.15	.027	10	48	1.12	143	.01	4	.91	.01	.08	1
90R39 15-20	4	53	228	397	.5	12	8	344	1.93	10	5	ND	4	15	2.4	2	2	15	.15	.028	8	52	1.14	189	.02	3	.93	.01	.10	2
90R39 20-25	4	55	249	308	.8	17	9	341	2.01	12	5	ND	6	31	1.8	2	2	21	.34	.038	15	48	.94	269	.03	2	1.01	.01	.10	1
90R39 25-30	5	19	71	117	.8	8	5	164	1.40	5	5	ND	13	17	1.0	2	2	10	.18	.020	35	53	.56	190	.02	2	.63	.02	.11	1
90R39 30-35	5	14	89	138	.6	2	2	65	1.00	2	5	ND	18	7	14.5	2	2	2	.03	.005	37	38	.31	150	.01	2	.34	.01	.10	3
90R39 35-40	3	125	722	1837	7.2	10	11	158	2.85	11	5	ND	11	18	33.5	22	4	39	.26	.062	30	27	1.12	168	.04	4	1.14	.03	.11	1
90R39 40-45	2	29	146	2446	1.4	17	25	288	6.48	10	5	ND	2	43	22.4	10	2	94	.67	.172	28	34	2.64	215	.11	2	2.53	.09	.13	1
90R39 45-50	2	67	336	1551	4.7	12	13	194	3.85	2	5	ND	6	16	16.6	2	2	50	.28	.085	15	27	1.42	170	.02	2	1.44	.02	.13	1
90R39 50-55	1	35	124	2339	1.6	17	22	370	6.22	2	5	ND	2	41	15.2	4	2	85	.72	.152	21	26	2.66	251	.07	2	2.38	.07	.12	1
90R39 55-60	6	47	223	479	5.5	5	2	41	1.26	2	5	ND	17	8	4.7	4	2	3	.06	.010	17	28	.26	135	.01	2	.38	.01	.14	1
90R39 60-65	2	31	83	1409	2.0	16	21	740	6.29	5	5	ND	3	78	8.2	8	2	80	2.67	.143	25	26	2.56	166	.04	2	2.34	.05	.13	1
90R39 65-70	5	78	309	1587	5.5	12	12	477	3.39	2	5	ND	10	50	7.8	8	2	39	1.87	.075	25	32	1.54	176	.01	2	1.44	.02	.15	1
90R39 70-75	6	93	1501	894	4.6	5	3	149	1.19	8	5	ND	16	17	4.2	28	2	4	.50	.008	30	35	.35	136	.01	2	.42	.01	.15	1
90R39 75-80	4	149	1221	920	4.6	8	8	633	2.26	11	5	ND	10	24	5.1	30	2	13	.91	.014	16	34	1.70	83	.01	4	1.16	.01	.13	1
90R39 80-85	1	34	461	445	1.4	15	18	1255	4.13	5	5	ND	1	17	.9	9	2	34	.73	.020	4	28	3.95	56	.01	3	2.40	.01	.09	1
90R39 85-90	2	74	1575	2376	1.7	19	20	1122	4.69	3	5	ND	1	12	18.0	4	2	36	.48	.023	5	28	3.60	50	.01	2	2.23	.01	.10	1
90R39 90-95	3	195	2361	3867	1.9	5	7	472	2.39	8	5	ND	3	11	32.6	2	2	5	.36	.031	8	32	.82	73	.01	4	.69	.02	.13	1
90R39 95-100	1	146	1613	2223	2.0	14	15	997	3.84	21	5	ND	1	16	15.6	2	2	11	.58	.029	4	33	1.98	61	.01	2	1.34	.01	.13	1
90R39 100-105	2	95	2301	2469	1.9	17	19	1035	4.36	16	5	ND	1	14	17.2	6	3	15	.49	.029	4	36	2.28	56	.01	2	1.49	.01	.12	1
90R39 105-110	1	140	1538	2202	1.5	22	23	1300	4.71	28	5	ND	1	26	14.9	3	2	26	.79	.025	3	44	2.50	50	.01	2	1.67	.02	.11	1
90R39 110-115	1	128	1456	1851	1.4	18	25	1474	4.34	19	5	ND	1	34	13.3	3	2	21	.95	.023	2	37	2.42	57	.01	2	1.52	.01	.09	1
90R39 115-120	2	127	1011	1496	2.2	10	9	592	2.86	16	5	ND	1	11	14.6	3	5	8	.25	.031	3	35	1.85	66	.01	6	1.31	.01	.08	1
90R39 120-125	2	95	1290	1173	2.4	10	9	699	2.58	16	5	ND	1	29	14.9	2	5	5	.76	.028	3	32	1.66	77	.01	2	1.07	.02	.09	1
90R39 125-130	2	64	222	509	.7	7	6	594	1.98	16	5	ND	5	37	4.8	2	3	1	.96	.019	7	28	.84	90	.01	2	.54	.01	.12	1
90R39 130-135	3	39	241	529	.7	6	7	653	2.50	24	5	ND	4	38	5.2	2	2	1	1.04	.019	5	34	.85	74	.01	3	.51	.01	.11	1
90R39 135-140	3	27	70	202	.5	6	4	456	1.95	18	5	ND	6	31	2.1	2	3	1	.90	.020	5	37	.60	93	.01	4	.39	.01	.15	1
90R39 140-145	3	39	54	207	.4	6	6	540	2.28	19	5	ND	5	31	1.9	2	2	1	1.01	.021	5	25	.86	86	.01	4	.56	.01	.12	1
90R39 145-150	3	18	28	185	.3	7	7	448	2.03	6	5	ND	6	21	.7	2	2	1	.64	.015	6	32	.64	94	.01	5	.57	.02	.14	1
90R39 150-155	3	15	93	214	.7	8	6	592	1.99	7	5	ND	6	37	1.5	2	3	1	1.13	.017	5	30	.64	83	.01	4	.43	.03	.12	1
90R39 155-160	4	10	52	253	.5	9	7	592	2.17	7	5	ND	5	38	1.9	2	2	1	1.16	.023	4	32	.72	86	.01	5	.64	.03	.13	1
90R39 160-165	2	12	94	426	.5	21	15	1129	2.87	6	5	ND	1	69	3.0	2	2	10	2.10	.039	2	71	1.31	75	.01	2	.95	.01	.11	1
90R39 165-170	2	26	153	761	.6	12	10	685	2.25	5	5	ND	2	38	4.9	2	2	2	.98	.022	3	54	.67	73	.01	3	.54	.02	.13	1
90R39 170-175	2	40	41	287	.5	12	12	931	2.37	5	5	ND	1	52	2.0	2	2	11	1.23	.022	2	37	1.20	73	.01	4	.79	.02	.08	1
90R39 175-180	1	38	51	204	.4	11	12	808	2.58	7	5	ND	1	43	1.7	2	3	6	1.04	.025	2	28	1.02	64	.01	3	.70	.02	.07	1
STANDARD C	20	62	38	133	7.2	70	32	1058	3.95	41	16	7	36	52	18.6	14	19	57	.48	.096	39	61	.88	185	.09	33	1.88	.07	.13	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R39 180-185	5	20	80	257	.2	9	12	565	2.63	9	5	ND	1	27	2.3	2	2	3	.77	.028	2	27	.78	53	.01	5	.59	.02	.07	2
90R39 185-190	4	22	101	257	.5	11	12	714	2.84	26	5	ND	1	29	2.4	2	3	7	.80	.032	3	46	1.30	62	.01	3	.93	.01	.09	1
90R39 190-195	4	65	220	494	1.0	15	16	431	3.54	47	5	ND	2	18	4.5	3	2	6	.45	.040	7	35	1.31	49	.01	2	1.06	.01	.07	1
90R39 195-200	3	42	57	256	.3	43	29	348	5.42	82	5	ND	1	10	1.9	8	2	15	.19	.041	2	49	2.32	31	.01	2	1.58	.01	.07	1
90R39 200-205	3	84	415	213	1.2	13	15	207	3.69	74	5	ND	1	9	3.6	3	2	3	.20	.028	3	31	.73	40	.01	2	.63	.01	.07	1
90R39 205-210	2	44	171	159	.5	9	18	295	3.97	38	5	ND	1	11	1.9	2	2	8	.26	.027	2	31	1.15	34	.01	4	.88	.01	.06	1
90R39 210-215	1	180	110	271	.8	13	30	621	4.61	60	5	ND	1	20	3.5	4	2	28	.43	.038	2	29	2.76	32	.01	2	1.92	.01	.04	1
90R39 215-220	3	138	147	131	1.0	7	15	429	3.62	39	5	ND	1	29	6.2	2	3	9	.70	.026	2	31	.93	33	.01	4	.76	.02	.06	1
90R39 220-225	3	82	127	310	.8	14	17	528	3.10	26	5	ND	1	21	3.2	2	2	11	.48	.019	3	58	1.73	49	.01	2	1.17	.02	.07	1
90R39 225-230	5	104	99	306	.6	18	20	626	3.57	27	5	ND	1	14	2.4	2	2	14	.24	.020	3	65	2.72	41	.01	2	1.60	.02	.10	1
90R39 230-235	5	186	57	176	.7	8	12	389	1.99	22	5	ND	1	16	4.1	2	2	6	.29	.020	2	44	1.60	36	.01	4	1.07	.02	.08	1
90R39 235-240	3	32	31	88	.2	1	2	238	.98	2	5	ND	7	43	1.1	2	2	2	1.11	.006	11	36	.59	47	.01	3	.45	.01	.09	1
90R39 240-245	4	22	51	90	.1	2	2	228	.91	2	5	ND	8	54	.9	2	2	1	1.44	.003	29	43	.57	72	.01	3	.42	.01	.11	1
90R39 245-250	6	10	47	73	.3	2	2	179	.99	2	5	ND	9	32	.8	2	2	2	1.21	.002	24	63	.41	114	.01	6	.37	.02	.09	1
90R39 250-255	3	23	26	57	.1	3	2	165	.98	4	5	ND	9	30	.5	2	2	1	1.11	.004	17	40	.39	69	.01	2	.35	.02	.07	1
90R39 255-260	3	7	36	64	.2	2	2	158	.77	2	5	ND	9	34	.7	2	2	2	.85	.005	20	36	.35	110	.01	2	.32	.02	.09	1
90R39 260-265	3	11	37	87	.3	1	1	141	.79	5	5	ND	10	44	.3	2	2	1	.84	.002	30	35	.32	154	.01	2	.28	.01	.08	1
90R39 265-270	5	7	45	114	.2	4	1	167	.95	2	5	ND	10	44	.6	2	2	2	.65	.004	31	40	.55	127	.01	2	.38	.01	.10	1
90R39 270-275	4	20	96	304	.5	5	4	217	1.18	5	5	ND	8	54	2.3	2	2	4	.76	.008	31	40	.63	139	.01	2	.48	.01	.09	1
90R39 275-280	7	5	18	297	.1	4	2	117	.76	3	5	ND	11	41	1.3	2	2	1	.51	.001	35	40	.53	239	.01	5	.40	.01	.09	1
90R39 280-285	4	25	445	248	3.3	7	4	197	1.27	3	5	ND	11	32	3.0	4	4	6	.46	.011	27	43	.59	145	.01	5	.51	.02	.11	3
90R39 285-290	3	19	180	318	1.1	4	4	222	1.30	4	5	ND	9	50	2.4	2	2	7	.69	.013	28	41	.80	122	.01	3	.59	.02	.10	2
90R39 290-295	3	29	141	286	.7	4	4	195	1.18	6	5	ND	9	38	3.1	2	2	6	.50	.012	25	37	.73	174	.01	3	.54	.01	.10	2
90R39 295-300	4	29	163	415	1.5	7	6	231	1.41	8	5	ND	9	36	4.0	4	2	9	.40	.015	24	43	.88	212	.01	2	.68	.01	.12	2
STANDARD C	21	62	39	135	7.4	76	32	1073	4.04	43	18	8	36	52	18.8	15	20	57	.49	.095	39	59	.90	185	.09	35	1.92	.07	.13	12

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R45 0-5	5	11	10	54	.1	15	5	246	1.61	21	5	ND	5	22	.4	2	2	15	.40	.031	9	53	.72	194	.02	2	.82	.01	.11	1
90R45 5-10	3	8	11	41	.1	10	3	160	1.25	12	5	ND	5	15	.2	2	2	10	.20	.027	9	38	.55	187	.01	2	.61	.01	.09	1
90R45 10-15	4	7	11	47	.1	13	5	213	1.50	12	5	ND	4	17	.2	2	2	12	.24	.032	9	45	.63	190	.01	2	.71	.01	.09	1
90R45 15-20	3	18	9	73	.1	19	7	312	2.15	16	5	ND	3	67	.2	2	2	20	1.01	.044	7	36	1.12	141	.02	3	1.07	.01	.18	1
90R45 20-25	3	26	4	80	.2	17	7	318	2.51	11	5	ND	4	82	.3	2	2	21	1.34	.054	8	46	1.41	100	.03	3	1.36	.01	.24	1
90R45 25-30	3	22	17	81	.1	19	8	391	2.52	61	5	ND	3	88	.4	2	5	22	1.45	.052	8	35	1.44	91	.02	2	1.39	.01	.24	1
90R45 30-35	4	33	19	100	.1	27	8	461	2.89	144	5	ND	3	66	.3	2	2	26	1.15	.049	6	43	1.75	66	.02	2	1.65	.01	.19	1
90R45 35-40	5	40	23	108	.1	33	10	513	3.23	82	5	ND	4	47	.4	2	2	30	1.02	.051	6	48	1.88	60	.01	4	1.86	.01	.18	1
90R45 40-45	8	27	7	113	.2	26	11	466	3.50	34	5	ND	3	23	.3	3	5	27	.70	.053	5	98	2.00	44	.01	5	1.93	.01	.13	1
90R45 45-50	6	23	22	89	.2	15	7	614	2.76	34	5	ND	4	41	.2	3	2	16	1.24	.042	5	71	1.57	48	.01	2	1.43	.01	.15	1
90R45 50-55	6	33	31	100	.2	19	7	561	2.43	35	5	ND	4	38	.4	2	2	18	1.11	.040	6	63	1.49	77	.01	4	1.42	.01	.22	1
90R45 55-60	7	32	26	130	.4	28	10	565	2.96	63	5	ND	4	54	1.1	3	2	23	1.27	.050	5	78	1.77	60	.01	3	1.57	.01	.15	1
90R45 60-65	4	22	8	93	.1	20	8	467	2.64	22	5	ND	3	137	.8	2	3	22	2.07	.057	7	55	1.53	76	.02	2	1.39	.01	.27	1
90R45 65-70	6	31	6	98	.1	22	11	446	2.97	26	5	ND	4	128	.7	2	2	34	2.29	.053	7	68	1.63	107	.04	3	1.48	.01	.37	1
90R45 70-75	3	101	5	99	1.0	15	15	692	4.57	19	5	ND	4	125	.8	2	3	75	3.08	.051	5	39	1.91	118	.09	2	1.99	.01	.41	1
90R45 75-80	4	46	83	231	1.1	47	15	740	4.02	121	5	ND	3	85	1.8	3	2	34	2.57	.045	3	72	2.24	77	.01	2	2.02	.01	.16	1
90R45 80-85	5	35	61	192	.6	49	17	947	4.10	66	5	ND	2	97	1.6	3	3	41	3.62	.039	2	118	2.26	64	.01	2	2.13	.01	.15	1
90R45 85-90	10	32	86	116	.5	43	15	843	3.90	94	5	ND	2	110	.7	2	5	40	3.36	.050	4	79	1.99	64	.02	5	1.90	.01	.25	1
90R45 90-95	3	49	279	270	1.8	46	17	842	4.05	96	8	ND	2	86	2.4	2	2	36	3.09	.042	3	74	1.95	40	.02	3	1.79	.01	.16	1
90R45 95-100	3	46	185	293	1.2	13	11	704	3.71	60	5	ND	2	72	2.5	2	2	13	2.51	.036	7	31	1.29	50	.01	4	1.04	.01	.17	1
90R45 100-105	3	43	65	133	.5	75	25	969	4.92	74	5	ND	1	120	.7	2	2	47	4.35	.034	2	205	2.21	35	.02	3	1.88	.01	.15	1
90R45 105-110	2	20	45	122	.3	112	21	1111	3.80	46	5	ND	2	179	.5	2	2	55	5.71	.030	2	356	2.52	31	.03	2	2.10	.01	.17	1
90R45 110-115	4	36	42	118	.4	119	19	854	3.46	212	5	ND	3	108	1.0	2	2	33	4.12	.038	4	187	2.03	45	.01	2	1.82	.01	.10	1
90R45 115-120	7	47	26	137	.3	66	15	796	3.22	104	5	ND	3	95	1.1	2	2	26	3.72	.040	2	104	1.91	74	.01	6	1.78	.01	.10	1
90R45 120-125	8	46	36	148	.2	73	15	760	3.18	134	5	ND	4	96	1.1	3	2	22	4.03	.046	3	65	1.64	62	.01	5	1.49	.01	.08	1
90R45 125-130	9	34	29	119	.3	135	22	694	3.34	163	5	ND	5	127	1.0	2	3	36	4.37	.045	2	214	2.01	54	.01	3	1.82	.01	.06	1
90R45 130-135	4	13	116	228	.7	93	20	901	4.01	80	5	ND	2	151	1.9	2	2	33	5.82	.040	2	215	1.80	59	.01	2	1.58	.01	.06	1
90R45 135-140	3	35	83	222	.9	42	19	925	4.23	70	5	ND	4	137	2.1	2	2	23	5.02	.036	2	81	1.58	50	.01	2	1.36	.01	.05	1
90R45 140-145	3	25	39	132	.4	121	23	1002	3.27	110	5	ND	2	174	.9	2	3	44	5.93	.035	2	289	2.06	39	.01	2	1.88	.01	.03	1
90R45 145-150	4	27	13	78	.1	28	12	437	2.87	50	5	ND	1	55	.5	3	2	19	1.61	.031	3	58	1.15	26	.01	2	1.11	.01	.05	1
90R45 150-155	4	42	20	98	.1	30	12	645	2.97	51	5	ND	2	110	.6	3	2	37	3.31	.040	4	62	1.49	40	.01	4	1.64	.01	.05	1
90R45 155-160	4	56	34	98	.1	41	13	803	3.24	82	5	ND	2	177	1.1	3	2	38	5.33	.030	3	99	1.48	40	.01	4	1.55	.01	.05	1
90R45 160-165	5	31	23	77	.2	32	12	688	2.35	40	5	ND	3	140	.8	3	2	26	4.49	.023	5	88	1.08	37	.01	2	1.20	.01	.07	1
90R45 165-170	4	20	20	63	.1	30	11	486	2.11	41	5	ND	3	97	.6	2	2	24	2.70	.029	9	75	1.03	71	.01	2	1.16	.01	.08	1
90R45 170-175	3	20	9	77	.1	28	14	654	3.43	35	5	ND	4	109	.6	2	2	44	2.36	.076	16	65	1.47	275	.09	2	1.51	.09	.09	1
90R45 175-180	3	11	12	44	.1	13	7	322	1.98	15	6	ND	7	62	.4	2	2	20	1.15	.027	20	59	1.00	182	.02	5	1.07	.02	.12	1
STANDARD C	19	56	37	132	6.7	69	31	1051	4.00	42	23	7	38	52	18.9	14	19	56	.48	.091	38	55	.89	180	.09	36	1.90	.06	.13	13

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R45 180-185	4	18	26	50	1.2	8	9	250	1.99	7	5	ND	4	79	.6	2	2	24	1.55	.036	10	61	1.09	89	.03	3	1.19	.01	.10	1
90R45 185-190	4	19	14	63	.1	19	10	272	2.04	8	5	ND	5	57	1.1	2	2	19	1.13	.034	13	54	1.11	108	.04	5	1.11	.01	.08	1
90R45 190-195	3	18	11	53	.1	11	8	328	1.87	9	9	ND	5	88	.6	2	2	17	1.78	.032	12	47	1.04	100	.03	2	.99	.01	.09	1
90R45 195-200	3	28	14	71	.3	28	10	310	2.14	10	5	ND	6	102	.6	2	3	19	2.05	.050	11	48	1.13	95	.01	2	1.09	.01	.09	1
90R45 200-205	4	28	11	73	.3	27	11	319	2.24	16	6	ND	6	83	.6	2	5	24	1.72	.050	14	63	1.14	113	.01	2	1.12	.01	.10	1
90R45 205-210	4	28	10	71	.1	30	12	330	2.47	22	5	ND	5	78	.6	2	2	23	1.28	.052	16	68	1.12	152	.02	2	1.25	.01	.10	1
90R45 210-215	4	19	9	84	.2	29	10	390	2.89	36	5	ND	6	70	.7	2	3	23	1.31	.059	15	65	1.26	139	.01	3	1.45	.01	.11	1
90R45 215-220	4	47	17	105	.3	38	18	674	4.06	23	5	ND	7	95	1.4	2	3	23	2.01	.065	14	62	1.31	164	.02	9	1.81	.01	.12	1
90R45 220-225	10	8	5	27	.1	9	4	210	.98	11	5	ND	1	41	.3	2	2	7	.89	.015	4	121	.36	91	.01	2	.45	.01	.04	1
90R45 225-230	5	14	7	62	.1	22	7	421	2.06	11	5	ND	3	54	.2	2	4	15	1.21	.033	7	89	.87	193	.02	3	1.07	.01	.07	1
90R45 230-235	5	31	17	66	.3	27	10	429	2.27	21	5	ND	5	80	.8	2	3	19	1.93	.051	10	65	.93	153	.03	2	1.09	.01	.10	1
90R45 235-240	4	28	10	73	.4	30	11	439	2.18	15	6	ND	7	102	.9	2	4	22	2.04	.047	9	65	1.02	157	.03	2	1.10	.01	.09	1
90R45 245-250	4	26	8	72	.4	33	10	375	2.18	8	5	ND	3	89	.8	2	2	17	1.46	.048	8	58	1.12	111	.04	3	1.08	.01	.08	1
90R45 250-255	5	31	10	76	.2	37	15	326	2.90	16	5	ND	4	61	.7	2	6	36	.81	.051	9	81	1.36	132	.09	2	1.31	.01	.08	1
90R45 255-260	4	12	6	49	.1	13	7	253	1.68	10	5	ND	2	45	.3	2	4	16	.88	.027	4	55	.84	110	.04	2	.88	.01	.08	1
90R45 260-265	3	16	2	52	.1	8	9	442	2.07	10	5	ND	4	63	.7	2	2	18	1.33	.040	5	48	1.14	111	.05	2	1.17	.01	.12	1
90R45 265-270	2	13	4	63	.1	3	14	645	3.14	6	7	ND	4	150	.8	2	2	58	3.86	.029	5	25	1.85	66	.03	2	1.77	.01	.11	1
90R45 270-275	3	13	10	42	.3	7	8	339	1.69	11	5	ND	6	76	.6	2	5	26	1.80	.019	12	33	.84	117	.01	2	.91	.01	.12	1
90R45 275-280	4	9	12	24	.1	5	4	159	.82	10	5	ND	7	38	.6	2	2	5	.79	.014	18	41	.26	124	.01	2	.36	.01	.13	1
90R45 280-285	5	18	14	52	.2	16	8	274	1.43	27	5	ND	6	51	.4	2	2	15	1.18	.025	15	61	.62	140	.01	3	.75	.01	.11	1
90R45 285-290	4	19	10	52	.1	16	7	330	1.66	98	5	ND	4	71	.5	2	4	13	1.77	.032	10	47	.55	106	.03	2	.69	.01	.11	1
90R45 290-295	3	24	6	74	.1	21	10	443	2.36	12	7	ND	4	53	.8	2	4	20	1.54	.055	8	53	1.02	136	.06	4	1.29	.01	.09	1
90R45 295-300	3	24	13	84	.2	25	12	320	2.37	18	8	ND	4	59	1.1	2	2	25	1.52	.052	7	58	1.30	133	.05	3	1.40	.01	.09	1
90R45 300-305	3	22	9	78	.1	14	10	352	2.39	17	5	ND	1	47	1.2	2	2	15	1.20	.059	4	43	1.31	172	.06	5	1.41	.01	.09	1
90R45 305-310	3	24	9	88	.1	13	14	387	2.84	7	5	ND	1	33	1.0	2	3	16	.91	.069	3	48	1.59	80	.09	5	1.69	.01	.06	1
90R45 310-315	3	17	9	73	.3	7	12	475	3.13	7	5	ND	3	55	1.0	2	3	13	1.83	.062	6	32	1.47	66	.04	4	1.65	.01	.07	1
90R45 315-320	3	48	12	82	.2	8	20	765	4.23	6	5	ND	4	92	1.5	2	2	30	3.17	.045	5	27	1.91	30	.01	2	2.11	.01	.06	1
90R45 320-325	2	42	16	94	.2	14	16	693	3.26	11	5	ND	4	96	1.2	2	2	36	2.52	.049	5	33	1.65	69	.04	3	1.72	.01	.06	1
90R45 325-330	3	38	14	83	.5	19	13	573	3.03	26	5	ND	4	85	.9	2	6	34	2.16	.049	7	38	1.51	88	.03	7	1.64	.01	.08	1
90R45 330-335	2	27	20	76	.1	18	13	695	2.95	22	5	ND	3	87	.9	2	4	38	2.16	.043	8	39	1.48	140	.01	6	1.63	.01	.09	1
90R45 335-340	3	28	7	86	.4	21	13	519	3.01	19	5	ND	6	80	.9	2	4	41	1.71	.050	7	53	1.48	114	.06	2	1.72	.02	.17	1
90R45 340-345	4	31	19	85	.2	24	13	461	2.71	23	5	ND	4	77	1.1	2	2	36	1.81	.044	4	50	1.28	123	.07	2	1.39	.02	.29	1
90R45 345-350	4	32	20	78	.4	26	13	493	2.72	20	5	ND	5	60	.9	2	2	24	1.22	.049	6	60	1.66	90	.05	2	1.52	.01	.18	1
STANDARD C	19	57	37	133	6.9	70	32	1051	3.97	40	18	7	38	52	18.7	16	21	56	.48	.091	38	55	.88	182	.09	34	1.87	.06	.13	11

ACME ANALYTICAL LABORATORIES LTD. 852 E. HASTINGS ST. VANCOUVER B.C. V6A 1R6 PHONE(604)253-3158 FAX(604)253-1716

GEOCHEMICAL ANALYSIS CERTIFICATE

Northern Analytical Labs. Ltd. PROJECT WO#13038 File # 90-6403 Page 1

105 Copper Road, Whitehorse YT Y1A 2Z7

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R46 0-5	5	11	19	26	.1	10	5	82	.80	6	5	ND	8	8	.2	2	2	5	.06	.011	10	29	.19	193	.01	2	.39	.02	.12	2
90R46 5-10	4	10	14	28	.1	9	3	84	.90	5	5	ND	8	9	.2	2	2	6	.07	.013	12	41	.18	248	.02	4	.41	.02	.14	1
90R46 10-15	4	10	15	28	.1	8	6	72	1.03	5	5	ND	9	8	.2	2	2	5	.06	.012	12	43	.17	200	.01	2	.39	.02	.13	1
90R46 15-20	5	12	14	29	.1	8	4	75	.96	6	5	ND	9	9	.2	2	2	4	.06	.012	11	44	.16	469	.01	2	.39	.02	.14	1
90R46 20-25	4	10	12	25	.1	5	3	61	.87	3	5	ND	10	8	.2	2	2	4	.05	.010	12	34	.16	221	.01	2	.37	.02	.14	1
90R46 25-30	8	13	15	27	.1	8	4	98	1.00	6	5	ND	9	12	.2	2	2	4	.08	.013	13	77	.17	257	.01	2	.40	.03	.15	1
90R46 30-35	5	7	12	30	.1	8	5	145	.97	5	5	ND	8	21	.2	2	2	7	.19	.017	17	49	.25	412	.02	2	.46	.04	.15	1
90R46 35-40	6	7	12	35	.1	8	6	178	1.12	9	5	ND	7	24	.2	2	2	9	.26	.024	18	62	.35	380	.02	2	.55	.03	.15	1
90R46 40-45	5	18	23	50	.1	9	9	322	2.06	6	5	ND	5	38	.2	2	2	24	.57	.041	14	53	.75	440	.03	2	.92	.03	.14	1
90R46 45-50	3	20	8	50	.1	10	9	400	2.40	6	5	ND	5	55	.2	2	2	31	.91	.032	13	39	.96	257	.02	2	1.08	.02	.12	2
90R46 50-55	2	23	9	78	.1	10	11	498	3.67	5	5	ND	4	149	.2	2	2	27	2.51	.055	19	42	1.60	128	.01	2	1.81	.01	.14	3
90R46 55-60	1	30	3	77	.1	9	18	706	4.72	9	5	ND	1	120	.2	3	2	58	2.64	.047	11	35	2.18	150	.04	2	2.49	.02	.17	2
90R46 60-65	1	25	10	86	.3	12	14	609	4.15	12	5	ND	2	131	.2	4	2	52	2.35	.049	14	53	1.89	120	.02	2	2.08	.02	.13	1
90R46 65-70	4	38	7	94	.4	35	13	479	3.67	89	5	ND	4	101	.2	3	2	42	2.22	.059	18	50	1.85	368	.01	2	1.99	.02	.13	2
90R46 70-75	5	39	2	102	.5	31	14	478	3.71	70	5	ND	4	117	.2	5	2	48	2.25	.060	19	70	1.87	377	.01	2	2.09	.02	.17	1
90R46 75-80	3	34	11	95	.3	28	14	537	3.57	49	5	ND	3	118	.2	2	2	41	2.29	.058	17	50	1.86	139	.01	2	1.84	.01	.15	1
90R46 80-85	2	25	8	99	.2	23	14	537	3.70	48	5	ND	4	150	.2	2	2	32	3.18	.060	19	47	1.64	161	.01	2	1.81	.01	.14	1
90R46 85-90	4	32	15	96	.6	25	12	478	3.34	65	5	ND	4	89	.3	3	2	25	1.71	.057	15	49	1.59	123	.01	2	1.43	.01	.14	1
90R46 90-95	8	37	25	99	.6	32	14	443	3.45	53	5	ND	4	67	.4	3	2	25	1.21	.056	12	75	1.48	118	.01	2	1.36	.01	.17	2
90R46 95-100	7	41	25	115	.8	35	16	517	3.70	71	5	ND	3	77	.6	6	2	25	1.37	.059	10	63	1.72	105	.01	2	1.47	.01	.19	1
90R46 100-105	5	39	26	81	1.0	32	17	719	3.77	53	5	ND	4	135	.9	7	2	22	2.71	.056	6	47	1.41	67	.01	4	1.16	.01	.16	1
90R46 105-110	5	40	29	88	1.3	29	18	742	4.03	40	5	ND	2	104	.2	6	2	19	2.05	.060	4	69	1.80	99	.01	2	1.33	.01	.19	1
90R46 110-115	4	25	6	92	.6	16	13	754	3.56	11	5	ND	3	95	.2	2	2	16	1.76	.067	11	56	1.44	154	.02	2	1.35	.02	.20	1
90R46 115-120	3	28	21	89	1.2	19	15	724	3.58	18	5	ND	3	98	.5	4	2	23	1.85	.065	11	46	1.56	117	.01	2	1.30	.02	.16	1
90R46 120-125	2	17	18	104	.2	11	10	771	3.56	13	5	ND	3	96	.2	2	2	19	2.06	.084	12	41	1.48	220	.01	2	1.52	.02	.15	1
90R46 125-130	3	19	14	106	.3	14	12	804	3.76	8	5	ND	3	77	.2	3	2	27	1.57	.078	15	60	1.86	233	.01	2	1.74	.03	.16	1
90R46 130-135	3	21	10	98	.2	18	13	641	3.54	7	5	ND	4	65	.2	2	2	32	1.04	.072	15	59	1.83	133	.03	2	1.55	.03	.21	1
90R46 135-140	4	24	14	90	.3	26	14	639	3.55	8	5	ND	3	69	.2	2	2	36	1.24	.059	11	91	1.92	128	.02	2	1.66	.03	.20	2
90R46 140-145	3	16	26	105	.2	13	10	948	3.71	6	5	ND	5	129	.2	3	2	21	2.89	.075	16	49	2.01	263	.02	2	1.93	.02	.22	1
90R46 145-150	5	21	5	97	.3	17	10	621	3.20	14	5	ND	3	69	.2	5	2	20	1.67	.061	11	83	1.90	173	.01	2	1.71	.02	.18	1
90R46 150-155	6	37	28	122	.6	29	14	570	3.61	90	5	ND	3	82	.4	5	2	23	1.58	.066	4	66	1.97	124	.01	2	1.58	.01	.15	1
90R46 155-160	6	41	41	113	.6	32	13	672	3.35	47	5	ND	3	90	.2	3	2	22	1.64	.065	5	68	1.95	128	.01	2	1.41	.01	.14	1
90R46 160-165	4	29	11	111	.2	27	13	549	3.72	11	5	ND	3	114	.2	2	2	25	2.13	.076	8	71	1.84	139	.01	2	1.79	.02	.15	1
90R46 165-170	7	35	25	123	.5	32	13	634	3.63	29	5	ND	3	133	.3	2	2	26	2.21	.074	10	88	1.80	180	.01	2	1.76	.02	.18	1
90R46 170-175	5	41	34	99	.7	35	15	640	3.69	59	5	ND	3	141	.4	3	3	20	2.58	.059	11	46	1.37	112	.01	2	1.21	.01	.11	1
90R46 175-180	2	30	16	86	.4	27	16	547	3.60	31	5	ND	3	101	.2	3	2	29	1.89	.065	11	41	1.66	127	.01	2	1.57	.01	.11	1
STANDARD C	21	64	38	135	7.3	73	32	1076	3.98	41	20	7	40	53	18.9	14	22	60	.48	.096	39	59	.89	181	.09	32	1.89	.07	.14	11

ICP - .500 GRAM SAMPLE IS DIGESTED WITH 3ML 3-1-2 HCL-HNO3-H2O AT 95 DEG. C FOR ONE HOUR AND IS DILUTED TO 10 ML WITH WATER.
THIS LEACH IS PARTIAL FOR MN FE SR CA P LA CR MG BA TI B W AND LIMITED FOR NA K AND AL. AU DETECTION LIMIT BY ICP IS 3 PPM.
- SAMPLE TYPE: PULP

DATE RECEIVED: DEC 20 1990 DATE REPORT MAILED: Jan 2/91 SIGNED BY ..... D.TOYE, C.LEONG, J.WANG; CERTIFIED B.C. ASSAYERS

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R46 180-185	11	45	22	153	.5	74	14	507	3.29	55	5	ND	3	110	1.4	2	2	38	3.08	.055	12	59	1.79	79	.01	3	1.62	.01	.08	5
90R46 185-190	6	37	11	121	.3	48	17	627	4.29	74	5	ND	3	110	.6	2	2	56	3.05	.063	14	60	2.12	118	.02	2	2.15	.02	.12	1
90R46 190-195	4	31	23	87	.5	23	12	479	3.33	17	5	ND	3	77	.4	2	2	27	1.90	.055	13	55	1.94	92	.01	4	1.72	.02	.11	1
90R46 195-200	5	40	24	100	.5	41	13	522	3.68	25	5	ND	3	104	.6	3	2	32	2.69	.055	11	55	1.79	97	.01	2	1.57	.02	.09	1
90R46 200-205	8	36	26	108	.5	48	12	477	2.95	66	5	ND	3	135	.6	2	2	24	2.73	.047	9	52	1.29	146	.01	2	1.17	.01	.10	1
90R46 205-210	12	46	22	135	.6	68	10	447	2.73	104	5	ND	3	168	1.2	2	2	24	3.06	.055	7	72	1.41	133	.01	5	1.23	.01	.11	1
90R46 210-215	12	20	16	68	.4	37	6	196	1.45	148	5	ND	2	60	.4	2	2	10	1.01	.027	6	100	.59	126	.01	2	.58	.01	.08	1
90R46 215-220	10	29	27	123	.5	75	10	324	2.68	505	5	ND	6	114	.8	4	2	12	1.95	.042	9	61	1.19	125	.01	4	1.01	.01	.12	2
90R46 220-225	7	23	27	112	.3	106	10	367	2.45	265	5	ND	5	131	.6	2	2	11	2.58	.044	9	45	1.33	59	.01	2	.93	.01	.08	1
90R46 225-230	5	15	14	80	.2	29	6	283	1.86	81	5	ND	7	79	.3	2	2	6	1.35	.023	13	55	.93	164	.01	2	.91	.03	.15	1
90R46 230-235	4	18	20	58	.3	16	6	358	1.89	31	5	ND	6	72	.2	2	2	11	1.40	.031	14	55	.81	154	.01	5	.88	.03	.14	1
90R46 235-240	3	7	19	89	.1	21	8	200	2.03	142	5	ND	9	81	.2	2	2	3	1.14	.014	13	42	1.14	137	.01	4	1.05	.02	.15	1
90R46 240-245	7	20	22	101	.4	64	7	299	1.79	144	5	ND	8	122	.5	2	2	9	2.19	.026	13	54	1.07	138	.01	2	.90	.01	.13	1
90R46 245-250	4	25	11	69	.3	36	7	372	2.21	82	5	ND	6	106	.2	2	2	27	1.15	.049	18	74	.77	160	.01	3	.98	.03	.15	1
90R46 250-255	4	29	10	77	.4	19	6	344	1.94	25	5	ND	5	71	.4	2	2	16	1.11	.044	17	69	.62	188	.01	2	.89	.03	.15	1
90R46 255-260	5	11	42	58	.4	13	4	252	1.45	15	5	ND	8	54	.2	2	2	6	.89	.020	16	66	.85	185	.01	2	.91	.02	.16	1
90R46 260-265	7	17	18	77	.3	25	4	279	1.33	41	5	ND	8	72	.6	2	4	7	1.46	.019	17	68	.99	178	.01	4	.89	.02	.12	1
90R46 265-270	11	37	18	140	.4	65	11	483	2.92	58	5	ND	4	114	.8	2	2	29	2.35	.061	13	85	1.62	121	.01	2	1.46	.01	.12	2
90R46 270-275	7	35	16	103	.6	42	10	488	2.70	74	5	ND	6	136	1.4	4	2	24	2.69	.065	15	65	.99	142	.02	5	1.12	.02	.15	1
90R46 275-280	3	37	7	81	.2	25	9	450	2.31	51	5	ND	4	146	.2	2	2	25	2.43	.065	11	65	.59	199	.05	2	.88	.03	.18	1
90R46 280-285	4	41	7	118	.3	35	13	391	2.85	133	5	ND	4	138	.6	3	2	30	2.07	.063	10	69	.94	233	.05	3	1.09	.03	.14	1
90R46 285-290	4	32	15	83	.4	25	9	376	2.43	81	5	ND	4	140	.5	2	2	18	2.31	.056	10	53	.74	159	.03	2	.79	.03	.19	1
90R46 290-295	3	11	23	65	.4	16	5	282	1.47	35	5	ND	6	153	.2	2	2	7	2.03	.023	10	42	.84	139	.01	2	.77	.02	.14	1
90R46 295-300	7	17	21	78	1.1	20	4	166	1.59	131	5	ND	7	89	.5	2	2	5	1.23	.020	14	51	.62	221	.01	3	.65	.03	.15	1
90R46 300-305	7	24	24	77	1.8	28	5	177	1.71	105	5	ND	7	103	.5	2	2	6	1.56	.025	16	41	.58	209	.01	3	.61	.02	.13	1
90R46 305-310	3	5	22	56	.6	4	2	77	1.04	20	5	ND	9	63	.3	2	2	1	.79	.012	21	24	.23	144	.01	3	.37	.03	.14	2
90R46 310-315	4	8	20	60	.4	11	8	207	1.55	35	5	ND	8	72	.2	2	2	6	.98	.027	15	47	.58	165	.02	2	.69	.03	.19	2
90R46 315-320	6	28	10	108	.5	41	13	466	2.90	121	5	ND	5	115	.3	2	2	23	1.99	.064	12	64	1.05	183	.02	2	1.23	.02	.18	1
90R46 320-325	3	44	8	97	.2	30	21	702	4.62	109	5	ND	1	97	.2	2	2	68	2.35	.051	5	42	2.17	86	.08	2	2.18	.03	.08	1
90R46 325-330	4	31	3	87	.1	28	19	571	3.48	61	5	ND	2	92	.2	2	2	43	2.16	.057	10	67	1.90	136	.07	2	1.81	.03	.14	1
90R46 330-335	3	27	12	91	.3	32	11	477	2.48	86	5	ND	5	110	.2	2	2	21	2.29	.067	20	42	1.41	114	.01	2	1.27	.02	.12	1
90R46 335-340	5	30	9	83	.2	33	14	402	2.87	122	5	ND	3	80	.2	2	2	29	1.63	.060	15	70	1.74	130	.01	2	1.60	.02	.15	1
90R46 340-345	4	42	14	94	.6	48	15	571	3.34	150	5	ND	2	108	.5	2	2	28	2.60	.048	9	44	1.30	126	.01	2	1.23	.02	.09	1
90R46 345-350	7	38	13	99	.4	43	11	523	2.77	139	5	ND	3	123	.9	3	2	29	2.59	.045	9	67	1.10	143	.01	3	1.11	.02	.11	1
90R46 350-355	4	32	29	104	.6	23	14	590	3.45	81	5	ND	2	89	.8	2	4	25	2.18	.051	12	45	1.70	125	.01	2	1.44	.02	.11	1
90R46 355-360	3	36	15	95	.5	29	13	652	3.33	70	5	ND	2	126	.9	2	2	22	2.70	.057	10	46	1.31	120	.02	2	1.19	.02	.11	1
STANDARD C	21	62	39	137	7.4	74	32	1080	4.00	42	20	7	39	54	17.3	14	22	62	.48	.097	40	59	.89	182	.09	36	1.90	.07	.15	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R46 360-365	8	36	18	101	1.1	37	14	580	3.69	192	5	ND	2	182	.9	5	2	8	3.97	.065	6	52	.69	23	.01	2	.66	.01	.14	1
90R46 365-370	4	22	31	132	3.8	19	11	916	4.23	91	5	ND	1	163	1.5	10	2	8	4.42	.064	3	38	.85	22	.01	2	.66	.01	.12	1
90R46 370-375	7	33	22	129	2.1	34	12	726	3.96	120	5	ND	2	129	.9	5	2	11	3.46	.066	3	43	1.04	29	.03	2	.79	.01	.15	1
90R46 375-380	17	47	27	203	1.4	45	10	498	3.18	67	5	ND	2	148	2.2	4	2	19	3.59	.071	5	58	1.14	28	.03	2	.93	.01	.11	1
90R46 380-385	9	41	18	127	.8	55	12	435	2.75	54	5	ND	3	97	1.0	5	2	26	2.27	.056	7	60	1.44	73	.03	2	1.23	.01	.09	1
90R46 385-390	7	47	13	109	.9	75	13	587	2.99	68	5	ND	1	100	.8	4	2	33	2.56	.054	8	94	1.74	81	.02	2	1.46	.01	.07	1
90R46 390-395	6	50	16	86	.7	159	20	677	3.05	131	5	ND	1	114	.6	4	2	34	2.79	.044	6	155	2.41	92	.02	2	1.80	.01	.06	1
90R46 395-400	8	58	43	128	1.2	131	16	621	2.82	81	5	ND	2	149	1.2	5	2	27	3.40	.046	9	129	2.01	84	.01	2	1.51	.01	.07	1
90R46 400-405	8	54	30	116	1.1	124	18	518	3.14	169	5	ND	3	129	1.9	5	2	28	2.63	.052	8	109	2.02	59	.01	2	1.56	.01	.08	1
90R46 405-410	12	39	30	147	1.2	45	10	403	3.18	48	5	ND	3	140	1.3	6	2	18	3.02	.063	11	55	1.38	26	.01	2	1.09	.01	.09	1
90R46 410-415	15	47	20	146	.9	52	10	391	2.64	31	5	ND	4	158	1.6	3	2	19	3.15	.067	18	64	1.12	63	.01	2	.99	.01	.10	1
90R46 415-420	9	34	12	119	1.0	39	11	374	2.94	34	5	ND	4	111	1.1	2	2	16	2.08	.070	17	51	1.04	71	.01	2	1.05	.01	.11	1
90R46 420-425	8	30	23	107	6.5	39	10	406	3.18	80	5	ND	3	158	.9	6	2	11	3.22	.057	14	54	.64	22	.01	2	.64	.01	.11	1
90R46 425-430	8	40	16	104	1.3	36	11	433	2.90	36	5	ND	3	140	1.0	2	2	13	2.82	.065	14	64	.87	37	.01	2	.82	.01	.12	1
90R46 430-435	5	52	152	246	3.1	31	13	476	3.58	35	5	ND	2	138	1.8	5	2	11	2.71	.063	10	43	1.22	38	.01	2	.98	.01	.09	1
90R46 435-440	7	42	49	154	.8	34	10	446	3.05	60	5	ND	3	100	1.3	3	2	22	2.20	.065	11	69	1.18	90	.01	2	1.17	.01	.10	1
90R46 440-445	7	30	35	150	1.4	23	9	414	3.09	54	5	ND	2	116	1.5	4	2	12	2.56	.056	10	56	1.13	35	.01	2	.96	.01	.11	1
90R46 445-450	4	45	400	483	4.4	27	14	793	3.94	52	5	ND	1	166	4.8	7	2	16	4.58	.044	6	37	1.49	36	.01	2	1.04	.01	.08	1
90R46 450-455	5	36	75	258	1.3	31	11	567	3.06	52	5	ND	2	139	2.0	3	2	20	3.49	.056	11	52	1.13	60	.01	2	1.04	.01	.08	1
90R46 455-460	7	34	24	126	1.6	36	9	352	2.64	207	5	ND	5	154	1.1	2	2	18	3.10	.059	19	51	.91	57	.01	2	.92	.01	.13	1
90R46 460-465	7	32	24	122	8.4	43	9	351	2.76	67	5	ND	2	129	1.3	3	2	16	2.38	.054	8	44	.91	32	.01	2	.83	.01	.10	1
90R46 465-470	8	34	33	133	3.4	54	14	323	3.70	96	5	ND	2	101	1.5	6	2	17	2.00	.054	6	57	.99	25	.01	2	.90	.01	.09	2
90R46 470-475	5	32	36	145	8.3	39	13	460	3.85	133	5	ND	2	133	1.2	9	2	9	2.71	.053	6	41	.61	22	.01	3	.58	.01	.11	1
90R46 475-480	9	29	25	107	4.8	41	11	332	3.30	131	5	ND	2	101	1.2	5	2	11	2.03	.052	11	66	.61	25	.01	2	.62	.01	.13	1
90R46 480-485	7	26	16	84	.6	30	8	372	2.22	83	5	ND	3	96	.5	3	2	14	2.08	.053	11	58	.78	109	.01	2	.87	.01	.12	1
90R46 485-490	7	54	11	106	.8	36	10	457	1.92	43	5	ND	2	78	.9	2	2	21	1.91	.056	11	80	.85	158	.03	2	.97	.01	.12	1
90R46 490-495	5	26	12	94	.2	32	9	415	2.08	25	5	ND	2	77	.3	2	2	22	1.55	.057	11	72	.91	151	.04	2	1.04	.01	.10	1
90R46 495-500	4	24	10	90	.3	31	9	417	2.08	29	5	ND	2	77	.3	2	2	23	1.56	.057	11	67	.94	149	.04	2	1.07	.01	.10	1
STANDARD C	21	62	36	134	7.0	74	32	1073	4.03	43	18	7	36	52	18.6	14	21	56	.49	.097	39	58	.90	186	.09	34	1.92	.07	.13	12

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R47 0-5	6	42	23	98	.1	24	10	238	2.73	4	5	ND	5	16	.5	2	2	31	.17	.055	14	49	1.61	176	.01	3	1.74	.01	.12	2
90R47 5-10	5	58	28	115	.2	29	9	290	3.82	50	5	ND	6	23	.3	5	2	57	.15	.065	18	48	2.23	189	.02	2	2.28	.01	.15	1
90R47 10-15	3	39	28	115	.1	22	8	329	4.47	16	5	ND	4	11	.2	3	2	65	.14	.055	13	65	2.95	149	.03	3	2.84	.01	.12	1
90R47 15-20	5	51	30	111	.1	26	6	327	4.33	76	5	ND	4	10	.2	3	2	69	.12	.057	11	50	2.56	128	.03	2	2.49	.01	.11	1
90R47 20-25	8	81	15	117	.2	20	6	333	5.23	88	6	ND	5	8	.2	5	2	82	.09	.064	9	49	2.55	134	.02	4	2.60	.02	.12	1
90R47 25-30	10	58	20	113	.3	23	5	230	4.07	93	5	ND	7	14	.2	4	2	36	.09	.077	15	56	1.93	165	.02	2	1.94	.02	.14	1
90R47 30-35	8	40	18	84	.2	12	3	154	2.78	55	5	ND	7	15	.2	2	2	20	.11	.080	20	53	.97	215	.04	2	1.24	.02	.18	1
90R47 35-40	4	41	11	113	.2	43	13	251	2.81	17	5	ND	6	12	.6	2	2	33	.19	.061	18	77	.96	203	.09	2	1.43	.02	.16	1
90R47 40-45	4	40	10	141	.2	48	16	388	2.81	15	5	ND	5	76	.7	2	2	35	1.21	.058	19	65	.92	216	.05	2	1.32	.02	.17	1
90R47 45-50	3	39	10	135	.2	52	17	396	2.37	10	5	ND	5	40	.7	2	2	27	.83	.062	18	54	.69	219	.03	3	1.03	.01	.20	1
90R47 50-55	3	26	9	106	.1	35	10	384	2.50	8	5	ND	5	63	.4	2	3	32	1.14	.058	17	71	.76	211	.08	2	1.18	.02	.17	1
90R47 55-60	7	39	13	131	.2	39	15	350	2.62	25	5	ND	5	40	.6	2	2	25	.71	.060	19	86	.96	177	.06	2	1.21	.02	.14	1
90R47 60-65	7	33	19	126	.2	64	11	282	2.39	21	5	ND	7	27	.5	2	2	36	.48	.064	23	89	1.23	181	.10	2	1.46	.02	.16	1
90R47 65-70	14	34	25	106	.4	55	7	288	2.52	15	5	ND	7	28	.8	2	2	33	.39	.071	20	77	1.40	138	.06	3	1.47	.01	.13	1
90R47 70-75	15	48	20	160	.3	94	20	625	2.86	28	5	ND	6	57	1.1	3	2	22	1.03	.068	30	62	1.32	144	.01	2	1.33	.01	.14	2
90R47 75-80	9	32	14	128	.3	69	13	430	2.49	55	5	ND	6	60	.7	2	2	21	1.15	.065	24	72	1.23	149	.02	3	1.23	.01	.13	1
90R47 80-85	3	26	4	107	.2	33	11	441	2.62	24	5	ND	4	84	.2	3	2	26	2.06	.060	20	58	.99	163	.01	2	1.26	.02	.15	1
90R47 85-90	4	35	10	116	.1	25	12	422	2.74	26	5	ND	5	55	.3	2	2	32	1.00	.060	17	80	.94	236	.03	2	1.33	.02	.21	1
90R47 90-95	3	33	8	111	.2	30	11	377	2.66	34	5	ND	4	79	.2	2	2	29	1.25	.052	14	64	.91	162	.03	2	1.21	.02	.16	1
90R47 95-100	3	23	8	102	.2	30	9	330	2.70	34	5	ND	4	111	.5	2	2	33	1.30	.053	16	68	.85	170	.04	2	1.05	.03	.19	1
90R47 100-105	3	31	11	97	.2	25	9	455	2.59	29	5	ND	3	132	.3	2	2	26	2.11	.055	14	58	.86	202	.04	2	1.11	.01	.15	1
90R47 105-110	2	39	9	98	.2	29	11	428	2.38	11	5	ND	4	95	.2	2	2	18	1.53	.057	17	43	.71	251	.02	3	1.01	.01	.21	1
90R47 110-115	9	34	18	150	.4	71	17	330	2.73	64	5	ND	7	41	1.1	2	2	16	.61	.083	26	51	.93	220	.04	2	1.14	.01	.20	1
90R47 115-120	12	33	20	120	.6	54	10	418	2.68	24	5	ND	5	97	.8	2	2	13	2.09	.063	17	61	1.09	188	.03	3	1.15	.01	.19	1
90R47 120-125	9	30	18	121	.4	45	16	535	3.90	64	5	ND	3	85	.6	2	2	39	1.82	.059	16	52	1.87	120	.02	2	1.82	.01	.13	1
90R47 125-130	5	28	12	103	.1	38	15	444	3.56	35	5	ND	4	39	.3	2	2	38	.62	.061	20	59	2.28	143	.03	2	2.10	.02	.17	1
90R47 130-135	6	28	16	93	.2	27	14	510	3.62	14	5	ND	2	58	.2	2	2	33	.84	.058	11	67	2.20	136	.04	2	2.00	.02	.18	1
90R47 135-140	4	28	11	107	.1	30	16	478	3.91	17	5	ND	2	32	.2	4	2	39	.51	.058	7	56	2.47	108	.02	2	2.20	.01	.14	1
90R47 140-145	5	37	20	104	.6	47	19	572	3.37	31	5	ND	4	41	1.2	2	2	24	.68	.059	11	54	1.60	105	.02	2	1.43	.01	.15	1
90R47 145-150	5	33	12	97	.1	30	14	535	3.39	22	5	ND	2	54	.2	2	2	31	.90	.056	6	65	1.87	107	.01	2	1.76	.01	.15	1
90R47 150-155	5	29	14	103	.1	29	17	610	3.95	29	5	ND	1	49	.2	2	2	40	.94	.058	7	70	2.42	116	.01	2	2.26	.01	.17	1
90R47 155-160	2	26	10	90	.1	25	17	583	3.73	26	5	ND	1	55	.2	3	2	39	1.16	.056	7	38	2.32	88	.01	2	2.11	.01	.14	1
90R47 160-165	5	30	8	100	.2	27	15	565	3.82	15	5	ND	2	57	.2	2	2	46	.96	.057	6	69	2.40	109	.03	2	2.18	.01	.20	1
90R47 165-170	2	28	19	91	.3	27	16	687	3.50	81	5	ND	2	63	.2	5	2	37	1.33	.056	3	38	2.56	87	.02	2	2.15	.01	.20	1
90R47 170-175	3	26	14	87	.3	24	12	471	2.81	26	5	ND	3	105	.2	2	2	23	1.67	.060	4	42	1.76	103	.04	2	1.50	.01	.28	1
90R47 175-180	3	26	15	65	.4	20	10	657	2.13	16	5	ND	4	194	.2	2	2	20	2.81	.065	5	40	1.44	164	.05	2	1.13	.01	.52	1
STANDARD C	20	64	39	134	7.4	73	32	1066	3.95	42	20	6	39	53	18.7	15	21	59	.47	.095	41	59	.88	187	.09	36	1.88	.07	.14	12

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R47 180-185	3	44	3	102	1.1	22	18	631	3.46	20	5	3	2	205	.7	6	2	37	3.24	.052	4	56	1.79	140	.07	4	1.43	.02	.52	1
90R47 185-190	3	32	2	73	.3	20	13	717	2.54	21	5	ND	2	81	.3	3	2	28	1.92	.063	5	36	1.00	121	.08	2	1.05	.01	.40	1
90R47 190-195	3	39	11	86	.4	18	16	713	3.99	17	5	ND	1	84	.2	6	2	48	2.21	.064	4	31	1.63	116	.11	2	1.69	.02	.56	1
90R47 195-200	1	42	2	102	.5	16	26	874	6.31	11	5	ND	1	104	.2	6	2	100	2.45	.054	3	25	3.32	86	.14	2	3.08	.02	.57	1
90R47 200-205	4	45	5	82	1.5	26	17	825	3.94	26	5	ND	4	231	.9	6	2	39	3.21	.097	6	44	1.67	154	.10	4	1.46	.03	.72	1
90R47 205-210	1	202	8	69	5.5	20	20	678	4.61	27	5	ND	1	298	.3	9	2	42	2.65	.096	4	28	1.91	123	.14	2	1.36	.02	.72	1
90R47 210-215	1	189	10	79	4.8	9	19	801	5.12	24	5	ND	1	431	.8	11	2	51	4.03	.067	2	19	2.26	72	.16	2	1.59	.02	.94	2
90R47 215-220	1	46	4	50	1.1	20	15	598	3.22	63	5	ND	2	265	.2	7	2	29	2.72	.075	5	28	1.33	168	.08	2	1.05	.02	.69	1
90R47 220-225	2	34	2	74	.6	16	15	607	3.57	22	5	ND	1	157	.3	6	2	33	2.51	.092	5	26	1.34	126	.07	2	1.29	.02	.58	1
90R47 225-230	1	56	5	119	1.3	10	22	781	6.10	23	5	ND	1	264	.4	10	2	77	2.68	.049	2	20	2.93	134	.16	2	2.20	.03	1.31	1
90R47 230-235	1	75	6	121	1.7	16	17	947	4.69	22	5	ND	1	365	.4	8	2	41	4.28	.030	2	23	2.42	128	.08	2	1.65	.02	.75	1
90R47 235-240	2	68	6	112	.8	72	20	931	4.34	97	5	ND	1	127	.2	8	2	41	2.81	.046	3	66	2.57	126	.04	2	2.17	.01	.32	2
90R47 240-245	2	56	4	91	.6	62	19	826	4.23	50	5	ND	1	125	.2	6	2	39	2.83	.055	4	68	1.90	126	.03	2	1.81	.01	.23	1
90R47 245-250	3	29	12	101	.6	32	14	439	2.87	76	5	ND	2	116	.5	3	2	19	2.05	.080	9	49	1.10	137	.02	2	.96	.02	.30	1
STANDARD C	20	63	42	136	7.2	72	32	1085	4.02	42	18	7	38	53	18.8	15	21	58	.48	.094	39	60	.89	187	.09	34	1.91	.07	.13	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R48 0-5	5	14	15	67	.1	10	6	320	1.74	12	5	ND	5	35	.2	2	2	14	.47	.027	20	26	.69	324	.01	3	.99	.01	.15	2
90R48 5-10	3	10	13	66	.2	10	4	361	1.45	19	5	ND	5	109	.5	2	2	9	1.63	.046	14	26	.55	358	.01	3	.74	.01	.15	1
90R48 10-15	3	11	9	54	.2	11	6	280	1.51	15	5	ND	4	40	.4	2	2	15	.59	.031	13	43	.62	292	.02	3	.82	.01	.13	1
90R48 15-20	3	6	11	32	.1	6	3	361	1.05	21	5	ND	5	60	.2	2	2	7	1.09	.026	14	28	.17	396	.01	2	.52	.01	.16	1
90R48 20-25	2	8	16	17	.1	11	3	285	.73	18	5	ND	8	67	.2	2	2	4	1.14	.011	21	17	.09	306	.01	2	.36	.01	.18	1
90R48 25-30	4	6	13	52	.2	8	4	338	1.72	70	5	ND	7	113	.2	2	2	5	2.32	.019	24	44	.38	225	.01	3	.78	.01	.17	1
90R48 30-35	7	8	13	44	.4	7	4	317	1.41	64	5	ND	8	90	.7	3	2	6	2.12	.020	23	60	.25	223	.01	5	.61	.02	.15	2
90R48 35-40	4	3	12	33	.1	3	2	434	1.11	68	5	ND	7	92	.2	2	2	2	1.94	.015	25	27	.13	176	.01	2	.37	.01	.11	1
90R48 40-45	3	4	21	39	.1	5	2	352	.98	39	5	ND	8	82	.2	2	2	2	1.66	.011	25	21	.23	200	.01	2	.45	.01	.10	3
90R48 45-50	4	8	17	76	.1	8	5	557	1.76	46	5	ND	6	99	.2	2	2	6	1.99	.024	21	41	.49	197	.01	2	.85	.02	.11	1
90R48 50-55	3	8	17	72	.1	6	5	441	1.93	48	5	ND	6	112	.3	2	2	6	2.12	.026	19	33	.55	173	.01	2	.86	.02	.11	1
90R48 55-60	2	5	5	81	.1	7	4	247	1.75	11	5	ND	2	71	.2	2	2	5	1.16	.028	7	22	.97	239	.02	2	1.19	.01	.08	1
90R48 60-65	4	8	7	85	.1	6	5	339	1.92	10	5	ND	2	85	.4	2	2	6	1.59	.029	8	39	.92	271	.02	2	1.20	.02	.09	1
90R48 65-70	2	7	5	78	.1	6	5	296	1.90	10	5	ND	3	64	.2	2	2	6	1.19	.029	8	34	.85	211	.02	4	1.14	.02	.10	1
90R48 70-75	3	8	8	77	.1	5	5	286	1.75	9	5	ND	3	63	.2	2	2	6	1.24	.032	10	29	.81	189	.03	3	1.06	.01	.09	1
90R48 75-80	2	7	8	71	.1	6	5	315	1.79	12	5	ND	3	110	.2	2	2	5	1.85	.027	8	24	.89	189	.02	4	1.08	.01	.09	1
90R48 80-85	2	5	5	75	.1	6	4	229	1.64	6	5	ND	1	48	.2	2	2	5	.87	.028	5	37	.98	126	.03	3	1.19	.01	.07	1
90R48 85-90	3	6	4	71	.1	5	5	222	1.62	5	5	ND	1	39	.2	2	2	5	.76	.027	4	37	.91	157	.04	3	1.03	.01	.06	1
90R48 90-95	2	9	7	74	.2	8	4	176	1.42	7	5	ND	1	67	.2	2	2	4	.76	.030	4	34	.95	197	.03	4	1.06	.01	.08	1
90R48 95-100	3	8	2	69	.1	5	5	441	1.43	4	5	ND	1	48	.2	2	2	7	.88	.036	4	35	.66	170	.04	3	.84	.02	.06	1
STANDARD C	20	62	38	134	7.0	72	32	1070	4.01	43	17	7	37	52	18.7	15	20	57	.49	.096	39	58	.89	186	.09	35	1.91	.07	.13	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R49 0-5	7	12	18	48	.1	11	6	452	1.35	24	5	ND	3	114	.3	2	2	8	1.75	.050	15	36	.38	213	.01	2	.58	.01	.16	1
90R49 5-10	4	11	23	57	.3	12	5	471	1.58	29	5	ND	4	116	.2	2	2	11	1.82	.050	16	38	.50	261	.02	2	.73	.01	.16	1
90R49 10-15	5	10	28	57	.2	10	5	345	1.55	22	5	ND	5	67	.2	2	2	12	.89	.041	16	55	.52	243	.01	2	.74	.01	.17	1
90R49 15-20	3	8	14	26	.4	10	5	334	1.40	22	5	ND	5	103	.2	2	2	7	2.04	.046	19	28	.24	173	.01	2	.43	.01	.16	1
90R49 20-25	3	7	17	13	.1	11	4	501	.97	21	5	ND	6	132	.2	2	2	3	2.23	.042	24	33	.09	155	.01	2	.34	.02	.24	1
90R49 25-30	6	7	15	21	.2	9	4	824	.95	29	5	ND	6	155	.2	3	2	4	2.28	.038	22	64	.13	189	.01	2	.44	.02	.31	1
90R49 30-35	8	17	16	48	.4	22	5	591	1.73	118	5	ND	5	178	.3	3	2	7	2.81	.067	17	35	.27	99	.01	2	.46	.01	.20	1
90R49 35-40	27	39	17	176	.6	36	7	367	2.49	126	7	ND	5	207	1.2	6	2	19	3.69	.377	14	31	.77	63	.01	2	1.03	.01	.22	1
90R49 40-45	8	39	12	207	.5	31	7	525	1.92	125	5	ND	2	382	2.9	4	2	15	9.41	.111	11	36	.75	130	.01	2	.82	.01	.14	1
90R49 45-50	6	48	10	215	1.1	30	7	517	2.03	316	5	ND	2	394	3.9	2	2	16	8.45	.083	10	38	.86	89	.01	2	.83	.01	.12	1
90R49 50-55	12	38	48	343	1.7	34	7	458	2.34	89	5	ND	1	357	4.5	4	2	20	6.63	.096	6	43	1.08	82	.01	2	.84	.01	.11	1
90R49 55-60	7	49	25	154	2.0	40	8	511	2.12	151	5	ND	1	521	1.7	2	2	17	12.43	.124	7	43	.93	95	.01	2	.77	.01	.15	1
90R49 60-65	3	26	17	126	.6	54	12	469	3.10	62	5	ND	4	401	.3	6	2	19	4.79	.048	11	71	2.67	86	.01	3	2.10	.01	.12	1
90R49 65-70	3	17	9	68	.3	23	6	340	1.67	52	5	ND	7	229	.2	2	2	9	3.32	.027	21	42	.95	183	.01	2	.96	.01	.15	1
90R49 70-75	4	11	14	92	.3	15	6	323	1.70	46	5	ND	6	185	.3	4	2	7	2.81	.025	23	33	.76	129	.01	2	.87	.01	.11	1
90R49 75-80	5	14	11	91	.7	14	5	427	1.90	30	5	ND	7	172	1.3	3	2	11	2.93	.038	23	33	.79	121	.01	3	1.01	.01	.14	1
90R49 80-85	4	16	17	80	.4	14	4	404	1.57	36	5	ND	3	347	.5	3	2	8	5.59	.029	14	39	.78	160	.01	2	.79	.01	.10	1
90R49 85-90	4	12	15	73	.3	13	4	369	1.54	25	5	ND	4	329	.2	2	2	7	5.18	.024	17	44	.76	194	.01	2	.82	.01	.11	1
90R49 90-95	4	9	65	119	.3	8	5	457	1.84	25	5	ND	2	186	.3	2	2	9	2.54	.036	11	43	.88	124	.01	2	1.00	.02	.09	1
90R49 95-100	3	11	12	70	.3	5	6	738	1.92	7	5	ND	3	164	.2	3	2	11	2.72	.040	17	28	.57	146	.01	2	.81	.02	.11	1
STANDARD C	20	63	42	136	7.2	72	32	1085	4.02	42	18	7	38	53	18.8	15	21	58	.48	.094	39	60	.89	187	.09	34	1.91	.07	.13	11

SAMPLE#	Mo ppm	Cu ppm	Pb ppm	Zn ppm	Ag ppm	Ni ppm	Co ppm	Mn ppm	Fe %	As ppm	U ppm	Au ppm	Th ppm	Sr ppm	Cd ppm	Sb ppm	Bi ppm	V ppm	Ca %	P %	La ppm	Cr ppm	Mg %	Ba ppm	Ti %	B ppm	Al %	Na %	K %	W ppm
90R50 0-5	6	14	13	70	.1	15	9	319	1.99	11	5	ND	3	36	.5	2	2	21	.47	.043	13	88	.69	247	.02	2	1.08	.01	.10	1
90R50 5-10	8	10	14	48	.1	16	8	320	1.68	14	5	ND	3	70	.5	2	2	12	1.18	.065	11	98	.41	158	.02	3	.68	.01	.13	1
90R50 10-15	5	5	15	35	.1	15	7	482	1.70	16	5	ND	6	126	.4	2	2	3	3.22	.082	15	33	.14	90	.01	3	.33	.01	.13	1
90R50 15-20	5	7	9	45	.1	14	6	479	1.88	13	5	ND	5	111	.4	2	2	6	2.61	.054	16	38	.38	102	.01	3	.68	.01	.13	1
90R50 20-25	2	7	14	73	.1	6	6	562	2.37	11	5	ND	8	160	.2	4	4	8	3.11	.038	21	19	.95	162	.01	4	1.52	.01	.17	1
90R50 25-30	3	7	13	44	.5	11	6	1193	1.76	16	5	ND	10	274	.4	3	2	5	6.63	.038	11	30	.43	56	.01	2	.77	.01	.19	1
90R50 30-35	4	4	8	170	.1	13	5	696	1.53	15	6	ND	3	196	1.9	2	2	3	3.85	.035	5	38	.31	115	.01	3	.42	.01	.13	1
90R50 35-40	3	7	18	34	.2	15	5	714	1.33	19	5	ND	7	210	.5	2	2	3	4.17	.038	11	29	.20	139	.01	4	.40	.01	.19	1
90R50 40-45	3	8	13	27	.1	10	4	760	.98	17	5	ND	6	207	.2	2	2	2	4.23	.031	10	40	.15	205	.01	2	.32	.01	.19	1
90R50 45-50	4	3	16	21	.1	12	4	689	.95	26	8	ND	6	188	.2	2	2	2	3.84	.035	12	36	.13	176	.01	5	.34	.01	.22	1
90R50 50-55	3	5	11	23	.1	9	4	622	.83	6	5	ND	2	178	.2	2	2	1	3.30	.032	7	35	.14	232	.01	2	.28	.01	.16	1
90R50 55-60	3	7	13	18	.2	10	3	550	.81	13	5	ND	6	149	.2	2	2	2	3.11	.035	10	35	.10	223	.01	3	.28	.01	.20	1
90R50 60-65	11	6	12	13	.1	11	4	506	1.23	13	5	ND	6	175	.2	2	2	2	3.72	.036	13	146	.14	151	.01	2	.30	.01	.15	1
90R50 65-70	3	3	11	15	.2	11	4	407	1.21	16	5	ND	6	146	.2	2	3	3	2.92	.037	14	29	.18	154	.01	4	.33	.01	.15	1
90R50 70-75	4	3	9	13	.1	11	4	415	1.26	12	5	ND	3	155	.2	2	2	2	3.09	.030	8	47	.16	108	.01	2	.29	.02	.14	1
90R50 75-80	6	17	9	59	.1	18	5	449	1.71	35	5	ND	4	158	.3	2	2	5	2.98	.067	9	44	.30	108	.01	2	.44	.01	.15	1
90R50 80-85	6	37	15	79	1.3	30	7	329	2.22	57	5	ND	5	182	.7	2	2	6	3.27	.110	5	32	.44	87	.01	2	.50	.01	.11	1
90R50 85-90	45	34	36	238	1.4	98	10	421	2.99	73	5	ND	5	365	2.6	5	2	14	6.52	.117	4	32	.52	52	.01	5	.43	.01	.06	1
90R50 90-95	10	42	14	157	.7	54	10	425	2.23	95	5	ND	5	273	1.7	2	2	18	5.44	.085	7	34	1.00	76	.01	2	.80	.01	.07	1
90R50 95-100	10	24	17	211	.5	28	7	414	1.80	108	5	ND	6	298	2.5	2	2	12	6.37	.067	8	43	.75	84	.01	2	.68	.01	.08	1
90R50 100-105	7	13	19	131	.4	17	7	336	2.20	49	5	ND	8	153	1.2	2	2	10	2.95	.039	19	34	1.14	133	.01	2	1.15	.01	.08	1
90R50 105-110	4	8	16	89	.3	8	7	245	2.26	18	5	ND	6	100	.5	3	2	12	2.07	.034	17	30	1.16	102	.01	2	1.28	.02	.06	1
90R50 110-115	3	7	12	75	.1	7	5	252	2.10	13	5	ND	5	122	.4	2	2	10	3.65	.037	12	28	1.06	116	.01	2	1.21	.01	.06	1
STANDARD C	19	62	38	132	6.9	70	32	1073	4.05	39	18	7	40	52	18.4	14	19	56	.48	.092	38	57	.86	185	.10	33	1.98	.06	.13	11

BACON DONALDSON
& ASSOCIATES LTD.

12271 Horseshoe Way
Richmond, B.C.
V7A 4Z1
Telephone: (604) 277-2322
Telefax: (604) 274 7235

TELECOPIER COVER SHEET

MESSAGE NO: 8488	PAGE: 1 of 7	FILE NO: M1-007	DATE: Feb 5, 1991

TO: Hughes Lang Group

ATTENTION: Scott Tomlinson

FAX NUMBER: 687-3932

FROM: Lawrence Tamelin

Attached are the results & the gravity concentration tests of Drill hole 90R23.
If you have any questions please call.

Regards,

Lawrence Tamelin


If you do not receive all the pages, or if they are not legible, please phone.

BACON, DONALDSON & ASSOCIATES LTD.

PROJECT No. M1-003 DATE Feb 5, 1991

Subject Assays of hole 90R23

The four samples of hole 90R23 have been processed and assayed according to the following flowsheet.



The total sample assays are presented in the following table. Detailed balances of each sample are presented on the attached sheets.

CALCULATED SAMPLE ASSAYS

TEST NO.	HOLE NO.	DEPTH	CALCULATED ASSAYS			
			Au		Ag	
			g/tonne	oz/ton	g/tonne	oz/ton
A1	90R23	20-25	0.949	0.028	0.044	0.001
A2	90R23	25-30	5.693	0.166	2.463	0.072
A3	90R23	30-35	6.806	0.199	2.217	0.065
A4	90R23	35-40	13.236	0.386	2.406	0.070

BACON, DONALDSON & ASSOCIATES LTD.

PROJECT No. ____ DATE ____

Subject ____

Slimes and Jig tails were assayed in duplicate. Slight discrepancies in the slimes assays were noted and larger discrepancies in the jig tails assays of tests A1 and A2 were noted. The jig tails of A1 and A2 were reassayed in duplicate. The averages of the assays were used to calculate the total sample (head) assays.

The reassayed jig tails still showed discrepancies and are therefore presented in the following table.

JIG TAILS Au ASSAYS

TEST NO.	HOLE NO.	DEPTH	WEIGHT OF ASSAY CUT (g)	Au oz/ton	Average Au oz/ton	Average Au g/tonne
A1	90R23	20-25	40	0.002	0.024	0.823
	"	"	"	0.071		
	"	"	"	0.005		
	"	"	"	0.019		
A2	90R23	25-30	40	0.117	0.092	3.154
	"	"	"	0.063		
	"	"	"	0.064		
	"	"	"	0.124		

These discrepancies should be noted since the jig tails account for 79.3% and 76.9% of the total sample weight for A1 and A2 respectively. The assay variations will affect the total sample assay.

There are several possible explanations for these discrepancies. If you wish to discuss them please feel free to give me a call.

Sincerely,
Lawrence Palmer

TEST NUMBER: A1 (HOLE #UJ) R 23 (20-25)

PRODUCT	WEIGHT GMS	WEIGHT %	ASSAYS Au g/tonne	ASSAYS Ag g/tonne	% DIST Au	% DIST Ag
Jig Conc	16.1	0.17	117.704	25.680	21.16	100.00
Jig Tail	7073.0	79.27	0.823	<0.343	69.12	
Slimes (-325#)	1835.0	20.56	0.446	<0.343	9.71	
CALC HEAD	8923.1	100.0	0.944	0.044	100.00	100.00

4/

TEST NUMBER: A2 HOLE #80 R 23 (25-30)

PRODUCT	WEIGHT gms	WEIGHT %	ASSAYS Au g/tonne	ASSAYS Ag g/tonne	% DIST Au	% DIST Ag
Jig Conc	24.1	0.26	951.917	238.781	43.78	25.06
Jig Tail	7087.0	76.90	3.154	1.749	42.81	54.59
Slimes (-325#)	2105.0	22.84	3.994	2.184	18.02	20.35
CALC HEAD	9216.1	100.0	5.693	2.463	100.00	100.00

TEST NUMBER: A3 HOLE #90 R 23 (30-35)

PRODUCT	WEIGHT GMS	WEIGHT %	ASSAYS Au g/tonne	ASSAYS Ag g/tonne	% DIST Au	% DIST Ag
Jig Conc	43.7	0.32	434.541	108.424	20.47	15.39
Jig Tail	10781.0	78.78	4.560	1.371	52.79	48.78
Slimes (-325#)	2847.0	20.90	8.709	3.606	26.74	35.83
CALC HEAD	13621.7	100.0	8.806	2.217	100.00	100.00

TEST NUMBER: A4 HOLE #80 @ 23 (35-40)

PRODUCT	WEIGHT GMS	WEIGHT %	ASSAYS Au g/tonne	ASSAYS Ag g/tonne	% DIST Au	% DIST Ag
Jig Conc	29.9	0.36	3377.861	597.708	90.89	88.49
Jig Tail	8528.0	77.71	1.097	0.240	6.44	7.75
Slimes (-325#)	1643.0	21.94	1.611	0.411	2.67	3.75
CALC HEAD	8400.9	100.0	13.236	2.406	100.00	100.00

ACCURASSAY LABORATORIES LTD.

P.O. BOX 426
KIRKLAND LAKE, ONTARIO, CANADA P2N 3J1
TEL.: (705) 567-3361

President: Dr. GEORGE DUNCAN, M.Sc., Ph. D., C. Chem (Ont.), C. Chem (U.K.), M.C.I.C., M.R.S.C., A.R.C.S.T.

Certificate of Analysis

Scott Tomlinson
Hughes-Lang Group
1000-1177 W. Hastings St.
VANCOUVER, BC
V6E 2K3

36604


Date: January 17 19 91

WORK ORDER: T910008
PROJECT:

SAMPLE NUMBERS ACCURASSAY	CUSTOMER	WEIGHT PULP (g)	GOLD Oz/T	RESIDUE Oz/T	TOTAL ASSAY Oz/T	PERCENT RECOVERY
537953	90R18-100-105	1881.0 g	0.136	0.0079	0.144	94
537954	90R18-105-110	1684.0 g	0.227	0.0324	0.259	87
537955	90R18-110-115	3299.0 g	0.028	0.0026	0.031	92
537956	90R18-115-120	3482.0 g	0.210	0.0100	0.220	95
537957	90R18-120-125	1551.0 g	0.293	0.0189	0.311	94
537958	90R23-10-15	1834.0 g	0.029	0.0022	0.031	93
537959	90R23-15-20	940.0 g	0.015	0.0011	0.016	93
537960	90R23-20-25	1592.0 g	0.015	0.0006	0.016	96
537961	90R23-25-30	2164.0 g	0.269	0.0207	0.289	93
537962	90R23-30-35	1729.0 g	0.281	0.0181	0.300	94
537963	90R23-35-40	925.0 g	0.057	0.0047	0.061	92

Per:

ORIGINAL



LEGEND

qms	LIGHT TO DARK BROWN WEATHERING QUARTZ MUSCOVITE SCHIST
qmsa	LIGHT TO DARK BROWN WEATHERING ALTERED QUARTZ MUSCOVITE SCHIST
qmss	LIGHT GREEN TO BUFF BLOCKY SILICEOUS BANDED QUARTZ MUSCOVITE SCHIST, WITH FREQUENT QUARTZ VEINING AND LENTICULAR WHITE QUARTZ EYES < 3% < 4mm
qmsc	LIGHT GREEN CLAY RICH (ALTERATION ZONE) WELL FOLIATED qms
q	QUARTZ VEIN
qsm	SILVERY GREY WEATHERING SERICITE QUARTZ SCHIST
CSa	FOLIATED DARK GREY TO BLACK MUSCOVITE QUARTZ SCHIST
70°	ATTITUDE
	FAULT
	DEFINED GEOLOGICAL BOUNDARY
	INFERRED GEOLOGICAL BOUNDARY
x	ROCK CHIP SAMPLE LOCATION

NOTE: MAP BY C. MARRIOTT DWG 129

ARBOR RESOURCES INC.
LONE STAR PROPERTY
DAWSON MINING DISTRICT, Y.T.

27 PUP TRENCH MAP

BY: S.T./p.s.
DATE: MAY, 1991
FIGURE: 6

MAP# 115/0/10 Doc# 092969 (65)

APPIAN RESOURCES LTD.

ARBOR RESOURCES INC.

ARBOR RESOURCES INC.

STAKED

HISTORICAL RESERVE (NO STAKING)

STAKED

FAITH MINES LTD.

ARBOR RESOURCES INC.

FAITH MINES LTD.

FAITH MINES LTD.

BONANZA CREEK

IRISH GULCH

FRENCH GULCH

ELDORADO

LITTLE ELDORADO

GLACIER GULCH

22 GULCH

GRANGE CREEK

GAY GULCH

GOLDEN GULCH

NUGGET GULCH

SPRING GULCH

DAWSON GULCH

HOMESTAKE GULCH

JIM GULCH

NIGGER GULCH

DYKE

NAGLEY GULCH

VICTORIA GULCH

ADAIR GULCH

BASE LINE

STEWART WORKINGS

CHRISTY WORKINGS

THISTLE WORKINGS

HELENA WORKINGS

98 DOWSE TRENCH

98 GAY GULCH CUT

98 GAY GULCH HEADING

BOULDER LODE

PIONEER

PIP

ELEV. 6570

ELEV. 6480

ELEV. 6390

SCALE 1:10,000

0 100 200 300 400 500

METRES

LEGEND

- PLACER PAY STREAK
- AURIFEROUS QUARTZ VEIN
- GOLD SOIL ANOMALY ((10 PPB)
- IP RESISTIVITY LOWS
- PERCUSSION DRILL HOLE
- DIAMOND DRILL HOLE
- BUILDING
- ROAD
- RIVER
- TRENCH
- UNDERGROUND WORKINGS
- SAMPLE SITES

DWG 130

ARBOR RESOURCES INC.

LONE STAR PROPERTY

DAWSON MINING DISTRICT, Y.T.

COMPILATION MAP

MAP # 115/e/10

BY: S.T./p.a.

DATE: JUNE, 1991

Doc # 092089

(66)

FIGURE: 2

GEOPHYSICAL REPORT

ON

092969

INDUCED POLARIZATION, RESISTIVITY,

MAGNETIC, VLF-EM AND HORIZONTAL LOOP EM SURVEYS

OVER PORTIONS OF THE

LONESTAR PROPERTY

ELDORADO CREEK, DAWSON CITY

DAWSON M.D., YUKON TERRITORY

OFFICE OF THE REGIONAL MANAGER
MINERAL RIGHTS
JUL 12 1991
WHITEHORSE
YUKON TERRITORY

PROPERTY	: Center is 20.5 km S 20°E of Dawson City : 65°53' North Latitude, 139°14' West Longitude : N.T.S. 115 0/14
CLAIMS WORKED	: See Table II
SURVEY PERIOD	: July 25 - November 6, 1990
WRITTEN FOR	: ARBOR RESOURCES INC. : 1000 - 1177 West Hastings Street : Vancouver, B.C. V6E 2K3
WRITTEN BY	: David G. Mark, Geophysicist : GEOTRONICS SURVEYS LTD. : #530 - 800 West Pender Street : Vancouver, B.C., V6C 2V6
DATE	: March, 1991

Accompanies Report # 092969

Preliminary

This Report Was Never Approved for Assessment Credit.

GEOTRONICS SURVEYS LTD.
Engineering & Mining Geophysicists
VANCOUVER, CANADA

TABLE OF CONTENTS

INTRODUCTION AND GENERAL REMARKS	1
PROPERTY AND OWNERSHIP	3
LOCATION AND ACCESS	4
PHYSIOGRAPHY	4
PREVIOUS WORK	5
GEOLOGY	8
1) Property	8
2) Mineralization	10
3) Claims Worked	11
INDUCED POLARIZATION AND RESISTIVITY SURVEYS	12
1) Instrumentation	12
2) Theory	12
3) Survey Procedure	14
4) Compilation of Data	17
MAGNETIC SURVEY	18
1) Instrumentation	18
2) Theory	18
3) Survey Procedure	18
4) Compilation of Data	18
MAXMIN ELECTROMAGNETIC SURVEY	20
1) Instrumentation	20
2) Theory	20
3) Survey Procedure	21
4) Compilation of Data	21

092969

APR 18 1991

TABLE OF CONTENTS (cont'd)

VLF-EM SURVEY	23
1) Instrumentation	23
2) Theory	23
3) Survey Procedure	24
4) Compilation of Data	24
DISCUSSION OF RESULTS	25
SELECTED BIBLIOGRAPHY	31
GEOPHYSICIST'S CERTIFICATE	33
AFFIDAVIT OF EXPENSES	34

LIST OF TABLES

TABLE I - PROPERTY CLAIMS	3
TABLE II - CLAIMS WORKED	11
TABLE III - IP AND RESISTIVITY SURVEY LINES	15
TABLE IV - MAGNETIC, HLEM, VLF-EM SURVEY LINES	19

LIST OF ILLUSTRATIONS

AT END OF REPORT

	Scale	Map #
Location Map	1: 9,175,000	1
Claim Map	1: 50,000	2
IP Grid Location Map	1: 25,000	3

IN BACK POCKET

IP Grid Survey Plan	1: 5,000	4
Lone Star Grid		
1) Survey Data Plans		
Apparent Chargeability, n=2	1: 2,500	5
Apparent Chargeability, n=4	1: 2,500	6
Apparent Chargeability, n=6	1: 2,500	7
Apparent Resistivity, n=2	1: 2,500	8
Apparent Resistivity, n=4	1: 2,500	9
Apparent Resistivity, n=6	1: 2,500	10
2) Pseudosections		
Line 0 + 50N	1: 2,500	11
Line 0 + 00 (Bldr 333)	1: 2,500	12
Line 1 + 10 S	1: 2,500	13

	Scale	Map #
7 - Pup Grid		
1) Survey Data Plans		
Apparent Chargeability, n=2	1: 2,500	14
Apparent Chargeability, n=4	1: 2,500	15
Apparent Chargeability, n=6	1: 2,500	16
Apparent Resistivity, n=2	1: 2,500	17
Apparent Resistivity, n=4	1: 2,500	18
Apparent Resistivity, n=6	1: 2,500	19
2) Pseudosections		
Line 0 + 00 (crossline)	1: 2,500	20
Line 3 + 80E	1: 2,500	21
Line 4 + 80E	1: 2,500	22
Line 5 + 80E	1: 2,500	23
McKay - O'Neil Grid		
1) Survey Data Plans		
Apparent Chargeability, n=2	1: 2,500	24
Apparent Chargeability, n=4	1: 2,500	25
Apparent Chargeability, n=6	1: 2,500	26
Apparent Resistivity, n=2	1: 2,500	27
Apparent Resistivity, n=4	1: 2,500	28
Apparent Resistivity, n=6	1: 2,500	29
2) Pseudosections		
Line 1 + 00 S (crossline)	1: 2,500	30
Line 1 + 00 W	1: 2,500	31
Line 0 + 00	1: 2,500	32
Line 1 + 00 E	1: 2,500	33
Line 2 + 00 E	1: 2,500	34

	Scale	Map #
Irish Gulch Grid		
1) Survey Data Plans		
Apparent Chargeability, n=2	1: 2,500	35
Apparent Chargeability, n=4	1: 2,500	36
Apparent Chargeability, n=6	1: 2,500	37
Apparent Resistivity, n=2	1: 2,500	38
Apparent Resistivity, n=4	1: 2,500	39
Apparent Resistivity, n=6	1: 2,500	40
2) Pseudosections		
Line 12 + 30 S	1: 2,500	41
Line 13 + 30 S	1: 2,500	42
Line 14 + 30 S	1: 2,500	43
French Gulch Grid		
1) Survey Data Plans		
Apparent Chargeability, n=2	1: 5,000	44
Apparent Chargeability, n=4	1: 5,000	45
Apparent Chargeability, n=6	1: 5,000	46
Apparent Resistivity, n=2	1: 2,500	47
Apparent Resistivity, n=4	1: 5,000	48
Apparent Resistivity, n=6	1: 2,500	49
2) Pseudosections		
Line 3 + 60 E (crossline)	1: 2,500	50
Line 2 + 55 S	1: 2,500	51
Line 4 + 25 S	1: 2,500	52
Line 5 + 40 S	1: 2,500	53
Line 6 + 80 S	1: 2,500	54
Line 7 + 35 S	1: 2,500	55
Line 8 + 55 S	1: 2,500	56

	Scale	Map #
Oro Grande Grid and Gay Gulch Grid		
1) Survey Data Plans		
Apparent Chargeability, n=2	1: 2,500	57
Apparent Chargeability, n=4	1: 2,500	58
Apparent Chargeability, n=6	1: 2,500	59
Apparent Resistivity, n=2	1: 2,500	60
Apparent Resistivity, n=4	1: 2,500	61
Apparent Resistivity, n=6	1: 2,500	62
2) Pseudosections - Oro Grande Grid		
Line 49 + 70 S	1: 2,500	63
Line 52 + 50 S	1: 5,000	64
Line 54 + 50 S	1: 2,500	65
Line 56 + 40 S	1: 2,500	66
3) Pseudosections - Gay Gulch Grid		
Line 2 + 20 N	1: 2,500	67
Line 1 + 20 N	1: 2,500	68
Line 0 + 00 (west)	1: 5,000	69(a)
Line 0 + 00 (east)	1: 5,000	69(b)
Line 1 + 01 S	1: 2,500	70
Line 0 + 04N - Detail (n=5.0 m)	1: 500	71
Line 0 + 10N - Detail (n=7.5 m)	1: 500	72
Eldorado Creek		
1) Pseudosections		
Line Eldo-444	1: 2,500	73

GEOPHYSICAL REPORT

ON

INDUCED POLARIZATION, RESISTIVITY

MAGNETIC, VLF-EM AND HORIZONTAL LOOP EM SURVEYS

OVER PORTIONS OF THE

LONESTAR PROPERTY

ELDORADO CREEK, DAWSON CITY

DAWSON M.D., YUKON TERRITORY

INTRODUCTION AND GENERAL REMARKS

This report discusses the instrumentation, theory, field procedure and results of induced polarization (IP), resistivity, magnetic,very low frequency electromagnetic (VLF-EM) and horizontal loop electromagnetic (HLEM) surveys carried out over portions of the Lone Star property. The center of the property (Boulder Lode mine site) is located 20.5 km S20°E of Dawson City and occurs on Eldorado Creek, within the west central part of the Yukon.

The field work was completed from July 25 to November 6, 1990 under the supervision of David G. Mark, geophysicist, and under the field supervision of Alain Charest, geophysical technician, who also formed part of the field crew. A second geophysical technician as well as two helpers completed the crew of four.
The work was carried out over 7 grids, namely, (1) Lone Star, (2) 7-Pup, (3) McKay-

O'Neil, (4) Irish Gulch, (5) French Gulch, (6) Oro Grande, and (7) Gay Gulch, as well as a 7-km long line along a stretch of Eldorado Creek (see map #3).

Almost all of the work consisted of IP and resistivity surveys. In general, the main purpose was to locate sulphide mineralized zones since the only significant gold discovered in place was on the Lone Star part of the property and occurred with, or was associated with, sulphides. From previous work (Walcott), it was known the mineralization was reflected as chargeability (IP) highs of moderate amplitude. The correlating resistivity response was background or broad lows of low amplitude. This response contrasted sharply with that over graphitic zones which are reflected by strong IP highs correlating with strong resistivity lows.

A secondary purpose of the resistivity survey was to assist in the mapping of the bedrock geology. It was expected that faults and shear zones would show up as lineal-shaped resistivity lows; intrusive dykes as lineal-shaped resistivity highs (though the feldspar porphyry dyke seemed to be reflected as a resistivity low); alteration zones as resistivity lows; and siliceous zones as resistivity highs.

Magnetic, VLF-EM, and HLEM surveys for orientation purposes were also carried out over some lines on the McKay-O'Neil Grid, the 7-Pup Grid, and the Lone Star Grid. In addition, magnetic readings were taken on the French Gulch and Gay Gulch Grids. The purpose of the magnetic surveys was to locate intrusive dykes, especially the diabase dykes which respond as reverse polarity magnetic lows. The purpose of the VLF-EM and HLEM surveys was to locate sulphide mineralization containing gold values with the secondary purpose of the VLF-EM to map structure.

The Geotronics crew was located onto the various grids by Art Troup, geological engineer and exploration manager, or by Scott Tomlinson, geologist, and project manager.

Much of the following information up to and including the section on geology is taken from or directly quoted from P.B. Grunenberg's report of February, 1989. The writer has condensed the property description (physiography, geology, etc.) and thus a more thorough description is given in his report.

PROPERTY AND OWNERSHIP

The property consists of 284 located mineral claims and 13 Crown-Granted claims, all contiguous. They are shown on map #2 and are described below in Table I:

TABLE I - PROPERTY CLAIMS

CLAIM NAME	GRANT NO.	ANNIVERSARY DATE
DE 1-14	YA55250-263 (14)	DECEMBER 31
AC 1-12	YA64270-281 (12)	DECEMBER 31
AC 13-35	YA65627-650 (23)	DECEMBER 31
RJ 1-32	YA64216-247 (32)	DECEMBER 31
RJ 39-60	YA65595-616 (22)	DECEMBER 31
RJ 62-63	YA65618-619 (2)	DECEMBER 31
RJ 65-70	YA65621-626 (6)	DECEMBER 31
RON 1-40	YA10300-39 (40)	DECEMBER 31
CIM 1-4	YA64519-522 (4)	DECEMBER 31
REX 1-51	YA84183-233 (51)	DECEMBER 31
DN 1-2	YA32783-784 (2)	DECEMBER 31
DN 3-9	YA47890-896 (7)	DECEMBER 31
DN 10	YA47082 (1)	DECEMBER 31
DN 11-26	YA32946-961(16)	DECEMBER 31
DN 27-31	YA47083-087 (5)	DECEMBER 31
DN 32-33	YA47604-605 (2)	DECEMBER 31
DN 1F-2F	YA47090-091 (2)	DECEMBER 31
DN F	YA47088 (1)	DECEMBER 31
ND 1-22	YA49724-745 (22)	DECEMBER 31
ND F	YA47089 (1)	DECEMBER 31
VI 1-15	YA55285-299(15)	DECEMBER 31
VI 16	YA65523 (1)	DECEMBER 31
VI 18	YA65525 (1)	DECEMBER 31
VI 43-44	YA65550-551 (2)	DECEMBER 31

CROWN GRANT CLAIMS	LOT NO.	ANNIVERSARY DATE	CROWN GRANT CLAIMS	LOT NO.	ANNIVERSARY DATE
VICTORIA	86	JULY 1	ZULU CHIEF	411	JULY 1
PORPHYRY LODE	104	JULY 1	NEW BONANZA # 2	424	JULY 1
YANKEE GIRL	105	JULY 1	SWASTIKA	533	JULY 1
ESTER EDNA	106	JULY 1	UDAS	534	JULY 1
NEW BONANZA	408	JULY 1	CATO	535	JULY 1
NIOBE FRACTION	409	JULY 1	THISTLE	536	JULY 1
LONE STAR	410	JULY 1			

The property is 100% owned by Arbor Resources Inc. of Vancouver, B.C.

LOCATION AND ACCESS

The Lone Star Mine within the center of the property is located 20.5 km (12.7 miles) S20°E (160°E) of the town of Dawson City which is the principal supply center of the northwestern Yukon. The property is located along Bonanza and Eldorado Creeks as well as on the hill between the two creeks (see map #2).

The geographical coordinates are 65°53'N latitude and 139°14'W longitude.

Dawson City can be reached by a paved road from Whitehorse, a distance of 535 km (333 miles), or by air from Whitehorse by scheduled flights of Air North (DC-3 or DC-4) and Alcan Air (smaller aircraft).

"Excellent access to the property is provided by the well-maintained, all-weather Klondike Highway which connects with the Bonanza Creek Road approximately 3 km (2 miles) east of Dawson City. The Bonanza Creek Road branches at the former site of the town of Grand Forks with roads going along both Bonanza and Eldorado Creeks. Several recently completed 'bush' roads provide good access for 4X4 truck and other off road vehicles, within much of the claim group."

PHYSIOGRAPHY

The property occurs within the Klondike region which is part of the Yukon Plateau, an upland surface that has been dissected and eroded by numerous small streams. "The valleys are flat and wide in their lower reaches, but gradually narrow toward their head waters into steep-sided gulches ending in broad, amphitheatre-shaped bowls."

"The Klondike region was not glaciated and, as a result, the deeply weathered, pre-glacial, gently rolling upland surface has been preserved. The thick covering of decomposed schist, usually intermingled with slide rock, mantles the side hills nearly everywhere. On the ridges the covering is less; the schists, often worn into fantastic shapes, occasionally project above surface or crop out along the sides of the steeper hills."

Eldorado Creek and Upper Bonanza Creek and their tributaries drain the property.

The elevation ranges from 495m (1623 ft) on Eldorado Creek near its confluence with Upper Bonanza, to 1173m (3851 ft) within the southeast corner of the property to give a relief of 650m (1623 ft).

"The climate consists of long winters with temperatures that are often intensely cold while the summers are short, but with warm days and cool nights. The precipitation is about 30cm (12 in) per year. Vegetation is mixed boreal forest and tundra. Immature and stunted stands of aspen, balsam, poplar, and birch are present in the valley bottoms and are beginning to reclaim the older mining areas. Softwood timber consisting mainly of white and black spruce are limited to slopes and ridge tops."

PREVIOUS WORK

With the Klondike discovery in 1896, and the subsequent placer staking of all the creeks in the region, it was not long before attention was paid to locating the source of the gold. Several auriferous quartz veins were discovered near the turn of the century. This eventually led to the mining of the Lone Star property between 1912 and 1914 which consisted of 8,435 tons carrying 0.148 oz/ton. From then on, exploration was carried out sporadically up until 1960.

"In 1960, the property was acquired by Klondike Lode Gold Mines Ltd. This group conducted the first systematic exploration of the area outside of the limits of the old workings. Contour-controlled bulldozer trenching was carried out on various parts of the claim group, and overburden samples from the trenches were panned and sluiced to determine gold content. Results were encouraging and six diamond drill holes totalling 238 m (781 ft) were drilled on the Eldorado Creek side of the claims in 1962. Unfortunately, the project was abandoned in 1962 due to lack of funds.

"In 1979-80, Klon Explorations Company Ltd. carried out VLF-EM and magnetometer surveys across Eldorado Creek at French Gulch. This was followed by minor diamond drilling in an attempt to locate what were believed to be auriferous structures beneath the creek. A coincident programme involving reverse circulation drilling in the creek to locate buried placer gold was conducted. This project was also hampered by lack of funds, and was terminated in 1980.

"Dawson Eldorado Gold Explorations Ltd. acquired its present land position between 1980 and 1985 and were the first to attempt to understand the complex geological, geochemical, and mineralogical relationships involved with the property. In 1980, a resistivity survey was conducted over the Lone Star workings, with limited success (permafrost being the main problem). During 1981, much of the central portion of the claim group was soil sampled at 120 m stations using conventional sampling techniques and several bulldozer trenches were sampled. In 1984, the soil sampling grids were extended and additional bulldozer trenches were dug. In 1985, six rotary drill holes, totalling 168 m, were drilled in the vicinity of anomalous zones as outlined in the 1960 and 1981-84 programmes.

"Exploration continued by Mark Management Ltd. for Arbor Resources and an extensive programme was completed during 1986 and early 1987. This programme included 86 km of magnetometer, 3 km of VLF-EM16, and 31.3 km of I.P. surveys. Reconnaissance work included 250 soil and 42 rock chip samples. Targets outlined by this ground work were later drilled, and a total of 8,589 feet of diamond and 9,210 feet of rotary drilling were completed. Diamond drill holes intersected strataform disseminated sulphide horizons which contained gold values up to 0.357 oz/T. These were commonly bounded by wider zones of lower grade gold content.

"A low level helicopter supported airborne geophysical survey was carried out by Aerodat Limited of Mississauga, Ontario, during December 1986 and January 1987. Ground follow-up included 10 kilometres of VLF-EM16 survey and 18 kilometres of I.P. survey. An extensive grid was established over the ridge between Upper Bonanza and Eldorado Creeks, with 1599 soil samples and 29 rock samples being collected. Targets outlined by these surveys were eventually trenched and drilled, with 23 bulldozer trenches, 5,546 feet of diamond drilling, and 13,330 feet of rotary drilling being completed. Many gold bearing intersections were obtained, with two main zones of interest outlined, near Gay Gulch and near the old Lone Star mine workings. Geological interpretation indicates that these two zones are stratigraphically related through anticlinal folding, with the fold axis along the ridge between Eldorado and Upper Bonanza Creek.

"During the 1988 exploration season, the work included:

(1) Geophysical work consisting of 18 km of VLF-EM16 and 9 km of Induced Polarization surveys. The latter was contracted to P.E. Walcott and Associates Ltd. and is discussed in a separate report (See Walcott reference).

(2) 1,437 horizon soil samples taken from 63 kilometres of hip chain and compass flagged lines established over 4 grids on the claims.

(3) 61 rock chip samples taken during geological mapping and prospecting on the claims.

(4) 39 bulldozer trenches with a further 1,352 rock chip samples."

The 1988 work was thoroughly reported by P. Grunenberg. The purpose of the work was to extend known zones of mineralization, especially that of the Lone Star workings, as well as to locate previously unknown zones. This included testing of airborne anomalies such as magnetic laws. Some of the results are as follows:

(1) Soil sampling extended the Lone Star gold anomaly eastward and the IP survey located chargeable zones upslope from anomalous soil results. Subsequent trenching of the IP anomalies revealed pyrite and galena-bearing schist, but without gold values.

(2) A number of quartz veins containing "ore-grade" amount of gold were located in other areas of the property, but these were usually narrow and discontinuous.

During 1991, the exploration consisted of (besides the geophysics discussed within this report) prospecting, soil sampling, rock chip sampling, much "cat" trenching, and rotary drilling. The work is discussed in a report currently being written by Scott Tomlinson.

GEOLOGY

The following is quoted directly from Grunenberg's report, but for "up-to-date" geology, the reader is referred to Tomlinson's report.

(1) Property

"The geology of the property, as currently understood, was chiefly determined from the examination of trenches, road cuts, and diamond-drill core, and the interpretation of geophysical information, as there are few outcrops. The property is underlain almost entirely by facies of the Klondike Schist. Lithological and structural continuity has been disrupted by folding and faulting. Age relationships of the various lithologies are largely unknown since tops cannot be determined and contacts are either gradational, interlayered, or faulted.

"Rocks on the property are comprised of well-foliated, rust-yellow weathering, light greyish-green, undifferentiated chloritic schists, muscovite schists, and quartz-sericite schists. These schists are interbedded with narrow lenses of calcareous graphitic schist, particularly along Eldorado Creek, and with fine-grained, massive, tan weathering, grey-brown micaceous quartzites. Graphitic schists are traceable as marker horizons in stratigraphy.

"The micaceous schists and quartzites commonly contain up to 15% small, blue quartz eyes. The quartz eyes may represent crystals, tuff fragments, or porphyroblasts.

"To the west of the claim group the Klondike Schists are in contact with a blocky weathering, granitic textured, biotite-quartz-feldspar Orthogneiss. Thin section studies of these rocks indicate that they were originally medium-to coarse-grained plutonic rocks of granodiorite to quartz diorite composition, and may represent the original magma for those tuffs now comprising the Klondike Series.

"All formations are interrupted by a number of north to north-west trending, magnetite-bearing, quartz-feldspar porphyry (rhyolite) and diabase dykes which may be up to 60 m wide. Diabase dykes often contain serpentine alteration near surface; previously these had been mis-interpreted as thin ultramafic bodies. The dykes cut most structural trends but are offset by more recent northwest striking faults. The dykes may occupy old fault zones, and in places apparent offsets in strata of up to 300 metres is recorded. No extensive metamorphic halos are reported to be associated with these dykes.

"Numerous quartz and quartz-carbonate lenses and pods dot the hillsides on the property. These are mostly stretched along the primary foliation plane within the schists, and were likely metamorphically produced. Thin section studies (appendix 2) indicate that the quartz developed under stress under moderately deep-seated, possibly mesothermal conditions. The majority of these lenses have a mappable strike length of under 100 metres, and widths of 30 to 100 centimetres. Quartz veins often contain galena, and are thought to be of a higher temperature mesothermal origin. The margins of gold has been found within the oxidized boxworks of pyrite (trench samples) at the quartz-country rock contact.

"The local geology is complicated by a series of northwest trending antiforms and synforms. Interpretation of these features indicates that the schists are folded into a broad northwest trending anticline, with the hinge roughly following the ridge between Upper Bonanza and Eldorado Creeks. The repetition of graphitic schist horizons along Eldorado Creek to those found near the old Lone Star mine and Victoria Gulch, likely trace the opposing limbs of such an anticline. All stratigraphy in between would be subject to a similar kind of repetition. This is important if ore horizons prove to be strataform.

"Foliation is generally parallel to regional stratigraphic trends, except along Eldorado Creek, where strikes are westerly with dips to the south.

"On **figure 4** the target horizon for gold within the Klondike schists is outlined as a unit of quartz-muscovite schist which contains some combination of pyrite, arsenopyrite, mariposite, or grey coloured carbonate blebs (diamond drill core observations). The gold bearing units intersected near the old Lone Star mine may be genetically related to those intersected near Gay Gulch. The source then represents a particular time horizon of volcanogenic deposition which resulted in the formation of some or all of the above minerals, as well as gold."

(2) Mineralization

"The earliest reported study on the lode deposits was by Cairnes (1911) in which he briefly described the development work on some of the more promising quartz veins in the district. One property (Boulder Lode), near the head waters of Victoria Gulch, a tributary of Bonanza Creek, was considered the source of the gold in the gulch, and along part of Bonanza Creek. The principal vein, with its associated surrounding mineralized zone, varied in thickness from 1 to 3 m (3 to 10 ft) and was traceable along strike for 120 m (400 ft) with a possible extension of another 200 m (600 ft). Cairnes failed to indicate the grade of this deposit, but he suggested that the gold content was in excess of 0.25 ounces per ton. Reserves in this vein indicated approximately 1500 tons per metre containing about 400 ounces per metre. McConnell (1905) reported that ten 500 foot wide placer claims along Victoria Gulch and Bonanza Creek produced over 200,000 ounces: the inference is that all the gold recovered in the placers could not have come solely from this vein."

"Diamond drilling in 1986 of geochemical and geophysical targets near the Boulder Lode intercepted several sulphide rich horizons within quartz-muscovite and chloritic muscovite schists. Fire assays of samples from these zones detected gold values up to 0.357 oz/t. None of these gold bearing horizons were related to any quartz veining as studied by Cairnes. Rotary drilling during January and early February 1987 intersected several gold bearing zones between Oro Grande and Gay Gulches. Fire assays of samples from these zones detected gold values up to 0.230 oz/t at depths ranging from 6 m to 145 m (20 to 475 ft)."

"Continued trenching and drilling during 1987 and 1988 has further confirmed and expanded the gold bearing horizons as outlined in previous drilling; near the old Lone Star workings, and between Oro Grande and Gay Gulches."

CLAIMS WORKED:

The following table gives the names of the claims on which geophysics was carried out on.

TABLE II - CLAIMS WORKED

CLAIM NAME	GRANT NO.	ANNIVERSARY DATE
CIM 1-2	YA64519-520	DECEMBER 31
DE 9	YA55259	DECEMBER 31
DN 1-2	YA32783-784	DECEMBER 31
DN 5-7	YA47892-894	DECEMBER 31
DN 13-18	YA32948-953	DECEMBER 31
DN 20	YA32955	DECEMBER 31
DN 27, 29	YA47083, '85	DECEMBER 31
DN 32-33	YA47604-605	DECEMBER 31
DN F, 2F	YA47088, '90	DECEMBER 31
ND 4, 6, 8, 9	YA49727, '29, '31, '32	DECEMBER 31
ND F	YA47089	DECEMBER 31
RJ 5	YA64220	DECEMBER 31
RJ 7	YA64222	DECEMBER 31
RJ 9	YA64224	DECEMBER 31
RJ 65	YA65621	DECEMBER 31
RON 2-15	YA10301-314	DECEMBER 31
RON 17-20	YA10316-319	DECEMBER 31
RON 33	YA10332	DECEMBER 31
RON 35-40	YA10334-339	DECEMBER 31

CROWN GRANT CLAIMS	LOT NO.	ANNIVERSARY DATE
VICTORIA	86	JULY 1
PORPHYRY LODE	104	JULY 1
ESTER EDNA	106	JULY 1
NEW BONANZA	408	JULY 1
NIOBE FRACTION	409	JULY 1
LONE STAR	410	JULY 1
NEW BONANZA	424	JULY 1

INDUCED POLARIZATION AND RESISTIVITY SURVEYS

(1) Instrumentation

The transmitter used for the induced polarization and resistivity surveys was a Mark IV, 7.5 kw model, manufactured by Huntec ('70) Limited of Scarborough, Ontario. It is powered by a Mark IV 7.5 kw engine driven alternator. For difficult areas, the transmitter used was a Model IPT-1, manufactured by Phoenix Geophysics Ltd. of Markham, Ontario. It was powered by a 2.5 kw motor generator, Model MG-2, also manufactured by Phoenix.


The receiver used was a model Mark IV, manufactured by Huntec ('70) Limited. This has software controlled functions, programmable through the front panel. It features automatic calibration, gain setting, SP cancellation, fault diagnosis, and filter tuning. The Mark IV system is capable of time domain, frequency domain, and complex resistivity measurements.

(2) Theory

When a voltage is applied to the ground, electrical current flows, mainly in the electrolyte-filled capillaries within the rock. If the capillaries also contain certain mineral particles that transport current by electrons (most sulphides, some oxides and graphite), then the ionic charges build up at the particle-electrolyte interface, positive ones where the current enters the particle and negative ones where it leaves. This accumulation of charge creates a voltage that tends to oppose the current flow across the interface. When the current is switched off, the created voltage slowly decreases as the accumulated ions diffuse back into the electrolyte. This type of induced polarization phenomena is known as electrode polarization.

A similar effect occurs if clay particles are present in the conducting medium. Charged clay particles attract oppositely-charged ions from the surrounding electrolyte; when the current stops, the ions slowly diffuse back to their equilibrium state. This process is known as membrane polarization and gives rise to chargeable bodies.
Most IP surveys are carried out by taking measurements in the "time-domain" or the "frequency-domain".

Time-domain measurements involve sampling the waveform at intervals after the current is switched off, to derive a dimensionless parameter, the chargeability, "M", which is a measure of the strength of the induced polarization effect. Measurements in the frequency-domain are based upon the fact that the resistance produced at the electrolyte-charged particle interface decreases with the increasing frequency. The difference between the apparent resistivity readings at high and low frequency is expressed as the percentage frequency effect, "PFE".



The quantity apparent resistivity, ρ_a, computed from electrical survey results in only the true earth resistivity in a homogenous sub-surface. When vertical (and lateral) variations in electrical properties occur, as they always will in the real world, the apparent resistivity will be influenced by the various layers, depending on their depth relative to the electrode spacing. A single reading cannot therefore be attributed to a particular depth.

The ability of the ground to transmit electricity is, in the absence of metallic-type conductors, almost completely depending on the volume, nature and content of the pore space. Empirical relationships can be derived linking the formation resistivity to the pore water resistivity, as a function of porosity. Such a formula is Archie's Law, which states (assuming complete saturation) in clean formations:

$$\frac{R_o}{R_w} = 0^{-2}$$

Where: R_o is formation resistivity, R_w is pore water resistivity, O is porosity


(3) Survey Procedure

All lines were cut out and the stations marked thereon. The line cutting was at first carried out by Geotronics Surveys, and later by a separate contractor hired by Arbor.

The IP and resistivity measurements were taken in the time-domain mode using an 8-second square wave charge cycle (2-seconds positive charge, 2-seconds off, 2-seconds negative charge, 2-seconds off). The delay time used after the charge shuts off was 200 milliseconds and the integration time used was 1,500 milli-seconds divided into 10 windows.

The array chosen was the dipole-dipole shown as follows:

DIPOLE-DIPOLE ARRAY



The dipole lengths were chosen to be 30 metres for all survey lines, except for two detail lines on Gay Gulch. For one line, the dipole length was 5 m, and for the other, 7.5 m. The lines were usually read to eight separations, otherwise they were read to ten, especially for purposes of orientation. Eight separations give a theoretical depth penetration of 140 m, and 10 separations, 160 m.

The dipole-dipole array was chosen because of its symmetry resulting in a greater reliability in interpretation. Furthermore, narrow, vein-like targets can be missed by non-symmetrical arrays such as the pole-dipole array.

Stainless steel stakes were used for current electrodes and metallic copper in a copper sulphate solution, in non-polarizing, unglazed, porcelain pots were used for the potential electrodes. When the weather became colder in the fall, stainless steel stakes were also used for the potential electrodes.

Readings were taken over 33 different lines as shown on the survey plan (maps #3 and #4) and 33 different pseudosections were plotted, to give a total survey length of 35.9 km. The following table shows the lines done, the number of separations for each line, and the length of each line.

TABLE III - IP AND RESISTIVITY SURVEY LINES

LINE NO.	STATIONS	# OF SEPARATIONS	LENGTH
(1) Lone Star Grid			
Line 0+50N	630W to 240E	10	0.87 km
Line 0+00	750W to 540E	10	1.29
Line 1+10S	450W to 210E	10	0.66
			2.82
(2) 7-Pup Grid			
Line 0+00 (crossline)	000E to 750E	10	0.75
Line 3+80E	440S to 400N	8	0.84
Line 4+80E	240S to 390N	10	0.63
Line 5+80E	230S to 400N	8	0.63
			2.85
(3) McKay-O'Neil Grid			
Line 1+00S (crossline)	460W to 350E	10	0.81
Line 1+00W	660N to 300S	8	0.96
Line 0+00	660N to 270S	8	0.93
Line 1+00E	460N to 260S	10	0.72
Line 2+00E	660N to 360S	8	1.02
			4.44
(4) Irish Gulch Grid			
Line 12+30S	300W to 390E	8	0.69
Line 13+30S	300W to 390E	8	0.69
Line 14+30S	300W to 390E	8	0.69
			2.07

LINE NO.	STATIONS	# OF SEPARATIONS	LENGTH
(5) French Gulch Grid			
Line 3+60E (crossline)	000 to 900S	8	0.90 km
Line 2+55S	000 to 900E	8	0.90
Line 4+25S	060W to 900E	8	0.96
Line 5+40S	090W to 1110E	8	1.20
Line 6+80S	000 to 1200E	8	1.20
Line 7+55S	000 to 1020E	8	1.02
Line 8+55S	000 to 1110E	8	1.11
			7.29
(6) Oro Grande Grid			
Line 49+70S	300W to 390E	8	0.69
Line 52+50S	300W to 1980E	8	2.28
Line 54+50S	300W to 390E	8	0.69
Line 56+40S	300W to 390E	8	0.69
			4.35
(7) Gay Gulch Grid			
Line 2+20N	150W to 420E	7	0.57
Line 1+20N	120W to 510E	8	0.63
Line 0+00	000E to 3210E	7,8	3.21
Line 1+00S	000E to 510E	8	0.51
Line 0+04N (detail-n=5 m)	1225E to 1380E	10	0.155
Line 0+10N (detail-n=7.5 m)	1450E to 1675E	10	0.225
			5.30
(8) Eldorado Creek			
Line ELDO	000 to 6780S	6	6.78
			35.90

(4) COMPILATION OF DATA

All the data were reduced by a computer software program developed by Geosoft Inc. of Toronto, Ontario. Parts of this program have been modified by Geotronics for its own applications. The computerized data reduction included the resistivity calculations, pseudosection plotting, survey plan plotting and contouring.

The chargeability (IP) values are read directly from the instrument and no data processing is therefore required prior to plotting. The resistivity values are derived from current and voltage readings taken in the field. These values are combined with the geometrical factor appropriate for the dipole-dipole array, to compute the apparent resistivity.

All the data has been plotted in pseudosection form below the actual topographic profile at a scale of 1: 2,500 (1: 500 for the two detail lines). The map numbers are shown in the Table of Contents. Each value is plotted at a point formed from the intersection of a line drawn from the mid-point of each of the two dipoles. The result of this method of plotting is the farther the dipoles are separated, the deeper is the reading. The resistivity pseudosection is plotted on the upper part of the map for each of the lines, and the chargeability pseudosection is plotted on the lower part. For each of the seven grids (Oro Grande Grid and Gay Gulch Grid combined as one plan) six survey plans were drawn at a scale of 1: 2,500. These consisted of apparent chargeability at three different separations (n=2, 4, and 6) and apparent resistivity at the same separations. These plan maps were produced by taking the measured values from their exact subsurface locations, and vertically projecting them to the ground surface. The purpose was to determine anomalous trends and thus mineralogical and geological trends, especially quartz veins which may contain mineralization. All pseudosections and plans were contoured at an interval of 3 milliseconds for the chargeability results, and at an interval of logarithmic to the base 10 for the resistivity results.

MAGNETIC SURVEY

(1) Instrumentation

The magnetic survey was carried out with a model MP-2 proton precession magnetometer, manufactured by Scintrex Limited of Concord, Ontario. This instrument reads out directly in gammas to an accuracy of $\pm$ 1 gamma, over a range of 20,000 - 100,000 gammas. The operating temperature range is -35^0 to +50^0 C, and its gradient tolerance is up to 5,000 gammas per meter.

(2) Theory

Only two commonly occurring minerals are strongly magnetic, magnetite and pyrrhotite. Magnetic surveys are therefore used to detect the presence of these minerals in varying concentrations. Therefore, if magnetite or pyrrhotite occurs with economic mineralization, magnetic surveys are used to locate this type of mineralization. Magnetic surveys are also useful as a reconnaissance tool for mapping geologic lithology and structure since different rock types have different background amounts of magnetite and/or pyrrhotite.

(3) Survey Procedure

The readings were taken along lines and on grids as shown in Table IV. The readings of the earth's total magnetic field were taken at the 30 m stations along the IP/resistivity lines. The diurnal variation was monitored in the field by the closed loop method to enable the variation to be removed from the raw data prior to plotting. A total of km were surveyed.

(4) Compilation of Data

The data was plotted in profile form by the Geosoft software computer program above the IP and resistivity pseudosections.

TABLE IV
MAGNETIC, VLF-EM, AND HLEM SURVEY LINES

MAGNETIC SURVEY

GRID	LINE NO.	STATIONS	LENGTH (km)
Lonestar	0+00		
7-Pup	0+00	000 - 710E	0.71
7-Pup	4+80E	240S - 360N	0.63
McKay O'Neil	1+00E	350S - 425N	0.775
McKay O'Neil	1+00S		
French	2+55S	000E to 900E	0.9
French	4+25S	000E to 900E	0.9
French	5+40S	000E to 900E	0.9
French	6+80S	000E to 630	0.63
French	7+35S	000 to 1020	1.02
French	8+55S	000E to 1080E	1.08
Gay			

MAXMIN HLEM SURVEY

GRID	LINE NO.	STATIONS	LENGTH (km)
Lonestar	0+00	470W - 460E	0.93
7-Pup	0+00		
7-Pup	4+80E		
McKay O'Neil	1+00E	200S - 400N	0.60
McKay O'Neil	1+00S	050E to 325E	0.75

VLF-EM SURVEY

GRID	LINE NO.	STATIONS	LENGTH (km)
Lonestar	0+00	510W - 510E	1.20
7-Pup	0+00		
7-Pup	4+80E		
McKay-O'Neil	1+00E		
McKay-O'Neil	1+00S	400W - 350E	0.75

MAXMIN ELECTROMAGNETIC SURVEY

(1) Instrumentation

A MaxMin II portable 2-man electromagnetometer, manufactured by Apex Parametrics Ltd. of Toronto, Ontario was used for this survey. This instrument is designed for measuring the electromagnetic field which results from a conductive body; that is a structure which conducts electricity better than barren rock-types do. This particular instrument has the advantage of flexibility over most other EM units in that it can operate with different modes and frequencies as well as having a variety of distances between transmitter and receiver. Five frequencies can be used (222, 444, 888, 1777, and 3555 Hertz) and six different coil separations (25, 50, 100, 150, 200, and 250 meters).

(2) Theory

In all electromagnetic prospecting, a transmitter induces an alternating magnetic field (called the primary field) by having a strong alternating current move through a coil of wire. This primary field travels through any medium and if a conductive mass such as a sulphide body is present, the primary field induces a secondary alternating current in the conductor and this current in turn induces a secondary magnetic field. The receiver picks up the primary field and, if a conductor is present, the secondary field. The fields are expressed as a vector which has two components, the in-phase (or real) component and the out-of-phase (or quadrature) component. The results are expressed as the percent deviation of each component from what the values would be if no secondary field (and therefore no conductor) was present.

Since the fields lose strength proportionally with the distance they travel, a distant conductor has less of an effect than a close conductor. Also, the lower the frequency of the primary field, the further the field can travel and therefore the greater the depth penetration.

The MaxMin II EM unit can vary the strength of the primary field and so use different separations between transmitter and receiver coils, change the frequency of the primary field for varying depth penetrations, and use three different ways of

orienting the coils to duplicate the survey in three styles so that more accuracy is possible in the interpretation of the data.

The use of the MaxMin II electromagnetometer allows for better discrimination between low conductive structures such as clay beds and barren shear zones and more conductive bodies like massive sulphide mineralization. It also gives several different types of data over a given area so that statistical analysis can result in less error in the interpretation.

(3) Survey Procedure

The separation between the transmitter and receiver along the slope was measured to an accuracy of 0.3%. The separation between transmitter and receiver was 100 m with the reading interval being 30 m on the Lone Star and 7-Pup grids, and 25 m on the McKay-O'Neil grid. The lines read are shown in Table IV.

The receiver operator read and recorded the in-phase and out-of-phase responses. Calibration and phase mixing tests were also conducted three times a day and the appropriate corrections made when necessary. All five frequencies were read by the receiver operator, which were 222, 444, 888, 1777, and 3555 Hz. A total of km of electromagnetic survey were carried out.

(4) Compilation of Data

The plotting point is taken at the mid-point between the transmitter and the receiver. All in-phase and out-of-phase data for all five frequencies were profiled for each line on Maps #, respectively, at a horizontal scale of 1: 2,500 and a vertical scale of 1 cm = 5%.

Quantitative interpretation was carried out wherever anomalous readings (and thus, conductors) were encountered. The quantitative interpretation included:

(1) the location of the top of the conductor,
(2) the depth to the top of the conductor,
(3) the dip of the conductor, and

(4) the conductivity-thickness of the conductor.

Conductivity-thickness is always described as a product since a poorly conductive, thick conductor can give the same EM profile as a highly conductive, thin conductor.

The EM-mapped conductors have been divided into three classes, definite, probable, and possible conductors. Often, very little quantitative information can be interpreted from the probable and possible conductors, usually because of noise problems and/or a low response parameter.

The trace of the top of each conductor has been drawn on the base map (Map #4), at a scale of 1: 5,000. The definite conductor is drawn in solid, the probable, dashed and the possible dotted.

VLF-EM SURVEY

(1) Instrumentation

A VLF-EM receiver, Model EM-16, manufactured by Geonics Limited of Mississauga, Ontario was used for the VLF-EM survey. This instrument is designed to measure the electromagnetic component of the very low frequency field (VLF-EM), which for these surveys is transmitted at 24.8 KHz from Seattle, Washington. An exception was line 1+00S on the McKay-O'Neil grid where the Lualualei, Hawaii transmitter

was used transmitting at a frequency of 23.4 KHz.

(2) Theory

In all electromagnetic prospecting, a transmitter produces an alternating magnetic field (primary) by a strong alternating current usually through a coil of wire. If a conductive mass such as a sulphide body is within this magnetic field, a secondary alternating current is induced within it which in turn induces a secondary magnetic field that distorts the primary magnetic field. It is this distortion that the EM receiver measures.

The VLF-EM uses a frequency range from 16 to 24 KHz, whereas most EM instruments use frequencies ranging from a few hundred to a few thousand Hz. Because of its relatively high frequency, the VLF-EM can pick up bodies of a much lower conductivity and therefore is more susceptible to clay beds, electrolyte-filling fault or shear zones and porous horizons, graphite, carbonaceous sediments, lithological contacts as well as sulphide bodies of too low a conductivity for other EM methods to pick up. Consequently the VLF-EM has additional uses in mapping structure and in picking up sulphide bodies of too low a conductivity for conventional EM methods and too small for induced polarization (in places it can be used instead of IP). However, its susceptibility to lower conductivity results in a number of anomalies, many of them difficult to explain and, thus, VLF-EM preferable should not be interpreted without a good geological knowledge of the property and/or other geophysical and geochemical surveys.

(3) Survey Procedure

VLF-EM readings were taken at each station every 30 m facing towards the Seattle transmitter or the Lualualei transmitter. A total of line km was surveyed.

(4) Compilation of Data

The VLF-EM field results were reduced by applying the Fraser-filter and subsequently profiled above the respective IP and resistivity pseudosections. The filtered data were plotted mid-way between actual reading stations.

The Fraser-filter is essentially a 4-point difference operator, which transforms zero crossings into peaks, and a low pass smoothing operator which reduces the inherent high frequency noise in the data. Therefore, the noisy, non-contourable data are transformed into less noisy, contourable data. Another advantage of this filter is that a conductor that does not show up as a crossover on the unfiltered data quite often shows up on the filtered data.

DISCUSSION OF RESULTS

(1) Lone Star Grid

The area on and around the Lone Star showing had previously been surveyed by IP and resistivity methods (Walcott) on lines running 018°E. This work revealed widespread IP anomalies which were reflecting sulphide mineralization. Gold mineralization on the Lone Star showing occurs with sulphides. The theoretical depth penetration was about 50 m. The purpose, therefore, of the first line (0+00) on this grid was to measure to a greater depth. Since the new measurements were done with a 30 m dipole length to 10 separations, the theoretical depth of exploration was about 175 m. (For comparison sake, the previous work measured to about the third level of the present survey.) Also the new lines were run in a somewhat orthogonal direction at 080°E.

Line 0+00 revealed four IP anomalous features at depths that were not seen in the previous work. The most interesting of these was the strong anomaly below 1+20W beginning at the sixth level. Because of its strength and shape, it was postulated that it could be reflecting a more concentrated mineralized "root source" of the mineralization closer to the surface which occurred over a wider area. Therefore, an additional line was put in at 1+10S, and, later, another at 0+50N in order to determine the strike extent of this feature.

If the anomaly extends to the two additional lines, it does not occur as a feature this strong or definitive. On line 0+50N, the extension may occur below 0+75W with the strongest part at level three. On line 1+10S, a much weaker expression of the anomaly appears to occur below 1+05W starting at level seven.

Rotary hole 90R-18 was drilled to a depth of 120.4 m (approximately 6 1/2 levels) in order to try to locate as well as to determine the source of the anomaly. Though the upper part of the hole encountered significant gold mineralization, the lower part of the hole did not encounter the cause of the anomaly. The possible reasons may be the hole was not deep enough, or the dip of the causative source is either vertical or westerly (the hole was drilled to encounter an easterly dip).

Twelve rotary drill holes were put down in this area to about a 45 m depth (about 2 IP levels) except for the one hole mentioned above. Tomlinson and the writer correlated the intersections of gold mineralization with the IP and resistivity pseudosections. Though the holes could not always be correlated directly with the

pseudosections, the gold intersections in general correlated with IP highs and the edges of resistivity highs. The IP highs are, of course, caused by sulphides, and the resistivity highs, probably be silicification.

On line 0+00, the anomalies close the surface and running from about 3+60W to 0+60E were revealed by the previous work. The extension of this anomalous zone can also be seen on the other two lines. The trend of these anomalies appear to be northwesterly as can be seen on the n=2 survey plan of the chargeability (IP) results. As noted earlier these have been correlated with sulphide mineralization carrying gold values.

An IP anomaly (second of the four mentioned above) considered to be of strong exploration interest occurs at 3+60E and goes to depth. This anomaly can only be seen as a weak response in the previous survey. The probable reason is that line 0+00 crosses the causative source in a more optimum direction than the previous work did. This anomaly occurs along the edge of a resistivity high suggesting it to be a prime exploration target.

The third anomaly is a flat-lying feature centring at 4+50W at about a theoretical depth of 130 m (8th level). The length (or width) of the anomaly is 250 m with it possibly being open in a westerly direction. The resistivity correlation is not that clear, but generally is a resistivity high of small amplitude. The northern extension of this anomaly may occur at depths below 4+00W on line 0+50N, though on this line, the resistivity signature is different. The causative source is probably sulphides.

The fourth anomaly is a localized, but strong, feature occurring below 0+00 on line 0+00. It correlates with a strong resistivity low. Because of its small size, it is considered to be of limited exploration interest.

The strongest, most consistent feature on this pseudosection is a resistivity low centred at about 1+20E on all three lines. In discussions with Tomlinson and Troup, the causative source is probably a diabase dyke with a near-vertical dip. This feature can also be seen on the previous resistivity survey which shows it to be striking about 345°E (N15°W).

The HLEM survey shows a weak response over this feature indicating the causative source is centred at about 1+30W on line 0+00.

(2) 7-Pup Grid

This grid was placed in an attempt to locate the source of the placer gold within the 7-Pup stream. Because of the proximity to the Lone Star showing, it was thought that IP chargeability highs would locate gold mineralization by responding to zones of pyritization.

IP highs were located and subsequently drilled by three rotary drill holes. There was no return in gold values. It is quite possible the IP highs were not intersected. Or, the gold mineralization has a different geophysical signature (ie. different targets should be looked at).

(3) McKay-O'Neil Grid

This grid was placed at the head of a rich placer pay zone with Upper Bonanza Creek in such a manner that the western-most one or two lines were upstream, or past, the rich pay zone. The purpose was therefore to locate the source of the placer gold.

What is immediately apparent on the northwesterly-trending pseudosection is a double resistivity low along and close to Upper Bonanza Creek. This probably reflects two parallel faults. The interesting feature is that between lines 0+00 and 1+00 occurs a fault and/or diabase dyke that offsets the two parallel faults. It is strongly suggestive therefore that this offsetting fault is a significant event that relates to the emplacement of the source of the placer gold. Possibly it has broken the rock up enough in order to allow the emplacement of gold-rich fluids.

The Upper Bonanza parallel faults appear to dip southerly suggesting therefore the possible gold mineralization occurs along or below the southern bank. This bank is permafrosted and therefore would inhibit soil sample anomalies of gold mineralization. It may also inhibit IP anomalies as well as help mask any outcropping of gold mineralization. Scattered IP anomalies do exist in the area, however.

(4) Irish Gulch Grid

The Irish Gulch grid like the other three grids along Eldorado Creek, was placed at the head of very rich placer pay zones. Upstream of each of the four grids, the placer pay gold values trailed off. As on the McKay-O'Neil grid, one or two lines were placed where the values trailed off.

A resistivity low can be seen close to the creek on each of the three pseudosections. This low is likely reflecting a major fault along Eldorado Creek, possibly with associated alteration (some has been seen along Eldorado and Bonanza Creeks according to Tomlinson and Troup). The fault appears to be offset between lines 12+30S and 13+30S. This is verified by a lineal resistivity low that is located at 13+10S on the Eldorado Creek line (Eldo-444) and that probably reflects a fault. According to Troup, this right lateral cross fault occurs close to the head of the historic claim 5 which was the last claim containing very rich placer pay for the Irish Gulch area. The conclusion is therefore that the cross fault is related to the source of placer gold for the Irish Gulch area.

The IP pseudosections show scattered low level anomalies some of which may be related to gold mineralization.

(5) French Gulch Grid

In addition to the Eldo 444 cross line, this grid is composed of six survey lines plus one cross line (3+60E). This area is of particular interest because of the richness of the placer gravels downstream from French Gulch.

These pseudosections also show the Eldorado fault, but as two parallel faults, or one wide fault. THis suggests there is a wide area of fracturing or alteration associated with the faulting. It would appear there are at least two left lateral cross faults. The northern one is probably associated with possible gold mineralization since it occurs in the approximate area of the French Gulch rich placer pay.

The IP and resistivity pseudosections also outlined graphitic zones. These are indicated directly by strong IP highs correlating directly with strong resistivity lows. The graphitic zones also appear to verify the right lateral cross faulting.

There are also small IP highs that may be due to sulphide mineralization rather than graphite, largely because of the correlation with moderate-amplitude resistivity highs.

(6) Oro Grande Grid

As with the French Gulch grid, the Eldorado Creek fault as well as a graphitic zone shows an offset by left lateral faulting, and is in the other grids, this cross fault occurs near the head of the rich placer pay.

Additional faulting can also be seen further east along the two km long line, 52+50W.

(7) Gay Gulch Grid

On this grid, a major offset (left lateral fault) occurs between lines 2+20N and 1+20N that may be related to the source of the placer gold for the Gay Gulch area.

Also, on the 3.2 km long line, 0+00, the resistivity survey has picked up faulting and/or diabase dyking.

Two IP highs have also been picked up that may be caused by sulphide mineralization, these are located at 21+60E and 25+20E, respectively.

The two detail IP/resistivity lines were run to pick up quartz veins. Line 0+10N was run across a quartz outcrop containing visible gold that appeared to be a vein. There was no response to the "vein". It subsequently was "scissor" drilled with no quartz vein intersection. Therefore the quartz outcrop was probably due solely to solifluction.

(8) Eldorado Creek Line

This line runs along the Eldorado fault which shows up as a resistivity low on the cross lines on the various grids. Therefore many of the contours are horizontal. However, the line has been useful in picking up faults and graphitic zones, thereby aiding in the interpretation of each of the grids.

Some IP highs have been located that may be due to sulphides which may be associated with gold mienralization, but none that stand out as well as on the Lone Star grid.

Respectfully submitted,
GEOTRONICS SURVEYS LTD.

David G. Mark,
Geophysicist

SELECTED BIBLIOGRAPHY

Bostock, H.S., 1957; Yukon Territory-Selected Field Reports of the Geological Survey of Canada, 1893 to 1937: Geol. Surv. of Can., Mem. 284.

Boyle, R.W., 1979; The Geochemistry of Gold and its Deposits: Geol. Surv. of Can., Bulletin 280, p. 350-357.

Cairnes, D.D., 1912; Quartz Mining in the Klondike District: Geol. Surv. of Can., Sum. Rpt. for 1911, pp. 4, 17-40: Also Geol. Surv. of Can., Mem. 284, p. 343-351

DeCarle, R.J., 1984; Airborne Electromagnetic Survey, Mark Management Limited, Dawson Area, Yukon Territory: File No. 26023, Commissioned Report.

Desborough, George A., 1970; Silver Depletion Indicated by Microanalysis of Gold from Placer Occurrences, Western United States: Econ. Geol., v. 65, no. 3, p. 304-311.

Debicki, R.L., 1984; Bedrock Geology and Mineralization of the Klondike Area (West), 115 0/ 14, 15 and 116 B/2, 3 (1:50,000 scale map with marginal notes): Exploration and Geological Services Division, Mineral Resource Directorate, Whitehorse, Yukon.

Dufresnes, M.B., 1986; Origin of Gold in the White Channel Sediments of the Klondike Region, Yukon Territory. Master of Science Thesis, University of Alberta, 166 pp.

Gleeson, C.F., 1970; Heavy Mineral Studies in the Klondike Area, Yukon Territory: Geol. Surv. of Canada, Bull. 173, 63 pp.

Grunenberg, P. and Troup, A., 1985; Geological, Geochemical and Geophysical Report on the Dawson Property: Unpub. Rept., 42 pp.

Grunenberg, P. and Troup, A., 1986; Geological, Geochemical and Geophysical Report for Work Performed by Mark Management Ltd.: Unpub. Rept., 42 pp.

Grunenberg, P.B., 1989; Geological, Geochemical, Geophysical and Trenching Report on the Dawson Property, Dawson Mining District, Yukon, NTS 115 0/14 for Arbor Resources.

MacLean, T.A., 1914; Lode Mining in Yukon; An Investigation of Quartz Deposits in the Klondike Division: Can. Dept. of Mines, Mines Br. Pub. 222, Ottawa.

McConnell, R.G., 1905; Report on the Klondike Gold Fields: Geol. Surv. of Canada, Annu. Rept., pt. B, v.14, p.1-71.

Metcalfe, P., 1981; Petrogenesis of the Klondike Formation, Yukon Territory, a Thesis Presented to the University of Manitoba in Partial Fulfilment of the Requirements for the Degree of Master of Science in Department of Earth Sciences, University of Manitoba.

Milner, M.W., 1977; Geomorphology of the Klondike Placer Gold Fields, Yukon Territory. Indian and Northern Affairs Canada (Whitehorse), Final Report, 157 pp.

Mortensen, J.K., 1986; Bedrock Geology and U-Pb Geochronology of the Klondike District, West-Central Yukon Territory. Geological Survey of Canada.

Roche, W.J., 1916; The Yukon Territory; Its History and Resources: an Issue by the Ministry of the Interior, Ottawa.

Tomlinson, Scott, 1991; Verbal Discussions, Project Geologist for Arbor Resources Inc.

Troup, A., 1991; Verbal Discussions, Exploration Manager for Arbor Resources Inc.

Tuck, R., 1968; Origin of the Bedrock Values of Placer Deposits: Econ. Geol., v. 63, no.2, p. 191-193.

Van Angeren, P.D., 1986; Compilation Report on the Lone Star Property, Dawson Mining District, Y.T.: Unpub. Rept. for Dawson Eldorado Mines Ltd.

Walcott, P.E. and Associates Ltd., 1987; A Report on Magnetic and Electromagnetic Surveys, RON 17-22. (Unpublished Report for Arbor Resources Inc.)

Walcott, P.E. and Associates Ltd., 1987; A Report on Magnetic and Induced Polarization Surveys, RON, SYNDICATE, RJ, DN, ND, DE claims and LOTS. (Unpublished report for Arbor Resources Inc. and Kangeld Resources Ltd.)

GEOPHYSICIST'S CERTIFICATE

I, David G. Mark, of the City of Vancouver, in the Province of British Columbia, do hereby certify:

That I am a consulting Geophysicist of Geotronics Surveys Ltd., with offices located at #530 - 800 West Pender Street, Vancouver, British Columbia.


I further certify:

1. I am a graduate of the University of British Columbia (1968) and hold a B.Sc. degree in Geophysics.

2. I have been practising my profession for the past 23 years and have been active in the mining industry for the past 26 years.

3. This report is compiled from data obtained from IP, resistivity, magnetic VLF-EM, and horizontal loop EM surveys carried out by a crew of Geotronics Surveys Ltd., under the supervision of myself and under the field supervision of Alain Charest, geophysical technician, from July 25 to November 6, 1990.

4. I hold no interest in Arbor Resources Inc. nor in the property discussed in this report, nor will I receive any interest as a result of writing this report.



March 28, 1991

David G. Mark,
Geophysicist

AFFIDAVIT OF EXPENSES

IP, resistivity, magnetic, VLF-EM, and horizontal loop EM surveys were carried out over different portions of the Lone Star Property from July 25 to November 6, 1990, located along Upper Bonanza and Eldorado Creeks in the Dawson City area, Dawson Mining Division, Yukon Territory to the value of the following:

FIELD

Mob-demob	
Airfare, Vancouver to Dawson City, rtn. 6 men at $1,195/man	$ 7,188
Freight, air and land	2,908
Room and board	1,170
Wages, at cost	2,916
Sub-Total	14,182
Lone Star Property's Pro Rata share at 75%	$ 10,637
4-man crew, 50 days at $1,100/day	$ 55,000
3-man crew, 15.5 days at $950/day	14,725
Truck rental and gas, Suburban 4X4, 71 days at $100/day	7,100
Room and board, 268 man-days at $65/man-day	17,420
Linecutting, all-in cost, 35.9 km at $400/km	14,360
Sub-Total	$119,242

OFFICE

Senior geophysicist, 200 hours @ $45/hour	$ 9,000
Geological consultation (Art Troup & Scott Tomlinson)	6,000
Geophysical technician with computer, 454 hours @ $30/hour	13,620
Computer-aided drafting & plotting 60 hours at $30/hour	1,800
Report generation and printing	1,000
Sub-Total	$ 31,420
Grand Total	**$150,622**

Respectfully submitted,
GEOTRONICS SURVEYS LTD.

David G. Mark, Geophysicist
Manager

Eight men were involved in the field work as follows:

David Mark, senior geophysicist, Vancouver, B.C.

Alain Charest, geophysical technician/crew chief, Vancouver, B.C.

Marc Habel, geophysical technician/crew chief, Vancouver, B.C.

Sylvain Vaillencourt, geophysical technician, Jonquiere, Quebec

Maurice Lavoie, geophysical technician, Vancouver, B.C.

Al Harrison, geophysical technician, Vancouver, B.C.

Derwin Miller, helper, Dawson City, Yukon

Dan Robertson, helper, Vancouver, B.C.

An attempt was made to hire locally but, other than one person, no one else was available.

Some truck rental (Norcan Leasing), all room and board, and supplies were purchased locally.

ARBOR RESOURCES INC.


LONE STAR PROPERTY


DAWSOM MINING DISTRICT, Y.T.

LOCATION MAP

BY: D.M./p.s.
DATE: MARCH, 1991

Map ~~FIGURE~~: 1





092969 199

ARBOR RESOURCES INC.

LONE STAR PROPERTY

DAWSON MINING DISTRICT, Y.T.

CLAIM MAP

BY: D.M./p.s.
DATE: MARCH, 1991

~~FIGURE~~: 2

TO DAWSON CITY

L ELDO-444

BONANZA

GAUVIN GULCH

HOMESTAKE GULCH

McKAY GULCH

McKAY O'NEIL GRID

CIM

L1+00S

LOT 1002

CREEK

IRISH GULCH GRID

L12+30S

L13+30S

L14+30S

GULCH

IRISH

RON

RJ

L1+00W

L1+00E

L2+00E

L0+00

DE

O'NEIL

GULCH

DN

L3+80E

L4+80E

L5+80E

AC

7 PUP

FRENCH GULCH GRID

L4+80E

L2+55S

L4+25S

L5+40S

L6+80S

L7+55S

L8+55S

L0+00

7-PUP GRID

VICTORIA

ELDORADO

GULCH

FRENCH

LONE STAR GRID

L0+50N

L0+00

L1+10S

D

GULCH

GRANDE

DN

AC

ORO GRANDE GRID

ORO

L49+70S

L52+60S

L54+50S

L56+40S

NUGGET GULCH

GULCH

LOT 104

ND

L2+20N

L1+20N

L0+00

L1+00S

GAY

CREEK

GAY GULCH GRID

LEGEND

- ROAD
- TEMPORARY ROAD
- RIVER
- I.P. LINE
- TRENCH
- BUILDING

SCALE 1:25,000

0 250 500 750 1000 1250

METRES

ARBOR RESOURCES INC.

LONE STAR PROPERTY

DAWSON MINING DISTRICT, Y.T.

092969


I.P. GRID LOCATION MAP

200

BY: D.M./p.s.

DATE: MARCH, 1991

MAP #3



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
LONESTAR GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-O-14	1:2500	Nov/90	5

092969

201



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
LONESTAR GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-O-14	1:2500	Nov/90	6

092969

202



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
LONESTAR GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-O-14	1:2500	Nov/90	7

092969

203



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
LONESTAR GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-O-14	1:2500	Nov/90	8

092969

204



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
LONESTAR GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-O-14	1:2500	Nov/90	9

092969

205



Scale 1:2500

25 0 25 50 75 100 125
(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
LONESTAR GRID
DAWSON CITY AREA


Apparent RESISTIVITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	10


092969

206

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY



APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


LONESTAR GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 0+50N

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-O-14	1:2500	Sept/90	//

92969 207




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

LONESTAR GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 0+00(Bldr333)

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07		1:2500	Sept/90	1/2

092969 208

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY

APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES INC.

LONESTAR GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 1+10S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07		1:2500	Sept/90	13



SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
7-PUP GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-O-14	1:2500	Nov/90	/7

092969 210

Survey Direction: 80 Degrees N.E.




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

7-PUP GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 0+00

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-O-14	1:2500	Sept/90	20


092969

211

Survey Direction: south



APPARENT RESISTIVITY



APPARENT CHAGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

7-PUP GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 3+80E


Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-O-14	1:2500	Sept/90	21

092969 212

Survey Direction: south



APPARENT RESISTIVITY




APPARENT CHAGEABILITY

Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


7-PUP GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 4+80E

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-O-14	1:2500	Sept/90	22

Survey Direction: south



APPARENT RESISTIVITY


APPARENT CHAGEABILITY

Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervels:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver: Huntec Model MK IV
Transmitter/Generator: Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


7-PUP GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 5+80E

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-O-14	1:2500	Sept/90	23

Survey Direction: 110 degrees S.E.



APPARENT RESISTIVITY



APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


McKAY-O'NEIL GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 1+00S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	30

Survey Direction: 115 degrees S.E.



APPARENT RESISTIVITY



APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


McKAY-O'NEIL GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 1+00W

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	3

Survey Direction: 115 degrees S.E.




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

McKAY-O'NEIL GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 0+00


Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-0-14	1:2500	Sept/90	32

28

Survey Direction: 115 degrees S.E.



APPARENT RESISTIVITY




APPARENT CHARGEABILITY

Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervels:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


McKAY-O'NEIL GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 1+00E

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-0-14	1:2500	Sept/90	33

Survey Direction: 115 degrees S.E.




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


McKAY-O'NEIL GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 2+00E

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	34

220



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine


Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
IRISH GULCH GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	35



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine


Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
IRISH GULCH GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	36



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine


Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
IRISH GULCH GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-O-14	1:2500	Nov/90	37



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine


Surveyed by GEOTRONICS SURVEYS LTD..
September 1990


GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
IRISH GULCH GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-O-14	1:2500	Nov/90	38


L 1230 S
L 1330 S
L 1430 S
L 1230 S
L 1330 S
L 1430 S
1394
3098
1428
583
991
1731
848
720
578
976
1269
339
456
2207
1198
803
887
1530
1000
1000
1000



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990


GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
IRISH GULCH GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	40

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY


APPARENT CHARGEABILITY

Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervels:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


IRISH GULCH GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 12+30S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-O-14	1:2500	Sept/90	41

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY




APPARENT CHARGEABILITY

Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


IRISH GULCH GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 13+30S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-O-14	1:2500	Sept/90	42

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY



APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES INC.

IRISH GULCH GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 14+30S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-O-14	1:2500	Sept/90	43



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine


Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
FRENCH GULCH GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	44



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine


Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
FRENCH GULCH GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	45



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine


Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
FRENCH GULCH GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	46



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda-engine


Surveyed by GEOTRONICS SURVEYS LTD..
September 1990 .

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
FRENCH GULCH GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	47



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine


Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
FRENCH GULCH GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-O-14	1:5000	Nov/90	48



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
FRENCH GULCH GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=6


Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	49

Survey Direction: South

APPARENT RESISTIVITY



APPARENT CHARGEABILITY




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

FRENCH GULCH GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 3+60E


Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	50

236

Survey Direction: 85 degrees N.E.



APPARENT RESISTIVITY




APPARENT CHARGEABILITY

Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervels:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

FRENCH GULCH GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 2+55S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-O-14	1:2500	Sept/90	5/

237

Survey Direction: 84 degrees N.E.



APPARENT RESISTIVITY

APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


FRENCH GULCH GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 4+25S(Fr999)

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-O-14	1:2500	Sept/90	52

Survey Direction: 80 degrees N.E.




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver: Huntec Model MK IV
Transmitter/Generator: Huntec Model MK IV
7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


FRENCH GULCH GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 5+40S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	53

Survey Direction: 80 degrees N.E.






Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 Feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


FRENCH GULCH GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 6+80S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	54

Survey Direction: 77 degrees N.E.



APPARENT RESISTIVITY



APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


FRENCH GULCH GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 7+35S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	55

Survey Direction: 80 degrees N.E.






Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


FRENCH GULCH GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 8+55S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	56

Survey Direction: 80 degrees N.E.






Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


ORO GRANDE GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 49+70S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	63

Survey Direction: 80 degrees N.E.




Scale 1:5000

50 0 50 100 150 200 250

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


ORO GRANDE GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 52+50S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:5000	Sept/90	64

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY



APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK-IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


ORO GRANDE GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 54+50S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	65

Survey Direction: 80 degrees N.E.






Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

ORO GRANDE GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 56+40S


Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	66

Survey Direction: 76 degrees N.E.

APPARENT RESISTIVITY



APPARENT CHARGEABILITY




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


GAY GULCH GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 2+20N

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-O-14	1:2500	Sept/90	67

Survey Direction: 76 degrees N.E.



APPARENT RESISTIVITY

APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervels:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


GAY GULCH GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 1+20N

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-O-14	1:2500	Sept/90	68

Survey Direction: 77 degrees N.E.



APPARENT RESISTIVITY

APPARENT CHARGEABILITY


Scale 1:5000

50 0 50 100 150 200 250

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds
Survey Mode: Time Domain
Array: Double-Dipole
Dipole Length: 100 feet(30 metres)
Dipole separation: n=1 to 8

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


GAY GULCH GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 0+00(W)

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-O-14	1:5000	Sept/90	69(a)

Survey Direction: 77 degrees N.E.




Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

GAY GULCH GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 0+00(E)


Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-O-14	1:5000	Sept/90	69(6)

Survey Direction: 76 degrees N.E.

APPARENT RESISTIVITY



APPARENT CHARGEABILITY




Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

GAY GULCH GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 1+01S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-0-14	1:2500	Sept/90	70

TO DAWSON CITY

BONANZA

ELDO-444

GAUVIN GULCH

HOMESTAKE

GULCH

McKAY

IRISH GULCH GRID

L12+30S
L13+30S
L14+30S
3+00W
3+80E

IRISH GULCH

RON

FRENCH GULCH GRID

2+60S
L2+55S
L4+25S
L5+40S
L7+55S
L8+55S
0+00
0+60N
0+90W
300+6
11+10E
10+10E
1+50E
L3+60E
FRENCH L6+80S
graphitic zones
faults

RJ

CIM

McKAY O'NEIL GRID

6+60N
4+60N
L1+00S
2+60S
2+40S
3+00S
L1+00W
L1+00E
L2+00E
L0+00

GULCH

DE

O'NEIL

DN

L3+80E
L4+80E
4+00N
3+60N
7 PUP
6+30E
L0+00
7-PUP GRID
2+40S
2+30S
VICTORIA

LONE STAR GRID

6+30W
L0+50N
L0+00
L1+10S
1+50W
2+10E
5+10E

LEGEND

ROAD
TEMPORARY ROAD
RIVER
I.P. LINE
TRENCH
BUILDING

SCALE 1:10,000
0 100 200 300 400 500
METRES

ELDORADO

GRANDE

ORO GRANDE GRID

ORO
3+90E
L48+70S
L52+50S
L54+50S
L56+40S
3+00W
4+20E
5+10E
1+50W
L2+20N
L1+20W
L0+00
L1+00S
0+00

GAY GULCH GRID

GAY
CREEK

DN

19+80E

LOT 104

32+10E

GULCH

ND

NUGGET

DWG 234A

DRAFT

ARBOR RESOURCES INC.


LONE STAR PROPERTY
DAWSON MINING DISTRICT, Y.T.

1990 GEOPHYSICAL COMPILATION MAP

092969

BY: D.M./p.s.
DATE: APRIL, 1991

MAP #4



LEGEND

% OUT-OF-PHASE
% IN-PHASE

+10% / 0 / -10% — Percent deviation from normal field

0 100 200 300 400 metres

INTSTRUMENTATION: Apex Parametrics MAX MIN II
COIL SPACING: 100 metres

TO ACCOMPANY GEOPHYSICAL REPORT BY DAVID G. MARK, GEOPHYSICIST, DATED MARCH 19, 1991

Map#115/0/14 Doc#092969 (84)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


LONESTAR GRID

BOULDER LODE, DAWSON CITY AREA
DAWSON M.D., Y.T.

HORIZONTAL LOOP EM
Profiles — 0+00S

Drawn by:	Date:	Job No.	Scale:	Map No.
Geo-Comp	Mar.'91	90-07	Vert. 1cm=10% Horiz. 1:2,500	4

Geo-Comp Drawing File: LONE/0S



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990


MAP #115/0/14 Doc #092969 (75)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
LONESTAR GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	LS-5



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990


Map #115/0/14 Doc #092769 (76)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
LONESTAR GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	L 5-6



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990


MAP #115/6/14 Doc #092469 (77)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
LONESTAR GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	LS-7



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990


Map#115/0/14 Doc#092969 (78)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
LONESTAR GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	LS-8



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990


Map# 115/0/14 Doc# 092969 (79)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
LONESTAR GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	LS-9



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

MAP#115/0/14 Doc#092969 (80)


GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
LONESTAR GRID
DAWSON CITY AREA


Apparent RESISTIVITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	LS-10

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY




APPARENT CHARGEABILITY

Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 Feet(30 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

MAP #115/0/14 Doc # 092969 (61)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

LONESTAR GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 0+50N

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-0-14	1:2500	Sept/90	LS-11

Survey Direction: 80 degrees N.E.




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

MAP #115/0/14 Doc #092969 (83)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

LONESTAR GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 1+10S


Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07		1:2500	Sept/90	L S-13





Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 Feet(15 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

VLF-EM Profile
Scale: 1 cm = 5%

DWG 127
Mar #115/6/H Doc #092969 (82)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES INC.

LONESTAR GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE BL000

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-O-14	1:2500	Sept/90	2 S-12



SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990


map# 115/0/14 Doc# 092969 (124)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
7-PUP GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:5000	Nov/90	SP-5



N

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990 .


MAP# 115/0/14 Doc# 092969 (89)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
7-PUP GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:5000	Nov/90	SP-6



SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990 .


MAP#115/0/14 Doc# 092969 (90)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
7-PUP GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:5000	Nov/90	SP-7



SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
7-PUP GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	SP-8

MAP# 115/0/14 Doc#092969 (121)

7PUP – 17



SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990 .

MAP#115/0/14 Doc#092969 (128)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
7-PUP GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:5000	Nov/90	SP-8



N

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990


MAP# 115/0/14 Doc# 092969 (129)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
7-PUP GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:5000	Nov/90	SP-7



SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990 .


MAP# 115/0/14 Doc# 692469 (130)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
7-PUP GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:5000	Nov/90	5P-10




Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 Feet(15 metres)
Dipole seperation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

VLF profile
Scale: 1 cm = 20% dip

MAP #115/0/14 Doc #092969 (131)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


7-PUP GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 7-PUP(0+00)

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-0-14	1:2500	Sept/90	SP-11

Survey Direction: south




Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

MAP# 115/6/14 Doc# 092969 (135)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

7-PUP GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 3+80E

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-0-14	1:2500	Sept/90	SP-12

178

7PUP-21

Survey Direction: SOUTH



APPARENT RESISTIVITY

APPARENT CHAGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervels:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 Feet(15 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

VLF profile
Scale: 1 cm = 20% dip

MAP# 115/0/14 Doc# 092969 (122)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

7-PUP GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 480E

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-0-14	1:2500	Sept/90	SP-13

175 7PUP - 22

Survey Direction: south




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second squere wave

MAP# 115/0/14 Doc# 092969 (123)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


7-PUP GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 5+80E

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-0-14	1:2500	Sept/90	SP-14

176 7PUP - 23



LEGEND

% OUT-OF-PHASE
% IN-PHASE

+10% / 0 / -10% — Percent deviation from normal field

0 100 200 300 400
metres

INTSTRUMENTATION: Apex Parametrics MAX MIN II
COIL SPACING: 100 metres

TO ACCOMPANY GEOPHYSICAL REPORT BY DAVID G. MARK, GEOPHYSICIST
DATE: MARCH 19, 1991

MAP# 115/0/14 Doc#092969 (144)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

McKAY O'NEIL GRID


BOULDER LODE, DAWSON CITY AREA
DAWSON M.D., Y.T.

HORIZONTAL LOOP EM
Profiles – 1+00E

Drawn by:	Date:	Job No.	Scale:	Map No.
Geo-Comp	Mar.'91	90-07	Vert. 1cm=10% Horiz. 1:2,500	7

Geo-Comp Drawing File: MKY100E

197 MCKAY - 33A



LEGEND

% OUT-OF-PHASE
% IN-PHASE

+10%
0
-10%
Percent deviation from normal field

0 100 200 300 400
metres

INTSTRUMENTATION: Apex Parametrics MAX MIN II
COIL SPACING: 100 metres

TO ACCOMPANY GEOPHYSICAL REPORT BY DAVID G. MARK, GEOPHYSICIST
DATE MARCH 19, 1991

MAP# 115/0/14 Doc# 092969 (139)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.
McKAY O'NEIL GRID
BOULDER LODE, DAWSON CITY AREA
DAWSON M.D., Y.T.

HORIZONTAL LOOP EM
Profiles – 1+00S


Drawn by:	Date:	Job No.	Scale:	Map No.
Geo-Comp	Mar.'91	90-07	Vert. 1cm=10% Horiz. 1:2,500	MD 16

Geo-Comp Drawing File: MKY100S

192

MCKAY - 30A

Survey Direction: 115 degrees S.E.




Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

MAP #115/0/14 Dx #092969 (141)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

McKAY-O'NEIL GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY-
PSEUDOSECTIONS
LINE 0+00

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-0-14	1:2500	Sept/90	M0-13

194

MCKAY - 32

Survey Direction: 110 degrees S.E.



APPARENT RESISTIVITY

APPARENT CHAGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 feet(15 metres)
Dipole seperation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

VLF profile
Scale: 1 cm = 20% dip

map#115/0/14 Doc#092969 (138)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


MCKAY-O'NEIL GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 100S


Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-0-14	1:2500	Sept/90	MO-11

191 MCKAY - 30



Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 feet(15 metres)
Dipole seperation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

MAP# 115/0/14 Doc# 092969 (142)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


MCKAY-O'NEIL GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 100E

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-0-14	1:2500	Sept/90	MC-14

Survey Direction: 115 degrees S.E.




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

MM# 115/0/14 Doc# 093969 (143)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

McKAY-O'NEIL GRID


DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 2+00E

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	MO-15

196

McKAY - 34





SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990 .


MAP#115/0/14 Doc#092969 (73)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
McKAY - O'NEIL GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:5000	Nov/90	MO-5



SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990


mpp#115/0/14 D.c#092969 (94)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
McKAY - O'NEIL GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:5000	Nov/90	MC-6



SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

Map# 115/0/14 Doc# 092969 (95)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
McKAY - O'NEIL GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:5000	Nov/90	MC-7



SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990 .

Map# 115/0/14 Doc 092969 (96)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
McKAY - O'NEIL GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:5000	Nov/90	M0-8



SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

MAP#115/0/14 Doc#092969 (97)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
McKAY - O'NEIL GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:5000	Nov/90	MO-9

151



SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990 .


MAP#115/0/14 Doc#02969 (98)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
McKAY - O'NEIL GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:5000	Nov/90	M0-10



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

MAP# 115/0/14 Doc# 092969 (99)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
IRISH GULCH GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	IG-5

153

IRISH - 35



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

MAP#115/0/14 Doc#092969 (100)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
IRISH GULCH GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	IG-6

154

IRISH - 36



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

MAP# 115/0/14 Doc# 092969 (101)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
IRISH GULCH GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	IG-7

155

IRISH - 37



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

MAP# 115/0/14 Doc# 092969 (102)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
IRISH GULCH GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	IG-8

156

IRISH-38



Scale 1:2500

25 0 25 50 75 100 125

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

Map# 115/0/14 Dat# 092969 (103)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
IRISH GULCH GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=4


Drawn by	N.T.S.	Scale	Date	Map #
A.C.	115-0-14	1:2500	Nov/90	IG-9

157


IRISH - 39


L 1230 S
L 1330 S
L 1430 S
L 1230 S
L 1330 S
L 1430 S
2082
1136
1328
1433
489
645
1572
1544
739
1000
1000
1407
414
609
1706
1378
2186
1000
1000
1000

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY



APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres

Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

MAP#115/0/14 Doc#092969 (105)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

IRISH GULCH GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 12+30S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-0-14	1:2500	Sept/90	IG-11


159

IRISH-411

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY



APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

MAP# 115/0/14 Doc# 092969 (106)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

IRISH GULCH GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 13+30S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-0-14	1:2500	Sept/90	IG-12


160

IRISH - 42

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY



APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

map#115/0/14 Doc#092969 (107)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


IRISH GULCH GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 14+30S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-0-14	1:2500	Sept/90	I-13

161



Map# 115/6/14 Doc# 092969

(108)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

Scale 1:5000

50 0 50 100 150 200 250
(metres)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
FRENCH GULCH GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	FG-5

162

FRENCH-44



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

MAP# 115/0/14 Doc# 092969 (109)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
FRENCH GULCH GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	FG-6

163

FRENCH - 45



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

MAP#115/0/14 Doc#092969 (110)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
FRENCH GULCH GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	FG-7

164

FRENCH-46



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

MAP# 115/0/14 Doc# 092969 (111)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
FRENCH GULCH GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	FG-8

165

FRENCH - 47



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

MAP# 115/0/14 Doc#092969 (112)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
FRENCH GULCH GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	FG-9

166

FRENCH - 48



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

MAP#115/0/14 Doc#092969 (113)


GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
FRENCH GULCH GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	FG-10

167




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 feet(15 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

MAP# 115/0/14 Doc# 092969 (115)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES INC.

FRENCH GULCH GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 255S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-0-14	1:2500	Sept/90	FG-12



Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 feet(15 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

MAP# 115/0/14 Doc#092969 (117)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


FRENCH GULCH GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 540S


Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-0-14	1:2500	Sept '90	[illegible]

171 FRENCH - 53



Survey Direction: 078 degrees N.E.






Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 feet(15 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

FRENCH GULCH GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 680S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-O-14	1:2500	Sept/90	F-G-15

MAP#115/O/14 Doc#092969

FRENCH 1-54 17A




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 Feet(15 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

MAP#115/0/14 Doc#092969 (119)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES INC.

FRENCH GULCH GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 735S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-0-14	1:2500	Sept/90	FG-16




Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 feet(15 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

FRENCH GULCH GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 855S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-O-14	1:2500	Sept/90	FG-17


MAP# 115/O/14 Doc# 092969 (120)

FRENCH-56 173



Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 feet(15 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

MAP# 115/0/14 Doc# 092969 (116)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES INC.

FRENCH GULCH GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 999(4+25S)

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-0-14	1:2500	Sept/90	FG-13



Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 feet(15 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

MAP# 115/0/14 Doc# 092969 (114)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


FRENCH GULCH GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 360E

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-05	115-0-14	1:2500	Sept/90	FG-11

168
FRENCH - 50



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Preliminary

MAP# 115/O/14 Doc# 092969 (32)


GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
ORO-GAY GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-O-14	1:5000	Nov/90	57

092969 185



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

Preliminary

MAP#115/0/14 Doc# 092969 (33)


GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
ORO-GAY GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	58

092969 186



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

Preliminary

MDP# 115/0/14 Doc# 092969 (134)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
ORO-GAY GRID
DAWSON CITY AREA

Apparent CHARGEABILITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	59

092969 187



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

Preliminary


MAP# 115/0/14 Doc# 092969 (135)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
ORO-GAY GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=2

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	60



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

Preliminary

map #115/0/14 Doc #092969 (136)


GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD
ORO-GAY GRID
DAWSON CITY AREA

Apparent RESISTIVITY Survey
Data and Contours
For Level n=4

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-0-14	1:5000	Nov/90	61

092969 189



Scale 1:5000

50 0 50 100 150 200 250

(metres)

SURVEY PARAMETERS

Contour Intervals:
Resistivity : Log base 10 ohm-metres
Chargeability : 3 milliseconds

Trend Enhancement: 000 degrees
Receiver: Huntec Mark IV
Transmitter: Phoenix IPT-1
Generator: Phoenix MG-2
2.5 kWatt, with
5.0 HP Honda engine

Surveyed by GEOTRONICS SURVEYS LTD..
September 1990

Preliminary

MAP# 115/O/14 Doc# 092769 (137)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES LTD
ORO-GAY GRID
DAWSON CITY AREA


Apparent RESISTIVITY Survey
Data and Contours
For Level n=6

Drawn by	N.T.S.	Scale	Date	Map #
P.C.	115-O-14	1:5000	Nov/90	62

190 092069

Survey Direction: 80 degrees N.E.






Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

MAP# 115/0/14 Doc# 092969 (85)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

ORO GRANDE GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 49+70S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-0-14	1:2500	Sept/90	OG-11

ORO-63
140

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY


APPARENT CHARGEABILITY

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	n=1 to 8

MAP 115/0/14 Doc# 62969 (28)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


ORO GRANDE GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 52+50S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-0-14	1:5000	Sept/90	OG-12

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY




APPARENT CHARGEABILITY

Scale 1:2500

25 0 25 50 75 100 125
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

MAP#115/0/14 Dat#092969 (87)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

ORO GRANDE GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 54+50S


Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-0-14	1:2500	Sept/90	06-13

ORO-65
142

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY



APPARENT CHARGEABILITY


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervels:
Resistivity : log base 10 ohm-metres

Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

ORO GRANDE GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 56+40S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-07	115-O-14	1:2500	Sept/90	OG-14

143 ORO-66

Survey Direction: 80 degrees N.E.



APPARENT RESISTIVITY


APPARENT CHARGEABILITY

Scale 1:500

5 0 5 10 15 20 25
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity: log base 10 ohm-metres
Chargeability: milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 2.5 KWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	15 feet(5 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	4 second square wave

Map#115/0/14 Doc#092969 (72)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

GAY GULCH GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 0+04N

Drawn by:	Job No:	NTS	Scale	Date	Map No.
AC	90-07	115-0-14	1:500	Sept/90	GG-15


GAY - 71

(128)



Surveyed by Geotronics Surveys Ltd.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals :
Resistivity: log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array :	Double-Dipole
Dipole Length :	7.5 metres
Dipole separation:	n = 1 to 10
Delay Time :	200 milliseconds
Integration Time :	1500 milliseconds
Charge Cycle:	8 second square wave

map# 115/0/14 Doc# 09/7969 (145)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES INC.

GAY GULCH GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE No. (DETAIL) 0+10N.

Drawn by:	Job No.	NTS	Scale	Date	Map No.
J.W.	90-06	115-0-14	1:500	Sept./90	GG-16



APPARENT RESISTIVITY

APPARENT CHAGEABILITY

Survey Direction: 030 degrees N.E.


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 feet(15 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 millseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

MAP #115/0/14 Doc #092969 (68)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

GAY GULCH GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 120N


Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-0-14	1:2500	Sept/90	GG-12

(124)

GAY - 68



APPARENT RESISTIVITY



APPARENT CHAGEABILITY

Survey Direction: 030 degrees N.E.


Scale 1:2500

25 0 25 50 75 100 125

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 feet(15 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

MAP# 115/0/14 Doc#092969 (67)

GEOTRONICS SURVEYS LTD.


ARBOR RESOURCES INC.

GAY GULCH GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 220N

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-06	115-0-14	1:2500	Sept/90	GG-11



Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	50 feet(15 metres)
Dipole separation:	n=1 to 10
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

PROFILE LEGEND

Magnetic profile
Scale: 1 cm = 20 gammas

MAP #115/0/14 Dat#092969

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.


GAY GULCH GRID

DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 100S

Drawn by:	Job No.	NTS	Scale	Date	Map No.
PC	90-05	115-0-14	1:2500	Sept/90	G-G-14

Survey Direction: 77 degrees N.E.



APPARENT RESISTIVITY


APPARENT CHARGEABILITY

Scale 1:5000

50 0 50 100 150 200 250
(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervels:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds
Survey Mode: Time Domain
Array: Double-Dipole
Dipole Length: 100 Feet(30 metres)
Dipole separation: n=1 to 8

MAP# 115/0/14 Doc# 092969 (69)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

GAY GULCH GRID

DAWSON CITY, YUKON


APPARENT RESISTIVITY and CHARGEABILITY
PSEUDOSECTIONS
LINE 0+00(W)

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-0-14	1:5000	Sept/90	GG-13(1)

(125)

GAY - 69A

Survey Direction: 77 degrees N.E.




Scale 1:5000

50 0 50 100 150 200 250

(metres)

Surveyed by GEOTRONICS SURVEYS LTD.
September 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability: 3 milliseconds

INSTRUMENTATION

Receiver:	Huntec Model MK IV
Transmitter/Generator:	Huntec Model MK IV 7.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double-Dipole
Dipole Length:	100 feet(30 metres)
Dipole seperation:	n=1 to 8
Delay Time:	200 milliseconds
Integration Time:	1500 milliseconds
Charge Cycle:	8 second square wave

MAP # 115/0/14 Doc # 692969 (70)

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES INC.

GAY GULCH GRID


DAWSON CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 0+00(E)

Drawn by:	Job No.	NTS	Scale	Date	Map No.
AC	90-07	115-0-14	1:5000	Sept/90	GG-13(6)

(126)

GAY - 69B



Pseudosection Plotting Method

LEGEND

Contour Interval: Resistivity = Ohm-metres
Chargeability = milliseconds

INSTRUMENTATION

Transmitter: Huntec Model MK-IV
Transmitter/Generator: Huntec Model MK-IV (5.0 kVA)

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double Dipole
Dipole Length:	100 feet (30 metres)
Delay Time:	240 milliseconds
Integration Time:	1000 milliseconds

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD

ELDORADO LINE


SAMPLE CITY, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS

LINE 4+44 (North Half)

Drawn by:	Job No.	RTI	Scale:	Date:	Fig. No.
JC	GROUP 2000-01-3500		1:2500	June'91	73A

Dwg 852



This northern portion of the line overlaps the southern portion by approximately 360 metres

Surveyed by GEOTRONICS SURVEYS LTD. October 1990

Pseudosection Plotting Method



LEGEND

Contour Intervals:
Resistivity : log base 10 ohm-metres
Chargeability : 5 milliseconds

INSTRUMENTATION

Receiver:	Huntec Mark IV 10
Transmitter/Generator:	Huntec Mark IV 10
	2.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Double Dipole
Dipole Length:	100 Feet(30 metres)
Dipole separation:	n= 1 to 6
Delay Time:	360 milliseconds
Integration Time:	1000 milliseconds
Charge Cycle:	8 second square wave

Revised to Mar 07 2001

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD.


ELDORADO LINE

CARIBOU AREA, YUKON

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS

LINE 4+44 (North Half)

Drawn by:	Date:	Scale:	Date:	Dwg No.
PC	Jan 94	1:2500	Jan 94	ARC-96



Pseudosection Plotting Method



LEGEND

Contour Interval: log base 10 ohm-metres
Resistivity:
Chargeability: milliseconds

INSTRUMENTATION

Receiver: Huntec Model MK IV
Transmitter/Generator: Huntec Model MK IV 5.5 kWatt

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Dipole-Dipole
Dipole Length:	100 feet(30 metres)
Dipole separation:	Level No.6
Delay Time:	300 milliseconds
Integration Time:	1000 milliseconds
Charge Cycle:	8 second square wave

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD

ELDORADO LINE

TRANSVAAL, YUKON


APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS
LINE 4+44 (South Half)

Drawn by:	Job #:	Scale:	Date:	Rev #:
JC	2007	1:2500	June 2007	738

This southern portion of the line overlaps the northern portion by approximately 360 metres

Surveyed by GEOTRONICS SURVEYS LTD. October 1999

mineral 15/10/14 Doc # 019769
Dwg 953



This southern portion of the line overlaps the northern portion by approximately 360 metres

Surveyed by GEOTRONICS SURVEYS LTD. October 1990

Pseudosection Plotting Method



LEGEND

Contour Interval:
Resistivity : log base 10 ohm-metres
Chargeability : 5 milliseconds

INSTRUMENTATION

Receiver: Norten Model MK-15
Transmitter/Generator: Norten Model MK-15 (5.5 kVA)

SURVEY PARAMETERS

Survey Mode:	Time Domain
Array:	Dipole-Dipole
Dipole Length:	100 Feet(30 metres)
Dipole separation:	n=1 to 6
Delay Time:	200 milliseconds
Integration Time:	2000 milliseconds
Charge Cycle:	6 second square wave

Drawn by: PC

Job No.	Dwg. No.	Date
90-07	90-07-14	June/91

Map No. EC-356

GEOTRONICS SURVEYS LTD.

ARBOR RESOURCES LTD

ELDORADO LINE

(PERSON CITY, YUKON)

APPARENT RESISTIVITY and CHARGEABILITY PSEUDOSECTIONS

LINE 4+44 (South Half)

356