







SURVEY SPECIFICATIONS:
Survey flown: June 19 - 28, 2010
Traverse/Tie line spacing: 100/1000 metres
Traverse/Tie line direction: 20°/110°
Nominal EM bird height: 30 metres
Aircraft: Aerospasiale A-Star 350 B3 (C-GSGK)

INSTRUMENTATION:
Data acquisition: ADAS
Magnetometers: Geometrics G-823A caesium vapour
Installation: Towed upper magnetic bird 18 m below the helicopter
Installation: Towed lower magnetic bird 36 m below the helicopter
Sensitivity: .001 nanoTesla
Electromagnetics: AeroTEM II system (ECHO)
Configuration: Towed bird

NAVIGATION:
Navigation: Differential Global Positioning System (DGPS)
Navigation equipment: AGNAV with MID-TECH RX400p receiver
Radar Altimeter: Terra TRA3000/TRI-30

POSITIONING
Datum: NAD83
Major Axis: 6378137.000
Eccentricity: 0.081819191
MAP PROJECTION
Projection: Universal Transverse Mercator
Central Meridian: 129°W (Zone 09)
Central Scale Factor: 0.9996
False Easting/Northing: 500,000m/0m



TerraLogic Exploration Inc.
Ross River, Yukon

**TOTAL LOWER
MAGNETIC INTENSITY**

Sprogge Block
NTS 105H09

AEROQUEST
7687 Bath Road, Mississauga, ON, CANADA L4T 3T1
Tel: (905) 672-9129 Fax: (905) 672-7983
www.aeroquest.ca
September 2010