



TECHNICAL SUMMARY

Navigation
Date reduction grid interval : 40 metres
Terrain clearance : 60 m
Electromagnetic sensor : 35 m
Magnetometer : 35 m
Data sampling interval : 0.1 second
Magnetometer / sensitivity : Cesium / 0.01 nT
Electromagnetic system : DIGHEM[®]

Frequency	Sensitivity	Coil Orientation
1000 Hz	.06 ppm	Vertical coaxial
5500 Hz	.12 ppm	Vertical coaxial
300 Hz	.12 ppm	Horizontal coplanar
7200 Hz	.24 ppm	Horizontal coplanar
56000 Hz	.50 ppm	Horizontal coplanar

ELECTROMAGNETIC ANOMALIES

Grade	Anomaly	Conductance
7	●	>100 siemens
6	●	50-100 siemens
5	●	20-50 siemens
4	●	10-20 siemens
3	●	5-10 siemens
2	●	1-5 siemens
1	●	< 1 siemens
-	*	Questionable anomaly

FLIGHT LINES WITH EM ANOMALIES

Interpretive symbol
Anomaly identifier
Interpretive symbol

INTERPRETATION LEGEND

--- Inferred structural break

M Magnetic zone

R Conductive zone

LOCATION MAP

NTS: 105 O/1,2,3,6,7; 105 P/4

UTM ZONE: 9

NAD83

SCALE: 1:650,000

COLORADO RESOURCES LTD.
MAC PASS CLAIMS, YUKON

INTERPRETATION

FUGRO DIGHEM [®] SURVEY	NTS: 105 O/1,2,3,6,7	GEOPHYSICIST:
DATE: OCTOBER, 2011	JOB: 11046	SHEET: 4

Fugro Airborne Surveys

0 1 2 Km
0 1 Mi
Scale 1:20 000

FUGRO AIRBORNE SURVEYS

FUGRO