



TECHNICAL SUMMARY

Navigation: Differentially-corrected GPS
Data reduction grid interval: 40 metres
Terrain clearance: Helicopter 60 m
Electromagnetic sensor 35 m
Magnetometer 35 m
Data sampling interval: 0.1 second
Magnetometer / sensitivity: Cesium / 0.01 nT
Electromagnetic system: DIGHEM[®]

Frequency	Sensitivity	Coil Orientation
1000 Hz	.06 ppm	Vertical coaxial
5500 Hz	.12 ppm	Vertical coaxial
900 Hz	.12 ppm	Horizontal coplanar
7200 Hz	.24 ppm	Horizontal coplanar
56000 Hz	.50 ppm	Horizontal coplanar

FLIGHT LINES

Flight direction
Flight number
Flight line number
Reflight Number
Line Number
Area Number
Fiducials identified on profiles

RESISTIVITY CONTOURS

Contours in ohm-m at 10 intervals per decade.
Apparent resistivity calculated using a pseudo-layer half-space model (Fraser 1978).

1000
800
600
500
400
300
250
200
150
125
100

LOCATION MAP

NTS: 105 0/1,2,3,6,7
UTM ZONE: 9
NAD83
SCALE: 1:650,000

COLORADO RESOURCES LTD.

MAC PASS CLAIMS, YUKON

APPARENT RESISTIVITY

7200 Hz COPLANAR

FUGRO DIGHEM [®] SURVEY	NTS: 105 0/1,2,3,6,7	GEOPHYSICIST:
DATE: OCTOBER, 2011	JOB: 11046	SHEET: 1
Fugro Airborne Surveys		

0 1 2 Km
0 1 Mi
Scale 1:20 000

FUGRO AIRBORNE SURVEYS

FUGRO