

Hole No.: DNE-062	Depth: 177.50 m	Horizontal Length: 0.00 m	Project: 1710
Location Data:			
Property:	Selwyn Project	Claim Name:	NOD 39
Mining District:	Selwyn Basin	Grant Number:	YB49403
Province/Territory:	Yukon		
UTM Co-Ordinates & Altitude of Drill Hole Collar:			
UTM Easting:	479002.12 m	True Azimuth:	210.0 °
UTM Northing:	6933316.21 m	Hole Angle:	-80.0 °
Elevation (m):	1154.19 m	NTS Name:	No Title
		UTM Datum:	NAD 83
		UTM Grid Zone:	9
		NTS Number:	105I11
Grid Co-Ordinates of Drill Hole Collar:			
Grid Easting (m):	0.00 m	Grid Name:	HP 06
Grid Northing (m):	0.00 m	Grid Type:	100m
Grid Azimuth:	270.0 °		
Dimond Drilling Contract:			
Drilled By:	CYR-01	Date Drilling Start:	20-Mar-14
		Date Finish:	24-Mar-14
Diamond Drill Core:			
Logged By:	H. Grimson	Date Logging Start:	24-Mar-14
		Date Finish:	26-Mar-14
Legend for Core Logging Codes: PAX			
Core Size:	NQ3	Cemented:	No
Casing Depth:	27.00 m	Casing Pulled:	Yes
Water Depth:	0.00 m	Overburden Depth:	27.60 m
Level:			
Section:		Drift:	

Selwyn Project

Diamond Drill Log

Survey Data for Hole

DNE-062

Hole Comments:

Fri, Mar 21 --- DS: 24m of casing drilled, no major issues. NS: Frozen water line hindered drilling, 3m drilled.

=====

Sat, Mar 22 --- DS: Frozen water lines continued to cause issues, finally replaced pump in afternoon, original pump will be repaired at later date. NS: casing to 35m, total depth reached 44m.

=====

Sun, Mar 23 --- DS: reached ACTM at 27.6m- 51.0m, bound by fault. NS: FLMD followed by USMS, 101m depth reached. Minor hole conditioning required.

=====

Mon, Mar 24 --- DS: no major issues; 2 hours reaming from 98 to 102 m. NS: no major issues, 1 hour reaming from 149 to 152 m.

<i>Depth</i>	<i>Dip</i>	<i>Azimuth</i>
0.00	-80.0	210.0
47.00	-80.5	209.1
98.00	-79.9	208.9
110.00	-79.7	210.5
149.00	-79.5	206.9
177.00	-79.2	207.6

Selwyn Project Diamond Drill Log

Hole Number:
DNE-062

Selwyn Chihong Mining Ltd.
#2701- 1055 West Georgia
Vancouver, British Columbia
Canada, V6E 0B6

From (m)	To (m)	Rocktype & Description	Sample ID	From (m)	To (m)	Width (m)	Pb (%)	Zn (%)	Ag (ppm)	Cd (ppm)	Pb% / Zn%
0.00	26.70	OVBR									
26.70	50.10	ACTM	E6614701	26.70	27.10	0.40	0.21	0.57	1.25	14.20	0.37
<p><i>ACTM – Active Member</i></p> <p><i>The ACTM consists of a repetitive, possibly rhythmic, sequence of intercalated carbonaceous mudstone, cherty mudstone, chert and limestone and locally contains economically significant Zn and Pb sulphides (see bold marked facies), mainly in its sections with well developed lamination. Because of its heterogeneity, the member is distinctive and easily identified.</i></p> <p>=====</p> <p><i>The ACTM has 8 different facies:</i></p> <p>=====</p> <p>- GREY CHERT FACIES: <i>Consists of laminated medium light grey to medium dark grey chert. Mineralization: 95-99% quartz and up to 5% secondary calcite.</i></p> <p>- WHITISH GREY ZN-PB MUDSTONE FACIES: <i>Is a laminated cherty rock containing up to 70% sulphides. Mineralization: quartz, sphalerite and galena are the major minerals with only minor amounts of pyrite and locally calcite. Sedimentary diagenetic structures are common and well displayed in the facies, such as: lamination, pseudo-beds, calcite nodules & limestone nodules and abundant water escape structures. Most obvious structure in facies is cross-cutting veins containing massive sphalerite and galena with minor pyrite. They range in width from 0.5 to 10mm.</i></p> <p>- THIN BEDDED CHERTY MUDSTONE FACIES: <i>Consists of rhythmic intercalated laminae of chert, carbonaceous mudstone and minor micrite. This facies contains significant amounts of Zn and Pb sulphides.</i></p> <p>- CHERTY MUDSTONE FACIES: <i>Consists of a greyish black monotonous siliceous, carbonaceous mudstone. It is most typically found overlying the thin bedded calcareous mudstone facies.</i></p>			E6614702	27.10	28.00	0.90	1.35	6.50	1.25	165.00	0.21
			E6614703	28.00	29.00	1.00	2.03	4.30	1.25	104.00	0.47
			E6614704	29.00	30.10	1.10	0.23	2.02	1.25	48.10	0.12
			E6614705	30.10	31.00	0.90	0.37	1.25	1.25	30.10	0.30
			E6614706	31.00	31.80	0.80	2.11	2.91	1.25	77.60	0.73
			E6614707	31.80	32.50	0.70	0.03	0.28	1.25	8.40	0.12
			E6614708	32.50	33.20	0.70	0.03	0.51	1.25	14.90	0.06
			E6614709	33.20	34.00	0.80	2.04	13.00	3.20	342.00	0.16
			E6614710	34.00	34.50	0.50	0.97	1.23	1.25	29.50	0.79
			E6614711	34.00	34.50	0.50	0.77	5.35	1.25	140.00	0.14
			E6614712	34.50	35.00	0.50	0.05	0.03	1.25	1.25	1.61
			E6614713	35.00	35.60	0.60	0.19	0.17	1.25	4.60	1.12
			E6614714	35.60	36.20	0.60	0.56	2.30	1.25	56.90	0.24
			E6614715	36.20	36.80	0.60	1.42	5.24	1.25	132.00	0.27
			E6614716	36.80	37.30	0.50	1.83	10.80	2.50	271.00	0.17
			E6614717	37.30	38.00	0.70	0.91	3.65	1.25	81.40	0.25
			E6614718	38.00	38.50	0.50	1.23	3.88	1.25	83.80	0.32
			E6614719	38.50	39.00	0.50	1.94	9.81	1.25	230.00	0.20
			E6614720	39.00	39.00	0.00	0.01	0.00	1.25	1.25	2.25
			E6614721	39.00	39.40	0.40	1.87	6.89	1.25	153.00	0.27
			E6614722	39.40	39.70	0.30	0.15	0.94	1.25	21.20	0.16
			E6614723	39.70	40.40	0.70	1.61	6.56	1.25	149.00	0.25
			E6614724	40.40	41.20	0.80	0.89	2.27	1.25	64.30	0.39
			E6614725	41.20	41.90	0.70	4.41	9.59	2.80	361.00	0.46
			E6614726	41.90	42.80	0.90	0.38	0.68	1.25	17.00	0.56
			E6614727	42.80	43.80	1.00	0.02	0.02	1.25	1.25	1.18
			E6614728	43.80	44.80	1.00	0.33	1.27	1.25	30.40	0.26
			E6614729	44.80	45.70	0.90	0.32	0.55	1.25	14.10	0.58
			E6614730	45.70	45.70	0.00	1.46	4.16	27.90	265.00	0.35
			E6614731	45.70	46.50	0.80	0.44	0.96	1.25	24.40	0.46
			E6614732	46.50	47.00	0.50	0.16	0.06	1.25	1.25	2.49

Selwyn Project Diamond Drill Log

Hole Number:
DNE-062

Selwyn Chihong Mining Ltd.
#2701- 1055 West Georgia
Vancouver, British Columbia
Canada, V6E 0B6

From (m)	To (m)	Rocktype & Description	Sample ID	From (m)	To (m)	Width (m)	Pb (%)	Zn (%)	Ag (ppm)	Cd (ppm)	Pb% / Zn%
<p>- <i>THIN BEDDED CALCAREOUS MUDSTONE FACIES: Consists of laminated carbonaceous mudstone containing 20-40% calcite, 40-55% quartz and 10-20% muscovite. Sulphides occur in laminae. In the XY area it is usually the lowest facies in the section to contain laminated sulphides.</i></p> <p>- <i>CALCAREOUS MUDSTONE FACIES: Consists of grey to greyish black monotonous, calcareous siliceous carbonaceous mudstone. There are no feathery calcite beds or pyrite-calcite blebs in the facies, making it easily distinguishable from the CCMS.</i></p> <p>- <i>GRADED LIMESTONE FACIES: Is a laminated argillaceous limestone with intercalated carbonaceous limestone laminae. The main rock type in the facies is laminated limestone with laminae up to 0.1-7mm thick.</i></p> <p>- <i>LIGHT GREY BASAL LIMESTONE FACIES - LGLS: Consists of laminated argillaceous limestone. In the Anniv area it marks the end of the ACTM. It's not always present in the stratigraphy.</i></p> <p>- <i>BASAL FACIES: This is a highly contorted and locally foliated carbonaceous mudstone. Unlike the other facies it is not repeated higher in the member. It appears locally to contain the slip zone of a major slump. The facies has only been observed in the YX area. It is 0.1-2m thick. The facies consists of massive carbonaceous siliceous mudstone with lenses and laminae of contorted, slightly carbonaceous chert.</i></p> <p>« 26.70- 27.10 Barren, weakly calcareous »</p> <p>« 27.10- 28.00 Moderate-grade, strong slumping laminations, carbonaceous, silicious »</p> <p>« 28.00- 29.00 Barren mudstone, calcareous and silicious parts »</p>			E6614733	47.00	47.60	0.60	1.59	4.33	1.25	139.00	0.37
			E6614734	47.60	48.30	0.70	1.90	6.25	3.70	217.00	0.30
			E6614735	48.30	49.00	0.70	2.70	3.69	5.20	135.00	0.73
			E6614736	49.00	49.50	0.50	0.07	0.13	1.25	4.10	0.50
			E6614737	49.50	50.00	0.50	0.14	0.32	1.25	10.50	0.44

Selwyn Project Diamond Drill Log

Hole Number:
DNE-062

Selwyn Chihong Mining Ltd.
#2701- 1055 West Georgia
Vancouver, British Columbia
Canada, V6E 0B6

From (m)	To (m)	Rocktype & Description	Sample ID	From (m)	To (m)	Width (m)	Pb (%)	Zn (%)	Ag (ppm)	Cd (ppm)	Pb% / Zn%
		« 29.00- 30.10 Low-grade, moderately laminated, silicious »									
		« 30.10- 31.00 Barren black mudstone, silicious, irregular calcite bands »									
		« 31.00- 31.80 Low grade, moderate-strongly laminated, silicious »									
		« 31.80- 33.20 Barren black mudstone, homogenous, silicious »									
		« 33.20- 34.00 Moderate-strong grade, strongly laminated, silicious, high sphalerite content causes brown colour »									
		« 34.00- 35.60 Barren mudstone, calcareous, dark grey homogenous »									
		« 35.60- 36.20 Low grade, moderately laminated, calcareous »									
		« 36.20- 37.30 Moderate grade, strong and tightly laminated, calcareous with minor silicious parts »									
		« @ 37.00 Elevated Sphalerite, brown (20cm wide) »									
		« 37.30- 38.00 Low Grade, weak-moderately laminated, calcareous »									
		« 38.00- 39.40 Low-moderate grade, strong laminations, silicious and carbonaceous »									
		« 39.40- 39.70 Barren calcareous mudstone »									
		« 39.70- 40.40 Moderate grade, strongly laminated with slumping, silicious and carbonaceous »									
		« 40.40- 41.20 Very low grade, weak and spaced out laminations, calcareous »									
		« 41.20- 41.90 Moderate grade, strong and tight laminations, dominantly									

Selwyn Project Diamond Drill Log

Hole Number:
DNE-062

Selwyn Chihong Mining Ltd.
#2701- 1055 West Georgia
Vancouver, British Columbia
Canada, V6E 0B6

From (m)	To (m)	Rocktype & Description	Sample ID	From (m)	To (m)	Width (m)	Pb (%)	Zn (%)	Ag (ppm)	Cd (ppm)	Pb% / Zn%
<i>silicious, hight sphalerite content »</i> <i>« 41.90- 47.00 Barren calcareous mudstone. carbonaceous, homogenous »</i> <i>« 47.00- 49.00 Low grade, strong and tightly laminated units (clasts?) within barren limestone »</i> <i>« 49.00- 50.10 Barren calcareous mudstone, increasingly silicious with depth, dark-grey to black »</i>											
			E6614738	50.00	50.80	0.80	0.02	0.01	1.25	1.25	1.94
50.10	55.50	FLT	E6614739	50.80	51.50	0.70	0.01	0.01	1.25	1.25	1.05
<i>« 10% gg, 30% bx, 60% brco Dominantly silicious mudstone, homogenous, black »</i>			E6614740	51.50	52.00	0.50	0.02	0.01	1.25	1.25	1.78
			E6614741	51.50	52.00	0.50	0.02	0.01	1.25	1.25	2.66
			E6614742	52.00	53.00	1.00	0.01	0.06	1.25	1.25	0.23
55.50	89.50	FLMD									
<i>FLMD – Flaggy Mudstone Formation</i> <i>Dark grey mudstone in the upper portions of the unit grading into light grey mudstone to siltstone. Contains abundant wispy bioturbation which ranges from randomly-oriented at the top of the unit to bedding-parallel throughout the majority of the unit. Darker upper section has a strong fetid odour along broken surfaces. « btrb 0.10-2.00cm », « cg xtl crns ca 1.00-5.00% 5.00-150.00cm », « crns py 1.00-5.00% 0.10-0.50mm »,</i> <i>« @ 63.50 S0 Bioturbated bedding 50° »</i> <i>« @ 80.30 S0 Bioturbated Bedding 45° »</i>											
89.50	124.00	USMS	E6614743	120.00	121.00	1.00	0.01	0.01	1.25	1.25	0.75
<i>USMS – Upper Siliceous Mudstone</i>			E6614744	121.00	122.00	1.00	0.01	0.05	1.25	1.25	0.25
			E6614745	122.00	122.50	0.50	0.02	0.16	1.25	5.30	0.10
<i>Consists of interlaminated dark grey to black mudstone and light to medium grey chert. Regionally, a 1m thick graptolite zone occurs 15m below the top of the upper unit, this is usable as a horizon. The USMS is divided into 3 units. The Lower Unit contains abundant limestone concretions and Galena and sphalerite</i>			E6614746	122.50	123.00	0.50	0.01	0.20	1.25	7.40	0.04
			E6614747	123.00	124.00	1.00	0.01	0.16	1.25	4.90	0.09

Selwyn Project Diamond Drill Log

Hole Number:
DNE-062

Selwyn Chihong Mining Ltd.
#2701- 1055 West Georgia
Vancouver, British Columbia
Canada, V6E 0B6

From (m)	To (m)	Rocktype & Description	Sample ID	From (m)	To (m)	Width (m)	Pb (%)	Zn (%)	Ag (ppm)	Cd (ppm)	Pb% / Zn%
		micro-concretions occur locally near the base of this unit. « gra , lm chrt -20.00% », « cg xtl sph crns ca 5.00-20.00cm », « bed chrt 10.00-15.00% », < @ 96.20 S0 52° > < @ 105.00 S0 55° > < @ 112.80 S0 62° > < @ 116.30 Narrow broken galena stringer within silicious mudstone with no lamination >									
124.00	148.70	ACTM	E6614748	124.00	124.50	0.50	0.60	4.45	1.25	134.00	0.14
ACTM – Active Member			E6614749	124.50	125.00	0.50	2.57	9.34	3.20	301.00	0.28
<i>The ACTM consists of a repetitive, possibly rhythmic, sequence of intercalated carbonaceous mudstone, cherty mudstone, chert and limestone and locally contains economically significant Zn and Pb sulphides (see bold marked facies), mainly in its sections with well developed lamination. Because of its heterogeneity, the member is distinctive and easily identified.</i> ===== <i>The ACTM has 8 different facies:</i> ===== - GREY CHERT FACIES: Consists of laminated medium light grey to medium dark grey chert. Mineralization: 95-99% quartz and up to 5% secondary calcite. - WHITISH GREY ZN-PB MUDSTONE FACIES: Is a laminated cherty rock containing up to 70% sulphides. Mineralization: quartz, sphalerite and galena are the major minerals with only minor amounts of pyrite and locally calcite. Sedimentary diagenetic structures are common and well displayed in the facies, such as: lamination, pseudo-beds, calcite nodules & limestone nodules and abundant water escape structures. Most obvious structure in facies is cross-cutting veins containing massive sphalerite and galena with minor pyrite. They range in width from 0.5 to 10mm.			E6614750	125.00	125.00	0.00	0.01	0.01	1.25	1.25	1.05
			E6614751	125.00	125.50	0.50	0.72	4.30	1.25	114.00	0.17
			E6614752	125.50	125.80	0.30	0.47	1.96	1.25	47.50	0.24
			E6614753	125.80	126.20	0.40	0.30	1.20	1.25	29.00	0.25
			E6614754	126.20	126.80	0.60	0.33	2.63	1.25	60.60	0.12
			E6614755	126.80	127.90	1.10	1.22	3.23	1.25	76.80	0.38
			E6614756	127.90	128.40	0.50	1.46	12.50	3.40	309.00	0.12
			E6614757	128.40	128.90	0.50	0.53	9.13	3.40	184.00	0.06
			E6614758	128.90	129.50	0.60	3.24	18.20	5.30	450.00	0.18
			E6614759	129.50	130.00	0.50	3.91	9.83	1.25	239.00	0.40
			E6614760	130.00	130.00	0.00	5.79	6.80	66.00	164.00	0.85
			E6614761	130.00	130.50	0.50	0.82	10.70	1.25	220.00	0.08
			E6614762	130.50	131.00	0.50	0.13	0.58	1.25	14.50	0.23
			E6614763	131.00	131.30	0.30	1.06	4.61	1.25	122.00	0.23
			E6614764	131.30	131.70	0.40	0.03	0.05	1.25	1.25	0.51
			E6614765	131.70	132.70	1.00	0.02	0.01	1.25	1.25	2.26
			E6614766	132.70	133.70	1.00	0.11	0.17	1.25	3.50	0.63
			E6614767	133.70	134.30	0.60	0.22	0.48	1.25	20.50	0.46
			E6614768	134.30	134.90	0.60	0.59	1.02	1.25	31.00	0.58
			E6614769	134.90	135.50	0.60	0.19	0.85	1.25	20.30	0.23
			E6614770	135.50	136.00	0.50	0.21	0.97	1.25	23.10	0.22
			E6614771	135.50	136.00	0.50	1.72	1.12	1.25	30.60	1.54

Selwyn Project Diamond Drill Log

Hole Number:
DNE-062

Selwyn Chihong Mining Ltd.
#2701- 1055 West Georgia
Vancouver, British Columbia
Canada, V6E 0B6

From (m)	To (m)	Rocktype & Description	Sample ID	From (m)	To (m)	Width (m)	Pb (%)	Zn (%)	Ag (ppm)	Cd (ppm)	Pb% / Zn%
<p>- <i>THIN BEDDED CHERTY MUDSTONE FACIES: Consists of rhythmic intercalated laminae of chert, carbonaceous mudstone and minor micrite. This facies contains significant amounts of Zn and Pb sulphides.</i></p> <p>- <i>CHERTY MUDSTONE FACIES: Consists of a greyish black monotonous siliceous, carbonaceous mudstone. It is most typically found overlying the thin bedded calcareous mudstone facies.</i></p> <p>- <i>THIN BEDDED CALCAREOUS MUDSTONE FACIES: Consists of laminated carbonaceous mudstone containing 20-40% calcite, 40-55% quartz and 10-20% muscovite. Sulphides occur in laminae. In the XY area it is usually the lowest facies in the section to contain laminated sulphides.</i></p> <p>- <i>CALCAREOUS MUDSTONE FACIES: Consists of grey to greyish black monotonous, calcareous siliceous carbonaceous mudstone. There are no feathery calcite beds or pyrite-calcite blebs in the facies, making it easily distinguishable from the CCMS.</i></p> <p>- <i>GRADED LIMESTONE FACIES: Is a laminated argillaceous limestone with intercalated carbonaceous limestone laminae. The main rock type in the facies is laminated limestone with laminae up to 0.1-7mm thick.</i></p> <p>- <i>LIGHT GREY BASAL LIMESTONE FACIES - LGLS: Consists of laminated argillaceous limestone. In the Anniv area it marks the end of the ACTM. It's not always present in the stratigraphy.</i></p> <p>- <i>BASAL FACIES: This is a highly contorted and locally foliated carbonaceous mudstone. Unlike the other facies it is not repeated higher in the member. It appears locally to contain the slip zone of a major slump. The facies has only been observed in the YX area. It is 0.1-2m thick. The facies consists of massive carbonaceous siliceous mudstone with lenses and laminae of contorted, slightly carbonaceous chert.</i></p>			E6614772	136.00	136.30	0.30	1.85	4.51	1.25	120.00	0.41
			E6614773	136.30	136.80	0.50	0.72	1.98	1.25	48.20	0.37
			E6614774	136.80	137.30	0.50	0.20	0.74	1.25	17.50	0.27
			E6614775	137.30	138.00	0.70	2.91	9.62	1.25	295.00	0.30
			E6614776	138.00	138.50	0.50	1.12	3.16	1.25	89.00	0.35
			E6614777	138.50	139.20	0.70	1.69	7.43	1.25	204.00	0.23
			E6614778	139.20	140.20	1.00	0.19	0.54	1.25	13.10	0.35
			E6614779	140.20	141.20	1.00	0.04	0.04	1.25	1.25	0.97
			E6614780	141.20	141.20	0.00	0.01	0.00	1.25	1.25	7.36
			E6614781	141.20	142.20	1.00	0.03	0.01	1.25	1.25	2.95
			E6614782	142.20	142.70	0.50	1.18	2.67	1.25	68.50	0.44
			E6614783	142.70	143.40	0.70	1.57	4.55	1.25	119.00	0.35
			E6614784	143.40	144.40	1.00	0.06	0.44	1.25	13.90	0.13
			E6614785	144.40	145.30	0.90	0.13	0.62	1.25	30.40	0.21
			E6614786	145.30	146.00	0.70	0.01	0.08	1.25	5.90	0.09
			E6614787	146.00	147.00	1.00	0.01	0.00	1.25	1.25	3.59
			E6614788	147.00	148.00	1.00	0.01	0.00	1.25	1.25	2.48
			E6614789	148.00	148.70	0.70	0.01	0.00	1.25	1.25	4.61

Selwyn Project Diamond Drill Log

Hole Number:
DNE-062

Selwyn Chihong Mining Ltd.
#2701- 1055 West Georgia
Vancouver, British Columbia
Canada, V6E 0B6

From (m)	To (m)	Rocktype & Description	Sample ID	From (m)	To (m)	Width (m)	Pb (%)	Zn (%)	Ag (ppm)	Cd (ppm)	Pb% / Zn%
		« 124.00- 125.50 Moderate grade, strong and tightly laminated, start of interval has high pyrite content and slumping, silicious, medium-dark grey »									
		« 125.50- 125.80 Barren mudstone »									
		« 125.80- 126.20 Very low grade mudstone, very weakly and spaced laminations, carbonaceous, silicious »									
		« 126.20- 126.80 Low grade, weakly laminated, regions of <30cm with strong laminations but seperated by barren mudstone, silicious »									
		« 126.80- 127.90 Barren mudstone, very broken (faulted?), moderately carbonaceous, silicious »									
		« 127.90- 131.00 Low grade, moderately laminated, laminations rarely parallel (lots of slumping), silicious, irregular to massive calcite »									
		« 131.00- 131.30 Moderate grade, strongly laminated, brownish tint due to elevated sphalerite content, near parallel laminations with only moderate slumping »									
		« 131.30- 131.70 Barren modstone, carbonaceous, silicious »									
		« 131.70- 134.30 Barren calcareous limestone, homogenous with frequent narrow calcite stringers, medium-grey in colour »									
		« 134.30- 135.50 Brecciated calcareous mudstone, clasts within a calcite-stringer matrix, local massive calcite, upper <15cm of interval: weakly laminated calcareous mudstone »									
		« 135.50- 136.00 Barren calcaerious mudstone, upper part is carbonaceous, lower part is calcareous »									
		« 136.00- 136.30 Low grade, weak-moderately laminated with slumping, weakly									

Selwyn Project Diamond Drill Log

Hole Number:
DNE-062

Selwyn Chihong Mining Ltd.
#2701- 1055 West Georgia
Vancouver, British Columbia
Canada, V6E 0B6

From (m)	To (m)	Rocktype & Description	Sample ID	From (m)	To (m)	Width (m)	Pb (%)	Zn (%)	Ag (ppm)	Cd (ppm)	Pb% / Zn%
		<i>brecciated, weakly calcareous with minor silicious parts »</i> <i>« 136.30- 137.30 Barren mudstone, calcareous, weakly brecciated »</i> <i>« 137.30- 138.50 Low grade, weakly brecciated, weak-moderate lamination and slumping, calcareous, carbonaceous »</i> <i>« 138.50- 139.20 Low-moderate grade, strong laminations or both parallel and slumped, carbonaceous, very calcareous, @138.1m: 10cm of moderate-grade, strongly laminated and slumped, silicious »</i> <i>« 139.20- 142.20 Barren calcareous mudstone, medium-dark grey »</i> <i>« 142.20- 142.70 Low grade, weakly laminated, weakly calcareous, carbonaceous »</i> <i>« 142.70- 143.40 Low grade (slightly higher grade than upper unit), silicious »</i> <i>« 143.40- 146.00 Black barren mudstone, very calcareous, carbonaceous »</i> <i>« 146.00- 148.70 Basal limestone. very calcareous, light-medium grey in colour »</i>									
148.70	177.50	CCMS	E6614790	148.70	148.70	0.00	1.39	4.28	28.40	261.00	0.32
		CCMS – Calcareous Mudstone	E6614791	148.70	149.50	0.80	0.01	0.00	1.25	1.25	9.22
			E6614792	149.50	151.50	2.00	0.01	0.03	1.25	3.40	0.19
			E6614793	151.50	152.00	0.50	0.01	0.01	1.25	1.25	0.45
		<i>Massive, calcareous, carbonaceous, dark grey mudstone. Most of the member is massive, but rare poorly defined bedding and pyrite-calcite micro-concretions are present. Most diagnostic structures are feathery calcite beds (=thin calcite-cemented concretions, many of them contain pyrite cores) and calcite pseudo-beds (= fibrous calcite vein parallel to bedding).</i> <i>« lm ca 5.00-10.00mm », « nodules py -3.00% 2.00-20.00mm »,</i>									



Hole Number:
DNE-062

Selwyn Chihong Mining Ltd.
#2701- 1055 West Georgia
Vancouver, British Columbia
Canada, V6E 0B6

From (m)	To (m)	Rocktype & Description	Sample ID	From (m)	To (m)	Width (m)	Pb (%)	Zn (%)	Ag (ppm)	Cd (ppm)	Pb% / Zn%
◁ @ 160.70 S0 Define by narrow pyrite band 62° ▷											
◁ @ 175.00 S0 62° ▷											
« 176.00- 176.60 Laminated limestone concretion »											
177.50	177.50	EOH									