

Hole No.: DNE-080	Depth: 224.00 m	Horizontal Length: 0.00 m	Project: 1710
Location Data:			
Property:	Selwyn Project	Claim Name:	NOD 39
Mining District:	Selwyn Basin	Grant Number:	YB49403
Province/Territory:	Yukon		
UTM Co-Ordinates & Altitude of Drill Hole Collar:			
UTM Easting:	478802.90 m	True Azimuth:	218.0 °
UTM Northing:	6933142.54 m	Hole Angle:	-80.0 °
Elevation (m):	1183.09 m	NTS Name:	No Title
		UTM Datum:	NAD 83
		UTM Grid Zone:	9
		NTS Number:	105I11
Grid Co-Ordinates of Drill Hole Collar:			
Grid Easting (m):	0.00 m	Grid Name:	HP 06
Grid Northing (m):	0.00 m	Grid Type:	100m
Grid Azimuth:	278.0 °		
Dimond Drilling Contract:			
Drilled By:	CYR-01	Date Drilling Start:	07-Apr-14
		Date Finish:	11-Apr-14
Diamond Drill Core:			
Logged By:	H. Grimson	Date Logging Start:	9-Apr-2014
		Date Finish:	11-04-2011
Legend for Core Logging Codes: PAX			
Core Size:	NQ3	Cemented:	No
Casing Depth:	12.50 m	Casing Pulled:	Yes
Water Depth:	0.00 m	Overburden Depth:	12.50 m
Level:		Section:	
		Drift:	

Selwyn Project

Diamond Drill Log

Survey Data for Hole

DNE-080

Hole Comments:

Tue, Apr 08 --- DS: Shut down hole HCW-033, relocated to HCW-817 (HCW-034). NS: set casing and reached ~42m, currently in FLMD.

=====

Wed, Apr 09 ---DS: No major issues?, slow drilling, drilled 23m, NS: No major issues. Drilled ~43m.

=====

Thu, Apr 10 --- DS: No major issues, drilled about 35m. NS: Good production, down to 175m in USMS. Continue past TD until past ACTM.

=====

Fri, Apr 11 --- DS: Slow drilling through faulted rock. Rods kept getting squeezed. NS: No issues, ended shift 225m in CLST. Hole shut down at end of NS.

<i>Depth</i>	<i>Dip</i>	<i>Azimuth</i>
0.00	-80.0	218.0
35.00	-80.5	217.9
56.00	-80.0	217.4
104.00	-79.1	215.2
155.00	-78.0	213.1
206.00	-77.7	210.0
224.00	-77.8	209.3

Selwyn Project Diamond Drill Log

Hole Number:
DNE-080

Selwyn Chihong Mining Ltd.
#2701- 1055 West Georgia
Vancouver, British Columbia
Canada, V6E 0B6

From (m)	To (m)	Rocktype & Description	Sample ID	From (m)	To (m)	Width (m)	Pb (%)	Zn (%)	Ag (ppm)	Cd (ppm)	Pb% / Zn%
0.00	12.50	OVBR									
12.50	132.00	FLMD									
<p><i>FLMD – Flaggy Mudstone Formation</i></p> <p><i>Dark grey mudstone in the upper portions of the unit grading into light grey mudstone to siltstone. Contains abundant wispy bioturbation which ranges from randomly-oriented at the top of the unit to bedding-parallel throughout the majority of the unit. Darker upper section has a strong fetid odour along broken surfaces. « btrb 0.10-2.00cm », « cg xtl crns ca 1.00-5.00% 5.00-150.00cm », « crns py 1.00-5.00% 0.10-0.50mm »,</i></p> <p><i>« @ 50.50 S0 Bioturbation along bedding 42° »</i></p> <p><i>« @ 76.20 S0 Lamination 39° »</i></p> <p><i>« @ 84.00 S0 Bioturbation along bedding 38° »</i></p> <p><i>« @ 101.00 S0 Bioturbation along bedding 20° »</i></p>											
132.00	210.30	USMS	E6614251	148.60	149.60	1.00	0.00	0.01	1.25	1.25	0.71
<p><i>USMS – Upper Siliceous Mudstone</i></p> <p><i>Consists of interlaminated dark grey to black mudstone and light to medium grey chert. Regionally, a 1m thick graptolite zone occurs 15m below the top of the upper unit, this is usable as a horizon. The USMS is divided into 3 units. The Lower Unit contains abundant limestone concretions and Galena and sphalerite micro-concretions occur locally near the base of this unit. « gra , lm chrt -20.00% », « cg xtl sph crns ca 5.00-20.00cm », « bed chrt 10.00-15.00% »,</i></p> <p><i>« 149.60- 149.90 Trace mineralization, weak slumped laminations, minor fetid odor associated with HCl, silicious »</i></p> <p><i>« @ 184.50 S0 Chert pseudobed 30° »</i></p>			E6614252	149.60	149.60	0.00	0.01	0.00	1.25	1.25	29.29
			E6614253	149.60	149.90	0.30	0.00	0.00	1.25	1.25	2.99
			E6614254	149.60	149.90	0.30	0.00	0.00	1.25	1.25	7.06
			E6614255	149.90	151.00	1.10	0.00	0.00	1.25	1.25	1.97
			E6614256	151.00	151.00	0.00	5.83	6.21	67.10	167.00	0.94

Selwyn Project Diamond Drill Log

Hole Number:
DNE-080

Selwyn Chihong Mining Ltd.
#2701- 1055 West Georgia
Vancouver, British Columbia
Canada, V6E 0B6

From (m)	To (m)	Rocktype & Description	Sample ID	From (m)	To (m)	Width (m)	Pb (%)	Zn (%)	Ag (ppm)	Cd (ppm)	Pb% / Zn%
210.30	214.10	FLT									
Fault contact between Upper Siliceous Mudstone and Cambrian Limestone: 35% Intact core, 40%gg, 20%bx, 5%brco											
214.10	224.00	CLST									
CLST – Cambrian Limestone											
Consists of 2 units. The first unit, Wavy Banded Limestone Formation, is divided into two informal members, based on the amount of argillaceous material in some beds. Both members display well-banded limestone. The upper member consists of intercalated light grey siliceous micrite and grey to tan laminated calcareous mudstone beds, displaying a chain-link structure. It appears wavy because of variable bedding thickness. Bedding is in general thinner than the bedding in the lower member, with micrite beds ranging from 1 to 5 cm thick, and showing rapid lateral variation. The lower member consists of intercalated microspar and micrite, and shows even bedding.											
The second unit, Massive Limestone Formation, consists of massive grey, micritic siliceous limestone. « lt gra , lm microspar 5.00-40.00cm », « lm micrite 1.00-5.00cm », « gra to lt bro , calcareous mdst 5.00-30.00mm » ,											
◁ @ 219.00 S0 35° ▷											
224.00	224.00	EOH									