

Hole No.: HCE-043	Depth: 75.00 m	Horizontal Length: 0.00 m	Project: 1710
Location Data:			
Property:	Selwyn Project	Claim Name:	NOD 28
Mining District:	Selwyn Basin	Grant Number:	YB49392
Province/Territory:	Yukon		
UTM Co-Ordinates & Altitude of Drill Hole Collar:			
UTM Easting:	482913.66 m	True Azimuth:	3.0 °
UTM Northing:	6931317.17 m	Hole Angle:	-74.0 °
Elevation (m):	1191.40 m	NTS Name:	No Title
		UTM Datum:	NAD 83
		UTM Grid Zone:	9
		NTS Number:	105I11
Grid Co-Ordinates of Drill Hole Collar:			
Grid Easting (m):	0.00 m	Grid Name:	HP 06
Grid Northing (m):	0.00 m	Grid Type:	100m
Grid Azimuth:	65.0 °		
Dimond Drilling Contract:			
Drilled By:	NL-03	Date Drilling Start:	12-Jul-15
		Date Finish:	13-Jul-15
Diamond Drill Core:			
Logged By:	EH	Date Logging Start:	14-Jul-15
		Date Finish:	14-Jul-15
Legend for Core Logging Codes: PAX			
Core Size:	NQ3	Cemented:	No
Casing Depth:	33.10 m	Casing Pulled:	Yes
Water Depth:	0.00 m	Overburden Depth:	33.10 m
Level:		Section:	
		Drift:	

Selwyn Project

Diamond Drill Log

Survey Data for Hole

HCE-043

Hole Comments:

Sun, Jul 12 --- DS: Move and setup on pad HCE-819 to drill HCE-043 (4 hours) spent rest of the dayshift assisting with NL-04 move to Brodel, laying hoseline. NS: Drilled 75m down to target depth with 33m of casing. Current lithology is CCMS.

=====

Mon, Jul 13 ---

<i>Depth</i>	<i>Dip</i>	<i>Azimuth</i>
0.00	-74.0	3.0
51.00	-72.7	2.6
75.00	-72.5	2.9

Selwyn Project Diamond Drill Log

Hole Number:
HCE-043

Selwyn Chihong Mining Ltd.
#2701- 1055 West Georgia
Vancouver, British Columbia
Canada, V6E 0B6

From (m)	To (m)	Rocktype & Description	Sample ID	From (m)	To (m)	Width (m)	Pb (%)	Zn (%)	Ag (ppm)	Cd (ppm)	Pb% / Zn%
0.00	33.10	OVBR									
« 0.00- 32.70 no core recovered »											
« 32.70- 33.10 pebbles »											
33.10	75.00	CCMS									
CCMS – Calcareous Mudstone											
Massive, calcareous, carbonaceous, dark grey mudstone. Most of the member is massive, but rare poorly defined bedding and pyrite-calcite micro-concretions are present. Most diagnostic structures are feathery calcite beds (=thin calcite-cemented concretions, many of them contain pyrite cores) and calcite pseudo-beds (= fibrous calcite vein parallel to bedding).											
« lm ca 5.00-10.00mm », « nodules py -3.00% 2.00-20.00mm »,											
« 33.10- 36.90 FLT, minor fault gouge, low cohesive strength, not parallel to S1 »											
« 36.90- 58.00 foliation domain with prevailing orientation a=58° TCA »											
« 58.00- 62.60 FLT, fine grained rubble breccia, healed, no-low cohesive strength parallel to S1 @51° TCA, abundant quartz-calcite veining and stockworking and anastamosing»											
« 62.60- 75.00 cleavage-foliation domain; cleavage=16° TCA, foliation=48°TCA »											
« @ 70.50 qtz-calcite-barite Zn-pyrite veining, similar to ACTM L-tectonite »											
75.00	75.00	EOH									